




[P25 12.5 kHz Uplink High]














[FM Uplink Middle]






[FM Uplink High]






800 MHz Band_LTE, CDMA

[LTE 5 MHz Uplink Low]






30Mb ~ 1Gb-3 30Mb ~ 1Gb-4 Center Freq 914.500000 MHz Avg Type: RMS Avg|Hold: 100/100 Avg Type: RMS Avg|Hold: 20/20 Trig: Free Run Trig: Free Run 824.163 7 MH -78.822 dB Ref -10.00 dBm Ref -10.00 dBm 914.500000 MH: 826.550000 MH 824.100000 MH 829.000000 MH Stop Freq Stop Freq 1.000000000 GH Freq Offse Freq Offse Stop 1.00000 GHz Sweep 21.2 ms (3001 pts) #VBW 300 kHz* #VBW 300 kHz* 10Hz ~ 30Hz 30世~12.750世













[LTE 5 MHz Uplink High]














[CDMA 1.25 MHz Uplink Low]













[CDMA 1.25 MHz Uplink Middle]






[CDMA 1.25 MHz Uplink High]













800 MHz Band P25, FM


[Uplink Low]






Model: POD-H-FEM-L-P7P8

[Uplink Middle]









Model: POD-H-FEM-L-P7P8

[Uplink High]







Report No.: HCT-R-1609-F007-1 Model: POD-H-FEM-L-P7P8 Page 156 of 165

Intermodulation Spurious Emissions for FCC 700 MHz Band LTE

[700 Band LTE 5 MHz Uplink Low]



[700 Band LTE 5 MHz Uplink High]



F-TP22-03 (Rev.00) FCC ID: ZUQ-H-FEM-L-P7P8



Report No.: HCT-R-1609-F007-1 Model: POD-H-FEM-L-P7P8 Page 157 of 165

[LTE 10 MHz Uplink]

* Were omitted test because the device amplifies only one selected channel.

F-TP22-03 (Rev.00) FCC ID: ZUQ-H-FEM-L-P7P8


157 / 165

HCT CO.,LTD


Report No.: HCT-R-1609-F007-1 Model: POD-H-FEM-L-P7P8 Page 158 of 165

700 MHz P25, FM

[700 Band AGC threshold Uplink Low]




[700 Band AGC threshold Uplink High]




158 / 165

Report No.: HCT-R-1609-F007-1 Model: POD-H-FEM-L-P7P8 Page 159 of 165

[700 Band +3dB above the AGC threshold Uplink Low]




[700 Band +3dB above the AGC threshold Uplink High]



800 MHz Band LTE, CDMA

[800 Band LTE 5 MHz Uplink]

* Were omitted test because the device amplifies only one selected channel.





[800 Band CDMA 1.25 MHz Uplink High]




F-TP22-03 (Rev.00) FCC ID: ZUQ-H-FEM-L-P7P8

HCT CO.,LTD


Report No.: HCT-R-1609-F007-1 Model: POD-H-FEM-L-P7P8 Page 161 of 165

800 MHz Band P25, FM

[800 Band AGC threshold Uplink High]




[800 Band AGC threshold Uplink High]




F-TP22-03 (Rev.00) FCC ID: ZUQ-H-FEM-L-P7P8

[800 Band +3dB above the AGC threshold Uplink High]



[800 Band +3dB above the AGC threshold Uplink High]





Report No.: HCT-R-1609-F007-1 Model: POD-H-FEM-L-P7P8 Page 163 of 165

10. RADIATED SPURIOUS EMISSIONS

Test Requirement(s): § 2.1053 Measurements required: Field strength of spurious radiation.

- § 2.1053 (a) Measurements shall be made to detect spurious emissions that may be Radiated directly from the cabinet, control circuits, power leads, or intermediate circuit elements under normal conditions of installation and operation. Curves or equivalent data shall be supplied showing the magnitude of each harmonic and other spurious emission. For this test, single sideband, independent sideband, and controlled carrier transmitters shall be modulated under the conditions specified in paragraph (c) of § 2.1049, as appropriate. For equipment operating on frequencies below 890 MHz, an open field test is normally required with the measuring instrument antenna located in the far-field at all test frequencies. In the event it is either impractical or impossible to make open field measurements (e.g. a broadcast transmitter installed in a building) measurements will be accepted of the equipment as installed. Such measurements must be accompanied by a description of the site where the measurements were made showing the location of any possible source of reflections which might distort the field strength measurements. Information submitted shall include the relative radiated power of each spurious emission with reference to the rated power output of the transmitter, assuming all emissions are radiated from half-wave dipole antennas.
- § 2.1053 (b): The measurements specified in paragraph (a) of this section shall be made for the following equipment:
 - (1) Those in which the spurious emissions are required to be 60 dB or more below the mean power of the transmitter.
 - (2) All equipment operating on frequencies higher than 25 MHz.
 - **(3)** All equipment where the antenna is an integral part of, and attached directly to The transmitter.
 - **(4)** Other types of equipment as required, when deemed necessary by the Commission.
- **Test Procedures:** As required by 47 CFR 2.1053, *field strength of radiated spurious measurements* were made in accordance with the procedures of ANSI/TIA-603-C-2004 "Land Mobile FM or PM Communications Equipment Measurement and Performance Standards".

163 / 165

Radiated emission measurements were performed inside a 3 meter semi-anechoic chamber. The EUT was set at a distance of 3m from the receiving antenna. The EUT's RF ports were terminated to 50ohm load. The EUT was set to transmit at the low, mid and high channels of the transmitter frequency range at its maximum power level. The EUT was rotated about 360 and the receiving antenna scanned from 1-3m in order to capture the maximum


F-TP22-03 (Rev.00) FCC ID: ZUQ-H-FEM-L-P7P8



emission. A calibrated antenna source was positioned in place of the EUT and the previously recorded signal was duplicated. The maximum EIRP of the emission was calculated by adding the forward power to the calibrated source plus its appropriate gain value. These steps were carried. out with the receiving antenna in both vertical and horizontal polarization. Harmonic emissions up to the 10th or 40GHz, whichever was the lesser, were investigated.

Model: POD-H-FEM-L-P7P8

Radiated Spurious Emissions Test Setup



F-TP22-03 (Rev.00) FCC ID: ZUQ-H-FEM-L-P7P8



Report No.: HCT-R-1609-F007-1 Model: POD-H-FEM-L-P7P8 Page 165 of 165

Test Result:

Note.

Input signal is the CW signal.

700 MHz band

[Uplink]

Voltage supplied to EUT	Tx Freq.(MHz)	Freq.(MHz)	Substitute Level [dBm]	Ant. Gain (dBi)	C.L	Pol.	EIRP (dBm)	Margin (dB)		
120 Vac	758	No Peak Found								
	766.5									
	775									

800 MHz band

[Uplink]

Voltage supplied to EUT	Tx Freq.(MHz)	Freq.(MHz)	Substitute Level [dBm]	Amp. Gain (dB)	Ant Factor. (dB/m)	C.L (dB)	Pol.	EIRP (dBm)	Margin (dB)
120 Vac	851	1702.035	-32.07	41.10	25.760	3.050	Н	-44.36	14.36
	860	1719.960	-34.32	41.10	25.774	3.072	Н	-46.57	16.57
	869	1738.055	-36.43	41.02	25.788	3.073	Н	-48.59	18.59

F-TP22-03 (Rev.00) FCC ID: ZUQ-H-FEM-L-P7P8

165 / 165