



## MPE Report

Exposure category: General population/uncontrolled environment

EUT Type: Production Unit

Device Type: Mobile Device

Refer Standard: KDB 447498 D01 General RF Exposure Guidance v06

FCC Part 2 §2.1091

### 1. Evaluation method

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with HWB1BLE40AWH for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

### 2. Limits for General Population/Uncontrolled Exposure

(B) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1.0	30

Note: f = frequency in MHz ; \*Plane-wave equivalent power density

### 3. Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

Where: S=power density



## Compliance Certification Services (Shenzhen) Inc.

Report No: C180329Z07-RP1\_MPE

FCC ID: ZVA-IOT-S-SSM-M-B

Date of Issue: May 10, 2018

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

From the EUT RF output power, the minimum mobile separation distance,  $d=0.2\text{m}$ , as well as the maximum gain of the used  $-0.4\text{dBi}$  for Bluetooth, the RF power density can be obtained.

Frequency Band	Antenna type and antenna number	Maximum antenna gain
BT	BT Antenna	$-0.4\text{dBi}$

### 4. Estimation Result

#### 4.1 Conducted Power Results

##### *Bluetooth*

Mode	Channel	Frequency(MHz)	Peak Conducted Output Power (dBm)
GFSK-BLE	00	2402	6.64
	19	2440	6.86
	39	2480	7.09

#### 4.2 Manufacturing tolerance

##### *Bluetooth*

GFSK-BLE			
Frequency (MHz)	2402	2440	2480
Target (dBm)	6.0	6.0	7.0
Tolerance $\pm$ (dB)	1.0	1.0	1.0



### 4.3 Measurement Results

#### 4.3.1 Standalone MPE

##### *Bluetooth*

Mode	Output power (Including tune-up tolerance)		Antenna Gain (dBi)	Antenna Gain (linear)	Duty Cycle	MPE (mW/cm <sup>2</sup> )	MPE Limits (mW/cm <sup>2</sup> )
	(dBm)	(mW)					
CH Low	7.0	5.0119	-0.4	0.9120	100%	0.00091	1.0000
CH Mid	7.0	5.0119	-0.4	0.9120	100%	0.00091	1.0000
CH High	8.0	6.3096	-0.4	0.9120	100%	0.00115	1.0000

*Remark:*

1. *Maximum power including tune-up tolerance;*
2. *MPE use distance is 20cm from manufacturer declaration of user manual.*
3. *We choose 2402 MHz for Bluetooth (lowest frequency operate at 2.4GHz) to calculate MPE limit as higher frequency will have higher MPE limits*

According to KDB447498 for Transmitters used in mobile exposure conditions for simultaneous transmission operations;

#### **Conclusion**

The measurement results comply with the FCC Limit per 47 CFR 2.1091 for the uncontrolled RF Exposure of mobile device.

----- END OF REPORT -----