

FCC PART 15C TEST REPORT FOR CERTIFICATION  
On Behalf of

BYD Precision Manufacture Co., Ltd.

Tablet PC

Model No.: AT10-C

FCC ID: ZW9-PDA0N

Prepared for : BYD Precision Manufacture Co., Ltd.  
No.3001, Baohe Road, Baolong Industrial, Longgang,  
Shenzhen,P. R., China

Prepared By : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block,  
Shenzhen Science & Industrial Park,  
Nantou, Shenzhen, Guangdong, China

Tel: (0755) 26639496

Report Number : ACS-F15344  
Date of Test : Nov.21~Dec.24, 2015  
Date of Report : Dec.31, 2015

## TABLE OF CONTENTS

Description	Page
<b>1. SUMMARY OF STANDARDS AND RESULTS.....</b>	<b>1-1</b>
1.1. Description of Standards and Results .....	1-1
<b>2. GENERAL INFORMATION .....</b>	<b>2-1</b>
2.1. Description of Device (EUT).....	2-1
2.2. Tested Supporting System Details .....	2-2
2.3. Block Diagram of connection between EUT and simulators.....	2-3
2.4. Test information.....	2-3
2.5. Test Facility .....	2-4
2.6. Measurement Uncertainty (95% confidence levels, k=2).....	2-4
<b>3. POWER LINE CONDUCTED EMISSION TEST .....</b>	<b>3-1</b>
3.1. Test Equipments.....	3-1
3.2. Block Diagram of Test Setup.....	3-1
3.3. Power Line Conducted Emission Test Limits.....	3-1
3.4. Configuration of EUT on Test .....	3-2
3.5. Operating Condition of EUT .....	3-2
3.6. Test Procedure .....	3-2
3.7. Power Line Conducted Emission Test Results .....	3-2
<b>4. RADIATED EMISSION MEASUREMENT.....</b>	<b>4-1</b>
4.1. Test Equipment .....	4-1
4.2. Block Diagram of Test Setup.....	4-1
4.3. Radiated Emission Limit Standard: .....	4-2
4.4. EUT Configuration on Test .....	4-2
4.5. Operating Condition of EUT .....	4-2
4.6. Test Procedure .....	4-2
4.7. Radiated Emission Test Results.....	4-3
<b>5. CONDUCTED SPURIOUS EMISSIONS.....</b>	<b>5-1</b>
5.1. Test Equipment .....	5-1
5.2. Limit.....	5-1
5.3. Test Procedure .....	5-1
5.4. Test result.....	5-1
<b>6. 20 DB BANDWIDTH TEST .....</b>	<b>6-1</b>
6.1. Test Equipment .....	6-1
6.2. Limit.....	6-1
6.3. Test Results.....	6-1
<b>7. CARRIER FREQUENCY SEPARATION TEST .....</b>	<b>7-1</b>
7.1. Test Equipment .....	7-1
7.2. Limit.....	7-1
7.3. Test Results.....	7-1
<b>8. NUMBER OF HOPPING FREQUENCY TEST .....</b>	<b>8-1</b>
8.1. Test Equipment .....	8-1
8.2. Limit.....	8-1
8.3. Test Results.....	8-1
<b>9. DWELL TIME .....</b>	<b>9-1</b>
9.1. Test Equipment .....	9-1

9.2.	Limit.....	9-1
9.3.	Test Results.....	9-1
<b>10.</b>	<b>MAXIMUM PEAK OUTPUT POWER TEST .....</b>	<b>10-1</b>
10.1.	Test Equipment.....	10-1
10.2.	Limit.....	10-1
10.3.	Test Procedure .....	10-1
10.4.	Test Results.....	10-1
<b>11.</b>	<b>BAND EDGE COMPLIANCE TEST .....</b>	<b>11-1</b>
11.1.	Test Equipment.....	11-1
11.2.	Limit.....	11-1
11.3.	Test Produce.....	11-1
11.4.	Test Results .....	11-1
<b>12.</b>	<b>TENNA REQUIREMENT .....</b>	<b>12-1</b>
12.1.	Standard Applicable.....	12-1
12.2.	Antenna Connected Construction .....	12-1
<b>13.</b>	<b>DEVIATION TO TEST SPECIFICATIONS.....</b>	<b>13-1</b>
<b>14.</b>	<b>PHOTOGRAPH OF TEST .....</b>	<b>14-1</b>
14.1.	Photos of Power Line Conducted Emission Test.....	14-1
14.2.	Photos of Radiated Emission Test .....	14-2

### TEST REPORT CERTIFICATION

Applicant : BYD Precision Manufacture Co., Ltd.  
Manufacturer : TOSHIBA Corporation  
EUT Description : Tablet PC  
FCC ID : ZW9-PDA0N  
(A) Model NO. : AT10-C  
(B) Serial NO. : N/A  
(C) Test Voltage : DC 5V From Adapter Input 120V/60Hz

Tested for comply with:  
FCC CFR 47 Part 15 Subpart C: 2014

Test procedure used:  
ANSI C63.10: 2013

The device described above is tested by AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. to confirm comply with all the FCC Part 15 Subpart C requirements. The test results are contained in this test report and AUDIX TECHNOLOGY (SHENZHEN) CO., LTD. is assumed full responsibility for the accuracy and completeness of these tests. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC and IC requirements. This report contains data that are not covered by the NVLAP accreditation.

This Report is made under FCC Part 2.1075. No modifications were required during testing to bring this product into compliance.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of AUDIX TECHNOLOGY (SHENZHEN) CO., LTD.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.

Date of Test : Nov.21~Dec.24, 2015 Report of date: Dec.31, 2015

Prepared by : Monica Liu Reviewed by : Sunny Lu  
Monica Liu / Assistant Sunny Lu / Assistant Manager

**AUDIX**<sup>®</sup> 信華科技(深圳)有限公司  
Audix Technology (Shenzhen) Co., Ltd.  
EMC 部門報告專用章  
Stamp only for EMC Dept. Report  
Signature: David Jin

Approved & Authorized Signer : David Jin  
David Jin / Manager

## 1. SUMMARY OF STANDARDS AND RESULTS

### 1.1. Description of Standards and Results

The EUT have been tested according to the applicable standards as referenced below.

EMISSION		
Description of Test Item	Standard	Results
Power Line Conducted Emission Test	FCC Part 15: 15.207 ANSI C63.10 2013	PASS
Radiated Emission Test	FCC Part 15 15.209 FCC Part 15 15.247(d) ANSI C63.10 2013	PASS
Conducted Spurious Emissions	FCC Part 15: 15.247(a)(1) ANSI C63.10 2013	PASS
Carrier Frequency Separation Test	FCC Part 15: 15.247(a)(1) ANSI C63.10 2013	PASS
20dB Bandwidth Test	FCC Part 15: 15.215 ANSI C63.10 2013	PASS
Number Of Hopping Frequency Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 2013	PASS
Dwell Time Test	FCC Part 15: 15.247(a)(1)(iii) ANSI C63.10 2013	PASS
Maximum Peak Output Power Test	FCC Part 15 15.247(b)(1)\ ANSI C63.10 2013	PASS
Band Edge Compliance Test	FCC Part 15 15.247(d) ANSI C63.10 2013	PASS



## 2. GENERAL INFORMATION

### 2.1. Description of Device (EUT)

Product Name : Tablet PC

Model Number : AT10-C

FCC ID : ZW9-PDA0N

Radio : IEEE802.11 a/b/g/n/ac; Bluetooth V3.0+EDR; Bluetooth V4.0

Operation Frequency : IEEE 802.11a:  
5180MHz—5240MHz; 5260MHz—5320MHz  
5500MHz—5700MHz; 5745MHz—5825MHz  
IEEE 802.11ac VHT20:  
5180MHz—5240MHz; 5260MHz—5320MHz  
5500MHz—5700MHz; 5745MHz—5825MHz  
IEEE 802.11ac VHT40:  
5190MHz—5230MHz; 5270MHz—5310MHz  
5510MHz—5670MHz; 5755MHz—5795MHz  
IEEE 802.11ac VHT80: 5210MHz, 5290MHz; 5530MHz; 5775MHz  
IEEE 802.11b: 2412MHz—2462MHz  
IEEE 802.11g: 2412MHz—2462MHz  
IEEE802.11nHT20: 2412MHz—2462MHz;  
5180MHz—5240MHz; 5260MHz—5320MHz  
5500MHz—5700MHz; 5745MHz—5825MHz  
IEEE802.11nHT40:  
5190MHz—5230MHz; 5270MHz—5310MHz  
5510MHz—5670MHz; 5755MHz—5795MHz  
Bluetooth : 2402-2480MHz

Modulation Technology : IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK)  
IEEE 802.11a/g: OFDM(64QAM, 16QAM, QPSK, BPSK)  
IEEE 802.11ac VHT20, VHT40, VHT80: OFDM(16QAM, 64QAM,  
256QAM, QPSK, BPSK)  
IEEE 802.11n HT20, HT40: OFDM (64QAM, 16QAM,QPSK,BPSK)  
Bluetooth V3.0+EDR: GFSK,  $\pi/4$ DQPSK,8-DPSK  
Bluetooth V4.0:GFSK

Antenna Assembly Gain : Antenna Type: PIFA  
Bluetooth: 2.89dBi  
WIFI 2.4GHz:ANT 0: 2.89dBi; ANT 1: 3.94dBi  
U-NII 5180-5240MHz Band: ANT 0: 2.48dBi; ANT 1: 3.29dBi  
U-NII 5260-5320MHz Band: ANT 0: 2.85dBi; ANT 1: 2.69dBi  
U-NII 5500-5700MHz Band: ANT 0: 2.51dBi; ANT 1: 2.66dBi  
U-NII 5745-5825MHz Band: ANT 0: 2.84dBi; ANT 1: 3.41dBi

Applicant : BYD Precision Manufacture Co., Ltd.  
No.3001, Baohe Road, Baolong Industrial, Longgang, Shenzhen,P.  
R., China

Manufacturer : TOSHIBA Corporation  
1-1, Shibaura 1-Chome, Minato-ku, Tokyo, Japan

Factory : BYD Precision Manufacture Co., Ltd  
No.3001, Baohe Road, Baolong Industrial, Longgang,  
Shenzhen, 518116, P.R., China

Power Adapter : Manufacturer: Chicony power Technology Co., Ltd  
M/N: W12-010N3A  
Input: 100-240 V,50/60Hz, 0.3A  
Output: 5V,2A

USB Cable Unshielded, Detachable, 0.9m


Date of Test : Nov.21~Dec.24, 2015

Date of Receipt : Nov.18, 2015

## 2.2. Tested Supporting System Details

No.	Description	ACS No.	Manufacturer	Model	Serial Number
1.	Headphone	ACS-EMC-EP01	OVANN	OV880V	---
		Data Cable: Shielded, Undetachable, 2.0m			

2.3. Block Diagram of connection between EUT and simulators



**(EUT: Tablet PC)**

2.4. Test information

A special software was used to control EUT work in continuous TX mode (GFSK,  $\pi/4$ DQPSK, 8-DPSK Modulation)

Tested mode, channel, and data rate information			
Mode	data rate (Mbps)	Channel	Frequency (MHz)
Tx Mode GFSK modulation	1	Low :CH 0	2402
	1	Middle: CH39	2441
	1	High: CH78	2480
Tx Mode 8-DPSK modulation	3	Low :CH 0	2402
	3	Middle: CH39	2441
	3	High: CH78	2480

Note:  $\pi/4$ DQPSK modulation is same type modulation with 8-DPSK, and according exploratory test, 8-DPSK will have worse emissions, so the final test were only performed with GFSK and 8-DPSK modulation.



**2.5. Test Facility**

Site Description

- Name of Firm : Audix Technology (Shenzhen) Co., Ltd.  
No. 6, Ke Feng Rd., 52 Block, Shenzhen  
Science & Industrial Park, Nantou, Shenzhen,  
Guangdong, China
- 3m Anechoic Chamber : Certificated by FCC, USA  
Registration Number: 90454  
Valid Date: Dec.30, 2017
- 3m & 10m Anechoic Chamber : Certificated by FCC, USA  
Registration Number: 794232  
Valid Date: Jul.12, 2016
- EMC Lab. : Certificated by Industry Canada  
Registration Number: IC 5183A-1  
Valid Date: May.14, 2017
- : Certificated by DAkkS, Germany  
Registration No: D-PL-12151-01-00  
Valid Date: Dec.15, 2016
- : Accredited by NVLAP, USA  
NVLAP Code: 200372-0  
Valid Date: Mar.31, 2016

**2.6. Measurement Uncertainty (95% confidence levels, k=2)**


Test Item	Uncertainty
Uncertainty for Conduction emission test in No. 1 Conduction	3.4dB (150KHz to 30MHz)
Uncertainty for Radiation Emission test in 3m chamber	2.6 dB(30~200MHz, Polarization: H)
	2.6 dB(30~200MHz, Polarization: V)
	3.0 dB(200M~1GHz, Polarization: H)
	2.8 dB(200M~1GHz, Polarization: V)
Uncertainty for Radiation Emission test in 3m chamber (1GHz-18GHz)	6.3 dB (1~6GHz, Distance: 3m)
	5.7 dB (6~18GHz, Distance: 3m)
Uncertainty for Radiated Spurious Emission test in RF chamber	3.6 dB
Uncertainty for Conduction Spurious emission test	2.0 dB
Uncertainty for Output power test	0.8 dB
Uncertainty for Bandwidth test	83 kHz
Uncertainty for DC power test	0.1 %
Uncertainty for test site temperature and humidity	0.6°C
	3%

### 3. POWER LINE CONDUCTED EMISSION TEST

#### 3.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	1# Shielding Room	AUDIX	N/A	N/A	Apr.17,15	1 Year
2.	Test Receiver	Rohde & Schwarz	ESCI	100842	Apr.28,15	1 Year
3.	L.I.S.N.#1	Rohde & Schwarz	ESH2-Z5	100429	Oct.18,15	1 Year
4.	L.I.S.N.#2	Kyoritsu	K NW-403D	8-1750-2	Apr.28,15	1 Year
5.	Terminator	Hubersuhner	50Ω	No.1	Apr.28,15	1 Year
6.	Terminator	Hubersuhner	50Ω	No.2	Apr.28,15	1 Year
7.	RF Cable	MIYAZAKI	3D-2W	No.1	Apr.28,15	1 Year
8.	Coaxial Switch	Anritsu	MP59B	6200766906	Apr.28,15	1 Year
9.	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	101838	Oct.17,15	1 Year
10.	Test Software	AUDIX	E3	6.100913a	N/A	N/A

#### 3.2. Block Diagram of Test Setup



#### 3.3. Power Line Conducted Emission Test Limits

Frequency	Maximum RF Line Voltage	
	Quasi-Peak Level dB(μV)	Average Level dB(μV)
150kHz ~ 500kHz	66 ~ 56*	56 ~ 46*
500kHz ~ 5MHz	56	46
5MHz ~ 30MHz	60	50

Notes: 1. \* Decreasing linearly with logarithm of frequency.

2. The lower limit shall apply at the transition frequencies.

### 3.4. Configuration of EUT on Test

The following equipment are installed on Power Line Conducted Emission Test to meet the commission requirement and operating regulations in a manner which tends to maximize its emission characteristics in a normal application.

#### 3.4.1. Tablet PC (EUT)

Model Number : AT10-C  
Serial Number : N/A

3.4.2. Support Equipment: As Tested Supporting System Details, in Section 2.2.

### 3.5. Operating Condition of EUT

3.5.1. Setup the EUT and simulator as shown as Section 3.2.

3.5.2. Turn on the power of all equipments.

3.5.3. PC run test software to control EUT work in BT 3.0 Tx mode.

### 3.6. Test Procedure


The EUT was placed on a non-metallic table, 80cm above the ground plane. The EUT Power Via PC connected to the power mains through a line impedance stabilization network (L.I.S.N. 1#). This provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs). The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.

The bandwidth of test receiver (R & S ESCI ) is set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

### 3.7. Power Line Conducted Emission Test Results

**PASS.** (All emissions not reported below are too low against the prescribed limits.)




Trace: (Discrete)

Site no :1# Conduction Data No :1  
 Dis./Lisn :2015 ESH2-Z5 LINE  
 Limit :FCC PART 15 C  
 Env./Ins. :25.5\*C/56% Engineer :alvis-Wu  
 EUT :Table PC M/N:AT10-C  
 Power Rating :DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode :Tx Mode

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.150	0.12	0.05	30.20	30.37	56.00	25.63	Average
2	0.150	0.12	0.05	46.77	46.94	66.00	19.06	QP
3	0.170	0.12	0.05	26.90	27.07	54.94	27.87	Average
4	0.170	0.12	0.05	45.28	45.45	64.94	19.49	QP
5	0.198	0.12	0.05	29.60	29.77	53.71	23.94	Average
6	0.198	0.12	0.05	42.12	42.29	63.71	21.42	QP
7	0.513	0.14	0.06	32.30	32.50	46.00	13.50	Average
8	0.513	0.14	0.06	42.36	42.56	56.00	13.44	QP
9	0.904	0.16	0.07	25.30	25.53	46.00	20.47	Average
10	0.904	0.16	0.07	34.96	35.19	56.00	20.81	QP
11	6.592	0.30	0.16	24.70	25.16	50.00	24.84	Average
12	6.592	0.30	0.16	35.64	36.10	60.00	23.90	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.



Trace: (Discrete)

Site no :1# Conduction Data No :2  
 Dis./Lisn :2015 ESH2-25 NEUTRAL  
 Limit :FCC PART 15 C  
 Env./Ins. :25.5\*C/56% Engineer :Alvis-Wu  
 EUT :Table PC M/N:AT10-C  
 Power Rating :DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode :Tx Mode

No	Freq (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.162	0.12	0.05	28.40	28.57	55.34	26.77	Average
2	0.162	0.12	0.05	43.83	44.00	65.34	21.34	QP
3	0.182	0.12	0.05	29.30	29.47	54.42	24.95	Average
4	0.182	0.12	0.05	41.79	41.96	64.42	22.46	QP
5	0.190	0.12	0.05	26.80	26.97	54.02	27.05	Average
6	0.190	0.12	0.05	41.72	41.89	64.02	22.13	QP
7	0.211	0.12	0.05	29.30	29.47	53.18	23.71	Average
8	0.211	0.12	0.05	39.38	39.55	63.18	23.63	QP
9	0.521	0.14	0.06	30.20	30.40	46.00	15.60	Average
10	0.521	0.14	0.06	34.85	35.05	56.00	20.95	QP
11	6.252	0.33	0.15	18.90	19.38	50.00	30.62	Average
12	6.252	0.33	0.15	29.86	30.34	60.00	29.66	QP

Remarks: 1.Emission Level=LISN Factor+Cable Loss(Include 10dB pulse limit)+Reading.  
 2.If the average limit is met when using a quasi-peak detector, the EUT shall be deemed to meet both limits and measurement with average detector is unnecessary.

## 4. RADIATED EMISSION MEASUREMENT

### 4.1. Test Equipment


Frequency range: 30~1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	3#Chamber	AUDIX	N/A	N/A	Mar.28,15	1 Year
2.	EMI Spectrum	Agilent	E4407B	MY41440292	Apr.28,15	1 Year
3.	Test Receiver	Rohde & Schwarz	ESVS10	834468/011	Apr.28,15	1 Year
4.	Amplifier	HP	8447D	2648A04738	Apr.28,15	1 Year
5.	Bilog Antenna	TESEQ	CBL6112D	35375	Jun.30,15	1 Year
6.	RF Cable	MIYAZAKI	CFD400-NW(3.5M)	No.3	Apr.28,15	1 Year
7.	RF Cable	MIYAZAKI	CFD400-LW(22M)	No.7	Apr.28,15	1 Year
8.	Coaxial Switch	Anritsu	MP59B	6201397222	Apr.28,15	1 Year
9.	Test Software	AUDIX	E3	6.2009-5-21a(n)	N/A	N/A


Frequency range: above 1000MHz

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum Analyzer	Agilent	E4446A	US44300459	Apr.28,15	1 Year
2.	Horn Antenna	ETC	MCTD 1209	DRH15F03007	Feb.03,15	1 Year
3.	Amplifier	Agilent	8449B	3008A02495	Apr.28,15	1 Year
4.	RF Cable	Hubersuhner	SUCOFLEX106	77977/6	Apr.28,15	1 Year
5.	Horn Antenna	ETS	3116	00060088	Nov.18.15	1 Year
6.	Test Software	AUDIX	E3	6.2009-5-21a(n)	N/A	N/A

4.2. Block Diagram of Test Setup  
For frequency range 30MHz-1000MHz



For frequency range 1GHz-25GHz





4.3. Radiated Emission Limit Standard:

FREQUENCY MHz	DISTANCE Meters	FIELD STRENGTHS LIMIT	
		μV/m	dB(μV)/m
30 ~ 88	3	100	40.0
88 ~ 216	3	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000MHz	3	74.0 dB(μV)/m (Peak) 54.0 dB(μV)/m (Average)	

- Remark :
- (1) Emission level dBμV = 20 log Emission level μV/m
  - (2) The smaller limit shall apply at the cross point between two frequency bands.
  - (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.
  - (4) The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.

4.4. EUT Configuration on Test

The following equipment are installed on Radiated Emission Test to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.4.1. Tablet PC (EUT)

Model Number : AT10-C  
Serial Number : N/A

4.5. Operating Condition of EUT

- 4.5.1. Setup the EUT and simulator as shown as Section 4.2.
- 4.5.2. Turn on the power of all equipments.
- 4.5.3. Let EUT work in BT 3.0 Tx mode.

4.6. Test Procedure

EUT and its simulators are placed on a turn table, which is 0.8 meter high above ground for frequency 30MHz~1000MHz, 1.5 meter high above ground for frequency above 1GHz and put the absorbing with 2.4m(L)\*2.4m(W)\*0.3m(H) on the ground . The turn table can rotate 360 degrees to determine the position of the maximum emission level. Power on the EUT and let it working in test mode, then test it. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bilog antenna) is used as receiving antenna for frequency 30MHz~1000MHz, and the Horn antenna is used as receiving antenna for frequency above 1GHz. Both horizontal and vertical polarization of the antenna is set on Test. In order to find the maximum emission levels, all of the interface cables must be manipulated according to ANSI C63.10-2013 on radiated emission Test.

This test was performed with EUT in X, Y, Z position, and the worse case was found when EUT in X position as the test photo indicated.

The bandwidth of the EMI test receiver (R&S ESVS10) is set at 120kHz for frequency range from 30MHz to 1000 MHz.

The bandwidth of the Spectrum's RBW is set at 1MHz and VBW is set at 3MHz for peak emissions measurement above 1GHz

This device is pulse Modulated, a duty cycle factor was used to calculated average level based measured peak level.

The frequency range from 30MHz to 10th harmonic (25GHz) are checked. and no any emissions were found from 18GHz to 25 GHz, So the radiated emissions from 18GHz to 25GHz were not record.



#### 4.7.Radiated Emission Test Results

**PASS.**


All the emissions from 30MHz to 25GHz were comply with the 15.209 Limit.

Note: The duty cycle factor for calculate average level is -24.524dB, and average limit is 20dB below peak limit, so if peak measured level comply with average limit, the average level was deemed to comply with average limit.

Duty cycle factor =  $20\log (Dwell\ time/100ms) = -24.524$




**Frequency: 30MHz~1GHz**



Site no. : 3m Chamber Data no. : 2  
 Dis. / Ant. : 3m 2015 CBL6112D 35375 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 22.1°C/50% Engineer : Donjon  
 EUT : Tablet PC M/N:AT10-C  
 Power rating : DC 5V Frow Adapter Input AC 120V/60Hz  
 Test Mode : Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	34.850	17.15	0.61	5.19	22.95	40.00	17.05	QP
2	154.160	11.59	1.32	13.10	26.01	43.50	17.49	QP
3	390.840	16.56	2.18	14.18	32.92	46.00	13.08	QP
4	413.150	17.01	2.25	9.74	29.00	46.00	17.00	QP
5	801.150	21.09	3.26	11.06	35.41	46.00	10.59	QP
6	949.560	22.34	3.61	3.95	29.90	46.00	16.10	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 1  
 Dis. / Ant. : 3m 2015 CBL6112D 35375 Ant. pol. : VERTICAL  
 Limit : FCC PART 15 C (3M)  
 Env. / Ins. : 22.1°C/50% Engineer : Donjon  
 EUT : Tablet PC M/N:AT10-C  
 Power rating : DC 5V Frow Adapter Input AC 120V/60Hz  
 Test Mode : Tx Mode

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	31.940	18.94	0.61	9.63	29.18	40.00	10.82	QP
2	86.260	8.95	1.02	14.37	24.34	40.00	15.66	QP
3	138.640	12.24	1.27	15.73	29.24	43.50	14.26	QP
4	471.350	17.66	2.42	3.66	23.74	46.00	22.26	QP
5	600.360	19.31	2.77	3.08	25.16	46.00	20.84	QP
6	801.150	21.09	3.26	3.20	27.55	46.00	18.45	QP


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency: 1GHz~18GHz

Data: 1

File: F:\2015\_Report\B\BYD\ACS15Q1810-FCC-BT.EM6 (54)

Date: 2015-11-30



Site no. : 3m Chamber Data no. : 1  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : GFSK 2402MHz Tx Mode  
AT10-C




Site no. : 3m Chamber Data no. : 2  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : GFSK 2402MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.00	7.32	36.62	94.87	93.57	74.00	-19.57	Peak
2	4804.000	33.69	9.46	35.54	52.77	60.38	74.00	13.62	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit (dBuV/m)	Conclusion
4804	60.38	-24.524	35.856	54	Pass






Site no. : 3m Chamber Data no. : 3  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : GFSK 2402MHz Tx Mode  
AT10-C




Site no. : 3m Chamber Data no. : 4  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : GFSK 2402MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.00	7.32	36.62	77.09	75.79	74.00	-1.79	Peak
2	4804.000	33.69	9.46	35.54	42.96	50.57	74.00	23.43	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 7  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : GFSK 2441MHz Tx Mode  
AT10-C




Site no. : 3m Chamber Data no. : 8  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : GFSK 2441MHz Tx Mode  
 AT10-C


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.08	7.39	36.60	94.91	93.78	74.00	-19.78	Peak
2	4882.000	33.81	9.49	35.51	53.77	61.56	74.00	12.44	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit (dBuV/m)	Conclusion
4884	61.56	-24.524	37.036	54	Pass




Site no. : 3m Chamber Data no. : 9  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : GFSK 2441MHz Tx Mode  
AT10-C



Site no. : 3m Chamber Data no. : 10  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : GFSK 2441MHz Tx Mode  
 AT10-C


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.08	7.39	36.60	83.83	82.70	74.00	-8.70	Peak
2	4882.000	33.81	9.49	35.51	45.24	53.03	74.00	20.97	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 11  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : GFSK 2480MHz Tx Mode  
AT10-C






Site no. : 3m Chamber Data no. : 12  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : GFSK 2480MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.16	7.47	36.59	87.28	86.32	74.00	-12.32	Peak
2	4960.000	33.94	9.52	35.47	44.94	52.93	74.00	21.07	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 13  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : GFSK 2480MHz Tx Mode  
AT10-C




Site no. : 3m Chamber Data no. : 14  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : GFSK 2480MHz Tx Mode  
 AT10-C


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.16	7.47	36.59	96.35	95.39	74.00	-21.39	Peak
2	4960.000	33.94	9.52	35.47	53.37	61.36	74.00	12.64	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit (dBuV/m)	Conclusion
4960	61.36	-24.524	36.836	54	Pass




Site no. : 3m Chamber Data no. : 17  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : 8-DPSK 2402MHz Tx Mode  
AT10-C




Site no. : 3m Chamber Data no. : 18  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : 8-DPSK 2402MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.00	7.32	36.62	74.39	73.09	74.00	0.91	Peak
2	4804.000	33.69	9.46	35.54	43.44	51.05	74.00	22.95	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 19  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : 8-DPSK 2402MHz Tx Mode  
AT10-C




Site no. : 3m Chamber Data no. : 20  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : 8-DPSK 2402MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2402.000	28.00	7.32	36.62	88.68	87.38	74.00	-13.38	Peak
2	4804.000	33.69	9.46	35.54	49.11	56.72	74.00	17.28	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit (dBuV/m)	Conclusion
4804	56.72	-24.524	32.196	54	Pass





Site no. : 3m Chamber Data no. : 23  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : 8-DPSK 2441MHz Tx Mode  
AT10-C




Site no. : 3m Chamber Data no. : 24  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : 8-DPSK 2441MHz Tx Mode  
 AT10-C


No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.08	7.39	36.60	93.79	92.66	74.00	-18.66	Peak
2	4882.000	33.81	9.49	35.51	52.94	60.73	74.00	13.27	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit (dBuV/m)	Conclusion
4882	60.73	-24.524	36.206	54	Pass




Site no. : 3m Chamber Data no. : 25  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : 8-DPSK 2441MHz Tx Mode  
AT10-C




Site no. : 3m Chamber Data no. : 26  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : 8-DPSK 2441MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2441.000	28.08	7.39	36.60	78.90	77.77	74.00	-3.77	Peak
2	4882.000	33.81	9.49	35.51	42.98	50.77	74.00	23.23	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.




Site no. : 3m Chamber Data no. : 27  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : 8-DPSK 2480MHz Tx Mode  
AT10-C




Site no. : 3m Chamber Data no. : 28  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : 8-DPSK 2480MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.16	7.47	36.59	82.97	82.01	74.00	-8.01	Peak
2	4960.000	33.94	9.52	35.47	44.42	52.41	74.00	21.59	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 29  
Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
Limit : FCC PART 15C PEAK  
Env. / Ins. : 23.4°C/53.2%  
Engineer : Alice\_yang  
EUT : Tablet PC  
Power rating : DC 5V From Adapter Input AC 120V/60Hz  
Test Mode : 8-DPSK 2480MHz Tx Mode  
AT10-C



Site no. : 3m Chamber Data no. : 30  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4\*C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : 8-DPSK 2480MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.000	28.16	7.47	36.59	90.66	89.70	74.00	-15.70	Peak
2	4960.000	33.94	9.52	35.47	51.49	59.48	74.00	14.52	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit (dBuV/m)	Conclusion
4960	59.48	-24.524	34.956	54	Pass



## 5. CONDUCTED SPURIOUS EMISSIONS

### 5.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.17, 15	1Year
2.	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	Apr. 28,15	1 Year

### 5.2. Limit

In any 100kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power.

### 5.3. Test Procedure

The transmitter output was connected to a spectrum analyzer, The resolution bandwidth is set to 100 kHz, The video bandwidth is set to 300 kHz and measure all the emissions With peak detector.


### 5.4. Test result

**PASS** (The testing data was attached in the next pages.)


**Hopping off**

**GFSK**


2402MHz(30MHz – 1GHz)




2402MHz(10GHz – 25GHz)



2402MHz(1GHz – 10GHz)




2441(30MHz – 1GHz)




2402MHz(2.3GHz – 2.4GHz)



2441(1GHz – 10GHz)




2441(10GHz – 25GHz)




2480MHz(2.4GHz – 2.5GHz)




2480MHz(30MHz – 1GHz)



2480MHz(10GHz – 25GHz)




2480MHz(1GHz – 10GHz)




8-DPSK


2402MHz(30MHz – 1GHz)



2402MHz(1GHz – 10GHz)




2441MHz (30MHz – 1GHz)




2402MHz(2.3GHz – 2.4GHz)



2441MHz(1GHz – 10GHz)



2402MHz(10GHz – 25GHz)




2441MHz(10GHz – 25GHz)







2480MHz(30MHz – 1GHz)



2480MHz(10GHz – 25GHz)



2480MHz(1GHz – 10GHz)



Hopping on GFSK(2.3GHz – 2.4GHz)



2480MHz(2.4GHz – 2.5GHz)



(2.4GHz – 2.5GHz)



**8-DPSK(2.3GHz – 2.4GHz)**



**(2.4GHz – 2.5GHz)**



## 6. 20 DB BANDWIDTH TEST

### 6.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.17, 15	1 Year
2.	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	Apr. 28,15	1 Year

### 6.2. Limit


Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §§ 15.217 through 15.257 and in Subpart E of this part, must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.

### 6.3. Test Results

EUT: Tablet PC			
M/N: AT10-C			
Test date: 2015-11-21		Pressure: 101.8±1.0kpa	Humidity: 51.8±3.0%
Tested by: Donjon_Huang		Test site: RF site	Temperature: 21.7±0.6 °C
Test Mode	Frequency (MHz)	20dB bandwidth (kHz)	Limit (kHz)
GFSK	2402	1043	N/A
	2441	1043	N/A
	2480	1042	N/A
8-DPSK	2402	1319	N/A
	2441	1320	N/A
	2480	1318	N/A
Conclusion : PASS			

**GFSK**

2402MHz



**8-DPSK**

2402MHz



2441MHz



2441MHz



2480MHz



2480MHz





## 7. CARRIER FREQUENCY SEPARATION TEST

### 7.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.17, 15	1Year
2.	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	Apr. 28,15	1 Year

### 7.2. Limit

Frequency hopping systems shall have hopping channel carrier frequency separated by a minimum of 25kHz or the 20dB bandwidth of the hopping channel, whichever is greater. Alternatively, frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125mW.

### 7.3. Test Results.

EUT: Tablet PC		
M/N: AT10-C		
Test date: 2015-11-21	Pressure: 101.4±1.0 kpa	Humidity: 51.4±3.0%
Tested by: Donjon_Huang	Test site: RF Site	Temperature: 23.4±0.6°C

Test Mode	Channel separation	Limit(kHz)	Conclusion
8-DPSK	1.0MHz	879.333	PASS
GFSK	1.0MHz	695.333	PASS



## 8. NUMBER OF HOPPING FREQUENCY TEST

### 8.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.17, 15	1Year
2.	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	Apr.28, 15	1 Year


### 8.2. Limit

Frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels

### 8.3. Test Results

EUT: Tablet PC		
M/N: AT10-C		
Test date: 2015-11-21	Pressure: 101.4±1.0 kpa	Humidity: 51.4±3.0%
Tested by: Donjon_Huang	Test site: RF Site	Temperature: 23.4±0.6°C

Test Mode	Number of channel	Limit	Conclusion
8-DPSK	79	>=15	PASS
GFSK	79	>=15	PASS



## 9. DWELL TIME

### 9.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1	Spectrum Analyzer	Agilent	N9030A	MY51380221	Oct.17, 15	1Year
2.	RF Cable	Hubersuhner	SUCOFLEX102	28620/2	Apr.28, 15	1 Year

### 9.2. Limit

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

### 9.3. Test Results



EUT: Tablet PC		
M/N: AT10-C		
Test date: 2015-11-21	Pressure: 101.4±1.0 kpa	Humidity: 51.4±3.0%
Tested by: Donjon_Huang	Test site: RF Site	Temperature: 23.4±0.6°C

Mode		dwll time	Limit	Conclusion
GFSK	DH1	$45\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 0.455\text{ms} = 123.714\text{ms}$	<400ms	PASS
	DH3	$23\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 1.695\text{ms} = 246.385\text{ms}$	<400ms	PASS
	DH5	$14\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 2.945\text{ms} = 260.574\text{ms}$	<400ms	PASS
8-DPSK	DH1	$48\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 0.455\text{ms} = 138.029\text{ms}$	<400ms	PASS
	DH3	$24\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 1.722\text{ms} = 261.193\text{ms}$	<400ms	PASS
	DH5	$18\text{hops}/5\text{s} * 0.4 * 79\text{chanel} * 2.965\text{ms} = 337.298\text{ms}$	<400ms	PASS



Note: All the lower levels were signaled from receiver and should not be considered in here.

**GFSK**



**DH 1**



**DH 3**




**DH 5**





**8-DPSK**



**3DH 1**



**3DH 3**



**3DH 5**





## 10. MAXIMUM PEAK OUTPUT POWER TEST

### 10.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	N9030A	MY51380221	Oct.17, 15	1Year
2.	Power meter	Anritsu	ML2487A	6K00002472	Apr. 28,15	1Year
3.	Power sensor	Anritsu	MA2491A	0033005	Apr. 28,15	1Year
5.	RF Cable	Hubersuhner	SUCOFLEX102	28610/2	Apr. 28,15	1Year

### 10.2. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.

### 10.3. Test Procedure

Connected the EUT's antenna port to Power Sensor, and use power meter to test peak output power directly.

### 10.4. Test Results

EUT: Tablet PC			
M/N: AT10-C			
Test date: 2015-11-21		Pressure: 101.8±1.0 kpa	Humidity: 51.8±3.0%
Tested by: Donjon_Huang		Test site: RF site	Temperature: 21.7±0.6 °C
Test Mode	Frequency (MHz)	Peak output Power (dBm)	Limit (dBm)
GFSK	2402	-8.563	30
	2441	-6.238	30
	2480	-4.554	30
8-DPSK	2402	-9.304	30
	2441	-6.996	30
	2480	-5.324	30
Conclusion: PASS			

## 11. BAND EDGE COMPLIANCE TEST

### 11.1. Test Equipment

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	Spectrum	Agilent	E4446A	US44300459	Apr.28,15	1 Year
2.	Amp	HP	8449B	3008A02495	Apr.28,15	1 Year
3.	Horn Antenna	ETC	MCTD 1209	DRH15F03007	Feb.03,15	1 Year
4.	HF Cable	Hubersuhner	Sucoflex104	274094/4	Apr.28,15	1 Year

### 11.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

### 11.3. Test Produce

For upper band emissions that are up to two bandwidths(2MHz) away (2483.5MHz to 2485.5MHz) from the band-edge use below produce:

1. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 100KHz and with a video bandwidth 300KHz. Record the peak levels of the fundamental emission and the relevant band-edge emission, Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement, it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.
2. Subtract the delta measured in step (1) from the maximum field strengths measured in clause 4 .The resultant field strengths are then used to determine band-edge compliance as required by Section 15.205


For emissions above two bandwidths away from the band-edge use below produce:

1. The EUT is placed on a insulating material (up to 12mm thick) worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
  - (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
  - (b) This is pulse Modulation device a duty cycle factor was used to calculate average level based measured peak level.

### 11.4. Test Results

Pass (The testing data was attached in the next pages.)

Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.




Site no. : 3m Chamber Data no. : 5  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4\*C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : GFSK 2402MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	27.98	7.28	36.62	44.91	43.55	74.00	30.45	Peak
2	2400.000	28.00	7.32	36.62	46.80	45.50	74.00	28.50	Peak
3	2402.150	28.00	7.32	36.62	81.63	80.33	74.00	-6.33	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.






Site no. : 3m Chamber Data no. : 6  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : GFSK 2402MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	27.98	7.28	36.62	44.74	43.38	74.00	30.62	Peak
2	2400.000	28.00	7.32	36.62	59.60	58.30	74.00	15.70	Peak
3	2402.150	28.00	7.32	36.62	95.91	94.61	74.00	-20.61	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 15  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : GFSK 2480MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.805	28.16	7.47	36.59	98.20	97.24	74.00	-23.24	Peak
2	2483.500	28.17	7.51	36.59	44.96	44.05	74.00	29.95	Peak
3	2492.609	28.19	7.51	36.58	47.18	46.30	74.00	27.70	Peak
4	2500.000	28.20	7.51	36.58	44.49	43.62	74.00	30.38	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 16  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : GFSK 2480MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.871	28.16	7.47	36.59	87.37	86.41	74.00	-12.41	Peak
2	2483.500	28.17	7.51	36.59	44.12	43.21	74.00	30.79	Peak
3	2490.200	28.18	7.51	36.58	47.08	46.19	74.00	27.81	Peak
4	2500.000	28.20	7.51	36.58	45.53	44.66	74.00	29.34	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 21  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : 8-DPSK 2402MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	27.98	7.28	36.62	44.33	42.97	74.00	31.03	Peak
2	2400.000	28.00	7.32	36.62	59.37	58.07	74.00	15.93	Peak
3	2402.150	28.00	7.32	36.62	95.67	94.37	74.00	-20.37	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 22  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : 8-DPSK 2402MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2390.000	27.98	7.28	36.62	45.36	44.00	74.00	30.00	Peak
2	2400.000	28.00	7.32	36.62	60.08	58.78	74.00	15.22	Peak
3	2401.960	28.00	7.32	36.62	95.47	94.17	74.00	-20.17	Peak


Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 31  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : HORIZONTAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : 8-DPSK 2480MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2480.135	28.16	7.47	36.59	96.78	95.82	74.00	-21.82	Peak
2	2483.500	28.17	7.51	36.59	45.22	44.31	74.00	29.69	Peak
3	2487.824	28.18	7.51	36.58	46.15	45.26	74.00	28.74	Peak
4	2500.000	28.20	7.51	36.58	45.96	45.09	74.00	28.91	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.



Site no. : 3m Chamber Data no. : 32  
 Dis. / Ant. : 3m 2015 MCTD1209 3006 Ant. pol. : VERTICAL  
 Limit : FCC PART 15C PEAK  
 Env. / Ins. : 23.4°C/53.2%  
 Engineer : Alice\_yang  
 EUT : Tablet PC  
 Power rating : DC 5V From Adapter Input AC 120V/60Hz  
 Test Mode : 8-DPSK 2480MHz Tx Mode  
 AT10-C

No.	Freq. (MHz)	Ant. Factor (dB/m)	Cable Loss (dB)	AMP factor (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
1	2479.970	28.16	7.47	36.59	85.68	84.72	74.00	-10.72	Peak
2	2483.500	28.17	7.51	36.59	44.80	43.89	74.00	30.11	Peak
3	2489.045	28.18	7.51	36.58	46.17	45.28	74.00	28.72	Peak
4	2500.000	28.20	7.51	36.58	43.91	43.04	74.00	30.96	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading - Amp Factor  
 2. The emission levels that are 20dB below the official limit are not reported.

## 12. TENNA REQUIREMENT

### 12.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 12.2. Antenna Connected Construction

The antennas used for this product are PIFA antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 2.89dBi



### **13. DEVIATION TO TEST SPECIFICATIONS**

[NONE]