

RF EXPOSURE REPORT

Applicant	Guangdong Leetac Electronics Technology Co .,Ltd.
Address	No.15 Danli Road, South District, Zhongshan, Guangdong, China.

Manufacturer or Supplier	Guangdong Leetac Electronics Technology Co .,Ltd.			
Address	o.15 Danli Road, South District, Zhongshan, Guangdong, China.			
Product	esktop Jukebox			
Brand Name	Leetac, Innovative Technology			
Model	E-6H10			
Additional Model & Model Difference	E-6H1x, VJB-125, ITVS-125 ("x" can be replaced by digit "1-9" or letter A-Z); See items 1			
Date of tests	May 16, 2017 ~Jun. 21, 2017			

- **⊠** IEEE C95.1

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Andy Zhu	Approved by Glyn He	
Project Engineer / EMC Department	Supervisor/ EMC Department	

Date: Jun. 26, 2017

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

REL	EASE CONTROL RECORD	3
1.	CERTIFICATION	4
	RF EXPOSURE LIMIT	
3.	MPE CALCULATION FORMULA	5
4.	CLASSIFICATION	5
5.	ANTENNA GAIN	6
6	CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	6

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FS170516N034	Original release	Jun. 26, 2017

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



1. CERTIFICATION

FCC ID:	ZXNLEETACE6H10		
PRODUCT:	Desktop Jukebox		
BRAND NAME:	Leetac, Innovative Technology		
MODEL NO.: E-6H10			
ADDITIONAL NO.:	E-6H1x, VJB-125, ITVS-125 ("x" can be replaced by digit "1-9" or letter A-Z);		
APPLICANT:	Guangdong Leetac Electronics Technology Co.,Ltd.		
STANDARDS:	FCC Part 2 (Section 2.1091)		
	KDB 447498 D01		
	IEEE C95.1		

NOTE:

- 1. Additional models E-6H1x, VJB-125, ITVS-125 are identical with the test model E-6H10, except the model number for marketing purpose.
 - Remark: 1. Basic model: E-6H10
 - 2. Alternative model: E-6H1x, VJB-125, ITVS-125 ("x" can be replaced by digit "1-9" or letter A-Z);
 - 3. Brand Name: Leetac, Innovative Technology, Victrola
 - 4. Innovative Technology can be used for ITVS-125; Victrola can be used for VJB-125; Leetac can be used for E-6H10, E-6H1x.

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD MAGNETIC FIELD STRENGTH (V/m)		POWER DENSITY (mW/cm²)	AVERAGE TIME (minutes)		
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE						
300-1500	300-1500 F/1500 30					
1500-100,000			1.0	30		

F = Frequency in MHz

3. MPE CALCULATION FORMULA

 $Pd = (Pout*G) / (4*pi*r^2)$

where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as Mobile Device.

Fax: +86 769 8593 1080

Tel: +86 769 8593 5656

Email: customerservice.dg@cn.bureauveritas.com

Page 5 of 6

Report Version 1



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Peak Gain (dBi)		Antenna Type	
Chain 0	0	Integral PCB Antenna	

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
GFSK	2402-2480	-1	+-2	-3	1
8DPSK	2402-2480	-5	+-2	-7	-3

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
GFSK	2402	-0.64
8DPSK	2402	-4.21

FREQUENCY BAND (MHz)	UPPER TOLERANCE (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm²)	LIMIT (mW/cm²)
2402-2480	1	0	20	0.00025	1.0

--- END ---

Tel: +86 769 8593 5656 Fax: +86 769 8593 1080

Email: customerservice.dg@cn.bureauveritas.com

Page 6 of 6