



BUREAU
VERITAS

Test Report No.: RF160202N044



TEST REPORT



Applicant	Zhongshan Leetac Electronics Co.,Ltd
Address	No.15 Danli Road, South District, Zhongshan, Guangdong, China.

Manufacturer or Supplier	Zhongshan Leetac Electronics Co.,Ltd
Address	No.15 Danli Road, South District, Zhongshan, Guangdong, China.
Product	BRIGHT TUNES
Brand Name	Innovative Technology, Victrola
Model	BRT-150-GA-80
Additional Model & Model Difference	BRT-150-xy-z, BRT-250-xy-z, BRT-100-BCC-25, BRT-100-BW-20, BRT-100-BX-20, BRT-100-GA-80, BRT-100-GD-80, BRT-100-GF-80, BRT-100-WA-80, BRT-100-WU-20, BRT-200-GG-80, BRT-200-GI-80, BRT-100-xy-z, BRT-200-xy-z, see section 2.1
Date of tests	Feb. 02, 2016 ~ Feb. 29, 2016

the tests have been carried out according to the requirements of the following standards:

FCC Part 15, Subpart C, Section 15.247

CONCLUSION: The submitted sample was found to COMPLY with the test requirement

Tested by Breeze Jiang Project Engineer / EMC Department	Approved by Chris Chen Manager / EMC Department
	
	Date: Feb. 29, 2016

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification



TABLE OF CONTENTS

RELEASE CONTROL RECORD 5

1 SUMMARY OF TEST RESULTS..... 6

2 MEASUREMENT UNCERTAINTY 6

3 GENERAL INFORMATION..... 7

3.1 GENERAL DESCRIPTION OF EUT..... 7

3.2 DESCRIPTION OF TEST MODES..... 7

 3.2.1. CONFIGURATION OF SYSTEM UNDER TEST 9

 3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL..... 9

3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS..... 11

3.4 DESCRIPTION OF SUPPORT UNITS..... 11

4 TEST TYPES AND RESULTS 12

4.1. CONDUCTED EMISSION MEASUREMENT 12

 4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT 12

 4.1.2 TEST INSTRUMENTS..... 12

 4.1.3 TEST PROCEDURES 13

 4.1.4 DEVIATION FROM TEST STANDARD 13

 4.1.5 TEST SETUP..... 14

 4.1.6 EUT OPERATING CONDITIONS 14

 4.1.7 TEST RESULTS..... 15

4.2. RADIATED EMISSION AND BANDEDGE MEASUREMENT 17

 4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT 17

 4.2.2 TEST INSTRUMENTS..... 18

 4.2.3 TEST PROCEDURES..... 19

 4.2.4 DEVIATION FROM TEST STANDARD..... 20

 4.2.5 TEST SETUP..... 20

 4.2.6 EUT OPERATING CONDITIONS 20

 4.2.7 TEST RESULTS..... 21

4.3. NUMBER OF HOPPING FREQUENCY USED..... 21

 4.3.1. LIMIT OF HOPPING FREQUENCY USED 29

 4.3.2. TEST SETUP..... 29

 4.3.3. TEST INSTRUMENTS..... 29

 4.3.4. TEST PROCEDURES 30

 4.3.5. DEVIATION FROM TEST STANDARD 30

 4.3.6. TEST RESULTS..... 30

4.4. DWELL TIME ON EACH CHANNEL 33



4.4.1 LIMIT OF DWELL TIME USED 33

4.4.2 TEST SETUP 33

4.4.3 TEST INSTRUMENTS 33

4.4.4 TEST PROCEDURES..... 33

4.4.5 DEVIATION FROM TEST STANDARD..... 34

4.4.6 TEST RESULTS..... 34

4.5. CHANNEL BANDWIDTH..... 37

4.5.1 LIMITS OF CHANNEL BANDWIDTH..... 37

4.5.2 TEST SETUP 37

4.5.3 TEST INSTRUMENTS 37

4.5.4 TEST PROCEDURE 37

4.5.5 DEVIATION FROM TEST STANDARD..... 37

4.5.6 EUT OPERATING CONDITION..... 37

4.5.7 TEST RESULTS..... 38

4.6. HOPPING CHANNEL SEPARATION 42

4.6.1. LIMIT OF HOPPING CHANNEL SEPARATION 42

4.6.2. TEST SETUP 42

4.6.3. TEST INSTRUMENTS..... 42

4.6.4. TEST PROCEDURES 42

4.6.5. DEVIATION FROM TEST STANDARD 42

4.6.6. TEST RESULTS..... 43

4.7. MAXIMUM OUTPUT POWER..... 47

4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT..... 47

4.7.2 TEST SETUP 47

4.7.3 TEST INSTRUMENTS 47

4.7.4 TEST PROCEDURES..... 47

4.7.5 DEVIATION FROM TEST STANDARD..... 47

4.7.6 EUT OPERATING CONDITION..... 47

4.7.7 TEST RESULTS..... 48

4.8. OUT OF BAND EMISSION MEASUREMENT 49

4.8.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT 49

4.8.2 TEST INSTRUMENTS..... 49

4.8.3 TEST PROCEDURE 49

4.8.4 DEVIATION FROM TEST STANDARD..... 49

4.8.5 EUT OPERATING CONDITION..... 49

4.8.6 TEST RESULTS..... 49

5. PHOTOGRAPHS OF THE TEST CONFIGURATION 52



**BUREAU
VERITAS**

Test Report No.: RF160202N044

**6. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE
EUT BY THE LAB..... 53**



**BUREAU
VERITAS**

Test Report No.: RF160202N044

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
RF160202N044	Original release	Feb. 29, 2016



1 SUMMARY OF TEST RESULTS

The EUT has been tested according to the following specifications:

APPLIED STANDARD: FCC Part 15, Subpart C			
STANDARD SECTION	TEST TYPE AND LIMIT	RESULT	REMARK
15.207	AC Power Conducted Emission	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Number of Hopping Frequency Used	PASS	Meet the requirement of limit.
15.247(a)(1)(iii)	Dwell Time on Each Channel	PASS	Meet the requirement of limit.
15.247(a)(1)	1. Hopping Channel Separation 2. Spectrum Bandwidth of a Frequency Hopping Sequence Spread Spectrum System	PASS	Meet the requirement of limit.
15.247(b)	Maximum Peak Output Power	PASS	Meet the requirement of limit.
15.247(d)&15.209	Transmitter Radiated Emission	PASS	Meet the requirement of limit.
15.247(d)	Out of band Emission Measurement	PASS	Meet the requirement of limit.
15.203	Antenna Requirement	PASS	No antenna connector is used.

2 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

MEASUREMENT	FREQUENCY	UNCERTAINTY
Conducted emissions	9kHz~30MHz	2.70dB
Radiated emissions	9KHz ~ 30MHz	2.90dB
	30MHz ~ 1GMHz	3.67dB
	1GHz ~ 18GHz	4.84dB
	18GHz ~ 40GHz	4.84dB

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.



3 GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

PRODUCT	BRIGHT TUNES
MODEL NO.	BRT-150-GA-80
ADDITIONAL MODELS	BRT-150-xy-z, BRT-250-xy-z, BRT-100-BCC-25, BRT-100-BW-20, BRT-100-BX-20, BRT-100-GA-80, BRT-100-GD-80, BRT-100-GF-80, BRT-100-WA-80, BRT-100-WU-20, BRT-200-GG-80, BRT-200-GI-80, BRT-100-xy-z, BRT-200-xy-z
FCC ID	ZXNLEETACEZ400
POWER SUPPLY	AC 120V 60Hz
MODULATION TECHNOLOGY	FHSS
MODULATION TYPE	GFSK, 8DPSK, $\pi/4$ DQPSK
OPERATING FREQUENCY	2402MHz~2480MHz
NUMBER OF CHANNEL	79
MAX. OUTPUT POWER	0.9616mW (Max. Measured)
ANTENNA TYPE	Integral PCB Antenna, 0dBi Gain
I/O PORTS	Refer to user's manual
CABLE SUPPLIED	N/A

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.
- Please refer to the EUT photo document (Reference No.: 151013N001) for detailed product photo.

Remarks:

- Basic model: BRT-150-GA-80
- Alternative model: BRT-150-xy-z, BRT-250-xy-z, BRT-100-BCC-25, BRT-100-BW-20, BRT-100-BX-20, BRT-100-GA-80, BRT-100-GD-80, BRT-100-GF-80, BRT-100-WA-80, BRT-100-WU-20, BRT-200-GG-80, BRT-200-GI-80, BRT-100-xy-z, BRT-200-xy-z (x can be replaced by digit 0-1 or letter A-Z indicate the color of the light string; y can be replaced by 1 or 2 letter indicate the color and shape of the lamps or lamp shade; z can be replaced by 2 or 3 digit indicate the numbers of lamps;)
- Innovative Technology and Victrola can be used for all the models.



3.2 DESCRIPTION OF TEST MODES

79 channels are provided to this EUT:

CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)	CHANNEL	FREQ. (MHz)
0	2402	20	2422	40	2442	60	2462
1	2403	21	2423	41	2443	61	2463
2	2404	22	2424	42	2444	62	2464
3	2405	23	2425	43	2445	63	2465
4	2406	24	2426	44	2446	64	2466
5	2407	25	2427	45	2447	65	2467
6	2408	26	2428	46	2448	66	2468
7	2409	27	2429	47	2449	67	2469
8	2410	28	2430	48	2450	68	2470
9	2411	29	2431	49	2451	69	2471
10	2412	30	2432	50	2452	70	2472
11	2413	31	2433	51	2453	71	2473
12	2414	32	2434	52	2454	72	2474
13	2415	33	2435	53	2455	73	2475
14	2416	34	2436	54	2456	74	2476
15	2417	35	2437	55	2457	75	2477
16	2418	36	2438	56	2458	76	2478
17	2419	37	2439	57	2459	77	2479
18	2420	38	2440	58	2460	78	2480
19	2421	39	2441	59	2461		



3.2.1. CONFIGURATION OF SYSTEM UNDER TEST

Please see section 5 photograph of the test configuration for reference.

3.2.2. TEST MODE APPLICABILITY AND TESTED CHANNEL DETAIL

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates, XYZ axis and antenna ports

The worst case was found when positioned on X axis for radiated emission.

Following channel(s) was (were) selected for the final test as listed below:

EUT CONFIGURE MODE	APPLICABLE TO				DESCRIPTION
	RE<1G	RE≥1G	PLC	APCM	
A	√	√	√	√	Powered By AC 120V

Where **RE<1G**: Radiated Emission below 1GHz
PLC: Power Line Conducted Emission

RE≥1G: Radiated Emission above 1GHz
APCM: Antenna Port Conducted Measurement

RADIATED EMISSION TEST (BELOW 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	39	FHSS	GFSK	DH5

For the test results, only the worst case was shown in test report.

RADIATED EMISSION TEST (ABOVE 1 GHz):

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, XYZ axis, antenna ports (if EUT with antenna diversity architecture) and packet type.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5



POWER LINE CONDUCTED EMISSION TEST:

- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

EUT CONFIGURE MODE	AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
A	0 to 78	39	FHSS	GFSK	DH5

ANTENNA PORT CONDUCTED MEASUREMENT:

- This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, antenna ports (if EUT with antenna diversity architecture), and packet types.
- Following channel(s) was (were) selected for the final test as listed below.

AVAILABLE CHANNEL	TESTED CHANNEL	MODULATION TECHNOLOGY	MODULATION TYPE	PACKET TYPE
0 to 78	0, 39, 78	FHSS	GFSK	DH5
0 to 78	0, 39, 78	FHSS	8DPSK	DH5

TEST CONDITION:

APPLICABLE TO	ENVIRONMENTAL CONDITIONS	TEST VOLTAGE (SYSTEM)	TESTED BY
RE<1G	24deg. C, 56%RH	AC 120V 60Hz	Sen He
RE≥1G	24deg. C, 56%RH	AC 120V 60Hz	Sen He
PLC	20deg. C, 56%RH	AC 120V 60Hz	Sen He
APCM	20deg. C, 55%RH	AC 120V 60Hz	Blue Zheng



3.3 GENERAL DESCRIPTION OF APPLIED STANDARDS

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

FCC Part 15, Subpart C. Section 15.247
ANSI C63.10-2013

All test items have been performed and recorded as per the above standards.

3.4 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

NO.	PRODUCT	BRAND	MODEL NO.	SERIAL NO.	FCC ID
1	N/A	N/A	N/A	N/A	N/A

NO.	SIGNAL CABLE DESCRIPTION OF THE ABOVE SUPPORT UNITS
1	N/A



4 TEST TYPES AND RESULTS

4.1. CONDUCTED EMISSION MEASUREMENT

4.1.1 LIMITS OF CONDUCTED EMISSION MEASUREMENT

FREQUENCY OF EMISSION (MHz)	CONDUCTED LIMIT (dBµV)	
	Quasi-peak	Average
0.15 ~ 0.5	66 to 56	56 to 46
0.5 ~ 5	56	46
5 ~ 30	60	50

- NOTE:**
1. The lower limit shall apply at the transition frequencies.
 2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.
 3. All emanations from a class A/B digital device or system, including any network of conductors and apparatus connected thereto, shall not exceed the level of field strengths specified above.

4.1.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESCI	100962	Mar. 05,15	Mar. 04,16
Artificial Mains Network	Rohde&Schwarz	ENV216	101173	Apr. 25,15	Apr. 24,16
Artificial Mains Network	Rohde&Schwarz	ESH3-Z5	100317	Apr. 25,15	Apr. 24,16
Voltage probe	SCHWARZBECK	TK 9421	TK 9421-176	Jan. 08,16	Jan. 07,17
Test software	ADT	ADT_Cond_V7.3.7	N/A	N/A	N/A

- NOTE:**
1. The test was performed in shielded room 553.
 2. The calibration interval of the above test instruments is 12 months. And the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



4.1.3 TEST PROCEDURES

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.


NOTE: All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 DEVIATION FROM TEST STANDARD

No deviation.



4.1.5 TEST SETUP



- Note:**
- 1.Support units were connected to second LISN.
 - 2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT OPERATING CONDITIONS

- a. Turned on the power and connected of all equipment.
- b. EUT was operated according to the type used was description in manufacturer's specifications or the User's Manual.




4.1.7 TEST RESULTS

CONDUCTED WORST-CASE DATA: GFSK CH39

PHASE	Line	6dB BANDWIDTH	9kHz
-------	------	---------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.25156	9.72	40.02	20.55	49.74	30.27	61.71	51.71	-11.97	-21.44
2	0.34531	9.74	42.66	22.62	52.40	32.36	59.07	49.07	-6.68	-16.72
3	0.40000	9.76	42.99	19.30	52.75	29.06	57.85	47.85	-5.10	-18.79
4	0.51328	9.78	40.53	17.09	50.31	26.87	56.00	46.00	-5.69	-19.13
5	0.81797	9.75	34.35	16.15	44.10	25.90	56.00	46.00	-11.90	-20.10
6	1.42578	9.74	37.52	15.25	47.26	24.99	56.00	46.00	-8.74	-21.01

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.






PHASE	Neutral	6dB BANDWIDTH	9kHz
--------------	---------	----------------------	------

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.33750	9.52	41.56	19.60	51.08	29.12	59.26	49.26	-8.18	-20.14
2	0.39609	9.54	42.69	23.22	52.23	32.76	57.93	47.93	-5.71	-15.18
3	0.45469	9.55	43.54	21.25	53.09	30.80	56.79	46.79	-3.70	-15.99
4	0.48203	9.55	41.34	19.11	50.89	28.66	56.30	46.30	-5.42	-17.65
5	1.75781	9.66	34.77	11.57	44.43	21.23	56.00	46.00	-11.57	-24.77
6	4.89063	9.74	33.74	26.10	43.48	35.84	56.00	46.00	-12.52	-10.16

- REMARKS:**
1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
 2. "-": The Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
 3. The emission levels of other frequencies were very low against the limit.
 4. Margin value = Emission level - Limit value
 5. Correction factor = Insertion loss + Cable loss
 6. Emission Level = Correction Factor + Reading Value.





4.2. RADIATED EMISSION AND BANDEDGE MEASUREMENT

4.2.1 LIMITS OF RADIATED EMISSION AND BANDEDGE MEASUREMENT

Radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a). Other emissions shall be at least 20dB below the highest level of the desired power.

FREQUENCIES (MHz)	FIELD STRENGTH (microvolts/meter)	MEASUREMENT DISTANCE (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. As shown in 15.35(b), for frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.



4.2.2 TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
EMI Test Receiver	Rohde&Schwarz	ESR7	101494	Apr. 27,15	Apr. 26,16
Signal and Spectrum Analyzer	Rohde&Schwarz	FSV40	101094	Apr. 23,15	Apr. 22,16
Bilog Antenna	Teseq	CBL 6111D	30643	Jul. 16, 15	Jul. 15, 16
Horn Antenna	ETS-Lindgren	3117	00062558	May 30,14	May 29,16
GPS Generator+ Antenna	TOJOIN	GNSS-5000A	E1-010119	Aug. 08, 14	Aug. 07, 16
3m Semi-anechoic Chamber	ETS-LINDGREN	9m*6m*6m	NSEMC003	Apr. 19,14	Apr. 18,16
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
Horn Antenna (15GHz-40GHz)	SCHWARZBECK	BBHA 9170	BBHA9170147	Jan. 21,14	Jan. 20,17
Amplifier (9kHz-1GHz)	SONOMA	310D	186955	Mar. 04,15	Mar. 03, 16
Pre-Amplifier(1-18G)	HP	8449B	3008A00409	Apr. 25,15	Apr. 24,16
Pre-Amplifier (18GHz-40GHz)	EMCI	EMC 184045	980102	Nov. 20,15	Nov. 19,16
Test Software	ADT	ADT_Radiated_V7.6.15.9.2	N/A	N/A	N/A
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Sep. 01,15	Aug. 31,16

NOTE:

1. The test was performed in 966 Chamber.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.
3. The horn antenna is used only for the measurement of emission frequency above 1GHz if tested.
4. The FCC Site Registration No. is 494399.



4.2.3 TEST PROCEDURES

- a. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. During the test, each emission was maximized by: having the EUT continuously working, investigated all operating modes, rotated about all 3 axis (X, Y & Z) and considered typical configuration to obtain worst position, manipulating interconnecting cables, For battery operated equipment, the equipment tests shall be perform using fresh batteries. The turntable was rotated to maximize the emission level.

NOTE:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and video bandwidth is 3MHz for Peak detection at frequency above 1GHz.
3. Bluetooth duty factor correction is not correct as it is based on 79 channels, worst case would be with AFH enabled and device using the minimum of 20 channels. Channel hop rate = 800 hops/second (AFH Mode), Adjusted channel hop rate for DH5 mode = 133.33 hops/second, Time per channel hop = $1 / 133.33$ hops/second = 7.5 ms, Time to cycle through all channels = 7.5×20 channels = 150 ms, Number of times transmitter hits on one channel = $100 \text{ ms} / 150 \text{ ms} = 1$ time(s), Worst case dwell time = 7.5 ms, Duty cycle connection factor = $20 \log_{10}(7.5 \text{ms} / 100 \text{ms}) = -22.5 \text{ dB}$. Average value = peak reading + 20log(duty cycle).
4. All modes of operation were investigated and the worst-case emissions are reported.
5. The testing of the EUT was performed on all 3 orthogonal axes; the worst-case test configuration was reported on the file test setup photo.



4.2.4 DEVIATION FROM TEST STANDARD

No deviation.

4.2.5 TEST SETUP



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT OPERATING CONDITIONS

- Set the EUT under full load condition and placed them on a testing table.
- Set the transmitter part of EUT under transmission condition continuously at specific channel frequency.
- The necessary accessories enable the EUT in full functions.



4.2.7 TEST RESULTS

BELOW 1GHz WORST-CASE DATA:


GFSK DH5

CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	199.17	35.50	43.50	-8.00	100	0	56.10	-20.60
2	228.40	36.10	46.00	-9.90	100	0	54.70	-18.60
3	304.71	37.10	46.00	-8.90	100	0	51.60	-14.50
4	379.28	33.90	46.00	-12.10	100	0	45.90	-12.00
5	609.27	32.00	46.00	-14.00	100	0	37.50	-5.50
6	758.62	36.20	46.00	-9.80	100	0	38.60	-2.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.






CHANNEL	Channel 39	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	30MHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (cm)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	199.17	35.50	43.50	-8.00	100	0	56.10	-20.60
2	228.40	36.10	46.00	-9.90	100	0	54.70	-18.60
3	304.71	37.10	46.00	-8.90	100	0	51.60	-14.50
4	379.28	33.90	46.00	-12.10	100	0	45.90	-12.00
5	456.94	34.40	46.00	-11.60	100	0	43.70	-9.30
6	758.62	36.20	46.00	-9.80	100	0	38.60	-2.40

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.





ABOVE 1GHz DATA

BT_GFSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	46.6 PK	74.0	-27.4	1.36 H	164	42.90	3.70
2	2390.00	24.1 AV	54.0	-29.9	1.36 H	164	20.40	3.70
3	*2402.00	80.5 PK			1.36 H	164	76.80	3.70
4	*2402.00	58.0 AV			1.36 H	164	54.30	3.70
5	4804.00	49.6 PK	74.0	-24.4	1.04 H	209	41.20	8.40
6	4804.00	27.1 AV	54.0	-26.9	1.04 H	209	18.70	8.40
7	#7206.00	55.9 PK	60.5	-4.6	1.01 H	188	44.20	11.70
8	#7206.00	33.4 AV	38.0	-4.6	1.01 H	188	21.70	11.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	46.9 PK	74.0	-27.1	1.12 V	44	43.20	3.70
2	2390.00	24.4 AV	54.0	-29.6	1.12 V	44	20.70	3.70
3	*2402.00	80.6 PK			1.12 V	44	76.90	3.70
4	*2402.00	58.1 AV			1.12 V	44	54.40	3.70
5	4804.00	48.8 PK	74.0	-25.2	1.02 V	215	40.40	8.40
6	4804.00	26.3 AV	54.0	-27.7	1.02 V	215	17.90	8.40
7	#7206.00	56.5 PK	60.6	-4.1	1.04 V	233	44.80	11.70
8	#7206.00	34.0 AV	38.1	-4.1	1.04 V	233	22.30	11.70

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	81.7 PK			1.04 H	216	77.90	3.80
2	*2441.00	59.2 AV			1.04 H	216	55.40	3.80
3	4882.00	48.8 PK	74.0	-25.2	1.00 H	161	40.30	8.50
4	4882.00	26.3 AV	54.0	-27.7	1.00 H	161	17.80	8.50
5	7323.00	55.8 PK	74.0	-18.2	1.02 H	214	44.20	11.60
6	7323.00	33.3 AV	54.0	-20.7	1.02 H	214	21.70	11.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	82.6 PK			1.87 V	49	78.80	3.80
2	*2441.00	60.1 AV			1.87 V	49	56.30	3.80
3	4882.00	49.8 PK	74.0	-24.2	1.01 V	66	41.30	8.50
4	4882.00	27.3 AV	54.0	-26.7	1.01 V	66	18.80	8.50
5	7323.00	56.7 PK	74.0	-17.3	1.08 V	46	45.10	11.60
6	7323.00	34.2 AV	54.0	-19.8	1.08 V	46	22.60	11.60

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	83.9 PK			1.67 H	331	79.80	4.10
2	*2480.00	61.4 AV			1.67 H	331	57.30	4.10
3	2483.50	57.7 PK	74.0	-16.3	1.67 H	331	53.60	4.10
4	2483.50	35.2 AV	54.0	-18.8	1.67 H	331	31.10	4.10
5	4960.00	50.7 PK	74.0	-23.3	1.01 H	136	42.10	8.60
6	4960.00	28.2 AV	54.0	-25.8	1.01 H	136	19.60	8.60
7	7440.00	56.7 PK	74.0	-17.3	1.02 H	216	45.20	11.50
8	7440.00	34.2 AV	54.0	-19.8	1.02 H	216	22.70	11.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	80.8 PK			1.00 V	35	76.70	4.10
2	*2480.00	58.3 AV			1.00 V	35	54.20	4.10
3	2483.50	56.9 PK	74.0	-17.1	1.03 V	102	52.80	4.10
4	2483.50	34.4 AV	54.0	-19.6	1.03 V	102	30.30	4.10
5	4960.00	50.7 PK	74.0	-23.3	1.12 V	228	42.10	8.60
6	4960.00	28.2 AV	54.0	-25.8	1.12 V	228	19.60	8.60
7	7440.00	55.9 PK	74.0	-18.1	1.01 V	194	44.40	11.50
8	7440.00	33.4 AV	54.0	-20.6	1.01 V	194	21.90	11.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



BT_8DPSK

CHANNEL	TX Channel 0	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	46.6 PK	74.0	-27.4	1.37 H	155	42.90	3.70
2	2390.00	24.1 AV	54.0	-29.9	1.37 H	155	20.40	3.70
3	*2402.00	83.6 PK			1.37 H	155	79.90	3.70
4	*2402.00	61.1 AV			1.37 H	155	57.40	3.70
5	4804.00	48.9 PK	74.0	-25.1	1.07 H	231	40.50	8.40
6	4804.00	26.4 AV	54.0	-27.6	1.07 H	231	18.00	8.40
7	#7206.00	55.8 PK	63.6	-7.8	1.01 H	30	44.10	11.70
8	#7206.00	33.3 AV	41.1	-7.8	1.01 H	30	21.60	11.70

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	2390.00	44.8 PK	74.0	-29.2	1.74 V	284	41.10	3.70
2	2390.00	22.3 AV	54.0	-31.7	1.74 V	284	18.60	3.70
3	*2402.00	82.8 PK			1.74 V	284	79.10	3.70
4	*2402.00	60.3 AV			1.74 V	284	56.60	3.70
5	4804.00	49.9 PK	74.0	-24.1	1.00 V	84	41.50	8.40
6	4804.00	27.4 AV	54.0	-26.6	1.00 V	84	19.00	8.40
7	#7206.00	56.7 PK	62.8	-6.1	1.03 V	317	45.00	11.70
8	#7206.00	34.2 AV	40.3	-6.1	1.03 V	317	22.50	11.70

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.



CHANNEL	TX Channel 39	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	82.9 PK			1.46 H	201	79.10	3.80
2	*2441.00	60.4 AV			1.46 H	201	56.60	3.80
3	4882.00	50.6 PK	74.0	-23.4	1.02 H	55	42.10	8.50
4	4882.00	28.1 AV	54.0	-25.9	1.02 H	55	19.60	8.50
5	7323.00	54.7 PK	74.0	-19.3	1.03 H	87	43.10	11.60
6	7323.00	32.2 AV	54.0	-21.8	1.03 H	87	20.60	11.60

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2441.00	81.9 PK			1.03 V	61	78.10	3.80
2	*2441.00	59.4 AV			1.03 V	61	55.60	3.80
3	4882.00	49.6 PK	74.0	-24.4	1.04 V	7	41.10	8.50
4	4882.00	27.1 AV	54.0	-26.9	1.04 V	7	18.60	8.50
5	7323.00	53.6 PK	74.0	-20.4	1.00 V	318	42.00	11.60
6	7323.00	31.1 AV	54.0	-22.9	1.00 V	318	19.50	11.60

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.



CHANNEL	TX Channel 78	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 25GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	82.8 PK			1.42 H	217	78.70	4.10
2	*2480.00	60.3 AV			1.42 H	217	56.20	4.10
3	2483.50	59.9 PK	74.0	-14.1	1.42 H	217	55.80	4.10
4	2483.50	37.4 AV	54.0	-16.6	1.42 H	217	33.30	4.10
5	4960.00	49.6 PK	74.0	-24.4	1.02 H	162	41.00	8.60
6	4960.00	27.1 AV	54.0	-26.9	1.02 H	162	18.50	8.60
7	7440.00	52.6 PK	74.0	-21.4	1.04 H	81	41.10	11.50
8	7440.00	30.1 AV	54.0	-23.9	1.04 H	81	18.60	11.50

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*2480.00	80.7 PK			1.91 V	239	76.60	4.10
2	*2480.00	58.2 AV			1.91 V	239	54.10	4.10
3	2483.50	58.6 PK	74.0	-15.4	1.91 V	239	54.50	4.10
4	2483.50	36.1 AV	54.0	-17.9	1.91 V	239	32.00	4.10
5	4960.00	49.8 PK	74.0	-24.2	1.02 V	10	41.20	8.60
6	4960.00	27.3 AV	54.0	-26.7	1.02 V	10	18.70	8.60
7	7440.00	53.6 PK	74.0	-20.4	1.08 V	117	42.10	11.50
8	7440.00	31.1 AV	54.0	-22.9	1.08 V	117	19.60	11.50

REMARKS:

1. Emission level (dBuV/m) = Raw Value (dBuV) + Correction Factor (dB/m).
2. Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB).
3. The other emission levels were very low against the limit.
4. Margin value = Emission level – Limit value.
5. " * ": Fundamental frequency.




5.1. NUMBER OF HOPPING FREQUENCY USED

5.1.1. LIMIT OF HOPPING FREQUENCY USED

At least 15 channels frequencies, and should be equally spaced.

5.1.2. TEST SETUP



5.1.3. TEST INSTRUMENTS

Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Next Cal.
Power Sensor	Keysight	U2021XA	MY55060016	Feb. 18,16	Feb. 17,17
Power Sensor	Keysight	U2021XA	MY55060018	Feb. 18,16	Feb. 17,17
Digital Multimeter	FLUKE	15B	A1220010DG	Oct. 12, 15	Oct.11, 16
Humid & Temp Programmable Tester	Haida	HD-2257	110807201	Sep.07,15	Sep. 06,16
Oscilloscope	Agilent	DSO9254A	MY51260160	Nov. 28,15	Nov. 27,16
Signal Analyzer	Rohde & Schwarz	FSV7	102331	Nov. 05,15	Nov. 04,16
Signal Generator	Agilent	N5183A	MY50140980	Nov. 05,15	Nov. 04,16
ESG Vector Signal Generator	Agilent	E4438C	MY49072505	Apr. 22, 15	Apr. 21, 16
BLUETOOTH TESTER	Rohde&Schwarz	CBT32	100811	Sep. 01,15	Aug. 31,16

NOTE:

1. The test was performed in RF Oven room.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to CEPREI/CHINA, GRGT/CHINA and NIM/CHINA.



5.1.4. TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Set the SA on MaxHold Mode, and then keep the EUT in hopping mode. Record all the signals from each channel until each one has been recorded.
- d. Set the SA on View mode and then plot the result on SA screen.
- e. Repeat above procedures until all frequencies measured were completed.

5.1.5. DEVIATION FROM TEST STANDARD

No deviation.

5.1.6. TEST RESULTS



There are 79 hopping frequencies in the hopping mode. Please refer to next two pages for the test result. On the plots, it shows that the hopping frequencies are equally spaced.



BUREAU
VERITAS

Test Report No.: RF160202N044

GFSK



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China



Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



**BUREAU
VERITAS**

Test Report No.: RF160202N044

8DPSK



**Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch**

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




5.2. DWELL TIME ON EACH CHANNEL

4.4.1 LIMIT OF DWELL TIME USED

The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

4.4.2 TEST SETUP



4.4.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.4.4 TEST PROCEDURES

- a. Check the calibration of the measuring instrument (SA) using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect its antenna terminal to measurement via a low loss cable. Then set it to any one measured frequency within its operating range and make sure the instrument is operated in its linear range.
- c. Adjust the center frequency of SA on any frequency be measured and set SA to zero span mode. And then, set RBW and VBW of spectrum analyzer to proper value.
- d. Measure the time duration of one transmission on the measured frequency. And then plot the result with time difference of this time duration.
- e. Repeat above procedures until all different time-slot modes have been completed.



4.4.5 DEVIATION FROM TEST STANDARD

No deviation.

4.4.6 TEST RESULTS

GFSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	49	309.68	0.450	139.36	400	PASS
DH3	79	31.6	5	24	151.68	1.740	263.92	400	PASS
DH5	79	31.6	5	17	107.44	2.944	316.30	400	PASS

8DPSK

Mode	Number of Hopping Channel	Number of transmission in a period(channel number*0.4 sec)				Length of transmission time (msec)	Result (msec)	Limit (msec)	PASS / FAIL
		period (sec)	sweep time (sec)	times in a sweep	times in a period				
DH1	79	31.6	5	48	303.36	0.504	152.89	400	PASS
DH3	79	31.6	5	25	158.00	1.710	270.18	400	PASS
DH5	79	31.6	5	16	101.12	2.848	287.99	400	PASS


NOTE: Test plots of the transmitting time slot are shown on next page.



BUREAU VERITAS

Test Report No.: RF160202N044

GFSK




Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



8DPSK






5.3. CHANNEL BANDWIDTH

4.5.1 LIMITS OF CHANNEL BANDWIDTH

For frequency hopping system operating in the 2400-2483.5MHz, If the 20dB bandwidth of hopping channel is greater than 25kHz, two-thirds 20dB bandwidth of hopping channel shall be a minimum limit for the hopping channel separation.

4.5.2 TEST SETUP



4.5.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.5.4 TEST PROCEDURE

- a. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
- b. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
- c. Measure the frequency difference of two frequencies that were attenuated 20dB from the reference level. Record the frequency difference as the emission bandwidth.
- d. Repeat above procedures until all frequencies measured were complete.

4.5.5 DEVIATION FROM TEST STANDARD

No deviation.

4.5.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.




4.5.7 TEST RESULTS

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.05
39	2441	1.10
78	2480	1.10

CH 0






BUREAU VERITAS

Test Report No.: RF160202N044

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	20dB BANDWIDTH (MHz)
0	2402	1.36
39	2441	1.36
78	2480	1.34

CH 0







BUREAU VERITAS

Test Report No.: RF160202N044

CH 39



CH 78



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




5.4. HOPPING CHANNEL SEPARATION

5.4.1. LIMIT OF HOPPING CHANNEL SEPARATION

At least 25kHz or two-third of 20dB hopping channel bandwidth (whichever is greater).

5.4.2. TEST SETUP



5.4.3. TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

5.4.4. TEST PROCEDURES

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range.
3. By using the MaxHold function record the separation of two adjacent channels.
4. Measure the frequency difference of these two adjacent channels by SA MARK function. And then plot the result on SA screen.
5. Repeat above procedures until all frequencies measured were complete.

5.4.5. DEVIATION FROM TEST STANDARD

No deviation.




5.4.6. TEST RESULTS

GFSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.01	1.05	0.700	PASS
39	2441	1.00	1.10	0.733	PASS
78	2480	1.01	1.10	0.733	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0







BUREAU VERITAS

Test Report No.: RF160202N044

CH 39



CH 78



Bureau Veritas Shenzhen Co., Ltd.
Dongguan Branch

No. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, China

Tel: +86 769 8593 5656
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com




8DPSK

CHANNEL	FREQUENCY (MHz)	ADJACENT CHANNEL SEPARATION (MHz)	20dB BANDWIDTH (MHz)	MINIMUM LIMIT (MHz)	PASS / FAIL
0	2402	1.00	1.36	0.907	PASS
39	2441	1.01	1.36	0.907	PASS
78	2480	1.01	1.34	0.893	PASS

NOTE: The minimum limit is two-third 20dB bandwidth.

CH 0







BUREAU VERITAS

Test Report No.: RF160202N044

CH 39



CH 78






5.5. MAXIMUM OUTPUT POWER

4.7.1 LIMITS OF MAXIMUM OUTPUT POWER MEASUREMENT

The Maximum Output Power Measurement is 125mW.

4.7.2 TEST SETUP



4.7.3 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.7.4 TEST PROCEDURES

A peak power sensor was used on the output port of the EUT. A peak power meter was used to read the response of the peak power sensor. Record the peak power level.

4.7.5 DEVIATION FROM TEST STANDARD

No deviation.

4.7.6 EUT OPERATING CONDITION

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.



4.7.7 TEST RESULTS

MAXIMUM PEAK OUTPUT POWER

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PK POWER (dBm)	PK POWER (mW)	PK POWER LIMIT (mW)	PASS/FAIL
0	2402	-0.17	0.9616	125	PASS
39	2441	-0.68	0.8551	125	PASS
78	2480	-1.34	0.7345	125	PASS

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	PK POWER (dBm)	PK POWER (mW)	PK POWER LIMIT (mW)	PASS/FAIL
0	2402	-3.05	0.4955	125	PASS
39	2441	-3.48	0.4487	125	PASS
78	2480	-4.16	0.3837	125	PASS

AVERAGE OUTPUT POWER(FOR REFERENCE)

GFSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	-1.37	0.729
39	2441	-1.83	0.656
78	2480	-2.41	0.574

8DPSK

CHANNEL	CHANNEL FREQUENCY (MHz)	AVERAGE POWER (dBm)	AVERAGE POWER (mW)
0	2402	-5.14	0.306
39	2441	-5.70	0.269
78	2480	-6.33	0.233



5.6. OUT OF BAND EMISSION MEASUREMENT

4.8.1 LIMITS OF OUT OF BAND EMISSION MEASUREMENT

Below -20dB of the highest emission level of operating band (in 100KHz RBW).

4.8.2 TEST INSTRUMENTS

Refer to section 4.3.3 to get information of above instrument.

4.8.3 TEST PROCEDURE

The transmitter output was connected to the spectrum analyzer via a low loss cable. of Spectrum Analyzer was set RBW to 100 kHz and VBW to 300 kHz with suitable frequency span including 100 MHz bandwidth from band edge. Detector = PEAK and Trace mode = Max Hold. The band edges was measured and recorded.

4.8.4 DEVIATION FROM TEST STANDARD

No deviation.

4.8.5 EUT OPERATING CONDITION


The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.8.6 TEST RESULTS

The spectrum plots are attached on the following images. D1 line indicates the highest level. D2 line indicates the 20dB offset below D1. It shows compliance to the requirement.




GFSK





8DPSK





BUREAU Test Report No.: RF160202N044
VERITAS

6. PHOTOGRAPHS OF THE TEST CONFIGURATION

Please refer to the attached file (Test Setup Photo).



BUREAU Test Report No.: RF160202N044
VERITAS

7. APPENDIX A - MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

---END---