



## RF Exposure evaluation

**Report Reference No.....: GTSR18070292-WLAN**

**FCC ID.....: ZXZWF150A**

Compiled by

( position+printed name+signature)..: File administrators Jimmy Wang



Supervised by

( position+printed name+signature)..: Test Engineer Aaron Tan



Approved by

( position+printed name+signature)..: Manager Jason Hu

Date of issue.....: Aug. 01, 2018

**Representative Laboratory Name. : Shenzhen Global Test Service Co.,Ltd.**

Address.....: No.7-101 and 8A-104, Building 7 and 8, DCC Cultural and Creative Garden, No.98, Pingxin North Road, Shangmugu Community, Pinghu Street, Longgang District, Shenzhen, Guangdong

**Applicant's name.....: Dayton Audio Division of Parts Express**

Address.....: 725 Pleasant Valley Drive, Springboro OH 45066

**Test specification.....:**

Standard.....: **FCC 2.1091:2017**

TRF Originator.....: Shenzhen Global Test Service Co.,Ltd.

Master TRF.....: Dated 2014-12

**Shenzhen Global Test Service Co.,Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Global Test Service Co.,Ltd. is acknowledged as copyright owner and source of the material. Shenzhen Global Test Service Co.,Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**Test item description.....: Wi-Fi INTEGRATED AMPLIFIER**

Trade Mark.....: /

Manufacturer.....: Vistron (Dong Guan) Audio Equipment Co.,Ltd

Model/Type reference.....: WF150A

Listed Models .....: /

Difference .....: /

Modulation Type.....: BT:GFSK,PI/4DQPSK,8DPSK;WIFI: 802.11b/802.11g/802.11n

Operation Frequency.....: 2402MHz to 2480MHz

Hardware Version .....: WF150A

Software Version.....: V1.0

Rating.....: AC 110-120V/60Hz 150W

Result.....: **PASS**

**TEST REPORT**

<b>Test Report No. :</b>	<b>GTSR18070292-MPE</b>	Aug. 01, 2018
		Date of issue

Equipment under Test : Wi-Fi INTEGRATED AMPLIFIER

Model /Type : WF150A

Listed Models : /

**Applicant** : **Dayton Audio Division of Parts Express**

Address : 725 Pleasant Valley Drive, Springboro OH 45066

**Manufacturer** : **Vistron (Dong Guan) Audio Equipment Co.,Ltd**

Address : NO.17 Ji Cai Street, Song Gang District, Qing Xi Town, Dong Guan City, Guang Dong Province, China

<b>Test Result:</b>	<b>PASS</b>
---------------------	-------------

The test report merely corresponds to the test sample.  
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

# Contents

- 1. SUMMARY ..... 4**
- 1.1. EUT configuration.....4
- 1.2. Product Description..... 4
- 2. TEST ENVIRONMENT ..... 5**
- 2.1. Address of the test laboratory.....5
- 2.2. Test Facility..... 5
- 2.3. Environmental conditions..... 5
- 2.4. Statement of the measurement uncertainty..... 5
- 3. METHOD OF MEASUREMENT ..... 6**
- 3.1. Applicable Standard.....6
- 3.2. Requirement..... 6
- 3.3. Limit..... 6
- 3.4. MPE Calculation Method..... 7
- 4. EVALUATION RESULT ..... 8**
- 4.1. Standalone MPE..... 8
- 4.2. Simultaneous transmission MPE Considerations..... 9
- 5. CONCLUSION .....9**

## 1. SUMMARY

### 1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

○		Length (m) :	/
		Shield :	/
		Detachable :	/

### 1.2. Product Description

Name of EUT	Wi-Fi INTEGRATED AMPLIFIER
Trade Mark:	/
Model Number	WF150A
Listed Models	/
FCC ID	ZXZWF150A
Modulation Type	BT:GFSK, $\pi$ /4DQPSK,8DPSK IEEE 802.11b: DSSS(CCK,DQPSK,DBPSK) IEEE 802.11g: OFDM(64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n HT20: OFDM (64QAM, 16QAM, QPSK,BPSK)
Operation frequency	BT:2402-2480MHz IEEE 802.11b/g:2412-2462MHz IEEE 802.11n HT20:2412-2462MHz
Antenna Type	BT:External antenna; WIFI 2.4G:External antenna
Antenna gain	BT:1.8dBi; WIFI 2.4G:2dBi

## 2. TEST ENVIRONMENT

### 2.1. Address of the test laboratory

**Shenzhen Global Test Service Co.,Ltd.**

1F, Building No. 13A, Zhonghaixin Science and Technology City, No.12,6 Road, Ganli Industrial Park, Buji Street, Longgang District, Shenzhen, Guangdong

### 2.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

**FCC-Registration No.: 964637**

Shenzhen Global Test Service Co.,Ltd EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 964637, Jul 24, 2015.

**CNAS-Lab Code: L8169**

Shenzhen Global Test Service Co.,Ltd. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories. Date of Registration: Dec. 11, 2015. Valid time is until Dec. 10, 2018.

**A2LA-Lab Cert. No.: 4758.01**

Shenzhen Global Test Service Co.,Ltd. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

### 2.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature:	15-35 ° C
Humidity:	30-60 %
Atmospheric pressure:	950-1050mbar

### 2.4. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Global Test Service Co.,Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen GTS laboratory is reported:

Test Items	Measurement Uncertainty	Notes
Transmitter power conducted	0.57 dB	(1)

- (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 3. Method of measurement

#### 3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB447498 v06: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

#### 3.2. Requirement

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission’s guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

In accordance with KDB447498D01 for Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is  $\leq 1.0$ . The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to MPE limit, at the test frequency. Either the maximum peak or spatially averaged results from measurements or numerical simulations may be used to determine the MPE ratios. Spatial averaging does not apply when MPE is estimated using simple calculations based on far-field plane-wave equivalent conditions. The antenna installation and operating requirements for the host device must meet the minimum test separation distances required by all antennas, in both standalone and simultaneous transmission operations, to satisfy compliance.

#### 3.3. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f <sup>2</sup> )*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm <sup>2</sup> )	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

\*=Plane-wave equivalent power density

### 3.4. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = \frac{PG}{4\pi R^2}$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

As declared by the Applicant, the EUT transmits with the maximum source-based Duty Cycle of 100%-see the User manual, and the EUT is a wireless device used in a mobile application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum mobile separation distance,  $r = 20\text{cm}$ , as well as the gain of the used antenna is 1.06dBi for WLAN, and the power drift from Turn-up Procedure provide by manufacturer as following states, the RF power density can be obtained..

## 4. Evaluation Result

### 4.1. Standalone MPE

#### BT

Freq. (MHz)	Output Power (dBm)	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Output power to antenna (mW)	Ant Gain (dBi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/c m <sup>2</sup> )	Result
GFSK								
2402	3.43	3±1.0	4	2.512	1.8	0.00076	1	Pass
2441	3.18	3±1.0	4	2.512	1.8	0.00076	1	Pass
2480	3.07	3±1.0	4	2.512	1.8	0.00076	1	Pass
Pi/4DQPSK								
2402	1.66	1±1.0	2	1.585	1.8	0.00048	1	Pass
2441	1.29	1±1.0	2	1.585	1.8	0.00048	1	Pass
2480	1.34	1±1.0	2	1.585	1.8	0.00048	1	Pass
8-DPSK								
2402	1.86	1±1.0	2	1.585	1.8	0.00048	1	Pass
2441	1.62	1±1.0	2	1.585	1.8	0.00048	1	Pass
2480	1.07	1±1.0	2	1.585	1.8	0.00048	1	Pass

#### WIFI 2.4GHz

Freq. (MHz)	Output Power (dBm)	Target power W/ tolerance (dBm)	Max tune up power tolerance (dBm)	Output power to antenna (mW)	Ant Gain(d Bi)	Power Density at R=20cm (mW/cm <sup>2</sup> )	Limit (mW/c m <sup>2</sup> )	Result
802.11b								
2412	12.69	13±1.0	14	25.119	2	0.00792	1	Pass
2437	13.57	13±1.0	14	25.119	2	0.00792	1	Pass
2462	13.68	13±1.0	14	25.119	2	0.00792	1	Pass
802.11g								
2412	10.81	10±1.0	11	12.589	2	0.00397	1	Pass
2437	10.94	10±1.0	11	12.589	2	0.00397	1	Pass
2462	10.48	10±1.0	11	12.589	2	0.00397	1	Pass
802.11n(20)								



2412	9.75	10±1.0	11	12.589	2	0.00397	1	Pass
2437	10.49	10±1.0	11	12.589	2	0.00397	1	Pass
2462	10.12	10±1.0	11	12.589	2	0.00397	1	Pass

**4.2. Simultaneous transmission MPE Considerations**

According to KDB447498 :For mobile exposure host platform to qualify for simultaneous transmission MPE test exclusion, all transmitters and antennas in the host must be either evaluated for MPE compliance, by measurement or computational modeling, or qualify for the standalone MPE test exclusion in section 7.1. Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneous transmitting antennas incorporated in a host device, based on the calculated/estimated, numerically modeled or measured field strengths or power density, is  $\leq 1.0$ .

This means that:  
 $\sum$  of MPE ratios  $\leq 1.0$

The EUT is Not Applicable.

**5. Conclusion**

This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment.

.....**End of Report**.....