

Maximum Permissible Exposure report

For

Dayton Audio Division of Parts Express

725 Pleasant Valley Rd Springboro, Ohio 45066 USA

FCC ID:ZXZWFA02

Trade:  DAYTONAUDIO

This Report Concerns: Original Report	Equipment Type: WiFi Multiroom Audio Adapter
Test Engineer:	Lisa Chen <i>Lisa Chen</i>
Report No.:	BSL20151118-5
Receive EUT	November 01, 2015/
Date/Test Date:	November 01- November 18, 2015
Reviewed By:	Mike Moo <i>Mike Moo</i>
Prepared By:	BSL Testing Co.,LTD. NO. 24, ZH Park, Nantou, Shenzhen, 518000 China Tel: 86- 755-26508703 Fax: 86- 755-26508703

1.§ 15.247 (i) and §1.1307 (b) (1) – Maximum Permissible exposure (MPE)

1.1 Standard Applicable

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for General Population/Uncontrolled Exposure				
0.3–3.0	614	1.63	*(100)	30
3.0–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1500	/	/	f/1500	30
1500–100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

1.2 Test Data

Prediction of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S = PG/4\pi R^2$$

S: Power density, in mW/cm²

P: Power input to the antenna, in mW

G: numeric gain of the antenna

R: distance to the center of the antenna, in cm

802.11b Mode

Maximum AV output power at antenna input terminal (dBm):	<u>15.87</u>
Maximum AV output power at antenna input terminal (mW):	<u>38.64</u>
Prediction distance (cm):	<u>20</u>
Prediction frequency (MHz):	<u>2462</u>
Antenna Gain, typical (dBi):	<u>0</u>
Maximum Antenna Gain (numeric):	<u>1</u>
Power density at predication frequency and distance (mW/cm ²):	<u>0.0077</u>
MPE limit for the predication frequency (mW/cm ²):	<u>1.0</u>

802.11g Mode

Maximum AV output power at antenna input terminal (dBm):	<u>14.47</u>
Maximum AV output power at antenna input terminal (mW):	<u>27.99</u>
Prediction distance (cm):	<u>20</u>
Prediction frequency (MHz):	<u>2437</u>
Antenna Gain, typical (dBi):	<u>0</u>
Maximum Antenna Gain (numeric):	<u>1</u>
Power density at predication frequency and distance (mW/cm ²):	<u>0.0056</u>
MPE limit for the predication frequency (mW/cm ²):	<u>1.0</u>

802.11n Mode

Maximum AV output power at antenna input terminal (dBm):	<u>14.08</u>
Maximum AV output power at antenna input terminal (mW):	<u>25.59</u>
Prediction distance (cm):	<u>20</u>
Prediction frequency (MHz):	<u>2462</u>
Antenna Gain, typical (dBi):	<u>0</u>
Maximum Antenna Gain (numeric):	<u>1</u>
Power density at predication frequency and distance (mW/cm ²):	<u>0.0051</u>
MPE limit for the predication frequency (mW/cm ²):	<u>1.0</u>

1.3 Test Result

The device is compliant with the requirement MPE limit of General Population/Uncontrolled Exposure at predication frequency 1.0 mW/cm² .And the precaution is outlined in the user's manual to prevent to high level of RF energy.