



China

## FCC/IC - TEST REPORT

Report Number : **709502115326-00** Date of Issue: February 11, 2022

Model : CM-03-E

Product Type : Tubular motor

Applicant : Coulisse B.V.

Address : Vonderweg 48, 7468 DC Enter, THE NETHERLANDS

Production Facility : Ningbo Dooya Mechanic & Electronic Technology Co., Ltd.  
Address : No.168 Shengguang Road,Luotuo,Zhenhai, Ningbo,

Zhejiang province, People's republic of China

Test Result :  **Positive**       **Negative**

Total pages including Appendices : 46

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.*

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.*



# 1 Table of Contents

1	Table of Contents.....	2
2	Details about the Test Laboratory .....	3
3	Description of the Equipment under Test.....	4
4	Summary of Test Standards .....	6
5	Summary of Test Results .....	7
6	General Remarks.....	8
7	Test Setups .....	9
8	Systems test configuration.....	12
9	Technical Requirement.....	13
9.1	Conducted Emission .....	13
9.2	Conducted peak output power and e.i.r.p.....	16
9.3	6dB bandwidth and 99% Occupied Bandwidth .....	19
9.4	Power spectral density .....	24
9.5	Spurious RF conducted emissions.....	27
9.6	Band edge.....	34
9.7	Spurious radiated emissions for transmitter .....	37
10	Test Equipment List.....	43
11	System Measurement Uncertainty .....	44
12	Photographs of Test Set-ups .....	45
13	Photographs of EUT.....	46



## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch  
No.16 Lane, 1951 Du Hui Road,  
Shanghai 201108,  
P.R. China

Designation  
Number: CN1183

Test Firm FCC  
Registration  
Number: 820234

IC Company  
Number: 25988

CAB identifier: CN0101

Telephone: +86 21 6141 0123  
Fax: +86 21 6140 8600



### 3 Description of the Equipment under Test

#### Description of the Equipment Under Test

Product: Tubular motor

Model no./PMN/HVIN: CM-03-E

FCC ID: ZY4CM03E

IC: 28177-CM03E

Options and accessories: NA

Rating: 5V DC

RF Transmission Frequency: 433.92MHz  
2405~2480 MHz (thread)  
2402~2480 MHz (BLE 5.0)

Modulation: For 433.92MHz: 2GFSK  
For 2.4GHz Thread: OQPSK  
For 2.4GHz BLE: GFSK

Channel list:

Bluetooth Low Energy							
Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)	Ch	Fre(MHz)
0	2402	10	2422	20	2442	30	2462
1	2404	11	2424	21	2444	31	2464
2	2406	12	2426	22	2446	32	2466
3	2408	13	2428	23	2448	33	2468
4	2410	14	2430	24	2450	34	2470
5	2412	15	2432	25	2452	35	2472
6	2414	16	2434	26	2454	36	2474
7	2416	17	2436	27	2456	37	2476
8	2418	18	2438	28	2458	38	2478
9	2420	19	2440	29	2460	39	2480



Thread			
Channel	Frequency	Channel	Frequency
11	2405 MHz	19	2445 MHz
12	2410 MHz	20	2450 MHz
13	2415 MHz	21	2455 MHz
14	2420 MHz	22	2460 MHz
15	2425 MHz	23	2465 MHz
16	2430 MHz	24	2470 MHz
17	2435 MHz	25	2475 MHz
18	2440 MHz	26	2480 MHz

Antenna Type: For 433.92MHz: line antenna  
 For 2.4GHz Thread and BLE: line Antenna

Antenna Gain: For 433.92MHz: -7.16dBi  
 For 2.4GHz Thread and BLE: 3.5dBi

Description of the EUT: The Equipment Under Test (EUT) is a Tubular motor which transmitted at 433.92MHz and support 2.4GHz thread and BLE5.0 (support 1Mbps and 2Mbps data rate). we tested it and listed the worst data in this report.

Test sample no.: SHA-614504-2

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.



#### 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C:2020	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 Amendment 1 March 2019	General Requirements for Compliance of Radio Apparatus
RSS-247 Issue 2 February 2017	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2013).

## 5 Summary of Test Results

Technical Requirements				
Test Condition		Pages	Test Site	Test Result
§15.207 & RSS-GEN 8.8	Conducted emission AC power port	12-14	Site 1	Pass
§15.247 (b) (3) & RSS-247 5.4(d)	Conducted peak output power and e.i.r.p.	15-22	Site 1	Pass
§15.247(a)(1) & RSS-247 5.1(b)	20dB bandwidth	---	---	N/A
§15.247(a)(1) & RSS-247 5.1(b)	Carrier frequency separation	---	---	N/A
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Number of hopping frequencies	---	---	N/A
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Dwell Time	---	---	N/A
§15.247(a)(2) & RSS-247 5.2(a) & RSS-GEN 6.7	6dB bandwidth and 99% Occupied Bandwidth	15-22	Site 1	Pass
§15.247(e) & RSS-247 5.2(b)	Power spectral density	23-25	Site 1	Pass
§15.247(d) & RSS-247 5.5	Spurious RF conducted emissions	26-32	Site 1	Pass
§15.247(d) & RSS-247 5.5	Band edge	33-35	Site 1	Pass
§15.247(d) & §15.209 & RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	36-41	Site 1	Pass
§15.203 & RSS-Gen 6.8	Antenna requirement	See note 1		Pass

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses a line antenna which gain is -7.16dBi for 433.92MHz and 3.5dBi for 2.4GHz thread and BLE. In accordance to §15.203, It is considered sufficiently to comply with the provisions of this section.



## 6 General Remarks

### Remarks

This submittal(s) (test report) is intended for FCC ID: ZY4CM03E, IC: 28177-CM03E, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules and RSS-247, RSS-GEN.

This report is only for the 2.4GHz BLE test report, for the thread test report please refer to 709502115366-00 and the 433.92MHz test report please refer to 709502115362-00.

### SUMMARY:

All tests according to the regulations cited on page 5 were

n - Performed

o - **Not** Performed

The Equipment under Test

n - **Fulfills** the general approval requirements.

o - **Does not** fulfill the general approval requirements.

Sample Received Date: November 19, 2021

Testing Start Date: November 19, 2021

Testing End Date: December 2, 2021

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:

Hui TONG  
Review Engineer


Jiaxi XU  
Project Engineer

Huali CHENG  
Test Engineer




## 7 Test Setups

### 7.1 AC Power Line Conducted Emission test setups




### 7.2 Radiated test setups


#### 9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



18GHz ~ 40GHz Test Setup:



7.3 Conducted RF test setups





## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenove	E470	PF-OU5TS7 17/09

Test software: nRF\_DTM\_x64

The system was configured to channel 0, 19, and 39 for the test.

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.



## 9 Technical Requirement

### 9.1 Conducted Emission

#### Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

#### Limit


According to §15.207, conducted emissions limit as below:

Frequency MHz	QP Limit dBµV	AV Limit dBµV
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency



Product Type : Tubular motor  
 M/N : CM-03-E  
 Operating Condition : Mode 1: Tx\_2402MHz, 2Mbps (worst case)  
 Test Specification : L-line  
 Comment : 5VDC (powered by notebook whose input is 120V~,60Hz)




### Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.154500	45.31	---	65.75	20.44	1000.0	9.000	L1	19.5
0.159000	---	28.46	55.52	27.06	1000.0	9.000	L1	19.5
0.528000	---	27.89	46.00	18.11	1000.0	9.000	L1	19.5
0.528000	35.30	---	56.00	20.70	1000.0	9.000	L1	19.5
2.049000	26.65	---	56.00	29.35	1000.0	9.000	L1	19.5
2.103000	---	22.54	46.00	23.46	1000.0	9.000	L1	19.5
2.197500	28.03	---	56.00	27.97	1000.0	9.000	L1	19.5
2.224500	---	23.66	46.00	22.34	1000.0	9.000	L1	19.5
5.158500	22.20	---	60.00	37.80	1000.0	9.000	L1	19.6
5.158500	---	15.87	50.00	34.13	1000.0	9.000	L1	19.6
13.776000	27.19	---	60.00	32.81	1000.0	9.000	L1	19.7
13.785000	---	21.74	50.00	28.26	1000.0	9.000	L1	19.7

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)  
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator



Product Type : Tubular motor  
 M/N : CM-03-E  
 Operating Condition : Mode 1: Tx\_2402MHz, 2Mbps(worst case)  
 Test Specification : N-line  
 Comment : 5VDC (powered by notebook whose input is 120V~,60Hz)



### Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.159000	---	29.41	55.52	26.11	1000.0	9.000	N	19.5
0.159000	47.01	---	65.52	18.51	1000.0	9.000	N	19.5
0.514500	---	23.00	46.00	23.00	1000.0	9.000	N	19.5
0.523500	34.31	---	56.00	21.69	1000.0	9.000	N	19.5
2.098500	---	19.91	46.00	26.09	1000.0	9.000	N	19.5
2.121000	25.65	---	56.00	30.35	1000.0	9.000	N	19.5
2.481000	29.72	---	56.00	26.28	1000.0	9.000	N	19.5
2.481000	---	24.87	46.00	21.13	1000.0	9.000	N	19.5
11.670000	---	19.99	50.00	30.01	1000.0	9.000	N	19.7
11.692500	25.26	---	60.00	34.74	1000.0	9.000	N	19.7
14.059500	30.43	---	60.00	29.57	1000.0	9.000	N	19.7
14.118000	---	23.50	50.00	26.50	1000.0	9.000	N	19.7

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)  
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator



**9.2 Conducted peak output power and e.i.r.p.**

**Test Method**

1. Use the following spectrum analyzer settings:  
 RBW > the 6 dB bandwidth of the emission being measured, VBW≥3RBW, Span≥3RBW  
 Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Use a power meter to measure the conducted peak output power.

**Limits**

According to §15.247 (b) (1) & RSS-247 5.4(d), conducted peak output power and e.i.r.p. limit as below:

Conducted peak output power		
Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

e.i.r.p.

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤4	≤36

Test result as below table

**1Mbps**

BLE: Antenna gain=3.5dBi				
Frequency	Conducted Peak Output Power	Result	e.i.r.p.	Result
MHz	dBm		dBm	
Low channel 2402MHz	7.09	Pass	10.59	Pass
Middle channel 2440MHz	6.69	Pass	10.19	Pass
High channel 2480MHz	6.08	Pass	9.58	Pass

**2Mbps**

BLE: Antenna gain=3.5dBi				
Frequency	Conducted Peak Output Power	Result	e.i.r.p.	Result
MHz	dBm		dBm	
Low channel 2402MHz	<b>7.10</b>	Pass	<b>10.60</b>	Pass
Middle channel 2440MHz	6.68	Pass	10.18	Pass
High channel 2480MHz	6.08	Pass	9.58	Pass






1Mbps


Peak output power

Channel 0 (2402MHz)




Date: 12 DEC.2021 16:17:01

Channel 19 (2440MHz)



Date: 12 DEC.2021 16:19:08

Channel 39 (2480MHz)



Date: 12 DEC.2021 16:20:46





2Mbps

Peak output power

Channel 0 (2402MHz)


Channel 19 (2440MHz)



Date: 12.DEC.2021 16:22:54

Date: 12.DEC.2021 16:24:49

Channel 39 (2480MHz)



Date: 12.DEC.2021 16:26:27



### 9.3 6dB bandwidth and 99% Occupied Bandwidth

#### Test Method

1. Use the following spectrum analyzer settings:  
RBW=100K, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

#### Limit

Limit [kHz]

≥500

#### Test Method for 99 % Bandwidth

1. Use the following spectrum analyzer settings:  
RBW=1% to 5% of the actual occupied, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

#### Limit

Limit [kHz]

N/A

#### Test result

##### 1Mbps

Frequency MHz	6dB bandwidth kHz	Result	99% occupied bandwidth KHz
Top channel 2402MHz	708	Pass	1051
Middle channel 2440MHz	704	Pass	1050
Bottom channel 2480MHz	706	Pass	1050


##### 2Mbps

Frequency MHz	6dB bandwidth kHz	Result	99% occupied bandwidth KHz
Top channel 2402MHz	1129	Pass	2044
Middle channel 2440MHz	1127	Pass	2046
Bottom channel 2480MHz	1130	Pass	2047




6dB Bandwidth


1Mbps  
2402



2440




2480







2Mbps  
2402



2440



2480






99% Occupied Bandwidth


1Mbps

2402




Date: 12 DEC 2021 16:16:52

2440



Date: 12 DEC 2021 16:16:59


2480



Date: 12 DEC 2021 16:20:37




### 2Mbps 2402




Date: 12 DEC 2021 16:22:46

### 2440



Date: 12 DEC 2021 16:24:40

### 2480



Date: 12 DEC 2021 16:26:18



## 9.4 Power spectral density

### Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.  
RBW=3kHz,VBW≥3RBW,Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

### Limit

Limit [dBm/3kHz]

≤8

### Test result

Frequency MHz	Power spectral density dBm/3KHz	1Mbps	Result
		Data transmission rate	
Top channel 2402MHz	-8.57	1Mbps	Pass
Middle channel 2440MHz	-9.03	1Mbps	Pass
Bottom channel 2480MHz	-9.76	1Mbps	Pass

Frequency MHz	Power spectral density dBm/3KHz	2Mbps	Result
		Data transmission rate	
Top channel 2402MHz	-11.17	1Mbps	Pass
Middle channel 2440MHz	-11.56	1Mbps	Pass
Bottom channel 2480MHz	-12.24	1Mbps	Pass






### Power spectral density


1Mbps

PK PSD





2Mbps  
PK PSD





## 9.5 Spurious RF conducted emissions

### Test Method

1. Establish a reference level by using the following procedure:
  - a. Set RBW=100 kHz. VBW≥3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
  - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
  - a. Set the center frequency and span to encompass frequency range to be measured.
  - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.

### Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20



**Spurious RF conducted emissions**


1Mbps

Out-of-Band Emissions


Channel 0 (2402MHz)

Reference point

Spurious Emission (30MHz – 1GHz)




Date: 12.DEC.2021 16:17:21




Date: 12.DEC.2021 16:17:25

Spurious Emission (1GHz –5GHz)

Spurious Emission (5GHz –26.5GHz)



Date: 12.DEC.2021 16:17:37




Date: 12.DEC.2021 16:18:09




### Out-of-Band Emissions Channel 19 (2440MHz)

#### Reference point




Date: 12.DEC.2021 16:19:18

#### Spurious Emission (30MHz – 1GHz)




Date: 12.DEC.2021 16:19:22

#### Spurious Emission (1GHz –5GHz)



Date: 12.DEC.2021 16:19:35

#### Spurious Emission (5GHz –26.5GHz)




Date: 12.DEC.2021 16:20:06




Out-of-Band Emissions  
Channel 39 (2480MHz)

Reference point




Date: 12.DEC.2021 16:21:05

Spurious Emission (30MHz – 1GHz)




Date: 12.DEC.2021 16:21:10

Spurious Emission (1GHz –5GHz)



Date: 12.DEC.2021 16:21:22

Spurious Emission (5GHz –26.5GHz)




Date: 12.DEC.2021 16:21:53



2Mbps


Out-of-Band Emissions  
Channel 0 (2402MHz)

Reference point




Date: 12 DEC 2021 16:23:14

Spurious Emission (30MHz – 1GHz)




Date: 12 DEC 2021 16:23:19

Spurious Emission (1GHz – 5GHz)



Date: 12 DEC 2021 16:23:31

Spurious Emission (5GHz – 26.5GHz)




Date: 12 DEC 2021 16:24:02




### Out-of-Band Emissions Channel 19 (2440MHz)

#### Reference point




Date: 12.DEC.2021 16:24:59

#### Spurious Emission (30MHz – 1GHz)




Date: 12.DEC.2021 16:25:03

#### Spurious Emission (1GHz –5GHz)



Date: 12.DEC.2021 16:25:15

#### Spurious Emission (5GHz –26.5GHz)




Date: 12.DEC.2021 16:25:47






Out-of-Band Emissions  
Channel 39 (2480MHz)

Reference point




Date: 12.DEC.2021 16:26:47

Spurious Emission (30MHz – 1GHz)




Date: 12.DEC.2021 16:26:51

Spurious Emission (1GHz – 5GHz)



Date: 12.DEC.2021 16:27:03

Spurious Emission (5GHz – 26.5GHz)



Date: 12.DEC.2021 16:27:34

## 9.6 Band edge

### Test Method



- 1 Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section.

### Limit

According to §15.247(d) and RSS-247 5.5, in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a) and RSS-Gen 8.10, must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)) and RSS-Gen.




Test result






BLE\_2M\_Ant1\_Low\_2402



Date: 12.DEC.2021 16:23:09

BLE\_2M\_Ant1\_High\_2480



Date: 12.DEC.2021 16:26:42

## 9.7 Spurious radiated emissions for transmitter

### Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

#### For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious

RBW = 100 kHz to 120 kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious

RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### Procedures for average unwanted emissions measurements above 1000 MHz

a) RBW = 1MHz.

b) VBW ≥ [3 × RBW].

c) Detector = RMS (power averaging), if [span / (# of points in sweep)] ≤ RBW / 2.

Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.

d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)

e) Sweep time = auto.

f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of 1 / D, where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)

g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:



- 1) If power averaging (rms) mode was used in the preceding step e), then the correction factor is  $[10 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.
- 2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is  $[20 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.
- 3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

**Limit**

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 and RSS-GEN 8.10 must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Measured Distance Meters
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30	30	30

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK



**Spurious radiated emissions for transmitter**

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

Pre-scan with three orthogonal axis and worst case as X axis. The only worse case test result is listed in the report.

**Test result**

Test mode: GFSK (1Mbps)					
Channel 0 (2402MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2382.4	43.59	74.00	30.41	Peak	Horizontal
4804.0	42.29	74.00	31.71	Peak	Horizontal
7205.0	48.42	74.00	25.58	Peak	Horizontal
2369.5	42.18	74.00	31.82	Peak	Vertical
5617.8	44.35	74.00	29.65	Peak	Vertical
7205.5	49.93	74.00	24.07	Peak	Vertical

Test mode: GFSK (1Mbps)					
Channel 19 (2440MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
4809.7	41.93	74.00	32.07	Peak	Horizontal
7319.4	52.17	74.00	21.83	Peak	Horizontal
3756.8	45.04	74.00	28.96	Peak	Vertical
7319.4	48.89	74.00	25.11	Peak	Vertical

Test mode: GFSK (1Mbps)					
Channel 39 (2480MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2483.6	42.70	74.00	31.30	Peak	Horizontal
4826.7	42.68	74.00	31.32	Peak	Horizontal
7349.0	47.79	74.00	26.21	Peak	Horizontal
2483.5	43.97	74.00	30.03	Peak	Vertical
7377.2	47.45	74.00	26.55	Peak	Vertical
11397.7	51.76	74.00	22.24	Peak	Vertical



Test mode: GFSK (2Mbps)					
Channel 0 (2402MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2370.6	45.56	74.00	28.44	Peak	Horizontal
2385.5	46.76	74.00	27.24	Peak	Horizontal
7205.0	51.91	74.00	22.09	Peak	Horizontal
2370.1	45.16	74.00	28.84	Peak	Vertical
2385.9	46.05	74.00	27.95	Peak	Vertical
5945.8	46.12	74.00	27.88	Peak	Vertical

Test mode: GFSK (2Mbps)					
Channel 19 (2440MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
7318.3	51.97	74.00	22.03	Peak	Horizontal
6280.2	46.67	74.00	27.33	Peak	Vertical

Test mode: GFSK (2Mbps)					
Channel 39 (2480MHz)					
Frequency (MHz)	Measure Level (dBuV/m)	Limit (dBuV/M)	Margin (dB)	Detector	Polarization
2484.4	54.55	74.00	19.45	Peak	Horizontal
2484.4	42.05	54.00	11.95	AV	Horizontal
7438.4	51.45	74.00	22.55	Peak	Horizontal
2483.5	53.15	74.00	20.85	Peak	Vertical
2483.5	44.30	54.00	9.70	AV	Vertical
7438.4	48.50	74.00	25.50	Peak	Vertical

Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading






The worst case of Radiated Emission below 1GHz:

Site: 3 meter chamber	Time: 2021/11/30 - 13:11
Limit: FCC_Part15.209_RE(3m) Class B	Engineer: Huali CHENG
Probe: VULB9168	Polarity: Horizontal
EUT: Tubular motor, Model no: CM-03-E	Power: 5VDC (powered by notebook whose input is 120V~, 60Hz)
Note: Transmit by at channel 2402MHz, 2Mbps.	
Note: Pre-scan with three orthogonal axis and worst case as X axis	

RE\_VULB9168\_pre\_Cont\_30-1000



Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
120.000000	25.7	1000.0	120.000	100.0	H	59.0	18.1	17.8	43.5
168.000000	29.3	1000.0	120.000	150.0	H	185.0	20.4	14.2	43.5
311.960000	28.4	1000.0	120.000	200.0	H	226.0	21.9	17.6	46.0
360.000000	29.9	1000.0	120.000	200.0	H	321.0	23.0	16.1	46.0
455.960000	28.2	1000.0	120.000	320.0	H	216.0	25.9	17.8	46.0
743.840000	35.7	1000.0	120.000	400.0	H	188.0	31.7	10.3	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.




The worst case of Radiated Emission below 1GHz:

Site: 3 meter chamber	Time: 2021/11/30 - 13:45
Limit: FCC_Part15.209_RE(3m) Class B	Engineer ChengG
Probe: VULB9168	Polarity: Vertical
EUT: Tubular motor, Model no: CM-03-E	Power: 5VDC (powered by notebook whose input is 120V~, 60Hz)
Note: Transmit by at channel 2402MHz, 2Mbps.	
Note: Pre-scan with three orthogonal axis and worst case as X axis	

Level in dBuV/m

RE\_VULB9168\_pre\_Cont\_30-1000



Result Table Single

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
119.960000	25.1	1000.0	120.000	100.0	V	135.0	18.1	18.40	43.5
168.000000	26.5	1000.0	120.000	150.0	V	158.0	20.4	17.00	43.5
360.000000	27.2	1000.0	120.000	200.0	V	226.0	23.0	18.80	46.0
456.040000	32.9	1000.0	120.000	200.0	V	312.0	25.9	13.10	46.0
600.040000	32.3	1000.0	120.000	350.0	V	109.0	29.1	13.70	46.0
827.160000	33.0	1000.0	120.000	400.0	V	359.0	32.4	13.00	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.



## 10 Test Equipment List

List of Test Instruments  
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101091	2021-8-2	2022-8-1
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2021-8-2	2022-8-1
	Signal and Spectrum Analyzer	Rohde & Schwarz	FSV40	101091	2021-8-2	2022-8-1
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2019-3-16	2022-3-15
	Horn Antenna	Rohde & Schwarz	HF907	102393	2021-3-15	2024-3-14
	Pre-amplifier	Rohde & Schwarz	SCU-18D	19006451	2021-8-2	2022-8-1
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2021-5-21	2022-5-20
	DOUBLE-RIDGED WAVEGUIDE HORN WITH PRE-AMPLIFIER (18 GHZ - 40 GHZ)	ETS-Lindgren	3116C-PA	002222727	2020-9-23	2023-9-22
3m Semi-anechoic chamber	TDK	9X6X6	----	2021-5-8	2024-5-7	

Measurement Software Information			
Test Item	Software	Manufacturer	Version
C	Bluetooth and WiFi Test System	Shenzhen JS tonskend co.,ltd	2.6.77.0518
RE	EMC 32	Rohde & Schwarz	V9.15.00
CE	EMC 32	Rohde & Schwarz	V9.15.03

**C - Conducted RF tests**

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density\*
- Spurious RF conducted emissions
- Band edge



## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Radiated Disturbance	30MHz to 1GHz, $\pm 5.03\text{dB}$ (Horizontal) $\pm 5.12\text{dB}$ (Vertical) 1GHz to 18GHz, $\pm 5.49\text{dB}$ 18GHz to 40GHz, $\pm 5.63\text{dB}$
Carrier power conducted measurement	50MHz~18GHz, $\pm 1.238\text{dB}$
Spurious Emission Conducted Measurement	9kHz ~40GHz, $\pm 1.224\text{dB}$

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2007, clause 4.4.3 and 4.5.1.



## 12 Photographs of Test Set-ups

Refer to the < Test Setup photos >.



## 13 Photographs of EUT

Refer to the < External Photos > & < Internal Photos >.

---

THE END