



China

## FCC/IC - TEST REPORT

Report Number : **709502228931-00C** Date of Issue: March 28, 2023

Model : CM-08-E

Product Type : HONEYCOMB MOTOR

Applicant : Coulisse B.V.

Address : Vonderweg 48, 7468 DC Enter, THE NETHERLANDS

Production Facility : Ningbo Dooya Mechanic & Electronic Technology Co., Ltd.

Address : No.168 Shengguang Road, Luotuo, Zhenhai 315202 Ningbo,  
Zhejiang province People's Republic of China

Test Result :  **Positive**       **Negative**

Total pages including  
Appendices : 38

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch is a subcontractor to TÜV SÜD Product Service GmbH according to the principles outlined in ISO 17025.*

*TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch reports apply only to the specific samples tested under stated test conditions. Construction of the actual test samples has been documented. It is the manufacturer's responsibility to assure that additional production units of this model are manufactured with identical electrical and mechanical components. The manufacturer/importer is responsible to the Competent Authorities in Europe for any modifications made to the production units which result in non-compliance to the relevant regulations. TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch shall have no liability for any deductions, inferences or generalizations drawn by the client or others from TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch issued reports.*

*This report is the confidential property of the client. As a mutual protection to our clients, the public and ourselves, extracts from the test report shall not be reproduced except in full without our written approval.*



## 1 Table of Contents

1	Table of Contents .....	2
2	Details about the Test Laboratory.....	3
3	Description of the Equipment under Test.....	4
4	Summary of Test Standards .....	6
5	Summary of Test Results .....	7
6	General Remarks .....	8
7	Test Setups .....	9
8	Systems test configuration .....	12
9	Technical Requirement.....	13
9.1	Conducted Emission.....	13
9.2	Conducted peak output power .....	16
9.3	6dB bandwidth and 99% Occupied Bandwidth .....	18
9.4	Power spectral density.....	21
9.5	Spurious RF conducted emissions .....	23
9.6	Band edge .....	27
9.7	Spurious radiated emissions for transmitter.....	30
10	Test Equipment List.....	35
11	System Measurement Uncertainty.....	36
12	Photographs of Test Set-ups.....	37
13	Photographs of EUT .....	38



## 2 Details about the Test Laboratory

### Details about the Test Laboratory

#### Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch  
No.16 Lane, 1951 Du Hui Road,  
Shanghai 201108,  
P.R. China

Test Firm FCC Registration  
Number: 820234  
Designation Number:  
CN1183

Test Firm IC Registration  
Number: 25988  
CAB identifier: CN0101

Telephone: +86 21 6141 0123  
Fax: +86 21 6140 8600



### 3 Description of the Equipment under Test

#### Description of the Equipment Under Test

Product: HONEYCOMB MOTOR

Model no.: CM-08-E

PMN: CM-08-E

HVIN: CM-08-E

FCC ID: ZY4CM08E

IC: 28177-CM08E

Options and accessories: NA

Rating: DC 12V

RF Transmission Frequency: 2402~2480 MHz for BLE  
2405~2480 MHz for Thread  
433.92 MHz for SRD

No. of Operated Channel: 40 for BLE  
16 for Thread  
1 for SRD

Modulation: GFSK for BLE  
16-ary orthogonal modulation, O-QPSK PHY for Thread  
2GFSK for SRD

Data transmission rate: 1 Mbit/s for BLE

Channel list for Thread:

Operation Frequency each of channel			
Channel	Frequency	Channel	Frequency
11	2405 MHz	19	2445 MHz
12	2410 MHz	20	2450 MHz
13	2415 MHz	21	2455 MHz
14	2420 MHz	22	2460 MHz
15	2425 MHz	23	2465 MHz
16	2430 MHz	24	2470 MHz
17	2435 MHz	25	2475 MHz
18	2440 MHz	26	2480 MHz

Antenna Type: Line Antenna



China

Antenna Gain: 2.2 dBi for BLE and Thread

Description of the EUT: The Equipment Under Test (EUT) is a HONEYCOMB MOTOR with BLE, Thread and SRD function. We tested it and listed the worst data in this report.

Test sample no.: SHA-692942-2

The sample's mentioned in this report is/are submitted/ supplied/ manufactured by client. The laboratory therefore assumes no responsibility for accuracy of information on the brand name, model number, origin of manufacture, consignment, antenna gain or any information supplied.



## 4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators
RSS-Gen Issue 5 Amendment 2 February 2021	General Requirements for the Certification of Radio Apparatus
RSS-247 Issue 2 February 2017	Digital Transmission Systems (DTSS), Frequency Hopping Systems (FHSS) and License-Exempt Local Area Network (LE-LAN) Devices

All the test methods were according to KDB 558074 D01 15.247 Meas Guidance v05r02 and ANSI C63.10 (2013).

## 5 Summary of Test Results

Technical Requirements						
FCC Part 15 Subpart C						
Test Condition	Pages	Test Site	Test Result			
			Pass	Fail	N/A	
§15.207 & RSS-GEN 8.8	Conducted emission AC power port	13-15	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247 (b) (3) & RSS-247 5.4(d)	Conducted peak output power	16-17	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(a)(1) & RSS-247 5.1(b)	20dB bandwidth	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1) & RSS-247 5.1(b)	Carrier frequency separation	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Number of hopping frequencies	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(1)(iii) & RSS-247 5.1(d)	Dwell Time	---	---	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>
§15.247(a)(2) & RSS-247 5.2(a) & RSSGEN 6.7	6dB bandwidth and 99% Occupied Bandwidth	18-20	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(e) & RSS-247 5.2(b)	Power spectral density	21-22	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & RSS-247 5.5	Spurious RF conducted emissions	23-26	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & RSS-247 5.5	Band edge	27-29	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.247(d) & §15.209 & RSS-247 5.5 & RSS-Gen 6.13	Spurious radiated emissions for transmitter	30-34	Site 1	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
§15.203 & RSS-Gen 6.8	Antenna requirement	See note 1		<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>

Remark 1: N/A – Not Applicable.

Note 1: The EUT uses a Line Antenna, which gain is 2.2dBi. In accordance to §15.203 and RSS-Gen 6.8, It is considered sufficiently to comply with the provisions of this section.

## 6 General Remarks

### Remarks

This submittal(s) (test report) is intended for FCC ID: ZY4CM08E, IC: 28177-CM08E, complies with Section 15.207, 15.209, 15.247 of the FCC Part 15, Subpart C Rules and RSS-247, RSS-GEN.

This report is only for 2.4G Thread, for the 2.4GHz BLE test report please refer to 709502228931-00A, for the 433.92MHz SRD test report please refer to 709502228931-00B.

### SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.

Sample Received Date: January 31, 2023

Testing Start Date: January 31, 2023


Testing End Date: March 14, 2023

-TÜV SÜD Certification and Testing (China) Co., Ltd. Shanghai Branch

Reviewed by:

Prepared by:

Tested by:




Hui TONG  
EMC Section Manager


Wenqiang LU  
EMC Project Engineer

Yiquan WANG  
EMC Test Engineer




## 7 Test Setups

### 7.1 AC Power Line Conducted Emission test setups




### 7.2 Radiated test setups


#### 9kHz ~ 30MHz Test Setup:




30MHz ~ 1GHz Test Setup:




1GHz ~ 18GHz Test Setup:



### 18GHz ~ 25GHz Test Setup:



### 7.3 Conducted RF test setups





## 8 Systems test configuration

Auxiliary Equipment Used during Test:

DESCRIPTION	MANUFACTURER	MODEL NO.(SHIELD)	S/N(LENGTH)
Notebook	Lenove	X240	Notebook

Test software: EMI\_Test\_Tool

The system was configured to channel 11, 18, and 26 for the test.

Non-hopping mode: The system was configured to operate at a signal channel transmitting. The test software allows the configuration and operation at the worst-case duty and the highest transmit power.

## 9 Technical Requirement

### 9.1 Conducted Emission

#### Test Method

1. The EUT was placed on a table, which is 0.8m above ground plane
2. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.).
3. Maximum procedure was performed to ensure EUT compliance
4. A EMI test receiver is used to test the emissions from both sides of AC line

#### Limit


According to §15.207, conducted emissions limit as below:

Frequency MHz	QP Limit dB $\mu$ V	AV Limit dB $\mu$ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

Decreasing linearly with logarithm of the frequency



Product Type : HONEYCOMB MOTOR  
 M/N : CM-08-E  
 Operating Condition : Mode 1: Tx\_2405MHz (worst case)  
 Test Specification : L-line (charging mode)  
 Comment : AC 120V/60Hz (powered by adaptor)




### Final Result

Frequency (MHz)	Quasi Peak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.231000	39.10	---	62.41	23.31	1000.0	9.000	L1	19.6
0.348000	---	28.96	49.01	20.05	1000.0	9.000	L1	19.6
0.456000	---	34.71	46.77	12.06	1000.0	9.000	L1	19.6
0.865500	42.28	---	56.00	13.72	1000.0	9.000	L1	19.6
0.906000	43.06	---	56.00	12.94	1000.0	9.000	L1	19.6
0.915000	---	30.17	46.00	15.83	1000.0	9.000	L1	19.6
2.359500	---	25.39	46.00	20.61	1000.0	9.000	L1	19.6
2.436000	35.78	---	56.00	20.22	1000.0	9.000	L1	19.6
5.190000	---	27.11	50.00	22.89	1000.0	9.000	L1	19.6
9.199500	33.29	---	60.00	26.71	1000.0	9.000	L1	19.7
19.369500	---	24.44	50.00	25.56	1000.0	9.000	L1	20.0
21.273000	35.77	---	60.00	24.23	1000.0	9.000	L1	20.1

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)  
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator



Product Type : HONEYCOMB MOTOR  
 M/N : CM-08-E  
 Operating Condition : Mode 1: Tx\_2405MHz (worst case)  
 Test Specification : N-line (charging mode)  
 Comment : AC 120V/60Hz (powered by adaptor)



**Final Result**

Frequency (MHz)	Quasi Peak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.231000	41.53	---	62.41	20.88	1000.0	9.000	N	19.6
0.357000	---	26.10	48.80	22.70	1000.0	9.000	N	19.6
0.865500	---	32.22	46.00	13.78	1000.0	9.000	N	19.6
0.870000	38.68	---	56.00	17.32	1000.0	9.000	N	19.6
0.915000	---	29.78	46.00	16.22	1000.0	9.000	N	19.6
1.162500	36.23	---	56.00	19.77	1000.0	9.000	N	19.6
2.152500	---	21.02	46.00	24.98	1000.0	9.000	N	19.6
2.319000	30.31	---	56.00	25.69	1000.0	9.000	N	19.6
10.900500	---	22.65	50.00	27.35	1000.0	9.000	N	19.9
10.977000	32.04	---	60.00	27.96	1000.0	9.000	N	19.9
19.738500	---	22.97	50.00	27.03	1000.0	9.000	N	20.0
23.167500	32.78	---	60.00	27.22	1000.0	9.000	N	20.2

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)  
 Factor (dB) = Cable Loss (dB) + LISN Factor (dB) + 10dB Attenuator



## 9.2 Conducted peak output power

### Test Method

1. Use the following spectrum analyzer settings:  
 RBW > the 6 dB bandwidth of the emission being measured, VBW≥3RBW, Span≥3RBW  
 Sweep = auto, Detector function = peak, Trace = max hold.
2. Add a correction factor to the display.
3. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power.

### Limits

According to §15.247 (b) (3) & RSS-247 5.4(d), conducted peak output power limit as below:

Frequency Range MHz	Limit W	Limit dBm
2400-2483.5	≤1	≤30

Frequency Range MHz	Limit (EIRP) W	Limit dBm
2400-2483.5	≤4	≤36

Test result as below table

Frequency MHz	Conducted Peak Output Power dBm	Result
Low channel 2405MHz	7.39	Pass
Middle channel 2440MHz	6.64	Pass
High channel 2480MHz	6.58	Pass


Frequency MHz	EIRP dBm	Result
Low channel 2405MHz	9.59	Pass
Middle channel 2440MHz	8.84	Pass
High channel 2480MHz	8.78	Pass






Peak output power

Channel 11 (2405MHz)




Date: 31 JAN 2023 10:04:48

Channel 18 (2440MHz)



Date: 31 JAN 2023 10:06:33

Channel 26 (2480MHz)



Date: 31 JAN 2023 10:07:42



### 9.3 6dB bandwidth and 99% Occupied Bandwidth

#### Test Method

1. Use the following spectrum analyzer settings:  
RBW=100K, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, may be employed using the X dB bandwidth mode with X set to 6 dB, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

#### Limit

Limit [kHz]

≥500

#### Test Method for 99 % Bandwidth

1. Use the following spectrum analyzer settings:  
RBW=1% to 5% of the actual occupied, VBW≥3RBW, Sweep = auto, Detector function = peak, Trace = max hold
2. Use the automatic bandwidth measurement capability of an instrument, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.
3. Allow the trace to stabilize, record the X dB Bandwidth value.

#### Limit

Limit [kHz]

N/A


#### Test result

Frequency MHz	6dB bandwidth kHz	99% Occupied Bandwidth MHz	Result
Top channel 2405MHz	1.552	2.163	Pass
Middle channel 2440MHz	0.853	2.174	Pass
Bottom channel 2480MHz	1.006	2.174	Pass




6dB Bandwidth

Channel 11 (2405MHz)




Date: 31 JAN 2023 10:04:59

Channel 18 (2440MHz)



Date: 31 JAN 2023 10:06:43

Channel 26 (2480MHz)




Date: 31 JAN 2023 10:07:53




99% Occupied Bandwidth

Channel 0 (2405MHz)




Date: 31 JAN 2023 10:04:53

Channel 19 (2440MHz)



Date: 31 JAN 2023 10:06:38

Channel 39 (2480MHz)



Date: 31 JAN 2023 10:07:47



## 9.4 Power spectral density

### Test Method

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance:

1. Set analyzer center frequency to DTS channel center frequency.  
RBW=3kHz, VBW≥3RBW, Span=1.5 times DTS bandwidth, Detector=Peak, Sweep=auto, Trace= max hold.
2. Allow trace to fully stabilize, use the peak marker function to determine the maximum amplitude level within the RBW.
3. Repeat above procedures until other frequencies measured were completed.

### Limit

Limit [dBm/3kHz]

-----  
≤8


### Test result

Frequency MHz	Power spectral density dBm/3kHz	Result
Top channel 2405MHz	-7.24	Pass
Middle channel 2440MHz	-2.8	Pass
Bottom channel 2480MHz	-3	Pass




PK PSD

Channel 11 (2405MHz)




Date: 31 JAN 2023 10:05:03

Channel 18 (2440MHz)



Date: 31 JAN 2023 10:06:48

Channel 26 (2480MHz)



Date: 31 JAN 2023 10:07:57



## 9.5 Spurious RF conducted emissions

### Test Method


1. Establish a reference level by using the following procedure:
  - a. Set RBW=100 kHz. VBW $\geq$ 3RBW. Detector =peak, Sweep time = auto couple, Trace mode = max hold.
  - b. Allow trace to fully stabilize, use the peak marker function to determine the maximum PSD level.
2. Use the maximum PSD level to establish the reference level.
  - a. Set the center frequency and span to encompass frequency range to be measured.
  - b. Use the peak marker function to determine the maximum amplitude level. Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements, report the three highest emissions relative to the limit.
3. Repeat above procedures until other frequencies measured were completed.

### Limit

Frequency Range MHz	Limit (dBc)
30-25000	-20


### Out-of-Band Emission Channel 11 (2405MHz)

#### Reference point




Date: 31.JAN.2023 10:05:15

#### Spurious Emission (30MHz – 1GHz)




Date: 31.JAN.2023 10:05:16

#### Spurious Emission (1GHz –5GHz)



Date: 31.JAN.2023 10:05:19

#### Spurious Emission (5GHz –26.5GHz)



Date: 31.JAN.2023 10:05:27

Note: The emission which exceed the limit is the fundamental.







Out-of-Band Emission

Channel 18 (2440MHz)



Reference point

Spurious Emission (30MHz – 1GHz)



Spurious Emission (1GHz –5GHz)

Spurious Emission (5GHz –26.5GHz)




Note: The emission which exceed the limit is the fundamental.




Out-of-Band Emission  
Channel 26 (2480MHz)

Reference point




Date: 31 JAN 2023 10:08:08

Spurious Emission (30MHz – 1GHz)




Date: 31 JAN 2023 10:08:10

Spurious Emission (1GHz –5GHz)



Date: 31 JAN 2023 10:08:13

Spurious Emission (5GHz –26.5GHz)



Date: 31 JAN 2023 10:08:21

Note: The emission which exceed the limit is the fundamental.



## 9.6 Band edge

### Test Method



- 1 Use the following spectrum analyzer settings:  
Span = wide enough to capture the peak level of the in-band emission and all spurious  
RBW = 100 kHz, VBW $\geq$ RBW, Sweep = auto, Detector function = peak, Trace = max hold.
- 2 Allow the trace to stabilize, use the peak and delta measurement to record the result.
- 3 The level displayed must comply with the limit specified in this Section.



### Limit

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).



Test result





## 9.7 Spurious radiated emissions for transmitter

### Test Method

1. The EUT was placed on a turn table which is 1.5m above ground plane for above 1GHz and 0.8m above ground for below 1GHz at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
3. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. Use the following spectrum analyzer settings According to C63.10:

#### For Below 1GHz

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 100 kHz to 120 kHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### For Peak unwanted emissions Above 1GHz:

Span = wide enough to capture the peak level of the in-band emission and all spurious  
 RBW = 1MHz, VBW ≥ RBW for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

#### Procedures for average unwanted emissions measurements above 1000 MHz

- a) RBW = 1MHz.
- b) VBW ≥ [3 × RBW].
- c) Detector = RMS (power averaging), if  $[\text{span} / (\# \text{ of points in sweep})] \leq \text{RBW} / 2$ .  
 Satisfying this condition can require increasing the number of points in the sweep or reducing the span. If the condition is not satisfied, then the detector mode shall be set to peak.
- d) Averaging type = power (i.e., rms) (As an alternative, the detector and averaging type may be set for linear voltage averaging. Some instruments require linear display mode to use linear voltage averaging. Log or dB averaging shall not be used.)
- e) Sweep time = auto.
- f) Perform a trace average of at least 100 traces if the transmission is continuous. If the transmission is not continuous, then the number of traces shall be increased by a factor of  $1 / D$ , where D is the duty cycle. For example, with 50% duty cycle, at least 200 traces shall be averaged. (If a specific emission is demonstrated to be continuous—i.e., 100% duty cycle—then rather than turning ON and OFF with the transmit cycle, at least 100 traces shall be averaged.)
- g) If tests are performed with the EUT transmitting at a duty cycle less than 98%, then a correction factor shall be added to the measurement results prior to comparing with the emission limit, to compute the emission level that would have been measured had the test been performed at 100% duty cycle. The correction factor is computed as follows:
  - 1) If power averaging (rms) mode was used in the preceding step e), then the correction



factor is  $[10 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 3 dB shall be added to the measured emission levels.

2) If linear voltage averaging mode was used in the preceding step e), then the correction factor is  $[20 \log (1 / D)]$ , where D is the duty cycle. For example, if the transmit duty cycle was 50%, then 6 dB shall be added to the measured emission levels.

3) If a specific emission is demonstrated to be continuous (100% duty cycle) rather than turning ON and OFF with the transmit cycle, then no duty cycle correction is required for that emission.

**Limit**

The radio emission outside the operating frequency band shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power. Radiated emissions which fall in the restricted bands, as defined in section 15.205 and RSS-GEN 8.10 must comply with the radiated emission limits specified in section 15.209.

Frequency MHz	Field Strength uV/m	Measured Distance Meters
0.009~0.490	2400/F (kHz)	300
0.490~1.705	24000/F (kHz)	30
1.705~30	30	30

Frequency MHz	Field Strength uV/m	Field Strength dBµV/m	Detector
30-88	100	40	QP
88-216	150	43.5	QP
216-960	200	46	QP
960-1000	500	54	QP
Above 1000	500	54	AV
Above 1000	5000	74	PK

### Spurious radiated emissions for transmitter

According to C63.10, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement, so AV emission value did not show in below table if the peak value complies with average limit.

The only worse case (which is subject to the maximum EIRP) test result is listed in the report.

#### Transmitting spurious emission test result as below:

Frequency MHz	Mmission Level dBuV/m	Channel (2405MHz)		Detector	Polarization
		Limit dBuV/m	Margin dB		
2341.6	46.19	74.0	27.81	Peak	Horizontal
2379.1	47.06	74.0	26.94	Peak	Horizontal
4827.3	44.19	74.0	29.81	Peak	Horizontal
7216.3	47.11	74.0	26.89	Peak	Horizontal
2340.5	45.68	74.0	28.32	Peak	Vertical
2380.0	48.50	74.0	25.5	Peak	Vertical
1199.5	40.91	74.0	33.09	Peak	Vertical
4809.1	45.21	74.0	28.79	Peak	Vertical
7213.5	49.13	74.0	24.87	Peak	Vertical

Frequency MHz	Mmission Level dBuV/m	Channel (2440MHz)		Detector	Polarization
		Limit dBuV/m	Margin dB		
4857.9	43.17	74.0	30.83	Peak	Horizontal
7318.3	47.76	74.0	26.24	Peak	Horizontal
4971.8	44.63	74.0	29.37	Peak	Vertical
7321.2	52.21	74.0	21.79	Peak	Vertical

Frequency MHz	Mmission Level dBuV/m	Channel (2480MHz)		Detector	Polarization
		Limit dBuV/m	Margin dB		
2483.3	45.09	74.0	28.91	Peak	Horizontal
4912.3	43.67	74.0	30.33	Peak	Horizontal
7441.3	49.70	74.0	24.3	Peak	Horizontal
2483.8	45.47	74.0	28.53	Peak	Vertical
7438.5	50.95	74.0	23.05	Peak	Vertical

#### Remark:

- (1) Emission level= Original Receiver Reading + Correct Factor
- (2) Correct Factor = Antenna Factor + Cable Loss -Amplifier gain
- (3) Margin = limit – Corrected Reading






The worst case of Radiated Emission below 1GHz:

Site: 3 meter chamber	Time: 2023/01/31 - 10:26
Limit: FCC_Part15.209 and RSS-GEN 8.8_RE(3m)	Engineer: Wenqiang LU
Probe: VULB9168	Polarity: Horizontal
UT: HONEYCOMB MOTOR, Model no: CM-08-E	Power: 120VAC, 60Hz (Charging mode)
Note: Transmit by at channel 2405MHz.	
Note: Pre-scan with three orthogonal axis and worst case as X axis.	

RE\_VULB9168\_pre\_Cont\_30-1000



### Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
95.800000	34.6	1000.0	120.000	103.6	H	83.0	15.6	8.9	43.5
143.040000	36.8	1000.0	120.000	102.6	H	126.0	20.6	6.7	43.5
191.280000	35.5	1000.0	120.000	121.4	H	230.0	18.4	8.0	43.5
239.120000	44.1	1000.0	120.000	119.0	H	11.0	19.4	1.9	46.0
286.160000	38.6	1000.0	120.000	101.3	H	179.0	21.2	7.4	46.0
333.840000	36.2	1000.0	120.000	123.7	H	286.0	22.6	9.9	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)


Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.



Site: 3 meter chamber	Time: 2021/03/14 - 11:31
Limit: FCC_Part15.209 and RSS-GEN 8.8_RE(3m)	Engineer: Wenqiang LU
Probe: VULB9168	Polarity: Vertical
UT: HONEYCOMB MOTOR, Model no: CM-08-E	Power: 120VAC, 60Hz (Charging mode)
Note: Transmit by at channel 2405MHz.	
Note: Pre-scan with three orthogonal axis and worst case as X axis.	

RE\_VULB9168\_pre\_Cont\_30-1000



### Limit and Margin

Frequency (MHz)	QuasiPeak (dBuV/m)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB)	Margin - QPK (dB)	Limit - QPK (dBuV/m)
95.800000	29.7	1000.0	120.000	113.4	V	32.0	15.6	13.8	43.5
119.760000	24.5	1000.0	120.000	129.1	V	259.0	18.1	19.0	43.5
143.800000	28.7	1000.0	120.000	112.3	V	86.0	20.5	14.8	43.5
191.680000	26.2	1000.0	120.000	132.3	V	204.0	18.4	17.3	43.5
239.120000	31.1	1000.0	120.000	118.8	V	136.0	19.4	14.9	46.0
438.920000	26.9	1000.0	120.000	117.9	V	308.0	25.6	19.1	46.0

Note 1: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB)

Factor (dB) = Cable Loss (dB) + Antenna Factor (dB/m)

Note 2: The test trace is same as the ambient noise and the amplitude of the emissions are attenuated more than 20dB below the permissible (the test frequency range: 9kHz ~ 30MHz, 18GHz ~ 25GHz), therefore no data appear in the report.



## 10 Test Equipment List

List of Test Instruments  
Test Site1

	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	CAL. DATE	CAL. DUE DATE
C	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2022-8-1	2023-7-31
RE	EMI Test Receiver	Rohde & Schwarz	ESR3	101906	2022-8-1	2023-7-31
	Signal Analyzer	Rohde & Schwarz	FSV40	101091	2022-8-1	2023-7-31
	Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9168	961	2021-9-23	2024-9-22
	Horn Antenna	Rohde & Schwarz	HF907	102393	2021-4-13	2024-4-12
	Pre-amplifier	Rohde & Schwarz	SCU-18D	19006451	2022-8-1	2023-7-31
	Loop antenna	Rohde & Schwarz	HFH2-Z2	100443	2022-6-13	2023-6-12
	Double Ridged Horn Antenna	ETS-Lindgren	3116C	002222727	2020-9-23	2023-9-22
	Pre-amplifier	ETS-Lindgren	3116C-PA	----	2022-9-23	2023-9-22
CE	3m Semi-anechoic chamber	TDK	9X6X6	----	2021-5-8	2024-5-7
	EMI Test Receiver	Rohde & Schwarz	ESR3	101907	2022-8-1	2023-7-31
	LISN	Rohde & Schwarz	ENV216	101924	2022-8-1	2023-7-31
Measurement Software Information						
Test Item	Software	Manufacturer	Version			
C	Bluetooth and WiFi Test System	Shenzhen JS tonskend co.,ltd	2.6.77.0518			
RE	EMC 32	Rohde & Schwarz	V10.50.40			
CE	EMC 32	Rohde & Schwarz	V9.15.03			

**C - Conducted RF tests**

- Conducted peak output power
- 6dB bandwidth and 99% Occupied Bandwidth
- Power spectral density\*
- Spurious RF conducted emissions
- Band edge



## 11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

Items	Extended Uncertainty
Conducted Disturbance at Mains Terminals	150kHz to 30MHz, LISN, 3.16dB
Radiated Disturbance	30MHz to 1GHz, 5.03dB (Horizontal) 5.12dB (Vertical) 1GHz to 18GHz, 5.49dB 18GHz to 40GHz, 5.63dB
Carrier power conducted measurement	50MHz~18GHz, 1.238dB
Spurious Emission Conducted Measurement	9kHz ~40GHz, 1.224dB

Measurement Uncertainty Decision Rule:

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2021, clause 4.4.3 and 4.5.1.



## **12 Photographs of Test Set-ups**

Refer to the < Test Setup photos >.



## **13 Photographs of EUT**

Refer to the < External Photos > & < Internal Photos >.

---

THE END