



FCC PART 22H, PART 24E
TEST REPORT

For

Nexpro International Limitada

San Jose-Goicoechea, Guadalupe, Barrio Tournon, Frente Al Hotel Villas Tournon,
Oficinas Del Bufete Facio Y Canas, Costa Rica

FCC ID: ZYPS9081

Report Type: Original Report	Product Type: Smartphone
Test Engineer: Gardon Zhang	<i>Gardon Zhang</i>
Report Number: R1DG130121001-00D	
Report Date: 2013-03-06	
Reviewed By: RF Leader	<i>Alvin Huang</i>
Test Laboratory: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F, the 3rd Phase of WanLi Industrial Building ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This test report is prepared for the customer shown above and for the device described herein. It may not be duplicated or used in part without prior written consent from Bay Area Compliance Laboratories Corp. This report **must not** be used by the customer to claim product certification, approval, or endorsement by NVLAP*, or any agency of the Federal Government.

* This report may contain data that are not covered by the NVLAP accreditation and shall be marked with an asterisk "★"

TABLE OF CONTENTS

GENERAL INFORMATION.....	3
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	3
OBJECTIVE.....	3
RELATED SUBMITTAL(S)/GRANT(S).....	3
TEST METHODOLOGY.....	3
TEST FACILITY.....	4
SYSTEM TEST CONFIGURATION.....	5
DESCRIPTION OF TEST CONFIGURATION.....	5
EQUIPMENT MODIFICATIONS.....	8
BLOCK DIAGRAM OF TEST SETUP.....	8
SUMMARY OF TEST RESULTS.....	9
FCC §1.1307 & §2.1093 - RF EXPOSURE.....	10
APPLICABLE STANDARD.....	10
TEST RESULT.....	10
FCC §2.1047 - MODULATION CHARACTERISTIC.....	11
FCC § 2.1046, § 22.913 (A) & § 24.232 (C) - RF OUTPUT POWER.....	12
APPLICABLE STANDARD.....	12
TEST PROCEDURE.....	12
TEST EQUIPMENT LIST AND DETAILS.....	12
TEST DATA.....	13
FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH.....	17
APPLICABLE STANDARD.....	17
TEST PROCEDURE.....	17
TEST EQUIPMENT LIST AND DETAILS.....	17
TEST DATA.....	17
FCC §2.1051, §22.917(A) & §24.238(A) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS.....	30
APPLICABLE STANDARD.....	30
TEST PROCEDURE.....	30
TEST EQUIPMENT LIST AND DETAILS.....	30
TEST DATA.....	31
FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS.....	37
APPLICABLE STANDARD.....	37
TEST PROCEDURE.....	37
TEST EQUIPMENT LIST AND DETAILS.....	37
TEST DATA.....	38
FCC §22.917(A) & §24.238(A) - BAND EDGES.....	40
APPLICABLE STANDARD.....	40
TEST PROCEDURE.....	40
TEST EQUIPMENT LIST AND DETAILS.....	40
TEST DATA.....	40
FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY.....	48
APPLICABLE STANDARD.....	48
TEST PROCEDURE.....	48
TEST EQUIPMENT LIST AND DETAILS.....	49
TEST DATA.....	49

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

The *Nexpro International Limitada*'s product, model number: *Neat (FCC ID: ZYPS9081)* or the "EUT" in this report was a *Smartphone*, which was measured approximately: 147.0 mm (L) x 76.5 mm (W) x 9.7 mm (H), rated input voltage: DC 3.7 V Li-ion battery.

** All measurement and test data in this report was gathered from production sample serial number: 130121001 (Assigned by BACL, Shenzhen). The EUT supplied by the applicant was received on 2013-01-21.*

Objective

This test report is prepared on behalf of *Nexpro International Limitada* in accordance with Part 2-Subpart J, Part 22-Subpart H and Part 24-Subpart E of the Federal Communication Commissions rules.

The objective is to determine the compliance of the EUT with FCC rules for output power, modulation characteristic, occupied bandwidth, spurious emission at antenna terminal, spurious radiated emission, frequency stability and band edge.

Related Submittal(s)/Grant(s)

FCC Part 15.247 DSS, Part 15.247 DTS and Part 15B JBP submissions with FCC ID: ZYPS9081.

Test Methodology

All tests and measurements indicated in this document were performed in accordance with the Code of Federal Regulations Title 47 Part 2-Subpart J as well as the following parts:

Part 22 Subpart H - Public Mobile Services
Part 24 Subpart E - Personal Communication Services

Applicable Standards: TIA/EIA 603-D, ANSI C63.4-2003.

All radiated and conducted emissions measurements were performed at Bay Area Compliance Laboratories Corp. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Test Facility

The Test site used by Bay Area Compliance Laboratories Corp.(Shenzhen) to collect test data is located on the 6/F, the 3rd Phase of WanLi Industrial Building, ShiHua Road, FuTian Free Trade Zone Shenzhen, Guangdong, China.

Test site at Bay Area Compliance Laboratories Corp. (Shenzhen) has been fully described in reports submitted to the Federal Communication Commission (FCC). The details of these reports have been found to be in compliance with the requirements of Section 2.948 of the FCC Rules on December 06, 2010. The facility also complies with the radiated and AC line conducted test site criteria set forth in ANSI C63.4-2003.

The Federal Communications Commission has the reports on file and is listed under FCC Registration No.: 382179. The test site has been approved by the FCC for public use and is listed in the FCC Public Access Link (PAL) database.

Additionally, Bay Area Compliance Laboratories Corp. (Shenzhen) is an ISO/IEC 17025 accredited laboratory, and is accredited by National Voluntary Laboratory Accredited Program (Lab Code 200707-0).



The current scope of accreditations can be found at <http://ts.nist.gov/Standards/scopes/2007070.htm>

SYSTEM TEST CONFIGURATION

Description of Test Configuration

The EUT was configured for testing according to TIA/EIA-603-D.

The final qualification test was performed with the EUT operating at normal mode.

GSM:

The following tests were conducted according to the test requirements outlines in section 13.3 of the 3GPP TS 51.010-1 specification. The EUT has a nominal maximum output power of 33dBm (+3/-3) for GSM 850, 30dBm (+3/-3) for PCS 1900.

GPRS:

The following tests were conducted according to the test requirements outlines in section 13.16 of the 3GPP TS 51.010-1 specification. The EUT has a nominal maximum output power of 33dBm (+3/-3) for GSM 850, 30dBm (+3/-3) for PCS 1900.

EDGE:

The following tests were conducted according to the test requirements outlines in section 13.17 of the 3GPP TS 51.010-1 specification. The EUT has a nominal maximum output power of 27dBm (+3/-3) for GSM 850, 26dBm (+3/-3) for PCS 1900.

WCDMA-Release 99:

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification. The EUT has a nominal maximum output power of 24dBm (+1.7/-3.7).

WCDMA General Settings	Loopback Mode	Test Mode 1
	Rel99 RMC	12.2kbps RMC
	Power Control Algorithm	Algorithm2
	β_c / β_d	8/15

WCDMA HSDPA

The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSDPA	HSDPA	HSDPA	HSDPA
	Subset	1	2	3	4
WCDMA General Settings	Loopback Mode	Test Mode 1			
	Rel99 RMC	12.2kbps RMC			
	HSDPA FRC	H-Set1			
	Power Control Algorithm	Algorithm2			
	β_c	2/15	12/15	15/15	15/15
	β_d	15/15	15/15	8/15	4/15
	β_d (SF)	64			
	β_c / β_d	2/15	12/15	15/8	15/4
	β_{hs}	4/15	24/15	30/15	30/15
	MPR(dB)	0	0	0.5	0.5
HSDPA Specific Settings	D_{ACK}	8			
	D_{NAK}	8			
	D_{CQI}	8			
	Ack-Nack repetition factor	3			
	CQI Feedback	4ms			
	CQI Repetition Factor	2			
	$A_{hs} = \beta_{hs} / \beta_c$	30/15			

WCDMA HSUPA


The following tests were conducted according to the test requirements outlines in section 5.2 of the 3GPP TS34.121-1 specification.

	Mode	HSUPA	HSUPA	HSUPA	HSUPA	HSUPA
	Subset	1	2	3	4	5
WCDMA General Settings	Loopback Mode	Test Mode 1				
	Rel99 RMC	12.2kbps RMC				
	HSDPA FRC	H-Set1				
	HSUPA Test	HSUPA Loopback				
	Power Control Algorithm	Algorithm2				
	β_c	11/15	6/15	15/15	2/15	15/15
	β_d	15/15	15/15	9/15	15/15	0
	β_{ec}	209/225	12/15	30/15	2/15	5/15
	β_c / β_d	11/15	6/15	15/9	2/15	-
	β_{hs}	22/15	12/15	30/15	4/15	5/15
	CM(dB)	1.0	3.0	2.0	3.0	1.0
MPR(dB)	0	2	1	2	0	
HSDPA Specific Settings	DACK	8				
	DNAK	8				
	DCQI	8				
	Ack-Nack repetition factor	3				
	CQI Feedback	4ms				
	CQI Repetition Factor	2				
	$A_{hs} = \beta_{hs} / \beta_c$	30/15				
HSUPA Specific Settings	DE-DPCCH	6	8	8	5	7
	DHARQ	0	0	0	0	0
	AG Index	20	12	15	17	21
	ETFCI	75	67	92	71	81
	Associated Max UL Data Rate kbps	242.1	174.9	482.8	205.8	308.9
	Reference E_FCIs	E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27		E-TFCI 11 E-TFCI PO4 E-TFCI 92 E-TFCI PO 18		E-TFCI 11 E E-TFCI PO 4 E-TFCI 67 E-TFCI PO 18 E-TFCI 71 E-TFCI PO23 E-TFCI 75 E-TFCI PO26 E-TFCI 81 E-TFCI PO 27

Equipment Modifications

No modification was made to the EUT.

Block Diagram of Test Setup



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§1.1307, §2.1093	RF Exposure (SAR)	Compliance*
§2.1046; § 22.913 (a); § 24.232 (c)	RF Output Power	Compliance
§ 2.1047	Modulation Characteristics	Not Applicable
§ 2.1049; § 22.905 § 22.917; § 24.238	Occupied Bandwidth	Compliance
§ 2.1051, § 22.917 (a); § 24.238 (a)	Spurious Emissions at Antenna Terminal	Compliance
§ 2.1053 § 22.917 (a); § 24.238 (a)	Field Strength of Spurious Radiation	Compliance
§ 22.917 (a); § 24.238 (a)	Out of band emission, Band Edge	Compliance
§ 2.1055 § 22.355; § 24.235	Frequency stability vs. temperature Frequency stability vs. voltage	Compliance

Note: * Please refer to SAR report released by BACL, report number: R1DG130121001-20

FCC §1.1307 & §2.1093 - RF EXPOSURE

Applicable Standard

FCC§1.1307 and §2.1093.

Test Result

Compliance, please refer to the SAR report: R1DG130121001-20

FCC §2.1047 - MODULATION CHARACTERISTIC

According to FCC § 2.1047(d), Part 22H & 24E there is no specific requirement for digital modulation, therefore modulation characteristic is not presented.

FCC § 2.1046, § 22.913 (a) & § 24.232 (c) - RF OUTPUT POWER

Applicable Standard


According to FCC §2.1046 and §22.913 (a), the ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 watts.

According to FCC §2.1046 and §24.232 (C), mobile and portable stations are limited to 2 watts EIRP and the equipment must employ a means for limiting power to the minimum necessary for successful communications..

Test Procedure

Conducted method:

The RF output of the transmitter was connected to the wireless test set and the spectrum analyzer through sufficient attenuation.



Radiated method:

TIA 603-D section 2.2.17

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2014-11-30
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27
HP	Synthesized Sweeper	8341B	2624A00116	2012-05-17	2013-05-16
COM POWER	Dipole Antenna	AD-100	041000	2012-06-06	2013-06-05
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2015-02-10
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2012-12-01	2013-12-01

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0kPa

The testing was performed by Gardon Zhang on 2013-01-25.

Conducted Power

Cellular Band (Part 22H)

Mode	Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
GSM	128	824.2	32.31	38.45
	190	836.6	32.31	38.45
	251	848.8	32.31	38.45

Mode	Frequency (MHz)	Peak Output Power (dBm)				Limit (dBm)
		Slot 1	Slot 2	Slot 3	Slot 4	
GPRS	824.2	32.29	31.47	29.91	29.11	38.45
	836.6	32.27	31.50	29.92	29.13	38.45
	848.8	32.27	31.42	29.88	29.11	38.45

Mode	Frequency (MHz)	Peak Output Power (dBm)				Limit (dBm)
		Slot 1	Slot 2	Slot 3	Slot 4	
EGPRS (EDGE)	824.2	26.82	25.41	22.99	21.79	38.45
	836.6	26.60	25.20	22.78	21.63	38.45
	848.8	26.36	24.98	22.61	21.37	38.45

Test Mode	3GPP Sub Test	Peak Output Power (dBm)			
		Low Frequency (826.4MHz)	Middle Frequency (836.6 MHz)	High Frequency (846.6MHz)	
WCDMA	Rel 99	-	22.69	22.29	22.69
	Rel 6 HSDPA	1	22.48	22.25	22.56
		2	22.47	22.10	22.15
		3	22.33	22.25	22.09
		4	22.43	22.18	22.33
	Rel 6 HSUPA	1	22.44	22.09	22.45
		2	22.42	22.10	22.49
		3	22.28	22.15	22.29
		4	22.19	22.15	22.31
		5	22.50	22.19	22.43

PCS Band (Part 24E)

Mode	Channel	Frequency (MHz)	Peak Output Power (dBm)	Limit (dBm)
GSM	512	1850.2	29.30	33
	661	1880.0	29.06	33
	810	1909.8	28.82	33

Mode	Frequency (MHz)	Peak Output Power (dBm)				Limit (dBm)
		Slot 1	Slot 2	Slot 3	Slot 4	
GPRS	1850.2	29.30	28.52	26.99	26.19	33
	1880.0	29.05	28.25	26.64	25.90	33
	1909.8	28.81	28.00	26.38	25.63	33

Mode	Frequency (MHz)	Peak Output Power (dBm)				Limit (dBm)
		Slot 1	Slot 2	Slot 3	Slot 4	
EGPRS (EDGE)	1850.2	25.79	24.58	22.57	21.50	33
	1880.0	25.50	24.32	22.24	21.12	33
	1909.8	25.06	23.84	21.73	20.62	33

Test Mode	3GPP Sub Test	Peak Output Power (dBm)			
		Low Frequency (1852.4 MHz)	Middle Frequency (1880.0 MHz)	High Frequency (1907.6 MHz)	
WCDMA	Rel 99	-	22.46	22.61	22.27
	Rel 6 HSDPA	1	22.29	22.31	22.18
		2	21.98	22.54	22.10
		3	22.31	22.18	22.16
		4	22.18	22.13	22.10
	Rel 6 HSUPA	1	22.38	22.39	22.15
		2	22.27	22.51	22.09
		3	22.20	22.48	22.17
		4	22.09	22.42	22.27
		5	22.24	22.33	22.08

Radiated Power

ERP & EIRP

GSM Mode:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBµV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)
Middle Channel									
836.6	95.48	248	1.0	H	24.87	0.69	0	24.18	38.45
836.6	104.47	75	1.4	V	31.86	0.69	0	31.17	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Receiver Reading (dBµV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 24E
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)
Middle Channel									
1880.0	92.36	34	1.5	H	18.30	1.03	9.40	26.67	33
1880.0	89.78	111	1.8	V	20.87	1.03	9.40	29.24	33

EGPRS (EDGE) Mode:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBµV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)
Middle Channel									
836.6	90.65	98	1.0	H	20.04	0.69	0	19.35	38.45
836.6	99.28	147	1.4	V	26.67	0.69	0	25.98	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Receiver Reading (dBµV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 24E
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)
Middle Channel									
1880.0	87.94	63	1.7	H	13.18	1.03	9.40	21.55	33
1880.0	85.19	175	1.6	V	16.28	1.03	9.40	24.65	33

WCDMA Mode:

ERP for Cellular Band (Part 22H)

Frequency (MHz)	Receiver Reading (dBµV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)
Middle Channel									
836.6	82.70	16	1.0	H	12.09	0.69	0	11.40	38.45
836.6	91.10	134	1.5	V	20.49	0.69	0	19.80	38.45

EIRP for PCS Band (Part 24E)

Frequency (MHz)	Receiver Reading (dBµV)	Turn table Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 24E
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)
Middle Channel									
1880.0	84.26	56	1.5	H	10.20	1.03	9.40	18.57	33
1880.0	81.09	137	1.7	V	12.18	1.03	9.40	20.55	33

FCC §2.1049, §22.917, §22.905 & §24.238 - BANDWIDTH


Applicable Standard

FCC §2.1049, §22.917, §22.905 and §24.238.

Test Procedure

The RF output of the transmitter was connected to the simulator and the spectrum analyzer through sufficient attenuation.

The resolution bandwidth of the spectrum analyzer was set at 3 kHz (Cellular /PCS) and the 26 dB & 99% bandwidth was recorded.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2012-12-01	2013-12-01

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20~25 °C
Relative Humidity:	48~56 %
ATM Pressure:	100.0~101.1kPa

The testing was performed by Gardon Zhang from 2013-01-25 to 2013-02-04.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
GSM (GMSK)	836.6	246.49	316.63

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
EGPRS (8PSK)	836.6	244.49	302.61

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
WCDMA (QPSK)	836.6	4.19	4.73

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
HSUPA (64QAM)	836.6	4.17	4.67

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
HSDPA (16QAM)	836.6	4.17	4.67

PCS Band (Part 24E)

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
GSM (GMSK)	1880.0	248.50	314.63

Mode	Frequency (MHz)	99% Occupied Bandwidth (kHz)	26 dB Bandwidth (kHz)
EGPRS (8PSK)	1880.0	252.51	312.63


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
WCDMA (QPSK)	1880.0	4.19	4.69

Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
HSUPA (64QAM)	836.6	4.21	4.71


Mode	Frequency (MHz)	99% Occupied Bandwidth (MHz)	26 dB Bandwidth (MHz)
HSDPA (16QAM)	836.6	4.21	4.71

Cellular Band (Part 22H)


99% Occupied Bandwidth for GSM (GMSK) Mode




26 dB Bandwidth for GSM (GMSK) Mode




99% Occupied Bandwidth for EGPRS (8PSK) Mode




26 dB Bandwidth for EGPRS (8PSK) Mode




99% Occupied Bandwidth for WCDMA (QPSK) Mode




26 dB Bandwidth for WCDMA (QPSK) Mode




99% Occupied Bandwidth for HSUPA (64QAM) Mode




26 dB Bandwidth for HSUPA (64QAM) Mode



99% Occupied Bandwidth for HSDPA (16QAM) Mode




26 dB Bandwidth for HSDPA (16QAM) Mode




PCS Band (Part 24E)


99% Occupied Bandwidth for GSM (GMSK) Mode




26 dB Bandwidth for GSM (GMSK) Mode




99% Occupied Bandwidth for EGPRS (8PSK) Mode




26 dB Bandwidth for EGPRS (8PSK) Mode




99% Occupied Bandwidth for WCDMA (QPSK) Mode




26 dB Bandwidth for WCDMA (QPSK) Mode




99% Occupied Bandwidth for HSUPA (64QAM) Mode




26 dB Bandwidth for HSUPA (64QAM) Mode



99% Occupied Bandwidth for HSDPA (16QAM) Mode



26 dB Bandwidth for HSDPA (16QAM) Mode



FCC §2.1051, §22.917(a) & §24.238(a) - SPURIOUS EMISSIONS AT ANTENNA TERMINALS


Applicable Standard

FCC §2.1051, §22.917(a) and §24.238(a).

The spectrum was to be investigated to the tenth harmonics of the highest fundamental frequency as specified in § 2.1051.

Test Procedure

The RF output of the transceiver was connected to a spectrum analyzer and simulator through appropriate attenuation. The resolution bandwidth of the spectrum analyzer was set at 1MHz. Sufficient scans were taken to show any out of band emissions up to 10th harmonic.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2012-12-01	2013-12-01
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20~25 °C
Relative Humidity:	50~56 %
ATM Pressure:	100.0 kPa


The testing was performed by Gardon Zhang on 2013-03-06.


Test result: Compliance, please refer to the following plots.

GSM mode:

Cellular Band (Part 22H)


30 MHz – 10 GHz - Middle Channel






PCS Band (Part 24E)


30 MHz – 20 GHz - Middle Channel





Fundamental



Date: 6.MAR.2013 09:45:30




Date: 6.MAR.2013 09:46:14

PCS Band (Part 24E)

30 MHz – 20 GHz - Middle Channel





FCC §2.1053, §22.917 & §24.238 - SPURIOUS RADIATED EMISSIONS

Applicable Standard

FCC § 2.1053, §22.917 and § 24.238.

Test Procedure

The transmitter was placed on a wooden turntable, and it was transmitting into a non-radiating load which was also placed on the turntable.

The measurement antenna was placed at a distance of 3 meters from the EUT. During the tests, the receiving antenna height and polarization as well as EUT azimuth were varied in order to identify the maximum level of emissions from the EUT. The test was performed by placing the EUT on 3-orthogonal axis.

The frequency range up to tenth harmonic of the fundamental frequency was investigated.

Remove the EUT and replace it with substitution antenna. A signal generator was connected to the substitution antenna by a non-radiating cable. The absolute levels of the spurious emissions were measured by the substitution.

Spurious emissions in dB = 10 lg (TXpwr in Watts/0.001) – the absolute level

Spurious attenuation limit in dB = 43 + 10 Log₁₀ (power out in Watts)

Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Sunol Sciences	Horn Antenna	DRH-118	A052304	2011-12-01	2014-11-30
Sunol Sciences	Broadband Antenna	JB1	A040904-2	2011-11-28	2014-11-27
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23
SUPER ULTRA	Amplifier	ZVA-213+	N/A	2012-11-24	2013-11-23
HP	Amplifier	8447E	1937A01046	2012-11-24	2013-11-23
HP	Synthesized Sweeper	8341B	2624A00116	2012-05-17	2013-05-16
COM POWER	Dipole Antenna	AD-100	041000	2012-06-06	2013-06-05
A.H. System	Horn Antenna	SAS-200/571	135	2012-02-11	2015-02-10
Electro-Mechanics	Horn Antenna	3116	9510-2270	2010-10-14	2013-10-13
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2012-12-01	2013-12-01

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Gardon Zhang on 2013-02-01.

EUT operation mode: Transmitting (worst case)

30 MHz ~ 10 GHz:**Cellular Band (Part 22H) for GSM Mode**

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H	
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
Middle Channel (836.6 MHz)										
1673.2	55.26	137	1.7	V	-45.2	0.97	9.40	-36.77	-13	23.77
1673.2	56.33	35	1.6	H	-46.7	0.97	9.40	-38.27	-13	25.27
2509.8	43.34	17	1.6	V	-53.0	1.46	10.70	-43.76	-13	30.76
2509.8	47.03	205	1.8	H	-53.7	1.46	10.70	-44.46	-13	31.46
3346.4	37.83	89	1.7	H	-56.6	2.08	10.80	-47.88	-13	34.88
3346.4	35.72	107	1.6	V	-57.8	2.08	10.80	-49.08	-13	36.08
636.9	27.93	159	1.5	V	-69.1	0.58	0	-69.68	-13	56.68
636.9	25.68	59	1.8	H	-71.3	0.58	0	-71.88	-13	58.88

Cellular Band (Part 22H) for WCDMA Mode

Frequency (MHz)	Receiver Reading (dBμV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 22H	
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
Middle Channel (836.6 MHz)										
1673.2	51.48	168	1.7	V	-49.0	0.97	9.40	-40.57	-13	27.57
1673.2	51.37	37	1.6	H	-51.7	0.97	9.40	-43.27	-13	30.27
2509.8	41.89	104	1.8	V	-54.5	1.46	10.70	-45.26	-13	32.26
3346.4	34.83	163	1.9	V	-58.7	2.08	10.80	-49.98	-13	36.98
2509.8	41.10	59	1.7	H	-59.6	1.46	10.70	-50.36	-13	37.36
3346.4	33.76	71	1.7	H	-60.7	2.08	10.80	-51.98	-13	38.98

30 MHz ~ 20 GHz:

PCS Band (Part 24E) for GSM Mode

Frequency (MHz)	Receiver Reading (dBµV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 24E	
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
Middle Channel (1880.0 MHz)										
1880	92.84	34	1.5	H	18.8	1.03	9.40	27.17	/	/
1880	90.61	111	1.8	V	21.7	1.03	9.40	30.07	/	/
7520	38.41	177	1.5	H	-51.4	3.07	12.00	-42.47	-13	29.47
3760	43.47	25	1.8	V	-51.2	2.96	10.40	-43.76	-13	30.76
7520	36.30	15	1.7	V	-53.3	3.07	12.00	-44.37	-13	31.37
3760	44.21	53	1.6	H	-51.9	2.96	10.40	-44.46	-13	31.46
5640	33.23	203	1.6	V	-58.2	3.94	11.70	-49.05	-13	36.05
5640	33.36	109	1.7	H	-59.0	3.94	11.70	-49.85	-13	36.85
331.5	23.47	157	1.5	V	-73.5	0.38	0	-73.88	-13	60.88
331.5	22.37	16	1.0	H	-74.6	0.38	0	-74.98	-13	61.98

PCS Band (Part 24E) for WCDMA Mode

Frequency (MHz)	Receiver Reading (dBµV)	Turntable Angle Degree	Rx Antenna		Substituted			Absolute Level (dBm)	FCC Part 24E	
			Height (m)	Polar (H/V)	SG Level (dBm)	Cable Loss (dB)	Antenna Gain (dB)		Limit (dBm)	Margin (dB)
Middle Channel (1880.0 MHz)										
7409.6	32.06	314	1.6	V	-55.0	3.07	12.00	-46.31	-13	33.31
7409.6	31.87	207	1.7	H	-55.4	3.07	12.00	-46.71	-13	33.71
5557.2	34.13	159	1.8	V	-55.9	3.94	11.70	-48.14	-13	35.14
5557.2	33.56	117	1.9	H	-59.1	3.94	11.70	-51.34	-13	38.34
3704.8	35.72	54	1.7	V	-60.8	2.96	10.40	-52.99	-13	39.99
3704.8	34.63	63	1.8	H	-62.6	2.96	10.40	-54.79	-13	41.79

Note:

Absolute Level = SG Level - Cable loss + Antenna Gain

Margin = Limit- Absolute Level

FCC §22.917(a) & §24.238(a) - BAND EDGES

Applicable Standard


According to § 22.917(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

According to §24.238(a), the power of any emissions outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least $43 + 10 \log(P)$ dB.

Test Procedure

The RF output of the transmitter was connected to the input of the spectrum analyzer through sufficient attenuation.

The center of the spectrum analyzer was set to block edge frequency



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Rohde & Schwarz	Signal Analyzer	FSIQ26	8386001028	2012-11-24	2013-11-23
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2012-12-01	2013-12-01

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data

Environmental Conditions

Temperature:	20~25 °C
Relative Humidity:	50~56 %
ATM Pressure:	100.0 kPa

The testing was performed by Gardon Zhang on 2013-01-25 and 2013-01-27.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables and plots.

Cellular Band (Part 22H)

Mode	Band edges	Emission (dBm)	Limit (dBm)
GSM (GMSK)	L	-13.68	≤-13
	R	-14.15	≤-13

Mode	Band edges	Emission (dBm)	Limit (dBm)
EGPRS (8PSK)	L	-18.44	≤-13
	R	-16.91	≤-13

Mode	Band edges	Emission (dBm)	Limit (dBm)
WCDMA (QPSK)	L	-26.77	≤-13
	R	-20.04	≤-13

PCS Band (Part 24E)


Mode	Band edges	Emission (dBm)	Limit (dBm)
GSM (GMSK)	L	-17.13	≤-13
	R	-16.62	≤-13

Mode	Band edges	Emission (dBm)	Limit (dBm)
EGPRS (8PSK)	L	-26.54	≤-13
	R	-25.96	≤-13


Mode	Band edges	Emission (dBm)	Limit (dBm)
WCDMA (QPSK)	L	-25.39	≤-13
	R	-18.33	≤-13

GSM(GMSK) Mode


Cellular Band, Left Band Edge




Cellular Band, Right Band Edge



PCS Band, Left Band Edge




PCS Band, Right Band Edge




EGPRS (8PSK) Mode


Cellular Band, Left Band Edge




Cellular Band, Right Band Edge



PCS Band, Left Band Edge




PCS Band, Right Band Edge




WCDMA(QPSK) Mode


Cellular Band, Left Band Edge




Cellular Band, Right Band Edge



PCS Band, Left Band Edge



PCS Band, Right Band Edge



FCC §2.1055, §22.355 & §24.235 - FREQUENCY STABILITY

Applicable Standard

FCC § 2.1055, §22.355, §24.235

According to §22.355, the carrier frequency of each transmitter in the Public Mobile Services must be maintained within the tolerances given in Table below:

Frequency Tolerance for Transmitters in the Public Mobile Services

Frequency Range (MHz)	Base, fixed (ppm)	Mobile ≤ 3 watts (ppm)	Mobile ≤ 3 watts (ppm)
25 to 50	20.0	20.0	50.0
50 to 450	5.0	5.0	50.0
450 to 512	2.5	5.0	5.0
821 to 896	1.5	2.5	2.5
928 to 929.	5.0	N/A	N/A
929 to 960.	1.5	N/A	N/A
2110 to 2220	10.0	N/A	N/A


According to §24.235, the frequency stability shall be sufficient to ensure that the fundamental emissions stays within the authorized frequency block.

Test Procedure

Frequency Stability vs. Temperature: The equipment under test was connected to an external DC power supply and the RF output was connected to communication test set via feed-through attenuators. The EUT was placed inside the temperature chamber. The DC leads and RF output cable exited the chamber through an opening made for the purpose.

After the temperature stabilized for approximately 20 minutes, the frequency output was recorded from the communication test set.

Frequency Stability vs. Voltage: For hand carried, battery powered equipment; reduce primary supply voltage to the battery operating end point which shall be specified by the manufacturer.



Test Equipment List and Details

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
ESPEC	Temperature & Humidity Chamber	EL-10KA	09107726	2012-11-02	2013-11-01
Rohde & Schwarz	Universal Radio Communication Tester	CMU200	106891	2012-12-01	2013-12-01

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to NVLAP requirements, traceable to National Primary Standards and International System of Units (SI).

Test Data**Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	56 %
ATM Pressure:	100.0 kPa

The testing was performed by Gardon Zhang on 2013-02-01.

EUT operation mode: Transmitting

Test Result: Compliance. Please refer to the following tables.

GSM (GMSK) mode

Cellular Band (Part 22H)

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	13	0.0155	2.5
40		11	0.0131	2.5
30		16	0.0191	2.5
20		15	0.0179	2.5
10		18	0.0215	2.5
0		10	0.0120	2.5
-10		9	0.0108	2.5
-20		14	0.0167	2.5
-30		12	0.0143	2.5
20		V _{min.} = 3.5	16	0.0191
20	V _{max.} = 4.2	14	0.0167	2.5

PCS Band (Part 24E)

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	11	0.0059	Pass
-20		15	0.0080	Pass
-10		13	0.0069	Pass
0		16	0.0085	Pass
10		17	0.0090	Pass
20		12	0.0064	Pass
30		10	0.0053	Pass
40		14	0.0074	Pass
50		17	0.0090	Pass
20		V _{min.} = 3.5	15	0.0080
20	V _{max.} = 4.2	10	0.0053	Pass

GSM (8PSK) mode

Cellular Band (Part 22H)

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
50	3.7	25	0.0299	2.5
40		23	0.0275	2.5
30		26	0.0311	2.5
20		27	0.0323	2.5
10		28	0.0335	2.5
0		21	0.0251	2.5
-10		23	0.0275	2.5
-20		26	0.0311	2.5
-30		20	0.0239	2.5
20		V _{min.} = 3.5	26	0.0311
20	V _{max.} = 4.2	29	0.0347	2.5

PCS Band (Part 24E)

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	31	0.0165	Pass
-20		28	0.0149	Pass
-10		29	0.0154	Pass
0		32	0.0170	Pass
10		34	0.0181	Pass
20		30	0.0160	Pass
30		30	0.0160	Pass
40		32	0.0170	Pass
50		35	0.0186	Pass
20		V _{min.} = 3.5	36	0.0191
20	V _{max.} = 4.2	32	0.0170	Pass

WCDMA mode

Cellular Band (Part 22H)

Middle Channel, $f_0 = 836.6$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	18	0.0215	2.5
-20		20	0.0239	2.5
-10		17	0.0203	2.5
0		22	0.0263	2.5
10		21	0.0251	2.5
20		24	0.0287	2.5
30		20	0.0239	2.5
40		23	0.0275	2.5
50		19	0.0227	2.5
25		V _{min.} = 3.5	12	0.0143
25	V _{max.} = 4.2	13	0.0155	2.5

PCS Band (Part 24E)

Middle Channel, $f_0 = 1880.0$ MHz				
Temperature (°C)	Power Supplied (V _{DC})	Frequency Error (Hz)	Frequency Error (ppm)	Limit (ppm)
-30	3.7	9	0.0048	Pass
-20		10	0.0053	Pass
-10		8	0.0043	Pass
0		11	0.0059	Pass
10		7	0.0037	Pass
20		10	0.0053	Pass
30		9	0.0048	Pass
40		13	0.0069	Pass
50		12	0.0064	Pass
25		V _{min.} = 3.5	9	0.0048
25	V _{max.} = 4.2	10	0.0053	Pass

******* END OF REPORT *******