

FCC RF EXPOSURE REPORT

For

Amcrest SmartHome 2MP Wi-Fi Bullet Outdoor Security Camera

MODEL NUMBER: ASH22-W

PROJECT NUMBER: 4790425401-2.4

REPORT NUMBER: 4790425401-2.4-2

FCC ID: ZZ2-ASH22

ISSUE DATE: Aug. 12, 2022

Prepared for

Amcrest Technologies LLC.

Prepared by

UL-CCIC COMPANY LIMITED No. 2, Chengwan Road, Suzhou Industrial Park, People's Republic of China Tel: +86 512-6808 6400 Fax: +86 512-6808 4099 Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By
V0	08/12/2022	Initial Issue	



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	4
2.	TEST METHODOLOGY	5
3.	FACILITIES AND ACCREDITATION	5
4.	MEASUREMENT UNCERTAINTY	6
5.	REQUIREMENT	7



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name:	Amcrest Technologies LLC.
Address:	16727 Park Row Dr, Houston, TX 77084, United States of America
Manufacturer Information	
Company Name:	Amcrest Technologies LLC.
Address:	16727 Park Row Dr, Houston, Texas, 77084, United States
EUT Description	
Product Name:	Amcrest SmartHome 2MP Wi-Fi Bullet Outdoor Security Camera
Model Name:	ASH22-W
Sample Number:	5040307
Data of Receipt Sample:	Jun. 09, 2022
Test Date:	Jun. 09, 2022 ~ Aug. 09, 2022

APPLICABLE STANDARDS					
STANDARD	TEST RESULTS				
FCC Guidelines for Human Exposure IEEE	Complies				
C95.1					

Prepared By:

Tom Tang

Tom Tang

Reviewed By:

Leon Wu

Leon Wu

Authorized By:

Chris Zhong

Chris Zhong Laboratory Leader



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06 and FCC Guidelines for Human Exposure IEEE C95.1.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 25056) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
------------------------------	--

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, People's Republic of China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.



4. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty			
Output Power to Antenna	3.1 dB			
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.				

5. REQUIREMENT

<u>LIMIT</u>

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure						
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm ²)	Averaging Time E ² , H ² or S (minutes)		
0.3-1.34	614	1.63	(100)*	30		
1.34-30	824/f	2.19/f	(180/f2)*	30		
30-300	27.5	0.073	0.2	30		
300-1500			f/150	30		
1500-100,000			1.0	30		
Note 1: f = frequency in MHz, * means Plane-wave equivalent power density						

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm² is available for this EUT.

MPE CALCULATION METHOD

$S = PG/(4\pi R2)$

where: S = power density (in appropriate units, e.g. mW/ cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



CALCULATED RESULTS

WIFI (Worst case)							
Mode	Output Power to Antenna		Antenna Gain		Power Density	Limit	Test Result
11b	(dBm)	(mW)	(dBi)	(Numeric)	(mW/cm2)	(mW/cm2)	
	13.5	22.39	1.79	1.51	0.0067	1	Complies

Radio Frequency Radiation Exposure Evaluation

Note:

- 1. The output power to antenna and antenna gain are from OD.
- 2. The minimum separation distance of the device is greater than 20 cm.
- 3. All the modes and channels had been tested, but only the worst data was recorded in the report.
- 4. The calculated result for the sample received is <Pass> according to < 47 CFR FCC Part 2 Subpart J, section 2.1091> when <Accuracy Method> decision rule is applied.



END OF REPORT

Form-ULID-008536-12 V2.0