

FCC RF EXPOSURE REPORT

For

1080P Pan/Tilt Wi-Fi Indoor Security Camera

MODEL NUMBER: IP2M-841B-V3

ADDTIONAL MODEL NUMBER: IP2M-841W-V3

PROJECT NUMBER: 4790465786-2

REPORT NUMBER: 4790465786-2-2

FCC ID: ZZ2-IP2M-841-V3

ISSUE DATE: Jul. 20, 2022

Prepared for

Amcrest Technologies LLC.

Prepared by

UL-CCIC COMPANY LIMITED No. 2, Chengwan Road, Suzhou Industrial Park, People's Republic of China Tel: + 86-512-6808 6400 Fax: + 86-512-6808 4099 Website: www.ul.com



Revision History

Rev.	Issue Date	Revisions	Revised By		
V0	07/20/2022	Initial Issue			



TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	.4
2.	TEST METHODOLOGY	.5
3.	FACILITIES AND ACCREDITATION	.5
4.	MEASUREMENT UNCERTAINTY	.6
5.	REQUIREMENT	.7



1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Address:	Amcrest Technologies LLC. 16727 Park Row Dr, Houston, America	TX 77084,	United States of
Manufacturer Information Company Name: Address:	Amcrest Technologies LLC. 16727 Park Row Dr, Houston, America	TX 77084,	United States of

EUT Description

nera
1

APPLICABLE STANDARDS					
STANDARD	TEST RESULTS				
FCC 47CFR§2.1091	Complies				
KDB-447498 D01 V06	Complies				

Prepared By:

Tom Tang

Reviewed By:

Tom Tang

Leon Wu

Leon Wu

Authorized By:

Chris Zhong

Chris Zhong EMC&RF Lab Operations Manager



2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 4829.01) UL-CCIC COMPANY LIMITED has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1247) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules. IC (IC Designation No.: 25056; CAB No.: CN0073) UL-CCIC COMPANY LIMITED has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules.
------------------------------	---

Note 1: All tests measurement facilities use to collect the measurement data are located at No. 2, Chengwan Road, Suzhou Industrial Park, Suzhou 215122, People's Republic of China

Note 2: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. These measurements below 30MHz had been correlated to measurements performed on an OFS.

Note 3: The test anechoic chamber in UL-CCIC COMPANY LIMITED had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.



4. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty				
Output Power to Antenna	0.69 dB				
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.					

5. REQUIREMENT

<u>LIMIT</u>

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure							
Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	PowerDensity (S) (mW/cm²)	Averaging Time E ² , H ² or S (minutes)				
614	1.63	(100) *	30				
824/f	2.19/f	(180/f2) *	30				
27.5	0.073	0.2	30				
		f/150	30				
		1.0	30				
Note 1: f = frequency in MHz, * means Plane-wave equivalent power density							
	Electric Field Strength (E) (V/m) 614 824/f 27.5 cy in MHz, * mea	Electric Field Strength (E) (V/m)Magnetic Field Strength (H) (A/m)6141.63824/f2.19/f27.50.073cy in MHz, * means Plane-wave equiv	Electric Field Strength (E) (V/m) Magnetic Field Strength (H) (A/m) PowerDensity (S) (mW/cm²) 614 1.63 (100) * 824/f 2.19/f (180/f2) * 27.5 0.073 0.2 f/150 1.0 1.0				

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.

Note 3: The limit value 1.0mW/cm² is available for this EUT.

MPE CALCULATION METHOD

S =PG/(4πR2)

where: S = power density (in appropriate units, e.g. mW/ cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)



CALCULATED RESULTS

WIFI (Worst case)									
Mode	Frequency	•	Power to enna	Antenna Gain		Power Density	Limit	Verdict	
	(MHz)	(dBm)	(mW)	(dBi)	(Numeric)	(mW/cm2)	(mW/cm2)	, er allet	
11b	2412	12.5	17.78	2.84	1.92	0.0068	1	Complies	

Note:

- 1. The output power to antenna is from OD document and antenna gain are from report antenna spec. document provided by customer.
- 2. The minimum separation distance of the device is greater than 20 cm.
- 3. All the modes and channels had been tested, but only the worst data was recorded in the report.
- 4. The calculated result for the sample received is <Pass> according to < 47 CFR FCC Part 2 Subpart J, section 2.1091> when <Accuracy Method> decision rule is applied.

END OF REPORT