



ELECTRONICS

EMI TEST REPORT

FCC Part 15 Subpart B, Class B

Product : Inkjet Printer
Model No. : 1400P

JOB NO. : KE-01-0348

1. This test reports shall not be reproduced except in full, without the written approval of SEC EMC Testing laboratory.
2. This test reports does not constitute an endorsement by NIST/NVLAP or U.S Government.
3. This test report is to certify that the tested device properly complies with the requirements of FCC Rules and Regulations Part 15 Subpart B Unintentional Radiators.
All tests necessary to show compliance to the requirements were and these results met the specifications requirement.

Date of test : July 5, 2001

Issued Date : July 7, 2001

Prepared by: Kyeong Dong, Kim
Kyeong Dong, Kim / Test Engineer

Reviewed by: Chun Kil, Kim
Chun Kil, Kim / Technical Manager

Authorised by: Yang Su, Kim
Yang Su, Kim / Quality Manager

This laboratory is registered by the NIST/NVLAP, U.S.A.
The test reported herein have been performed in accordance with its terms of registration.



Table of Contents

1. General Information

- 1.1 Product Description
- 1.2 Tested System Details
- 1.3 Test Methodology
- 1.4 Test Facility

2. System Test Configuration

- 2.1 Operation Environment
- 2.2 Justification
- 2.3 EUT Exercise Software
- 2.4 Test Procedure
- 2.5 Test System configuration

3. Conducted and Radiated Measurement Photos

- 3.1 Conducted Measurement Photos
- 3.2 Radiated Measurement Photos

4. Measurement Uncertainty

- 4.1 Conducted Emission Test
- 4.2 Radiated Emission Test

5. Conducted Emission Test Data

6. Radiated Emission Test Data

7. Label and Label Location

8. Test Equipment Used

1. General Information

APPLICANT : SAMSUNG ELECTRONICS CO., LTD.

ADDRESS : 416, Maetan-3Dong, Paldal-Gu
Suwon-City, Kyungki-Do, Korea 442-742

CONTACT PERSON : Jae Hong, Park
TEL. +82-31-200-4166

CONTACT ADDRESS : 416, Maetan-3Dong, Paldal-Gu
Suwon-City, Kyungki-Do, Korea 442-742

REGULATION(S) : FCC Part 15 Subpart B, Class B

MODEL NUMBER : 1400P

SERIAL NUMBER : -

KIND OF PRODUCT : Inkjet Printer

TESTED DATE : July 5, 2001

TEST SITE : 3meter semi-anechoic chamber

TEST SITE ADDRESS : San 14, Nongseo-Ri, Kihung-Eup,
Yongin-City, Kyungki-Do, Korea, 449-900

1.1 Product Description

The Samsung 1400P print at 600x300(VerticalxHorizontal)dots per inch class, monochrome 14 pages-per-minute.

Standard 100 sheet automatic input tray support various sizes,types.

Main System Clock is 66MHz, Image Processor clock 48MHz and USB clock 48MHz.

Power rating is AC120~127V and less than 30W Power consumption during operation and less than 1 in sleep mode. See the attached 1400P User's Guide for more information.

1.2 Tested System Details

The FCC IDs for all equipment, plus descriptions of all products used in the tested system are:

Device Type	Manufacturer	Model Number	Serial No.	FCC ID / DoC
(1) Inkjet Printer (EUT)	Samsung	1400P	N/A	A3L1400P
(2) PC	SAMSUNG	TD260-DT	C92DK409981	FCC DoC
(3) Monitor	Samsung	SyncMaster 17GLsi	H3MF400637	FCC DoC
(4) Keyboard	Samsung	5900	K09141644	FCC DoC
(5) Mouse	Logitech	M-SAS51	LZB00478743	JNZ211167
(6) External Modem	US Robotics	SPORTSTER	33083962	CJE-0149-217
(7) AC/DC Adaptor	Sigma Telecom	STC-30100U	N/A	-
(8) AC/DC Adaptor	Skynet	DND-3012	N/A	-

1.3 Test Methodology

Both conducted and radiated testing were performed according to the procedures in FCC/ANSI C63.4(1992).

Radiated testing was performed at a distance of 3 meters from the antenna to EUT.

1.4 Test Facility

All test described in this report were performed by :

Open area test site : 781-14, Chung-Ri, Dongtan-Myun, Hwasung-Kun, Kyungki-Do, Korea

Conducted measurement facility and 3meter Semi-anechoic chamber :

San 14, Nongseo-Ri, Kihung-Eup, Yongin-City, Kyungki-Do, Korea, 449-900

12W

2. System Test Configuration

2.1 Operation Environment

	Conduction	Radiation
Temperature [] :	24	23
Humidity [%] :	47	50
Power supply :	AC115V/60Hz	AC115V/60Hz

2.2 Justification

The system was configured in typical fashion(as a customer would normally use it) for testing.

2.3 EUT Exercise Software

The EUT exercise program used during radiated and conducted testing is word editor(Hun2000).Type H character on document 10 page and then execute print to EUT continuously.

2.4 Test Procedure

2.4.1 Conducted Emissions

EUT was placed on a platform of nominal size, 1m by 1.5m, raised 80cm above the conducting ground plane. The rear of tabletop was located 40cm to the vertical conducting ground plane.

The rear of EUT, including peripherals was aligned and flush with rear of tabletop. All other surfaces of tabletop was at least 80cm from any other grounded conducting surface. I/O cables and AC cables that were connected to the peripherals were bundled in center. They were folded back and forth forming a bundle 30cm to 40cm long and were hanged at a 40cm height to the ground plane.

Each EUT current-carrying power lead, except the ground(safety) lead, were individually connected through a LISN to the input power source.

All unused 50 ohm connectors of the LISN were resistively terminated in 50 ohm when not connected to the measuring equipment.

2.4.2 Radiated Emissions

EUT was placed on a platform of nominal size, 1m by 1.5m, raised 80cm above the conducting ground plane.

The rear of EUT, including peripherals was aligned and flush with rear of tabletop.


I/O cables that were connected to the peripherals were bundle in center.

They were folded back and forth forming a bundle 30cm to 40cm long and were hanged 40cm height to the ground plane.

Test was made with the antenna positioned in both the horizontal and vertical planes of polarization. The measurement antenna was varied in height above the conducting ground plane to obtain the maximum signal strength.

2.5 Test System configuration

2.5.1 System Block Diagram of Test Configuration



2.5.2 Configuration of EUT and peripherals

Mark	Item	Model No.	Serial No.	Manufacturer	Remark
A	Desktop computer	TD260-DT	C92DK409981	Samsung	
B	External Modem	SPORTSTER	33083962	US ROBOTICS	
C	Monitor	SyncMaster 17GLsi	H3MF400637	Samsung	
D	Inkjet Printer	1400P	-	Samsung	EUT
E	PS/2 Mouse	M-SAS51	LZB00478743	Logitech	
F	Keyboard	5900	K09141644	Samsung	
G	AC/DC Adaptor	AW-1220A	-	US ROBOTICS	
H	AD/DC Adaptor	STC-30100U	-	Sigma Telecom	

2.5.3 Used Cable Description

No.	Item	Length[m]	Shielded(Y/N)	Remark
1	AC Power cable	1.7	N	
2	Video cable	1.8	Y	
3	Serial cable	3.0	Y	
4	Mouse cable	2.0	Y	
5	USB cable	1.8	Y	
6	Keyboard Cable	1.7	Y	
7	DC Power cable	1.7	N	
8	AC Power cable	1.7	N	
9	AC Power cable	1.7	N	
10	AC Power cable	1.7	N	
11	DC Power cable	1.5	N	

4. Measurement Uncertainty

All data in report are to be traceability to the national or international standards.

4.1 Conducted Emission Test

The measurement uncertainty(with a 95% confidence level)for this test was $\pm 2.08\text{dB}$.

The data listed in this test report may exceed the test limit because it does not have enough margin(more than 2.0dB).

The data listed in this test report has enough margin, more than 2.08dB.

4.2 Radiated Emission Test

The measurement uncertainty(with a 95% confidence level)for this test was as follow
30MHz~200MHz : ± 4.50 200MHz~1000MHz : ± 5.23

The data listed in this test report may exceed the test limit because it does not have enough margin(more than 2.0dB).

The data listed in this test report has enough margin, more than 3.4dB.

5. Conducted Emission Test Data

The initial step in collecting conducted data was to perform a quasi-peak scan over the measurement range using a spectrum analyzer. All modes of operation(USB mode only) were investigated and the worst case emission(the emission in printing on USB connection) was reported. All other emission are non-significant.

The minimum margin to the limit is as follows :

Frequency : 4.216 [MHz]
 Meter Reading : 31.23 [dBuV]
 LISN Loss : 0.23 [dB]
 Cable loss : 0.6 [dB]
 Corrected Readings : 32.06 [dBuV/m]
 Margin : -15.90 [dB]

Test Data Sheet

Tested Frequency [MHz]	Meter Reading [A] [dBuV]	LISN Pol. [L1/L2]	Factor[B]		Corrected Reading [A+B] [dBuV/m]	Limits [dBuV/m]	Margin [dB]
			LISN Loss [dB]	Cable Loss [dB]			
3.180	22.40	L1	0.20	0.40	23.00	47.96	-24.96
4.106	31.01	L1	0.23	0.60	31.84	47.96	-16.12
4.216	31.23	L2	0.23	0.60	32.06	47.96	-15.90
4.990	28.40	L1	0.25	0.60	29.25	47.96	-18.71
7.230	18.80	L1	0.30	0.50	19.60	47.96	-28.36
11.990	25.20	L2	0.39	0.70	26.29	47.96	-21.67
27.500	21.30	L2	0.73	1.00	23.03	47.96	-24.93

- * All readings are quasi-peak mode.
- * Set resolution bandwidth to 9kHz minimum.
- * Results = Meter Reading + LISN Insertion loss + Cable loss
- * Margin = Corrected Reading - Limits
- * L1 = Hot, L2 = Neutral

6. Radiated Emission Test Data

The initial step in collecting conducted data was to perform a quasi-peak scan over the measurement range using a spectrum analyzer. All modes of operation(USB mode only) were investigated and the worst case emission(the emission in printing on USB connection) was reported. All other emission are non-significant.

The minimum margin to the limit is as follows :

Frequency : **429.40** [MHz]
 Meter Reading : **25.0** [dBuV]
 Antenna Factor : **14.10** [dB]
 Cable loss : **2.20** [dB]
 Corrected Reading : **41.3** [dBuV/m]
 Margin : **-4.70** [dB]

Test Data Sheet

Frequency Range [MHz]	Tested Frequency [MHz]	Ant. Pol.	Meter Reading [A] [dBuV]	Factor[B]		Antenna Height [Cm]	Turn table Degree [Deg]	Corrected Reading [A+B] [dBuV/m]	Margin [dB]	Limits [3m] [dBuV/m]
				Ant. Factor	Cable Loss					
				[dB]						
30 - 88										40
88 - 216										43.5
216 - 960	240.0	H	26.20	9.00	1.46	100	60	36.66	-9.34	46
	266.0	H	20.40	9.90	1.50	130	70	31.80	-14.20	
	335.9	V	26.90	12.10	1.76	150	140	40.76	-5.24	
	336.3	V	23.10	12.10	1.76	130	150	36.96	-9.04	
	384.2	V	23.50	13.10	2.04	130	120	38.64	-7.36	
	397.0	V	24.20	13.50	2.10	130	175	39.80	-6.20	
	429.4	V	25.00	14.10	2.20	150	135	41.30	-4.70	
	432.0	V	24.20	14.20	2.20	150	120	40.60	-5.40	
	465.4	H	18.20	14.80	2.26	100	75	35.26	-10.74	
	664.9	H	14.30	18.10	2.68	100	60	35.08	-10.92	
960 -										54

* "<" Means equal or less than * All readings are quasi-peak mode.

* The selected bandwidth in emission testing is 100kHz.

* Corrected Reading = Meter Reading + Antenna Factor + Cable loss

* Margin = Corrected Reading - Limits

* H = Horizontal Polarization/Antenna, V = Vertical Polarization/Antenna

8. Test Equipment Used

Equipment	Model No.	Serial No.	Makers	Last calibration and Interval
Spectrum analyzer	8568B	2841A04394	H.P	00/11/02, 12Months
		Firmware versions : REV 7.4.87		
Quasi-peak adapter	85650A	2811A01182	H.P	00/11/16, 12Months
RF Preselector	85685A	2837A00835	H.P	00/11/16, 12Months
EMI Test Receiver	ESCS30	830986/004	R & S	01/01/06, 12Months
		F/W ver. : N/A		
L.I.S.N	ESH2-Z5	831886/006	R & S	00/11/30, 12Months
	3825/2	1408	EMCO	00/11/11, 12Months
Biconilog Antenna	HL 562	361324/003	R & S	01/01/22, 12Months
EMI Measurement Software	HP	Firmware versions : Rev. A.00.00		