

3.5 EUT Description

The following features describe EUT represented by this report:

Item	Specification	Remarks
Processor	CHORUS4(600MHz)	-
Standard System memory	128MB DDR2 SDRAM	-
Resolution	True 600x600dpi (Up to 1,200x1,200dpi effective output)	-
Paper Handling	Paper Tray(standard) 250Sheets Manual Tray 50Sheet	-
Power Rating	110~127VAC, 6.5A, 50/60Hz	-
Power Consumption	Sleep mode : 2.5Watts Ready mode : 60Watts Printing mode: 550Watts	-
Printer Language	PostScript3, PCL6/5e, IBM ProPrinter, EPSON	-
PC Interfaces	USB2.0, NW, Wireless LAN	-
OS compatibility	Windows 2000/XP(32/64bits)/ Vista(32/64bits)/2003 Server(32/64bits)/2008 Server(32/64bits)/ 7(32/64bit)/2008 Server R2 Various Linux OS: Fedora Core 4, 5, 6 Fedora 7, 8, 9, 10, 11, 12 RedHat Enterprise Linux WS 4, 5 SuSE 10.0, 10.1 openSuSE 10.2, 10.3, 11.0, 11.1, 11.2 SuSE Linux Enterprise Desktop 10, 11 Debian 4.0, 5.0 Ubuntu 5.04, 5.10, 6.04, 6.10, 7.04, 7.10, 8.04, 8.10, 9.04, 9.10 Mandriva 2005LE, 2006, 2007, 2007.1, 2008, 2008.1, 2009, 2009.1	-
Modes of Operation	USB Printing, 1200dpi Printing, Network Printing, Wireless LAN Printing	-
Intended Class for Emissions	Class B	-