

SAMSUNG FCC ID : A3LSCHS109 835MHz CDMA Head SAR

DUT: SCH-S109; Serial: FD-028-B

Program Name: SCH-S109 CDMA Right (Job No. : FD-028)

Procedure Name: Cheek/Touch, Ch.1013, Intenna, Bat. Standard

Procedure Notes: Meas. Ambient Temp(celsius) -22.4; Tissue Temp(celsius) -21.9; Test Date -10/Mar/2006 [OET Bulletin 65-Supplement C, July 2001]

Communication System: CDMA; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 824.7$ MHz; $\sigma = 0.91$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3017; ConvF(6.14, 6.14, 6.14); Calibrated: 2005-09-20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn486; Calibrated: 2005-08-30
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1248
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Cheek/Touch, Ch.1013, Intenna, Bat. Standard/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 30.9 V/m; Power Drift = -0.193 dB

Peak SAR (extrapolated) = 1.77 W/kg


SAR(1 g) = 1.24 mW/g

Maximum value of SAR (measured) = 1.33 mW/g

Cheek/Touch, Ch.1013, Intenna, Bat. Standard/Area Scan (51x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.42 mW/g



0 dB = 1.42mW/g

SAMSUNG FCC ID : A3LSCHS109 835MHz CDMA Head SAR

DUT: SCH-S109; Serial: FD-028-B

Program Name: SCH-S109 CDMA Right (Job No. : FD-028)

Procedure Name: Ear/Tilt, Ch.0384, Intenna, Bat. Standard

Procedure Notes: Meas. Ambient Temp(celsius) -22.4; Tissue Temp(celsius) -21.9; Test Date -10/Mar/2006 [OET Bulletin 65-Supplement C, July 2001]

Communication System: CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 836.52 \text{ MHz}$; $\sigma = 0.91 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Right Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3017; ConvF(6.14, 6.14, 6.14); Calibrated: 2005-09-20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn486; Calibrated: 2005-08-30
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1248
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Ear/Tilt, Ch.0384, Intenna, Bat. Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.679 mW/g


Ear/Tilt, Ch.0384, Intenna, Bat. Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 24.6 V/m; Power Drift = -0.125 dB

Peak SAR (extrapolated) = 0.860 W/kg

SAR(1 g) = 0.615 mW/g

Maximum value of SAR (measured) = 0.658 mW/g



0 dB = 0.658mW/g

SAMSUNG FCC ID : A3LSCHS109 835MHz CDMA Head SAR

DUT: SCH-S109; Serial: FD-028-B

Program Name: SCH-S109 CDMA Left (Job No. : FD-028)

Procedure Name: Cheek/Touch, Ch.1013, Intenna, Bat. Standard

Procedure Notes: Meas. Ambient Temp(celsius)-22.4; Tissue Temp(celsius)-21.9; Test Date-10/Mar/2006[OET Bulletin 65-Supplement C, July 2001]

Communication System: CDMA; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 824.7$ MHz; $\sigma = 0.91$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3017; ConvF(6.14, 6.14, 6.14); Calibrated: 2005-09-20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn486; Calibrated: 2005-08-30
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1248
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Cheek/Touch, Ch.1013, Intenna, Bat. Standard/Area Scan (51x71x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.37 mW/g

Cheek/Touch, Ch.1013, Intenna, Bat. Standard/Zoom Scan (5x5x7)/Cube 0:


Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.6 V/m; Power Drift = -0.170 dB

Peak SAR (extrapolated) = 1.77 W/kg

SAR(1 g) = 1.24 mW/g

Maximum value of SAR (measured) = 1.32 mW/g



0 dB = 1.32mW/g

SAMSUNG FCC ID : A3LSCHS109 835MHz CDMA Head SAR

DUT: SCH-S109; Serial: FD-028-B

Program Name: SCH-S109 CDMA Left (Job No. : FD-028)

Procedure Name: Ear/Tilt, Ch.0384, Intenna, Bat. Standard

Procedure Notes: Meas. Ambient Temp(celsius) -22.4; Tissue Temp(celsius) -21.9; Test Date -10/Mar/2006 [OET Bulletin 65-Supplement C, July 2001]

Communication System: CDMA; Frequency: 836.52 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 836.52 \text{ MHz}$; $\sigma = 0.91 \text{ mho/m}$; $\epsilon_r = 41.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3017; ConvF(6.14, 6.14, 6.14); Calibrated: 2005-09-20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn486; Calibrated: 2005-08-30
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1248
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Ear/Tilt, Ch.0384, Intenna, Bat. Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 0.642 mW/g


Ear/Tilt, Ch.0384, Intenna, Bat. Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 22.9 V/m; Power Drift = 0.162 dB

Peak SAR (extrapolated) = 0.815 W/kg

SAR(1 g) = 0.579 mW/g

Maximum value of SAR (measured) = 0.613 mW/g



0 dB = 0.613mW/g

SAMSUNG FCC ID : A3LSCHS109 835MHz CDMA Body SAR

DUT: SCH-S109; Serial: FD-028-B

Program Name: SCH-S109 CDMA Body (Job No. : FD-028)

Procedure Name: Body, Ch. 0777, Ant. Intenna, Bat. Standard

Procedure Notes: Meas. Ambient Temp(celsius) -22.0; Tissue Temp(celsius) -21.9; Test Date -10/Mar/2006 [OET Bulletin 65-Supplement C, July 2001]

Communication System: CDMA; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 848.31 \text{ MHz}$; $\sigma = 0.99 \text{ mho/m}$; $\epsilon_r = 53.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3017; ConvF(6.18, 6.18, 6.18); Calibrated: 2005-09-20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn486; Calibrated: 2005-08-30
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1247
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Body, Ch. 0777, Ant. Intenna, Bat. Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid: $dx=8\text{mm}$, $dy=8\text{mm}$, $dz=5\text{mm}$

Reference Value = 29.3 V/m; Power Drift = -0.103 dB

Peak SAR (extrapolated) = 1.78 W/kg


SAR(1 g) = 1.3 mW/g

Maximum value of SAR (measured) = 1.38 mW/g

Body, Ch. 0777, Ant. Intenna, Bat. Standard/Area Scan (51x71x1): Measurement grid:

$dx=20\text{mm}$, $dy=20\text{mm}$

Maximum value of SAR (interpolated) = 1.45 mW/g



0 dB = 1.45mW/g

SAMSUNG FCC ID : A3LSCHS109 835MHz CDMA Head SAR

DUT: SCH-S109; Serial: FD-028-B

Program Name: SCH-S109 CDMA Left (Job No. : FD-028)

Procedure Name: Cheek/Touch, Ch.1013, Intenna, Bat. Standard

Procedure Notes: Meas. Ambient Temp(celsius) -22.4; Tissue Temp(celsius) -21.9; Test Date -10/Mar/2006 [OET Bulletin 65-Supplement C, July 2001]

Communication System: CDMA; Frequency: 824.7 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 824.7$ MHz; $\sigma = 0.91$ mho/m; $\epsilon_r = 41.2$; $\rho = 1000$ kg/m³

Phantom section: Left Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3017; ConvF(6.14, 6.14, 6.14); Calibrated: 2005-09-20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn486; Calibrated: 2005-08-30
- Phantom: SAM PHANTOM #2; Type: SAM; Serial: TP-1248
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Cheek/Touch, Ch.1013, Intenna, Bat. Standard/Area Scan (51x71x1): Measurement grid: dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.37 mW/g

Cheek/Touch, Ch.1013, Intenna, Bat. Standard/Zoom Scan (5x5x7)/Cube 0:

Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 28.6 V/m; Power Drift = -0.170 dB

Peak SAR (extrapolated) = 1.77 W/kg

SAR(1 g) = 1.24 mW/g

Maximum value of SAR (measured) = 1.32 mW/g



SAMSUNG FCC ID : A3LSCHS109 835MHz CDMA Body SAR

DUT: SCH-S109; Serial: FD-028-B

Program Name: SCH-S109 CDMA Body (Job No. : FD-028)

Procedure Name: Body, Ch. 0777, Ant. Intenna, Bat. Standard

Procedure Notes: Meas. Ambient Temp(celsius) -22.0; Tissue Temp(celsius) -21.9; Test Date-10/Mar/2006 [OET Bulletin 65-Supplement C, July 2001]

Communication System: CDMA; Frequency: 848.31 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 848.31$ MHz; $\sigma = 0.99$ mho/m; $\epsilon_r = 53.8$; $\rho = 1000$ kg/m³

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ES3DV2 - SN3017; ConvF(6.18, 6.18, 6.18); Calibrated: 2005-09-20
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn486; Calibrated: 2005-08-30
- Phantom: SAM PHANTOM #1; Type: SAM; Serial: TP-1247
- Measurement SW: DASY4, V4.6 Build 23; Postprocessing SW: SEMCAD, V1.8 Build 160

Body, Ch. 0777, Ant. Intenna, Bat. Standard/Zoom Scan (5x5x7)/Cube 0: Measurement grid: dx=8mm, dy=8mm, dz=5mm

Reference Value = 29.3 V/m; Power Drift = -0.103 dB

Peak SAR (extrapolated) = 1.78 W/kg

SAR(1 g) = 1.3 mW/g

Maximum value of SAR (measured) = 1.38 mW/g

Body, Ch. 0777, Ant. Intenna, Bat. Standard/Area Scan (51x71x1): Measurement grid:

dx=20mm, dy=20mm

Maximum value of SAR (interpolated) = 1.45 mW/g

