

1) Please include details of user modes for frequency response compliance in the test report such as in section IV to fully explain the test configuration.

Please find attached revised report including details of user modes for frequency response compliance in the test report on Page 21.

2) It appears that the T-coil is offset from the speaker. The RF scan should be made centered on the T-coil. Please readdress the RF T-coil emission category. Please provide test data with the scan properly centered.

Please see below data with RF scan data centered on the T-coil for the worst-case configurations. The RT category is M3.



Peak E-field in V/m

Grid 1	Grid 2	Grid 3
169.3	198.5	193.1
Grid 4	Grid 5	Grid 6
170.9	218.9	218.1
Grid 7	Grid 8	Grid 9
154.1	197.2	197.0



Cellular E-field – Max 218.9 V/m (M3)

Peak H-field in A/m

Grid 1	Grid 2	Grid 3
0.300	0.211	0.130
Grid 4	Grid 5	Grid 6
0.295	0.211	0.131
Grid 7	Grid 8	Grid 9
0.275	0.197	0.124



Cellular H-field – Max 0.211 A/m (M4)

Peak E-field in V/m

Grid 1	Grid 2	Grid 3
61.6	41.6	36.6
Grid 4	Grid 5	Grid 6
52.0	35.0	35.0
Grid 7	Grid 8	Grid 9
32.6	27.3	28.8



PCS E-field – Max 61.6 V/m (M3)

Peak H-field in A/m

Grid 1	Grid 2	Grid 3
0.124	0.113	0.091
Grid 4	Grid 5	Grid 6
0.117	0.105	0.090
Grid 7	Grid 8	Grid 9
0.091	0.076	0.073



PCS H-field – Max 0.124 A/m (M4)

3) Please provide configuration details for figures 6-1 and Section V.

Please find attached revised report including configuration details for figures 6-1 and Section V on Page 21.

4) Please send details explaining figure 6-2. Also, please provide ambient noise levels for both ABM1 and ABM2 measurements.1) Please explain how the voltages in Table 5.3 were derived for both GSM and UMTS.

Please find attached revised report with details regarding figure 6-2 and ambient noise levels for ABM1 and ABM2 measurements in Table 6-4 on Page 20.