


## 4. Maximum Peak Output Power Measurement

### 4.1. Test Setup



### 4.2. Limit

According to §15.247(b)(3), for systems using digital modulation in the 902 ~ 928 MHz, 2 400 ~2 483.5 MHz, and 5 725 ~ 5 850 MHz band: 1 Watt. As an alternative to a peak power measurement, compliance with the one watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antenna elements. The average must not include any intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

According to §15.247(b)(4), the conducted output power limit specified in paragraph(b) of this section is based on the use of antenna with directional gains that do not exceed 6 dBi. Except as shown in paragraph(c) of this section, if transmitting antenna of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraph (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6dBi.

### 4.3. Test Procedure

#### 4.3.1. 11b, g, n\_HT20

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the Power sensor.
3. Test program : (S/W name : R&S Power Viewer, Version : 3.2.0)
4. Measure peak & average power each channel.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

#### 4.4. Test Results

Ambient temperature : (24 ± 2) °C

Relative humidity : 47 % R.H.

Mode	Channel	Channel Frequency (MHz)	Data Rate (Mbps)	Attenuator + Cable offset (dB)	Average power Result (dB m)	Peak Power Result (dB m)
DSSS (802.11b)	Low	2 412	1	21.33	15.06	17.26
			2		15.07	17.32
			5.5		15.13	17.43
			11		<u>15.14</u>	<u>17.44</u>
	Middle	2 437	1	21.17	15.41	17.55
			2		15.40	<u>17.58</u>
			5.5		<u>15.43</u>	17.58
			11		15.42	17.54
	High	2 462	1	21.24	15.36	17.54
			2		15.39	17.57
			5.5		15.42	17.58
			11		<u>15.43</u>	<u>17.59</u>
OFDM (802.11g)	Low	2 412	6	21.33	11.23	20.07
			9		11.20	19.61
			12		11.17	19.96
			18		11.21	19.28
			24		11.17	20.15
			36		11.25	19.67
			48		12.98	<u>20.19</u>
			54		<u>13.06</u>	19.99
	Middle	2 437	6	21.17	11.59	20.03
			9		11.62	19.70
			12		11.61	20.18
			18		11.58	19.91
			24		11.52	20.14
			36		11.59	20.23
			48		<u>12.91</u>	20.41
			54		12.86	<u>20.50</u>
	High	2 462	6	21.24	11.65	20.17
			9		11.64	19.83
			12		11.58	20.29
			18		11.62	19.56
			24		11.68	20.46
			36		11.59	19.92
			48		<u>13.37</u>	<u>20.41</u>
			54		13.30	20.29


The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Mode	Channel	Channel Frequency (MHz)	Data rate (Mbps)	Attenuator + Cable offset (dB)	Average power Result (dB m)	Peak Power Result (dB m)
OFDM (802.11n_HT20)	Low	2 412	MCS0	21.33	9.43	17.45
			MCS1		9.42	17.25
			MCS2		9.52	17.09
			MCS3		10.83	18.04
			MCS4		<u>10.87</u>	18.04
			MCS5		10.44	17.76
			MCS6		10.53	17.67
			MCS7		10.57	<u>18.22</u>
	Middle	2 437	MCS0	21.17	9.77	17.52
			MCS1		9.69	17.15
			MCS2		9.81	17.24
			MCS3		11.14	18.30
			MCS4		<u>11.19</u>	<u>18.33</u>
			MCS5		10.78	18.17
			MCS6		10.76	18.09
			MCS7		10.62	18.01
	High	2 462	MCS0	21.24	9.89	17.13
			MCS1		9.76	17.42
			MCS2		9.76	17.78
			MCS3		<u>11.38</u>	<u>18.27</u>
			MCS4		11.17	18.19
			MCS5		11.30	18.16
			MCS6		11.28	18.02
			MCS7		11.21	18.00

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 5. Power Spectral Density Measurement

### 5.1. Test Setup



### 5.2. Limit

§15.247(e) For digitally modulated system, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

### 5.3. Test Procedure

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section.

The measurements are recorded using the AVGPSD measurement procedure in section 5.3 of KDB 558074.

1. Use this procedure when the maximum conducted output power in the fundamental emission is used to demonstrate compliance. The EUT must be configured to transmit continuously at full power over the measurement duration.
2. Set the analyzer span to 5 – 30 % greater than the EBW.
3. Set the RBW = 100 kHz
4. Set the VBW  $\geq$  300 kHz
5. Detector = power average (RMS).
6. Ensure that the number of measurement points in the sweep  $\geq 2 \times$  span/RBW (use of a greater number of measurement points than this minimum requirement is recommended).
7. Manually set the sweep time to :  $\geq 10 \times$  (number of measurement points in sweep)  $\times$  (transmission symbol period).
8. Perform the measurement over a single sweep.
9. Use the peak marker function to determine the maximum level in any 100 kHz band segment within the fundamental EBW.
10. Scale the observed power level to an equivalent level in 3 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where :  $BWCF = 10\log(3 \text{ kHz}/100 \text{ kHz} = -15.2 \text{ dB})$ .
11. The resulting PSD level must be  $\leq 8 \text{ dBm}$ .

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

## 5.4. Test Results

Ambient temperature : (24 ± 2) °C  
 Relative humidity : 47 % R.H.

Operation Mode	Data Rate (Mbps)	Channel	Frequency	Measured PSD (dB m)	Bandwidth Correction Factor (dB)	Corrected PSD (dB m)	Maximum Limit (dB m)
DSSS (802.11b)	1	Low	2 412 MHz	-3.59	-15.20	-18.79	8
		Middle	2 437 MHz	-3.30	-15.20	-18.50	8
		High	2 462 MHz	-3.08	-15.20	-18.28	8
OFDM (802.11g)	6	Low	2 412 MHz	-9.28	-15.20	-24.48	8
		Middle	2 437 MHz	-9.08	-15.20	-24.28	8
		High	2 462 MHz	-8.97	-15.20	-24.17	8
OFDM (802.11n_HT20)	MCS0	Low	2 412 MHz	-11.17	-15.20	-26.37	8
		Middle	2 437 MHz	-11.10	-15.20	-26.30	8
		High	2 462 MHz	-11.36	-15.20	-26.56	8


Note;

Corrected Power Spectral Density (dB m) = Measured Power Spectral Density (dB m) + Bandwidth Correction Factor (dB)


*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

**DSSS : 802.11b**

Low Channel




Middle Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

High Channel




OFDM : 802.11g

Low Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Middle Channel




High Channel




The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## OFDM : 802.11n\_HT20

### Low Channel




### Middle Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.


High Channel



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 6. Transmitter AC Power Line Conducted Emission

### 6.1. Test Setup



### 6.2. Limit

According to §15.207(a) for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 uH/50 ohm line impedance stabilization network(LISN).

Compliance with the provision of this paragraph shall on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower applies at the boundary between the frequency ranges.

Frequency of Emission (MHz)	Conducted limit (dB $\mu$ V)	
	Quasi-peak	Average
0.15 – 0.50	66 - 56*	56 - 46*
0.50 – 5.00	56	46
5.00 – 30.0	60	50

\* Decreases with the logarithm of the frequency.

The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

---

### 6.3. Test Procedures

All data rates and modes were investigated for this test. The full data for the worst case data rate are reported in this section.

AC line conducted emissions from the EUT were measured according to the dictates of ANSI C63.4-2003

1. The test procedure is performed in a 6.5m × 3.6m × 3.6m (L × W × H) shielded room. The EUT along with its peripherals were placed on a 1.0 m(W) × 1.5 m(L) and 0.8 m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane.
2. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room.
3. The excess power cable between the EUT and the LISN was bundled. All connecting cables of EUT were moved to find the maximum emission.

---

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*

#### 6.4. Test Results (Worst case configuration\_11b mode, 1 Mbps, high channel)

The following table shows the highest levels of conducted emissions on both phase of Hot and Neutral line.

Ambient temperature : (24 ± 2) °C  
 Relative humidity : 47 % R.H.

Frequency range : 0.15 MHz – 30 MHz  
 Measured Bandwidth : 9 kHz

FREQ. (MHz)	LEVEL(dB $\mu$ V)		LINE	LIMIT(dB $\mu$ V)		MARGIN(dB)	
	Q-Peak	Average		Q-Peak	Average	Q-Peak	Average
0.47	48.35	43.75	N	56.51	46.51	8.16	2.76
0.76	48.45	39.85	N	56.00	46.00	7.55	6.15
1.06	46.76	39.52	N	56.00	46.00	9.24	6.48
1.35	46.73	37.16	N	56.00	46.00	9.27	8.84
10.69	25.67	14.81	N	60.00	50.00	34.33	35.19
21.44	17.68	8.55	N	60.00	50.00	42.32	41.45
0.47	45.42	36.39	H	56.51	46.51	11.09	10.12
0.77	45.26	36.39	H	56.00	46.00	10.74	9.61
1.35	42.67	29.42	H	56.00	46.00	13.33	16.58
1.78	39.43	27.93	H	56.00	46.00	16.57	18.07
3.09	40.06	25.75	H	56.00	46.00	15.94	20.25
5.58	34.75	22.64	H	60.00	50.00	25.25	27.36


Note ;

1. Line ( H ): Hot, Line ( N ): Neutral
2. All modes of operation were investigated and the worst-case emissions are reported using 11b\_11Mbps\_high.
3. The limit for Class B device(s) from 150 kHz to 30 MHz are specified in Section of the Title 47 CFR.
4. Traces shown in plot mad using a peak detector and average detector
5. Deviations to the Specifications: None.

*The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.*


## Plots of Conducted Power line

Test mode : (Hot)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

Test mode : (Neutral)



The results shown in this test report refer only to the sample(s) tested unless otherwise stated. This test report cannot be reproduced, except in full, without prior written permission of the Company.

## 7. Antenna Requirement

### 7.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section §15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section §15.247 (b) if transmitting antennas of directional gain greater than 6 dB i are used, the power shall be reduced by the amount in dB that the gain of the antenna exceeds 6 dB i.

### 7.2. Antenna Connected Construction

Antenna used in this product is Internal type with gain of -4.1 dB i.