

**MEASUREMENT REPORT**
LTE**Applicant Name:**

Samsung Electronics Co., Ltd.
129, Samsung-ro,
Yeongtong-gu, Suwon-si
Gyeonggi-do, 16677, Korea

Date of Testing:

8/30 - 10/18/2018

Test Site/Location:

PCTEST Lab. Columbia, MD, USA

Test Report Serial No.:

1M1809140179-03.A3L

FCC ID:

A3LSMA9200

APPLICANT:

Samsung Electronics Co., Ltd.

Application Type:

Certification

Model:

SM-A9200

EUT Type:

Portable Handset

FCC Classification:

PCS Licensed Transmitter Held to Ear (PCE)

FCC Rule Part(s):

22 & 27

Test Procedure(s):

ANSI C63.26-2015, ANSI/TIA-603-E-2016, KDB 971168 D01 v03r01

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.



Randy Ortanez
President

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION)		 Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 1 of 143

T A B L E O F C O N T E N T S


1.0	INTRODUCTION	5
1.1	Scope	5
1.2	PCTEST Test Location	5
1.3	Test Facility / Accreditations	5
2.0	PRODUCT INFORMATION	6
2.1	Equipment Description	6
2.2	Device Capabilities	6
2.3	Test Configuration	6
2.4	EMI Suppression Device(s)/Modifications	6
3.0	DESCRIPTION OF TESTS	7
3.1	Measurement Procedure	7
3.2	Block C Frequency Range	7
3.3	Block A Frequency Range	7
3.4	Cellular - Base Frequency Blocks	7
3.5	Cellular - Mobile Frequency Blocks	7
3.6	AWS - Base Frequency Blocks	8
3.7	AWS - Mobile Frequency Blocks	8
3.8	BRS/EBS Frequency Block	8
3.9	Radiated Power and Radiated Spurious Emissions	9
4.0	MEASUREMENT UNCERTAINTY	10
5.0	TEST EQUIPMENT CALIBRATION DATA	11
6.0	SAMPLE CALCULATIONS	12
7.0	TEST RESULTS	13
7.1	Summary	13
7.2	Occupied Bandwidth	15
7.3	Spurious and Harmonic Emissions at Antenna Terminal	43
7.4	Band Edge Emissions at Antenna Terminal	64
7.5	Peak-Average Ratio	91
7.6	Uplink Carrier Aggregation	101
7.7	Radiated Power (ERP/EIRP)	111
7.8	Radiated Spurious Emissions Measurements	117
7.9	Uplink Carrier Aggregation Radiated Measurements	128
7.10	Frequency Stability / Temperature Variation	134
8.0	CONCLUSION	143

FCC ID: A3LSMA9200		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 2 of 143



MEASUREMENT REPORT

FCC Part 22 & 27



Mode	FCC Rule Part	Tx Frequency (MHz)	ERP		EIRP		Emission Designator	Modulation
			Max. Power (W)	Max. Power (dBm)	Max. Power (W)	Max. Power (dBm)		
LTE Band 12	27	699.7 - 715.3	0.082	19.14	0.135	21.29	1M09G7D	QPSK
LTE Band 12	27	699.7 - 715.3	0.072	18.58	0.118	20.73	1M10W7D	16QAM
LTE Band 12	27	699.7 - 715.3	0.058	17.61	0.095	19.76	1M09W7D	64QAM
LTE Band 12	27	700.5 - 714.5	0.084	19.26	0.138	21.41	2M72G7D	QPSK
LTE Band 12	27	700.5 - 714.5	0.079	18.97	0.129	21.12	2M71W7D	16QAM
LTE Band 12	27	700.5 - 714.5	0.060	17.77	0.098	19.92	2M72W7D	64QAM
LTE Band 12/17	27	701.5 - 713.5	0.080	19.04	0.132	21.19	4M55G7D	QPSK
LTE Band 12/17	27	701.5 - 713.5	0.071	18.53	0.117	20.68	4M53W7D	16QAM
LTE Band 12/17	27	701.5 - 713.5	0.056	17.51	0.093	19.66	4M54W7D	64QAM
LTE Band 12/17	27	704 - 711	0.088	19.44	0.144	21.59	8M99G7D	QPSK
LTE Band 12/17	27	704 - 711	0.071	18.54	0.117	20.69	8M96W7D	16QAM
LTE Band 12/17	27	704 - 711	0.055	17.43	0.091	19.58	8M97W7D	64QAM
LTE Band 5	22H	824.7 - 848.3	0.136	21.34	0.223	23.49	1M09G7D	QPSK
LTE Band 5	22H	824.7 - 848.3	0.104	20.18	0.171	22.33	1M10W7D	16QAM
LTE Band 5	22H	824.7 - 848.3	0.081	19.11	0.134	21.26	1M09W7D	64QAM
LTE Band 5	22H	825.5 - 847.5	0.139	21.43	0.228	23.58	2M71G7D	QPSK
LTE Band 5	22H	825.5 - 847.5	0.109	20.37	0.179	22.52	2M72W7D	16QAM
LTE Band 5	22H	825.5 - 847.5	0.084	19.26	0.138	21.41	2M72W7D	64QAM
LTE Band 5	22H	826.5 - 846.5	0.144	21.57	0.236	23.72	4M53G7D	QPSK
LTE Band 5	22H	826.5 - 846.5	0.110	20.40	0.180	22.55	4M53W7D	16QAM
LTE Band 5	22H	826.5 - 846.5	0.091	19.58	0.149	21.73	4M54W7D	64QAM
LTE Band 5	22H	829 - 844	0.131	21.18	0.215	23.33	9M01G7D	QPSK
LTE Band 5	22H	829 - 844	0.107	20.29	0.175	22.44	9M02W7D	16QAM
LTE Band 5	22H	829 - 844	0.085	19.31	0.140	21.46	8M99W7D	64QAM

EUT Overview (<1GHz)

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 3 of 143

Mode	FCC Rule Part	Tx Frequency (MHz)	EIRP		Emission Designator	Modulation
			Max. Power (W)	Max. Power (dBm)		
LTE Band 4	27	1710.7 - 1754.3	0.188	22.74	1M10G7D	QPSK
LTE Band 4	27	1710.7 - 1754.3	0.147	21.66	1M11W7D	16QAM
LTE Band 4	27	1710.7 - 1754.3	0.108	20.32	1M09W7D	64QAM
LTE Band 4	27	1711.5 - 1753.5	0.174	22.41	2M72G7D	QPSK
LTE Band 4	27	1711.5 - 1753.5	0.132	21.21	2M72W7D	16QAM
LTE Band 4	27	1711.5 - 1753.5	0.103	20.12	2M71W7D	64QAM
LTE Band 4	27	1712.5 - 1752.5	0.170	22.29	4M56G7D	QPSK
LTE Band 4	27	1712.5 - 1752.5	0.137	21.36	4M54W7D	16QAM
LTE Band 4	27	1712.5 - 1752.5	0.112	20.49	4M54W7D	64QAM
LTE Band 4	27	1715 - 1750	0.165	22.17	9M03G7D	QPSK
LTE Band 4	27	1715 - 1750	0.130	21.15	9M05W7D	16QAM
LTE Band 4	27	1715 - 1750	0.102	20.08	9M04W7D	64QAM
LTE Band 4	27	1717.5 - 1747.5	0.191	22.81	13M5G7D	QPSK
LTE Band 4	27	1717.5 - 1747.5	0.151	21.79	13M5W7D	16QAM
LTE Band 4	27	1717.5 - 1747.5	0.117	20.68	13M5W7D	64QAM
LTE Band 4	27	1720 - 1745	0.174	22.41	18M0G7D	QPSK
LTE Band 4	27	1720 - 1745	0.142	21.52	17M9W7D	16QAM
LTE Band 4	27	1720 - 1745	0.119	20.77	17M9W7D	64QAM
LTE Band 41	27	2557.5 - 2652.5	0.178	22.51	4M51G7D	QPSK
LTE Band 41	27	2557.5 - 2652.5	0.146	21.64	4M52W7D	16QAM
LTE Band 41	27	2557.5 - 2652.5	0.114	20.57	4M52W7D	64QAM
LTE Band 41	27	2560 - 2650	0.180	22.55	9M00G7D	QPSK
LTE Band 41	27	2560 - 2650	0.151	21.80	9M03W7D	16QAM
LTE Band 41	27	2560 - 2650	0.120	20.79	9M01W7D	64QAM
LTE Band 41	27	2562.5 - 2647.5	0.181	22.59	13M5G7D	QPSK
LTE Band 41	27	2562.5 - 2647.5	0.150	21.77	13M5W7D	16QAM
LTE Band 41	27	2562.5 - 2647.5	0.115	20.61	13M5W7D	64QAM
LTE Band 41	27	2565 - 2645	0.183	22.63	17M9G7D	QPSK
LTE Band 41	27	2565 - 2645	0.153	21.84	18M0W7D	16QAM
LTE Band 41	27	2565 - 2645	0.123	20.91	17M9W7D	64QAM

EUT Overview (>1GHz)

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 4 of 143

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EMC) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Innovation, Science and Economic Development Canada.

1.2 PCTEST Test Location

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility located at 7185 Oakland Mills Road, Columbia, MD 21046. The measurement facility is compliant with the test site requirements specified in ANSI C63.4-2014.

1.3 Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab located in Columbia, MD 21046, U.S.A.

- PCTEST is an ISO 17025-2005 accredited test facility under the American Association for Laboratory Accreditation (A2LA) with Certificate number 2041.01 for Specific Absorption Rate (SAR), Hearing Aid Compatibility (HAC) testing, where applicable, and Electromagnetic Compatibility (EMC) testing for FCC and Innovation, Science, and Economic Development Canada rules.
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC 17065-2012 by A2LA (Certificate number 2041.03) in all scopes of FCC Rules and ISSED Standards (RSS).
- PCTEST facility is a registered (2451B) test laboratory with the site description on file with ISSED.

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 5 of 143

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **Samsung Portable Handset FCC ID: A3LSMA9200**. The test data contained in this report pertains only to the emissions due to the EUT's LTE function.

Test Device Serial No.: 17715, 01420, 39131, 10132, 10280, 10262, 39156, 01420, 16244, 02239, 02203, 02270

2.2 Device Capabilities

This device contains the following capabilities:

850/1900 GSM/GPRS/EDGE, 850/1900 WCDMA/HSPA, Multi-band LTE, 802.11b/g/n WLAN, 802.11a/n/ac UNII, Bluetooth (1x, EDR, LE), NFC, ANT+

LTE Band 12 (698 - 716 MHz) overlaps the entire frequency range of LTE Band 17 (704 - 716 MHz). Therefore, test data provided in this report covers Band 17 as well as Band 12.

2.3 Test Configuration

The EUT was tested per the guidance of ANSI/TIA-603-E-2016 and KDB 971168 D01 v03r01. See Section 7.0 of this test report for a description of the radiated and antenna port conducted emissions tests.

2.4 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

FCC ID: A3LSMA9200		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 6 of 143

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The measurement procedures described in the document titled "Land Mobile FM or PM – Communications Equipment – Measurements and Performance Standards" (ANSI/TIA-603-E-2016) and "Procedures for Compliance Measurement of the Fundamental Emission Power of Licensed Wideband (> 1 MHz) Digital Transmission Systems" (KDB 971168 D01 v03r01) were used in the measurement of the EUT.

3.2 Block C Frequency Range


Two paired channels of 11 megahertz each are available for assignment in Block C in the 746-757 MHz and 776-787 MHz bands. In the event that no licenses for two channels in this Block C are assigned based on the results of the first auction in which such licenses were offered because the auction results do not satisfy the applicable reserve price, the spectrum in the 746-757 MHz and 776-787 MHz bands will instead be made available for assignment at a subsequent auction as follows: (i) Two paired channels of 6 megahertz each available for assignment in Block C1 in the 746-752 MHz and 776-782 MHz bands. (ii) Two paired channels of 5 megahertz each available for assignment in Block C2 in the 752-757 MHz and 782-787 MHz bands.

3.3 Block A Frequency Range

698-746 MHz band. The following frequencies are available for licensing pursuant to this part in the 698-746 MHz band: (1) Three paired channel blocks of 12 megahertz each are available for assignment as follows:

Block A: 698-704 MHz and 728-734 MHz;
Block B: 704-710 MHz and 734-740 MHz; and
Block C: 710-716 MHz and 740-746 MHz.


3.4 Cellular - Base Frequency Blocks



BLOCK 1: 869 – 880 MHz (A* Low + A)
BLOCK 2: 880 – 890 MHz (B)

BLOCK 3: 890 – 891.5 MHz (A* High)
BLOCK 4: 891.5 – 894 MHz (B*)

3.5 Cellular - Mobile Frequency Blocks




BLOCK 1: 824 – 835 MHz (A* Low + A)
BLOCK 2: 835 – 845 MHz (B)


BLOCK 3: 845 – 846.5 MHz (A* High)
BLOCK 4: 846.5 – 849 MHz (B*)

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	
			Page 7 of 143


3.6 AWS - Base Frequency Blocks



3.7 AWS - Mobile Frequency Blocks



3.8 BRS/EBS Frequency Block



FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 8 of 143

3.9 Radiated Power and Radiated Spurious Emissions

The radiated test facilities consisted of an indoor 3 meter semi-anechoic chamber used for final measurements and exploratory measurements, when necessary. The measurement area is contained within the semi-anechoic chamber which is shielded from any ambient interference. The test site inside the chamber is a 6m x 5.2m elliptical, obstruction-free area in accordance with Figure 5.7 of Clause 5 in ANSI C63.4-2014. Absorbers are arranged on the floor between the turn table and the antenna mast in such a way so as to maximize the reduction of reflections for measurements above 1GHz. For measurements below 1GHz, the absorbers are removed. A raised turntable is used for radiated measurement. The turn table is a continuously rotatable, remote-controlled, metallic turntable and 2 meters (6.56 ft.) in diameter. The turn table is flush with the raised floor of the chamber in order to maintain its function as a ground plane. An 80cm tall test table made of Styrodur is placed on top of the turn table. A Styrodur pedestal is placed on top of the test table to bring the total table height to 1.5m.

The equipment under test was transmitting while connected to its integral antenna and is placed on a turntable 3 meters from the receive antenna. The receive antenna height is adjusted between 1 and 4 meter height, the turntable is rotated through 360 degrees, and the EUT is manipulated through all orthogonal planes representative of its typical use to achieve the highest reading on the receive spectrum analyzer. Radiated power levels are also investigated with the receive antenna horizontally and vertically polarized. The maximized power level is recorded using the spectrum analyzer "Channel Power" function with the integration band set to the emissions' occupied bandwidth, a RMS detector, RBW = 100kHz, VBW = 300kHz, and a 1 second sweep time over a minimum of 10 sweeps, per the guidelines of KDB 971168 D01 v03r01.

Per the guidance of ANSI/TIA-603-E-2016, a half-wave dipole is then substituted in place of the EUT. For emissions above 1GHz, a horn antenna is substituted in place of the EUT. The substitute antenna is driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive spectrum analyzer level previously recorded from the spurious emission from the EUT. The power of the emission is calculated using the following formula:

$$P_d \text{ [dBm]} = P_g \text{ [dBm]} - \text{cable loss [dB]} + \text{antenna gain [dBd/dBi]}$$

Where, P_d is the dipole equivalent power, P_g is the generator output into the substitution antenna, and the antenna gain is the gain of the substitute antenna used relative to either a half-wave dipole (dBd) or an isotropic source (dBi). The substitute level is equal to $P_g \text{ [dBm]} - \text{cable loss [dB]}$.

The calculated P_d levels are then compared to the absolute spurious emission limit of -13dBm which is equivalent to the required minimum attenuation of $43 + 10\log_{10}(\text{Power [Watts]})$. For Band 41, the calculated P_d levels are compared to the absolute spurious emission limit of -25dBm which is equivalent to the required minimum attenuation of $55 + 10\log_{10}(\text{Power [Watts]})$.

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 9 of 143

4.0 MEASUREMENT UNCERTAINTY

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI C63.4-2014. All measurement uncertainty values are shown with a coverage factor of $k = 2$ to indicate a 95% level of confidence. The measurement uncertainty shown below meets or exceeds the U_{CISPR} measurement uncertainty values specified in CISPR 16-4-2 and, thus, can be compared directly to specified limits to determine compliance.

Contribution	Expanded Uncertainty ($\pm$ dB)
Conducted Bench Top Measurements	1.13
Radiated Disturbance (<1GHz)	4.98
Radiated Disturbance (>1GHz)	5.07
Radiated Disturbance (>18GHz)	5.09

FCC ID: A3LSMA9200		MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 10 of 143

5.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST). Measurements antennas used during testing were calibrated in accordance to the requirements of ANSI C63.5-2017.

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	LTx3	Licensed Transmitter Cable Set	8/23/2018	Annual	8/23/2019	LTx3
Agilent	N9030A	PXA Signal Analyzer (44GHz)	5/25/2018	Annual	5/25/2019	MY52350166
Anritsu	MT8820C	Radio Communication Analyzer	1/30/2018	Annual	1/30/2019	6201300731
Com-Power	AL-130	9kHz - 30MHz Loop Antenna	10/10/2017	Biennial	10/10/2019	121034
EMCO	3160-09	Small Horn (18 - 26.5GHz)	8/9/2018	Biennial	8/9/2020	135427
Espec	ESX-2CA	Environmental Chamber	3/28/2018	Annual	3/28/2019	17620
ETS Lindgren	3164-08	Quad Ridge Horn Antenna	3/28/2018	Biennial	3/28/2020	128337
ETS Lindgren	3117	1-18 GHz DRG Horn (Medium)	12/1/2016	Biennial	12/1/2018	125518
Huber + Suhner	Sucoflex 102A	40GHz Radiated Cable Set	1/23/2018	Annual	1/23/2019	251425001
Mini Circuits	TVA-11-422	RF Power Amp	N/A			QA1317001
Mini Circuits	PWR-SEN-4GHS	USB Power Sensor	3/30/2018	Annual	3/30/2019	11401010036
Mini-Circuits	SSG-4000HP	Synthesized Signal Generator	N/A			11208010032
Rohde & Schwarz	TS-PR26	18-26.5 GHz Pre-Amplifier	1/24/2018	Annual	1/24/2019	100040
Rohde & Schwarz	ESU40	EMI Test Receiver (40GHz)	8/9/2018	Annual	8/9/2019	100348
Rohde & Schwarz	CMW500	Radio Communication Tester	11/3/2017	Annual	11/3/2018	100976
Rohde & Schwarz	SFUNIT-Rx	Shielded Filter Unit	6/18/2018	Annual	6/18/2019	102134
Sunol	DRH-118	Horn Antenna (1-18GHz)	8/11/2017	Biennial	8/11/2019	A050307
Sunol	JB6	Bi-Log Antenna (30M - 6GHz)	9/27/2016	Biennial	9/27/2018	A082816

Table 5-1. Test Equipment

Notes:

- For equipment listed above that has a calibration date or calibration due date that falls within the test date range, care was taken to ensure that this equipment was used after the calibration date and before the calibration due date.
- Equipment with a calibration date of "N/A" shown in this list was not used to make direct calibrated measurements.

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 11 of 143

6.0 SAMPLE CALCULATIONS

Emission Designator

QPSK Modulation

Emission Designator = 8M62G7D

LTE BW = 8.62 MHz

G = Phase Modulation

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

QAM Modulation

Emission Designator = 8M45W7D

LTE BW = 8.45 MHz

W = Amplitude/Angle Modulated

7 = Quantized/Digital Info

D = Data transmission, telemetry, telecommand

Spurious Radiated Emission – LTE Band

Example: Middle Channel LTE Mode 2nd Harmonic (1564 MHz)

The average spectrum analyzer reading at 3 meters with the EUT on the turntable was –81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of –81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 1564 MHz. So 6.1 dB is added to the signal generator reading of –30.9 dBm yielding –24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm – (-24.80).

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 12 of 143

7.0 TEST RESULTS

7.1 Summary

Company Name: Samsung Electronics Co., Ltd.
 FCC ID: A3LSMA9200
 FCC Classification: PCS Licensed Transmitter Held to Ear (PCE)
 Mode(s): LTE

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Test Result	Reference
2.1049	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.2
2.1051 2.917(a) 27.53(c) 27.53(g) 27.53(h)	Out of Band Emissions	> 43 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 7.3, 7.4
27.53(m)	Out of Band Emissions	Undesirable emissions must meet the limits detailed in 27.53(m)		PASS	Section 7.3, 7.4
27.50(b)	Peak-Average Ratio	< 13 dB		PASS	Section 7.5
2.1046	Transmitter Conducted Output Power	N/A		See RF Exposure Report	See RF Exposure Report
27.53(m)	Uplink Carrier Aggregation	Undesirable emissions must meet the limits detailed in 27.53(m)		PASS	Section 7.6
2.1055 22.355 27.54	Frequency Stability	< 2.5 ppm (Part 22) and fundamental emissions stay within authorized frequency block (Part 27)		PASS	Section 7.10

Table 7-1. Summary of Conducted Test Results

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 13 of 143

FCC Part Section(s)	Test Description	Test Limit	Test Condition	Reference	Reference
22.913(a)(5)	Effective Radiated Power / Equivalent Isotropic Radiated Power (Band 5)	< 7 Watts max. ERP	RADIATED	PASS	Section 7.7
27.50(b)(10) 27.50(c)(10)	Effective Radiated Power / Equivalent Isotropic Radiated Power (Band 12/17)	< 3 Watts max. ERP		PASS	Section 7.7
27.50(h)(2)	Equivalent Isotropic Radiated Power (Band 41)	< 2 Watts max. EIRP		PASS	Section 7.7
27.50(d)(4)	Equivalent Isotropic Radiated Power (Band 4)	< 1 Watts max. EIRP		PASS	Section 7.7
2.1053 22.917(a) 27.53(c) 27.53(g) 27.53(h)	Undesirable Emissions (Band 12/17, 5, 4)	> 43 + 10log ₁₀ (P[Watts]) for all out-of-band emissions		PASS	Section 7.8
27.53(m)	Undesirable Emissions (Band 41)	Undesirable emissions must meet the limits detailed in 27.53(m)		PASS	Section 7.8
27.53(m)	Uplink Carrier Aggregation	Undesirable emissions must meet the limits detailed in 27.53(m)		PASS	Section 7.9

Table 7-2. Summary of Radiated Test Results

Notes:

- 1) All modes of operation and data rates were investigated. The test results shown in the following sections represent the worst case emissions.
- 2) The analyzer plots (Sections 7.2, 7.3, 7.4, 7.5, 7.6) were all taken with a correction table loaded into the analyzer. The correction table was used to account for the losses of the cables, directional couplers, and attenuators used as part of the system to maintain a link between the call box and the EUT at all frequencies of interest.
- 3) All antenna port conducted emissions testing was performed on a test bench with the antenna port of the EUT connected to the spectrum analyzer through calibrated cables, attenuators, and couplers.
- 4) For conducted spurious emissions, automated test software was used to measure emissions and capture the corresponding plots necessary to show compliance. The measurement software utilized is PCTEST "LTE Automation," Version 4.8.
- 5) For operation <1GHz, the EIRP limits in the table above are referenced to the specifications written in the relevant Radio Standards Specifications for Innovation, Science, and Economic Development Canada.

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 14 of 143

7.2 Occupied Bandwidth

Test Overview

The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. All modes of operation were investigated and the worst case configuration results are reported in this section.

Test Procedure Used

KDB 971168 D01 v03r01 – Section 4.2

Test Settings

1. The signal analyzer's automatic bandwidth measurement capability was used to perform the 99% occupied bandwidth and the 26dB bandwidth. The bandwidth measurement was not influenced by any intermediate power nulls in the fundamental emission.
2. RBW = 1 – 5% of the expected OBW
3. VBW $\geq 3 \times$ RBW
4. Detector = Peak
5. Trace mode = max hold
6. Sweep = auto couple
7. The trace was allowed to stabilize
8. If necessary, steps 2 – 7 were repeated after changing the RBW such that it would be within 1 – 5% of the 99% occupied bandwidth observed in Step 7

Test Setup

The EUT and measurement equipment were set up as shown in the diagram below.




Figure 7-1. Test Instrument & Measurement Setup

Test Notes


None.

FCC ID: A3LSMA9200	 MEASUREMENT REPORT (CERTIFICATION) 		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 15 of 143

Band 12/17




Plot 7-1. Occupied Bandwidth Plot (Band 12 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-2. Occupied Bandwidth Plot (Band 12 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 16 of 143




Plot 7-3. Occupied Bandwidth Plot (Band 12 - 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-4. Occupied Bandwidth Plot (Band 12 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 17 of 143




Plot 7-5. Occupied Bandwidth Plot (Band 12 - 3.0MHz 16-QAM - Full RB Configuration)




Plot 7-6. Occupied Bandwidth Plot (Band 12 - 3.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 18 of 143




Plot 7-7. Occupied Bandwidth Plot (Band 12/17 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-8. Occupied Bandwidth Plot (Band 12/17 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 19 of 143




Plot 7-9. Occupied Bandwidth Plot (Band 12/17 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-10. Occupied Bandwidth Plot (Band 12/17 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMA9200	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 20 of 143




Plot 7-11. Occupied Bandwidth Plot (Band 12/17 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-12. Occupied Bandwidth Plot (Band 12/17 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	MEASUREMENT REPORT (CERTIFICATION)		Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 21 of 143

Band 5




Plot 7-13. Occupied Bandwidth Plot (Band 5 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-14. Occupied Bandwidth Plot (Band 5 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 22 of 143




Plot 7-15. Occupied Bandwidth Plot (Band 5 - 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-16. Occupied Bandwidth Plot (Band 5 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 23 of 143



Plot 7-17. Occupied Bandwidth Plot (Band 5 - 3.0MHz 16-QAM - Full RB Configuration)




Plot 7-18. Occupied Bandwidth Plot (Band 5 - 3.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 24 of 143



Plot 7-19. Occupied Bandwidth Plot (Band 5 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-20. Occupied Bandwidth Plot (Band 5 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 25 of 143




Plot 7-21. Occupied Bandwidth Plot (Band 5 - 5.0MHz 64-QAM - Full RB Configuration)




Plot 7-22. Occupied Bandwidth Plot (Band 5 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 26 of 143




Plot 7-23. Occupied Bandwidth Plot (Band 5 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-24. Occupied Bandwidth Plot (Band 5 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 27 of 143

Band 4




Plot 7-25. Occupied Bandwidth Plot (Band 4 - 1.4MHz QPSK - Full RB Configuration)




Plot 7-26. Occupied Bandwidth Plot (Band 4 - 1.4MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 28 of 143




Plot 7-27. Occupied Bandwidth Plot (Band 4 - 1.4MHz 64-QAM - Full RB Configuration)




Plot 7-28. Occupied Bandwidth Plot (Band 4 - 3.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 29 of 143




Plot 7-29. Occupied Bandwidth Plot (Band 4 - 3.0MHz 16-QAM - Full RB Configuration)




Plot 7-30. Occupied Bandwidth Plot (Band 4 - 3.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 30 of 143




Plot 7-31. Occupied Bandwidth Plot (Band 4 - 5.0MHz QPSK - Full RB Configuration)




Plot 7-32. Occupied Bandwidth Plot (Band 4 - 5.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 31 of 143




Plot 7-33. Occupied Bandwidth Plot (Band 4 - 5.0MHz 64-QAM - Full RB Configuration)



Plot 7-34. Occupied Bandwidth Plot (Band 4 - 10.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	SAMSUNG	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 32 of 143




Plot 7-35. Occupied Bandwidth Plot (Band 4 - 10.0MHz 16-QAM - Full RB Configuration)




Plot 7-36. Occupied Bandwidth Plot (Band 4 - 10.0MHz 64-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 33 of 143




Plot 7-37. Occupied Bandwidth Plot (Band 4 - 15.0MHz QPSK - Full RB Configuration)




Plot 7-38. Occupied Bandwidth Plot (Band 4 - 15.0MHz 16-QAM - Full RB Configuration)

FCC ID: A3LSMA9200	PCTEST ENGINEERING LABORATORY, INC.	MEASUREMENT REPORT (CERTIFICATION)	Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset	Page 34 of 143



Plot 7-39. Occupied Bandwidth Plot (Band 4 - 15.0MHz 64-QAM - Full RB Configuration)



Plot 7-40. Occupied Bandwidth Plot (Band 4 - 20.0MHz QPSK - Full RB Configuration)

FCC ID: A3LSMA9200	MEASUREMENT REPORT (CERTIFICATION)			Approved by: Quality Manager
Test Report S/N: 1M1809140179-03.A3L	Test Dates: 8/30 - 10/18/2018	EUT Type: Portable Handset		Page 35 of 143