

APPENDIX D: SAR SYSTEM VALIDATION

Per FCC KDB Publication 865664 D02v01r02, SAR system validation status should be documented to confirm measurement accuracy. The SAR systems (including SAR probes, system components and software versions) used for this device were validated against its performance specifications prior to the SAR measurements. Reference dipoles were used with the required tissue- equivalent media for system validation, according to the procedures outlined in FCC KDB Publication 865664 D01v01r04 and IEEE 1528-2013. Since SAR probe calibrations are frequency dependent, each probe calibration point was validated at a frequency within the valid frequency range of the probe calibration point, using the system that normally operates with the probe for routine SAR measurements and according to the required tissue-equivalent media.

A tabulated summary of the system validation status including the validation date(s), measurement frequencies, SAR probes and tissue dielectric parameters has been included.



Table D-1
SAR System Validation Summary – 1g

SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (ε _r)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
A	750	08/13/2021	7406	750	Head	0.896	40.771	PASS	PASS	PASS	N/A	N/A	N/A
E	835	09/01/2021	7571	835	Head	0.896	41.128	PASS	PASS	PASS	GMSK	PASS	N/A
A	1750	08/13/2021	7406	1750	Head	1.373	38.653	PASS	PASS	PASS	N/A	N/A	N/A
B	1900	08/19/2021	7660	1900	Head	1.456	38.927	PASS	PASS	PASS	GMSK	PASS	N/A
A	1900	08/31/2021	7406	1900	Head	1.459	38.754	PASS	PASS	PASS	GMSK	PASS	N/A
B	2450	08/12/2021	7660	2450	Head	1.856	39.026	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
B	2600	08/11/2021	7660	2600	Head	1.972	38.826	PASS	PASS	PASS	TDD	PASS	N/A
K	5250	03/24/2021	7538	5250	Head	4.577	36.451	PASS	PASS	PASS	OFDM	N/A	PASS
K	5600	03/24/2021	7538	5600	Head	4.972	35.736	PASS	PASS	PASS	OFDM	N/A	PASS
K	5750	03/24/2021	7538	5750	Head	5.166	35.516	PASS	PASS	PASS	OFDM	N/A	PASS
G	750	05/27/2021	7357	750	Body	0.997	53.632	PASS	PASS	PASS	N/A	N/A	N/A
E	750	08/23/2021	7571	750	Body	0.971	53.715	PASS	PASS	PASS	N/A	N/A	N/A
H	835	08/23/2021	7409	835	Body	0.943	52.956	PASS	PASS	PASS	GMSK	PASS	N/A
D	1750	03/01/2021	3589	1750	Body	1.480	51.896	PASS	PASS	PASS	N/A	N/A	N/A
G	1750	08/27/2021	7357	1750	Body	1.488	51.324	PASS	PASS	PASS	N/A	N/A	N/A
P	1900	08/23/2021	7410	1900	Body	1.582	52.055	PASS	PASS	PASS	GMSK	PASS	N/A
L	2450	07/02/2021	7539	2450	Body	2.020	52.209	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
J	2450	08/09/2021	7526	2450	Body	2.006	51.654	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
L	2600	07/06/2021	7539	2600	Body	2.142	51.597	PASS	PASS	PASS	TDD	PASS	N/A
J	2600	08/10/2021	7526	2600	Body	2.137	53.008	PASS	PASS	PASS	TDD	PASS	N/A
J	5250	08/10/2021	7526	5250	Body	5.412	48.914	PASS	PASS	PASS	OFDM	N/A	PASS
J	5600	08/10/2021	7526	5600	Body	5.925	48.311	PASS	PASS	PASS	OFDM	N/A	PASS
J	5750	08/11/2021	7526	5750	Body	6.084	46.123	PASS	PASS	PASS	OFDM	N/A	PASS

Table D-2
SAR System Validation Summary – 10g

SAR System	Freq. (MHz)	Date	Probe SN	Probe Cal Point		Cond. (σ)	Perm. (ε _r)	CW VALIDATION			MOD. VALIDATION		
								SENSITIVITY	PROBE LINEARITY	PROBE ISOTROPY	MOD. TYPE	DUTY FACTOR	PAR
G	1750	08/27/2021	7357	1750	Body	1.488	51.324	PASS	PASS	PASS	N/A	N/A	N/A
P	1900	08/23/2021	7410	1900	Body	1.582	52.055	PASS	PASS	PASS	GMSK	PASS	N/A
H	1900	08/31/2021	7409	1900	Body	1.552	51.698	PASS	PASS	PASS	GMSK	PASS	N/A
J	2450	08/09/2021	7526	2450	Body	2.006	51.654	PASS	PASS	PASS	OFDM/TDD	PASS	PASS
J	2600	08/10/2021	7526	2600	Body	2.137	53.008	PASS	PASS	PASS	TDD	PASS	N/A
J	5250	08/10/2021	7526	5250	Body	5.412	48.914	PASS	PASS	PASS	OFDM	N/A	PASS
J	5600	08/10/2021	7526	5600	Body	5.925	48.311	PASS	PASS	PASS	OFDM	N/A	PASS
J	5750	08/11/2021	7526	5750	Body	6.084	46.123	PASS	PASS	PASS	OFDM	N/A	PASS

NOTE: While the probes have been calibrated for both CW and modulated signals, all measurements were performed using communication systems calibrated for CW signals only. Modulations in the table above represent test configurations for which the measurement system has been validated per FCC KDB Publication 865664 D01v01r04 for scenarios when CW probe calibrations are used with other signal types. SAR systems were validated for modulated signals with a periodic duty cycle, such as GMSK, or with a high peak to average ratio (>5 dB), such as OFDM according to FCC KDB Publication 865664 D01v01r04.

FCC ID A3LSMF711B1		SAR EVALUATION REPORT		Approved by: Quality Manager
Test Dates: 08/14/2021-09/19/2021	DUT Type: Portable Handset	APPENDIX D: Page 1 of 1		