9.4.1. FREQUENCY STABILITY RESULTS

GSM 850, Channel 128/251, Frequency 824.2/848.8 MHz

Reference Frequency : GSM850 Low Channel 824.2 MHz / High Channel 848.8 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2060.500	Hz	High Channel	2122.000	Hz
Power Supply [Vdc]	Environment Temperature [*C]	Frequency Deviation Measureed with Time Elapse				Limit [ppm]
		Low Channel		High Channel		
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.88	50	824.20002623	-0.011	848.80002109	-0.003	2.5
3.88	40	824.20002021	-0.004	848.80001950	-0.001	2.5
3.88	30	824.20002028	-0.004	848.80001876	0.000	2.5
3.88	***20***	***824.20001723***	***0.000***	***848.80001838***	***0.000***	***2.5***
3.88	10	824.20001875	-0.002	848.80001624	0.003	2.5
3.88	0	824.20001973	-0.003	848.80001805	0.000	2.5
3.88	-10	824.20001830	-0.001	848.80001684	0.002	2.5
3.88	-20	824.20002025	-0.004	848.80001925	-0.001	2.5
3.88	-30	824.20001991	-0.003	848.80001864	0.000	2.5

Reference Frequency : GSM850 Low Channel 824.2 MHz / High Channel 848.8 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2060.500	Hz	High Channel	2122.000	Hz
Power Supply [Vdc]	Environment Temperature [*C]	Frequency Deviation Measureed with Time Elapse				Limit [ppm]
		Low Channel		High Channel		
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.88	***20***	**824.20001723**	***0***	**848.80001838**	***0***	***2.5***
4.42	20	824.20002050	-0.004	848.80002160	-0.004	2.5
3.65	20	824.20001820	-0.001	848.80001940	-0.001	2.5

GSM 1900, Channel 512/810, Frequency 1850.0/1910.0 MHz (Lowest Frequency:EGPRS / Highest Frequency: GPRS)

Limit		1850	1910	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	1850.0757	1909.9240		
Extreme (50C)		1850.0757	1909.9240	20.8	0.011
Extreme (40C)		1850.0757	1909.9240	20.4	0.011
Extreme (30C)		1850.0757	1909.9240	18.7	0.010
Extreme (10C)		1850.0757	1909.9240	18.6	0.010
Extreme (0C)		1850.0757	1909.9240	21.3	0.011
Extreme (-10C)		1850.0757	1909.9240	22.2	0.012
Extreme (-20C)		1850.0757	1909.9240	24.4	0.013
Extreme (-30C)		1850.0757	1909.9240	22.1	0.012
20C	15%	1850.0757	1909.9240	13.5	0.007
	-15%	1850.0757	1909.9240	11.9	0.006
	End Point	1850.0757	1909.9240	10.8	0.006

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 5

Reference Frequency : WCDMA Band 5 Low Channel 826.4 MHz / High Channel 846.6 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2066.000	Hz	High Channel	2116.500	Hz
Power Supply [Vdc]	Environment Temperature [*C]	Frequency Deviation Measureed with Time Elapse				Limit [ppm]
		Low Channel		High Channel		
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.88	50	826.40001106	-0.001	846.60001003	0.002	2.5
3.88	40	826.40001025	0.000	846.60001021	0.002	2.5
3.88	30	826.40000911	0.002	846.60001206	-0.001	2.5
3.88	***20***	***826.40001035***	***0.000***	***846.60001158***	***0.000***	***2.5***
3.88	10	826.40001006	0.000	846.60001033	0.001	2.5
3.88	0	826.40001121	-0.001	846.60000928	0.003	2.5
3.88	-10	826.40001173	-0.002	846.60001028	0.002	2.5
3.88	-20	826.40000836	0.002	846.60001037	0.001	2.5
3.88	-30	826.40000833	0.002	846.60001058	0.001	2.5

Reference Frequency : WCDMA Band 5 Low Channel 826.4 MHz / High Channel 846.6 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2066.000	Hz	High Channel	2116.500	Hz
Power Supply [Vdc]	Environment Temperature [*C]	Frequency Deviation Measureed with Time Elapse				Limit [ppm]
		Low Channel		High Channel		
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.88	***20***	**826.40001035**	***0***	**846.60001158**	***0***	***2.5***
4.42	20	826.40000430	0.007	846.60000457	0.008	2.5
3.65	20	826.40000563	0.006	846.60000484	0.008	2.5

WCDMA Band 4 (Lowest Frequency:HSDPA / Highest Frequency: Rel99)

Limit		1710	1755	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	1710.3097	1754.6870		
Extreme (50C)		1710.3097	1754.6870	5.2	0.003
Extreme (40C)		1710.3097	1754.6870	3.6	0.002
Extreme (30C)		1710.3097	1754.6870	4.9	0.003
Extreme (10C)		1710.3097	1754.6870	5.1	0.003
Extreme (0C)		1710.3097	1754.6870	4.1	0.002
Extreme (-10C)		1710.3097	1754.6870	4.1	0.002
Extreme (-20C)		1710.3097	1754.6870	5.2	0.003
Extreme (-30C)		1710.3097	1754.6870	7.2	0.004
20C	15%	1710.3097	1754.6870	5.9	0.003
	-15%	1710.3097	1754.6870	5.6	0.003
	End Point	1710.3097	1754.6870	5.8	0.003

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 2 (Lowest Frequency: HSDPA / Highest Frequency: HSDPA)

Limit		1850	1910	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	1850.3135	1909.6849		
Extreme (50C)		1850.3135	1909.6849	13.5	0.007
Extreme (40C)		1850.3135	1909.6849	13.6	0.007
Extreme (30C)		1850.3135	1909.6849	11.7	0.006
Extreme (10C)		1850.3135	1909.6849	13.8	0.007
Extreme (0C)		1850.3135	1909.6849	12.9	0.007
Extreme (-10C)		1850.3135	1909.6849	13.2	0.007
Extreme (-20C)		1850.3135	1909.6849	14.9	0.008
Extreme (-30C)		1850.3135	1909.6849	15.2	0.008
20C	15%	1850.3135	1909.6849	5.3	0.003
	-15%	1850.3135	1909.6849	5.2	0.003
	End Point	1850.3135	1909.6849	5.5	0.003

LTE Band 12 (Lowest Frequency:QPSK / Highest Frequency: 16QAM)

Limit		699	716	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	699.1561	715.8480		
Extreme (50C)		699.1561	715.8480	33.0	0.047
Extreme (40C)		699.1561	715.8480	33.0	0.047
Extreme (30C)		699.1561	715.8480	35.0	0.049
Extreme (10C)		699.1561	715.8480	27.7	0.039
Extreme (0C)		699.1561	715.8480	27.0	0.038
Extreme (-10C)		699.1561	715.8480	26.6	0.038
Extreme (-20C)		699.1561	715.8480	28.1	0.040
Extreme (-30C)		699.1561	715.8480	29.1	0.041
20C	15%	699.1561	715.8480	6.6	0.009
	-15%	699.1561	715.8480	5.0	0.007
	End Point	699.1561	715.8480	4.7	0.007

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 13 (Lowest Frequency: 16QAM / Highest Frequency: 16QAM)

Limit		777	787	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	777.2454	786.7508		
Extreme (50C)		777.2454	786.7508	17.5	0.022
Extreme (40C)		777.2454	786.7508	16.1	0.021
Extreme (30C)		777.2454	786.7508	16.3	0.021
Extreme (10C)		777.2454	786.7508	15.1	0.019
Extreme (0C)		777.2454	786.7508	14.9	0.019
Extreme (-10C)		777.2454	786.7508	13.8	0.018
Extreme (-20C)		777.2454	786.7508	13.5	0.017
Extreme (-30C)		777.2454	786.7508	13.4	0.017
20C	15%	777.2454	786.7508	6.3	0.008
	-15%	777.2454	786.7508	5.9	0.008
	End Point	777.2454	786.7508	6.1	0.008

LTE Band 25 (Lowest Frequency:QPSK / Highest Frequency: 16QAM)

Limit		1850	1915	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	1850.1558	1914.8446		
Extreme (50C)		1850.1558	1914.8446	26.2	0.014
Extreme (40C)		1850.1558	1914.8446	27.4	0.015
Extreme (30C)		1850.1558	1914.8446	28.3	0.015
Extreme (10C)		1850.1558	1914.8446	27.5	0.015
Extreme (0C)		1850.1558	1914.8446	29.2	0.016
Extreme (-10C)		1850.1558	1914.8446	28.6	0.015
Extreme (-20C)		1850.1558	1914.8446	26.4	0.014
Extreme (-30C)		1850.1558	1914.8446	26.4	0.014
20C	15%	1850.1558	1914.8446	11.6	0.006
	-15%	1850.1558	1914.8446	11.8	0.006
	End Point	1850.1558	1914.8446	11.7	0.006

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26

Reference Frequency : LTE Band 26 Low Channel 814.7 MHz / High Channel 848.3 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2036.750	Hz	High Channel	2120.750	Hz
Power Supply [Vdc]	Environment Temperature [*C]	Frequency Deviation Measureed with Time Elapse				Limit [ppm]
		Low Channel		High Channel		
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.88	50	814.70003713	0.001	848.30003314	0.005	2.5
3.88	40	814.70003507	0.003	848.30003420	0.004	2.5
3.88	30	814.70003638	0.002	848.30003508	0.003	2.5
3.88	***20***	***814.70003781***	***0.000***	***848.30003751***	***0.000***	***2.5***
3.88	10	814.70003570	0.003	848.30003638	0.001	2.5
3.88	0	814.70003487	0.004	848.30003585	0.002	2.5
3.88	-10	814.70003248	0.007	848.30003421	0.004	2.5
3.88	-20	814.70003608	0.002	848.30003465	0.003	2.5
3.88	-30	814.70003213	0.007	848.30003516	0.003	2.5

Reference Frequency : LTE Band 26 Low Channel 814.7 MHz / High Channel 848.3 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2036.750	Hz	High Channel	2120.750	Hz
Power Supply [Vdc]	Environment Temperature [*C]	Frequency Deviation Measureed with Time Elapse				Limit [ppm]
		Low Channel		High Channel		
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.88	***20***	**814.70003781**	***0***	**848.30003751**	***0***	***2.5***
4.42	20	814.70000543	0.040	848.30000628	0.037	2.5
3.65	20	814.70000593	0.039	848.30000539	0.038	2.5

LTE Band 41 PC2 (Lowest Frequency: 16QAM / Highest Frequency: QPSK)

Limit		2496	2690	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	2496.2480	2689.7431		
Extreme (50C)		2496.2480	2689.7431	25.1	0.010
Extreme (40C)		2496.2480	2689.7431	24.1	0.009
Extreme (30C)		2496.2480	2689.7431	23.8	0.009
Extreme (10C)		2496.2480	2689.7431	23.4	0.009
Extreme (0C)		2496.2480	2689.7431	23.9	0.009
Extreme (-10C)		2496.2480	2689.7431	24.1	0.009
Extreme (-20C)		2496.2480	2689.7431	23.3	0.009
Extreme (-30C)		2496.2480	2689.7431	21.2	0.008
20C	15%	2496.2480	2689.7431	18.8	0.007
	-15%	2496.2480	2689.7431	15.3	0.006
	End Point	2496.2480	2689.7431	14.3	0.006

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 66 (Lowest Frequency: 16QAM / Highest Frequency: 16QAM)

Limit		1710	1780	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	1710.6995	1779.3005		
Extreme (50C)		1710.6995	1779.3006	49.4	0.028
Extreme (40C)		1710.6995	1779.3006	50.8	0.029
Extreme (30C)		1710.6995	1779.3006	51.5	0.030
Extreme (10C)		1710.6995	1779.3006	51.2	0.029
Extreme (0C)		1710.6995	1779.3006	50.2	0.029
Extreme (-10C)		1710.6995	1779.3006	49.9	0.029
Extreme (-20C)		1710.6995	1779.3006	52.5	0.030
Extreme (-30C)		1710.6995	1779.3006	64.9	0.037
20C	15%	1710.6995	1779.3006	11.4	0.007
	-15%	1710.6995	1779.3006	12.4	0.007
	End Point	1710.6995	1779.3006	10.2	0.006

NR Band 5

Reference Frequency : NR Band 5 Low Channel 824.7 MHz / High Channel 848.3 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2061.750	Hz	High Channel	2120.750	Hz
Power Supply [Vdc]	Environment Temperature [ºC]	Frequency Deviation Measureed with Time Elapse				Limit [ppm]
		Low Channel		High Channel		
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.88	50	824.70003608	0.004	848.30004315	-0.008	2.5
3.88	40	824.70004006	0.000	848.30003988	-0.004	2.5
3.88	30	824.70004220	-0.003	848.30003207	0.005	2.5
3.88	***20***	***824.70003970***	***0.000***	***848.30003610***	***0.000***	***2.5***
3.88	10	824.70003400	0.007	848.30003819	-0.002	2.5
3.88	0	824.70003590	0.005	848.30003621	0.000	2.5
3.88	-10	824.70003699	0.003	848.30003541	0.001	2.5
3.88	-20	824.70003240	0.009	848.30003425	0.002	2.5
3.88	-30	824.70003316	0.008	848.30003390	0.003	2.5

Reference Frequency : NR Band 5 Low Channel 824.7 MHz / High Channel 848.3 MHz @ 20ºC						
Limit: +- 2.5 ppm =	Low Channel	2061.750	Hz	High Channel	2120.750	Hz
Power Supply [Vdc]	Environment Temperature [ºC]	Frequency Deviation Measureed with Time Elapse				Limit [ppm]
		Low Channel		High Channel		
		[MHz]	Delta [ppm]	[MHz]	Delta [ppm]	
3.88	***20***	***824.70003970***	***0***	***848.30003610***	***0***	***2.5***
4.42	20	824.70000629	0.041	848.30000594	0.036	2.5
3.65	20	824.70000597	0.041	848.30000680	0.035	2.5

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR Band 66 (Lowest Frequency: QPSK / Highest Frequency: QPSK)

Limit		1710	1780	Delta (Hz)	Frequency Stability (ppm)
Condition		F low @ End of OBW	F high @ End of OBW		
Temperature	Voltage	(MHz)	(MHz)		
Normal (20C)	Normal	1710.6995	1779.3005		
Extreme (50C)		1710.6995	1779.3006	49.6	0.028
Extreme (40C)		1710.6995	1779.3006	51.6	0.030
Extreme (30C)		1710.6995	1779.3006	52.7	0.030
Extreme (10C)		1710.6995	1779.3006	50.7	0.029
Extreme (0C)		1710.6995	1779.3006	53.1	0.030
Extreme (-10C)		1710.6995	1779.3006	54.5	0.031
Extreme (-20C)		1710.6995	1779.3006	53.6	0.031
Extreme (-30C)		1710.6995	1779.3006	59.0	0.034
20C	15%	1710.6995	1779.3006	13.8	0.008
	-15%	1710.6995	1779.3006	14.1	0.008
	End Point	1710.6995	1779.3006	13.7	0.008

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

9.5. RADIATED POWER (ERP & EIRP)

RULE PART(S)

FCC: §2.1046, §22.913, §24.232, §27.50, §27.53 and §90.635

LIMITS

22.913(a) - The ERP of mobile transmitters and auxiliary test transmitters must not exceed 7 Watts.

24.232(c) - Mobile/portable stations are limited to 2 watts e.i.r.p. peak power and the equipment must employ means to limit the power to the minimum necessary for successful communications.

27.50:

(b)(10) Portable stations (hand-held devices) transmitting in the 746-757 MHz, 776-788 MHz, and 805-806 MHz bands are limited to 3 watts ERP.

(c) (10) - Portable stations (hand-held devices) in the 600 MHz uplink band and the 698-746 MHz band, and fixed and mobile stations in the 600 MHz uplink band are limited to 3 watts ERP.

(d) (4) Fixed, mobile, and portable (hand-held) stations operating in the 1710-1755 MHz band and mobile and portable stations operating in the 1695-1710 MHz and 1755-1780 MHz bands are limited to 1 watt EIRP.

(h) The following power limits shall apply in the BRS and EBS:

(2) Mobile stations are limited to 2.0 watts EIRP. All user stations are limited to 2.0 watts transmitter output power.

90.635(b) – The maximum output power of the transmitter for mobile stations is 100 watts (20dBw).

TEST PROCEDURE

ANSI / TIA / EIA 603 E Clause 2.2.17; ESU40 setting reference to 971168 D01 v03r01

For radiated output power measurement with a ESU40:

a) Set the RBW ≥ OBW;

b) Set VBW ≥ 3 × RBW;

c) Set span ≥ 2 x RBW;

d) Sweep time = auto couple;

e) Detector = rms;

f) Ensure that the number of measurement points ≥ span/RBW;

g) Trace mode = max hold(GSM, WCDMA), average(LTE,NR);

NOTE

5G NR: All Waveforms (CP-OFDM vs DFT-s OFDM) and modulations (QPSK, 16QAM, 64QAM, 256QAM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

TEST RESULTS

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

9.5.1. ERP/EIRP Results

GSM

Band	Mode	Channel	f [MHz]	ERP / EIRP	
				[dBm]	[mW]
GSM850	GPRS	128	824.2	**29.57**	**905.73**
		190	836.6	28.93	781.63
		251	848.8	29.38	866.96
	EGPRS	128	824.2	**23.46**	**221.82**
		190	836.6	22.37	172.58
		251	848.8	22.66	184.50
GSM1900	GPRS	512	1850.2	29.29	849.18
		661	1880	29.93	984.01
		810	1909.8	**30.64**	**1158.78**
	EGPRS	512	1850.2	25.30	338.84
		661	1880	26.72	469.89
		810	1909.8	**27.26**	**532.11**

WCDMA

Band	Mode	Channel	f [MHz]	ERP / EIRP	
				[dBm]	[mW]
Band 5	REL99	4132	826.4	**19.60**	**91.20**
		4183	836.6	19.56	90.36
		4233	846.6	19.18	82.79
	HSDPA	4132	826.4	16.77	47.53
		4183	836.6	**16.79**	**47.75**
		4233	846.6	16.63	46.03
Band 4	REL99	1312	1712.4	21.83	152.41
		1413	1732.6	**22.05**	**160.32**
		1513	1752.6	21.09	128.53
	HSDPA	1312	1712.4	**20.64**	**115.88**
		1413	1732.6	20.13	103.04
		1513	1752.6	19.80	95.50
Band 2	REL99	9262	1852.4	21.81	151.71
		9400	1880.0	22.77	189.23
		9538	1907.6	**23.12**	**205.12**
	HSDPA	9262	1852.4	20.28	106.66
		9400	1880.0	21.21	132.13
		9538	1907.6	**21.92**	**155.60**

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 12

Band	BW [MHz]	Mode	RB Size/ RB Offset	f [MHz]	ERP / EIRP [dBm]	ERP / EIRP [mW]
Band 12	10	QPSK	1/0	704.0	17.27	53.33
			1/0	707.5	16.75	47.32
			1/0	711.0	**17.81**	**60.39**
		16QAM	1/49	704.0	14.72	29.65
			1/25	707.5	14.66	29.24
			1/25	711.0	**15.12**	**32.51**
	5	QPSK	1/0	701.5	16.55	45.19
			1/12	707.5	16.94	49.43
			1/0	713.5	**17.42**	**55.21**
		16QAM	1/0	701.5	14.10	25.70
			1/0	707.5	14.43	27.73
			1/24	713.5	**15.34**	**34.20**
	3	QPSK	1/0	700.5	19.76	94.62
			1/14	707.5	20.58	114.29
			1/8	714.5	**21.14**	**130.02**
		16QAM	1/0	700.5	17.48	55.98
			1/8	707.5	18.09	64.42
			1/0	714.5	**18.58**	**72.11**
	1.4	QPSK	1/0	699.7	16.68	46.56
			1/5	707.5	16.72	46.99
			1/0	715.3	**17.36**	**54.45**
		16QAM	1/3	699.7	14.09	25.64
			1/5	707.5	14.75	29.85
			1/3	715.3	**15.42**	**34.83**

LTE Band 13

Band	BW [MHz]	Mode	RB size / RB Offset	f [MHz]	ERP / EIRP [dBm]	ERP / EIRP [mW]
Band 13	10	QPSK	1/0	782.0	**19.79**	**95.28**
		16QAM	1/25	782.0	16.52	44.87
	5	QPSK	1/24	779.5	**19.74**	**94.19**
			1/12	782.0	18.67	73.62
			1/24	784.5	19.08	80.91
		16QAM	1/12	779.5	**17.87**	**61.24**
			1/0	782.0	16.93	49.32
			1/0	784.5	16.34	43.05

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 25

Band	BW [MHz]	Mode	RB Size/ RB Offset	f [MHz]	ERP / EIRP [dBm]	ERP / EIRP [mW]
Band 25	20	QPSK	1/0	1860.0	22.92	195.88
			1/49	1882.5	23.40	218.78
			1/0	1905.0	**23.41**	**219.28**
		16QAM	1/0	1860.0	20.91	123.31
			1/99	1882.5	21.25	133.35
			1/49	1905.0	**21.69**	**147.57**
	15	QPSK	1/0	1857.5	23.00	199.53
			1/74	1882.5	23.18	207.97
			1/0	1907.5	**23.36**	**216.77**
		16QAM	1/0	1857.5	21.00	125.89
			1/0	1882.5	21.30	134.90
			1/0	1907.5	**21.43**	**139.00**
	10	QPSK	1/0	1855.0	23.21	209.41
			1/0	1882.5	23.60	229.09
			1/0	1910.0	**23.64**	**231.21**
		16QAM	1/25	1855.0	20.78	119.67
			1/25	1882.5	21.52	141.91
			1/0	1910.0	**21.84**	**152.76**
	5	QPSK	1/0	1852.5	23.38	217.77
			1/0	1882.5	23.83	241.55
			1/0	1912.5	**24.05**	**254.10**
		16QAM	1/0	1852.5	21.17	130.92
			1/0	1882.5	21.71	148.25
			1/0	1912.5	**22.19**	**165.58**
	3	QPSK	1/0	1851.5	22.67	184.93
			1/0	1882.5	23.21	209.41
			1/0	1913.5	**23.89**	**244.91**
		16QAM	1/14	1851.5	21.18	131.22
			1/0	1882.5	21.26	133.66
			1/0	1913.5	**22.07**	**161.06**
	1.4	QPSK	1/3	1850.7	22.93	196.34
			1/0	1882.5	23.53	225.42
			1/0	1914.3	**24.15**	**260.02**
		16QAM	1/3	1850.7	21.23	132.74
			1/0	1882.5	21.52	141.91
			1/3	1914.3	**21.95**	**156.68**

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26

Band	BW [MHz]	Mode	RB Size/ RB Offset	f [MHz]	ERP/EIRP [dBm]	ERP/EIRP [mW]
Band 26	15	QPSK	1/0	821.5	17.11	51.40
			1/0	831.5	**16.96**	**49.66**
			1/37	841.5	16.95	49.55
		16QAM	1/0	821.5	14.98	31.48
			1/0	831.5	14.62	28.97
			1/0	841.5	**14.65**	**29.17**
	10	QPSK	1/49	819.0	16.76	47.42
			1/0	829.0	17.00	50.12
			1/0	831.5	16.73	47.10
			1/25	844.0	**17.01**	**50.23**
		16QAM	1/25	819.0	15.02	31.77
			1/0	829.0	**15.30**	**33.88**
			1/0	831.5	14.59	28.77
			1/25	844.0	14.95	31.26
	5	QPSK	1/0	816.5	16.95	49.55
			1/0	821.5	**17.26**	**53.21**
			1/0	826.5	16.83	48.19
			1/24	831.5	16.53	44.98
			1/12	846.5	16.59	45.60
		16QAM	1/0	816.5	15.13	32.58
			1/0	821.5	**15.21**	**33.19**
			1/0	826.5	15.02	31.77
			1/12	831.5	14.56	28.58
			1/0	846.5	15.03	31.84
	3	QPSK	1/14	815.5	16.94	49.43
			1/0	822.5	17.08	51.05
			1/0	825.5	**17.26**	**53.21**
			1/8	831.5	16.68	46.56
			1/14	847.5	16.71	46.88
		16QAM	1/14	815.5	15.06	32.06
			1/0	822.5	**15.10**	**32.36**
			1/14	825.5	14.96	31.33
			1/8	831.5	14.67	29.31
			1/8	847.5	15.09	32.28
	1.4	QPSK	1/5	814.7	16.43	43.95
			1/5	823.3	16.93	49.32
			1/0	824.7	**17.08**	**51.05**
			1/0	831.5	16.79	47.75
			1/0	848.3	16.80	47.86
		16QAM	1/0	814.7	**15.23**	**33.34**
			1/0	823.3	14.75	29.85
			1/0	824.7	15.04	31.92
			1/0	831.5	14.58	28.71
			1/0	848.3	14.72	29.65

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26(Straddle)

Band	BW [MHz]	Mode	RB Size/ RB Offset	f [MHz]	ERP/EIRP [dBm]	ERP/EIRP [mW]
Band 26 Straddle	15	QPSK	1/0	824	17.27	53.33
		16QAM	1/37		15.01	31.70
	10	QPSK	1/0	824	17.50	56.23
		16QAM	1/0		15.11	32.43
	5	QPSK	1/0	824	17.08	51.05
		16QAM	1/0		15.12	32.51
	3	QPSK	1/0	824	17.14	51.76
		16QAM	1/0		14.90	30.90
	1.4	QPSK	1/0	824	17.01	50.23
		16QAM	1/0		15.14	32.66

LTE Band 41 (PC2)

Band	BW [MHz]	Mode	RB Size/ RB Offset	f [MHz]	ERP / EIRP [dBm]	ERP / EIRP [mW]
Band 41	20	QPSK	1/99	2506.0	**22.81**	**190.99**
			1/99	2593.0	20.89	122.74
			1/99	2680.0	22.50	177.83
		16QAM	1/99	2506.0	**22.51**	**178.24**
			1/49	2593.0	20.85	121.62
			1/0	2680.0	21.27	133.97
	15	QPSK	1/74	2503.5	**22.49**	**177.42**
			1/0	2593.0	21.46	139.96
			1/74	2682.5	22.46	176.20
		16QAM	1/37	2503.5	**23.03**	**200.91**
			1/74	2593.0	20.05	101.16
			1/74	2682.5	21.91	155.24
	10	QPSK	1/49	2501.0	**23.10**	**204.17**
			1/0	2593.0	21.24	133.05
			1/0	2685.0	22.33	171.00
		16QAM	1/49	2501.0	**22.63**	**183.23**
			1/49	2593.0	19.73	93.97
			1/0	2685.0	21.94	156.31
	5	QPSK	1/0	2498.5	22.99	199.07
			1/12	2593.0	20.97	125.03
			1/0	2687.5	**23.14**	**206.06**
		16QAM	1/24	2498.5	**22.37**	**172.58**
			1/0	2593.0	20.45	110.92
			1/24	2687.5	21.78	150.66

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 66

Band	BW [MHz]	Mode	RB Size/ RB Offset	f [MHz]	ERP / EIRP [dBm]	ERP / EIRP [mW]
Band 66	20	QPSK	1/0	1720.0	23.03	200.91
			1/0	1745.0	**23.18**	**207.97**
			1/0	1770.0	22.83	191.87
		16QAM	1/49	1720.0	21.10	128.82
			1/0	1745.0	**21.43**	**139.00**
			1/49	1770.0	20.45	110.92
	15	QPSK	1/37	1717.5	**23.16**	**207.01**
			1/37	1747.5	22.31	170.22
			1/37	1772.5	22.89	194.54
		16QAM	1/37	1717.5	**21.08**	**128.23**
			1/37	1747.5	20.45	110.92
			1/37	1772.5	20.69	117.22
	10	QPSK	1/25	1715.0	**22.78**	**189.67**
			1/25	1745.0	22.22	166.72
			1/25	1775.0	22.61	182.39
		16QAM	1/25	1715.0	20.75	118.85
			1/25	1745.0	20.46	111.17
			1/0	1775.0	**21.09**	**128.53**
	5	QPSK	1/12	1712.5	22.73	187.50
			1/24	1745.0	22.22	166.72
			1/12	1777.5	**22.97**	**198.15**
		16QAM	1/0	1712.5	20.73	118.30
			1/12	1745.0	20.33	107.89
			1/12	1777.5	**20.85**	**121.62**
	3	QPSK	1/8	1711.5	22.92	195.88
			1/8	1745.0	22.64	183.65
			1/8	1778.5	**22.94**	**196.79**
		16QAM	1/8	1711.5	**20.78**	**119.67**
			1/8	1745.0	20.53	112.98
			1/8	1778.5	**20.78**	**119.67**
	1.4	QPSK	1/5	1710.7	22.89	194.54
			1/0	1745.0	22.32	170.61
			1/0	1779.3	**23.01**	**199.99**
		16QAM	1/3	1710.7	20.63	115.61
			1/3	1745.0	20.13	103.04
			1/5	1779.3	**20.93**	**123.88**

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR Band 5

Band	BW [MHz]	Modulation	Mode	RB Size/ RB Offset	f [MHz]	ERP / EIRP [dBm]	ERP / EIRP [mW]
n5	20	DFT-s OFDM	QPSK	1/53	834.0	18.27	67.14
				1/53	836.5	18.31	67.76
				1/53	839.0	**18.52**	**71.12**
			16QAM	1/53	834.0	17.01	50.23
				1/53	836.5	17.05	50.70
				1/53	839.0	**17.36**	**54.45**
	15	DFT-s OFDM	QPSK	1/40	831.5	**19.02**	**79.80**
				1/40	836.5	18.55	71.61
				1/40	841.5	18.26	66.99
			16QAM	1/40	831.5	**18.04**	**63.68**
				1/40	836.5	17.35	54.33
				1/40	841.5	17.08	51.05
	10	DFT-s OFDM	QPSK	1/26	829.0	**19.07**	**80.72**
				1/26	836.5	18.54	**71.45**
				1/26	844.0	18.50	70.79
			16QAM	1/26	829.0	**18.05**	63.83
				1/26	836.5	17.60	**57.54**
				1/26	844.0	17.33	54.08
	5	DFT-s OFDM	QPSK	1/23	826.5	**18.95**	**78.52**
				1/1	836.5	18.69	73.96
				1/1	846.5	18.49	70.63
			16QAM	1/23	826.5	**17.54**	**56.75**
				1/1	836.5	17.35	54.33
				1/1	846.5	17.27	53.33

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR Band 66

Band	BW [MHz]	Modulation	Mode	RB Size/ RB Offset	f [MHz]	ERP / EIRP [dBm]	ERP / EIRP [mW]
n66	20	DFT-s OFDM	QPSK	1/53	1720.0	23.92	246.60
				1/53	1745.0	23.70	234.42
				1/53	1770.0	**24.09**	**256.45**
			16QAM	1/53	1720.0	22.57	180.72
				1/53	1745.0	22.52	178.65
				1/53	1770.0	**22.85**	**192.75**
	15	DFT-s OFDM	QPSK	1/77	1717.5	**24.02**	**252.35**
				1/1	1745.0	23.64	231.21
				1/1	1772.5	23.52	224.91
			16QAM	1/77	1717.5	**22.74**	**187.93**
				1/1	1745.0	22.35	171.79
				1/1	1772.5	22.48	177.01
	10	DFT-s OFDM	QPSK	1/50	1715.0	24.13	**258.82**
				1/1	1745.0	**24.21**	**263.63**
				1/1	1775.0	23.76	237.68
			16QAM	1/50	1715.0	**22.90**	194.98
				1/1	1745.0	22.88	**194.09**
				1/1	1775.0	22.53	179.06
	5	DFT-s OFDM	QPSK	1/23	1712.5	23.54	225.94
				1/1	1745.0	**24.13**	**258.82**
				1/1	1777.5	23.39	218.27
			16QAM	1/23	1712.5	22.70	186.21
				1/1	1745.0	**22.86**	**193.20**
				1/1	1777.5	22.30	169.82

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

9.5.2. ERP/EIRP DATA

GSM850

GSM850

GPRS

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/17/2021
Test Engineer: 22943
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: GPRS 850 MHz Fundamentals

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
824.20	33.91	V	3.0	-1.3	29.57	38.5	-8.9	
824.20	21.78	H	3.0	-1.3	17.44	38.5	-21.1	
Mid Ch								
836.60	33.18	V	3.0	-1.2	28.93	38.5	-9.6	
836.60	22.04	H	3.0	-1.2	17.79	38.5	-20.7	
High Ch								
848.80	33.54	V	3.1	-1.1	29.38	38.5	-9.1	
848.80	21.98	H	3.1	-1.1	17.82	38.5	-20.7	

GSM850

EGPRS

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/17/2021
Test Engineer: 22943
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: EGPRS 850 MHz Fundamentals

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
824.20	27.80	V	3.0	-1.3	23.46	38.5	-15.0	
824.20	14.31	H	3.0	-1.3	9.97	38.5	-28.5	
Mid Ch								
836.60	26.62	V	3.0	-1.2	22.37	38.5	-16.1	
836.60	15.03	H	3.0	-1.2	10.78	38.5	-27.7	
High Ch								
848.80	26.82	V	3.1	-1.1	22.66	38.5	-15.8	
848.80	14.99	H	3.1	-1.1	10.83	38.5	-27.7	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

GSM1900

GSM1900

GPRS

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/17/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: GPRS 1900 MHz Fundamentals

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1850.20	21.34	V	4.5	9.6	26.47	33.0	-6.5	
1850.20	24.16	H	4.5	9.6	29.29	33.0	-3.7	
Mid Ch								
1880.00	19.14	V	4.5	9.4	24.02	33.0	-9.0	
1880.00	25.05	H	4.5	9.4	29.93	33.0	-3.1	
High Ch								
1909.80	19.92	V	4.5	9.1	24.50	33.0	-8.5	
1909.80	26.06	H	4.5	9.1	30.64	33.0	-2.4	

GSM1900

EGPRS

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/17/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: EGPRS 1900 MHz Fundamentals

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1850.20	17.27	V	4.5	9.6	22.40	33.0	-10.6	
1850.20	20.17	H	4.5	9.6	25.30	33.0	-7.7	
Mid Ch								
1880.00	15.76	V	4.5	9.4	20.64	33.0	-12.4	
1880.00	21.84	H	4.5	9.4	26.72	33.0	-6.3	
High Ch								
1909.80	15.77	V	4.5	9.1	20.35	33.0	-12.6	
1909.80	22.68	H	4.5	9.1	27.26	33.0	-5.7	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 5

Band 5
REL99

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/23/2021
Test Engineer: 22943
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: Rel99 Band 5 Fundamentals

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
826.40	23.92	V	3.0	-1.3	19.60	38.5	-18.9	
826.40	12.42	H	3.0	-1.3	8.10	38.5	-30.4	
Mid Ch								
836.60	23.81	V	3.0	-1.2	19.56	38.5	-18.9	
836.60	13.41	H	3.0	-1.2	9.16	38.5	-29.3	
High Ch								
846.60	23.35	V	3.0	-1.1	19.18	38.5	-19.3	
846.60	13.44	H	3.0	-1.1	9.26	38.5	-29.2	

Band 5
HSDPA

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: HSDPA Band 5 Fundamentals

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
826.40	21.09	V	3.0	-1.3	16.77	38.5	-21.7	
826.40	9.57	H	3.0	-1.3	5.25	38.5	-33.3	
Mid Ch								
836.60	21.04	V	3.0	-1.2	16.79	38.5	-21.7	
836.60	10.42	H	3.0	-1.2	6.17	38.5	-32.3	
High Ch								
846.60	20.80	V	3.0	-1.1	16.63	38.5	-21.9	
846.60	10.19	H	3.0	-1.1	6.01	38.5	-32.5	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 4

Band 4 REL99

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/23/2021
Test Engineer: 22943
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: Rel99 Band 4 Fundamentals

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1712.40	16.55	V	4.3	9.6	21.83	30.0	-8.2	
1712.40	9.40	H	4.3	9.6	14.68	30.0	-15.3	
Mid Ch								
1732.60	16.73	V	4.3	9.6	22.05	30.0	-8.0	
1732.60	9.14	H	4.3	9.6	14.46	30.0	-15.5	
High Ch								
1752.60	15.74	V	4.3	9.7	21.09	30.0	-8.9	
1752.60	9.08	H	4.3	9.7	14.43	30.0	-15.6	

Band 4 HSDPA

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: HSDPA Band 4 Fundamentals

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1712.40	15.36	V	4.3	9.6	20.64	30.0	-9.4	
1712.40	7.09	H	4.3	9.6	12.37	30.0	-17.6	
Mid Ch								
1732.60	14.81	V	4.3	9.6	20.13	30.0	-9.9	
1732.60	7.94	H	4.3	9.6	13.26	30.0	-16.7	
High Ch								
1752.60	14.45	V	4.3	9.7	19.80	30.0	-10.2	
1752.60	6.24	H	4.3	9.7	11.59	30.0	-18.4	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 2

Band 2
REL99

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/17/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: Rel99 Band 2 Fundamentals

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1852.40	12.99	V	4.5	9.6	18.10	33.0	-14.9	
1852.40	16.70	H	4.5	9.6	21.81	33.0	-11.2	
Mid Ch								
1880.00	12.01	V	4.5	9.4	16.89	33.0	-16.1	
1880.00	17.89	H	4.5	9.4	22.77	33.0	-10.2	
High Ch								
1907.60	11.89	V	4.5	9.2	16.50	33.0	-16.5	
1907.60	18.51	H	4.5	9.2	23.12	33.0	-9.9	

Band 2
HSDPA

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/17/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: HSDPA Band 2 Fundamentals

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1852.40	11.62	V	4.5	9.6	16.73	33.0	-16.3	
1852.40	15.17	H	4.5	9.6	20.28	33.0	-12.7	
Mid Ch								
1880.00	10.32	V	4.5	9.4	15.20	33.0	-17.8	
1880.00	16.33	H	4.5	9.4	21.21	33.0	-11.8	
High Ch								
1907.60	10.80	V	4.5	9.2	15.41	33.0	-17.6	
1907.60	17.31	H	4.5	9.2	21.92	33.0	-11.1	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 12

LTE Band 12

10MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/23/2021
Test Engineer: 19227
Configuration: EUT, X-Position
Location: Chamber 2
Mode: LTE_QPSK Band 12 Fundamentals, 10MHz Bandwidth

Test Equpment:
Receiving: VULB9163-749, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
704.00	14.56	V	2.8	-1.4	10.41	34.8	-24.4	
704.00	21.42	H	2.8	-1.4	17.27	34.8	-17.5	
Mid Ch								
707.50	13.72	V	2.8	-1.4	9.55	34.8	-25.2	
707.50	20.91	H	2.8	-1.4	16.75	34.8	-18.0	
High Ch								
711.00	14.70	V	2.8	-1.4	10.53	34.8	-24.2	
711.00	21.98	H	2.8	-1.4	17.81	34.8	-17.0	

LTE Band 12

10MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/23/2021
Test Engineer: 19227
Configuration: EUT, X-Position
Location: Chamber 2
Mode: LTE_16QAM Band 12 Fundamentals, 10MHz Bandwidth

Test Equpment:
Receiving: VULB9163-749, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
704.00	11.89	V	2.8	-1.4	7.74	34.8	-27.0	
704.00	18.87	H	2.8	-1.4	14.72	34.8	-20.0	
Mid Ch								
707.50	11.26	V	2.8	-1.4	7.09	34.8	-27.7	
707.50	18.82	H	2.8	-1.4	14.66	34.8	-20.1	
High Ch								
711.00	12.38	V	2.8	-1.4	8.21	34.8	-26.6	
711.00	19.29	H	2.8	-1.4	15.12	34.8	-19.7	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 12

5MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/23/2021
Test Engineer: 19227
Configuration: EUT, X-Position
Location: Chamber 2
Mode: LTE_QPSK Band 12 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: VULB9163-749, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
701.50	13.55	V	2.8	-1.4	9.42	34.8	-25.4	
701.50	20.68	H	2.8	-1.4	16.55	34.8	-18.2	
Mid Ch								
707.50	13.32	V	2.8	-1.4	9.15	34.8	-25.6	
707.50	21.10	H	2.8	-1.4	16.94	34.8	-17.8	
High Ch								
713.50	13.93	V	2.8	-1.4	9.75	34.8	-25.0	
713.50	21.60	H	2.8	-1.4	17.42	34.8	-17.3	

LTE Band 12

5MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/23/2021
Test Engineer: 19227
Configuration: EUT, X-Position
Location: Chamber 2
Mode: LTE_16QAM Band 12 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: VULB9163-749, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
701.50	11.14	V	2.8	-1.4	7.01	34.8	-27.8	
701.50	18.23	H	2.8	-1.4	14.10	34.8	-20.7	
Mid Ch								
707.50	11.14	V	2.8	-1.4	6.97	34.8	-27.8	
707.50	18.59	H	2.8	-1.4	14.43	34.8	-20.3	
High Ch								
713.50	11.24	V	2.8	-1.4	7.06	34.8	-27.7	
713.50	19.52	H	2.8	-1.4	15.34	34.8	-19.4	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 12

3MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/23/2021
Test Engineer: 19227
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 12 Fundamentals, 3MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
700.50	16.70	V	2.8	-1.4	12.56	34.8	-22.2	
700.50	23.90	H	2.8	-1.4	19.76	34.8	-15.0	
Mid Ch								
707.50	16.95	V	2.8	-1.4	12.79	34.8	-22.0	
707.50	24.75	H	2.8	-1.4	20.58	34.8	-14.2	
High Ch								
714.50	17.76	V	2.8	-1.4	13.57	34.8	-21.2	
714.50	25.33	H	2.8	-1.4	21.14	34.8	-13.6	

LTE Band 12

3MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/23/2021
Test Engineer: 19227
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 12 Fundamentals, 3MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
700.50	14.41	V	2.8	-1.4	10.27	34.8	-24.5	
700.50	21.62	H	2.8	-1.4	17.48	34.8	-17.3	
Mid Ch								
707.50	14.93	V	2.8	-1.4	10.77	34.8	-24.0	
707.50	22.26	H	2.8	-1.4	18.09	34.8	-16.7	
High Ch								
714.50	15.30	V	2.8	-1.4	11.11	34.8	-23.7	
714.50	22.77	H	2.8	-1.4	18.58	34.8	-16.2	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 12

1.4MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/23/2021
Test Engineer: 19227
Configuration: EUT, X-Position
Location: Chamber 2
Mode: LTE_QPSK Band 12 Fundamentals, 1.4MHz Bandwidth

Test Equipment:
Receiving: VULB9163-749, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
699.70	13.46	V	2.8	-1.4	9.33	34.8	-25.4	
699.70	20.81	H	2.8	-1.4	16.68	34.8	-18.1	
Mid Ch								
707.50	13.12	V	2.8	-1.4	8.95	34.8	-25.8	
707.50	20.88	H	2.8	-1.4	16.72	34.8	-18.1	
High Ch								
715.30	13.67	V	2.8	-1.4	9.48	34.8	-25.3	
715.30	21.55	H	2.8	-1.4	17.36	34.8	-17.4	

LTE Band 12

1.4MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/23/2021
Test Engineer: 19227
Configuration: EUT, X-Position
Location: Chamber 2
Mode: LTE_16QAM Band 12 Fundamentals, 1.4MHz Bandwidth

Test Equipment:
Receiving: VULB9163-749, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
699.70	11.42	V	2.8	-1.4	7.29	34.8	-27.5	
699.70	18.22	H	2.8	-1.4	14.09	34.8	-20.7	
Mid Ch								
707.50	11.10	V	2.8	-1.4	6.93	34.8	-27.8	
707.50	18.91	H	2.8	-1.4	14.75	34.8	-20.0	
High Ch								
715.30	11.17	V	2.8	-1.4	6.98	34.8	-27.8	
715.30	19.61	H	2.8	-1.4	15.42	34.8	-19.3	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 13

LTE Band 13

10MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 20890
Configuration: EUT / Z - Position
Location: Chamber 2
Mode: LTE_QPSK Band 13 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: VULB9163-749, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Mid Ch								
782.00	24.24	V	2.9	-1.5	19.79	34.8	-15.0	
782.00	11.06	H	2.9	-1.5	6.61	34.8	-28.2	

LTE Band 13

10MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 20890
Configuration: EUT / Z - Position
Location: Chamber 2
Mode: LTE_16QAM Band 13 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: VULB9163-749, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Mid Ch								
782.00	20.97	V	2.9	-1.5	16.52	34.8	-18.2	
782.00	8.41	H	2.9	-1.5	3.96	34.8	-30.8	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 13

5MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 20890
Configuration: EUT/ Z - Position
Location: Chamber 2
Mode: LTE_QPSK Band 13 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: VULB9163-749, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
779.50	24.18	V	2.9	-1.5	19.74	34.8	-15.0	
779.50	11.04	H	2.9	-1.5	6.60	34.8	-28.2	
Mid Ch								
782.00	23.12	V	2.9	-1.5	18.67	34.8	-16.1	
782.00	11.80	H	2.9	-1.5	7.35	34.8	-27.4	
High Ch								
784.50	23.54	V	2.9	-1.5	19.08	34.8	-15.7	
784.50	10.19	H	2.9	-1.5	5.73	34.8	-29.0	

LTE Band 13

5MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 20890
Configuration: EUT/ Z - Position
Location: Chamber 2
Mode: LTE_16QAM Band 13 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: VULB9163-749, and Chamber 2 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
779.50	22.31	V	2.9	-1.5	17.87	34.8	-16.9	
779.50	8.64	H	2.9	-1.5	4.20	34.8	-30.6	
Mid Ch								
782.00	21.38	V	2.9	-1.5	16.93	34.8	-17.8	
782.00	8.39	H	2.9	-1.5	3.94	34.8	-30.8	
High Ch								
784.50	20.80	V	2.9	-1.5	16.34	34.8	-18.4	
784.50	7.59	H	2.9	-1.5	3.13	34.8	-31.6	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 25

LTE Band 25

20MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 25 Fundamentals, 20MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1860.00	13.25	V	4.5	9.5	18.29	33.0	-14.7	
1860.00	17.87	H	4.5	9.5	22.92	33.0	-10.1	
Mid Ch								
1882.50	13.10	V	4.5	9.4	17.96	33.0	-15.0	
1882.50	18.54	H	4.5	9.4	23.40	33.0	-9.6	
High Ch								
1905.00	14.01	V	4.5	9.2	18.66	33.0	-14.3	
1905.00	18.76	H	4.5	9.2	23.41	33.0	-9.6	

LTE Band 25

20MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 25 Fundamentals, 20MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1860.00	11.12	V	4.5	9.5	16.16	33.0	-16.8	
1860.00	15.86	H	4.5	9.5	20.91	33.0	-12.1	
Mid Ch								
1882.50	11.14	V	4.5	9.4	16.00	33.0	-17.0	
1882.50	16.39	H	4.5	9.4	21.25	33.0	-11.7	
High Ch								
1905.00	11.60	V	4.5	9.2	16.25	33.0	-16.8	
1905.00	17.04	H	4.5	9.2	21.69	33.0	-11.3	

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 25

15MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 25 Fundamentals, 15MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1857.50	12.76	V	4.5	9.5	17.83	33.0	-15.2	
1857.50	17.93	H	4.5	9.5	23.00	33.0	-10.0	
Mid Ch								
1882.50	13.37	V	4.5	9.4	18.23	33.0	-14.8	
1882.50	18.32	H	4.5	9.4	23.18	33.0	-9.8	
High Ch								
1907.50	13.45	V	4.5	9.2	18.07	33.0	-14.9	
1907.50	18.75	H	4.5	9.2	23.36	33.0	-9.6	

LTE Band 25

15MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 25 Fundamentals, 15MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1857.50	10.66	V	4.5	9.5	15.73	33.0	-17.3	
1857.50	15.93	H	4.5	9.5	21.00	33.0	-12.0	
Mid Ch								
1882.50	10.07	V	4.5	9.4	14.93	33.0	-18.1	
1882.50	16.44	H	4.5	9.4	21.30	33.0	-11.7	
High Ch								
1907.50	11.31	V	4.5	9.2	15.93	33.0	-17.1	
1907.50	16.82	H	4.5	9.2	21.43	33.0	-11.6	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 25

10MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 25 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1855.00	13.17	V	4.5	9.6	18.26	33.0	-14.7	
1855.00	18.12	H	4.5	9.6	23.21	33.0	-9.8	
Mid Ch								
1882.50	12.62	V	4.5	9.4	17.48	33.0	-15.5	
1882.50	18.74	H	4.5	9.4	23.60	33.0	-9.4	
High Ch								
1910.00	13.64	V	4.5	9.1	18.22	33.0	-14.8	
1910.00	19.06	H	4.5	9.1	23.64	33.0	-9.4	

LTE Band 25

10MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 25 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1855.00	10.78	V	4.5	9.6	15.87	33.0	-17.1	
1855.00	15.69	H	4.5	9.6	20.78	33.0	-12.2	
Mid Ch								
1882.50	10.90	V	4.5	9.4	15.76	33.0	-17.2	
1882.50	16.66	H	4.5	9.4	21.52	33.0	-11.5	
High Ch								
1910.00	11.61	V	4.5	9.1	16.19	33.0	-16.8	
1910.00	17.26	H	4.5	9.1	21.84	33.0	-11.2	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 25

5MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 25 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1852.50	13.02	V	4.5	9.6	18.13	33.0	-14.9	
1852.50	18.27	H	4.5	9.6	23.38	33.0	-9.6	
Mid Ch								
1882.50	12.86	V	4.5	9.4	17.72	33.0	-15.3	
1882.50	18.97	H	4.5	9.4	23.83	33.0	-9.2	
High Ch								
1912.50	13.58	V	4.5	9.1	18.13	33.0	-14.9	
1912.50	19.50	H	4.5	9.1	24.05	33.0	-9.0	

LTE Band 25

5MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 25 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1852.50	11.05	V	4.5	9.6	16.16	33.0	-16.8	
1852.50	16.06	H	4.5	9.6	21.17	33.0	-11.8	
Mid Ch								
1882.50	10.90	V	4.5	9.4	15.76	33.0	-17.2	
1882.50	16.85	H	4.5	9.4	21.71	33.0	-11.3	
High Ch								
1912.50	11.62	V	4.5	9.1	16.17	33.0	-16.8	
1912.50	17.64	H	4.5	9.1	22.19	33.0	-10.8	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 25

3MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 25 Fundamentals, 3MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1851.50	13.21	V	4.5	9.6	18.33	33.0	-14.7	
1851.50	17.54	H	4.5	9.6	22.67	33.0	-10.3	
Mid Ch								
1882.50	13.09	V	4.5	9.4	17.95	33.0	-15.0	
1882.50	18.35	H	4.5	9.4	23.21	33.0	-9.8	
High Ch								
1913.50	13.93	V	4.5	9.1	18.47	33.0	-14.5	
1913.50	19.35	H	4.5	9.1	23.89	33.0	-9.1	

LTE Band 25

3MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 25 Fundamentals, 3MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1851.50	11.01	V	4.5	9.6	16.13	33.0	-16.9	
1851.50	16.05	H	4.5	9.6	21.18	33.0	-11.8	
Mid Ch								
1882.50	11.26	V	4.5	9.4	16.12	33.0	-16.9	
1882.50	16.40	H	4.5	9.4	21.26	33.0	-11.7	
High Ch								
1913.50	12.24	V	4.5	9.1	16.78	33.0	-16.2	
1913.50	17.53	H	4.5	9.1	22.07	33.0	-10.9	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 25

1.4MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 25 Fundamentals, 1.4MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1850.70	13.00	V	4.5	9.6	18.13	33.0	-14.9	
1850.70	17.80	H	4.5	9.6	22.93	33.0	-10.1	
Mid Ch								
1882.50	13.18	V	4.5	9.4	18.04	33.0	-15.0	
1882.50	18.67	H	4.5	9.4	23.53	33.0	-9.5	
High Ch								
1914.30	14.04	V	4.5	9.1	18.56	33.0	-14.4	
1914.30	19.62	H	4.5	9.1	24.15	33.0	-8.8	

LTE Band 25

1.4MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/24/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 25 Fundamentals, 1.4MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1850.70	10.81	V	4.5	9.6	15.94	33.0	-17.1	
1850.70	16.10	H	4.5	9.6	21.23	33.0	-11.8	
Mid Ch								
1882.50	10.95	V	4.5	9.4	15.81	33.0	-17.2	
1882.50	16.66	H	4.5	9.4	21.52	33.0	-11.5	
High Ch								
1914.30	12.11	V	4.5	9.1	16.63	33.0	-16.4	
1914.30	17.42	H	4.5	9.1	21.95	33.0	-11.0	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26 (Part 22)

LTE Band 26

15MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 26 Fundamentals, 15MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Straddle Ch								
824.00	18.80	V	3.0	-1.3	14.46	38.5	-24.0	
824.00	21.61	H	3.0	-1.3	17.27	38.5	-21.2	
Mid Ch								
831.50	19.17	V	3.0	-1.3	14.88	38.5	-23.6	
831.50	21.25	H	3.0	-1.3	16.96	38.5	-21.5	
High Ch								
841.50	17.09	V	3.0	-1.2	12.88	38.5	-25.6	
841.50	21.16	H	3.0	-1.2	16.95	38.5	-21.6	

LTE Band 26

15MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 26 Fundamentals, 15MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Straddle Ch								
824.00	16.31	V	3.0	-1.3	11.97	38.5	-26.5	
824.00	19.35	H	3.0	-1.3	15.01	38.5	-23.5	
Mid Ch								
831.50	17.03	V	3.0	-1.3	12.74	38.5	-25.8	
831.50	18.91	H	3.0	-1.3	14.62	38.5	-23.9	
High Ch								
841.50	14.32	V	3.0	-1.2	10.11	38.5	-28.4	
841.50	18.86	H	3.0	-1.2	14.65	38.5	-23.9	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26

10MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 26 Fundamentals, 10MHz Bandwidth

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Straddle Ch								
824.00	18.49	V	3.0	-1.3	14.15	38.5	-24.3	
824.00	21.84	H	3.0	-1.3	17.50	38.5	-21.0	
Low Ch								
829.00	18.93	V	3.0	-1.3	14.62	38.5	-23.9	
829.00	21.31	H	3.0	-1.3	17.00	38.5	-21.5	
Mid Ch								
831.50	18.83	V	3.0	-1.3	14.54	38.5	-24.0	
831.50	21.02	H	3.0	-1.3	16.73	38.5	-21.8	
High Ch								
844.00	17.16	V	3.0	-1.2	12.96	38.5	-25.5	
844.00	21.21	H	3.0	-1.2	17.01	38.5	-21.5	

LTE Band 26

10MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 26 Fundamentals, 10MHz Bandwidth

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Straddle Ch								
824.00	16.49	V	3.0	-1.3	12.15	38.5	-26.3	
824.00	19.45	H	3.0	-1.3	15.11	38.5	-23.4	
Low Ch								
829.00	17.03	V	3.0	-1.3	12.72	38.5	-25.8	
829.00	19.61	H	3.0	-1.3	15.30	38.5	-23.2	
Mid Ch								
831.50	16.59	V	3.0	-1.3	12.30	38.5	-26.2	
831.50	18.88	H	3.0	-1.3	14.59	38.5	-23.9	
High Ch								
844.00	14.80	V	3.0	-1.2	10.60	38.5	-27.9	
844.00	19.15	H	3.0	-1.2	14.95	38.5	-23.6	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26

5MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 26 Fundamentals, 5MHz Bandwidth

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Straddle Ch								
824.00	18.69	V	3.0	-1.3	14.35	38.5	-24.1	
824.00	21.42	H	3.0	-1.3	17.08	38.5	-21.4	
Low Ch								
826.50	18.73	V	3.0	-1.3	14.41	38.5	-24.1	
826.50	21.16	H	3.0	-1.3	16.83	38.5	-21.7	
Mid Ch								
831.50	18.25	V	3.0	-1.3	13.96	38.5	-24.5	
831.50	20.82	H	3.0	-1.3	16.53	38.5	-22.0	
High Ch								
846.50	17.91	V	3.0	-1.1	13.73	38.5	-24.8	
846.50	20.77	H	3.0	-1.1	16.59	38.5	-21.9	

LTE Band 26

5MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 26 Fundamentals, 5MHz Bandwidth

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Straddle Ch								
824.00	16.37	V	3.0	-1.3	12.03	38.5	-26.5	
824.00	19.46	H	3.0	-1.3	15.12	38.5	-23.4	
Low Ch								
826.50	17.04	V	3.0	-1.3	12.72	38.5	-25.8	
826.50	19.35	H	3.0	-1.3	15.02	38.5	-23.5	
Mid Ch								
831.50	16.27	V	3.0	-1.3	11.98	38.5	-26.5	
831.50	18.85	H	3.0	-1.3	14.56	38.5	-23.9	
High Ch								
846.50	15.39	V	3.0	-1.1	11.21	38.5	-27.3	
846.50	19.21	H	3.0	-1.1	15.03	38.5	-23.5	

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26

3MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/8/2021
Test Engineer: 19568
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 26 Fundamentals, 3MHz Bandwidth

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
824.00	17.99	V	3.0	-1.3	13.65	38.5	-24.8	
824.00	21.48	H	3.0	-1.3	17.14	38.5	-21.4	
Mid Ch								
825.50	18.22	V	3.0	-1.3	13.89	38.5	-24.6	
825.50	21.59	H	3.0	-1.3	17.26	38.5	-21.2	
Mid Ch								
831.50	18.33	V	3.0	-1.3	14.04	38.5	-24.5	
831.50	20.97	H	3.0	-1.3	16.68	38.5	-21.8	
High Ch								
847.50	17.73	V	3.0	-1.1	13.56	38.5	-24.9	
847.50	20.88	H	3.0	-1.1	16.71	38.5	-21.8	

LTE Band 26

3MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/8/2021
Test Engineer: 19568
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 26 Fundamentals, 3MHz Bandwidth

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
824.00	15.94	V	3.0	-1.3	11.60	38.5	-26.9	
824.00	19.24	H	3.0	-1.3	14.90	38.5	-23.6	
Mid Ch								
825.50	15.38	V	3.0	-1.3	11.05	38.5	-27.4	
825.50	19.29	H	3.0	-1.3	14.96	38.5	-23.5	
Mid Ch								
831.50	16.12	V	3.0	-1.3	11.83	38.5	-26.7	
831.50	18.96	H	3.0	-1.3	14.67	38.5	-23.8	
High Ch								
847.50	15.58	V	3.0	-1.1	11.41	38.5	-27.1	
847.50	19.26	H	3.0	-1.1	15.09	38.5	-23.4	

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26

1.4MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/8/2021
Test Engineer: 19568
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 26 Fundamentals, 1.4MHz Bandwidth

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Straddle Ch								
824.00	17.75	V	3.0	-1.3	13.41	38.5	-25.1	
824.00	21.35	H	3.0	-1.3	17.01	38.5	-21.5	
Low Ch								
824.70	17.82	V	3.0	-1.3	13.48	38.5	-25.0	
824.70	21.41	H	3.0	-1.3	17.08	38.5	-21.4	
Mid Ch								
831.50	18.43	V	3.0	-1.3	14.14	38.5	-24.4	
831.50	21.08	H	3.0	-1.3	16.79	38.5	-21.7	
High Ch								
848.30	18.07	V	3.1	-1.1	13.90	38.5	-24.6	
848.30	20.97	H	3.1	-1.1	16.80	38.5	-21.7	

LTE Band 26

1.4MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/8/2021
Test Engineer: 19568
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 26 Fundamentals, 1.4MHz Bandwidth

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Straddle Ch								
824.00	15.69	V	3.0	-1.3	11.35	38.5	-27.1	
824.00	19.48	H	3.0	-1.3	15.14	38.5	-23.4	
Low Ch								
831.50	15.66	V	3.0	-1.3	11.37	38.5	-27.1	
831.50	19.33	H	3.0	-1.3	15.04	38.5	-23.5	
Mid Ch								
831.50	16.34	V	3.0	-1.3	12.05	38.5	-26.5	
831.50	18.87	H	3.0	-1.3	14.58	38.5	-23.9	
High Ch								
848.30	16.01	V	3.1	-1.1	11.84	38.5	-26.7	
848.30	18.89	H	3.1	-1.1	14.72	38.5	-23.8	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26 (Part 90)

LTE Band 26

15MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 26 Fundamentals, 15MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
821.50	18.14	V	3.0	-1.4	13.77	50.0	-36.2	Part 90
821.50	21.48	H	3.0	-1.4	17.11	50.0	-32.9	Part 90

LTE Band 26

15MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 26 Fundamentals, 15MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
821.50	16.28	V	3.0	-1.4	11.91	50.0	-38.1	Part 90
821.50	19.35	H	3.0	-1.4	14.98	50.0	-35.0	Part 90

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26

10MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 26 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
819.00	18.11	V	3.0	-1.4	13.73	50.0	-36.3	Part 90
819.00	21.14	H	3.0	-1.4	16.76	50.0	-33.2	Part 90

LTE Band 26

10MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 26 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
819.00	16.09	V	3.0	-1.4	11.71	50.0	-38.3	Part 90
819.00	19.40	H	3.0	-1.4	15.02	50.0	-35.0	Part 90

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE
Band 26

5MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 26 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
816.50	17.45	V	3.0	-1.4	13.05	50.0	-37.0	Part 90
816.50	21.35	H	3.0	-1.4	16.95	50.0	-33.1	Part 90
Mid Ch								
821.50	18.45	V	3.0	-1.4	14.08	50.0	-35.9	Part 90
821.50	21.63	H	3.0	-1.4	17.26	50.0	-32.7	Part 90

LTE
Band 26

5MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 26 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
816.50	15.32	V	3.0	-1.4	10.92	50.0	-39.1	Part 90
816.50	19.53	H	3.0	-1.4	15.13	50.0	-34.9	Part 90
Mid Ch								
821.50	16.39	V	3.0	-1.4	12.02	50.0	-38.0	Part 90
821.50	19.58	H	3.0	-1.4	15.21	50.0	-34.8	Part 90

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE
Band 26

3MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 26 Fundamentals, 3MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
815.50	17.51	V	3.0	-1.4	13.10	50.0	-36.9	Part 90
815.50	21.34	H	3.0	-1.4	16.94	50.0	-33.1	Part 90
Mid Ch								
822.50	18.66	V	3.0	-1.3	14.31	50.0	-35.7	Part 90
822.50	21.44	H	3.0	-1.3	17.08	50.0	-32.9	Part 90

LTE
Band 26

3MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 20881
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 26 Fundamentals, 3MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
815.50	15.41	V	3.0	-1.4	11.00	50.0	-39.0	Part 90
815.50	19.46	H	3.0	-1.4	15.06	50.0	-34.9	Part 90
Mid Ch								
822.50	16.47	V	3.0	-1.3	12.12	50.0	-37.9	Part 90
822.50	19.46	H	3.0	-1.3	15.10	50.0	-34.9	Part 90

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE
Band 26

1.4MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 19227
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_QPSK Band 26 Fundamentals, 1.4MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
814.70	17.24	V	3.0	-1.4	12.83	50.0	-37.2	Part 90
814.70	20.84	H	3.0	-1.4	16.43	50.0	-33.6	Part 90
Mid Ch								
823.30	18.45	V	3.0	-1.3	14.10	50.0	-35.9	Part 90
823.30	21.28	H	3.0	-1.3	16.93	50.0	-33.1	Part 90

LTE
Band 26

1.4MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/7/2021
Test Engineer: 19227
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: LTE_16QAM Band 26 Fundamentals, 1.4MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
814.70	15.17	V	3.0	-1.4	10.76	50.0	-39.2	Part 90
814.70	19.64	H	3.0	-1.4	15.23	50.0	-34.8	Part 90
Mid Ch								
823.30	16.23	V	3.0	-1.3	11.88	50.0	-38.1	Part 90
823.30	19.10	H	3.0	-1.3	14.75	50.0	-35.2	Part 90

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41 (PC2)

LTE Band 41

20MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/6/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 41 Fundamentals, 20MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
2506.00	14.68	V	5.2	10.2	19.60	33.0	-13.4	
2506.00	17.89	H	5.2	10.2	22.81	33.0	-10.2	
Mid Ch								
2593.00	13.30	V	5.3	10.0	18.00	33.0	-15.0	
2593.00	16.20	H	5.3	10.0	20.89	33.0	-12.1	
High Ch								
2680.00	16.42	V	5.4	10.1	21.04	33.0	-12.0	
2680.00	17.88	H	5.4	10.1	22.50	33.0	-10.5	

LTE Band 41

20MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/6/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 41 Fundamentals, 20MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
2506.00	13.94	V	5.2	10.2	18.86	33.0	-14.1	
2506.00	17.59	H	5.2	10.2	22.51	33.0	-10.5	
Mid Ch								
2593.00	12.92	V	5.3	10.0	17.62	33.0	-15.4	
2593.00	16.16	H	5.3	10.0	20.85	33.0	-12.1	
High Ch								
2680.00	16.59	V	5.4	10.1	21.21	33.0	-11.8	
2680.00	16.65	H	5.4	10.1	21.27	33.0	-11.7	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41

15MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/6/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 41 Fundamentals, 15MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
2503.50	14.46	V	5.2	10.2	19.38	33.0	-13.6	
2503.50	17.56	H	5.2	10.2	22.49	33.0	-10.5	
Mid Ch								
2593.00	13.62	V	5.3	10.0	18.32	33.0	-14.7	
2593.00	16.77	H	5.3	10.0	21.46	33.0	-11.5	
High Ch								
2682.50	15.75	V	5.4	10.1	20.37	33.0	-12.6	
2682.50	17.84	H	5.4	10.1	22.46	33.0	-10.5	

LTE Band 41

15MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/6/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 41 Fundamentals, 15MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
2503.50	14.05	V	5.2	10.2	18.97	33.0	-14.0	
2503.50	18.10	H	5.2	10.2	23.03	33.0	-10.0	
Mid Ch								
2593.00	12.15	V	5.3	10.0	16.85	33.0	-16.2	
2593.00	15.36	H	5.3	10.0	20.05	33.0	-12.9	
High Ch								
2682.50	17.04	V	5.4	10.1	21.66	33.0	-11.3	
2682.50	17.29	H	5.4	10.1	21.91	33.0	-11.1	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41

10MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/5/2021
Test Engineer: 47989
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 41 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
2501.00	14.95	V	5.2	10.2	19.89	33.0	-13.1	
2501.00	18.16	H	5.2	10.2	23.10	33.0	-9.9	
Mid Ch								
2593.00	13.63	V	5.3	10.0	18.33	33.0	-14.7	
2593.00	16.55	H	5.3	10.0	21.24	33.0	-11.8	
High Ch								
2685.00	16.10	V	5.4	10.1	20.72	33.0	-12.3	
2685.00	17.71	H	5.4	10.1	22.33	33.0	-10.7	

LTE Band 41

10MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/5/2021
Test Engineer: 47989
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 41 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
2501.00	14.28	V	5.2	10.2	19.22	33.0	-13.8	
2501.00	17.69	H	5.2	10.2	22.63	33.0	-10.4	
Mid Ch								
2593.00	12.32	V	5.3	10.0	17.02	33.0	-16.0	
2593.00	15.04	H	5.3	10.0	19.73	33.0	-13.3	
High Ch								
2685.00	15.69	V	5.4	10.1	20.31	33.0	-12.7	
2685.00	17.32	H	5.4	10.1	21.94	33.0	-11.1	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41

5MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/5/2021
Test Engineer: 47989
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 41 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
2498.50	14.92	V	5.2	10.2	19.86	33.0	-13.1	
2498.50	18.05	H	5.2	10.2	22.99	33.0	-10.0	
Mid Ch								
2593.00	13.51	V	5.3	10.0	18.21	33.0	-14.8	
2593.00	16.28	H	5.3	10.0	20.97	33.0	-12.0	
High Ch								
2687.50	16.60	V	5.4	10.1	21.22	33.0	-11.8	
2687.50	18.52	H	5.4	10.1	23.14	33.0	-9.9	

LTE Band 41

5MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/5/2021
Test Engineer: 47989
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 41 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
2498.50	14.35	V	5.2	10.2	19.29	33.0	-13.7	
2498.50	17.43	H	5.2	10.2	22.37	33.0	-10.6	
Mid Ch								
2593.00	12.83	V	5.3	10.0	17.53	33.0	-15.5	
2593.00	15.76	H	5.3	10.0	20.45	33.0	-12.5	
High Ch								
2687.50	15.62	V	5.4	10.1	20.24	33.0	-12.8	
2687.50	17.16	H	5.4	10.1	21.78	33.0	-11.2	

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 66

LTE Band 66

20MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 66 Fundamentals, 20MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1720.00	10.51	V	4.3	9.6	15.80	30.0	-14.2	
1720.00	17.74	H	4.3	9.6	23.03	30.0	-7.0	
Mid Ch								
1745.00	12.63	V	4.3	9.7	17.98	30.0	-12.0	
1745.00	17.83	H	4.3	9.7	23.18	30.0	-6.8	
High Ch								
1770.00	12.69	V	4.4	9.7	18.02	30.0	-12.0	
1770.00	17.49	H	4.4	9.7	22.83	30.0	-7.2	

LTE Band 66

20MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 66 Fundamentals, 20MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1720.00	9.08	V	4.3	9.6	14.37	30.0	-15.6	
1720.00	15.81	H	4.3	9.6	21.10	30.0	-8.9	
Mid Ch								
1745.00	10.82	V	4.3	9.7	16.17	30.0	-13.8	
1745.00	16.08	H	4.3	9.7	21.43	30.0	-8.6	
High Ch								
1770.00	10.14	V	4.4	9.7	15.47	30.0	-14.5	
1770.00	15.11	H	4.4	9.7	20.45	30.0	-9.6	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 66

15MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 66 Fundamentals, 15MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1717.50	10.31	V	4.3	9.6	15.60	30.0	-14.4	
1717.50	17.87	H	4.3	9.6	23.16	30.0	-6.8	
Mid Ch								
1745.00	12.13	V	4.3	9.7	17.48	30.0	-12.5	
1745.00	16.96	H	4.3	9.7	22.31	30.0	-7.7	
High Ch								
1772.50	10.88	V	4.4	9.7	16.21	30.0	-13.8	
1772.50	17.56	H	4.4	9.7	22.89	30.0	-7.1	

LTE Band 66

15MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 66 Fundamentals, 15MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1717.50	8.63	V	4.3	9.6	13.92	30.0	-16.1	
1717.50	15.79	H	4.3	9.6	21.08	30.0	-8.9	
Mid Ch								
1745.00	10.28	V	4.3	9.7	15.63	30.0	-14.4	
1745.00	15.10	H	4.3	9.7	20.45	30.0	-9.6	
High Ch								
1772.50	8.95	V	4.4	9.7	14.28	30.0	-15.7	
1772.50	15.36	H	4.4	9.7	20.69	30.0	-9.3	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 66

10MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 66 Fundamentals, 10MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1715.00	10.11	V	4.3	9.6	15.39	30.0	-14.6	
1715.00	17.50	H	4.3	9.6	22.78	30.0	-7.2	
Mid Ch								
1745.00	12.28	V	4.3	9.7	17.63	30.0	-12.4	
1745.00	16.87	H	4.3	9.7	22.22	30.0	-7.8	
High Ch								
1775.00	11.31	V	4.4	9.7	16.64	30.0	-13.4	
1775.00	17.28	H	4.4	9.7	22.61	30.0	-7.4	

LTE Band 66

10MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 66 Fundamentals, 10MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1715.00	8.31	V	4.3	9.6	13.59	30.0	-16.4	
1715.00	15.47	H	4.3	9.6	20.75	30.0	-9.2	
Mid Ch								
1745.00	10.34	V	4.3	9.7	15.69	30.0	-14.3	
1745.00	15.11	H	4.3	9.7	20.46	30.0	-9.5	
High Ch								
1775.00	10.10	V	4.4	9.7	15.43	30.0	-14.6	
1775.00	15.76	H	4.4	9.7	21.09	30.0	-8.9	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 66

5MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 66 Fundamentals, 5MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1712.50	10.16	V	4.3	9.6	15.44	30.0	-14.6	
1712.50	17.45	H	4.3	9.6	22.73	30.0	-7.3	
Mid Ch								
1745.00	12.56	V	4.3	9.7	17.91	30.0	-12.1	
1745.00	16.87	H	4.3	9.7	22.22	30.0	-7.8	
High Ch								
1777.50	11.74	V	4.4	9.7	17.07	30.0	-12.9	
1777.50	17.64	H	4.4	9.7	22.97	30.0	-7.0	

LTE Band 66

5MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 66 Fundamentals, 5MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1712.50	8.47	V	4.3	9.6	13.75	30.0	-16.3	
1712.50	15.45	H	4.3	9.6	20.73	30.0	-9.3	
Mid Ch								
1745.00	10.42	V	4.3	9.7	15.77	30.0	-14.2	
1745.00	14.98	H	4.3	9.7	20.33	30.0	-9.7	
High Ch								
1777.50	9.74	V	4.4	9.7	15.07	30.0	-14.9	
1777.50	15.52	H	4.4	9.7	20.85	30.0	-9.2	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 66

3MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 66 Fundamentals, 3MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1711.50	10.37	V	4.3	9.6	15.64	30.0	-14.4	
1711.50	17.65	H	4.3	9.6	22.92	30.0	-7.1	
Mid Ch								
1745.00	12.34	V	4.3	9.7	17.69	30.0	-12.3	
1745.00	17.29	H	4.3	9.7	22.64	30.0	-7.4	
High Ch								
1778.50	11.63	V	4.4	9.7	16.96	30.0	-13.0	
1778.50	17.61	H	4.4	9.7	22.94	30.0	-7.1	

LTE Band 66

3MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 66 Fundamentals, 3MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1711.50	8.03	V	4.3	9.6	13.30	30.0	-16.7	
1711.50	15.51	H	4.3	9.6	20.78	30.0	-9.2	
Mid Ch								
1745.00	10.64	V	4.3	9.7	15.99	30.0	-14.0	
1745.00	15.18	H	4.3	9.7	20.53	30.0	-9.5	
High Ch								
1778.50	9.64	V	4.4	9.7	14.97	30.0	-15.0	
1778.50	15.45	H	4.4	9.7	20.78	30.0	-9.2	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 66

1.4MHz

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 66 Fundamentals, 1.4MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1710.70	11.17	V	4.3	9.6	16.44	30.0	-13.6	
1710.70	17.62	H	4.3	9.6	22.89	30.0	-7.1	
Mid Ch								
1745.00	12.26	V	4.3	9.7	17.61	30.0	-12.4	
1745.00	16.97	H	4.3	9.7	22.32	30.0	-7.7	
High Ch								
1779.30	11.74	V	4.4	9.7	17.07	30.0	-12.9	
1779.30	17.69	H	4.4	9.7	23.01	30.0	-7.0	

LTE Band 66

1.4MHz

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 19568
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM Band 66 Fundamentals, 1.4MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1710.70	9.13	V	4.3	9.6	14.40	30.0	-15.6	
1710.70	15.36	H	4.3	9.6	20.63	30.0	-9.4	
Mid Ch								
1745.00	10.26	V	4.3	9.7	15.61	30.0	-14.4	
1745.00	14.78	H	4.3	9.7	20.13	30.0	-9.9	
High Ch								
1779.30	9.64	V	4.4	9.7	14.97	30.0	-15.0	
1779.30	15.61	H	4.4	9.7	20.93	30.0	-9.1	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR Band 5

NR Band 5

20MHz

DFT-s

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 19568
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: LTE_QPSK NR n5 Fundamentals, 20MHz Bandwidth

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
834.00	22.54	V	3.0	-1.2	18.27	38.5	-20.2	
834.00	10.69	H	3.0	-1.2	6.42	38.5	-32.1	
Mid Ch								
836.50	22.56	V	3.0	-1.2	18.31	38.5	-20.2	
836.50	11.09	H	3.0	-1.2	6.84	38.5	-31.7	
High Ch								
839.00	22.75	V	3.0	-1.2	18.52	38.5	-20.0	
839.00	11.08	H	3.0	-1.2	6.85	38.5	-31.7	

NR Band 5

20MHz

DFT-s

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 19568
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: LTE_16QAM NR n5 Fundamentals, 20MHz Bandwidth

Test Equpment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
834.00	21.28	V	3.0	-1.2	17.01	38.5	-21.5	
834.00	9.64	H	3.0	-1.2	5.37	38.5	-33.1	
Mid Ch								
836.50	21.30	V	3.0	-1.2	17.05	38.5	-21.4	
836.50	9.78	H	3.0	-1.2	5.53	38.5	-33.0	
High Ch								
839.00	21.59	V	3.0	-1.2	17.36	38.5	-21.1	
839.00	9.83	H	3.0	-1.2	5.60	38.5	-32.9	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR
Band 5

15MHz

DFT-s

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 22943
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: LTE_QPSK NR n5 Fundamentals, 15MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
831.50	23.31	V	3.0	-1.3	19.02	38.5	-19.5	
831.50	10.73	H	3.0	-1.3	6.44	38.5	-32.1	
Mid Ch								
836.50	22.80	V	3.0	-1.2	18.55	38.5	-19.9	
836.50	10.95	H	3.0	-1.2	6.70	38.5	-31.8	
High Ch								
841.50	22.47	V	3.0	-1.2	18.26	38.5	-20.2	
841.50	10.98	H	3.0	-1.2	6.77	38.5	-31.7	

NR
Band 5

15MHz

DFT-s

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 22943
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: LTE_16QAM NR n5 Fundamentals, 15MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
831.50	22.33	V	3.0	-1.3	18.04	38.5	-20.5	
831.50	9.32	H	3.0	-1.3	5.03	38.5	-33.5	
Mid Ch								
836.50	21.60	V	3.0	-1.2	17.35	38.5	-21.1	
836.50	9.66	H	3.0	-1.2	5.41	38.5	-33.1	
High Ch								
841.50	21.29	V	3.0	-1.2	17.08	38.5	-21.4	
841.50	9.69	H	3.0	-1.2	5.48	38.5	-33.0	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR
Band 5

10MHz

DFT-s

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 22943
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: LTE_QPSK NR n5 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
829.00	23.38	V	3.0	-1.3	19.07	38.5	-19.4	
829.00	10.54	H	3.0	-1.3	6.23	38.5	-32.3	
Mid Ch								
836.50	22.79	V	3.0	-1.2	18.54	38.5	-20.0	
836.50	10.75	H	3.0	-1.2	6.50	38.5	-32.0	
High Ch								
844.00	22.70	V	3.0	-1.2	18.50	38.5	-20.0	
844.00	11.32	H	3.0	-1.2	7.12	38.5	-31.4	

NR
Band 5

10MHz

DFT-s

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 22943
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: LTE_16QAM NR n5 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
829.00	22.36	V	3.0	-1.3	18.05	38.5	-20.4	
829.00	9.49	H	3.0	-1.3	5.18	38.5	-33.3	
Mid Ch								
836.50	21.85	V	3.0	-1.2	17.60	38.5	-20.9	
836.50	9.64	H	3.0	-1.2	5.39	38.5	-33.1	
High Ch								
844.00	21.53	V	3.0	-1.2	17.33	38.5	-21.2	
844.00	9.80	H	3.0	-1.2	5.60	38.5	-32.9	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR Band 5

5MHz

DFT-s

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 22943
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: LTE_QPSK NR n5 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
826.50	23.27	V	3.0	-1.3	18.95	38.5	-19.6	
826.50	10.48	H	3.0	-1.3	6.15	38.5	-32.3	
Mid Ch								
836.50	22.94	V	3.0	-1.2	18.69	38.5	-19.8	
836.50	10.68	H	3.0	-1.2	6.43	38.5	-32.1	
High Ch								
846.50	22.67	V	3.0	-1.1	18.49	38.5	-20.0	
846.50	11.16	H	3.0	-1.1	6.98	38.5	-31.5	

NR Band 5

5MHz

DFT-s

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 22943
Configuration: EUT, Z-Position
Location: Chamber 1
Mode: LTE_16QAM NR n5 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: VULB9163-750, and Chamber 1 SMA Cables
Substitution: Dipole 3121_DB4, 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBd)	ERP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
826.50	21.86	V	3.0	-1.3	17.54	38.5	-21.0	
826.50	9.28	H	3.0	-1.3	4.95	38.5	-33.5	
Mid Ch								
836.50	21.60	V	3.0	-1.2	17.35	38.5	-21.1	
836.50	9.36	H	3.0	-1.2	5.11	38.5	-33.4	
High Ch								
846.50	21.45	V	3.0	-1.1	17.27	38.5	-21.2	
846.50	9.90	H	3.0	-1.1	5.72	38.5	-32.8	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR Band 66

NR Band 66

20MHz

DFT-s

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/14/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK NR n66 Fundamentals, 20MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1720.00	11.46	V	4.3	9.6	16.75	30.0	-13.2	
1720.00	18.63	H	4.3	9.6	23.92	30.0	-6.1	
Mid Ch								
1745.00	12.56	V	4.3	9.7	17.91	30.0	-12.1	
1745.00	18.35	H	4.3	9.7	23.70	30.0	-6.3	
High Ch								
1770.00	11.79	V	4.4	9.7	17.12	30.0	-12.9	
1770.00	18.75	H	4.4	9.7	24.09	30.0	-5.9	

NR Band 66

20MHz

DFT-s

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/14/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM NR n66 Fundamentals, 20MHz Bandwidth

Test Equpment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1720.00	9.59	V	4.3	9.6	14.88	30.0	-15.1	
1720.00	17.28	H	4.3	9.6	22.57	30.0	-7.4	
Mid Ch								
1745.00	10.78	V	4.3	9.7	16.13	30.0	-13.9	
1745.00	17.17	H	4.3	9.7	22.52	30.0	-7.5	
High Ch								
1770.00	10.00	V	4.4	9.7	15.33	30.0	-14.7	
1770.00	17.51	H	4.4	9.7	22.85	30.0	-7.2	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR
Band 66

15MHz

DFT-s

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/14/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK NR n66 Fundamentals, 15MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1717.50	11.43	V	4.3	9.6	16.72	30.0	-13.3	
1717.50	18.73	H	4.3	9.6	24.02	30.0	-6.0	
Mid Ch								
1745.00	12.73	V	4.3	9.7	18.08	30.0	-11.9	
1745.00	18.29	H	4.3	9.7	23.64	30.0	-6.4	
High Ch								
1772.50	10.89	V	4.4	9.7	16.22	30.0	-13.8	
1772.50	18.19	H	4.4	9.7	23.52	30.0	-6.5	

NR
Band 66

15MHz

DFT-s

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/14/2021
Test Engineer: 22943
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM NR n66 Fundamentals, 15MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1717.50	9.50	V	4.3	9.6	14.79	30.0	-15.2	
1717.50	17.45	H	4.3	9.6	22.74	30.0	-7.3	
Mid Ch								
1745.00	10.82	V	4.3	9.7	16.17	30.0	-13.8	
1745.00	17.00	H	4.3	9.7	22.35	30.0	-7.7	
High Ch								
1772.50	8.80	V	4.4	9.7	14.13	30.0	-15.9	
1772.50	17.15	H	4.4	9.7	22.48	30.0	-7.5	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR
Band 66

10MHz

DFT-s

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 20882
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK NR n66 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1715.00	11.75	V	4.3	9.6	17.03	30.0	-13.0	
1715.00	18.85	H	4.3	9.6	24.13	30.0	-5.9	
Mid Ch								
1745.00	12.59	V	4.3	9.7	17.94	30.0	-12.1	
1745.00	18.86	H	4.3	9.7	24.21	30.0	-5.8	
High Ch								
1775.00	10.81	V	4.4	9.7	16.14	30.0	-13.9	
1775.00	18.43	H	4.4	9.7	23.76	30.0	-6.2	

NR
Band 66

10MHz

DFT-s

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 20882
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM NR n66 Fundamentals, 10MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1715.00	9.39	V	4.3	9.6	14.67	30.0	-15.3	
1715.00	17.62	H	4.3	9.6	22.90	30.0	-7.1	
Mid Ch								
1745.00	10.29	V	4.3	9.7	15.64	30.0	-14.4	
1745.00	17.53	H	4.3	9.7	22.88	30.0	-7.1	
High Ch								
1775.00	9.04	V	4.4	9.7	14.37	30.0	-15.6	
1775.00	17.20	H	4.4	9.7	22.53	30.0	-7.5	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR
Band 66

5MHz

DFT-s

QPSK

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 20882
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_QPSK NR n66 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1712.50	11.55	V	4.3	9.6	16.83	30.0	-13.2	
1712.50	18.26	H	4.3	9.6	23.54	30.0	-6.5	
Mid Ch								
1745.00	12.90	V	4.3	9.7	18.25	30.0	-11.8	
1745.00	18.78	H	4.3	9.7	24.13	30.0	-5.9	
High Ch								
1777.50	10.53	V	4.4	9.7	15.86	30.0	-14.1	
1777.50	18.06	H	4.4	9.7	23.39	30.0	-6.6	

NR
Band 66

5MHz

DFT-s

16QAM

UL Verification Services, Inc.
High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/13/2021
Test Engineer: 20882
Configuration: EUT, X-Position
Location: Chamber 1
Mode: LTE_16QAM NR n66 Fundamentals, 5MHz Bandwidth

Test Equipment:
Receiving: Horn 3117[00168717], and Chamber 1 SMA Cables
Substitution: Horn 3115[00167211], 8.5m SMA-type Cable

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Cable Loss (dB)	Antenna Gain (dBi)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch								
1712.50	9.50	V	4.3	9.6	14.78	30.0	-15.2	
1712.50	17.42	H	4.3	9.6	22.70	30.0	-7.3	
Mid Ch								
1745.00	10.87	V	4.3	9.7	16.22	30.0	-13.8	
1745.00	17.51	H	4.3	9.7	22.86	30.0	-7.1	
High Ch								
1777.50	8.75	V	4.4	9.7	14.08	30.0	-15.9	
1777.50	16.97	H	4.4	9.7	22.30	30.0	-7.7	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

9.6. FIELD STRENGTH OF SPURIOUS RADIATION

RULE PART(S)

FCC: §2.1053, §22.917, §24.238, §27. 53 and §90.691

LIMIT

Part 22.917(a) & Part 24.238(a) & Part 27.53(h) The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least 43 + 10 log (P) dB.

Part 27.53:
(c)(2) On any frequency outside the 776-788 MHz band, the power of any emission shall be attenuated outside the band below the transmitter power (P) by at least 43 + 10 log (P) dB.

(f) For operations in the 746-758 MHz, 775-788 MHz, and 805-806 MHz bands, emissions in the band 1559-1610 MHz shall be limited to −70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and −80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth.

(g) For operations in the 600 MHz band and the 698-746 MHz band, the power of any emission outside a licensee's frequency band(s) of operation shall be attenuated below the transmitter power (P) within the licensed band(s) of operation, measured in watts, by at least 43 + 10 log (P) dB.

(h) The power of any emission outside a licensee's frequency block shall be attenuated below the transmitter power (P) in watts by at least 43 + 10 $\log_{10}$ (P) dB.

(m) (4) For mobile digital stations, the attenuation factor shall be not less than 40 + 10 log (P) dB on all frequencies between the channel edge and 5 megahertz from the channel edge, 43 + 10 log (P) dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and 55 + 10 log (P) dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less that 43 + 10 log (P) dB on all frequencies between 2490.5 MHz and 2496 MHz and 55 + 10 log (P) dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

Part 90.691(a):

(1) For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 116 Log10(f/6.1) decibels or 50 + 10 Log10(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.

(2) For any frequency removed from the EA licensee's frequency block greater than 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least 43 + 10Log_{10}(P) decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 37.5 kHz.(NOTE : Use 100kHz reference bandwidth)

(b) When an emission outside of the authorized bandwidth causes harmful interference, the Commission may, at its discretion, require greater attenuation than specified in this section.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

TEST PROCEDURE

ANSI / TIA / EIA 603 E Clause 2.2.12; ESU40 setting reference to 971168 D01 v03r01

For peak power measurement with a ESU40:
a) Set the RBW = 100 KHz for emission below 1GHz and 1MHz for emissions above 1GHz
b) Set VBW ≥ 3 × RBW;
c) Set span ≥ 1.5 times the OBW;
d) Sweep time = auto couple;
e) Detector = rms;
f) Ensure that the number of measurement points ≥ span/RBW;
g) Trace mode = average(WCDMA, LTE FDD, NR), Maxhold(GSM, LTE TDD);

NOTE

5G NR: All Waveforms (CP-OFDM vs DFT-s OFDM) and modulations (QPSK, 16QAM, 64QAM, 256QAM) were investigated to determine the worst case configuration. All modes of operation were investigated and the worst case configuration results are reported in this section.

RESULTS

See the following pages.

NOTE : Please refer to section 5.4 for bandwidth and RB setting about LTE,NR bands.

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

9.6.1. SPURIOUS RADIATION PLOTS

GSM850

GSM850

GPRS

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/27/2021
Test Engineer: 22943
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: GPRS 850 MHz Harmonics
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 824.2MHz									
1648.40	-6.7	V	3.0	45.6	1.0	-51.4	-13.0	-38.4	
2472.60	4.8	V	3.0	45.4	1.0	-39.7	-13.0	-26.7	
3296.80	-8.9	V	3.0	45.7	1.0	-53.6	-13.0	-40.6	
1648.40	-12.7	H	3.0	45.6	1.0	-57.3	-13.0	-44.3	
2472.60	0.9	H	3.0	45.4	1.0	-43.5	-13.0	-30.5	
3296.80	-8.8	H	3.0	45.7	1.0	-53.5	-13.0	-40.5	
Mid Ch, 836.6MHz									
1673.20	-6.1	V	3.0	45.6	1.0	-50.7	-13.0	-37.7	
2509.80	6.9	V	3.0	45.5	1.0	-37.5	-13.0	-24.5	
3346.40	-8.8	V	3.0	45.7	1.0	-53.5	-13.0	-40.5	
1673.20	-13.4	H	3.0	45.6	1.0	-58.0	-13.0	-45.0	
2509.80	2.1	H	3.0	45.5	1.0	-42.4	-13.0	-29.4	
3346.40	-8.5	H	3.0	45.7	1.0	-53.2	-13.0	-40.2	
High Ch, 848.8MHz									
1697.60	-4.2	V	3.0	45.6	1.0	-48.8	-13.0	-35.8	
2546.40	6.2	V	3.0	45.5	1.0	-38.2	-13.0	-25.2	
3395.20	-8.4	V	3.0	45.7	1.0	-53.1	-13.0	-40.1	
1697.60	-9.6	H	3.0	45.6	1.0	-54.2	-13.0	-41.2	
2546.40	3.2	H	3.0	45.5	1.0	-41.3	-13.0	-28.3	
3395.20	-8.5	H	3.0	45.7	1.0	-53.2	-13.0	-40.2	

GSM850

EGPRS

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/27/2021
Test Engineer: 22943
Configuration: EUT, Y-Position
Location: Chamber 1
Mode: EGPRS 850 MHz Harmonics
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 824.2MHz									
1648.40	-13.9	V	3.0	45.6	1.0	-58.6	-13.0	-45.6	
2472.60	-7.9	V	3.0	45.4	1.0	-52.4	-13.0	-39.4	
3296.80	-8.9	V	3.0	45.7	1.0	-53.6	-13.0	-40.6	
1648.40	-15.3	H	3.0	45.6	1.0	-60.0	-13.0	-47.0	
2472.60	-9.3	H	3.0	45.4	1.0	-53.8	-13.0	-40.8	
3296.80	-8.8	H	3.0	45.7	1.0	-53.5	-13.0	-40.5	
Mid Ch, 836.6MHz									
1673.20	-14.2	V	3.0	45.6	1.0	-58.8	-13.0	-45.8	
2509.80	-5.5	V	3.0	45.5	1.0	-49.9	-13.0	-36.9	
3346.40	-8.6	V	3.0	45.7	1.0	-53.3	-13.0	-40.3	
1673.20	-15.4	H	3.0	45.6	1.0	-60.0	-13.0	-47.0	
2509.80	-9.7	H	3.0	45.5	1.0	-54.2	-13.0	-41.2	
3346.40	-8.6	H	3.0	45.7	1.0	-53.3	-13.0	-40.3	
High Ch, 848.8MHz									
1697.60	-13.8	V	3.0	45.6	1.0	-58.4	-13.0	-45.4	
2546.40	-8.2	V	3.0	45.5	1.0	-52.7	-13.0	-39.7	
3395.20	-8.4	V	3.0	45.7	1.0	-53.1	-13.0	-40.1	
1697.60	-15.2	H	3.0	45.6	1.0	-59.7	-13.0	-46.7	
2546.40	-9.4	H	3.0	45.5	1.0	-53.9	-13.0	-40.9	
3395.20	-8.3	H	3.0	45.7	1.0	-53.0	-13.0	-40.0	

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

GSM1900

GSM1900

GPRS

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 22943
Configuration: EUT / AC Adapter, X-Position
Location: Chamber 1
Mode: GPRS 1900 MHz Harmonics
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3700.40	-10.4	V	3.0	45.8	1.0	-55.2	-13.0	-42.2	
5550.60	-8.0	V	3.0	45.7	1.0	-52.8	-13.0	-39.8	
7400.80	-4.8	V	3.0	44.6	1.0	-48.3	-13.0	-35.3	
3700.40	-10.3	H	3.0	45.8	1.0	-55.1	-13.0	-42.1	
5550.60	-8.1	H	3.0	45.7	1.0	-52.9	-13.0	-39.9	
7400.80	-5.1	H	3.0	44.6	1.0	-48.7	-13.0	-35.7	
Mid Ch, 1880MHz									
3760.00	-10.1	V	3.0	45.8	1.0	-54.9	-13.0	-41.9	
5640.00	-7.6	V	3.0	45.7	1.0	-52.4	-13.0	-39.4	
7520.00	-5.0	V	3.0	44.5	1.0	-48.5	-13.0	-35.5	
3760.00	-9.9	H	3.0	45.8	1.0	-54.8	-13.0	-41.8	
5640.00	-7.6	H	3.0	45.7	1.0	-52.4	-13.0	-39.4	
7520.00	-5.2	H	3.0	44.5	1.0	-48.7	-13.0	-35.7	
High Ch, 1909.8MHz									
3819.60	-9.9	V	3.0	45.8	1.0	-54.8	-13.0	-41.8	
5729.40	-7.6	V	3.0	45.7	1.0	-52.3	-13.0	-39.3	
7639.20	-4.9	V	3.0	44.4	1.0	-48.3	-13.0	-35.3	
3819.60	-10.1	H	3.0	45.8	1.0	-55.0	-13.0	-42.0	
5729.40	-7.6	H	3.0	45.7	1.0	-52.4	-13.0	-39.4	
7639.20	-4.9	H	3.0	44.4	1.0	-48.3	-13.0	-35.3	

GSM1900

EGPRS

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 22943
Configuration: EUT / AC Adapter, X-Position
Location: Chamber 1
Mode: EGPRS 1900 MHz Harmonics
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1850.2MHz									
3700.40	-10.5	V	3.0	45.8	1.0	-55.3	-13.0	-42.3	
5550.60	-8.0	V	3.0	45.7	1.0	-52.8	-13.0	-39.8	
7400.80	-5.1	V	3.0	44.6	1.0	-48.6	-13.0	-35.6	
3700.40	-10.6	H	3.0	45.8	1.0	-55.4	-13.0	-42.4	
5550.60	-8.1	H	3.0	45.7	1.0	-52.9	-13.0	-39.9	
7400.80	-5.3	H	3.0	44.6	1.0	-48.9	-13.0	-35.9	
Mid Ch, 1880MHz									
3760.00	-10.2	V	3.0	45.8	1.0	-55.0	-13.0	-42.0	
5640.00	-7.8	V	3.0	45.7	1.0	-52.5	-13.0	-39.5	
7520.00	-5.1	V	3.0	44.5	1.0	-48.6	-13.0	-35.6	
3760.00	-10.1	H	3.0	45.8	1.0	-54.9	-13.0	-41.9	
5640.00	-7.7	H	3.0	45.7	1.0	-52.5	-13.0	-39.5	
7520.00	-5.1	H	3.0	44.5	1.0	-48.6	-13.0	-35.6	
High Ch, 1909.8MHz									
3819.60	-10.0	V	3.0	45.8	1.0	-54.8	-13.0	-41.8	
5729.40	-7.9	V	3.0	45.7	1.0	-52.6	-13.0	-39.6	
7639.20	-4.9	V	3.0	44.4	1.0	-48.3	-13.0	-35.3	
3819.60	-10.1	H	3.0	45.8	1.0	-54.9	-13.0	-41.9	
5729.40	-7.7	H	3.0	45.7	1.0	-52.4	-13.0	-39.4	
7639.20	-5.0	H	3.0	44.4	1.0	-48.4	-13.0	-35.4	

UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 5

Band 5 REL99

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/27/2021
Test Engineer: 22943
Configuration: EUT / AC Adapter, Z-Position
Location: Chamber 1
Mode: Rel99 Band 5 Harmonics
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.4MHz									
1652.80	-14.4	V	3.0	45.6	1.0	-59.0	-13.0	-46.0	
2479.20	-11.0	V	3.0	45.5	1.0	-55.4	-13.0	-42.4	
3305.60	-9.0	V	3.0	45.7	1.0	-53.7	-13.0	-40.7	
1652.80	-15.5	H	3.0	45.6	1.0	-60.1	-13.0	-47.1	
2479.20	-11.8	H	3.0	45.5	1.0	-56.2	-13.0	-43.2	
3305.60	-8.9	H	3.0	45.7	1.0	-53.6	-13.0	-40.6	
Mid Ch, 836.6MHz									
1673.20	-14.3	V	3.0	45.6	1.0	-58.9	-13.0	-45.9	
2509.80	-10.9	V	3.0	45.5	1.0	-55.4	-13.0	-42.4	
3346.40	-8.5	V	3.0	45.7	1.0	-53.2	-13.0	-40.2	
1673.20	-15.5	H	3.0	45.6	1.0	-60.1	-13.0	-47.1	
2509.80	-11.5	H	3.0	45.5	1.0	-56.0	-13.0	-43.0	
3346.40	-8.6	H	3.0	45.7	1.0	-53.3	-13.0	-40.3	
High Ch, 846.6MHz									
1693.20	-14.2	V	3.0	45.6	1.0	-58.8	-13.0	-45.8	
2539.80	-11.0	V	3.0	45.5	1.0	-55.4	-13.0	-42.4	
3386.40	-8.1	V	3.0	45.7	1.0	-52.8	-13.0	-39.8	
1693.20	-15.1	H	3.0	45.6	1.0	-59.7	-13.0	-46.7	
2539.80	-11.3	H	3.0	45.5	1.0	-55.7	-13.0	-42.7	
3386.40	-8.3	H	3.0	45.7	1.0	-53.0	-13.0	-40.0	

Band 5 HSDPA

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/27/2021
Test Engineer: 22943
Configuration: EUT / AC Adapter, Z-Position
Location: Chamber 1
Mode: HSDPA Band 5 Harmonics
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 826.4MHz									
1652.80	-14.3	V	3.0	45.6	1.0	-58.9	-13.0	-45.9	
2479.20	-11.3	V	3.0	45.5	1.0	-55.7	-13.0	-42.7	
3305.60	-8.8	V	3.0	45.7	1.0	-53.5	-13.0	-40.5	
1652.80	-15.6	H	3.0	45.6	1.0	-60.2	-13.0	-47.2	
2479.20	-11.8	H	3.0	45.5	1.0	-56.2	-13.0	-43.2	
3305.60	-9.0	H	3.0	45.7	1.0	-53.7	-13.0	-40.7	
Mid Ch, 836.6MHz									
1673.20	-14.4	V	3.0	45.6	1.0	-59.0	-13.0	-46.0	
2509.80	-11.1	V	3.0	45.5	1.0	-55.6	-13.0	-42.6	
3346.40	-8.6	V	3.0	45.7	1.0	-53.3	-13.0	-40.3	
1673.20	-15.4	H	3.0	45.6	1.0	-60.0	-13.0	-47.0	
2509.80	-11.6	H	3.0	45.5	1.0	-56.1	-13.0	-43.1	
3346.40	-8.7	H	3.0	45.7	1.0	-53.4	-13.0	-40.4	
High Ch, 846.6MHz									
1693.20	-14.2	V	3.0	45.6	1.0	-58.8	-13.0	-45.8	
2539.80	-11.2	V	3.0	45.5	1.0	-55.7	-13.0	-42.7	
3386.40	-8.4	V	3.0	45.7	1.0	-53.1	-13.0	-40.1	
1693.20	-15.3	H	3.0	45.6	1.0	-59.8	-13.0	-46.8	
2539.80	-11.4	H	3.0	45.5	1.0	-55.9	-13.0	-42.9	
3386.40	-8.3	H	3.0	45.7	1.0	-53.0	-13.0	-40.0	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 4

Band 4 REL99

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 22943
Configuration: EUT / AC Adapter, Y-Position
Location: Chamber 1
Mode: Rel99 Band 4 Harmonics
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1712.4MHz									
3424.80	-7.9	V	3.0	45.7	1.0	-52.7	-13.0	-39.7	
5137.20	-8.8	V	3.0	45.8	1.0	-53.6	-13.0	-40.6	
6849.60	-5.6	V	3.0	44.9	1.0	-49.5	-13.0	-36.5	
3424.80	-8.0	H	3.0	45.7	1.0	-52.7	-13.0	-39.7	
5137.20	-8.7	H	3.0	45.8	1.0	-53.5	-13.0	-40.5	
6849.60	-5.5	H	3.0	44.9	1.0	-49.4	-13.0	-36.4	
Mid Ch, 1732.6MHz									
3465.20	-7.6	V	3.0	45.7	1.0	-52.3	-13.0	-39.3	
5197.80	-8.3	V	3.0	45.8	1.0	-53.1	-13.0	-40.1	
6930.40	-5.2	V	3.0	44.8	1.0	-49.0	-13.0	-36.0	
3465.20	-7.5	H	3.0	45.7	1.0	-52.3	-13.0	-39.3	
5197.80	-8.5	H	3.0	45.8	1.0	-53.2	-13.0	-40.2	
6930.40	-5.5	H	3.0	44.8	1.0	-49.4	-13.0	-36.4	
High Ch, 1752.6MHz									
3505.20	-7.4	V	3.0	45.7	1.0	-52.2	-13.0	-39.2	
5257.80	-8.3	V	3.0	45.8	1.0	-53.1	-13.0	-40.1	
7010.40	-5.0	V	3.0	44.8	1.0	-48.8	-13.0	-35.8	
3505.20	-7.6	H	3.0	45.7	1.0	-52.3	-13.0	-39.3	
5257.80	-8.4	H	3.0	45.8	1.0	-53.1	-13.0	-40.1	
7010.40	-5.1	H	3.0	44.8	1.0	-48.9	-13.0	-35.9	

Band 4 HSDPA

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/28/2021
Test Engineer: 22943
Configuration: EUT / AC Adapter, Y-Position
Location: Chamber 1
Mode: HSDPA Band 4 Harmonics
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1712.4MHz									
3424.80	-7.8	V	3.0	45.7	1.0	-52.5	-13.0	-39.5	
5137.20	-8.7	V	3.0	45.8	1.0	-53.6	-13.0	-40.6	
6849.60	-5.5	V	3.0	44.9	1.0	-49.4	-13.0	-36.4	
3424.80	-7.9	H	3.0	45.7	1.0	-52.6	-13.0	-39.6	
5137.20	-8.9	H	3.0	45.8	1.0	-53.7	-13.0	-40.7	
6849.60	-5.6	H	3.0	44.9	1.0	-49.5	-13.0	-36.5	
Mid Ch, 1732.6MHz									
3465.20	-7.7	V	3.0	45.7	1.0	-52.4	-13.0	-39.4	
5197.80	-8.5	V	3.0	45.8	1.0	-53.3	-13.0	-40.3	
6930.40	-5.4	V	3.0	44.8	1.0	-49.3	-13.0	-36.3	
3465.20	-7.7	H	3.0	45.7	1.0	-52.5	-13.0	-39.5	
5197.80	-8.5	H	3.0	45.8	1.0	-53.3	-13.0	-40.3	
6930.40	-5.4	H	3.0	44.8	1.0	-49.2	-13.0	-36.2	
High Ch, 1752.6MHz									
3505.20	-7.5	V	3.0	45.7	1.0	-52.3	-13.0	-39.3	
5257.80	-8.4	V	3.0	45.8	1.0	-53.1	-13.0	-40.1	
7010.40	-5.1	V	3.0	44.8	1.0	-48.9	-13.0	-35.9	
3505.20	-7.7	H	3.0	45.7	1.0	-52.4	-13.0	-39.4	
5257.80	-8.4	H	3.0	45.8	1.0	-53.2	-13.0	-40.2	
7010.40	-5.2	H	3.0	44.8	1.0	-49.0	-13.0	-36.0	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

WCDMA Band 2

Band 2 REL99

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/27/2021
Test Engineer: 22943
Configuration: EUT / AC Adapter, X-Position
Location: Chamber 1
Mode: Rel99 Band 2 Harmonics
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3704.80	-10.1	V	3.0	45.8	1.0	-54.9	-13.0	-41.9	
5557.20	-7.9	V	3.0	45.7	1.0	-52.6	-13.0	-39.6	
7409.60	-5.3	V	3.0	44.6	1.0	-48.8	-13.0	-35.8	
3704.80	-9.7	H	3.0	45.8	1.0	-54.5	-13.0	-41.5	
5557.20	-7.8	H	3.0	45.7	1.0	-52.5	-13.0	-39.5	
7409.60	-5.2	H	3.0	44.6	1.0	-48.8	-13.0	-35.8	
Mid Ch, 1880MHz									
3760.00	-9.9	V	3.0	45.8	1.0	-54.8	-13.0	-41.8	
5640.00	-7.7	V	3.0	45.7	1.0	-52.4	-13.0	-39.4	
7520.00	-5.3	V	3.0	44.5	1.0	-48.8	-13.0	-35.8	
3760.00	-10.0	H	3.0	45.8	1.0	-54.8	-13.0	-41.8	
5640.00	-7.8	H	3.0	45.7	1.0	-52.5	-13.0	-39.5	
7520.00	-5.0	H	3.0	44.5	1.0	-48.5	-13.0	-35.5	
High Ch, 1907.6MHz									
3815.20	-9.7	V	3.0	45.8	1.0	-54.6	-13.0	-41.6	
5722.80	-7.7	V	3.0	45.7	1.0	-52.4	-13.0	-39.4	
7630.40	-5.0	V	3.0	44.4	1.0	-48.4	-13.0	-35.4	
3815.20	-10.2	H	3.0	45.8	1.0	-55.0	-13.0	-42.0	
5722.80	-7.8	H	3.0	45.7	1.0	-52.5	-13.0	-39.5	
7630.40	-4.9	H	3.0	44.4	1.0	-48.4	-13.0	-35.4	

Band 2 HSDPA

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 9/27/2021
Test Engineer: 22943
Configuration: EUT / AC Adapter, X-Position
Location: Chamber 1
Mode: HSDPA Band 2 Harmonics
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1852.4MHz									
3704.80	-10.2	V	3.0	45.8	1.0	-55.0	-13.0	-42.0	
5557.20	-7.9	V	3.0	45.7	1.0	-52.7	-13.0	-39.7	
7409.60	-5.1	V	3.0	44.6	1.0	-48.7	-13.0	-35.7	
3704.80	-10.5	H	3.0	45.8	1.0	-55.3	-13.0	-42.3	
5557.20	-8.1	H	3.0	45.7	1.0	-52.8	-13.0	-39.8	
7409.60	-5.2	H	3.0	44.6	1.0	-48.8	-13.0	-35.8	
Mid Ch, 1880MHz									
3760.00	-9.9	V	3.0	45.8	1.0	-54.8	-13.0	-41.8	
5640.00	-7.6	V	3.0	45.7	1.0	-52.4	-13.0	-39.4	
7520.00	-5.0	V	3.0	44.5	1.0	-48.5	-13.0	-35.5	
3760.00	-10.1	H	3.0	45.8	1.0	-54.9	-13.0	-41.9	
5640.00	-7.9	H	3.0	45.7	1.0	-52.6	-13.0	-39.6	
7520.00	-5.1	H	3.0	44.5	1.0	-48.6	-13.0	-35.6	
High Ch, 1907.6MHz									
3815.20	-10.0	V	3.0	45.8	1.0	-54.8	-13.0	-41.8	
5722.80	-7.8	V	3.0	45.7	1.0	-52.5	-13.0	-39.5	
7630.40	-4.8	V	3.0	44.4	1.0	-48.2	-13.0	-35.2	
3815.20	-10.1	H	3.0	45.8	1.0	-55.0	-13.0	-42.0	
5722.80	-7.8	H	3.0	45.7	1.0	-52.6	-13.0	-39.6	
7630.40	-4.9	H	3.0	44.4	1.0	-48.3	-13.0	-35.3	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 12

LTE Band 12

3MHz

QPSK

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company:	Samsung
Project #:	4790089626
Date:	10/12/2021
Test Engineer:	22943
Configuration:	EUT / AC Adapter, X-Position
Location:	Chamber 1
Mode:	LTE_QPSK Band 12 Harmonics, 3MHz Bandwidth
Test Votage:	AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 700.5MHz									
1401.00	-16.8	V	3.0	45.8	1.0	-61.6	-13.0	-48.6	
2101.50	-9.1	V	3.0	45.4	1.0	-53.4	-13.0	-40.4	
2802.00	-11.0	V	3.0	45.5	1.0	-55.5	-13.0	-42.5	
1401.00	-17.6	H	3.0	45.8	1.0	-62.4	-13.0	-49.4	
2101.50	-2.6	H	3.0	45.4	1.0	-46.9	-13.0	-33.9	
2802.00	-11.1	H	3.0	45.5	1.0	-55.6	-13.0	-42.6	
Mid Ch, 707.5MHz									
1415.00	-16.6	V	3.0	45.8	1.0	-61.4	-13.0	-48.4	
2122.50	-9.2	V	3.0	45.4	1.0	-53.6	-13.0	-40.6	
2830.00	-10.8	V	3.0	45.5	1.0	-55.4	-13.0	-42.4	
1415.00	-17.4	H	3.0	45.8	1.0	-62.2	-13.0	-49.2	
2122.50	-3.8	H	3.0	45.4	1.0	-48.2	-13.0	-35.2	
2830.00	-11.0	H	3.0	45.5	1.0	-55.5	-13.0	-42.5	
High Ch, 714.5MHz									
1429.00	-16.5	V	3.0	45.8	1.0	-61.3	-13.0	-48.3	
2143.50	-7.9	V	3.0	45.4	1.0	-52.3	-13.0	-39.3	
2858.00	-10.5	V	3.0	45.5	1.0	-55.0	-13.0	-42.0	
1429.00	-17.5	H	3.0	45.8	1.0	-62.3	-13.0	-49.3	
2143.50	-0.5	H	3.0	45.4	1.0	-44.8	-13.0	-31.8	
2858.00	-10.9	H	3.0	45.5	1.0	-55.5	-13.0	-42.5	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 13

LTE Band 13

5MHz

QPSK

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company:	Samsung
Project #:	4790089626
Date:	10/5/2021
Test Engineer:	19227
Configuration:	EUT / AC Adater, Z-Position
Location:	Chamber 1
Mode:	LTE_QPSK Band 13 Harmonics, 5MHz Bandwidth
Test Votage:	AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 779.5MHz									
1559.00	-15.8	V	3.0	45.7	1.0	-60.5	-40.0	-20.5	
2338.50	-12.2	V	3.0	45.4	1.0	-56.6	-13.0	-43.6	
3118.00	-10.3	V	3.0	45.6	1.0	-55.0	-13.0	-42.0	
1559.00	-16.9	H	3.0	45.7	1.0	-61.6	-40.0	-21.6	
2338.50	-12.8	H	3.0	45.4	1.0	-57.2	-13.0	-44.2	
3118.00	-10.2	H	3.0	45.6	1.0	-54.8	-13.0	-41.8	
Mid Ch, 782MHz									
1564.00	-15.9	V	3.0	45.7	1.0	-60.6	-40.0	-20.6	
2346.00	-11.7	V	3.0	45.4	1.0	-56.1	-13.0	-43.1	
3128.00	-10.2	V	3.0	45.6	1.0	-54.8	-13.0	-41.8	
1564.00	-16.8	H	3.0	45.7	1.0	-61.5	-40.0	-21.5	
2346.00	-12.1	H	3.0	45.4	1.0	-56.6	-13.0	-43.6	
3128.00	-10.2	H	3.0	45.6	1.0	-54.8	-13.0	-41.8	
High Ch, 784.5MHz									
1569.00	-15.7	V	3.0	45.7	1.0	-60.4	-40.0	-20.4	
2353.50	-12.2	V	3.0	45.4	1.0	-56.6	-13.0	-43.6	
3138.00	-10.2	V	3.0	45.6	1.0	-54.9	-13.0	-41.9	
1569.00	-16.3	H	3.0	45.7	1.0	-60.9	-40.0	-20.9	
2353.50	-12.9	H	3.0	45.4	1.0	-57.3	-13.0	-44.3	
3138.00	-10.2	H	3.0	45.6	1.0	-54.8	-13.0	-41.8	

Note : No narrowband emissions so only applied the -70dBW/MHz (-40dBm/MHz) wideband emission limit for the 1559-1610 MHz band

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 25

LTE Band 25

3MHz

QPSK

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company:	Samsung
Project #:	4790089626
Date:	10/12/2021
Test Engineer:	20882
Configuration:	EUT/ AC Adapter, X-Position
Location:	Chamber 1
Mode:	LTE_QPSK Band 25 Harmonics, 3MHz Bandwidth
Test Votage:	AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1851.5MHz									
3703.00	-10.8	V	3.0	45.8	1.0	-55.6	-13.0	-42.6	
5554.50	-8.6	V	3.0	45.7	1.0	-53.4	-13.0	-40.4	
7406.00	-5.6	V	3.0	44.6	1.0	-49.2	-13.0	-36.2	
3703.00	-11.2	H	3.0	45.8	1.0	-56.0	-13.0	-43.0	
5554.50	-8.5	H	3.0	45.7	1.0	-53.2	-13.0	-40.2	
7406.00	-6.1	H	3.0	44.6	1.0	-49.6	-13.0	-36.6	
Mid Ch, 1882.5MHz									
3765.00	-10.9	V	3.0	45.8	1.0	-55.7	-13.0	-42.7	
5647.50	-8.0	V	3.0	45.7	1.0	-52.7	-13.0	-39.7	
7530.00	-5.4	V	3.0	44.5	1.0	-48.9	-13.0	-35.9	
3765.00	-10.8	H	3.0	45.8	1.0	-55.6	-13.0	-42.6	
5647.50	-8.5	H	3.0	45.7	1.0	-53.2	-13.0	-40.2	
7530.00	-6.0	H	3.0	44.5	1.0	-49.5	-13.0	-36.5	
High Ch, 1913.5MHz									
3827.00	-10.7	V	3.0	45.9	1.0	-55.5	-13.0	-42.5	
5740.50	-8.2	V	3.0	45.7	1.0	-53.0	-13.0	-40.0	
7654.00	-5.5	V	3.0	44.4	1.0	-49.0	-13.0	-36.0	
3827.00	-10.7	H	3.0	45.9	1.0	-55.6	-13.0	-42.6	
5740.50	-8.2	H	3.0	45.7	1.0	-52.9	-13.0	-39.9	
7654.00	-5.4	H	3.0	44.4	1.0	-48.9	-13.0	-35.9	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26 (Part 90& Straddle)

LTE Band 26

1.4MHz

QPSK

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company:	Samsung
Project #:	4790089626
Date:	10/12/2021
Test Engineer:	20882
Configuration:	EUT / AC Adapter, X-Position
Location:	Chamber 1
Mode:	LTE_QPSK Band 26 Harmonics, 1.4MHz Bandwidth
Test Votage:	AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 814.7MHz									
1629.40	-15.4	V	3.0	45.6	1.0	-60.1	-13.0	-47.1	
2444.10	-10.3	V	3.0	45.4	1.0	-54.8	-13.0	-41.8	
3258.80	-9.7	V	3.0	45.7	1.0	-54.3	-13.0	-41.3	
1629.40	-16.1	H	3.0	45.6	1.0	-60.7	-13.0	-47.7	
2444.10	-7.5	H	3.0	45.4	1.0	-51.9	-13.0	-38.9	
3258.80	-9.4	H	3.0	45.7	1.0	-54.1	-13.0	-41.1	
Mid Ch, 823MHz									
1646.00	-14.1	V	3.0	45.6	1.0	-58.7	-13.0	-45.7	
2469.00	-9.0	V	3.0	45.4	1.0	-53.5	-13.0	-40.5	
3292.00	-9.4	V	3.0	45.7	1.0	-54.0	-13.0	-41.0	
1646.00	-11.9	H	3.0	45.6	1.0	-56.5	-13.0	-43.5	
2469.00	-7.5	H	3.0	45.4	1.0	-52.0	-13.0	-39.0	
3292.00	-9.3	H	3.0	45.7	1.0	-54.0	-13.0	-41.0	
High Ch, 824MHz									
1648.00	-14.3	V	3.0	45.6	1.0	-58.9	-13.0	-45.9	
2472.00	-9.4	V	3.0	45.4	1.0	-53.8	-13.0	-40.8	
3296.00	-9.7	V	3.0	45.7	1.0	-54.3	-13.0	-41.3	
1648.00	-14.7	H	3.0	45.6	1.0	-59.3	-13.0	-46.3	
2472.00	-7.0	H	3.0	45.4	1.0	-51.5	-13.0	-38.5	
3296.00	-9.6	H	3.0	45.7	1.0	-54.2	-13.0	-41.2	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 26 (Part 22)

LTE Band 26

1.4MHz

QPSK

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company:	Samsung
Project #:	4790089626
Date:	10/12/2021
Test Engineer:	20882
Configuration:	EUT/ AC Adapter, X-Position
Location:	Chamber 1
Mode:	LTE_QPSK Band 26 Harmonics, 1.4MHz Bandwidth
Test Votage:	AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 824.7MHz									
1649.40	-14.3	V	3.0	45.6	1.0	-58.9	-13.0	-45.9	
2474.10	-9.5	V	3.0	45.4	1.0	-54.0	-13.0	-41.0	
3298.80	-9.3	V	3.0	45.7	1.0	-54.0	-13.0	-41.0	
1649.40	-14.1	H	3.0	45.6	1.0	-58.7	-13.0	-45.7	
2474.10	-6.8	H	3.0	45.4	1.0	-51.2	-13.0	-38.2	
3298.80	-9.6	H	3.0	45.7	1.0	-54.3	-13.0	-41.3	
Mid Ch, 831.5MHz									
1663.00	-13.9	V	3.0	45.6	1.0	-58.5	-13.0	-45.5	
2494.50	-8.6	V	3.0	45.5	1.0	-53.0	-13.0	-40.0	
3326.00	-9.3	V	3.0	45.7	1.0	-53.9	-13.0	-40.9	
1663.00	-13.2	H	3.0	45.6	1.0	-57.8	-13.0	-44.8	
2494.50	-5.9	H	3.0	45.5	1.0	-50.3	-13.0	-37.3	
3326.00	-9.4	H	3.0	45.7	1.0	-54.1	-13.0	-41.1	
High Ch, 848.3MHz									
1696.60	-13.8	V	3.0	45.6	1.0	-58.4	-13.0	-45.4	
2544.90	-8.6	V	3.0	45.5	1.0	-53.0	-13.0	-40.0	
3393.20	-8.9	V	3.0	45.7	1.0	-53.6	-13.0	-40.6	
1696.60	-12.9	H	3.0	45.6	1.0	-57.5	-13.0	-44.5	
2544.90	-4.9	H	3.0	45.5	1.0	-49.4	-13.0	-36.4	
3393.20	-9.1	H	3.0	45.7	1.0	-53.8	-13.0	-40.8	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 41 (PC2)

LTE Band 41 (PC2)

5MHz

QPSK

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/6/2021
Test Engineer: 19227
Configuration: EUT/ AC Adapter, Z-Position
Location: Chamber 1
Mode: LTE_QPSK Band 41 Harmonics, 5MHz Bandwidth
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 2498.5MHz									
4997.00	-6.1	V	3.0	45.8	1.0	-51.0	-25.0	-26.0	
7495.50	-1.3	V	3.0	44.5	1.0	-44.9	-25.0	-19.9	
9994.00	-8.2	V	3.0	42.6	1.0	-49.8	-25.0	-24.8	
12492.50	2.1	V	3.0	43.6	1.0	-40.6	-25.0	-15.6	
14991.00	-0.2	V	3.0	45.7	1.0	-44.9	-25.0	-19.9	
4997.00	1.2	H	3.0	45.8	1.0	-43.6	-25.0	-18.6	
7495.50	3.4	H	3.0	44.5	1.0	-40.1	-25.0	-15.1	
9994.00	-5.5	H	3.0	42.6	1.0	-47.1	-25.0	-22.1	
12492.50	2.3	H	3.0	43.6	1.0	-40.4	-25.0	-15.4	
14991.00	2.2	H	3.0	45.7	1.0	-42.5	-25.0	-17.5	
Mid Ch, 2593MHz									
5186.00	2.6	V	3.0	45.8	1.0	-42.2	-25.0	-17.2	
7779.00	4.4	V	3.0	44.4	1.0	-38.9	-25.0	-13.9	
10372.00	-5.9	V	3.0	42.7	1.0	-47.6	-25.0	-22.6	
12965.00	-0.6	V	3.0	44.0	1.0	-43.6	-25.0	-18.6	
15558.00	0.7	V	3.0	45.1	1.0	-43.3	-25.0	-18.3	
5186.00	-6.6	H	3.0	45.8	1.0	-51.4	-25.0	-26.4	
7779.00	6.5	H	3.0	44.4	1.0	-36.9	-25.0	-11.9	
10372.00	-4.7	H	3.0	42.7	1.0	-46.4	-25.0	-21.4	
12965.00	0.1	H	3.0	44.0	1.0	-42.9	-25.0	-17.9	
15558.00	-1.0	H	3.0	45.1	1.0	-45.1	-25.0	-20.1	
High Ch, 2687.5MHz									
5375.00	-0.8	V	3.0	45.8	1.0	-45.6	-25.0	-20.6	
8062.50	1.2	V	3.0	44.2	1.0	-42.0	-25.0	-17.0	
10750.00	0.9	V	3.0	42.8	1.0	-40.9	-25.0	-15.9	
13437.50	1.6	V	3.0	44.4	1.0	-41.8	-25.0	-16.8	
16125.00	2.0	V	3.0	44.4	1.0	-41.5	-25.0	-16.5	
5375.00	1.8	H	3.0	45.8	1.0	-43.0	-25.0	-18.0	
8062.50	9.0	H	3.0	44.2	1.0	-34.2	-25.0	-9.2	
10750.00	2.6	H	3.0	42.8	1.0	-39.2	-25.0	-14.2	
13437.50	1.2	H	3.0	44.4	1.0	-42.2	-25.0	-17.2	
16125.00	-2.1	H	3.0	44.4	1.0	-45.5	-25.0	-20.5	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

LTE Band 66

LTE Band 66

20MHz

QPSK

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/12/2021
Test Engineer: 20882
Configuration: EUT/ AC Adapter, X-Position
Location: Chamber 1
Mode: LTE_QPSK Band 66 Harmonics, 20MHz Bandwidth
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1720MHz									
3440.00	-3.1	V	3.0	45.7	1.0	-47.8	-13.0	-34.8	
5160.00	-2.2	V	3.0	45.8	1.0	-47.0	-13.0	-34.0	
6880.00	0.6	V	3.0	44.9	1.0	-43.3	-13.0	-30.3	
3440.00	-3.0	H	3.0	45.7	1.0	-47.8	-13.0	-34.8	
5160.00	-2.7	H	3.0	45.8	1.0	-47.5	-13.0	-34.5	
6880.00	0.6	H	3.0	44.9	1.0	-43.3	-13.0	-30.3	
Mid Ch, 1745MHz									
3490.00	-2.9	V	3.0	45.7	1.0	-47.6	-13.0	-34.6	
5235.00	-1.6	V	3.0	45.8	1.0	-46.4	-13.0	-33.4	
6980.00	1.7	V	3.0	44.8	1.0	-42.1	-13.0	-29.1	
3490.00	-2.9	H	3.0	45.7	1.0	-47.6	-13.0	-34.6	
5235.00	-1.2	H	3.0	45.8	1.0	-46.0	-13.0	-33.0	
6980.00	2.0	H	3.0	44.8	1.0	-41.8	-13.0	-28.8	
High Ch, 1770MHz									
3540.00	-2.7	V	3.0	45.8	1.0	-47.5	-13.0	-34.5	
5310.00	-1.5	V	3.0	45.8	1.0	-46.3	-13.0	-33.3	
7080.00	1.9	V	3.0	44.7	1.0	-41.8	-13.0	-28.8	
3540.00	-2.3	H	3.0	45.8	1.0	-47.1	-13.0	-34.1	
5310.00	-1.5	H	3.0	45.8	1.0	-46.3	-13.0	-33.3	
7080.00	1.3	H	3.0	44.7	1.0	-42.5	-13.0	-29.5	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR Band 5

NR Band 5

10MHz

QPSK

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company:	Samsung
Project #:	4790089626
Date:	10/18/2021
Test Engineer:	20882
Configuration:	EUT / AC Adapter, Y-Position
Location:	Chamber 1
Mode:	LTE_QPSK NR n5 Harmonics, 10MHz Bandwidth
Test Votage:	AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 829MHz									
1658.00	-13.6	V	3.0	45.6	1.0	-58.2	-13.0	-45.2	
2487.00	-8.7	V	3.0	45.5	1.0	-53.1	-13.0	-40.1	
3316.00	-9.4	V	3.0	45.7	1.0	-54.1	-13.0	-41.1	
1658.00	-13.6	H	3.0	45.6	1.0	-58.3	-13.0	-45.3	
2487.00	-8.3	H	3.0	45.5	1.0	-52.7	-13.0	-39.7	
3316.00	-9.6	H	3.0	45.7	1.0	-54.3	-13.0	-41.3	
Mid Ch, 836.5MHz									
1673.00	-14.6	V	3.0	45.6	1.0	-59.2	-13.0	-46.2	
2509.50	-5.8	V	3.0	45.5	1.0	-50.2	-13.0	-37.2	
3346.00	-9.3	V	3.0	45.7	1.0	-53.9	-13.0	-40.9	
1673.00	-13.8	H	3.0	45.6	1.0	-58.4	-13.0	-45.4	
2509.50	-7.1	H	3.0	45.5	1.0	-51.6	-13.0	-38.6	
3346.00	-9.2	H	3.0	45.7	1.0	-53.9	-13.0	-40.9	
High Ch, 844MHz									
1688.00	-14.1	V	3.0	45.6	1.0	-58.7	-13.0	-45.7	
2532.00	-8.9	V	3.0	45.5	1.0	-53.3	-13.0	-40.3	
3376.00	-9.0	V	3.0	45.7	1.0	-53.7	-13.0	-40.7	
1688.00	-14.0	H	3.0	45.6	1.0	-58.6	-13.0	-45.6	
2532.00	-8.4	H	3.0	45.5	1.0	-52.9	-13.0	-39.9	
3376.00	-9.0	H	3.0	45.7	1.0	-53.7	-13.0	-40.7	

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.

NR Band 66

NR Band 66

10MHz

QPSK

UL Verification Services, Inc.
Above 1GHz High Frequency Substitution Measurement

Company: Samsung
Project #: 4790089626
Date: 10/19/2021
Test Engineer: 20882
Configuration: EUT / AC Adapter, X-Position
Location: Chamber 1
Mode: LTE_QPSK NR n66 Harmonics, 10MHz Bandwidth
Test Votage: AC 120 V, 60 Hz

f MHz	SG reading (dBm)	Ant. Pol. (H/V)	Distance (m)	Preamp (dB)	Filter (dB)	EIRP (dBm)	Limit (dBm)	Delta (dB)	Notes
Low Ch, 1715MHz									
3430.00	-8.4	V	3.0	45.7	1.0	-53.1	-13.0	-40.1	
5145.00	-9.2	V	3.0	45.8	1.0	-54.0	-13.0	-41.0	
6860.00	-5.9	V	3.0	44.9	1.0	-49.8	-13.0	-36.8	
3430.00	-8.5	H	3.0	45.7	1.0	-53.2	-13.0	-40.2	
5145.00	-9.1	H	3.0	45.8	1.0	-53.9	-13.0	-40.9	
6860.00	-6.2	H	3.0	44.9	1.0	-50.1	-13.0	-37.1	
Mid Ch, 1745MHz									
3490.00	-7.7	V	3.0	45.7	1.0	-52.4	-13.0	-39.4	
5235.00	-8.6	V	3.0	45.8	1.0	-53.4	-13.0	-40.4	
6980.00	-5.7	V	3.0	44.8	1.0	-49.5	-13.0	-36.5	
3490.00	-8.2	H	3.0	45.7	1.0	-52.9	-13.0	-39.9	
5235.00	-8.8	H	3.0	45.8	1.0	-53.6	-13.0	-40.6	
6980.00	-5.8	H	3.0	44.8	1.0	-49.6	-13.0	-36.6	
High Ch, 1775MHz									
3550.00	-7.6	V	3.0	45.8	1.0	-52.3	-13.0	-39.3	
5325.00	-8.6	V	3.0	45.8	1.0	-53.3	-13.0	-40.3	
10650.00	-0.8	V	3.0	42.8	1.0	-42.6	-13.0	-29.6	
3550.00	-7.6	H	3.0	45.8	1.0	-52.4	-13.0	-39.4	
5325.00	-8.5	H	3.0	45.8	1.0	-53.3	-13.0	-40.3	
7100.00	-5.8	H	3.0	44.7	1.0	-49.5	-13.0	-36.5	

END OF REPORT

UL Korea, Ltd. Suwon Laboratory FORM ID: FCC_22/24/27/90(04)
218 Maeyeong-ro, Yeongtong-gu, Suwon-si, Gyeonggi-do, 16675, Korea TEL: (031) 337-9902 FAX: (031) 213-5433
UL Korea, Ltd. Confidential
This report shall not be reproduced except in full, without the written approval of UL Korea, Ltd.