

# TEST REPORT

Reference No. .... : WTX21D04040833W002  
FCC ID ..... : AUSCR8005F  
Applicant..... : Modern Marketing Concepts, Inc.  
Address..... : 1220 E Oak, St. Louisville, KY 40204 United States  
Manufacturer ..... : Timsen Development Limited  
Address..... : 5F, 447# Tianhebei Road, Guangzhou, China  
Product..... : Cruiser Plus  
Model(s) ..... : CR8005F-BK  
Standards..... : FCC Part 2.1091  
Date of Receipt sample .... : 2021-04-28  
Date of Test ..... : 2021-04-28 to 2021-05-12  
Date of Issue..... : 2021-05-13  
Test Result..... : Pass

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:  
**Waltek Testing Group Co., Ltd.**

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China  
Tel: +86-769-2267 6998  
Fax: +86-769-2267 6828

Compiled by:

Approved by:

*Estel Qian*

Estel Qian / Project Engineer



*Daniel Liu*

Daniel Liu / Designated Reviewer

## 2. Contents

|                                        | <b>Page</b> |
|----------------------------------------|-------------|
| <b>1 COVER PAGE.....</b>               | <b>1</b>    |
| <b>2. CONTENTS .....</b>               | <b>2</b>    |
| <b>3. REVISION HISTORY .....</b>       | <b>3</b>    |
| <b>4. GENERAL INFORMATION.....</b>     | <b>4</b>    |
| 4.1. GENERAL DESCRIPTION OF E.U.T..... | 4           |
| 4.2. DETAILS OF E.U.T.....             | 4           |
| <b>5. TEST SUMMARY .....</b>           | <b>5</b>    |
| <b>6. RF EXPOSURE.....</b>             | <b>6</b>    |
| 6.1. REQUIREMENTS.....                 | 6           |
| 6.2. THE PROCEDURES / LIMIT .....      | 6           |
| 6.3. MPE CALCULATION METHOD .....      | 7           |
| 6.4. RESULT: COMPLIANCE .....          | 7           |

### 3. Revision History

| Test report No.        | Date of Receipt sample | Date of Test                   | Date of Issue | Purpose  | Comment | Approved |
|------------------------|------------------------|--------------------------------|---------------|----------|---------|----------|
| WTX21D04040833<br>W002 | 2021-04-28             | 2021-04-28<br>to<br>2021-05-12 | 2021-05-13    | Original | -       | Valid    |

## 4. General Information

### 4.1. General Description of E.U.T.

|                       |                                                                                                    |
|-----------------------|----------------------------------------------------------------------------------------------------|
| Product:              | Cruiser Plus                                                                                       |
| Model(s):             | CR8005F-BK                                                                                         |
| Additional model(s):  | CR8005X-XXXX ("X-XXXX" can be replaced by letter from "A" to "Z", number from "0" to "9" or blank) |
| Operation Frequency:  | 2402-2480MHz, 79 Channels in total                                                                 |
| Max. RF output power: | -1.47dBm                                                                                           |
| Antenna installation: | PCB Printed Antenna                                                                                |
| Antenna Gain:         | -0.58dBi                                                                                           |
| Type of Modulation:   | GFSK, $\pi/4$ DQPSK, 8DPSK                                                                         |
| Hardware Version:     | 1.0                                                                                                |
| Software Version:     | 1.0                                                                                                |

### 4.2. Details of E.U.T.

|          |                                                                                              |
|----------|----------------------------------------------------------------------------------------------|
| Ratings: | DC 5V 1A from adapter                                                                        |
| Adapter: | Model: ZWSP-050100US002<br>Input: 100-240V ~ 50/60Hz 0.5A<br>Output: 5V $\Rightarrow$ 1000mA |

## 5. Test Summary

| Test Items                                                        | Test Requirement | Result |
|-------------------------------------------------------------------|------------------|--------|
| Maximum Permissible Exposure<br>(Exposure of Humans to RF Fields) | FCC Part 2.1091  | PASS   |

## 6. RF Exposure

Test Requirement: FCC Part 2.1091

Evaluation Method: KDB 447498 D01 General RF Exposure Guidance v06

### 6.1. Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

### 6.2. The procedures / limit

#### (A) Limits for Occupational / Controlled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-3.0               | 614                               | 1.63                              | (100)*                                   | 6                                                                |
| 3.0-30                | 1842 / f                          | 4.89 / f                          | (900 / f)*                               | 6                                                                |
| 30-300                | 61.4                              | 0.163                             | 1.0                                      | 6                                                                |
| 300-1500              |                                   |                                   | F/300                                    | 6                                                                |
| 1500-100,000          |                                   |                                   | 5                                        | 6                                                                |

#### (B) Limits for General Population / Uncontrolled Exposure

| Frequency Range (MHz) | Electric Field Strength (E) (V/m) | Magnetic Field Strength (H) (A/m) | Power Density (S) (mW/ cm <sup>2</sup> ) | Averaging Time  E  <sup>2</sup> , H  <sup>2</sup> or S (minutes) |
|-----------------------|-----------------------------------|-----------------------------------|------------------------------------------|------------------------------------------------------------------|
| 0.3-1.34              | 614                               | 1.63                              | (100)*                                   | 30                                                               |
| 1.34-30               | 824/f                             | 2.19/f                            | (180/f)*                                 | 30                                                               |
| 30-300                | 27.5                              | 0.073                             | 0.2                                      | 30                                                               |
| 300-1500              |                                   |                                   | F/1500                                   | 30                                                               |
| 1500-100,000          |                                   |                                   | 1.0                                      | 30                                                               |

Note: f = frequency in MHz; \*Plane-wave equivalent power density

### 6.3. MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm<sup>2</sup>)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator,  
the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, R=20cm,  
as well as the gain of the used antenna, the RF power density can be obtained

| Antenna Gain (dBi) | Antenna Gain (numeric) | Max. conducted Output Power (dBm) | Max. conducted Output Power (mW) | Power Density (mW/cm <sup>2</sup> ) | Limit of Power Density (mW/cm <sup>2</sup> ) | Result     |
|--------------------|------------------------|-----------------------------------|----------------------------------|-------------------------------------|----------------------------------------------|------------|
| -0.58              | 0.875                  | -1.47                             | 0.71                             | 0.000124                            | 1                                            | Compliance |

### 6.4. Result: Compliance

No SAR measurement is required.

=====End of Report=====