

 MOTOROLA SOLUTIONS	 TESTING CERT # 2518.01
DECLARATION OF COMPLIANCE: MPE ASSESSMENT	
EME Test Laboratory 8000 West Sunrise Blvd Fort Lauderdale, FL. 33322	Date of Report: February 11, 2015 Report Revision: A
Responsible Engineer: William M. Elliott (Principal Staff EME Test Engineer) Report author: William M. Elliott (Principal Staff EME Test Engineer) Assessment Date(s): 09/14/2014 Manufacturer/Location: Motorola Solutions, Reynosa / Schaumburg Sector/Group/Div.: AESS – Astro Engineering Subscriber Solutions Date submitted: 05/30/2014 DUT Description: APX5000 / 6000 UHF R1 380 – 470 MHz, 3-5.7W, 6.25kHz/12.5kHz/25kHz. Capable of digital and analog FM transmission. Also capable of TDMA transmission. TX mode(s): FM and TDMA Max. Power output: 380 – 470 5.7 Watts Nominal Power: 380 – 470 5.0 Watts TX Frequency Bands: 380 – 470 MHz Signaling type: FM and TDMA (UHF) Model(s) Certified: H98QDD9PW5AN (MNUE1005B), H98QDH9PW7AN (MNUE1009B), H98QDD9PW5AN (NUE1052), H98QDH9PW7AN (NUE1056) Classification: Occupational/Controlled Environment FCC ID: AZ489FT4899 Part 90 (406.1 – 470 MHz) Results outside FCC bands are not applicable for FCC compliance demonstration. IC: 109U-89FT4899 IC bands; (406.1-430MHz & 450-470MHz) Results outside IC bands are not applicable for IC compliance demonstration.	
Based on the information and the testing results provided herein, the undersigned certifies that when used as stated in the operating instructions supplied, said product complies with the national and international reference standards and guidelines listed in section 4.0 of this report. This report shall not be reproduced without written approval from an officially designated representative of the Motorola Solutions Inc. EME Laboratory. I attest to the accuracy of the data and assume full responsibility for the completeness of these measurements. This reporting format is consistent with the suggested guidelines of the TIA TSB-159 April 2006 The results and statements contained in this report pertain only to the device(s) evaluated herein.	
 Deanna Zakharia EME Lab Senior Resource Manager and Laboratory Director Approval Date: 2/13/2015	Certification Date: 12/9/2014 Certification No.: 141007AD

Document Revision History

Date	Revision	Comments
09/15/2014	O	Initial release
02/11/2015	A	Correct reference to KDB 447498 to most recent version

Table of Contents

1.0	Introduction.....	3
2.0	FCC MPE Summary	3
3.0	Abbreviations / Definitions.....	3
4.0	Referenced Standards and Guidelines	3
5.0	Power Density Limits	4
6.0	Product and System Description.....	6
7.0	Assessment Method	6
8.0	MPE Assessment	7
9.0	Conclusion	8

1.0 Introduction

This report contains calculated Maximum Permissible Exposure (MPE) results for radio product models presently Certified as portable radio equipment under FCC ID: AZ489FT4899 and IC: 109U-89FT4899 when used in conjunction with vehicle adapter NNTN8527A and antennas listed in Section 8 of this report for vehicular mobile applications.

2.0 FCC MPE Summary

Table 1

Equipment Class	Frequency band (MHz)	Power Density (mW/cm ²)	% of FCC MPE Limit
TNB	380 - 406	0.145	57.3
TNB	406.1 - 470	0.145	53.7
Simultaneous Results		NA	NA

Results are based on highest percentage of limit.

3.0 Abbreviations / Definitions

C4FM: Continuous Four Level FM
 CQPSK: Compatible Differential Offset Quadrature Phase Shift Keying
 DUT: Device Under Test
 EME: Electromagnetic Energy
 FHSS: Frequency Hopping Spread Spectrum
 FM: Frequency Modulation
 MPE: Maximum Permissible Exposure
 TDMA: Time Division Multiple Access

4.0 Referenced Standards and Guidelines

This product is designed to comply with the following applicable national and international standards and guidelines.

- Federal Communications Commission, “Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields”, OET Bulletin 65, FCC, Washington, D.C.: 1997.
- American National Standards Institute (ANSI) / Institute of Electrical and Electronics Engineers (IEEE) C95. 1-1999
- American National Standards Institute (ANSI) / Institute of Electrical and Electronics Engineers (IEEE) C95. 1-1992. Specific to FCC rules and regulations.
- Institute of Electrical and Electronics Engineers (IEEE) C95.3-2002
- International Commission on Non-Ionizing Radiation Protection (ICNIRP) 1998
- Ministry of Health (Canada) Safety Code 6 (2014), Limits of Human Exposure to Radio frequency Electromagnetic Fields in the Frequency Range from 3 kHz to 300 GHz
- Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), Industry Canada RSS-102 Issue 4, 2010
- FCC KDB – 447498 D01 General RF Exposure Guidance v05r02 (02/07/2014)
- FCC KDB – 865664 D02 RF Exposure Reporting v01r01 (05/28/2013)

5.0 Power Density Limits

Table 2 – Occupational / Controlled Exposure Limits

Frequency Range (MHz)	FCC OET Bulletin 65 mW/cm ²	ICNIRP W/m ²	IEEE C95.1 1992/1999 mW/cm ²	IEEE C95.1 2005 W/m ²	RSS 102 issue 4 – 2010 W/m ²	Health Canada Safety Code 6 (2014) W/m ²
10 - 20						10.0
20 – 48						$44.72 / f^{0.5}$
30 – 300	1.0				*10.0	
48 – 100						6.455
10 – 400		10.0				
100 – 300			1.0	10.0		
100 – 6,000						$0.6455 f^{0.5}$
300 – 1,500	$f/300$				$f/30$	
300 - 3,000			$f/300$	$f/30$		
400 – 2,000		$f/40$				
1,500 – 15,000					50.0	
1,500 – 100,000	5.0					
2,000 – 300,000		50.0				
3,000 – 300,000			10.0	100.0		
6,000 – 15,000						50.0
15000 – 150,000						50.0
150000 – 300,000						$3.33 \times 10^{-4} f$

*Power density limit is applicable at frequencies greater than 100MHz

Table 3 – General Population / Uncontrolled Exposure Limits

Frequency Range (MHz)	FCC OET Bulletin 65	ICNIRP	IEEE C95.1 1992/1999	IEEE C95.1 2005	RSS 102 issue 4 – 2010	Health Canada Safety Code 6 (2014)
	mW/cm ²	W/m ²	mW/cm ²	W/m ²	W/m ²	W/m ²
10 - 20						2.0
20 – 48						$8.944 / f^{0.5}$
30 – 300	0.2				*2.0	
48 – 300						1.291
10 – 400		2.0				
100 – 300			0.2			
100 – 400				2.0		
300 – 1,500	$f/1,500$				$f/150$	
300 – 6000						$0.02619 f^{0.6834}$
400 – 2,000		$f/200$		$f/200$		
300 – 15,000			$f/1,500$			
1,500 – 15,000					10.0	
1,500 – 100,000	1.0					
2,000 – 100,000				10.0		
2,000 – 300,000		10.0				
6,000 – 15,000						10.0
15,000 – 150,000						10.0
150,000 - 300,000						$6.67 \times 10^{-5} f$

*Power density limit is applicable at frequencies greater than 100MHz

6.0 Product and System Description

This device operates using digital and analog frequency modulation (FM) as well as TDMA signaling incorporating traditional simplex two-way radio transmission protocol.

Time Division Multiple Access (TDMA) is used to allocate portions of the RF signal by dividing time into two slots. Time allocation enables each unit to transmit its voice information without interference from other transmitting units. Transmission from a unit or base station is accommodated during two time-slot lengths of 30 milliseconds with frame length of 60 milliseconds. C4FM CQPSK modulation is used and includes 12.5kHz channel spacing. The TDMA technique requires sophisticated algorithms and a digital signal processor (DSP) to perform voice compressions/decompressions and RF modulation/demodulation. The maximum duty cycle for TDMA 1:2 is 50%.

The LMR bands in this device operate in a half duplex system. A half duplex system only allows the user to transmit or receive. This device cannot transmit and receive simultaneously. The user must stop transmitting in order to receive a signal or listen for a response, regardless of PTT button or use of voice activated audio accessories. This type of operation, along with the RF safety booklet, which instructs the user to transmit no more than 50% of the time, justifies the use of 50% duty factor for this device.

In the evaluated configuration of the radio models represented in this report, a vehicle adapter is utilized to connect the RF connector of the certified portable radio to external vehicular antennas to form a mobile radio solution.

Table 4 below summarizes the technologies, bands, maximum duty cycles and maximum output powers. Maximum output powers are defined as upper limit of the production line final test station.

Table 4

Radio Type	Band (MHz)	Transmission	Duty Cycle (%)	Max Power (W)
LMR	380 – 470	FM or TDMA	*50 / *25	5.7

Note - * includes 50% PTT operation

This device is capable of operating in the TX frequency range(s), duty cycle(s), maximum output power(s) and antenna gain(s) presented in Table 4 and Table 5 in section 8.0 MPE Assessment.

7.0 Assessment Method

MPE calculations were used to determine the RF exposure for this device. According to FCC's OET Bulletin 65 Edition 97-01 Section 2, calculations can be made to predict RF field strength and power density levels around typical RF sources. For example, in the case of a single radiating antenna, a prediction for power density in the far-field of the antenna can be made by use of the general Equations (1) or (2) below. These equations are generally accurate in the far-field of an antenna but will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction. Equation 2 was used to show compliance for this device.

Equation 1

$$S = \frac{PG}{4\pi R^2} = \frac{EIRP}{4\pi R^2}$$

Where: S = power density (mW/cm²)
P = power input to the antenna (mW)
G = power gain of the antenna in the direction of interest relative to an isotropic radiator (dBi)
R = distance to center of radiation of the antenna (cm)
EIRP = equivalent (or effective) isotropically radiated power

Or Equation 2

$$S = \frac{P_t G}{4\pi d^2 L} F$$

Equation (2) accounts for the maximum duty cycle of the signal, and the factor, F, to provide a worst-case prediction of power density per FCC OET Bulletin 65, Edition 97-01 1997.

Where: S = power density (mW/cm²)
P_t = maximum output power scaled by the maximum duty cycle of the signal
G = power gain of the antenna in the direction of interest relative to an isotropic radiator (dBi)
d = distance from antenna (cm)
L = cable loss (dB)
F = 1.0

The separation distance chosen to demonstrate compliance with the uncontrolled limits for general population (bystanders) was 90cm for all antennas being offered with the product.

8.0 MPE Assessment

Table 5
MPE Calculation Results

Antenna #	Tx Frequency (MHz)	User Category	MPE Spec Limit (mW/cm ²)			Duty Cycle (%)	Max Power (W)	Antenna Gain (dBi)	Cable Loss, L (dB)	Dist., d (cm)	Max Calc. MPE (mW/cm ²)	Highest Percentage of Lowest Limit
			FCC	ICNIRP	Proposed IC Limits							
HAE4003A	450.0125	Uncontrolled	0.30	0.23	0.17	50%	5.7	2.15	0.00	90	0.046	27.0
HAE4003A	460.0125	Uncontrolled	0.31	0.23	0.17	50%	5.7	2.15	0.00	90	0.046	26.6
HAE4003A	470	Uncontrolled	0.31	0.24	0.18	50%	5.7	2.15	0.00	90	0.046	26.2
HAE4011A	450.0125	Uncontrolled	0.30	0.23	0.17	50%	5.7	5.65	0.00	90	0.103	60.4
HAE4011A	460.0125	Uncontrolled	0.31	0.23	0.17	50%	5.7	5.65	0.00	90	0.103	59.4
HAE4011A	470	Uncontrolled	0.31	0.24	0.18	50%	5.7	5.65	0.00	90	0.103	58.6
HAE6010A	380	Uncontrolled	0.25	0.20	0.15	50%	5.7	5.65	0.00	90	0.103	67.7
HAE6010A	393.1	Uncontrolled	0.26	0.20	0.16	50%	5.7	5.65	0.00	90	0.103	66.2
HAE6010A	406.125	Uncontrolled	0.27	0.20	0.16	50%	5.7	5.65	0.00	90	0.103	64.8
HAE6010A	419.6	Uncontrolled	0.28	0.21	0.16	50%	5.7	5.65	0.00	90	0.103	63.2
HAE6010A	433	Uncontrolled	0.29	0.22	0.17	50%	5.7	5.65	0.00	90	0.103	62.0

Table 5 (Cont.)

Antenna #	Tx Frequency (MHz)	User Category	MPE Spec Limit (mW/cm ²)			Duty Cycle (%)	Max Power (W)	Antenna Gain (dBi)	Cable Loss, L (dB)	Dist., d (cm)	Max Calc. MPE (mW/cm ²)	Highest Percentage of Lowest Limit
			FCC	ICNIRP	Proposed IC Limits							
HAE6011A	380	Uncontrolled	0.25	0.20	0.15	50%	5.7	7.15	0.00	90	0.145	95.7
HAE6011A	393.1	Uncontrolled	0.26	0.20	0.16	50%	5.7	7.15	0.00	90	0.145	93.5
HAE6011A	406.125	Uncontrolled	0.27	0.20	0.16	50%	5.7	7.15	0.00	90	0.145	91.5
HAE6011A	419.6	Uncontrolled	0.28	0.21	0.16	50%	5.7	7.15	0.00	90	0.145	89.3
HAE6011A	433	Uncontrolled	0.29	0.22	0.17	50%	5.7	7.15	0.00	90	0.145	87.5
HAE6012A	380	Uncontrolled	0.25	0.20	0.15	50%	5.7	2.15	0.00	90	0.046	30.3
HAE6012A	393.1	Uncontrolled	0.26	0.20	0.16	50%	5.7	2.15	0.00	90	0.046	29.6
HAE6012A	406.125	Uncontrolled	0.27	0.20	0.16	50%	5.7	2.15	0.00	90	0.046	28.9
HAE6012A	419.6	Uncontrolled	0.28	0.21	0.16	50%	5.7	2.15	0.00	90	0.046	28.3
HAE6012A	433	Uncontrolled	0.29	0.22	0.17	50%	5.7	2.15	0.00	90	0.046	27.7
HAE6013A	380	Uncontrolled	0.25	0.20	0.15	50%	5.7	4.15	0.00	90	0.073	48.0
HAE6013A	393.1	Uncontrolled	0.26	0.20	0.16	50%	5.7	4.15	0.00	90	0.073	46.9
HAE6013A	406.125	Uncontrolled	0.27	0.20	0.16	50%	5.7	4.15	0.00	90	0.073	44.6
HAE6013A	422.1	Uncontrolled	0.28	0.21	0.16	50%	5.7	4.15	0.00	90	0.073	44.6
HAE6013A	438.1	Uncontrolled	0.29	0.22	0.17	50%	5.7	4.15	0.00	90	0.073	43.5
HAE6013A	453.9875	Uncontrolled	0.30	0.23	0.17	50%	5.7	4.15	0.00	90	0.073	42.5
HAE6013A	470	Uncontrolled	0.31	0.24	0.24	50%	5.7	4.15	0.00	90	0.073	30.3

9.0 Conclusion

The MPE results per the assessment in Table 5 are compliant to the FCC General Population/Uncontrolled RF exposure limits in OET Bulletin 65 for every antenna offered with this product.

The MPE results per the assessment in Table 5 are also compliant to the ICNIRP general public exposure limits, per ICNIRP (1998) Guidelines for limiting exposure in time-varying electric, magnetic, and electromagnetic fields (up to 300GHz) and IEEE C95.1-2005..

Finally, the MPE results per the assessment in Table 5 are compliant with the proposed uncontrolled RF exposure limits found in Health Canada Safety Code 6 (2014).

Table 6: Maximum MPE RF Exposure Summary

Designator	Frequency (MHz)	Bystander (mW/cm ²)
Overall	380 - 470	0.145
FCC	406.1-470	0.145
IC	406.1-430 & 450-470	0.145

*Results are based on highest percentage of limit.