

## **Certification Test Report**

**FCC ID: AZ489FT6009**  
**IC: 109U-89FT6009**

**FCC Rule Part: 15.209**  
**IC Radio Standards Specification: RSS-210**

**ACS Report Number: 13-2168.W06.2A**

**Manufacturer: Motorola Solutions SDNBHD**  
**Model: PMMN4095A**

**Test Begin Date: January 10, 2014**  
**Test End Date: February 14, 2014**

**Report Issue Date: March 18, 2014**



FOR THE SCOPE OF ACCREDITATION UNDER CERTIFICATE NUMBER AT-1533

This report must not be used by the client to claim product certification, approval, or endorsement by ACLASS, ANSI, or any agency of the Federal Government.

**Project Manager:**

A handwritten signature in blue ink, appearing to read "Thierry Jean-Charles".

**Thierry Jean-Charles**  
**EMC Engineer**  
**Advanced Compliance Solutions, Inc.**

**Reviewed by:**

A handwritten signature in blue ink, appearing to read "Kirby Munroe".

**Kirby Munroe**  
**Director, Wireless Certifications**  
**Advanced Compliance Solutions, Inc.**

This test report shall not be reproduced except in full. This report may be reproduced in part with prior written consent of ACS, Inc. The results contained in this report are representative of the sample(s) submitted for evaluation.

**This report contains 19 pages**

## **TABLE OF CONTENTS**

|          |                                                                             |           |
|----------|-----------------------------------------------------------------------------|-----------|
| <b>1</b> | <b>GENERAL .....</b>                                                        | <b>3</b>  |
| 1.1      | Purpose.....                                                                | 3         |
| 1.2      | Product Description .....                                                   | 3         |
| 1.3      | Test Methodology and Considerations.....                                    | 3         |
| <b>2</b> | <b>TEST FACILITIES .....</b>                                                | <b>4</b>  |
| 2.1      | Location.....                                                               | 4         |
| 2.2      | Laboratory Accreditations/Recognitions/Certifications.....                  | 4         |
| 2.3      | Radiated & Conducted Emissions Test Site Description.....                   | 5         |
| <b>3</b> | <b>APPLICABLE STANDARD REFERENCES.....</b>                                  | <b>6</b>  |
| <b>4</b> | <b>LIST OF TEST EQUIPMENT.....</b>                                          | <b>7</b>  |
| <b>5</b> | <b>SUPPORT EQUIPMENT .....</b>                                              | <b>8</b>  |
| <b>6</b> | <b>EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM .....</b>                       | <b>8</b>  |
| <b>7</b> | <b>SUMMARY OF TESTS.....</b>                                                | <b>10</b> |
| 7.1      | Antenna Requirement – FCC: Section 15.203.....                              | 10        |
| 7.2      | 20dB / 99% Bandwidth: FCC: Section 15.215 / IC RSS-Gen 4.6.1 .....          | 10        |
| 7.3      | Radiated Spurious Emissions – FCC: Section 15.209 / IC: RSS-210 2.5.....    | 12        |
| 7.4      | Power Line Conducted Emissions – FCC: Section 15.207 IC: RSS-Gen 7.2.4..... | 15        |
| <b>8</b> | <b>CONCLUSION .....</b>                                                     | <b>18</b> |

## 1 GENERAL

### 1.1 Purpose

The purpose of this report is to demonstrate compliance with Part 15 Subpart C of the FCC's Code of Federal Regulations and Industry Canada's Radio Standards Specification RSS-210.

### 1.2 Product Description

The Wireless Remote Speaker Microphone (WRSM), model PMMN4095A, is a Bluetooth audio device that can be paired with Bluetooth audio gateway for TX & RX audio and supports data communication. The EUT also includes a 125 kHz transmitter.

#### Technical Details

Frequency of Operation: 125 kHz

Number of Channels: 1

Modulation: On Off Keying (OOK)

Data Rate: 1.212 kbps

Antenna: Telecoil Antenna

Input Voltage: 3.7 VDC (Lithium Ion Battery)

#### Manufacturer Information:

Motorola Solutions Malaysia Sdn Bhd

Plot 2, Bayan Lepas,

Technoplex Industrial Park,

Mukim 12, SWD (CSC)

11900 Bayan Lepas, Penang Malaysia

Test Sample Serial Number(s): ACS# 2

Test Sample Condition: The test samples were provided in good condition with no physical damage.

### 1.3 Test Methodology and Considerations

The EUT was evaluated for radiated and power line conducted emissions when transmitting at 125 kHz. The radiated emissions evaluation was performed for the EUT set in three orthogonal orientations. The measurements below 30 MHz were performed at a distance of 1m due to the low level of the fundamental frequency. Emissions above 30 MHz were measured at a distance of 3m from the EUT.

## **2 TEST FACILITIES**

### **2.1 Location**

The radiated and conducted emissions test sites are located at the following address:

Advanced Compliance Solutions, Inc.  
3998 FAU Blvd, Suite 310  
Boca Raton, Florida 33431  
Phone: (561) 961-5585  
Fax: (561) 961-5587  
[www.acstestlab.com](http://www.acstestlab.com)

FCC Test Firm Registration #: 475089  
Industry Canada Lab Code: 4175C

### **2.2 Laboratory Accreditations/Recognitions/Certifications**

ACS is accredited to ISO/IEC 17025 by ANSI-ASQ National Accreditation Board under their ACLASS program and has been issued certificate number AT-1533 in recognition of this accreditation. Unless otherwise specified, all test methods described within this report are covered under the ISO/IEC 17025 scope of accreditation.

## 2.3 Radiated & Conducted Emissions Test Site Description

### 2.3.1 Semi-Anechoic Chamber Test Site

The EMC radiated test facility consists of an RF-shielded enclosure. The interior dimensions of the indoor semi-anechoic chamber are approximately 48 feet (14.6 m) long by 36 feet (10.8 m) wide by 24 feet (7.3 m) high and consist of rigid, 1/8 inch (0.32 cm) steel-clad, wood core modular panels with steel framing. In the shielded enclosure, the faces of the panels are galvanized and the chamber is self-supporting. 8-foot RF absorbing cones are installed on 4 walls and the ceiling. The steel-clad ground plane is covered with vinyl floor.

The turntable is driven by pneumatic motor, which is capable of supporting a 2000 lb. load. The turntable is flushed with the chamber floor which it is connected to, around its circumference, with a continuous metallic loaded spring. An EMCO Model 1050 Multi-device Controller controls the turntable position.

A pneumatic motor is used to control antenna polarizations and height relative to the ground. The height information is displayed on the control unit EMCO Model 1050.

The control room is an RF shielded enclosure attached to the semi-anechoic chamber with two bulkhead panels for connecting RF, and control cables. The dimension of the room is 7.3 m x 4.9 m x 3 m high and the entrance doors of both control and conducted rooms are 3 feet (0.91 m) by 7 feet (2.13 m).

A diagram of the Semi-Anechoic Chamber Test Site is shown in Figure 2.3.1-1 below:




Figure 2.3.1-1: Semi-Anechoic Chamber Test Site

### 2.3.2 Conducted Emissions Test Site Description

The dimensions of the shielded conducted room are  $7.3 \times 4.9 \times 3 \text{ m}^3$ . As per ANSI C63.4 2003 requirements, the data were taken using two LISNs; a Solar Model 8028-50  $50 \Omega/50 \mu\text{H}$  and an EMCO Model 3825, which are installed as shown in Photograph 3. For 220 V, 50 Hz, a Polarad LISN (S/N 879341/048) is used in conjunction with a 1 kVA, 50 Hz/220 V EDGAR variable frequency generator, Model 1001B, to filter conducted noise from the generator.

A diagram of the room is shown below in figure 2.3.2-1:




Figure 2.3.2-1: AC Mains Conducted EMI Site

## 3 APPLICABLE STANDARD REFERENCES

The following standards were used:

- ❖ ANSI C63.4-2003: Method of Measurements of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the 9KHz to 40GHz
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 2, Subpart J: Equipment Authorization Procedures, 2014
- ❖ US Code of Federal Regulations (CFR): Title 47, Part 15, Subpart C: Radio Frequency Devices, Intentional Radiators, 2014
- ❖ Industry Canada Radio Standards Specification: RSS-210 - Low-power License-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment, Issue 8 December 2010.
- ❖ Industry Canada Radio Standards Specification: RSS-GEN – General Requirements and Information for the Certification of Radiocommunication Equipment, Issue 3, Dec 2010.

#### 4 LIST OF TEST EQUIPMENT

The calibration interval of test equipment is annually or the manufacturer's recommendations. Where the calibration interval deviates from the annual cycle based on the instrument manufacturer's recommendations, it shall be stated below.

**Table 4-1: Test Equipment**

| AssetID | Manufacturer    | Model #                | Equipment Type     | Serial #   | Last Calibration Date | Calibration Due Date |
|---------|-----------------|------------------------|--------------------|------------|-----------------------|----------------------|
| 78      | EMCO            | 6502                   | Antennas           | 9104-2608  | 2/5/2013              | 2/5/2015             |
| 523     | Agilent         | E7405                  | Spectrum Analyzers | MY45103293 | 1/8/2013              | 1/8/2015             |
| 524     | Chase           | CBL6111                | Antennas           | 1138       | 1/7/2013              | 1/7/2015             |
| 2011    | Hewlett-Packard | HP 8447D               | Amplifiers         | 2443A03952 | 12/31/2013            | 12/31/2014           |
| 2022    | EMCO            | LISN3825/2R            | LISN               | 1095       | 9/9/2013              | 9/9/2015             |
| 2037    | ACS Boca        | Chamber EMI Cable Set  | Cable Set          | 2037       | 1/1/2014              | 1/1/2015             |
| 2045    | ACS Boca        | Conducted Cable Set    | Cable Set          | 2045       | 1/1/2014              | 1/1/2015             |
| 2095    | ETS Lindgren    | TILE4! - Version 4.2.A | Software           | 85242      | NCR                   | NCR                  |
| 3004    | Teseq           | CFL 9206A              | Attenuators        | 34720      | 10/21/2013            | 10/21/2015           |


**NCR=No Calibration Required**

**5 SUPPORT EQUIPMENT****Table 5-1: Support Equipment**

| Item # | Type Device          | Manufacturer | Model/Part #    | Serial #            |
|--------|----------------------|--------------|-----------------|---------------------|
| 1      | Charger              | Motorola     | PMNL6714A       | N/A                 |
| 2      | Charger Power Supply | Motorola     | MU15-M050275-A1 | 1100051039134010987 |
| 3      | Headset              | Motorola     | WADN4190B       | 1119                |

**Table 5-2: Cable Description**

| Cable # | Cable Type     | Length | Shield | Termination              |
|---------|----------------|--------|--------|--------------------------|
| A       | Headset cable  | 0.68 m | No     | EUT to headset           |
| B       | Power cable    | 1.5 m  | No     | EUT to power supply      |
| C       | Ext Power Cord | 1.82 m | No     | Power Supply to AC Mains |

**6 EQUIPMENT UNDER TEST SETUP BLOCK DIAGRAM****Figure 6-1: Radiated Emissions Setup**




Figure 6-2: Power Line Conducted Emissions Setup

## 7 SUMMARY OF TESTS

Along with the tabular data shown below, plots were taken of all signals deemed important enough to document.

### 7.1 Antenna Requirement – FCC: Section 15.203

The 125kHz Telecoil Antenna of the EUT is permanently attached, thus meeting the requirements of 15.203.

### 7.2 20dB / 99% Bandwidth: FCC: Section 15.215 / IC RSS-Gen 4.6.1

#### 7.2.1 Measurement Procedure

The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected.

The 20 dB bandwidth was measured with the Span of the Spectrum Analyzer configured between two to five times the 20 dB bandwidth. The RBW of the SA was set to 1% to 5% of the occupied 20 dB bandwidth. The reference level was set to the highest amplitude signal observed. The bandwidth was measured 20 dB down from the reference level.

The 99% occupied bandwidth was measured with the spectrum analyzer span set to fully display the emission, including the emissions skirts. The RBW was greater or equal to 1% of the span. The occupied 99% bandwidth was measured by using a delta marker at the lower and upper frequencies leading to 0.5% of the total power.

#### 7.2.2 Measurement Results

Results are shown below in Table 7.2.2-1 and Figures 7.2.2-1 through 7.2.2-2

**Table 7.2.2-1: 20dB / 99% Bandwidth**

| Frequency<br>[MHz] | 20dB Bandwidth<br>[kHz] | 99% Bandwidth<br>[kHz] |
|--------------------|-------------------------|------------------------|
| 0.125              | 6.10                    | 14.65                  |




Figure 7.2.2-1: 20dB BW




Figure 7.2.2-2: 99% OBW

### 7.3 Radiated Spurious Emissions – FCC: Section 15.209 / IC: RSS-210 2.5

#### 7.3.1 Measurement Procedure

Radiated emissions tests were made over the frequency range of 10 kHz to 1GHz. Section 15.33(a)(4) specifies, if the intentional radiator contains a digital device, regardless of whether this digital device controls the functions of the intentional radiator or the digital device is used for additional control or function purposes other than to enable the operation of the intentional radiator, the frequency range shall be investigated up to frequency specified in 15.33(b)(1) for unintentional radiators. The upper frequency range for the digital device is 1000MHz which greater than the 10<sup>th</sup> harmonic of the fundamental frequency. The upper frequency range measured was 1000MHz.

Measurements below 30MHz were performed in a semi-anechoic chamber with a 1 meter separation distance between the EUT and measurement antenna. The EUT was rotated 360 and the loop antenna rotated about the vertical axis to maximize each emission. The magnetic loop receiving antenna was positioned with its center 1 meter above the ground.

The spectrum analyzer's resolution and video bandwidths were set to 300 Hz and 1000 Hz respectively for frequencies below 150 kHz and 9 kHz and 30 kHz respectively for frequencies above 150 kHz and below 30 MHz. The fundamental levels were measured using a resolution bandwidth of 30 kHz which is greater than the measured emission bandwidth. For measurements in the frequency bands 9-90 kHz and 110-490 kHz, an average detector was used. When average measurements are specified, the peak emissions were also compared to a limit corresponding to 20 dB above the maximum permitted average limit according to Part 15.35. All other emissions were measured using a Quasi-peak detector. The final measurements were then corrected by antenna correction factors and cable loss for comparison to the limits.

Measurements above 30 MHz were performed in a semi-anechoic chamber with a 3 meter separation distance between the EUT and measurement antenna. The EUT was rotated through 360° and the receive antenna height was varied from 1m to 4m so that the maximum radiated emissions level would be detected. For frequencies below 1000 MHz, quasi-peak measurements were made using a resolution bandwidth (RBW) of 120 kHz and a video bandwidth (VBW) of 300 kHz.

#### 7.3.2 Distance Correction for Measurements Below 30 MHz – Part 15.31

Radiated measurements were performed at a distance closer than 300 meters and 30m as required, according to Part 15.209. Therefore a correction factor was applied to account for propagation loss at the specified distance. The propagation loss was determined by using the square of an inverse linear distance extrapolation factor (40dB/decade) according to 15.31. A sample calculation of the distance correction factor is shown below for limits expressed at a 300m measurement distance and a 30m measurement distance.

Distance correction factor (300m Specified Test Distance) =  $40 \cdot \log(\text{Test Distance}/300)$   
=  $40 \cdot \log(1/300)$   
= - 99.08 dB

Distance correction factor (30m Specified Test Distance) =  $40 \cdot \log(\text{Test Distance}/30)$   
=  $40 \cdot \log(1/30)$   
= - 59.08 dB

### 7.3.3 Measurement Results

Radiated spurious emissions found in the band of 10 kHz to 1GHz are reported in the Table 7.3.3-1 below.

**Table 7.3.3-1: Radiated Spurious Emissions Tabulated Data**

| Frequency<br>(MHz)    | Level<br>(dBuV) |         | Antenna<br>Polarity<br>(H/V) | Correction<br>Factors<br>(dB) | Corrected Level<br>(dBuV/m) |         | Limit<br>(dBuV/m) |         | Margin<br>(dB) |         |
|-----------------------|-----------------|---------|------------------------------|-------------------------------|-----------------------------|---------|-------------------|---------|----------------|---------|
|                       | pk              | QPk/avg |                              |                               | pk                          | QPk/avg | pk                | QPk/avg | pk             | QPk/avg |
| Fundamental Frequency |                 |         |                              |                               |                             |         |                   |         |                |         |
| 0.125                 | 57.85           | 45.90   | V                            | 10.95                         | 68.80                       | 56.85   | 144.8             | 124.8   | 76.0           | 68.0    |
| Spurious Emissions    |                 |         |                              |                               |                             |         |                   |         |                |         |
| 30.0146               | -----           | 23.50   | H                            | -7.39                         | -----                       | 16.11   | -----             | 40.0    | -----          | 23.9    |
| 993.661               | -----           | 21.83   | H                            | 3.39                          | -----                       | 25.23   | -----             | 54.0    | -----          | 28.8    |
| 32.5721               | -----           | 23.63   | V                            | -8.85                         | -----                       | 14.78   | -----             | 40.0    | -----          | 25.2    |
| 717.405               | -----           | 22.24   | V                            | -0.69                         | -----                       | 21.54   | -----             | 46.0    | -----          | 24.5    |
| 982.27                | -----           | 21.98   | V                            | 3.21                          | -----                       | 25.19   | -----             | 54.0    | -----          | 28.8    |

Notes:

- The fundamental frequency was measured with RBW = 30 kHz, which is greater than the measured emission bandwidth.
- The measurements below 30 MHz were performed at a distance of 1m from the EUT while the emissions above 1 GHz were measured at a distance of 3m.

**7.3.4 Sample Calculation:**

$$R_C = R_U + CF_T$$

Where:

|        |   |                                                                   |
|--------|---|-------------------------------------------------------------------|
| $CF_T$ | = | Total Correction Factor (AF+CA+AG)-DC (Average Measurements Only) |
| $R_U$  | = | Uncorrected Reading                                               |
| $R_C$  | = | Corrected Level                                                   |
| AF     | = | Antenna Factor                                                    |
| CA     | = | Cable Attenuation                                                 |
| AG     | = | Amplifier Gain                                                    |
| DC     | = | Duty Cycle Correction Factor                                      |

**Example Calculation : Average/Quasi-Peak Limit < 30MHz**

Measurement Distance 300m @ 125kHz

$$\text{Limit (dBuV/m)} = 20 * \text{Log}(2400/F(\text{kHz})) - \text{Distance Correction Factor (Section 7.3.2)}$$

$$\text{Limit (dBuV/m)} = 20 * \text{Log}(2400/125) + 99.08$$

$$\text{Limit (dBuV/m)} = 124.8$$

**Example Calculation : -Peak Limit < 30MHz**

Measurement Distance 300m @ 125kHz

$$\text{Limit (dBuV/m)} = \text{Average/Quasi-Peak Limit < 30MHz} + 20$$

$$\text{Limit (dBuV/m)} = 20 * \text{Log}(2400/F(\text{kHz})) - \text{Distance Correction Factor (Section 7.3.2)} + 20$$

$$\text{Limit (dBuV/m)} = 20 * \text{Log}(2400/125) + 99.08 + 20$$

$$\text{Limit (dBuV/m)} = 144.8$$

**Example Calculation: Peak**

$$\text{Corrected Level: } 57.85 + 10.95 = 68.8 \text{ dB}\mu\text{V/m}$$

$$\text{Margin: } 144.8 \text{ dB}\mu\text{V/m} - 68.8 \text{ dB}\mu\text{V/m} = 76.0 \text{ dB}$$

**Example Calculation: Average**

$$\text{Corrected Level: } 45.9 + 10.95 - 0 = 56.85 \text{ dB}\mu\text{V/m}$$

$$\text{Margin: } 124.8 \text{ dB}\mu\text{V/m} - 56.85 \text{ dB}\mu\text{V/m} = 68.0 \text{ dB}$$

**7.4 Power Line Conducted Emissions – FCC: Section 15.207 IC: RSS-Gen 7.2.4****7.4.1 Measurement Procedure**


ANSI C63.4 sections 6 and 7 were the guiding documents for this evaluation. Conducted emissions were performed from 150 kHz to 30 MHz with the spectrum analyzer's resolution bandwidth set to 9 kHz and the video bandwidth set to 30 kHz. The calculation for the conducted emissions is as follows:

**Corrected Reading = Analyzer Reading + LISN Loss + Cable Loss**

**Margin = Applicable Limit - Corrected Reading**

**7.4.2 Measurement Results**

Results of the test corresponding to the EUT configuration leading to the worse case emissions are shown below in Table 7.4.2-1 and Figure 7.4.2-1 to Figure 7.4.2-2.



**Figure 7.4.2-1: Conducted Emissions Results – Line 1**




Figure 7.4.2-2: Conducted Emissions Results – Line 2

Table 7.4.2-1: Conducted EMI Results

| <div><input checked="" type="checkbox"/> Line 1 <input checked="" type="checkbox"/> Line 2 <input type="checkbox"/> Line 3 <input type="checkbox"/> Line 4</div> <div><input type="checkbox"/> To Ground <input checked="" type="checkbox"/> Floating</div> <div><input type="checkbox"/> Telecom Port _____</div> <div><input checked="" type="checkbox"/> dBµV <input type="checkbox"/> dBµA</div> <div>Plot Number: <u>13-2168CE06</u></div> <div>Power Supply Description: <u>5 VDC</u></div> |                     |         |                              |                 |         |            |         |             |         |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|---------|------------------------------|-----------------|---------|------------|---------|-------------|---------|
| Frequency (MHz)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Uncorrected Reading |         | Total Correction Factor (dB) | Corrected Level |         | Limit      |         | Margin (dB) |         |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Quasi-Peak          | Average |                              | Quasi-Peak      | Average | Quasi-Peak | Average | Quasi-Peak  | Average |
| Line 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                     |         |                              |                 |         |            |         |             |         |
| 0.150513                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 30.403              | 21.866  | 10.10                        | 40.50           | 31.96   | 65.97      | 55.97   | 25.5        | 24.0    |
| 0.174749                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 25.848              | 18.492  | 10.09                        | 35.93           | 28.58   | 64.73      | 54.73   | 28.8        | 26.2    |
| 0.189699                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 20.854              | 13.067  | 10.09                        | 30.94           | 23.15   | 64.05      | 54.05   | 33.1        | 30.9    |
| 0.204625                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 25.258              | 15.86   | 10.10                        | 35.35           | 25.96   | 63.42      | 53.42   | 28.1        | 27.5    |
| 0.234475                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 19.977              | 14.086  | 10.10                        | 30.07           | 24.18   | 62.29      | 52.29   | 32.2        | 28.1    |
| 0.479999                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 15.002              | 10.875  | 10.08                        | 25.08           | 20.95   | 56.34      | 46.34   | 31.3        | 25.4    |
| 0.831475                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 12.317              | 7.872   | 10.09                        | 22.41           | 17.97   | 56.00      | 46.00   | 33.6        | 28.0    |
| 2.32397                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 11.305              | 6.801   | 10.18                        | 21.49           | 16.98   | 56.00      | 46.00   | 34.5        | 29.0    |
| 4.98                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 10.333              | 5.947   | 10.28                        | 20.61           | 16.23   | 56.00      | 46.00   | 35.4        | 29.8    |
| Line 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                     |         |                              |                 |         |            |         |             |         |
| 0.152825                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 30.082              | 22.577  | 10.08                        | 40.16           | 32.65   | 65.85      | 55.85   | 25.7        | 23.2    |
| 0.167313                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 22.539              | 11.587  | 10.08                        | 32.62           | 21.66   | 65.09      | 55.09   | 32.5        | 33.4    |
| 0.182237                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 25.011              | 18.123  | 10.07                        | 35.08           | 28.19   | 64.38      | 54.38   | 29.3        | 26.2    |
| 0.1997                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 22.58               | 12.31   | 10.07                        | 32.65           | 22.38   | 63.62      | 53.62   | 31.0        | 31.2    |
| 0.2571                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 18.75               | 10.63   | 10.07                        | 28.82           | 20.70   | 61.52      | 51.52   | 32.7        | 30.8    |
| 0.5484                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 15.49               | 10.02   | 10.06                        | 25.55           | 20.08   | 56.00      | 46.00   | 30.5        | 25.9    |
| 1.255                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 12.25               | 6.208   | 10.08                        | 22.33           | 16.29   | 56.00      | 46.00   | 33.7        | 29.7    |

\* Note: Results are reported for the EUT configuration leading to the worst case emissions.

## **8 CONCLUSION**

In the opinion of ACS, Inc. the PMMN4095A manufactured by Motorola Solutions SDNBHD meets the requirements of FCC Part 15 subpart C and Industry Canada's Radio Standards Specification RSS-210.

**END REPORT**