

Conducted Output Power (802.11g-CH 1) 48Mbps



Conducted Output Power (802.11g-CH 1) 54Mbps



Conducted Output Power (802.11g-CH 6) 6Mbps



Conducted Output Power (802.11g-CH 6) 9Mbps



Conducted Output Power (802.11g-CH 6) 12Mbps



Conducted Output Power (802.11g-CH 6) 18Mbps



Conducted Output Power (802.11g-CH 6) 24Mbps



Conducted Output Power (802.11g-CH 6) 36Mbps



Conducted Output Power (802.11g-CH 6) 48Mbps



Conducted Output Power (802.11g-CH 6) 54Mbps



Conducted Output Power (802.11g-CH 11) 6Mbps



Conducted Output Power (802.11g-CH 11) 9Mbps



Conducted Output Power (802.11g-CH 11) 12Mbps



Conducted Output Power (802.11g-CH 11) 18Mbps



Conducted Output Power (802.11g-CH 11) 24Mbps



Conducted Output Power (802.11g-CH 11) 36Mbps



Conducted Output Power (802.11g-CH 11) 48Mbps



Conducted Output Power (802.11g-CH 11) 54Mbps



Conducted Output Power (802.11n-CH 1) 6.5Mbps



Conducted Output Power (802.11n-CH 1) 13Mbps



Conducted Output Power (802.11n-CH 1) 19.5Mbps



Conducted Output Power (802.11n-CH 1) 26Mbps



Conducted Output Power (802.11n-CH 1) 39Mbps



Conducted Output Power (802.11n-CH 1) 52Mbps



Conducted Output Power (802.11n-CH 1) 58.5Mbps



Conducted Output Power (802.11n-CH 1) 65Mbps



Conducted Output Power (802.11n-CH 6) 6.5Mbps



Conducted Output Power (802.11n-CH 6) 13Mbps



Conducted Output Power (802.11n-CH 6) 19.5Mbps



Conducted Output Power (802.11n-CH 6) 26Mbps



Conducted Output Power (802.11n-CH 6) 39Mbps



Conducted Output Power (802.11n-CH 6) 52Mbps



Conducted Output Power (802.11n-CH 6) 58.5Mbps



Conducted Output Power (802.11n-CH 6) 65Mbps



Conducted Output Power (802.11n-CH 11) 6.5Mbps



Conducted Output Power (802.11n-CH 11) 13Mbps



Conducted Output Power (802.11n-CH 11) 19.5Mbps



Conducted Output Power (802.11n-CH 11) 26Mbps



Conducted Output Power (802.11n-CH 11) 39Mbps



Conducted Output Power (802.11n-CH 11) 52Mbps



Conducted Output Power (802.11n-CH 11) 58.5Mbps



Conducted Output Power (802.11n-CH 11) 65Mbps



(5745 MHz ~5825 MHz)

Conducted Output Power (802.11a-CH 149) 6 Mbps



Conducted Output Power (802.11a-CH 149) 9 Mbps



Conducted Output Power (802.11a-CH 149) 12 Mbps



Conducted Output Power (802.11a-CH 149) 18 Mbps



Conducted Output Power (802.11a-CH 149) 24 Mbps



Conducted Output Power (802.11a-CH 149) 36 Mbps



Conducted Output Power (802.11a-CH 149) 48 Mbps



Conducted Output Power (802.11a-CH 149) 54 Mbps



Conducted Output Power (802.11a-CH 157) 6 Mbps



Conducted Output Power (802.11a-CH 157) 9 Mbps



Conducted Output Power (802.11a-CH 157) 12 Mbps



Conducted Output Power (802.11a-CH 157) 18 Mbps



Conducted Output Power (802.11a-CH 157) 24 Mbps



Conducted Output Power (802.11a-CH 157) 36 Mbps



Conducted Output Power (802.11a-CH 157) 48 Mbps



Conducted Output Power (802.11a-CH 157) 54 Mbps



Conducted Output Power (802.11a-CH 165) 6 Mbps



Conducted Output Power (802.11a-CH 165) 9 Mbps



Conducted Output Power (802.11a-CH 165) 12 Mbps



Conducted Output Power (802.11a-CH 165) 18 Mbps



Conducted Output Power (802.11a-CH 165) 24 Mbps



Conducted Output Power (802.11a-CH 165) 36 Mbps



Conducted Output Power (802.11a-CH 165) 48 Mbps



Conducted Output Power (802.11a-CH 165) 54 Mbps



(5745 MHz ~5825 MHz)

Conducted Output Power (802.11n-CH 149) 6.5 Mbps



Conducted Output Power (802.11n-CH 149) 13 Mbps



Conducted Output Power (802.11n-CH 149) 19.5 Mbps



Conducted Output Power (802.11n-CH 149) 26 Mbps



Conducted Output Power (802.11n-CH 149) 39 Mbps



Conducted Output Power (802.11n-CH 149) 52 Mbps



Conducted Output Power (802.11n-CH 149) 58.5 Mbps



Conducted Output Power (802.11n-CH 149) 65 Mbps



Conducted Output Power (802.11n-CH 157) 6.5 Mbps



Conducted Output Power (802.11n-CH 157) 13 Mbps



Conducted Output Power (802.11n-CH 157) 19.5 Mbps



Conducted Output Power (802.11n-CH 157) 26 Mbps



Conducted Output Power (802.11n-CH 157) 39 Mbps



Conducted Output Power (802.11n-CH 157) 52 Mbps



Conducted Output Power (802.11n-CH 157) 58.5 Mbps



Conducted Output Power (802.11n-CH 157) 65 Mbps



Conducted Output Power (802.11n-CH 165) 6.5 Mbps



Conducted Output Power (802.11n-CH 165) 13 Mbps



Conducted Output Power (802.11n-CH 165) 19.5 Mbps



Conducted Output Power (802.11n-CH 165) 26 Mbps



Conducted Output Power (802.11n-CH 165) 39 Mbps



Conducted Output Power (802.11n-CH 165) 52 Mbps



Conducted Output Power (802.11n-CH 165) 58.5 Mbps



Conducted Output Power (802.11n-CH 165) 65 Mbps




8.3 POWER SPECTRAL DENSITY (802.11a/b/g/n)

Test Requirements and limit, §15.247(e)

The peak power spectral density is measured with a spectrum analyzer connected to the antenna terminal while the EUT is operating in transmission mode at the appropriate frequencies.

Minimum Standard – the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

▣ TEST CONFIGURATION



▣ TEST PROCEDURE

We tested according to KDB 558074(issued 10/04/2012).

The spectrum analyzer is set to :

1. Span = 5 – 30 % greater than the EBW
2. RBW $\geq$ 3 kHz
3. VBW $\geq$ 3 kHz * RBW
4. Sweep = Auto couple
5. Detector Mode = Peak
6. Trace Mode = Max hold
7. Search peak

▣ Sample Calculation

$$\begin{aligned}
 \text{PSD} &= \text{Reading Value} + \text{ATT loss} + \text{Cable loss}(1 \text{ ea}) \\
 &= -5 \text{ dBm} + 10 \text{ dB} + 0.8 \text{ dB} = 5.8 \text{ dBm}
 \end{aligned}$$

Note :

1. Spectrum reading values are not plot data. The PSD results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz and 5.8 GHz range that was rounded off to the closest tenth dB. So, the offset is 10.1 dB in 2.4 GHz. And the offset gap in the 2.4 GHz range do not affect the PSD final result. Actual value of loss for the attenuator and cable combination is below table.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1210FR01-2	Date of Issue: October 26, 2012	EUT Type: CDMA/GSM/WCDMA/LTE Telematics with Bluetooth/WLAN	FCC ID: BEJLTTTC10F

Band	Frequency(MHz)	Loss(dB)
2.4 GHz	2412	10.11
	2437	10.10
	2462	10.12
5.8 GHz	5745	10.37
	5785	10.38
	5825	10.37

(Actual value of loss for the attenuator and cable combination)

■ TEST RESULTS

Conducted Power Density Measurements

Frequency (MHz)	Channel No.	Mode	Test Result		
			PSD (dBm)	Limit (dBm)	Pass/Fail
2412	1	802.11b	7.322	8	Pass
2437	6		7.403	8	Pass
2462	11		7.924	8	Pass
2412	1	802.11g	3.128	8	Pass
2437	6		3.571	8	Pass
2462	11		3.561	8	Pass
2412	1	802.11n	2.175	8	Pass
2437	6	2.4 GHz	2.264	8	Pass
2462	11	Band	2.747	8	Pass
5745	149	802.11a	-0.916	8	Pass
5785	157		-1.222	8	Pass
5825	165		-0.862	8	Pass
5745	149	802.11n	-1.153	8	Pass
5785	157	5.8 GHz	-0.867	8	Pass
5825	165	Band	-1.330	8	Pass

RESULT PLOTS

Power Spectral Density (802.11b-CH 1)



Power Spectral Density (802.11b-CH 6)



Power Spectral Density (802.11b-CH 11)



Power Spectral Density (802.11g-CH 1)



Power Spectral Density (802.11g-CH 6)




Power Spectral Density (802.11g-CH11)



Power Spectral Density (802.11n-CH 1)



Power Spectral Density (802.11n-CH 6)



Power Spectral Density (802.11n-CH11)



Power Spectral Density (802.11a-CH 149)



Power Spectral Density (802.11a-CH 157)



Power Spectral Density (802.11a-CH 165)



Power Spectral Density (802.11n-CH 149)



Power Spectral Density (802.11n-CH 157)



Power Spectral Density (802.11n-CH 165)



FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1210FR01-2	Date of Issue: October 26, 2012	EUT Type: CDMA/GSM/WCDMA/LTE Telematics with Bluetooth/WLAN	FCC ID: BEJLTC10F


8.4 OUT OF BAND EMISSIONS AT THE BAND EDGE/ CONDUCTED SPURIOUS EMISSIONS

Test Requirements and limit, §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a) (see § 15.205(c)).

Limit : 20 dBc

▣ TEST CONFIGURATION



▣ TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer.

RBW = 100 kHz(Upon 1 GHz = 1 MHz)

VBW = 300 kHz(Upon 1 GHz = 1 MHz)

Set span to encompass the spectrum to be examined

Detector = Peak

Trace Mode = max hold

Sweep = auto couple

Measurements are made over the 30 MHz to 40 GHz range with the transmitter set to the lowest, middle, and highest channels.

Note :

1. The band edge results in plot is already including the actual values of loss for the attenuator and cable combination.
2. Spectrum offset = Attenuator loss + Cable loss
3. We apply to the offset in the 2.4 GHz and 5.8 GHz range that was rounded off to the closest tenth dB. So, the offset is 10.1 dB in 2.4 GHz. And the offset gap in the 2.4 GHz range do not affect the Band Edge final result. Actual value of loss for the attenuator and cable combination is below table.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1210FR01-2	Date of Issue: October 26, 2012	EUT Type: CDMA/GSM/WCDMA/LTE Telematics with Bluetooth/WLAN	FCC ID: BEJLTC10F

Band	Frequency(MHz)	Loss(dB)
2.4 GHz	2412	10.11
	2437	10.10
	2462	10.12
5.8 GHz	5745	10.37
	5785	10.38
	5825	10.37

(Actual value of loss for the attenuator and cable combination)

4. In case of conducted spurious emissions test, please check factors blow table.

▣ **FACTORS FOR FREQUENCY**

Freq(MHz)	Factor(dB)
30	10.37
100	10.16
200	10.15
300	10.14
400	10.18
500	10.19
600	10.20
700	10.30
800	10.25
900	10.28
1000	10.29
2000	10.17
2400*	10.10
2500*	10.12
3000	10.26
4000	10.31
5000	9.85
5700*	10.40
5800*	10.38
6000	10.20
7000	10.60
8000	10.53
9000	10.23
10000	10.41
11000	10.65
12000	11.19
13000	10.97

14000	11.42
15000	12.01
16000	11.77
17000	10.78
18000	10.76
19000	11.15
20000	10.75
21000	10.82
22000	10.82
23000	11.26
24000	11.08
25000	11.18
26000	10.90
27000	11.32
28000	11.33
29000	11.77
30000	11.40
31000	11.82
32000	11.07
33000	13.05
34000	15.68
35000	14.08
36000	15.88
37000	17.32
38000	15.44
39000	14.48
40000	16.50


Note : 1. '*' is fundamental frequency range.
2. Factor = Cable loss + Attenuator loss

RESULT PLOTS

BandEdge (802.11b-CH1)




BandEdge (802.11b-CH11)



BandEdge (802.11g-CH1)




BandEdge (802.11g-CH11)



BandEdge (802.11n-CH1)




BandEdge (802.11n-CH11)



BandEdge (802.11a-CH 149)




BandEdge (802.11a-CH 165)



BandEdge (802.11n-CH 149)



BandEdge (802.11n-CH 165)



30 MHz ~ 1 GHz

Conducted Spurious Emission (802.11b-CH1)



Conducted Spurious Emission (802.11b-CH6)



Conducted Spurious Emission (802.11b-CH11)



Conducted Spurious Emission (802.11g-CH1)




Conducted Spurious Emission (802.11g-CH6)



Conducted Spurious Emission (802.11g-CH11)



Conducted Spurious Emission (802.11n-CH1)



Conducted Spurious Emission (802.11n-CH6)




Conducted Spurious Emission (802.11n-CH11)




FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1210FR01-2	Date of Issue: October 26, 2012	EUT Type: CDMA/GSM/WCDMA/LTE Telematics with Bluetooth/WLAN	FCC ID: BEJLTC10F


Conducted Spurious Emission (802.11a-CH149)




Conducted Spurious Emission (802.11a-CH157)




Conducted Spurious Emission (802.11a-CH165)




Conducted Spurious Emission (802.11n-CH149)



Conducted Spurious Emission (802.11n-CH157)



Conducted Spurious Emission (802.11n-CH165)



1 GHz ~ 26 GHz

Conducted Spurious Emission (802.11b-CH1)



Conducted Spurious Emission (802.11b-CH6)



Conducted Spurious Emission (802.11b-CH11)



Conducted Spurious Emission (802.11g-CH1)



Conducted Spurious Emission (802.11g-CH6)



Conducted Spurious Emission (802.11g-CH11)



Conducted Spurious Emission (802.11n-CH1)



Conducted Spurious Emission (802.11n-CH6)




Conducted Spurious Emission (802.11n-CH11)




FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1210FR01-2	Date of Issue: October 26, 2012	EUT Type: CDMA/GSM/WCDMA/LTE Telematics with Bluetooth/WLAN	FCC ID: BEJLTC10F

1 GHz ~ 40 GHz


Conducted Spurious Emission (802.11a-CH149)




Conducted Spurious Emission (802.11a-CH157)




Conducted Spurious Emission (802.11a-CH165)




Conducted Spurious Emission (802.11n-CH149)



Conducted Spurious Emission (802.11n-CH157)



Conducted Spurious Emission (802.11n-CH165)



8.5 RADIATED MEASUREMENT.


8.5.1 RADIATED SPURIOUS EMISSIONS.

Test Requirements and limit, §15.205, §15.209


Frequency (MHz)	Field Strength (uV/m)	Measurement Distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Test Configuration


Below 30 MHz



30 MHz - 1 GHz



Above 1 GHz



TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8 m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3 m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1210FR01-2	Date of Issue: October 26, 2012	EUT Type: CDMA/GSM/WCDMA/LTE Telematics with Bluetooth/WLAN	FCC ID: BEJLTC10F

TEST RESULTS

9 kHz – 30MHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 9 kHz to the 30MHz.
2. The reading of emissions are attenuated more than 20 dB below the permissible limits or the field strength is too small to be measured.
3. Distance extrapolation factor = 40 log (specific distance / test distance) (dB)
4. Limit line = specific Limits (dB μ V) + Distance extrapolation factor
5. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

TEST RESULTS

Below 1 GHz

Operation Mode: Normal Mode

Frequency	Reading	Ant. factor	Cable loss	Ant. POL	Total	Limit	Margin
MHz	dB μ V	dB /m	dB	(H/V)	dB μ V/m	dB μ V/m	dB
No Critical peaks found							

Notes:

1. Measuring frequencies from 30 MHz to the 1 GHz.
2. Radiated emissions measured in frequency range from 30 MHz to 1000 MHz were made with an instrument using Quasi peak detector mode.
3. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Above 1 GHz

Operation Mode:	802.11 b
Transfer Rate:	1 Mbps
Operating Frequency	2412
Channel No.	01 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4824	58.05	-0.79	V	57.26	74	16.74	PK
4824	53.06	-0.79	V	52.27	54	1.73	AV
7236	51.65	9.08	V	60.73	74	13.27	PK
7236	40.74	9.08	V	49.82	54	4.18	AV
4824	57.79	-0.79	H	57.00	74	17.00	PK
4824	53.25	-0.79	H	52.46	54	1.54	AV
7236	52.04	9.08	H	61.12	74	12.88	PK
7236	42.53	9.08	H	51.61	54	2.39	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz, Detector = Peak, Trace = Max hold.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 3 MHz, Detector = Sample, Trace Averaging over a minimum of 100 traces.
6. We have done 802.11b/g/n(2.4 GHz) mode test. Worst case of EUT is 1 Mbps in 802.11b.
7. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode:	802.11 b
Transfer Rate:	1 Mbps
Operating Frequency	2437
Channel No.	06 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4874	56.80	-0.37	V	56.43	74	17.57	PK
4874	51.02	-0.37	V	50.65	54	3.35	AV
7311	50.83	8.64	V	59.47	74	14.53	PK
7311	40.38	8.64	V	49.02	54	4.98	AV
4874	56.40	-0.37	H	56.03	74	17.97	PK
4874	50.80	-0.37	H	50.43	54	3.57	AV
7311	52.71	8.64	H	61.35	74	12.65	PK
7311	43.09	8.64	H	51.73	54	2.27	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz, Detector = Peak, Trace = Max hold.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 3 MHz, Detector = Sample, Trace Averaging over a minimum of 100 traces.
6. We have done 802.11b/g/n(2.4 GHz) mode test. Worst case of EUT is 1 Mbps in 802.11b.
7. We have done x, y, z planes 802.11 b in EUT and horizontal and vertical polarization in detecting antenna.

Operation Mode:

Transfer Rate:	1 Mbps
Operating Frequency	2462
Channel No.	11 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-AMP G [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
4924	55.46	-0.15	V	55.31	74.00	18.69	PK
4924	50.54	-0.15	V	50.39	54.00	3.61	AV
7386	51.52	9.06	V	60.58	74	13.42	PK
7386	39.98	9.06	V	49.04	54	4.96	AV
4924	55.21	-0.15	H	55.06	74	18.94	PK
4924	49.63	-0.15	H	49.48	54	4.52	AV
7386	52.78	9.06	H	61.84	74	12.16	PK
7386	43.09	9.06	H	52.15	54	1.85	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz, Detector = Peak, Trace = Max hold.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 3 MHz, Detector = Sample, Trace Averaging over a minimum of 100 traces.
6. We have done 802.11b/g/n(2.4 GHz) mode test. Worst case of EUT is 1 Mbps in 802.11b.
7. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Band :	5.8 GHz
Operation Mode:	802.11 a
Transfer Rate:	6 Mbps
Operating Frequency	5745 MHz
Channel No.	149 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-Amp G. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
11490	25.93	11.22	V	37.15	74	36.85	PK
11490	38.61	11.22	V	49.83	54	4.17	AV
17235	47.37	18.82	V	66.19	74	7.81	PK
17235	32.71	18.82	V	51.53	54	2.47	AV
11490	39.75	11.22	H	50.97	74	23.03	PK
11490	26.20	11.22	H	37.42	54	16.58	AV
17235	47.54	18.82	H	66.36	74	7.64	PK
17235	33.25	18.82	H	52.07	54	1.93	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz, Detector = Peak, Trace = Max hold.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 3 MHz, Detector = Sample, Trace Averaging over a minimum of 100 traces.
6. We have done 802.11b/g/n(2.4 GHz) mode test. Worst case of EUT is 1 Mbps in 802.11b.
7. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Band :	5.8 GHz
Operation Mode:	802.11 a
Transfer Rate:	6 Mbps
Operating Frequency	5785 MHz
Channel No.	157 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-Amp G. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
11570	37.80	11.71	V	49.51	74	24.49	PK
11570	24.73	11.71	V	36.44	54	17.56	AV
17355	43.71	18.94	V	62.65	74	11.36	PK
17355	31.50	18.94	V	50.44	54	3.57	AV
11570	39.34	11.71	H	51.05	74	22.95	PK
11570	25.49	11.71	H	37.20	54	16.80	AV
17355	44.48	18.94	H	63.42	74	10.59	PK
17355	31.31	18.94	H	50.25	54	3.76	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz, Detector = Peak, Trace = Max hold.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 3 MHz, Detector = Sample, Trace Averaging over a minimum of 100 traces.
6. We have done 802.11b/g/n(2.4 GHz) mode test. Worst case of EUT is 1 Mbps in 802.11b.
7. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

Band :	5.8 GHz
Operation Mode:	802.11 a
Transfer Rate:	6 Mbps
Operating Frequency	5825 MHz
Channel No.	165 Ch

Frequency [MHz]	Reading dBuV	AN.+CL-Amp G. [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
11650	38.29	11.34	V	49.63	74	24.37	PK
11650	25.03	11.34	V	36.37	54	17.63	AV
17475	44.61	19.52	V	64.13	74	9.87	PK
17475	31.86	19.52	V	51.38	54	2.62	AV
11650	38.36	11.34	H	49.70	74	24.30	PK
11650	24.90	11.34	H	36.24	54	17.76	AV
17475	44.95	19.52	H	64.47	74	9.53	PK
17475	31.65	19.52	H	51.17	54	2.83	AV

Notes:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser if no specific emissions from the EUT are recorded (ie: margin > 20 dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Radiated emissions measured in frequency above 1000MHz were made with an instrument using Peak detector mode and average detector mode of the emission shown in Actual FS column.
4. Total = Reading Value + Antenna Factor + Cable Loss - Amp Gain
5. Spectrum setting:
 - a. Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz, Detector = Peak, Trace = Max hold.
 - b. AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 3 MHz, Detector = Sample, Trace Averaging over a minimum of 100 traces.
6. We have done 802.11b/g/n(2.4 GHz) mode test. Worst case of EUT is 1 Mbps in 802.11b.
7. We have done x, y, z planes in EUT and horizontal and vertical polarization in detecting antenna.

FCC PT.15.247 TEST REPORT	FCC CERTIFICATION REPORT		www.hct.co.kr
Test Report No. HCTR1210FR01-2	Date of Issue: October 26, 2012	EUT Type: CDMA/GSM/WCDMA/LTE Telematics with Bluetooth/WLAN	FCC ID: BEJLTC10F

8.5.2 RADIATED RESTRICTED BAND EDGE MEASUREMENTS

Test Requirements and limit, §15.247(d) §15.205, §15.209

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in section 15.209(a) (See section 15.205(c)).

Operation Mode:	802.11g
Transfer Rate:	6 Mbps
Operating Frequency	2412 MHz, 2462 MHz
Channel No.	01 Ch, 11 Ch

Frequency [MHz]	Reading dBuV	AN.+CL [dB]	ANT. POL [H/V]	Total [dBuV/m]	Limit [dBuV/m]	Margin [dB]	Detect
2390.0	38.29	33.90	H	72.19	74	1.81	PK
2390.0	16.93	33.90	H	50.83	54	3.17	AV
2390.0	34.70	33.90	V	68.60	74	5.40	PK
2390.0	15.28	33.90	V	49.18	54	4.82	AV
2483.5	36.84	33.99	H	70.83	74	3.17	PK
2483.5	16.89	33.99	H	50.88	54	3.12	AV
2483.5	36.17	33.99	V	70.16	74	3.84	PK
2483.5	16.18	33.99	V	50.17	54	3.83	AV

Notes:

- Total = Reading Value + Antenna Factor + Cable Loss
- Spectrum setting:
 - Peak Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 1 MHz.
 - AV Setting 1 GHz – 26 GHz, RBW = 1 MHz, VBW = 3 MHz, Detector = Sample, Trace Averaging over a minimum of 100 traces.
- We have done 802.11b/g/n(2.4 GHz) mode test. . Worst case of EUT is 6 Mbps in 802.11g.

8.6 POWERLINE CONDUCTED EMISSIONS

Test Requirements and limit, §15.207

For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range is listed as follows:

Frequency Range (MHz)	Limits (dBµV)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56	56 to 46
0.50 to 5	56	46
5 to 30	60	50

Compliance with this provision shall be based on the measurement of the radio frequency voltage between each power line (LINE and NEUTRAL) and ground at the power terminals.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT is placed on a wooden table 80 cm above the reference ground plane.
2. The EUT is connected via LISN to a test power supply.
3. The measurement results are obtained as described below:
4. Detectors – Quasi Peak and Average Detector.

Note : We don't perform powerline conducted emission test. Because this EUT is used with vehicle.

9. LIST OF TEST EQUIPMENT

Manufacturer	Model / Equipment	Calibration Interval	Calibration Due	Serial No.
Rohde & Schwarz	ENV216/ LISN	Annual	02/09/2013	100073
Schwarzbeck	VULB 9168/ TRILOG Antenna	Biennial	02/09/2013	200
Rohde & Schwarz	ESI 40 / EMI TEST RECEIVER	Annual	05/03/2013	831564103
Agilent	E4440A/ Spectrum Analyzer	Annual	05/02/2013	US45303008
Agilent	N9020A/ SIGNAL ANALYZER	Annual	07/31/2013	MY51110020
HD	MA240/ Antenna Position Tower	N/A	N/A	556
EMCO	1050/ Turn Table	N/A	N/A	114
HD GmbH	HD 100/ Controller	N/A	N/A	13
HD GmbH	KMS 560/ SlideBar	N/A	N/A	12
Rohde & Schwarz	SCU-18/ Signal Conditioning Unit	Annual	09/11/2013	10094
MITEQ	AMF-6B-180265-35-10P / POWER AMP	Annual	04/16/2013	667624
CERNEX	CBL26405040 / POWER AMP	Annual	04/16/2013	19660
Schwarzbeck	BBHA 9120D/ Horn Antenna	Biennial	10/17/2013	937
Schwarzbeck	BBHA9170 / Horn Antenna(15 GHz ~ 40 GHz)	Biennial	10/26/2012	BBHA9170342
Rohde & Schwarz	FSP / Spectrum Analyzer	Annual	02/09/2013	839117/011
Agilent	E4416A /Power Meter	Annual	11/07/2012	GB41291412
Agilent	E9327A /POWER SENSOR	Annual	05/02/2013	MY4442009
Wainwright Instrument	WHF3.3/18G-10EF / High Pass Filter	Annual	05/02/2013	1
Wainwright Instrument	WRCJ2400/2483.5-2370/2520-60/14SS / Band Reject Filter	Annual	05/02/2013	1
Hewlett Packard	11636B/Power Divider	Annual	11/07/2012	11377
Hewlett Packard	11667B / Power Splitter	Annual	06/05/2013	05001
DIGITAL	EP-3010 /DC POWER SUPPLY	Annual	11/07/2012	3110117
ITECH	IT6720 / DC POWER SUPPLY	Annual	11/07/2012	010002156287001199
TESCOM	TC-3000C / BLUETOOTH TESTER	Annual	11/14/2012	3000C000276
Rohde & Schwarz	CBT / BLUETOOTH TESTER	Annual	05/02/2013	100422
EMCO	6502.LOOP ANTENNA	Biennial	01/11/2014	9009-2536
CERNEX	CBLU1183540 / POWER AMP	Annual	07/27/2013	21691