

Cybiotronics Limited

Application  
For  
Certification

5.8GHz Frequency Hopping Spread Spectrum Cordless Phone with Caller ID  
and Speakerphone

**(FCC ID: CAC677001)**

05132221  
TL/Ann Choy  
September 1, 2005

- The test results reported in this test report shall refer only to the sample actually tested and shall not refer or be deemed to refer to bulk from which such a sample may be said to have been obtained.
- This report shall not be reproduced except in full without prior authorization from Intertek Testing Services Hong Kong Limited.
- For Terms And Conditions of the services, it can be provided upon request.
- The evaluation data of the report will be kept for 3 years from the date of issuance.

**Intertek Testing Services Hong Kong Ltd.**

2/F., Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong.  
Tel: (852) 2173 8888 Fax: (852) 2741 1693 Website: [www.hk.intertek-etlsemko.com](http://www.hk.intertek-etlsemko.com)

**LIST OF EXHIBITS**

*INTRODUCTION*

<i>EXHIBIT 1:</i>	Summary of Tests
<i>EXHIBIT 2:</i>	General Description
<i>EXHIBIT 3:</i>	System Test Configuration
<i>EXHIBIT 4:</i>	Measurement Results
<i>EXHIBIT 5:</i>	Equipment Photographs
<i>EXHIBIT 6:</i>	Product Labelling
<i>EXHIBIT 7:</i>	Technical Specifications
<i>EXHIBIT 8:</i>	Instruction Manual
<i>EXHIBIT 9:</i>	Security Code Information
<i>EXHIBIT 10:</i>	Confidentiality Request



---

# INTERTEK TESTING SERVICES

---

## Table of Contents

<b>1.0 <u>Summary of test results</u></b>	<b>2</b>
<b>2.0 <u>General Description</u></b>	<b>4</b>
2.1 Product Description	4
2.2 Related Submittal(s) Grants	5
2.3 Test Methodology	5
2.4 Test Facility	5
<b>3.0 <u>System Test Configuration</u></b>	<b>7</b>
3.1 Justification	7
3.2 EUT Exercising Software	7
3.3 Support Equipment List and Description	8
3.4 Measurement Uncertainty	9
3.5 Equipment Modification	9
<b>4.0 <u>Measurement Results</u></b>	<b>11</b>
4.1 Maximum Conducted Output Power at Antenna Terminals	11
4.2 Maximum 20 dB RF Bandwidth	13
4.3 Minimum Number of Hopping Frequencies	15
4.4 Minimum Hopping Channel Carrier Frequency Separation	16
4.5 Average Time of Occupancy	18
4.6 Out of Band Conducted Emissions	19
4.7 Out of Band Radiated Emissions	20
4.8 Transmitter Radiated Emissions in Restricted Bands	21
4.9 Field Strength Calculation	22
4.10 Radiated Emission Configuration Photograph - Base Unit	23
4.11 Radiated Emission Data - Base Unit	24
4.12 Radiated Emission Configuration Photograph - Handset	28
4.13 Radiated Emission Data - Handset	29
4.14 AC Line Conducted Emission	33
4.15 Line Conducted Configuration Photograph - Base Unit	34
4.16 Line Conducted Emission Configuration Data	35
4.17 Radiated Emission from Digital Section of Transceiver	36
4.18 Transmitter Duty Cycle Calculation and Measurements	39
<b>5.0 <u>Equipment Photographs</u></b>	<b>41</b>
<b>6.0 <u>Product Labelling</u></b>	<b>43</b>
<b>7.0 <u>Technical Specifications</u></b>	<b>45</b>
<b>8.0 <u>Instruction Manual</u></b>	<b>47</b>
<b>9.0 <u>Security Code Information</u></b>	<b>49</b>
<b>10.0 <u>Confidentiality Request</u></b>	<b>51</b>

---

## INTERTEK TESTING SERVICES

---

### List of attached file

Exhibit type	File Description	filename
Cover Letter	Confidentiality Request	request.pdf
Test Report	Test Report	report.pdf
Test Report	Maximum Output Power Plot	maxop.pdf
Test Report	20 dB Bandwidth Plot	20dB.pdf
Test Report	Minimum Number of Hopping Frequencies	chno.pdf
Test Report	Minimum Hopping Channel Carrier Frequency Separation	fsepa.pdf
Test Report	Average Channel Occupancy Time	avetime.pdf
Test Report	Out Band Antenna Conducted Emission Plot	obantcon.pdf
Test Report	Duty Cycle Calculation and Measurement	dcc.pdf
Test Report	Conducted Emission Test Result	conduct.pdf
Test Setup Photo	Radiated Emission for Base	config photos.doc
Test Setup Photo	Radiated Emission for Handset	config photos.doc
Test Setup Photo	Conducted Emission	config photos.doc
External Photo	External Photo	external photos.doc
Internal Photo	Internal Photo	internal photos.doc
Block Diagram	Block Diagram	block.pdf
Schematics	Circuit Diagram	circuit.pdf
ID Label/Location	Label Artwork and Location	label.pdf
User Manual	User Manual	manual.pdf
User Manual	FCC Information	FCC information.pdf
RF Exposure Info	RF Safety	RF exposure info.pdf
Operation Description	Technical Description	descri.pdf
Operation Description	Security Code Information	security code information.pdf

**EXHIBIT 1**  
**SUMMARY OF TEST RESULTS**

---

## INTERTEK TESTING SERVICES

---

### 1.0 Summary of Test

#### **Cybiotronics Limited**

**MODEL: CY-677(XXX), BS-677(XXX), SBC 677(XXX), CYBIOLINK 677(XXX),  
CY-677B(XXX), BS-677B(XXX), SBC 677B(XXX), CYBIOLINK 677B(XXX),  
CY-671(XXX), BS-671(XXX), SBC 671(XXX), CYBIOLINK 671(XXX)**

**FCC ID: CAC677001**

TEST	REFERENCE	RESULTS
Max. Output Power	15.247(b)	Pass
Min. No. of Hopping Frequencies	15.247(a)(1)	Pass
Min. Hopping Channel Carrier Frequency Separation	15.247(a)(1)	Pass
Average Time of Occupancy	15.247(a)(1)	Pass
Out of Band Antenna Conducted Emission	15.247(d)	Pass
Radiated Emission in Restricted Bands	15.247(d)	Pass
AC Conducted Emission	15.207	Pass
Radiated Emission from Digital Part	15.109	Pass
Antenna Requirement	15.203	Pass (See Notes)

Notes: The EUT uses a permanently attached antenna which, in accordance to Section 15.203, is considered sufficient to comply with the provisions of this section.

**EXHIBIT 2**  
**GENERAL DESCRIPTION**



---

## INTERTEK TESTING SERVICES

---

### 2.0 **General Description**

#### 2.1 Product Description

The CY-677 is a 5.8GHz Frequency Hopping Spread Spectrum Cordless Phone with Caller ID and Speakerphone. It operates at frequency range of 5761.486MHz to 5839.077MHz with 88 physical hopping frequencies and 75 logical hopping frequencies. The unit is capable of either tone or pulse dialing. The internal power supply's isolation is accomplished through a power transformer having an adequate dielectric rating. The circuit wiring is consistent under the requirement of part 68.

The handset unit consists of a keypad with twelve standard keys (0,...9,\*,#), five function keys (Int, Mute, Redial/Pause, Spk., Up/Down). A Talk key is provided to control pick/release telephone line in a toggle base.

The base unit has a page key, which is used to communicate with handset unit.

The antennas used in base unit and handset are integral, and the test sample is a prototype.

The Model: CY-677 is one of the Model: CY-677(XXX), and the Models: BS-677(XXX), SBC 677(XXX), and CYBIOLINK 677(XXX) are the same as the Model: CY-677 in hardware aspect. The Models: CY-677B(XXX), BS-677B(XXX), SBC 677B(XXX), and CYBIOLINK 677B(XXX) have one base unit plus two identical handsets with a charger. The Models: CY-671(XXX), BS-671(XXX), SBC 671(XXX), and CYBIOLINK 671(XXX) are an additional identical handset with a charger for selling handset standalone. The suffix, (XXX), followed by the model number stands for color difference and different packaging. The model numbers are identical in electrical, mechanical, and physical design. The difference in model number serves as marketing strategy.

The circuit description and frequency hopping algorithm is saved with filename: descri.pdf

Connection between the device and the telephone network is accomplished through the use of USOC RJ11C in the 2-wire loop calling central office line.

## INTERTEK TESTING SERVICES

---

### 2.2 Related Submittal(s) Grants

This is an application for Certification of a DSS-Part 15 Spread Spectrum Cordless Telephone System. Two transmitters are included in this application. The device is also subject to Part 68 Registration.

### 2.3 Test Methodology

Both AC mains line-conducted and radiated emission measurements were performed according to the procedures in ANSI C63.4 (2003). All measurements were performed in Open Area Test Sites. Preliminary scans were performed in the Open Area Test Sites only to determine worst case modes. All Radiated tests were performed at an antenna to EUT distance of 3 meters, unless stated otherwise in the "**Justification Section**" of this Application. All other measurements were made in accordance with the procedures in 47 CFR Part 2.

### 2.4 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located at Garment Centre, 576 Castle Peak Road, Kowloon, Hong Kong. This test facility and site measurement data have been fully placed on file with the FCC.

**EXHIBIT 3**  
**SYSTEM TEST CONFIGURATION**

### 3.0 **System Test Configuration**

#### 3.1 Justification

For emissions testing, the equipment under test (EUT) was setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, all cables were manipulated to produce worst case emissions. The handset was powered by a fully charged battery.

For the measurements, the EUT is attached to a plastic stand if necessary and placed on the wooden turntable. If the base unit attaches to peripherals, they are connected and operational (as typical as possible). The handset is remotely located as far from the antenna and the base as possible to ensure full power transmission from the base. Else, the base is wired to transmit full power without modulation.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Detector function is in peak mode. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000MHz. The resolution is 1MHz or greater for frequencies above 1000MHz.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9kHz to 40GHz.

#### 3.2 EUT Exercising Software

The EUT exercise program used during radiated and conducted testing was designed to exercise the various system components in a manner similar to a typical use.

---

## INTERTEK TESTING SERVICES

---

### 3.3 Support Equipment List and Description

The FCC ID's for all equipment, plus descriptions of all cables used in the tested system (included inserted cards, which have grants) are:

#### *HARDWARE:*

The unit was operated standalone. An AC adapter and a battery (provided with the unit) were used to power the device. Their description are listed below.

- (1) Base Unit: An AC adaptor (120VAC to 7.5VDC 500mA, Model: AD-0750)
- (2) Extra Charger: An AC adaptor (120VAC to 9VDC 200mA, Model : SA35-39A)
- (3) Handset: A "Ni-MH" type rechargeable battery (3.6V 800mAh)

#### *CABLES:*

- (1) Telecommunication cable with RJ11C connectors (1m, unshielded), terminated

#### *OTHERS:*

- (1) A headset for telephone use with 1.2m unshielded cable permanently affixed.  
(Supplied by Intertek)

---

## INTERTEK TESTING SERVICES

---

### 3.4 Measurement Uncertainty

When determining of the test conclusion, the Measurement Uncertainty of test has been considered.

### 3.5 Equipment Modification


Any modifications installed previous to testing by Cybionics Limited will be incorporated in each production model sold/leased in the United States.

No modifications were installed by ETL Division, Intertek Testing Services Hong Kong Ltd.

All the items listed under section 3.0 of this report are confirmed by:

*Confirmed by:*

*Tommy Leung  
Assistant Manager  
Intertek Testing Services Hong Kong Ltd.  
Agent for Cybionics Limited*

  
\_\_\_\_\_  
Signature

\_\_\_\_\_  
Sep 29, 2005 Date

**EXHIBIT 4**  
**MEASUREMENT RESULTS**

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.0 Measurement Results

#### 4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b) :

- ☐ The antenna power of the EUT was connected to the input of a power meter. Power was read directly and cable loss correction was added to the reading to obtain power at the EUT antenna terminals.
- ☒ The antenna port of the EUT was connected to the input of a spectrum analyzer. The analyzer was set for RBW>20dB bandwidth and power was read directly in dBm. External attenuation and cable loss were compensated for using the OFFSET function of the analyser.

For antennas with gains of 6 dBi or less, maximum allowed transmitter output is 1 watt (+30 dBm).

(Base Unit) Antenna Gain = 1.5 dBi		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 5761.486	19.88	97.27
Middle Channel: 5800.728	19.02	79.80
High Channel: 5839.077	18.28	67.30

Cable loss : 0.5 dB External Attenuation : N/A dB

Cable loss, external attenuation: ☒ included in OFFSET function  
☐ added to SA raw reading

dBm max. output level = 19.88 dBm (30 dBm or less)

Please refer to the attached plots for details:

Plot B1A: Low Channel Output Power  
Plot B1B: Middle Channel Output Power  
Plot B1C: High Channel Output Power



---

## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.1 Maximum Conducted Output Power at Antenna Terminals, FCC Rules 15.247(b) - Continued:

(Handset Unit) Maximum Antenna Gain = 1.5 dBi		
Frequency (MHz)	Output in dBm	Output in mWatt
Low Channel: 5761.486	20.24	105.68
Middle Channel: 5800.728	19.65	92.26
High Channel: 5839.077	18.25	66.83

Cable loss : 0.5 dB External Attenuation : N/A dB

Cable loss, external attenuation: [ x ] included in OFFSET function  
[ ] added to SA raw reading

dBm max. output level = 20.24 dBm (30 dBm or less)

Please refer to the attached plots for details:

Plot H1A: Low Channel Output Power  
Plot H1B: Middle Channel Output Power  
Plot H1C: High Channel Output Power

For electronic filing, the above plots are saved with filename: maxop.pdf

For RF Safety, the information is saved with filename: RF exposure info.pdf.

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.2 Maximum 20 dB RF Bandwidth, FCC Rule 15.247(a)(1):

The antenna port of the EUT was connected to the input of a spectrum analyzer. Analyzer RES BW was chosen so that the display was a result of the hopping channel modulation. For each RF output channel investigated, the spectrum analyzer center frequency was set to the channel carrier. A PEAK output reading was taken, a DISPLAY line was drawn 20 dB lower than PEAK level. The 20 dB bandwidth was determined from where the channel output spectrum intersected the display line.

(Base Unit)	
Frequency (MHz)	20 dB Bandwidth (kHz)
5761.486	684

Refer to the following plots for 20 dB bandwidth sharp:

Plot B2A: Low Channel 20 dB RF Bandwidth  
Plot B2B: Middle Channel 20 dB RF Bandwidth  
Plot B2C: High Channel 20 dB RF Bandwidth

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.2 Maximum 20 dB RF Bandwidth, FCC Rule 15.247(a)(1) - Continued:

(Handset Unit)	
Frequency (MHz)	20 dB Bandwidth (kHz)
5839.077	678

Refer to the following plots for 20 dB bandwidth sharp:

Plot H2A: Low Channel 20 dB RF Bandwidth

Plot H2B: Middle Channel 20 dB RF Bandwidth

Plot H2C: High Channel 20 dB RF Bandwidth

For electronic filing, the above plots are saved with filename: 20dB.pdf

## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.3 Minimum Number of Hopping Frequencies, FCC Rule 15.247(a)(1)(iii) :

The RF passband of the EUT was divided into 4 approximately equal bands. With the analyzer set to MAX HOLD readings were taken for 2-3 minutes in each band. The channel peaks so recorded were added together, and the total number compared to the minimum number of channels required in the regulation.

Base Unit and Handset	
No. of hopping channels	75

Minimum Requirements: at least 75 hopping channels for 5725MHz-5850MHz.

For electronic filing, the above plots are saved with filename: chno.pdf

## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.4 Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1) :

Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit.

[ ] 25 kHz [ x ] 20 dB bandwidth of hopping channel: 684kHz

Base Unit	
Channel Separation	888 kHz

Plot B4: Channel 26 and Channel 27

Requirement: The frequency separation is more than 20dB bandwidth of hopping channel.

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.4 Minimum Hopping Channel Carrier Frequency Separation, FCC Ref: 15.247(a)(1)(iii) - Continued:

Using the DELTA MARKER function of the analyzer, the frequency separation between two adjacent channels was measured and compared against the limit.

[ ] 25 kHz [ x ] 20 dB bandwidth of hopping channel: 678kHz

Handset	
Channel Separation	892 kHz

Plot H4: Channel 26 and Channel 27

Requirement: The frequency separation is more than 20dB bandwidth of hopping channel.

For electronic filing, the above plots are saved with filename: fsepa.pdf

---

## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.5 Average Channel Occupancy Time, FCC Ref: 15.247(a)(1)(iii)

The spectrum analyzer center frequency was set to one of the known hopping channels. The SWEEP was set to 10ms, the SPAN was set to ZERO SPAN, and the TRIGGER was set to VIDEO. The time duration of the transmission so captured was measured with the MARKER DELTA function.

The SWEEP was then set to the time required by the regulation (20 seconds for 902-928 MHz devices, if the 20dB bandwidth is less than 250kHz, 10 seconds for 902-928 MHz if the 20dB bandwidth is or greater than 250kHz, "0.4 seconds x Number of hopping channels employed" seconds for 2400-2483.5 MHz, 30 seconds for 5725-5850 MHz). The analyzer was set to SINGLE SWEEP, the total ON time was added and compared against the limit (0.4 seconds).

Average 0.4 seconds maximum occupancy in 30 seconds for 5725MHz-5850MHz.

Base Unit for 3 Handsets Operation	
Average Occupancy Time = $920\mu\text{s} \times 40 \times 3 + 260\mu\text{s} \times 40$	120.8 ms

Refer to attached spectrum analyzer plots B5A-E, (One Handset Operation)

Handset Unit for Single Slot Operation	
Average Occupancy Time = $960\mu\text{s} \times 40$	38.4 ms

Refer to attached spectrum analyzer plots H5A-C (Single Slot Operation)

For electronic filing, the above plots are saved with filename: avetime.pdf

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.6 Out of Band Conducted Emissions, FCC Rule 15.247(d):

In any 100 kHz bandwidth outside the EUT passband, the RF power produced by the modulation products of the spreading sequence, the information sequence, and the carrier frequency shall be at least 20 dB below that of the maximum in-band 100 kHz emission, or else shall meet the general limits for radiated emissions at frequencies outside the passband, whichever results in lower attenuation.

All other types of emissions from the EUT shall meet the general limits for radiated frequencies outside the passband.

Refer to the following plots for out of band conducted emissions data:

Plot B6A1 - B6A2: Low Channel Emissions  
Plot B6B1 - B6B2: Middle Channel Emissions  
Plot B6C1 - B6C2: High Channel Emissions  
Plot B6D1 - B6D2: Modulation Products Emission\*  
Plot H6A1 - H6A2: Low Channel Emissions  
Plot H6B1 - H6B2: Middle Channel Emissions  
Plot H6C1 - H6C2: High Channel Emissions  
Plot H6D1 - H6D2: Modulation Products Emissions\*

The plots showed the 2<sup>nd</sup> harmonic and modulation products at the band edges of 5725 MHz and 5850 MHz. In addition, all spurious emission and up to the tenth harmonic was measured and they were found to be at least 20 dB below the highest level of the desired power in the passband.

\*These 2 plots are shown the worst-case which has been already considered between enable and disable the hopping function of the EUT.

For electronic filing, the above plots are saved with filenames: obantcon.pdf



## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

4.7 Out of Band Radiated Emissions (for emissions in 4.6 above that are less than 20 dB below carrier), FCC Rule 15.247(d):

For out of band emissions that are close to or that exceed the 20dB attenuation requirement described in the specification, radiated measurements were performed at a 3m separation distance to determine whether these emissions complied with the general radiated emission requirement.

- ☒ Not required, all emissions more than 20dB below fundamental
- ☐ See attached data sheet

## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.8 Transmitter Radiated Emissions in Restricted Bands, FCC Rule 15.35(b), (c):

Data is included of the worst case configuration (the configuration which resulted in the highest emission levels). A sample calculation, configuration photographs and data tables of the emissions are included. All measurements were performed with peak detection unless otherwise specified.

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.9 Field Strength Calculation

The field strength is calculated by adding the reading on the Spectrum Analyzer to the factors associated with preamplifiers (if any), antennas, cables, pulse desensitization and average factors (when specified limit is in average and measurements are made with peak detectors). A sample calculation is included below.

$$FS = RA + AF + CF - AG + PD + AV$$

where FS = Field Strength in dB $\mu$ V/m

RA = Receiver Amplitude (including preamplifier) in dB $\mu$ V

CF = Cable Attenuation Factor in dB

AF = Antenna Factor in dB

AG = Amplifier Gain in dB

PD = Pulse Desensitization in dB

AV = Average Factor in -dB

In the radiated emission table which follows, the reading shown on the data table may reflect the preamplifier gain. An example of the calculations, where the reading does not reflect the preamplifier gain, follows:

$$FS = RA + AF + CF - AG + PD + AV$$

#### Example

Assume a receiver reading of 62.0 dB $\mu$ V is obtained. The antenna factor of 7.4 dB and cable factor of 1.6 dB is added. The amplifier gain of 29 dB is subtracted. The pulse desensitization factor of the spectrum analyzer was 0 dB, and the resultant average factor was -10 dB. The net field strength for comparison to the appropriate emission limit is 32 dB $\mu$ V/m. This value in dB $\mu$ V/m was converted to its corresponding level in  $\mu$ V/m.

$$RA = 62.0 \text{ dB}\mu\text{V}$$

$$AF = 7.4 \text{ dB}$$

$$CF = 1.6 \text{ dB}$$

$$AG = 29.0 \text{ dB}$$

$$PD = 0 \text{ dB}$$

$$AV = -10 \text{ dB}$$

$$FS = 62 + 7.4 + 1.6 - 29 + 0 + (-10) = 32 \text{ dB}\mu\text{V/m}$$

$$\text{Level in mV/m} = \text{Common Antilogarithm } [(32 \text{ dB}\mu\text{V/m})/20] = 39.8 \mu\text{V/m}$$

## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.10 Radiated Emission Configuration Photograph - Base Unit

Worst Case Radiated Emission  
at  
11522.972 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.11 Radiated Emission Data - Base Unit

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 7.7 dB margin compare with the peak limit

\*\*\*\*\*

### **TEST PERSONNEL:**



---

*Tester Signature*

Kenneth C. C. Lam, Senior Lead Engineer  
*Typed/Printed Name*

September 1, 2005  
*Date*

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677  
Mode : TX-Channel 1

Date of Test: June 14-August 2, 2005

Table 1, Base Unit

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (-dB)	Calculated at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
H	*11522.972	59.7	34	40.6	66.3	30.4	35.9	54	-18.1

- NOTES:
1. Peak detector is used for the emission measurement.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function, and this is the worst-case of 7.7dB margin at 11522.972MHz.

Test Engineer: Kenneth C. C. Lam

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677  
Mode : TX-Channel 45

Date of Test: June 14-August 2, 2005

Table 2, Base unit

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (-dB)	Calculated at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	*11601.456	57.7	34	40.6	64.3	30.4	33.9	54	-20.1

- NOTES:
1. Peak detector is used for the emission measurement.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Kenneth C. C. Lam

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677  
Mode : TX-Channel 88

Date of Test: June 14-August 2, 2005

Table 3, Base unit

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dBμV/m)	Average Factor (-dB)	Calculated at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
H	*11678.154	57.2	34	40.6	63.8	30.4	33.4	54	-20.6

- NOTES:
1. Peak detector is used for the emission measurement.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Kenneth C. C. Lam



## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.12 Radiated Emission Configuration Photograph - Handset

Worst Case Radiated Emission  
at  
11522.972 MHz

For electronic filing, the worst case radiated emission configuration photographs are saved with filename: config photos.doc

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005


### 4.13 Radiated Emission Data - Handset

The data on the following pages list the significant emission frequencies, the limit and the margin of compliance.

Judgement : Passed by 8.3 dB margin compare with the peak limit

\*\*\*\*\*

### **TEST PERSONNEL:**



---

*Tester Signature*

Kenneth C. C. Lam, Senior Lead Engineer  
*Typed/Printed Name*

September 1, 2005  
*Date*

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677  
Mode : TX-Channel 1

Date of Test: June 14-August 2, 2005

Table 4, Handset

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (-dB)	Calculated at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	*11522.972	59.1	34	40.6	65.7	40.3	25.4	54	-28.6

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function, and this is the worst-case of 8.3dB margin at 11522.972MHz.

Test Engineer: Kenneth C. C. Lam

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677  
Mode : TX-Channel 45

Date of Test: June 14-August 2, 2005

Table 5, Handset

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (-dB)	Calculated at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	*11601.456	58.1	34	40.6	64.7	40.3	24.4	54	-29.6

- NOTES: 1. Peak detector is used for the emission measurement.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Kenneth C. C. Lam

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677  
Mode : TX-Channel 88

Date of Test: June 14-August 2, 2005

Table 6, Handset

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m - Peak (dB $\mu$ V/m)	Average Factor (-dB)	Calculated at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
H	*11678.154	57.7	34	40.6	64.3	40.3	24.0	54	-30.0

- NOTES:
1. Peak detector is used for the emission measurement.
  2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
  3. Negative value in the margin column shows emission below limit.
  4. Horn antenna used for the emission over 1000MHz.
- \* Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak limit for frequencies below 1000 MHz and average limit for frequencies over 1000 MHz. The radio frequency emissions above 1GHz also meet corresponding 20dB permitted peak limit with a peak detector function.

Test Engineer: Kenneth C. C. Lam

## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.14 AC Line Conducted Emission, FCC Rule 15.207:

☐ Not required; battery operation only

☒ Test data attached

## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.15 Line Conducted Configuration Photograph - Base

#### Worst Case Line-Conducted Configuration

For electronic filing, the worst case line conducted configuration photographs are saved with filename: config photos.doc

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005


### 4.16 Line Conducted Emission Data

The data on the following pages list the significant emission frequencies, the limit, and the margin of compliance.

Judgement : Passed by more than 20 dB margin

For electronic filing, the worst case line conducted emission data are saved with filename: conduct.pdf

### **TEST PERSONNEL:**



---

*Tester Signature*

Kenneth C. C. Lam, Senior Lead Engineer  
*Typed/Printed Name*

September 1, 2005  
*Date*



## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.17 Radiated Emissions from Digital Section of Transceiver (Transmitter), FCC Ref: 15.109

- ☐ Not required - No digital part
- ☒ Test results are attached
- ☐ Included in the separated DOC report.

---

## INTERTEK TESTING SERVICES

---

Company: Cybionics Limited  
Model: CY-677  
Mode: Talk

Date of Test: June 14-August 2, 2005

Table 7, Base Unit

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dBμV)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
V	55.296	29.9	16	11.0	24.9	40.0	-15.1
V	110.592	29.2	16	12.6	25.8	43.5	-17.7
V	165.888	30.0	16	13.8	27.8	43.5	-15.7
V	221.184	33.5	16	11.8	29.3	46.0	-16.7
V	294.913	32.9	16	13.3	30.2	46.0	-15.8
V	304.131	31.8	16	14.3	30.1	46.0	-15.9

- NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

Test Engineer: Kenneth C. C. Lam

---

## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677  
Mode: Talk

Date of Test: June 14-August 2, 2005

Table 8, Handset

### Radiated Emissions

Polarization	Frequency (MHz)	Reading (dB $\mu$ V)	Pre-Amp Gain (dB)	Antenna Factor (dB)	Net at 3m (dB $\mu$ V/m)	Limit at 3m (dB $\mu$ V/m)	Margin (dB)
V	55.296	29.7	16	11.0	24.7	40.0	-15.3
V	110.592	28.9	16	12.6	25.5	43.5	-18.0
V	165.888	30.0	16	13.8	27.8	43.5	-15.7
V	221.184	33.3	16	11.8	29.1	46.0	-16.9
V	294.913	32.7	16	13.3	30.0	46.0	-16.0
V	304.131	31.5	16	14.3	29.8	46.0	-16.2

- NOTES: 1. Quasi-peak detector is used for the emission below or equal to 1000 MHz.
2. All measurements were made at 3 meters. Harmonic emissions not detected at the 3-meter distance were measured at 0.3-meter and an inverse proportional extrapolation was performed to compare the signal level to the 3-meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3-meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna used for the emission over 1000MHz.

Test Engineer: Kenneth C. C. Lam

---

## INTERTEK TESTING SERVICES

---

Company: Cybiotronics Limited  
Model: CY-677

Date of Test: June 14-August 2, 2005

### 4.18 Transmitter Duty Cycle Calculation and Measurements, FCC Rule 15.35(b), (c)

The EUT antenna output port was connected to the input of the spectrum analyzer. The analyzer center frequency was set to EUT RF channel carrier. The SWEF function on the analyzer was set to ZERO SPAN. The transmitter ON time was determined from the resultant time-amplitude display:

Base Unit:

Duty cycle (DC) = Maximum ON time in 100ms/100ms  
= (0.92 x 3 + 0.26)ms/100ms for 3 handsets operation

Duty cycle correction, dB =  $20 \times \log(\text{DC})$   
=  $20 \times \log(0.0302)$   
= -30.4 dB

Handset:

Duty cycle (DC) = Maximum ON time in 100ms/100ms  
= 0.960ms/100ms for single slot operation

Duty cycle correction, dB =  $20 \times \log(\text{DC})$   
=  $20 \times \log(0.0096)$   
= -40.3 dB

X	See attached spectrum analyzer chart (s) for transmitter timing Base Unit: Plot B7A-B (One Handset Operation), Handset: Plot H7
	See transmitter timing diagram provided by manufacturer
	Not applicable, duty cycle was not used.

For electronic filing, the above plots are saved with filenames: dcc.pdf

**EXHIBIT 5**  
**EQUIPMENT PHOTOGRAPHS**

### 5.0 **Equipment Photographs**

For electronic filing, the photographs are saved with filename: external photos.doc & internal photos.doc

**EXHIBIT 6**  
**PRODUCT LABELLING**

### 6.0 **Product Labelling**

For electronic filing, the FCC ID label artwork and location is saved with filename:  
label.pdf



**EXHIBIT 7**  
**TECHNICAL SPECIFICATIONS**

### 7.0 **Technical Specifications**

For electronic filing, the block diagram and circuit diagram are saved with filename: block.pdf and circuit.pdf respectively.

**EXHIBIT 8**  
**INSTRUCTION MANUAL**

### 8.0 **Instruction Manual**

For electronic filing, a preliminary copy of the Instruction Manual is saved with filename: manual.pdf.

Please note that the required FCC Information to the User is saved with filename: FCC information.pdf.

This manual will be provided to the end-user with each unit sold/leased in the United States.

**EXHIBIT 9**  
**SECURITY CODE INFORMATION**

### 9.0 **Security code information**

The security code is randomly generated with  $2^{24}$  possible combinations during the first handset registration with base unit. Other handsets in the same system will follow the same security code.

**EXHIBIT 10**  
**CONFIDENTIALITY REQUEST**

### 10.0 **Confidentiality Request**

For electronic filing, a preliminary copy of the confidentiality request is saved with filename: request.pdf.