

## FCC Test Report

**Report No.:** RF140402E02F

**FCC ID:** HEDAC1200

**Test Model:** SF-AC1200, SF-AC1200-1, SF-AC1200-2

**Series Model:** ECWO5320, ECWO5320-L, ECWO5320-C, ECWO5324, ECWO5324-L, ECWO5324-C

**Received Date:** Apr. 08, 2014

**Test Date:** Apr. 08 to 16, 2014 and Mar. 19 to Apr. 09, 2015

**Issued Date:** Apr. 17, 2015

**Applicant:** Accton Technology Corporation

**Address:** No.1, Creation Rd. III, Science-based Industrial Park, Hsinchu, Taiwan, R.O.C.

**Issued By:** Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch  
Hsin Chu Laboratory

**Lab Address:** No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan R.O.C.

**Test Location (1):** No. 81-1, Lu Liao Keng, 9th Ling, Wu Lung Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan R.O.C.

**Test Location (2):** No. 49, Ln. 206, Wende Rd., Shangshan Tsuen, Chiung Lin Hsiang, Hsin Chu Hsien 307, Taiwan R.O.C.



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. This report should not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

## Table of Contents

|                                                            |           |
|------------------------------------------------------------|-----------|
| <b>Release Control Record</b>                              | <b>4</b>  |
| <b>1 Certificate of Conformity</b>                         | <b>5</b>  |
| <b>2 Summary of Test Results</b>                           | <b>6</b>  |
| 2.1 Measurement Uncertainty                                | 6         |
| 2.2 Modification Record                                    | 6         |
| <b>3 General Information</b>                               | <b>7</b>  |
| 3.1 General Description of EUT                             | 7         |
| 3.2 Description of Test Modes                              | 11        |
| 3.2.1 Test Mode Applicability and Tested Channel Detail    | 12        |
| 3.3 Duty Cycle of Test Signal                              | 14        |
| 3.4 Description of Support Units                           | 15        |
| 3.4.1 Configuration of System under Test                   | 16        |
| 3.5 General Description of Applied Standards               | 17        |
| <b>4 Test Types and Results</b>                            | <b>18</b> |
| 4.1 Radiated Emission and Bandedge Measurement             | 18        |
| 4.1.1 Limits of Radiated Emission and Bandedge Measurement | 18        |
| 4.1.2 Test Instruments                                     | 19        |
| 4.1.3 Test Procedures                                      | 22        |
| 4.1.4 Deviation from Test Standard                         | 22        |
| 4.1.5 Test Setup                                           | 23        |
| 4.1.6 EUT Operating Conditions                             | 24        |
| 4.1.7 Test Results (Mode 1)                                | 25        |
| 4.1.8 Test Results (Mode 2)                                | 44        |
| 4.2 Conducted Emission Measurement                         | 63        |
| 4.2.1 Limits of Conducted Emission Measurement             | 63        |
| 4.2.2 Test Instruments                                     | 63        |
| 4.2.3 Test Procedures                                      | 64        |
| 4.2.4 Deviation from Test Standard                         | 64        |
| 4.2.5 Test Setup                                           | 64        |
| 4.2.6 EUT Operating Conditions                             | 64        |
| 4.2.7 Test Results (Mode 1)                                | 65        |
| 4.2.8 Test Results (Mode 2)                                | 67        |
| 4.3 6dB Bandwidth Measurement                              | 69        |
| 4.3.1 Limits of 6dB Bandwidth Measurement                  | 69        |
| 4.3.2 Test Setup                                           | 69        |
| 4.3.3 Test Instruments                                     | 69        |
| 4.3.4 Test Procedure                                       | 69        |
| 4.3.5 Deviation from Test Standard                         | 69        |
| 4.3.6 EUT Operating Conditions                             | 69        |
| 4.3.7 Test Results (Mode 1)                                | 70        |
| 4.3.8 Test Results (Mode 2)                                | 73        |
| 4.4 Conducted Output Power Measurement                     | 76        |
| 4.4.1 Limits of Conducted Output Power Measurement         | 76        |
| 4.4.2 Test Setup                                           | 76        |
| 4.4.3 Test Instruments                                     | 76        |
| 4.4.4 Test Procedures                                      | 76        |
| 4.4.5 Deviation from Test Standard                         | 76        |
| 4.4.6 EUT Operating Conditions                             | 76        |
| 4.4.7 Test Results (Mode 1)                                | 77        |
| 4.4.8 Test Results (Mode 2)                                | 79        |
| 4.5 Power Spectral Density Measurement                     | 81        |
| 4.5.1 Limits of Power Spectral Density Measurement         | 81        |
| 4.5.2 Test Setup                                           | 81        |

|                                                                  |            |
|------------------------------------------------------------------|------------|
| 4.5.3 Test Instruments .....                                     | 81         |
| 4.5.4 Test Procedures.....                                       | 81         |
| 4.5.5 Deviation from Test Standard .....                         | 81         |
| 4.5.6 EUT Operating Conditions.....                              | 81         |
| 4.5.7 Test Results (Mode 1).....                                 | 82         |
| 4.5.8 Test Results (Mode 2).....                                 | 85         |
| 4.6 Conducted Out of Band Emission Measurement.....              | 88         |
| 4.6.1 Limits of Conducted Out of Band Emission Measurement ..... | 88         |
| 4.6.2 Test Setup.....                                            | 88         |
| 4.6.3 Test Instruments .....                                     | 88         |
| 4.6.4 Test Procedures.....                                       | 88         |
| 4.6.5 Deviation from Test Standard .....                         | 88         |
| 4.6.6 EUT Operating Conditions.....                              | 88         |
| 4.6.7 Test Results (Mode 1).....                                 | 88         |
| 4.6.8 Test Results (Mode 2).....                                 | 97         |
| <b>5 Pictures of Test Arrangements.....</b>                      | <b>106</b> |
| <b>Appendix – Information on the Testing Laboratories .....</b>  | <b>107</b> |

**Release Control Record**

| Issue No.    | Description       | Date Issued   |
|--------------|-------------------|---------------|
| RF140402E02F | Original release. | Apr. 17, 2015 |

## 1 Certificate of Conformity

**Product:** Dualband Outdoor AP, 802.11ac Outdoor Dual Band Access Point

**Brand:** IgniteNet, Edge-CorE

**Test Model:** SF-AC1200, SF-AC1200-1, SF-AC1200-2

**Series Model:** ECWO5320, ECWO5320-L, ECWO5320-C, ECWO5324, ECWO5324-L, ECWO5324-C

**Sample Status:** ENGINEERING SAMPLE

**Applicant:** Accton Technology Corporation

**Test Date:** Apr. 08 to 16, 2014 and Mar. 19 to Apr. 09, 2015

**Standards:** 47 CFR FCC Part 15, Subpart C (Section 15.247)  
ANSI C63.10:2009

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

**Prepared by :** Phoenix Huang, **Date:** Apr. 17, 2015  
Phoenix Huang / Specialist

**Approved by :** May Chen, **Date:** Apr. 17, 2015  
May Chen / Manager

## 2 Summary of Test Results

| 47 CFR FCC Part 15, Subpart C (SECTION 15.247) |                                              |        |                                                                                                                                        |
|------------------------------------------------|----------------------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------|
| FCC Clause                                     | Test Item                                    | Result | Remarks                                                                                                                                |
| 15.207                                         | AC Power Conducted Emission                  | PASS   | Meet the requirement of limit.<br>Minimum passing margin is -18.86dB at 0.15000MHz.                                                    |
| 15.205 /<br>15.209 /<br>15.247(d)              | Radiated Emissions and Band Edge Measurement | PASS   | Meet the requirement of limit.<br>Minimum passing margin is -0.1dB at 2483.5MHz, 4874.00MHz & 4924.00MHz.                              |
| 15.247(d)                                      | Antenna Port Emission                        | PASS   | Meet the requirement of limit.                                                                                                         |
| 15.247(a)(2)                                   | 6dB bandwidth                                | PASS   | Meet the requirement of limit.                                                                                                         |
| 15.247(b)                                      | Conducted power                              | PASS   | Meet the requirement of limit.                                                                                                         |
| 15.247(e)                                      | Power Spectral Density                       | PASS   | Meet the requirement of limit.                                                                                                         |
| 15.203                                         | Antenna Requirement                          | PASS   | For External Antenna connector is RP-SMA not a standard connector.<br>For Internal Antenna connector is MMCX not a standard connector. |

### 2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

| Measurement                        | Frequency      | Expanded Uncertainty (k=2) ( $\pm$ ) |
|------------------------------------|----------------|--------------------------------------|
| Conducted Emissions at mains ports | 150kHz ~ 30MHz | 2.86 dB                              |
| Radiated Emissions up to 1 GHz     | 30MHz ~ 1GHz   | 5.37 dB                              |
| Radiated Emissions above 1 GHz     | 1GHz ~ 6GHz    | 3.72 dB                              |
|                                    | 6GHz ~ 18GHz   | 4.00 dB                              |
|                                    | 18GHz ~ 40GHz  | 4.11 dB                              |

### 2.2 Modification Record

There were no modifications required for compliance.

### 3 General Information

#### 3.1 General Description of EUT

|                       |                                                                                                                                                                                                                    |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Product               | Dualband Outdoor AP, 802.11ac Outdoor Dual Band Access Point                                                                                                                                                       |
| Brand                 | IgniteNet, Edge-CorE                                                                                                                                                                                               |
| Test Model            | SF-AC1200, SF-AC1200-1, SF-AC1200-2                                                                                                                                                                                |
| Series Model:         | ECWO5320, ECWO5320-L, ECWO5320-C, ECWO5324, ECWO5324-L, ECWO5324-C                                                                                                                                                 |
| Status of EUT         | ENGINEERING SAMPLE                                                                                                                                                                                                 |
| Power Supply Rating   | DC 24V from POE                                                                                                                                                                                                    |
| Modulation Type       | CCK, DQPSK, DBPSK for DSSS<br>64QAM, 16QAM, QPSK, BPSK for OFDM<br>256QAM for OFDM in 11ac mode only                                                                                                               |
| Modulation Technology | DSSS, OFDM                                                                                                                                                                                                         |
| Transfer Rate         | 802.11b: up to 11Mbps<br>802.11a/g: up to 54Mbps<br>802.11n: up to 300Mbps<br>802.11ac: up to 866.7Mbps                                                                                                            |
| Operating Frequency   | For 15.247<br>2.412GHz ~ 2.462GHz<br>For 15.407<br>5.18GHz ~ 5.24GHz, 5.745GHz ~ 5.825GHz                                                                                                                          |
| Number of Channel     | For 15.247<br>11 for 802.11b, 802.11g, 802.11n (HT20)<br>7 for 802.11n (HT40)<br>For 15.407<br>9 for 802.11a, 802.11n (HT20), 802.11ac (VHT20)<br>4 for 802.11n (HT40), 802.11ac (VHT40)<br>2 for 802.11ac (VHT80) |
| Output Power          | Refer to Note                                                                                                                                                                                                      |
| Antenna Type          | Refer to Note                                                                                                                                                                                                      |
| Antenna Connector     | Refer to Note                                                                                                                                                                                                      |
| Accessory Device      | PoE × 1                                                                                                                                                                                                            |
| Data Cable Supplied   | NA                                                                                                                                                                                                                 |

Note:

1. The EUT is a 2.4GHz & 5GHz WLAN device.
2. 2.4GHz & 5GHz technology can transmit at same time.

3. The maximum output power (mW) table as below table:

| 15.247 (2.4GHz)  |                  |         |                  |         |
|------------------|------------------|---------|------------------|---------|
| Modulation Mode  | External antenna |         | Internal antenna |         |
|                  | 1Tx              | 2Tx     | 1Tx              | 2Tx     |
| 802.11b          | 137.404          | -       | 209.894          | -       |
| 802.11g          | 146.893          | -       | 142.889          | -       |
| 802.11n (HT20)   | 148.594          | 222.389 | 143.880          | 120.881 |
| 802.11n (HT40)   | 102.802          | 260.942 | 53.088           | 102.505 |
| 15.407 (5GHz)    |                  |         |                  |         |
| Modulation Mode  | External antenna |         | Internal antenna |         |
|                  | 1Tx              | 2Tx     | 1Tx              | 2Tx     |
| 802.11a          | 265.461          | -       | 137.721          | -       |
| 802.11ac (VHT20) | 240.436          | 283.351 | 142.561          | 130.78  |
| 802.11ac (VHT40) | 209.411          | 265.659 | 83.56            | 105.454 |
| 802.11ac (VHT80) | 87.297           | 77.763  | 15.311           | 24.755  |

4. The EUT has below model names, which are identical to each other in all aspects except for the followings:

| Product Name                            | Brand Name | Model Name  | Different                                                                              |
|-----------------------------------------|------------|-------------|----------------------------------------------------------------------------------------|
| Dualband Outdoor AP                     | IgniteNet  | SF-AC1200   | 1. External antenna 1 (2.4GHz) + Internal antenna 1 (5GHz)<br>2. Without mini USB port |
|                                         | IgniteNet  | SF-AC1200-1 | 1. External antenna 1 (2.4GHz) + External antenna 2 (5GHz)<br>2. Without mini USB port |
|                                         | IgniteNet  | SF-AC1200-2 | 1. Internal antenna 2 (2.4GHz) + Internal antenna 2 (5GHz)<br>2. Without mini USB port |
| 802.11ac Outdoor Dual Band Access Point | Edge-corE  | ECWO5320    | 1. External antenna 1 (2.4GHz) + Internal antenna 3 (5GHz)<br>2. With mini USB port    |
|                                         | Edge-corE  | ECWO5320-L  | 1. External antenna 1 (2.4GHz) + Internal antenna 3 (5GHz)<br>2. With mini USB port    |
|                                         | Edge-corE  | ECWO5320-C  | 1. External antenna 1 (2.4GHz) + Internal antenna 3 (5GHz)<br>2. With mini USB port    |
|                                         | Edge-corE  | ECWO5324    | 1. External antenna 1 (2.4GHz) + External antenna 2 (5GHz)<br>2. With mini USB port    |
|                                         | Edge-corE  | ECWO5324-L  | 1. External antenna 1 (2.4GHz) + External antenna 2 (5GHz)<br>2. With mini USB port    |
|                                         | Edge-corE  | ECWO5324-C  | 1. External antenna 1 (2.4GHz) + External antenna 2 (5GHz)<br>2. With mini USB port    |

Note:

- 2.4GHz band: from the above models, models: **SF-AC1200**, **SF-AC1200-2** were selected as representative model for the test and its data was recorded in this report.
- 5GHz band: from the above models, models: **SF-AC1200-1**, **SF-AC1200-2** were selected as representative model for the test and its data was recorded in this report.



5. The EUT must be supplied with a POE as following table:

| Brand | Model No.       | Spec.                                                                           |
|-------|-----------------|---------------------------------------------------------------------------------|
| LEI   | NU24-F240100-I2 | AC Input: 100-240V, 0.7A, 50/60Hz<br>AC Input cable: 0.8m<br>DC Output: 24V, 1A |

6. The antennas provided to the EUT, please refer to the following table:

#### External antenna 1 (Signal Band Ant.)

Brand Name: Cortec / Model Name: AN2400-0334RS

| Transmitter Circuit | Antenna Type | Connector Type | Antenna Gain(dBi)<br><excluding cable loss> | Inside EUT      |                   | Outside EUT     |                   | Net. Gain (dBi) | Frequency range (MHz to MHz) |
|---------------------|--------------|----------------|---------------------------------------------|-----------------|-------------------|-----------------|-------------------|-----------------|------------------------------|
|                     |              |                |                                             | Cable Loss (dB) | Cable Length (mm) | Cable Loss (dB) | Cable Length (mm) |                 |                              |
| Chain (0)           | Dipole       | RP-SMA         | 2.65                                        | 1               | 250               | 1.5             | 500               | 0.15            | 2400~2500                    |
| Chain (1)           | Dipole       | RP-SMA         | 2.65                                        | 1               | 250               | 1.5             | 500               | 0.15            | 2400~2500                    |

#### External antenna 2 (Signal Band Ant.)

Brand Name: Cortec / Model Name: AN5000-0301RS

| Transmitter Circuit | Antenna Type | Connector Type | Antenna Gain(dBi)<br><excluding cable loss> | Inside EUT      |                   | Outside EUT     |                   | Net. Gain (dBi) | Frequency range (MHz to MHz) |
|---------------------|--------------|----------------|---------------------------------------------|-----------------|-------------------|-----------------|-------------------|-----------------|------------------------------|
|                     |              |                |                                             | Cable Loss (dB) | Cable Length (mm) | Cable Loss (dB) | Cable Length (mm) |                 |                              |
| Chain (0)           | Dipole       | RP-SMA         | 2.7                                         | 1.2             | 250               | 2.9             | 500               | -1.4            | 5150~5850                    |
| Chain (1)           | Dipole       | RP-SMA         | 2.7                                         | 1.2             | 250               | 2.9             | 500               | -1.4            | 5150~5850                    |

#### Internal antenna 1 (Signal Band Ant.)

Brand Name: Accton / Model Name: 123800000297A

| Transmitter Circuit | Antenna Type | Connector Type | Antenna Gain(dBi) | Frequency range (MHz to MHz) |
|---------------------|--------------|----------------|-------------------|------------------------------|
| Chain (0)           | Patch Array  | MMCX           | 13.81             | 5150~5850                    |
| Chain (1)           | Patch Array  | MMCX           | 13.72             | 5150~5850                    |

#### Internal antenna 2 (Dual Band Ant.)

Brand Name: Accton / Model Name: 123800000295A

| Transmitter Circuit | Antenna Type | Connector Type | Antenna Gain(dBi) | Frequency range (MHz to MHz) |
|---------------------|--------------|----------------|-------------------|------------------------------|
| Chain (0)           | Dipole       | MMCX           | 3.03              | 2400~2500                    |
|                     | Patch Array  |                | 11.94             | 5150~5850                    |
| Chain (1)           | Dipole       | MMCX           | 5.58              | 2400~2500                    |
|                     | Patch Array  |                | 12.19             | 5150~5850                    |

#### Internal antenna 3 (Signal Band Ant.)

Brand Name: Accton / Model Name: OAP1232RL-FLF-EC

| Transmitter Circuit | Antenna Type | Connector Type | Antenna Gain(dBi) | Frequency range (MHz to MHz) |
|---------------------|--------------|----------------|-------------------|------------------------------|
| Chain (0)           | Patch Array  | MMCX           | 12.5              | 5150~5850                    |
| Chain (1)           | Patch Array  | MMCX           | 12.5              | 5150~5850                    |

Note:

- For 802.11a/b/g mode will fix transmission on Chain (0)
- From the above Internal antennas, **Internal antenna 2** max gain was selected as representative antenna for the 2.4GHz test and **Internal antenna 1** max gain was selected as representative antenna for the 5GHz test, its data was recorded in this report.

7. The EUT incorporates a MIMO function.

| 2.4GHz Band      |                 |                       |     |
|------------------|-----------------|-----------------------|-----|
| MODULATION MODE  | DATA RATE (MCS) | TX & RX CONFIGURATION |     |
| 802.11b          | 1 ~ 11Mbps      | 1TX (fix Chain 0)     | 2RX |
| 802.11g          | 6 ~ 54Mbps      | 1TX (fix Chain 0)     | 2RX |
| 802.11n (HT20)   | MCS 0~7         | 1TX (fix Chain 0)     | 2RX |
|                  | MCS 8~15*       | 2TX                   | 2RX |
| 802.11n (HT40)   | MCS 0~7         | 1TX (fix Chain 0)     | 2RX |
|                  | MCS 8~15*       | 2TX                   | 2RX |
| 5GHz Band        |                 |                       |     |
| MODULATION MODE  | DATA RATE (MCS) | TX & RX CONFIGURATION |     |
| 802.11a          | 6 ~ 54Mbps      | 1TX (fix Chain 0)     | 2RX |
| 802.11n (HT20)   | MCS 0~7         | 1TX (fix Chain 0)     | 2RX |
|                  | MCS 8~15*       | 2TX                   | 2RX |
| 802.11n (HT40)   | MCS 0~7         | 1TX (fix Chain 0)     | 2RX |
|                  | MCS 8~15*       | 2TX                   | 2RX |
| 802.11ac (VHT20) | MCS0~8 Nss= 1   | 1TX (fix Chain 0)     | 2RX |
|                  | MCS0~8 Nss= 2*  | 2TX                   | 2RX |
| 802.11ac (VHT40) | MCS0~9 Nss= 1   | 1TX (fix Chain 0)     | 2RX |
|                  | MCS0~9 Nss= 2*  | 2TX                   | 2RX |
| 802.11ac (VHT80) | MCS0~9 Nss= 1   | 1TX (fix Chain 0)     | 2RX |
|                  | MCS0~9 Nss= 2*  | 2TX                   | 2RX |

Remark: “\*” means the device operate with two spatial stream (Nss = 2) with different data, and two signals are not correlated.

Note: The modulation and bandwidth are similar for 802.11n mode for 20MHz (40MHz) and 802.11ac mode for 20MHz (40MHz), therefore investigated worst case to representative mode in test report. (Final test mode refer section 3.2.1)

8. The emission of the simultaneous operation (2.4GHz & 5GHz) has been evaluated and no non-compliance was found.
9. The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.

### 3.2 Description of Test Modes

11 channels are provided for 802.11b, 802.11g and 802.11n (HT20):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 1       | 2412MHz   | 7       | 2442MHz   |
| 2       | 2417MHz   | 8       | 2447MHz   |
| 3       | 2422MHz   | 9       | 2452MHz   |
| 4       | 2427MHz   | 10      | 2457MHz   |
| 5       | 2432MHz   | 11      | 2462MHz   |
| 6       | 2437MHz   |         |           |

7 channels are provided for 802.11n (HT40):

| Channel | Frequency | Channel | Frequency |
|---------|-----------|---------|-----------|
| 3       | 2422MHz   | 7       | 2442MHz   |
| 4       | 2427MHz   | 8       | 2447MHz   |
| 5       | 2432MHz   | 9       | 2452MHz   |
| 6       | 2437MHz   |         |           |

### 3.2.1 Test Mode Applicability and Tested Channel Detail

| EUT CONFIGURE MODE | APPLICABLE TO |       |     |      | DESCRIPTION           |
|--------------------|---------------|-------|-----|------|-----------------------|
|                    | RE $\geq$ 1G  | RE<1G | PLC | APCM |                       |
| 1                  | √             | √     | √   | √    | With External Antenna |
| 2                  | √             | √     | √   | √    | With Internal Antenna |

Where **RE $\geq$ 1G**: Radiated Emission above 1GHz & Bandedge Measurement  
**RE<1G**: Radiated Emission below 1GHz  
**PLC**: Power Line Conducted Emission  
**APCM**: Antenna Port Conducted Measurement

#### Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| 1TX Mode           |                |                   |                |                       |                 |                  |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
| 1, 2               | 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1                |
|                    | 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6                |
|                    | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              |
|                    | 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             |
| 2TX Mode           |                |                   |                |                       |                 |                  |
| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
| 1, 2               | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 13               |
|                    | 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 27               |

#### Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| 2TX Mode           |                |                   |                |                       |                 |                  |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
| 1                  | 802.11n (HT40) | 3 to 9            | 6              | OFDM                  | BPSK            | 27               |
| 2                  | 802.11n (HT20) | 1 to 11           | 6              | OFDM                  | BPSK            | 13               |

### Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

| 2TX Mode           |                |                   |                |                       |                 |                  |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
| 1                  | 802.11n (HT40) | 3 to 9            | 6              | OFDM                  | BPSK            | 27               |
| 2                  | 802.11n (HT20) | 1 to 11           | 6              | OFDM                  | BPSK            | 13               |

### Antenna Port Conducted Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.


| 1TX Mode           |                |                   |                |                       |                 |                  |
|--------------------|----------------|-------------------|----------------|-----------------------|-----------------|------------------|
| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
| 1, 2               | 802.11b        | 1 to 11           | 1, 6, 11       | DSSS                  | DBPSK           | 1                |
|                    | 802.11g        | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6                |
|                    | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 6.5              |
|                    | 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 13.5             |
| 2TX Mode           |                |                   |                |                       |                 |                  |
| EUT CONFIGURE MODE | MODE           | AVAILABLE CHANNEL | TESTED CHANNEL | MODULATION TECHNOLOGY | MODULATION TYPE | DATA RATE (Mbps) |
| 1, 2               | 802.11n (HT20) | 1 to 11           | 1, 6, 11       | OFDM                  | BPSK            | 13               |
|                    | 802.11n (HT40) | 3 to 9            | 3, 6, 9        | OFDM                  | BPSK            | 27               |

### Test Condition:

| APPLICABLE TO | ENVIRONMENTAL CONDITIONS | INPUT POWER (SYSTEM) | TESTED BY     |
|---------------|--------------------------|----------------------|---------------|
| RE≥1G         | 24deg. C, 73%RH          | 120Vac, 60Hz         | Andy Ho       |
|               | 23deg. C, 66%RH          | 120Vac, 60Hz         | Andy Ho       |
|               | 24deg. C, 73%RH          | 120Vac, 60Hz         | Tim Ho        |
|               | 23deg. C, 66%RH          | 120Vac, 60Hz         | Tim Ho        |
|               | 23deg. C, 66%RH          | 120Vac, 60Hz         | Nelson Teng   |
|               | 24deg. C, 71%RH          | 120Vac, 60Hz         | Weiwei Lo     |
| RE<1G         | 23deg. C, 68%RH          | 120Vac, 60Hz         | Robert Cheng  |
| PLC           | 28deg. C, 72%RH          | 120Vac, 60Hz         | Wythe Lin     |
| APCM          | 25deg. C, 60%RH          | 120Vac, 60Hz         | Robert Cheng  |
|               | 25deg. C, 60%RH          | 120Vac, 60Hz         | Anderson Chen |

### 3.3 Duty Cycle of Test Signal

Duty cycle of test signal is 100 %, duty factor is not required.



### 3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.


| ID | Product           | Brand | Model No. | Serial No. | FCC ID  | Remarks         |
|----|-------------------|-------|-----------|------------|---------|-----------------|
| A. | NOTEBOOK COMPUTER | DELL  | PP32LA    | DSL32S     | FCC DoC | Provided by Lab |
| B. | NOTEBOOK COMPUTER | DELL  | E5440     | 6FC7F12    | FCC DoC | Provided by Lab |

Note:

1. All power cords of the above support units are non-shielded (1.8m).

| ID | Descriptions | Qty. | Length (m) | Shielding (Yes/No) | Cores (Qty.) | Remarks            |
|----|--------------|------|------------|--------------------|--------------|--------------------|
| 1. | RJ45         | 1    | 10         | No                 | 0            | Provided by Lab    |
| 2. | RJ45         | 1    | 1.5        | No                 | 0            | Provided by Lab    |
| 3. | AC           | 1    | 0.8        | No                 | 0            | Supplied by Client |
| 4. | Earth Line   | 1    | 1.5        | No                 | 0            | Provided by Lab    |

### 3.4.1 Configuration of System under Test





### 3.5 General Description of Applied Standards

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC Part 15, Subpart C (15.247)**

**558074 D01 DTS Meas Guidance v03r02**

**662911 D01 Multiple Transmitter Output v02r01**

**ANSI C63.10-2009**

All test items have been performed and recorded as per the above standards.

**Note:** The EUT has been verified to comply with the requirements of FCC Part 15, Subpart B, Class B (DoC).  
The test report has been issued separately.

## 4 Test Types and Results

### 4.1 Radiated Emission and Bandedge Measurement

#### 4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 30dB below the highest level of the desired power:

| Frequencies (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-------------------|-----------------------------------|-------------------------------|
| 0.009 ~ 0.490     | 2400/F(kHz)                       | 300                           |
| 0.490 ~ 1.705     | 24000/F(kHz)                      | 30                            |
| 1.705 ~ 30.0      | 30                                | 30                            |
| 30 ~ 88           | 100                               | 3                             |
| 88 ~ 216          | 150                               | 3                             |
| 216 ~ 960         | 200                               | 3                             |
| Above 960         | 500                               | 3                             |

#### NOTE:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

#### 4.1.2 Test Instruments

##### For Above 1GHz test – Mode 1

| DESCRIPTION & MANUFACTURER              | MODEL NO.                | SERIAL NO.                          | CALIBRATED DATE | CALIBRATED UNTIL |
|-----------------------------------------|--------------------------|-------------------------------------|-----------------|------------------|
| MXE EMI Receiver<br>Agilent             | N9038A                   | MY50010156                          | Jan. 15, 2014   | Jan. 14, 2015    |
| Pre-Amplifier<br>Mini-Circuits          | ZFL-1000VH2<br>B         | AMP-ZFL-04                          | Nov. 13, 2013   | Nov. 12, 2014    |
| Trilog Broadband Antenna<br>SCHWARZBECK | VULB 9168                | 9168-361                            | Feb. 27, 2014   | Feb. 26, 2015    |
| RF Cable                                | NA                       | CHHCAB_001                          | Oct. 06, 2013   | Oct. 05, 2014    |
| Spectrum Analyzer<br>R&S                | FSV40                    | 100964                              | July 15, 2013   | July 14, 2014    |
| Horn_Antenna<br>AISI                    | AIH.8018                 | 0000220091110                       | Dec. 06, 2013   | Dec. 05, 2014    |
| Pre-Amplifier<br>Agilent                | 8449B                    | 3008A01923                          | Oct. 29, 2013   | Oct. 28, 2014    |
| RF Cable                                | NA                       | RF104-205<br>RF104-207<br>RF104-202 | Dec. 12, 2013   | Dec. 11, 2014    |
| Spectrum Analyzer<br>Agilent            | E4446A                   | MY48250253                          | Aug. 28, 2013   | Aug. 27, 2014    |
| Pre-Amplifier<br>SPACEK LABS            | SLKKa-48-6               | 9K16                                | Nov. 13, 2013   | Nov. 12, 2014    |
| Horn_Antenna<br>SCHWARZBECK             | BBHA 9170                | 9170-424                            | Oct. 08, 2013   | Oct. 07, 2014    |
| Software                                | ADT_Radiated<br>_V8.7.07 | NA                                  | NA              | NA               |
| Antenna Tower & Turn Table<br>CT        | NA                       | NA                                  | NA              | NA               |
| Spectrum Analyzer<br>R&S                | FSV 40                   | 100964                              | July 15, 2013   | July 14, 2014    |
| Power meter<br>Anritsu                  | ML2495A                  | 1014008                             | Apr. 23, 2013   | Apr. 22, 2014    |
| Power sensor<br>Anritsu                 | MA2411B                  | 0917122                             | Apr. 23, 2013   | Apr. 22, 2014    |

##### Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3 The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
- 5 The CANADA Site Registration No. is IC 7450H-3.
- 6 Tested Date: Apr. 08 to 16, 2014

**For Above 1GHz test – Mode 2**

| DESCRIPTION & MANUFACTURER              | MODEL NO.                | SERIAL NO.                                | CALIBRATED DATE | CALIBRATED UNTIL |
|-----------------------------------------|--------------------------|-------------------------------------------|-----------------|------------------|
| MXE EMI Receiver<br>Agilent             | N9038A                   | MY50010156                                | Aug. 11, 2014   | Aug. 10, 2015    |
| Pre-Amplifier<br>Mini-Circuits          | ZFL-1000VH2<br>B         | AMP-ZFL-04                                | Nov. 12, 2014   | Nov. 11, 2015    |
| Trilog Broadband Antenna<br>SCHWARZBECK | VULB 9168                | 9168-361                                  | Feb. 06, 2015   | Feb. 05, 2016    |
| RF Cable                                | NA                       | CHHCAB_001                                | Oct. 05, 2014   | Oct. 04, 2015    |
| Horn_Antenna<br>AISI                    | AIH.8018                 | 0000220091110                             | Aug. 26, 2014   | Aug. 25, 2015    |
| Pre-Amplifier<br>Agilent                | 8449B                    | 300801923                                 | Oct. 28, 2014   | Oct. 27, 2015    |
| RF Cable                                | NA                       | 131206<br>131213<br>131215<br>SNMY23685/4 | Jan. 16, 2015   | Jan. 15, 2016    |
| Spectrum Analyzer<br>R&S                | FSV40                    | 100964                                    | July 05, 2014   | July 04, 2015    |
| Pre-Amplifier<br>SPACEK LABS            | SLKKa-48-6               | 9K16                                      | Dec. 12, 2014   | Dec. 11, 2015    |
| Horn_Antenna<br>SCHWARZBECK             | BBHA 9170                | 9170-424                                  | Aug. 26, 2014   | Aug. 25, 2015    |
| RF Cable                                | NA                       | 329751/4<br>RF104-204                     | Dec. 11, 2014   | Dec. 10, 2015    |
| Software                                | ADT_Radiated<br>_V8.7.07 | NA                                        | NA              | NA               |
| Antenna Tower & Turn Table<br>CT        | NA                       | NA                                        | NA              | NA               |
| SPECTRUM ANALYZER<br>R&S                | FSP 40                   | 100060                                    | May 08, 2014    | May 07, 2015     |
| Power Meter<br>Anritsu                  | ML2495A                  | 1014008                                   | Apr. 30, 2014   | Apr. 29, 2015    |
| Power Sensor<br>Anritsu                 | MA2411B                  | 0917122                                   | Apr. 30, 2014   | Apr. 29, 2015    |

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
3. The test was performed in 966 Chamber No. H.
4. The FCC Site Registration No. is 797305.
5. The CANADA Site Registration No. is IC 7450H-3.
6. Tested Date: Apr. 08 to 09, 2015

**For Below 1GHz test – Mode 1 & 2**

| DESCRIPTION & MANUFACTURER              | MODEL NO.        | SERIAL NO.                      | CALIBRATED DATE | CALIBRATED UNTIL |
|-----------------------------------------|------------------|---------------------------------|-----------------|------------------|
| MXE EMI Receiver<br>Agilent             | N9038A           | MY51210105                      | July 21, 2014   | July 20, 2015    |
| Pre-Amplifier<br>Mini-Circuits          | ZFL-1000VH2<br>B | AMP-ZFL-03                      | Nov. 12, 2014   | Nov. 11, 2015    |
| Trilog Broadband Antenna<br>SCHWARZBECK | VULB 9168        | 9168-360                        | Feb. 06, 2015   | Feb. 05, 2016    |
| RF Cable                                | NA               | CHGCAB_001                      | Oct. 04, 2014   | Oct. 03, 2015    |
| Horn_Antenna<br>AISI                    | AIH.8018         | 0000320091110                   | Aug. 27, 2014   | Aug. 26, 2015    |
| Pre-Amplifier<br>Agilent                | 8449B            | 3008A02578                      | June 24, 2014   | June 23, 2015    |
| RF Cable                                | NA               | 131205<br>131214<br>SNMY23684/4 | Jan. 16, 2015   | Jan. 15, 2016    |
| Spectrum Analyzer<br>R&S                | FSV40            | 100964                          | July 05, 2014   | July 04, 2015    |
| Pre-Amplifier<br>EMCI                   | EMC184045        | 980143                          | Jan. 16, 2015   | Jan. 15, 2016    |
| Horn_Antenna<br>SCHWARZBECK             | BBHA 9170        | 9170-424                        | Aug. 26, 2014   | Aug. 25, 2015    |
| RF Cable                                | NA               | RF104-121<br>RF104-204          | Dec. 11, 2014   | Dec. 10, 2015    |
| Antenna Tower & Turn Table<br>CT        | NA               | NA                              | NA              | NA               |

**Note:**

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The horn antenna, preamplifier (model: 8449B) are used only for the measurement of emission frequency above 1GHz if tested.
- 3 The test was performed in 966 Chamber No. G.
4. The FCC Site Registration No. is 966073.
- 5 The VCCI Site Registration No. is G-137.
- 6 The CANADA Site Registration No. is IC 7450H-2.
- 7 Tested Date: Mar. 19, 2015

#### 4.1.3 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

**Note:**


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 3MHz for RMS Average (Duty cycle < 98%) for Average detection (AV) at frequency above 1GHz, then the measurement results was added to a correction factor ( $10 \log(1/\text{duty cycle})$ ).
4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz (Duty cycle  $\geq 98\%$ ) for Average detection (AV) at frequency above 1GHz.
5. All modes of operation were investigated and the worst-case emissions are reported.

#### 4.1.4 Deviation from Test Standard


No deviation.

#### 4.1.5 Test Setup

<Frequency Range below 1GHz>



<Frequency Range above 1GHz>



For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.1.6 EUT Operating Conditions

1. Connect the EUT with the support unit A (Notebook computer) which is placed in remote site.
2. The communication partner run test program "MP\_TEST.exe" to enable EUT under transmission/receiving condition continuously at specific channel frequency.



#### 4.1.7 Test Results (Mode 1)

##### 1TX Mode

##### Above 1GHz Data

##### 802.11b

|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 1 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 50.0 PK                 | 74.0           | -24.0       | 1.13 H             | 146                  | 55.60            | -5.60                    |
| 2                                                   | 2390.00     | 37.8 AV                 | 54.0           | -16.2       | 1.13 H             | 146                  | 43.40            | -5.60                    |
| 3                                                   | *2412.00    | 104.1 PK                |                |             | 1.13 H             | 146                  | 109.60           | -5.50                    |
| 4                                                   | *2412.00    | 100.9 AV                |                |             | 1.13 H             | 146                  | 106.40           | -5.50                    |
| 5                                                   | 4824.00     | 50.2 PK                 | 74.0           | -23.8       | 1.00 H             | 95                   | 46.40            | 3.80                     |
| 6                                                   | 4824.00     | 46.9 AV                 | 54.0           | -7.1        | 1.00 H             | 95                   | 43.10            | 3.80                     |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 54.5 PK                 | 74.0           | -19.5       | 1.54 V             | 42                   | 60.10            | -5.60                    |
| 2                                                   | 2390.00     | 43.0 AV                 | 54.0           | -11.0       | 1.54 V             | 42                   | 48.60            | -5.60                    |
| 3                                                   | *2412.00    | 108.5 PK                |                |             | 1.54 V             | 42                   | 114.00           | -5.50                    |
| 4                                                   | *2412.00    | 106.0 AV                |                |             | 1.54 V             | 42                   | 111.50           | -5.50                    |
| 5                                                   | 4824.00     | 55.8 PK                 | 74.0           | -18.2       | 1.38 V             | 141                  | 52.00            | 3.80                     |
| 6                                                   | 4824.00     | 53.8 AV                 | 54.0           | -0.2        | 1.38 V             | 141                  | 50.00            | 3.80                     |

##### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2384.00        | 50.3 PK                       | 74.0              | -23.7          | 1.36 H                   | 152                        | 55.90                  | -5.60                          |
| 2                                                   | 2384.00        | 38.0 AV                       | 54.0              | -16.0          | 1.36 H                   | 152                        | 43.60                  | -5.60                          |
| 3                                                   | *2437.00       | 105.7 PK                      |                   |                | 1.36 H                   | 152                        | 111.10                 | -5.40                          |
| 4                                                   | *2437.00       | 102.4 AV                      |                   |                | 1.36 H                   | 152                        | 107.80                 | -5.40                          |
| 5                                                   | 2483.50        | 51.2 PK                       | 74.0              | -22.8          | 1.36 H                   | 152                        | 56.30                  | -5.10                          |
| 6                                                   | 2483.50        | 38.9 AV                       | 54.0              | -15.1          | 1.36 H                   | 152                        | 44.00                  | -5.10                          |
| 7                                                   | 4874.00        | 51.3 PK                       | 74.0              | -22.7          | 1.29 H                   | 235                        | 47.50                  | 3.80                           |
| 8                                                   | 4874.00        | 47.9 AV                       | 54.0              | -6.1           | 1.29 H                   | 235                        | 44.10                  | 3.80                           |
| 9                                                   | 7311.00        | 53.6 PK                       | 74.0              | -20.4          | 1.00 H                   | 274                        | 45.30                  | 8.30                           |
| 10                                                  | 7311.00        | 41.8 AV                       | 54.0              | -12.2          | 1.00 H                   | 274                        | 33.50                  | 8.30                           |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | 2384.00        | 53.3 PK                       | 74.0              | -20.7          | 1.21 V                   | 42                         | 58.90                  | -5.60                          |
| 2                                                 | 2384.00        | 40.1 AV                       | 54.0              | -13.9          | 1.21 V                   | 42                         | 45.70                  | -5.60                          |
| 3                                                 | *2437.00       | 111.5 PK                      |                   |                | 1.21 V                   | 42                         | 116.90                 | -5.40                          |
| 4                                                 | *2437.00       | 107.7 AV                      |                   |                | 1.21 V                   | 42                         | 113.10                 | -5.40                          |
| 5                                                 | 2483.50        | 53.2 PK                       | 74.0              | -20.8          | 1.21 V                   | 42                         | 58.30                  | -5.10                          |
| 6                                                 | 2483.50        | 41.1 AV                       | 54.0              | -12.9          | 1.21 V                   | 42                         | 46.20                  | -5.10                          |
| 7                                                 | 4874.00        | 55.5 PK                       | 74.0              | -18.5          | 1.82 V                   | 174                        | 51.70                  | 3.80                           |
| 8                                                 | 4874.00        | 53.9 AV                       | 54.0              | -0.1           | 1.82 V                   | 174                        | 50.10                  | 3.80                           |
| 9                                                 | 7311.00        | 53.9 PK                       | 74.0              | -20.1          | 1.00 V                   | 152                        | 45.60                  | 8.30                           |
| 10                                                | 7311.00        | 41.7 AV                       | 54.0              | -12.3          | 1.00 V                   | 152                        | 33.40                  | 8.30                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 105.4 PK                      |                   |                | 1.41 H                   | 147                        | 110.80                 | -5.40                          |
| 2                                                   | *2462.00       | 102.6 AV                      |                   |                | 1.41 H                   | 147                        | 108.00                 | -5.40                          |
| 3                                                   | 2483.50        | 51.6 PK                       | 74.0              | -22.4          | 1.41 H                   | 147                        | 56.70                  | -5.10                          |
| 4                                                   | 2483.50        | 39.4 AV                       | 54.0              | -14.6          | 1.41 H                   | 147                        | 44.50                  | -5.10                          |
| 5                                                   | 4924.00        | 51.7 PK                       | 74.0              | -22.3          | 1.30 H                   | 231                        | 47.90                  | 3.80                           |
| 6                                                   | 4924.00        | 48.1 AV                       | 54.0              | -5.9           | 1.30 H                   | 231                        | 44.30                  | 3.80                           |
| 7                                                   | 7386.00        | 53.5 PK                       | 74.0              | -20.5          | 1.00 H                   | 283                        | 44.90                  | 8.60                           |
| 8                                                   | 7386.00        | 41.4 AV                       | 54.0              | -12.6          | 1.00 H                   | 283                        | 32.80                  | 8.60                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 110.3 PK                      |                   |                | 1.22 V                   | 42                         | 115.70                 | -5.40                          |
| 2                                                   | *2462.00       | 107.8 AV                      |                   |                | 1.22 V                   | 42                         | 113.20                 | -5.40                          |
| 3                                                   | 2483.50        | 56.8 PK                       | 74.0              | -17.2          | 1.22 V                   | 42                         | 61.90                  | -5.10                          |
| 4                                                   | 2483.50        | 44.7 AV                       | 54.0              | -9.3           | 1.22 V                   | 42                         | 49.80                  | -5.10                          |
| 5                                                   | 4924.00        | 55.9 PK                       | 74.0              | -18.1          | 1.11 V                   | 144                        | 52.10                  | 3.80                           |
| 6                                                   | 4924.00        | 53.9 AV                       | 54.0              | -0.1           | 1.11 V                   | 144                        | 50.10                  | 3.80                           |
| 7                                                   | 7386.00        | 53.7 PK                       | 74.0              | -20.3          | 1.00 V                   | 205                        | 45.10                  | 8.60                           |
| 8                                                   | 7386.00        | 41.5 AV                       | 54.0              | -12.5          | 1.00 V                   | 205                        | 32.90                  | 8.60                           |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

# 802.11g

|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 1 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 62.0 PK                 | 74.0           | -12.0       | 1.02 H             | 336                  | 67.60            | -5.60                    |
| 2                                                   | 2390.00     | 46.9 AV                 | 54.0           | -7.1        | 1.02 H             | 336                  | 52.50            | -5.60                    |
| 3                                                   | *2412.00    | 104.6 PK                |                |             | 1.02 H             | 336                  | 110.10           | -5.50                    |
| 4                                                   | *2412.00    | 95.2 AV                 |                |             | 1.02 H             | 336                  | 100.70           | -5.50                    |
| 5                                                   | 4824.00     | 49.3 PK                 | 74.0           | -24.7       | 1.30 H             | 27                   | 45.50            | 3.80                     |
| 6                                                   | 4824.00     | 37.9 AV                 | 54.0           | -16.1       | 1.30 H             | 27                   | 34.10            | 3.80                     |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 70.6 PK                 | 74.0           | -3.4        | 1.24 V             | 40                   | 76.20            | -5.60                    |
| 2                                                   | 2390.00     | 53.5 AV                 | 54.0           | -0.5        | 1.24 V             | 40                   | 59.10            | -5.60                    |
| 3                                                   | *2412.00    | 110.0 PK                |                |             | 1.24 V             | 40                   | 115.50           | -5.50                    |
| 4                                                   | *2412.00    | 100.6 AV                |                |             | 1.24 V             | 40                   | 106.10           | -5.50                    |
| 5                                                   | 4824.00     | 61.4 PK                 | 74.0           | -12.6       | 1.33 V             | 132                  | 57.60            | 3.80                     |
| 6                                                   | 4824.00     | 47.5 AV                 | 54.0           | -6.5        | 1.33 V             | 132                  | 43.70            | 3.80                     |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 46.2 PK                       | 74.0              | -27.8          | 1.02 H                   | 333                        | 51.80                  | -5.60                          |
| 2                                                   | 2390.00        | 34.5 AV                       | 54.0              | -19.5          | 1.02 H                   | 333                        | 40.10                  | -5.60                          |
| 3                                                   | *2437.00       | 106.7 PK                      |                   |                | 1.02 H                   | 333                        | 112.10                 | -5.40                          |
| 4                                                   | *2437.00       | 97.2 AV                       |                   |                | 1.02 H                   | 333                        | 102.60                 | -5.40                          |
| 5                                                   | 2483.50        | 50.0 PK                       | 74.0              | -24.0          | 1.02 H                   | 333                        | 55.10                  | -5.10                          |
| 6                                                   | 2483.50        | 37.5 AV                       | 54.0              | -16.5          | 1.02 H                   | 333                        | 42.60                  | -5.10                          |
| 7                                                   | 4874.00        | 49.3 PK                       | 74.0              | -24.7          | 1.33 H                   | 16                         | 45.50                  | 3.80                           |
| 8                                                   | 4874.00        | 37.7 AV                       | 54.0              | -16.3          | 1.33 H                   | 16                         | 33.90                  | 3.80                           |
| 9                                                   | 7311.00        | 52.1 PK                       | 74.0              | -21.9          | 1.00 H                   | 162                        | 43.80                  | 8.30                           |
| 10                                                  | 7311.00        | 39.0 AV                       | 54.0              | -15.0          | 1.00 H                   | 162                        | 30.70                  | 8.30                           |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | 2390.00        | 53.5 PK                       | 74.0              | -20.5          | 1.24 V                   | 42                         | 59.10                  | -5.60                          |
| 2                                                 | 2390.00        | 40.1 AV                       | 54.0              | -13.9          | 1.24 V                   | 42                         | 45.70                  | -5.60                          |
| 3                                                 | *2437.00       | 111.8 PK                      |                   |                | 1.24 V                   | 42                         | 117.20                 | -5.40                          |
| 4                                                 | *2437.00       | 102.5 AV                      |                   |                | 1.24 V                   | 42                         | 107.90                 | -5.40                          |
| 5                                                 | 2483.50        | 55.6 PK                       | 74.0              | -18.4          | 1.24 V                   | 42                         | 60.70                  | -5.10                          |
| 6                                                 | 2483.50        | 42.5 AV                       | 54.0              | -11.5          | 1.24 V                   | 42                         | 47.60                  | -5.10                          |
| 7                                                 | 4874.00        | 61.2 PK                       | 74.0              | -12.8          | 1.37 V                   | 143                        | 57.40                  | 3.80                           |
| 8                                                 | 4874.00        | 47.4 AV                       | 54.0              | -6.6           | 1.37 V                   | 143                        | 43.60                  | 3.80                           |
| 9                                                 | 7311.00        | 54.0 PK                       | 74.0              | -20.0          | 1.00 V                   | 218                        | 45.70                  | 8.30                           |
| 10                                                | 7311.00        | 41.9 AV                       | 54.0              | -12.1          | 1.00 V                   | 218                        | 33.60                  | 8.30                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 105.4 PK                      |                   |                | 1.25 H                   | 336                        | 110.80                 | -5.40                          |
| 2                                                   | *2462.00       | 96.4 AV                       |                   |                | 1.25 H                   | 336                        | 101.80                 | -5.40                          |
| 3                                                   | 2483.50        | 63.4 PK                       | 74.0              | -10.6          | 1.25 H                   | 336                        | 68.50                  | -5.10                          |
| 4                                                   | 2483.50        | 48.4 AV                       | 54.0              | -5.6           | 1.25 H                   | 336                        | 53.50                  | -5.10                          |
| 5                                                   | 4924.00        | 48.7 PK                       | 74.0              | -25.3          | 1.30 H                   | 23                         | 44.90                  | 3.80                           |
| 6                                                   | 4924.00        | 37.4 AV                       | 54.0              | -16.6          | 1.30 H                   | 23                         | 33.60                  | 3.80                           |
| 7                                                   | 7386.00        | 51.7 PK                       | 74.0              | -22.3          | 1.00 H                   | 163                        | 43.10                  | 8.60                           |
| 8                                                   | 7386.00        | 38.9 AV                       | 54.0              | -15.1          | 1.00 H                   | 163                        | 30.30                  | 8.60                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 109.8 PK                      |                   |                | 1.22 V                   | 42                         | 115.20                 | -5.40                          |
| 2                                                   | *2462.00       | 100.6 AV                      |                   |                | 1.22 V                   | 42                         | 106.00                 | -5.40                          |
| 3                                                   | 2483.50        | 69.0 PK                       | 74.0              | -5.0           | 1.22 V                   | 42                         | 74.10                  | -5.10                          |
| 4                                                   | 2483.50        | 53.9 AV                       | 54.0              | -0.1           | 1.22 V                   | 42                         | 59.00                  | -5.10                          |
| 5                                                   | 4924.00        | 45.9 PK                       | 74.0              | -28.1          | 1.12 V                   | 154                        | 42.10                  | 3.80                           |
| 6                                                   | 4924.00        | 34.3 AV                       | 54.0              | -19.7          | 1.12 V                   | 154                        | 30.50                  | 3.80                           |
| 7                                                   | 7386.00        | 53.8 PK                       | 74.0              | -20.2          | 1.00 V                   | 221                        | 45.20                  | 8.60                           |
| 8                                                   | 7386.00        | 41.7 AV                       | 54.0              | -12.3          | 1.00 V                   | 221                        | 33.10                  | 8.60                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11n (HT20)

|                        |              |                          |              |
|------------------------|--------------|--------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 1 | <b>DETECTOR FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                          | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 67.5 PK                 | 74.0           | -6.5        | 1.38 H             | 73                   | 73.10            | -5.60                    |
| 2                                                   | 2390.00     | 49.4 AV                 | 54.0           | -4.6        | 1.38 H             | 73                   | 55.00            | -5.60                    |
| 3                                                   | *2412.00    | 105.7 PK                |                |             | 1.38 H             | 73                   | 111.20           | -5.50                    |
| 4                                                   | *2412.00    | 95.0 AV                 |                |             | 1.38 H             | 73                   | 100.50           | -5.50                    |
| 5                                                   | 4824.00     | 55.9 PK                 | 74.0           | -18.1       | 1.06 H             | 29                   | 52.10            | 3.80                     |
| 6                                                   | 4824.00     | 41.7 AV                 | 54.0           | -12.3       | 1.06 H             | 29                   | 37.90            | 3.80                     |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 2390.00     | 71.7 PK                 | 74.0           | -2.3        | 1.00 V             | 192                  | 77.30            | -5.60                    |
| 2                                                   | 2390.00     | 53.4 AV                 | 54.0           | -0.6        | 1.00 V             | 192                  | 59.00            | -5.60                    |
| 3                                                   | *2412.00    | 107.8 PK                |                |             | 1.00 V             | 192                  | 113.30           | -5.50                    |
| 4                                                   | *2412.00    | 98.0 AV                 |                |             | 1.00 V             | 192                  | 103.50           | -5.50                    |
| 5                                                   | 4824.00     | 60.0 PK                 | 74.0           | -14.0       | 1.00 V             | 2                    | 56.20            | 3.80                     |
| 6                                                   | 4824.00     | 45.2 AV                 | 54.0           | -8.8        | 1.00 V             | 2                    | 41.40            | 3.80                     |

### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 109.7 PK                      |                   |                | 1.32 H                   | 67                         | 115.10                 | -5.40                          |
| 2                                                   | *2437.00       | 99.1 AV                       |                   |                | 1.32 H                   | 67                         | 104.50                 | -5.40                          |
| 3                                                   | 4874.00        | 56.2 PK                       | 74.0              | -17.8          | 1.00 H                   | 16                         | 52.40                  | 3.80                           |
| 4                                                   | 4874.00        | 41.8 AV                       | 54.0              | -12.2          | 1.00 H                   | 16                         | 38.00                  | 3.80                           |
| 5                                                   | 7311.00        | 51.8 PK                       | 74.0              | -22.2          | 1.00 H                   | 169                        | 43.50                  | 8.30                           |
| 6                                                   | 7311.00        | 38.6 AV                       | 54.0              | -15.4          | 1.00 H                   | 169                        | 30.30                  | 8.30                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 111.6 PK                      |                   |                | 1.44 V                   | 197                        | 117.00                 | -5.40                          |
| 2                                                   | *2437.00       | 102.0 AV                      |                   |                | 1.44 V                   | 197                        | 107.40                 | -5.40                          |
| 3                                                   | 4874.00        | 60.4 PK                       | 74.0              | -13.6          | 1.00 V                   | 12                         | 56.60                  | 3.80                           |
| 4                                                   | 4874.00        | 45.5 AV                       | 54.0              | -8.5           | 1.00 V                   | 12                         | 41.70                  | 3.80                           |
| 5                                                   | 7311.00        | 54.2 PK                       | 74.0              | -19.8          | 1.00 V                   | 220                        | 45.90                  | 8.30                           |
| 6                                                   | 7311.00        | 42.3 AV                       | 54.0              | -11.7          | 1.00 V                   | 220                        | 34.00                  | 8.30                           |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 106.8 PK                      |                   |                | 1.35 H                   | 53                         | 112.20                 | -5.40                          |
| 2                                                   | *2462.00       | 95.8 AV                       |                   |                | 1.35 H                   | 53                         | 101.20                 | -5.40                          |
| 3                                                   | 2483.50        | 67.6 PK                       | 74.0              | -6.4           | 1.36 H                   | 88                         | 72.70                  | -5.10                          |
| 4                                                   | 2483.50        | 49.7 AV                       | 54.0              | -4.3           | 1.36 H                   | 88                         | 54.80                  | -5.10                          |
| 5                                                   | 4924.00        | 56.2 PK                       | 74.0              | -17.8          | 1.00 H                   | 15                         | 52.40                  | 3.80                           |
| 6                                                   | 4924.00        | 42.0 AV                       | 54.0              | -12.0          | 1.00 H                   | 15                         | 38.20                  | 3.80                           |
| 7                                                   | 7386.00        | 52.2 PK                       | 74.0              | -21.8          | 1.04 H                   | 169                        | 43.60                  | 8.60                           |
| 8                                                   | 7386.00        | 38.7 AV                       | 54.0              | -15.3          | 1.04 H                   | 169                        | 30.10                  | 8.60                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 108.6 PK                      |                   |                | 1.00 V                   | 196                        | 114.00                 | -5.40                          |
| 2                                                   | *2462.00       | 98.6 AV                       |                   |                | 1.00 V                   | 196                        | 104.00                 | -5.40                          |
| 3                                                   | 2483.50        | 70.4 PK                       | 74.0              | -3.6           | 1.00 V                   | 196                        | 75.50                  | -5.10                          |
| 4                                                   | 2483.50        | 53.7 AV                       | 54.0              | -0.3           | 1.00 V                   | 196                        | 58.80                  | -5.10                          |
| 5                                                   | 4924.00        | 60.1 PK                       | 74.0              | -13.9          | 1.01 V                   | 25                         | 56.30                  | 3.80                           |
| 6                                                   | 4924.00        | 45.1 AV                       | 54.0              | -8.9           | 1.01 V                   | 25                         | 41.30                  | 3.80                           |
| 7                                                   | 7386.00        | 54.1 PK                       | 74.0              | -19.9          | 1.04 V                   | 208                        | 45.50                  | 8.60                           |
| 8                                                   | 7386.00        | 42.2 AV                       | 54.0              | -11.8          | 1.04 V                   | 208                        | 33.60                  | 8.60                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11n (HT40)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.8 PK                       | 74.0              | -15.2          | 1.00 H                   | 327                        | 64.40                  | -5.60                          |
| 2                                                   | 2390.00        | 43.4 AV                       | 54.0              | -10.6          | 1.00 H                   | 327                        | 49.00                  | -5.60                          |
| 3                                                   | *2422.00       | 96.9 PK                       |                   |                | 1.00 H                   | 327                        | 102.40                 | -5.50                          |
| 4                                                   | *2422.00       | 88.0 AV                       |                   |                | 1.00 H                   | 327                        | 93.50                  | -5.50                          |
| 5                                                   | 4844.00        | 56.8 PK                       | 74.0              | -17.2          | 1.04 H                   | 24                         | 53.00                  | 3.80                           |
| 6                                                   | 4844.00        | 42.4 AV                       | 54.0              | -11.6          | 1.04 H                   | 24                         | 38.60                  | 3.80                           |
| 7                                                   | 7266.00        | 52.8 PK                       | 74.0              | -21.2          | 1.00 H                   | 185                        | 44.70                  | 8.10                           |
| 8                                                   | 7266.00        | 39.1 AV                       | 54.0              | -14.9          | 1.00 H                   | 185                        | 31.00                  | 8.10                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 67.1 PK                       | 74.0              | -6.9           | 1.00 V                   | 193                        | 72.70                  | -5.60                          |
| 2                                                   | 2390.00        | 53.3 AV                       | 54.0              | -0.7           | 1.00 V                   | 193                        | 58.90                  | -5.60                          |
| 3                                                   | *2422.00       | 102.0 PK                      |                   |                | 1.00 V                   | 193                        | 107.50                 | -5.50                          |
| 4                                                   | *2422.00       | 93.7 AV                       |                   |                | 1.00 V                   | 193                        | 99.20                  | -5.50                          |
| 5                                                   | 4844.00        | 59.8 PK                       | 74.0              | -14.2          | 1.00 V                   | 11                         | 56.00                  | 3.80                           |
| 6                                                   | 4844.00        | 45.0 AV                       | 54.0              | -9.0           | 1.00 V                   | 11                         | 41.20                  | 3.80                           |
| 7                                                   | 7266.00        | 53.8 PK                       | 74.0              | -20.2          | 1.09 V                   | 223                        | 45.70                  | 8.10                           |
| 8                                                   | 7266.00        | 41.8 AV                       | 54.0              | -12.2          | 1.09 V                   | 223                        | 33.70                  | 8.10                           |

## REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 59.0 PK                       | 74.0              | -15.0          | 1.00 H                   | 337                        | 64.60                  | -5.60                          |
| 2                                                   | 2390.00        | 43.5 AV                       | 54.0              | -10.5          | 1.00 H                   | 337                        | 49.10                  | -5.60                          |
| 3                                                   | *2437.00       | 101.7 PK                      |                   |                | 1.00 H                   | 337                        | 107.10                 | -5.40                          |
| 4                                                   | *2437.00       | 92.5 AV                       |                   |                | 1.00 H                   | 337                        | 97.90                  | -5.40                          |
| 5                                                   | 2483.50        | 59.0 PK                       | 74.0              | -15.0          | 1.00 H                   | 337                        | 64.10                  | -5.10                          |
| 6                                                   | 2483.50        | 45.2 AV                       | 54.0              | -8.8           | 1.00 H                   | 337                        | 50.30                  | -5.10                          |
| 7                                                   | 4874.00        | 56.3 PK                       | 74.0              | -17.7          | 1.03 H                   | 16                         | 52.50                  | 3.80                           |
| 8                                                   | 4874.00        | 42.1 AV                       | 54.0              | -11.9          | 1.03 H                   | 16                         | 38.30                  | 3.80                           |
| 9                                                   | 7311.00        | 52.3 PK                       | 74.0              | -21.7          | 1.03 H                   | 180                        | 44.00                  | 8.30                           |
| 10                                                  | 7311.00        | 38.8 AV                       | 54.0              | -15.2          | 1.03 H                   | 180                        | 30.50                  | 8.30                           |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | 2390.00        | 68.5 PK                       | 74.0              | -5.5           | 1.00 V                   | 190                        | 74.10                  | -5.60                          |
| 2                                                 | 2390.00        | 53.8 AV                       | 54.0              | -0.2           | 1.00 V                   | 190                        | 59.40                  | -5.60                          |
| 3                                                 | *2437.00       | 107.3 PK                      |                   |                | 1.00 V                   | 190                        | 112.70                 | -5.40                          |
| 4                                                 | *2437.00       | 98.9 AV                       |                   |                | 1.00 V                   | 190                        | 104.30                 | -5.40                          |
| 5                                                 | 2483.50        | 65.1 PK                       | 74.0              | -8.9           | 1.00 V                   | 190                        | 70.20                  | -5.10                          |
| 6                                                 | 2483.50        | 52.4 AV                       | 54.0              | -1.6           | 1.00 V                   | 190                        | 57.50                  | -5.10                          |
| 7                                                 | 4874.00        | 59.6 PK                       | 74.0              | -14.4          | 1.05 V                   | 27                         | 55.80                  | 3.80                           |
| 8                                                 | 4874.00        | 44.7 AV                       | 54.0              | -9.3           | 1.05 V                   | 27                         | 40.90                  | 3.80                           |
| 9                                                 | 7311.00        | 53.5 PK                       | 74.0              | -20.5          | 1.11 V                   | 230                        | 45.20                  | 8.30                           |
| 10                                                | 7311.00        | 41.7 AV                       | 54.0              | -12.3          | 1.11 V                   | 230                        | 33.40                  | 8.30                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 9 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 97.3 PK                       |                   |                | 1.00 H                   | 319                        | 102.70                 | -5.40                          |
| 2                                                   | *2452.00       | 88.2 AV                       |                   |                | 1.00 H                   | 319                        | 93.60                  | -5.40                          |
| 3                                                   | 2483.50        | 59.0 PK                       | 74.0              | -15.0          | 1.00 H                   | 319                        | 64.10                  | -5.10                          |
| 4                                                   | 2483.50        | 45.1 AV                       | 54.0              | -8.9           | 1.00 H                   | 319                        | 50.20                  | -5.10                          |
| 5                                                   | 4904.00        | 56.3 PK                       | 74.0              | -17.7          | 1.08 H                   | 12                         | 52.60                  | 3.70                           |
| 6                                                   | 4904.00        | 42.0 AV                       | 54.0              | -12.0          | 1.08 H                   | 12                         | 38.30                  | 3.70                           |
| 7                                                   | 7356.00        | 52.0 PK                       | 74.0              | -22.0          | 1.00 H                   | 174                        | 43.60                  | 8.40                           |
| 8                                                   | 7356.00        | 38.7 AV                       | 54.0              | -15.3          | 1.00 H                   | 174                        | 30.30                  | 8.40                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 102.7 PK                      |                   |                | 1.00 V                   | 191                        | 108.10                 | -5.40                          |
| 2                                                   | *2452.00       | 94.3 AV                       |                   |                | 1.00 V                   | 191                        | 99.70                  | -5.40                          |
| 3                                                   | 2483.50        | 64.3 PK                       | 74.0              | -9.7           | 1.00 V                   | 191                        | 69.40                  | -5.10                          |
| 4                                                   | 2483.50        | 53.1 AV                       | 54.0              | -0.9           | 1.00 V                   | 191                        | 58.20                  | -5.10                          |
| 5                                                   | 4904.00        | 60.0 PK                       | 74.0              | -14.0          | 1.00 V                   | 27                         | 56.30                  | 3.70                           |
| 6                                                   | 4904.00        | 45.2 AV                       | 54.0              | -8.8           | 1.00 V                   | 27                         | 41.50                  | 3.70                           |
| 7                                                   | 7356.00        | 53.1 PK                       | 74.0              | -20.9          | 1.16 V                   | 214                        | 44.70                  | 8.40                           |
| 8                                                   | 7356.00        | 41.4 AV                       | 54.0              | -12.6          | 1.16 V                   | 214                        | 33.00                  | 8.40                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 2TX Mode

### 802.11n (HT20)

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 1 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 49.2 PK                       | 74.0              | -24.8          | 1.03 H                   | 154                        | 54.80                  | -5.60                          |
| 2                                                   | 2390.00        | 37.6 AV                       | 54.0              | -16.4          | 1.03 H                   | 154                        | 43.20                  | -5.60                          |
| 3                                                   | *2412.00       | 109.8 PK                      |                   |                | 1.07 H                   | 149                        | 115.30                 | -5.50                          |
| 4                                                   | *2412.00       | 98.3 AV                       |                   |                | 1.07 H                   | 149                        | 103.80                 | -5.50                          |
| 5                                                   | 4824.00        | 55.5 PK                       | 74.0              | -18.5          | 1.57 H                   | 250                        | 51.70                  | 3.80                           |
| 6                                                   | 4824.00        | 41.9 AV                       | 54.0              | -12.1          | 1.57 H                   | 250                        | 38.10                  | 3.80                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 68.9 PK                       | 74.0              | -5.1           | 1.22 V                   | 38                         | 74.50                  | -5.60                          |
| 2                                                   | 2390.00        | 53.8 AV                       | 54.0              | -0.2           | 1.22 V                   | 38                         | 59.40                  | -5.60                          |
| 3                                                   | *2412.00       | 111.8 PK                      |                   |                | 1.22 V                   | 38                         | 117.30                 | -5.50                          |
| 4                                                   | *2412.00       | 100.6 AV                      |                   |                | 1.22 V                   | 38                         | 106.10                 | -5.50                          |
| 5                                                   | 4824.00        | 57.4 PK                       | 74.0              | -16.6          | 1.32 V                   | 140                        | 53.60                  | 3.80                           |
| 6                                                   | 4824.00        | 45.2 AV                       | 54.0              | -8.8           | 1.32 V                   | 140                        | 41.40                  | 3.80                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 49.1 PK                       | 74.0              | -24.9          | 1.05 H                   | 148                        | 54.70                  | -5.60                          |
| 2                                                   | 2390.00        | 37.3 AV                       | 54.0              | -16.7          | 1.05 H                   | 148                        | 42.90                  | -5.60                          |
| 3                                                   | *2437.00       | 112.0 PK                      |                   |                | 1.05 H                   | 148                        | 117.40                 | -5.40                          |
| 4                                                   | *2437.00       | 100.2 AV                      |                   |                | 1.05 H                   | 148                        | 105.60                 | -5.40                          |
| 5                                                   | 2483.50        | 51.0 PK                       | 74.0              | -23.0          | 1.05 H                   | 148                        | 56.10                  | -5.10                          |
| 6                                                   | 2483.50        | 39.0 AV                       | 54.0              | -15.0          | 1.05 H                   | 148                        | 44.10                  | -5.10                          |
| 7                                                   | 4874.00        | 55.0 PK                       | 74.0              | -19.0          | 1.59 H                   | 245                        | 51.20                  | 3.80                           |
| 8                                                   | 4874.00        | 41.7 AV                       | 54.0              | -12.3          | 1.59 H                   | 245                        | 37.90                  | 3.80                           |
| 9                                                   | 7311.00        | 53.0 PK                       | 74.0              | -21.0          | 1.00 H                   | 291                        | 44.70                  | 8.30                           |
| 10                                                  | 7311.00        | 41.1 AV                       | 54.0              | -12.9          | 1.00 H                   | 291                        | 32.80                  | 8.30                           |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | 2390.00        | 54.3 PK                       | 74.0              | -19.7          | 1.17 V                   | 38                         | 59.90                  | -5.60                          |
| 2                                                 | 2390.00        | 42.7 AV                       | 54.0              | -11.3          | 1.17 V                   | 38                         | 48.30                  | -5.60                          |
| 3                                                 | *2437.00       | 113.9 PK                      |                   |                | 1.17 V                   | 38                         | 119.30                 | -5.40                          |
| 4                                                 | *2437.00       | 102.7 AV                      |                   |                | 1.17 V                   | 38                         | 108.10                 | -5.40                          |
| 5                                                 | 2483.50        | 55.7 PK                       | 74.0              | -18.3          | 1.17 V                   | 38                         | 60.80                  | -5.10                          |
| 6                                                 | 2483.50        | 42.5 AV                       | 54.0              | -11.5          | 1.17 V                   | 38                         | 47.60                  | -5.10                          |
| 7                                                 | 4874.00        | 66.2 PK                       | 74.0              | -7.8           | 1.37 V                   | 143                        | 62.40                  | 3.80                           |
| 8                                                 | 4874.00        | 53.6 AV                       | 54.0              | -0.4           | 1.37 V                   | 143                        | 49.80                  | 3.80                           |
| 9                                                 | 7311.00        | 54.6 PK                       | 74.0              | -19.4          | 1.00 V                   | 213                        | 46.30                  | 8.30                           |
| 10                                                | 7311.00        | 41.0 AV                       | 54.0              | -13.0          | 1.00 V                   | 213                        | 32.70                  | 8.30                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 109.8 PK                      |                   |                | 1.09 H                   | 146                        | 115.20                 | -5.40                          |
| 2                                                   | *2462.00       | 98.4 AV                       |                   |                | 1.09 H                   | 146                        | 103.80                 | -5.40                          |
| 3                                                   | 2483.50        | 64.6 PK                       | 74.0              | -9.4           | 1.09 H                   | 146                        | 69.70                  | -5.10                          |
| 4                                                   | 2483.50        | 50.6 AV                       | 54.0              | -3.4           | 1.09 H                   | 146                        | 55.70                  | -5.10                          |
| 5                                                   | 4924.00        | 54.8 PK                       | 74.0              | -19.2          | 1.61 H                   | 234                        | 51.00                  | 3.80                           |
| 6                                                   | 4924.00        | 41.7 AV                       | 54.0              | -12.3          | 1.61 H                   | 234                        | 37.90                  | 3.80                           |
| 7                                                   | 7386.00        | 53.6 PK                       | 74.0              | -20.4          | 1.00 H                   | 302                        | 45.00                  | 8.60                           |
| 8                                                   | 7386.00        | 41.5 AV                       | 54.0              | -12.5          | 1.00 H                   | 302                        | 32.90                  | 8.60                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 111.6 PK                      |                   |                | 1.22 V                   | 41                         | 117.00                 | -5.40                          |
| 2                                                   | *2462.00       | 100.1 AV                      |                   |                | 1.22 V                   | 41                         | 105.50                 | -5.40                          |
| 3                                                   | 2483.50        | 67.2 PK                       | 74.0              | -6.8           | 1.22 V                   | 41                         | 72.30                  | -5.10                          |
| 4                                                   | 2483.50        | 53.4 AV                       | 54.0              | -0.6           | 1.22 V                   | 41                         | 58.50                  | -5.10                          |
| 5                                                   | 4924.00        | 57.7 PK                       | 74.0              | -16.3          | 1.35 V                   | 144                        | 53.90                  | 3.80                           |
| 6                                                   | 4924.00        | 45.3 AV                       | 54.0              | -8.7           | 1.35 V                   | 144                        | 41.50                  | 3.80                           |
| 7                                                   | 7386.00        | 54.2 PK                       | 74.0              | -19.8          | 1.00 V                   | 211                        | 45.60                  | 8.60                           |
| 8                                                   | 7386.00        | 42.0 AV                       | 54.0              | -12.0          | 1.00 V                   | 211                        | 33.40                  | 8.60                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

# 802.11n (HT40)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 61.0 PK                       | 74.0              | -13.0          | 1.02 H                   | 311                        | 66.60                  | -5.60                          |
| 2                                                   | 2390.00        | 47.7 AV                       | 54.0              | -6.3           | 1.02 H                   | 311                        | 53.30                  | -5.60                          |
| 3                                                   | *2422.00       | 105.9 PK                      |                   |                | 1.00 H                   | 340                        | 111.40                 | -5.50                          |
| 4                                                   | *2422.00       | 94.3 AV                       |                   |                | 1.00 H                   | 340                        | 99.80                  | -5.50                          |
| 5                                                   | 4844.00        | 52.8 PK                       | 74.0              | -21.2          | 1.00 H                   | 287                        | 49.00                  | 3.80                           |
| 6                                                   | 4844.00        | 40.7 AV                       | 54.0              | -13.3          | 1.00 H                   | 287                        | 36.90                  | 3.80                           |
| 7                                                   | 7266.00        | 54.0 PK                       | 74.0              | -20.0          | 1.00 H                   | 303                        | 45.90                  | 8.10                           |
| 8                                                   | 7266.00        | 41.9 AV                       | 54.0              | -12.1          | 1.00 H                   | 303                        | 33.80                  | 8.10                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 66.6 PK                       | 74.0              | -7.4           | 1.20 V                   | 40                         | 72.20                  | -5.60                          |
| 2                                                   | 2390.00        | 53.8 AV                       | 54.0              | -0.2           | 1.20 V                   | 40                         | 59.40                  | -5.60                          |
| 3                                                   | *2422.00       | 107.6 PK                      |                   |                | 1.20 V                   | 40                         | 113.10                 | -5.50                          |
| 4                                                   | *2422.00       | 96.2 AV                       |                   |                | 1.20 V                   | 40                         | 101.70                 | -5.50                          |
| 5                                                   | 4844.00        | 63.0 PK                       | 74.0              | -11.0          | 1.33 V                   | 158                        | 59.20                  | 3.80                           |
| 6                                                   | 4844.00        | 50.7 AV                       | 54.0              | -3.3           | 1.33 V                   | 158                        | 46.90                  | 3.80                           |
| 7                                                   | 7266.00        | 53.6 PK                       | 74.0              | -20.4          | 1.00 V                   | 208                        | 45.50                  | 8.10                           |
| 8                                                   | 7266.00        | 41.5 AV                       | 54.0              | -12.5          | 1.00 V                   | 208                        | 33.40                  | 8.10                           |

## REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.



|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 6 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 61.2 PK                       | 74.0              | -12.8          | 1.01 H                   | 324                        | 66.80                  | -5.60                          |
| 2                                                   | 2390.00        | 47.9 AV                       | 54.0              | -6.1           | 1.01 H                   | 324                        | 53.50                  | -5.60                          |
| 3                                                   | *2437.00       | 109.6 PK                      |                   |                | 1.01 H                   | 324                        | 115.00                 | -5.40                          |
| 4                                                   | *2437.00       | 97.9 AV                       |                   |                | 1.01 H                   | 324                        | 103.30                 | -5.40                          |
| 5                                                   | 2483.50        | 61.5 PK                       | 74.0              | -12.5          | 1.01 H                   | 324                        | 66.60                  | -5.10                          |
| 6                                                   | 2483.50        | 47.5 AV                       | 54.0              | -6.5           | 1.01 H                   | 324                        | 52.60                  | -5.10                          |
| 7                                                   | 4874.00        | 53.1 PK                       | 74.0              | -20.9          | 1.00 H                   | 296                        | 49.30                  | 3.80                           |
| 8                                                   | 4874.00        | 41.2 AV                       | 54.0              | -12.8          | 1.00 H                   | 296                        | 37.40                  | 3.80                           |
| 9                                                   | 7311.00        | 54.2 PK                       | 74.0              | -19.8          | 1.00 H                   | 295                        | 45.90                  | 8.30                           |
| 10                                                  | 7311.00        | 41.9 AV                       | 54.0              | -12.1          | 1.00 H                   | 295                        | 33.60                  | 8.30                           |

| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|---------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                               | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                 | 2390.00        | 66.5 PK                       | 74.0              | -7.5           | 1.19 V                   | 39                         | 72.10                  | -5.60                          |
| 2                                                 | 2390.00        | 53.2 AV                       | 54.0              | -0.8           | 1.19 V                   | 39                         | 58.80                  | -5.60                          |
| 3                                                 | *2437.00       | 111.4 PK                      |                   |                | 1.19 V                   | 39                         | 116.80                 | -5.40                          |
| 4                                                 | *2437.00       | 100.5 AV                      |                   |                | 1.19 V                   | 39                         | 105.90                 | -5.40                          |
| 5                                                 | 2483.50        | 64.8 PK                       | 74.0              | -9.2           | 1.19 V                   | 39                         | 69.90                  | -5.10                          |
| 6                                                 | 2483.50        | 50.3 AV                       | 54.0              | -3.7           | 1.19 V                   | 39                         | 55.40                  | -5.10                          |
| 7                                                 | 4874.00        | 63.6 PK                       | 74.0              | -10.4          | 1.37 V                   | 144                        | 59.80                  | 3.80                           |
| 8                                                 | 4874.00        | 51.0 AV                       | 54.0              | -3.0           | 1.37 V                   | 144                        | 47.20                  | 3.80                           |
| 9                                                 | 7311.00        | 53.2 PK                       | 74.0              | -20.8          | 1.00 V                   | 206                        | 44.90                  | 8.30                           |
| 10                                                | 7311.00        | 41.3 AV                       | 54.0              | -12.7          | 1.00 V                   | 206                        | 33.00                  | 8.30                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 9 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 106.3 PK                      |                   |                | 1.00 H                   | 325                        | 111.70                 | -5.40                          |
| 2                                                   | *2452.00       | 94.4 AV                       |                   |                | 1.00 H                   | 325                        | 99.80                  | -5.40                          |
| 3                                                   | 2483.50        | 61.1 PK                       | 74.0              | -12.9          | 1.04 H                   | 334                        | 66.20                  | -5.10                          |
| 4                                                   | 2483.50        | 47.1 AV                       | 54.0              | -6.9           | 1.04 H                   | 334                        | 52.20                  | -5.10                          |
| 5                                                   | 4904.00        | 53.1 PK                       | 74.0              | -20.9          | 1.01 H                   | 290                        | 49.40                  | 3.70                           |
| 6                                                   | 4904.00        | 40.8 AV                       | 54.0              | -13.2          | 1.01 H                   | 290                        | 37.10                  | 3.70                           |
| 7                                                   | 7356.00        | 54.5 PK                       | 74.0              | -19.5          | 1.00 H                   | 309                        | 46.10                  | 8.40                           |
| 8                                                   | 7356.00        | 42.2 AV                       | 54.0              | -11.8          | 1.00 H                   | 309                        | 33.80                  | 8.40                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 108.2 PK                      |                   |                | 1.19 V                   | 40                         | 113.60                 | -5.40                          |
| 2                                                   | *2452.00       | 96.8 AV                       |                   |                | 1.19 V                   | 40                         | 102.20                 | -5.40                          |
| 3                                                   | 2483.50        | 66.2 PK                       | 74.0              | -7.8           | 1.19 V                   | 40                         | 71.30                  | -5.10                          |
| 4                                                   | 2483.50        | 53.7 AV                       | 54.0              | -0.3           | 1.19 V                   | 40                         | 58.80                  | -5.10                          |
| 5                                                   | 4904.00        | 63.1 PK                       | 74.0              | -10.9          | 1.25 V                   | 171                        | 59.40                  | 3.70                           |
| 6                                                   | 4904.00        | 50.9 AV                       | 54.0              | -3.1           | 1.25 V                   | 171                        | 47.20                  | 3.70                           |
| 7                                                   | 7356.00        | 52.7 PK                       | 74.0              | -21.3          | 1.05 V                   | 214                        | 44.30                  | 8.40                           |
| 8                                                   | 7356.00        | 41.1 AV                       | 54.0              | -12.9          | 1.05 V                   | 214                        | 32.70                  | 8.40                           |

**REMARKS:**

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 2TX Mode

### Below 1GHz Data

#### 802.11n (HT40)

|                 |              |                   |                 |
|-----------------|--------------|-------------------|-----------------|
| CHANNEL         | TX Channel 6 | DETECTOR FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | Below 1GHz   |                   |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |             |                         |                |             |                    |                      |                  |                          |
|-----------------------------------------------------|-------------|-------------------------|----------------|-------------|--------------------|----------------------|------------------|--------------------------|
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 125.25      | 33.0 QP                 | 43.5           | -10.5       | 1.64 H             | 211                  | 47.88            | -14.86                   |
| 2                                                   | 175.12      | 34.3 QP                 | 43.5           | -9.2        | 1.75 H             | 201                  | 48.20            | -13.86                   |
| 3                                                   | 249.75      | 42.3 QP                 | 46.0           | -3.7        | 1.45 H             | 301                  | 56.36            | -14.02                   |
| 4                                                   | 374.71      | 37.7 QP                 | 46.0           | -8.3        | 1.24 H             | 311                  | 47.69            | -9.98                    |
| 5                                                   | 500.11      | 35.4 QP                 | 46.0           | -10.6       | 1.42 H             | 100                  | 42.25            | -6.83                    |
| 6                                                   | 749.74      | 38.5 QP                 | 46.0           | -7.5        | 1.24 H             | 100                  | 39.73            | -1.22                    |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |             |                         |                |             |                    |                      |                  |                          |
| NO.                                                 | FREQ. (MHz) | EMISSION LEVEL (dBuV/m) | LIMIT (dBuV/m) | MARGIN (dB) | ANTENNA HEIGHT (m) | TABLE ANGLE (Degree) | RAW VALUE (dBuV) | CORRECTION FACTOR (dB/m) |
| 1                                                   | 34.21       | 36.0 QP                 | 40.0           | -4.0        | 1.34 V             | 64                   | 50.14            | -14.13                   |
| 2                                                   | 66.34       | 33.2 QP                 | 40.0           | -6.8        | 1.64 V             | 245                  | 47.69            | -14.48                   |
| 3                                                   | 209.54      | 37.0 QP                 | 43.5           | -6.5        | 1.24 V             | 301                  | 53.01            | -16.04                   |
| 4                                                   | 249.24      | 37.5 QP                 | 46.0           | -8.5        | 2.14 V             | 301                  | 51.54            | -14.03                   |
| 5                                                   | 400.24      | 38.3 QP                 | 46.0           | -7.7        | 1.24 V             | 301                  | 47.70            | -9.39                    |
| 6                                                   | 424.51      | 41.2 QP                 | 46.0           | -4.8        | 1.64 V             | 201                  | 49.75            | -8.51                    |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

#### 4.1.8 Test Results (Mode 2)

##### 1TX Mode

##### Above 1GHz Data

##### 802.11b

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2320.00        | 46.4 PK                       | 74.0              | -27.6          | 1.30 H                   | 20                         | 49.38                  | -2.98                          |
| 2                                                   | 2320.00        | 38.1 AV                       | 54.0              | -15.9          | 1.30 H                   | 20                         | 41.08                  | -2.98                          |
| 3                                                   | 2390.00        | 53.8 PK                       | 74.0              | -20.2          | 1.29 H                   | 19                         | 56.69                  | -2.89                          |
| 4                                                   | 2390.00        | 43.5 AV                       | 54.0              | -10.5          | 1.29 H                   | 19                         | 46.39                  | -2.89                          |
| 5                                                   | *2412.00       | 106.3 PK                      |                   |                | 1.25 H                   | 24                         | 109.15                 | -2.85                          |
| 6                                                   | *2412.00       | 103.5 AV                      |                   |                | 1.25 H                   | 24                         | 106.35                 | -2.85                          |
| 7                                                   | 4824.00        | 51.5 PK                       | 74.0              | -22.5          | 1.00 H                   | 322                        | 45.28                  | 6.22                           |
| 8                                                   | 4824.00        | 42.8 AV                       | 54.0              | -11.2          | 1.00 H                   | 322                        | 36.58                  | 6.22                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2320.00        | 56.4 PK                       | 74.0              | -17.6          | 1.32 V                   | 360                        | 59.38                  | -2.98                          |
| 2                                                   | 2320.00        | 47.4 AV                       | 54.0              | -6.6           | 1.32 V                   | 360                        | 50.38                  | -2.98                          |
| 3                                                   | 2390.00        | 62.5 PK                       | 74.0              | -11.5          | 1.28 V                   | 360                        | 65.39                  | -2.89                          |
| 4                                                   | 2390.00        | 52.6 AV                       | 54.0              | -1.4           | 1.28 V                   | 360                        | 55.49                  | -2.89                          |
| 5                                                   | *2412.00       | 115.6 PK                      |                   |                | 1.56 V                   | 360                        | 118.45                 | -2.85                          |
| 6                                                   | *2412.00       | 113.4 AV                      |                   |                | 1.56 V                   | 360                        | 116.25                 | -2.85                          |
| 7                                                   | 4824.00        | 56.6 PK                       | 74.0              | -17.4          | 1.08 V                   | 351                        | 50.38                  | 6.22                           |
| 8                                                   | 4824.00        | 53.2 AV                       | 54.0              | -0.8           | 1.08 V                   | 351                        | 46.98                  | 6.22                           |

##### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 107.3 PK                      |                   |                | 1.19 H                   | 12                         | 110.09                 | -2.79                          |
| 2                                                   | *2437.00       | 104.3 AV                      |                   |                | 1.19 H                   | 12                         | 107.09                 | -2.79                          |
| 3                                                   | 4874.00        | 50.8 PK                       | 74.0              | -23.2          | 1.00 H                   | 306                        | 44.54                  | 6.26                           |
| 4                                                   | 4874.00        | 42.7 AV                       | 54.0              | -11.3          | 1.00 H                   | 306                        | 36.44                  | 6.26                           |
| 5                                                   | 7311.00        | 58.2 PK                       | 74.0              | -15.8          | 1.34 H                   | 25                         | 47.00                  | 11.20                          |
| 6                                                   | 7311.00        | 45.2 AV                       | 54.0              | -8.8           | 1.34 H                   | 25                         | 34.00                  | 11.20                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2437.00       | 116.6 PK                      |                   |                | 1.50 V                   | 360                        | 119.39                 | -2.79                          |
| 2                                                   | *2437.00       | 114.2 AV                      |                   |                | 1.50 V                   | 360                        | 116.99                 | -2.79                          |
| 3                                                   | 4874.00        | 55.9 PK                       | 74.0              | -18.1          | 1.06 V                   | 360                        | 49.64                  | 6.26                           |
| 4                                                   | 4874.00        | 53.1 AV                       | 54.0              | -0.9           | 1.06 V                   | 360                        | 46.84                  | 6.26                           |
| 5                                                   | 7311.00        | 58.3 PK                       | 74.0              | -15.7          | 1.06 V                   | 360                        | 47.10                  | 11.20                          |
| 6                                                   | 7311.00        | 46.5 AV                       | 54.0              | -7.5           | 1.06 V                   | 360                        | 35.30                  | 11.20                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 107.6 PK                      |                   |                | 1.31 H                   | 40                         | 110.32                 | -2.72                          |
| 2                                                   | *2462.00       | 104.7 AV                      |                   |                | 1.31 H                   | 40                         | 107.42                 | -2.72                          |
| 3                                                   | 2483.50        | 53.7 PK                       | 74.0              | -20.3          | 1.30 H                   | 20                         | 56.37                  | -2.67                          |
| 4                                                   | 2483.50        | 42.9 AV                       | 54.0              | -11.1          | 1.30 H                   | 20                         | 45.57                  | -2.67                          |
| 5                                                   | 4924.00        | 50.3 PK                       | 74.0              | -23.7          | 1.06 H                   | 317                        | 44.05                  | 6.25                           |
| 6                                                   | 4924.00        | 42.4 AV                       | 54.0              | -11.6          | 1.06 H                   | 317                        | 36.15                  | 6.25                           |
| 7                                                   | 7386.00        | 58.8 PK                       | 74.0              | -15.2          | 1.33 H                   | 26                         | 47.19                  | 11.61                          |
| 8                                                   | 7386.00        | 45.5 AV                       | 54.0              | -8.5           | 1.33 H                   | 26                         | 33.89                  | 11.61                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 116.8 PK                      |                   |                | 1.53 V                   | 360                        | 119.52                 | -2.72                          |
| 2                                                   | *2462.00       | 114.5 AV                      |                   |                | 1.53 V                   | 360                        | 117.22                 | -2.72                          |
| 3                                                   | 2483.50        | 61.9 PK                       | 74.0              | -12.1          | 1.51 V                   | 360                        | 64.57                  | -2.67                          |
| 4                                                   | 2483.50        | 52.1 AV                       | 54.0              | -1.9           | 1.51 V                   | 360                        | 54.77                  | -2.67                          |
| 5                                                   | 4924.00        | 57.3 PK                       | 74.0              | -16.7          | 1.19 V                   | 360                        | 51.05                  | 6.25                           |
| 6                                                   | 4924.00        | 53.6 AV                       | 54.0              | -0.4           | 1.19 V                   | 360                        | 47.35                  | 6.25                           |
| 7                                                   | 7386.00        | 58.4 PK                       | 74.0              | -15.6          | 1.04 V                   | 360                        | 46.79                  | 11.61                          |
| 8                                                   | 7386.00        | 46.6 AV                       | 54.0              | -7.4           | 1.04 V                   | 360                        | 34.99                  | 11.61                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11g

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2320.00        | 46.1 PK                       | 74.0              | -27.9          | 1.26 H                   | 35                         | 49.08                  | -2.98                          |
| 2                                                   | 2320.00        | 36.8 AV                       | 54.0              | -17.2          | 1.26 H                   | 35                         | 39.78                  | -2.98                          |
| 3                                                   | 2390.00        | 60.3 PK                       | 74.0              | -13.7          | 1.25 H                   | 32                         | 63.19                  | -2.89                          |
| 4                                                   | 2390.00        | 44.7 AV                       | 54.0              | -9.3           | 1.25 H                   | 32                         | 47.59                  | -2.89                          |
| 5                                                   | *2412.00       | 105.5 PK                      |                   |                | 1.30 H                   | 32                         | 108.35                 | -2.85                          |
| 6                                                   | *2412.00       | 95.7 AV                       |                   |                | 1.30 H                   | 32                         | 98.55                  | -2.85                          |
| 7                                                   | 4824.00        | 51.7 PK                       | 74.0              | -22.3          | 1.02 H                   | 306                        | 45.48                  | 6.22                           |
| 8                                                   | 4824.00        | 43.0 AV                       | 54.0              | -11.0          | 1.02 H                   | 306                        | 36.78                  | 6.22                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2320.00        | 56.1 PK                       | 74.0              | -17.9          | 1.33 V                   | 360                        | 59.08                  | -2.98                          |
| 2                                                   | 2320.00        | 46.1 AV                       | 54.0              | -7.9           | 1.33 V                   | 360                        | 49.08                  | -2.98                          |
| 3                                                   | 2390.00        | 69.0 PK                       | 74.0              | -5.0           | 1.29 V                   | 360                        | 71.89                  | -2.89                          |
| 4                                                   | 2390.00        | 53.8 AV                       | 54.0              | -0.2           | 1.29 V                   | 360                        | 56.69                  | -2.89                          |
| 5                                                   | *2412.00       | 114.6 PK                      |                   |                | 1.29 V                   | 360                        | 117.45                 | -2.85                          |
| 6                                                   | *2412.00       | 105.3 AV                      |                   |                | 1.29 V                   | 360                        | 108.15                 | -2.85                          |
| 7                                                   | 4824.00        | 52.5 PK                       | 74.0              | -21.5          | 1.22 V                   | 360                        | 46.28                  | 6.22                           |
| 8                                                   | 4824.00        | 40.4 AV                       | 54.0              | -13.6          | 1.22 V                   | 360                        | 34.18                  | 6.22                           |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 52.4 PK                       | 74.0              | -21.6          | 1.32 H                   | 32                         | 55.29                  | -2.89                          |
| 2                                                   | 2390.00        | 44.0 AV                       | 54.0              | -10.0          | 1.32 H                   | 32                         | 46.89                  | -2.89                          |
| 3                                                   | *2437.00       | 108.8 PK                      |                   |                | 1.30 H                   | 54                         | 111.59                 | -2.79                          |
| 4                                                   | *2437.00       | 99.0 AV                       |                   |                | 1.30 H                   | 54                         | 101.79                 | -2.79                          |
| 5                                                   | 4874.00        | 52.0 PK                       | 74.0              | -22.0          | 1.56 H                   | 343                        | 45.74                  | 6.26                           |
| 6                                                   | 4874.00        | 40.1 AV                       | 54.0              | -13.9          | 1.56 H                   | 343                        | 33.84                  | 6.26                           |
| 7                                                   | 7311.00        | 58.0 PK                       | 74.0              | -16.0          | 1.06 H                   | 355                        | 46.80                  | 11.20                          |
| 8                                                   | 7311.00        | 45.2 AV                       | 54.0              | -8.8           | 1.06 H                   | 355                        | 34.00                  | 11.20                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 61.0 PK                       | 74.0              | -13.0          | 1.64 V                   | 360                        | 63.89                  | -2.89                          |
| 2                                                   | 2390.00        | 53.0 AV                       | 54.0              | -1.0           | 1.64 V                   | 360                        | 55.89                  | -2.89                          |
| 3                                                   | *2437.00       | 117.9 PK                      |                   |                | 1.29 V                   | 360                        | 120.69                 | -2.79                          |
| 4                                                   | *2437.00       | 108.6 AV                      |                   |                | 1.29 V                   | 360                        | 111.39                 | -2.79                          |
| 5                                                   | 4874.00        | 52.9 PK                       | 74.0              | -21.1          | 1.20 V                   | 353                        | 46.64                  | 6.26                           |
| 6                                                   | 4874.00        | 40.9 AV                       | 54.0              | -13.1          | 1.20 V                   | 353                        | 34.64                  | 6.26                           |
| 7                                                   | 7311.00        | 58.1 PK                       | 74.0              | -15.9          | 1.04 V                   | 354                        | 46.90                  | 11.20                          |
| 8                                                   | 7311.00        | 45.6 AV                       | 54.0              | -8.4           | 1.04 V                   | 354                        | 34.40                  | 11.20                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 105.7 PK                      |                   |                | 1.29 H                   | 16                         | 108.42                 | -2.72                          |
| 2                                                   | *2462.00       | 95.9 AV                       |                   |                | 1.29 H                   | 16                         | 98.62                  | -2.72                          |
| 3                                                   | 2483.50        | 58.8 PK                       | 74.0              | -15.2          | 1.30 H                   | 16                         | 61.47                  | -2.67                          |
| 4                                                   | 2483.50        | 44.3 AV                       | 54.0              | -9.7           | 1.30 H                   | 16                         | 46.97                  | -2.67                          |
| 5                                                   | 4924.00        | 51.7 PK                       | 74.0              | -22.3          | 1.00 H                   | 338                        | 45.45                  | 6.25                           |
| 6                                                   | 4924.00        | 39.8 AV                       | 54.0              | -14.2          | 1.00 H                   | 338                        | 33.55                  | 6.25                           |
| 7                                                   | 7386.00        | 58.0 PK                       | 74.0              | -16.0          | 1.35 H                   | 3                          | 46.39                  | 11.61                          |
| 8                                                   | 7386.00        | 45.0 AV                       | 54.0              | -9.0           | 1.35 H                   | 3                          | 33.39                  | 11.61                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 114.8 PK                      |                   |                | 1.54 V                   | 360                        | 117.52                 | -2.72                          |
| 2                                                   | *2462.00       | 105.5 AV                      |                   |                | 1.54 V                   | 360                        | 108.22                 | -2.72                          |
| 3                                                   | 2483.50        | 67.0 PK                       | 74.0              | -7.0           | 1.24 V                   | 360                        | 69.67                  | -2.67                          |
| 4                                                   | 2483.50        | 53.5 AV                       | 54.0              | -0.5           | 1.24 V                   | 360                        | 56.17                  | -2.67                          |
| 5                                                   | 4924.00        | 53.3 PK                       | 74.0              | -20.7          | 1.10 V                   | 342                        | 47.05                  | 6.25                           |
| 6                                                   | 4924.00        | 41.5 AV                       | 54.0              | -12.5          | 1.10 V                   | 342                        | 35.25                  | 6.25                           |
| 7                                                   | 7386.00        | 57.9 PK                       | 74.0              | -16.1          | 1.09 V                   | 358                        | 46.29                  | 11.61                          |
| 8                                                   | 7386.00        | 45.3 AV                       | 54.0              | -8.7           | 1.09 V                   | 358                        | 33.69                  | 11.61                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11n (HT20)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2320.00        | 46.1 PK                       | 74.0              | -27.9          | 1.26 H                   | 35                         | 49.08                  | -2.98                          |
| 2                                                   | 2320.00        | 38.4 AV                       | 54.0              | -15.6          | 1.26 H                   | 35                         | 41.38                  | -2.98                          |
| 3                                                   | 2390.00        | 61.4 PK                       | 74.0              | -12.6          | 1.25 H                   | 18                         | 64.29                  | -2.89                          |
| 4                                                   | 2390.00        | 44.6 AV                       | 54.0              | -9.4           | 1.25 H                   | 18                         | 47.49                  | -2.89                          |
| 5                                                   | *2412.00       | 103.8 PK                      |                   |                | 1.26 H                   | 17                         | 106.65                 | -2.85                          |
| 6                                                   | *2412.00       | 95.0 AV                       |                   |                | 1.26 H                   | 17                         | 97.85                  | -2.85                          |
| 7                                                   | 4824.00        | 51.7 PK                       | 74.0              | -22.3          | 1.01 H                   | 295                        | 45.48                  | 6.22                           |
| 8                                                   | 4824.00        | 43.0 AV                       | 54.0              | -11.0          | 1.01 H                   | 295                        | 36.78                  | 6.22                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2320.00        | 56.2 PK                       | 74.0              | -17.8          | 1.30 V                   | 360                        | 59.18                  | -2.98                          |
| 2                                                   | 2320.00        | 47.6 AV                       | 54.0              | -6.4           | 1.30 V                   | 360                        | 50.58                  | -2.98                          |
| 3                                                   | 2390.00        | 70.0 PK                       | 74.0              | -4.0           | 1.30 V                   | 360                        | 72.89                  | -2.89                          |
| 4                                                   | 2390.00        | 53.6 AV                       | 54.0              | -0.4           | 1.30 V                   | 360                        | 56.49                  | -2.89                          |
| 5                                                   | *2412.00       | 112.8 PK                      |                   |                | 1.03 V                   | 360                        | 115.65                 | -2.85                          |
| 6                                                   | *2412.00       | 104.6 AV                      |                   |                | 1.03 V                   | 360                        | 107.45                 | -2.85                          |
| 7                                                   | 4824.00        | 52.4 PK                       | 74.0              | -21.6          | 1.19 V                   | 360                        | 46.18                  | 6.22                           |
| 8                                                   | 4824.00        | 40.5 AV                       | 54.0              | -13.5          | 1.19 V                   | 360                        | 34.28                  | 6.22                           |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2390.00        | 54.4 PK                       | 74.0              | -19.6          | 1.26 H                   | 15                         | 57.29                  | -2.89                          |
| 2   | 2390.00        | 44.7 AV                       | 54.0              | -9.3           | 1.26 H                   | 15                         | 47.59                  | -2.89                          |
| 3   | *2437.00       | 108.9 PK                      |                   |                | 1.30 H                   | 31                         | 111.69                 | -2.79                          |
| 4   | *2437.00       | 98.8 AV                       |                   |                | 1.30 H                   | 31                         | 101.59                 | -2.79                          |
| 5   | 2483.50        | 49.4 PK                       | 74.0              | -24.6          | 1.24 H                   | 33                         | 52.07                  | -2.67                          |
| 6   | 2483.50        | 37.9 AV                       | 54.0              | -16.1          | 1.24 H                   | 33                         | 40.57                  | -2.67                          |
| 7   | 4874.00        | 51.6 PK                       | 74.0              | -22.4          | 1.04 H                   | 335                        | 45.34                  | 6.26                           |
| 8   | 4874.00        | 39.7 AV                       | 54.0              | -14.3          | 1.04 H                   | 335                        | 33.44                  | 6.26                           |
| 9   | 7311.00        | 58.1 PK                       | 74.0              | -15.9          | 1.36 H                   | 22                         | 46.90                  | 11.20                          |
| 10  | 7311.00        | 45.3 AV                       | 54.0              | -8.7           | 1.36 H                   | 22                         | 34.10                  | 11.20                          |

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2390.00        | 63.0 PK                       | 74.0              | -11.0          | 1.27 V                   | 360                        | 65.89                  | -2.89                          |
| 2   | 2390.00        | 53.6 AV                       | 54.0              | -0.4           | 1.27 V                   | 360                        | 56.49                  | -2.89                          |
| 3   | *2437.00       | 117.9 PK                      |                   |                | 1.25 V                   | 350                        | 120.69                 | -2.79                          |
| 4   | *2437.00       | 108.3 AV                      |                   |                | 1.25 V                   | 350                        | 111.09                 | -2.79                          |
| 5   | 2483.50        | 60.1 PK                       | 74.0              | -13.9          | 1.51 V                   | 360                        | 62.77                  | -2.67                          |
| 6   | 2483.50        | 48.4 AV                       | 54.0              | -5.6           | 1.51 V                   | 360                        | 51.07                  | -2.67                          |
| 7   | 4874.00        | 52.7 PK                       | 74.0              | -21.3          | 1.24 V                   | 360                        | 46.44                  | 6.26                           |
| 8   | 4874.00        | 40.9 AV                       | 54.0              | -13.1          | 1.24 V                   | 360                        | 34.64                  | 6.26                           |
| 9   | 7311.00        | 57.5 PK                       | 74.0              | -16.5          | 1.03 V                   | 356                        | 46.30                  | 11.20                          |
| 10  | 7311.00        | 45.2 AV                       | 54.0              | -8.8           | 1.03 V                   | 356                        | 34.00                  | 11.20                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |               |                              |              |
|------------------------|---------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 11 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz  |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 104.4 PK                      |                   |                | 1.30 H                   | 35                         | 107.12                 | -2.72                          |
| 2                                                   | *2462.00       | 95.8 AV                       |                   |                | 1.30 H                   | 35                         | 98.52                  | -2.72                          |
| 3                                                   | 2483.50        | 57.9 PK                       | 74.0              | -16.1          | 1.20 H                   | 11                         | 60.57                  | -2.67                          |
| 4                                                   | 2483.50        | 44.6 AV                       | 54.0              | -9.4           | 1.20 H                   | 11                         | 47.27                  | -2.67                          |
| 5                                                   | 4924.00        | 52.0 PK                       | 74.0              | -22.0          | 1.02 H                   | 343                        | 45.75                  | 6.25                           |
| 6                                                   | 4924.00        | 39.9 AV                       | 54.0              | -14.1          | 1.02 H                   | 343                        | 33.65                  | 6.25                           |
| 7                                                   | 7386.00        | 58.4 PK                       | 74.0              | -15.6          | 1.36 H                   | 16                         | 46.79                  | 11.61                          |
| 8                                                   | 7386.00        | 45.4 AV                       | 54.0              | -8.6           | 1.36 H                   | 16                         | 33.79                  | 11.61                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2462.00       | 113.4 PK                      |                   |                | 1.52 V                   | 360                        | 116.12                 | -2.72                          |
| 2                                                   | *2462.00       | 105.3 AV                      |                   |                | 1.52 V                   | 360                        | 108.02                 | -2.72                          |
| 3                                                   | 2483.50        | 66.0 PK                       | 74.0              | -8.0           | 1.50 V                   | 360                        | 68.67                  | -2.67                          |
| 4                                                   | 2483.50        | 53.7 AV                       | 54.0              | -0.3           | 1.50 V                   | 360                        | 56.37                  | -2.67                          |
| 5                                                   | 4924.00        | 53.4 PK                       | 74.0              | -20.6          | 1.16 V                   | 351                        | 47.15                  | 6.25                           |
| 6                                                   | 4924.00        | 41.4 AV                       | 54.0              | -12.6          | 1.16 V                   | 351                        | 35.15                  | 6.25                           |
| 7                                                   | 7386.00        | 58.1 PK                       | 74.0              | -15.9          | 1.07 V                   | 360                        | 46.49                  | 11.61                          |
| 8                                                   | 7386.00        | 45.5 AV                       | 54.0              | -8.5           | 1.07 V                   | 360                        | 33.89                  | 11.61                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11n (HT40)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2320.00        | 42.8 PK                       | 74.0              | -31.2          | 1.35 H                   | 12                         | 45.78                  | -2.98                          |
| 2                                                   | 2320.00        | 39.0 AV                       | 54.0              | -15.0          | 1.35 H                   | 12                         | 41.98                  | -2.98                          |
| 3                                                   | 2390.00        | 57.8 PK                       | 74.0              | -16.2          | 1.30 H                   | 21                         | 60.69                  | -2.89                          |
| 4                                                   | 2390.00        | 44.9 AV                       | 54.0              | -9.1           | 1.30 H                   | 21                         | 47.79                  | -2.89                          |
| 5                                                   | *2422.00       | 99.2 PK                       |                   |                | 1.29 H                   | 14                         | 102.03                 | -2.83                          |
| 6                                                   | *2422.00       | 90.5 AV                       |                   |                | 1.29 H                   | 14                         | 93.33                  | -2.83                          |
| 7                                                   | 4844.00        | 51.7 PK                       | 74.0              | -22.3          | 1.09 H                   | 327                        | 45.47                  | 6.23                           |
| 8                                                   | 4844.00        | 39.5 AV                       | 54.0              | -14.5          | 1.09 H                   | 327                        | 33.27                  | 6.23                           |
| 9                                                   | 7266.00        | 58.3 PK                       | 74.0              | -15.7          | 1.35 H                   | 9                          | 47.12                  | 11.18                          |
| 10                                                  | 7266.00        | 45.6 AV                       | 54.0              | -8.4           | 1.35 H                   | 9                          | 34.42                  | 11.18                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2320.00        | 53.2 PK                       | 74.0              | -20.8          | 1.04 V                   | 360                        | 56.18                  | -2.98                          |
| 2                                                   | 2320.00        | 48.0 AV                       | 54.0              | -6.0           | 1.04 V                   | 360                        | 50.98                  | -2.98                          |
| 3                                                   | 2390.00        | 66.5 PK                       | 74.0              | -7.5           | 1.04 V                   | 360                        | 69.39                  | -2.89                          |
| 4                                                   | 2390.00        | 53.7 AV                       | 54.0              | -0.3           | 1.04 V                   | 360                        | 56.59                  | -2.89                          |
| 5                                                   | *2422.00       | 108.1 PK                      |                   |                | 1.55 V                   | 360                        | 110.93                 | -2.83                          |
| 6                                                   | *2422.00       | 99.7 AV                       |                   |                | 1.55 V                   | 360                        | 102.53                 | -2.83                          |
| 7                                                   | 4844.00        | 53.5 PK                       | 74.0              | -20.5          | 1.21 V                   | 360                        | 47.27                  | 6.23                           |
| 8                                                   | 4844.00        | 41.3 AV                       | 54.0              | -12.7          | 1.21 V                   | 360                        | 35.07                  | 6.23                           |
| 9                                                   | 7266.00        | 58.4 PK                       | 74.0              | -15.6          | 1.04 V                   | 360                        | 47.22                  | 11.18                          |
| 10                                                  | 7266.00        | 45.7 AV                       | 54.0              | -8.3           | 1.04 V                   | 360                        | 34.52                  | 11.18                          |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

# ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2390.00        | 56.5 PK                       | 74.0              | -17.5          | 1.22 H                   | 15                         | 59.39                  | -2.89                          |
| 2   | 2390.00        | 44.7 AV                       | 54.0              | -9.3           | 1.22 H                   | 15                         | 47.59                  | -2.89                          |
| 3   | *2437.00       | 102.7 PK                      |                   |                | 1.20 H                   | 15                         | 105.49                 | -2.79                          |
| 4   | *2437.00       | 94.2 AV                       |                   |                | 1.20 H                   | 15                         | 96.99                  | -2.79                          |
| 5   | 2483.50        | 49.1 PK                       | 74.0              | -24.9          | 1.23 H                   | 12                         | 51.77                  | -2.67                          |
| 6   | 2483.50        | 37.4 AV                       | 54.0              | -16.6          | 1.23 H                   | 12                         | 40.07                  | -2.67                          |
| 7   | 4874.00        | 51.9 PK                       | 74.0              | -22.1          | 1.01 H                   | 333                        | 45.64                  | 6.26                           |
| 8   | 4874.00        | 40.0 AV                       | 54.0              | -14.0          | 1.01 H                   | 333                        | 33.74                  | 6.26                           |
| 9   | 7311.00        | 58.4 PK                       | 74.0              | -15.6          | 1.35 H                   | 17                         | 47.20                  | 11.20                          |
| 10  | 7311.00        | 45.6 AV                       | 54.0              | -8.4           | 1.35 H                   | 17                         | 34.40                  | 11.20                          |

# ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2390.00        | 65.0 PK                       | 74.0              | -9.0           | 1.22 V                   | 360                        | 67.89                  | -2.89                          |
| 2   | 2390.00        | 53.4 AV                       | 54.0              | -0.6           | 1.22 V                   | 360                        | 56.29                  | -2.89                          |
| 3   | *2437.00       | 111.6 PK                      |                   |                | 1.41 V                   | 360                        | 114.39                 | -2.79                          |
| 4   | *2437.00       | 103.4 AV                      |                   |                | 1.41 V                   | 360                        | 106.19                 | -2.79                          |
| 5   | 2483.50        | 57.1 PK                       | 74.0              | -16.9          | 1.38 V                   | 360                        | 59.77                  | -2.67                          |
| 6   | 2483.50        | 46.4 AV                       | 54.0              | -7.6           | 1.38 V                   | 360                        | 49.07                  | -2.67                          |
| 7   | 4874.00        | 52.3 PK                       | 74.0              | -21.7          | 1.14 V                   | 352                        | 46.04                  | 6.26                           |
| 8   | 4874.00        | 40.5 AV                       | 54.0              | -13.5          | 1.14 V                   | 352                        | 34.24                  | 6.26                           |
| 9   | 7311.00        | 58.2 PK                       | 74.0              | -15.8          | 1.04 V                   | 360                        | 47.00                  | 11.20                          |
| 10  | 7311.00        | 45.5 AV                       | 54.0              | -8.5           | 1.04 V                   | 360                        | 34.30                  | 11.20                          |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                        |              |                              |              |
|------------------------|--------------|------------------------------|--------------|
| <b>CHANNEL</b>         | TX Channel 9 | <b>DETECTOR<br/>FUNCTION</b> | Peak (PK)    |
| <b>FREQUENCY RANGE</b> | 1GHz ~ 25GHz |                              | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 100.6 PK                      |                   |                | 1.28 H                   | 36                         | 103.35                 | -2.75                          |
| 2                                                   | *2452.00       | 91.9 AV                       |                   |                | 1.28 H                   | 36                         | 94.65                  | -2.75                          |
| 3                                                   | 2483.50        | 55.3 PK                       | 74.0              | -18.7          | 1.32 H                   | 12                         | 57.97                  | -2.67                          |
| 4                                                   | 2483.50        | 44.4 AV                       | 54.0              | -9.6           | 1.32 H                   | 12                         | 47.07                  | -2.67                          |
| 5                                                   | 4904.00        | 52.0 PK                       | 74.0              | -22.0          | 1.04 H                   | 351                        | 45.72                  | 6.28                           |
| 6                                                   | 4904.00        | 39.8 AV                       | 54.0              | -14.2          | 1.04 H                   | 351                        | 33.52                  | 6.28                           |
| 7                                                   | 7356.00        | 57.3 PK                       | 74.0              | -16.7          | 1.38 H                   | 36                         | 45.85                  | 11.45                          |
| 8                                                   | 7356.00        | 44.8 AV                       | 54.0              | -9.2           | 1.38 H                   | 36                         | 33.35                  | 11.45                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | *2452.00       | 109.5 PK                      |                   |                | 1.65 V                   | 360                        | 112.25                 | -2.75                          |
| 2                                                   | *2452.00       | 101.1 AV                      |                   |                | 1.65 V                   | 360                        | 103.85                 | -2.75                          |
| 3                                                   | 2483.50        | 63.2 PK                       | 74.0              | -10.8          | 1.51 V                   | 360                        | 65.87                  | -2.67                          |
| 4                                                   | 2483.50        | 53.4 AV                       | 54.0              | -0.6           | 1.51 V                   | 360                        | 56.07                  | -2.67                          |
| 5                                                   | 4904.00        | 52.8 PK                       | 74.0              | -21.2          | 1.23 V                   | 357                        | 46.52                  | 6.28                           |
| 6                                                   | 4904.00        | 41.0 AV                       | 54.0              | -13.0          | 1.23 V                   | 357                        | 34.72                  | 6.28                           |
| 7                                                   | 7356.00        | 57.7 PK                       | 74.0              | -16.3          | 1.07 V                   | 347                        | 46.25                  | 11.45                          |
| 8                                                   | 7356.00        | 45.4 AV                       | 54.0              | -8.6           | 1.07 V                   | 347                        | 33.95                  | 11.45                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 2TX Mode

### 802.11n (HT20)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 1 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 56.2 PK                       | 74.0              | -17.8          | 1.19 H                   | 11                         | 59.09                  | -2.89                          |
| 2                                                   | 2390.00        | 43.2 AV                       | 54.0              | -10.8          | 1.19 H                   | 11                         | 46.09                  | -2.89                          |
| 3                                                   | *2412.00       | 106.9 PK                      |                   |                | 1.19 H                   | 11                         | 109.75                 | -2.85                          |
| 4                                                   | *2412.00       | 95.9 AV                       |                   |                | 1.19 H                   | 11                         | 98.75                  | -2.85                          |
| 5                                                   | 2500.00        | 59.2 PK                       | 74.0              | -14.8          | 1.21 H                   | 138                        | 61.83                  | -2.63                          |
| 6                                                   | 2500.00        | 50.3 AV                       | 54.0              | -3.7           | 1.21 H                   | 138                        | 52.93                  | -2.63                          |
| 7                                                   | 4824.00        | 47.0 PK                       | 74.0              | -27.0          | 1.04 H                   | 337                        | 40.78                  | 6.22                           |
| 8                                                   | 4824.00        | 38.4 AV                       | 54.0              | -15.6          | 1.04 H                   | 337                        | 32.18                  | 6.22                           |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 68.1 PK                       | 74.0              | -5.9           | 1.42 V                   | 360                        | 70.99                  | -2.89                          |
| 2                                                   | 2390.00        | 53.8 AV                       | 54.0              | -0.2           | 1.42 V                   | 360                        | 56.69                  | -2.89                          |
| 3                                                   | *2412.00       | 115.7 PK                      |                   |                | 1.42 V                   | 360                        | 118.55                 | -2.85                          |
| 4                                                   | *2412.00       | 104.2 AV                      |                   |                | 1.42 V                   | 360                        | 107.05                 | -2.85                          |
| 5                                                   | 2500.00        | 62.8 PK                       | 74.0              | -11.2          | 1.17 V                   | 360                        | 65.43                  | -2.63                          |
| 6                                                   | 2500.00        | 53.6 AV                       | 54.0              | -0.4           | 1.17 V                   | 360                        | 56.23                  | -2.63                          |
| 7                                                   | 4824.00        | 52.4 PK                       | 74.0              | -21.6          | 1.05 V                   | 347                        | 46.18                  | 6.22                           |
| 8                                                   | 4824.00        | 49.2 AV                       | 54.0              | -4.8           | 1.05 V                   | 347                        | 42.98                  | 6.22                           |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.



|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

#### ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2357.00        | 52.4 PK                       | 74.0              | -21.6          | 1.19 H                   | 24                         | 55.34                  | -2.94                          |
| 2   | 2357.00        | 40.2 AV                       | 54.0              | -13.8          | 1.19 H                   | 24                         | 43.14                  | -2.94                          |
| 3   | *2437.00       | 110.0 PK                      |                   |                | 1.19 H                   | 24                         | 112.79                 | -2.79                          |
| 4   | *2437.00       | 99.4 AV                       |                   |                | 1.19 H                   | 24                         | 102.19                 | -2.79                          |
| 5   | 2500.00        | 58.3 PK                       | 74.0              | -15.7          | 1.16 H                   | 137                        | 60.93                  | -2.63                          |
| 6   | 2500.00        | 49.6 AV                       | 54.0              | -4.4           | 1.16 H                   | 137                        | 52.23                  | -2.63                          |
| 7   | 4874.00        | 47.2 PK                       | 74.0              | -26.8          | 1.04 H                   | 341                        | 40.94                  | 6.26                           |
| 8   | 4874.00        | 38.4 AV                       | 54.0              | -15.6          | 1.04 H                   | 341                        | 32.14                  | 6.26                           |
| 9   | 7311.00        | 43.4 PK                       | 74.0              | -30.6          | 1.35 H                   | 35                         | 32.20                  | 11.20                          |
| 10  | 7311.00        | 34.6 AV                       | 54.0              | -19.4          | 1.35 H                   | 35                         | 23.40                  | 11.20                          |

#### ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | 2357.00        | 60.4 PK                       | 74.0              | -13.6          | 1.21 V                   | 27                         | 63.34                  | -2.94                          |
| 2   | 2357.00        | 48.7 AV                       | 54.0              | -5.3           | 1.21 V                   | 27                         | 51.64                  | -2.94                          |
| 3   | *2437.00       | 118.7 PK                      |                   |                | 1.16 V                   | 5                          | 121.49                 | -2.79                          |
| 4   | *2437.00       | 107.3 AV                      |                   |                | 1.16 V                   | 5                          | 110.09                 | -2.79                          |
| 5   | 2500.00        | 62.3 PK                       | 74.0              | -11.7          | 1.18 V                   | 1                          | 64.93                  | -2.63                          |
| 6   | 2500.00        | 53.0 AV                       | 54.0              | -1.0           | 1.18 V                   | 1                          | 55.63                  | -2.63                          |
| 7   | 4874.00        | 53.4 PK                       | 74.0              | -20.6          | 1.03 V                   | 319                        | 47.14                  | 6.26                           |
| 8   | 4874.00        | 50.8 AV                       | 54.0              | -3.2           | 1.03 V                   | 319                        | 44.54                  | 6.26                           |
| 9   | 7311.00        | 52.3 PK                       | 74.0              | -21.7          | 1.22 V                   | 360                        | 41.10                  | 11.20                          |
| 10  | 7311.00        | 44.6 AV                       | 54.0              | -9.4           | 1.22 V                   | 360                        | 33.40                  | 11.20                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |               |                      |              |
|-----------------|---------------|----------------------|--------------|
| CHANNEL         | TX Channel 11 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz  |                      | Average (AV) |

# ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | *2462.00       | 106.3 PK                      |                   |                | 1.17 H                   | 16                         | 109.02                 | -2.72                          |
| 2   | *2462.00       | 95.5 AV                       |                   |                | 1.17 H                   | 16                         | 98.22                  | -2.72                          |
| 3   | 2483.50        | 57.2 PK                       | 74.0              | -16.8          | 1.17 H                   | 16                         | 59.87                  | -2.67                          |
| 4   | 2483.50        | 43.2 AV                       | 54.0              | -10.8          | 1.17 H                   | 16                         | 45.87                  | -2.67                          |
| 5   | 2500.00        | 59.4 PK                       | 74.0              | -14.6          | 1.21 H                   | 138                        | 62.03                  | -2.63                          |
| 6   | 2500.00        | 50.6 AV                       | 54.0              | -3.4           | 1.21 H                   | 138                        | 53.23                  | -2.63                          |
| 7   | 4924.00        | 47.4 PK                       | 74.0              | -26.6          | 1.03 H                   | 332                        | 41.15                  | 6.25                           |
| 8   | 4924.00        | 38.6 AV                       | 54.0              | -15.4          | 1.03 H                   | 332                        | 32.35                  | 6.25                           |
| 9   | 7386.00        | 42.2 PK                       | 74.0              | -31.8          | 1.31 H                   | 22                         | 30.59                  | 11.61                          |
| 10  | 7386.00        | 33.2 AV                       | 54.0              | -20.8          | 1.31 H                   | 22                         | 21.59                  | 11.61                          |

# ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | *2462.00       | 115.4 PK                      |                   |                | 1.41 V                   | 6                          | 118.12                 | -2.72                          |
| 2   | *2462.00       | 104.1 AV                      |                   |                | 1.41 V                   | 6                          | 106.82                 | -2.72                          |
| 3   | 2483.50        | 67.8 PK                       | 74.0              | -6.2           | 1.11 V                   | 27                         | 70.47                  | -2.67                          |
| 4   | 2483.50        | 53.7 AV                       | 54.0              | -0.3           | 1.11 V                   | 27                         | 56.37                  | -2.67                          |
| 5   | 2500.00        | 62.1 PK                       | 74.0              | -11.9          | 1.18 V                   | 6                          | 64.73                  | -2.63                          |
| 6   | 2500.00        | 53.4 AV                       | 54.0              | -0.6           | 1.18 V                   | 6                          | 56.03                  | -2.63                          |
| 7   | 4924.00        | 51.0 PK                       | 74.0              | -23.0          | 1.01 V                   | 307                        | 44.75                  | 6.25                           |
| 8   | 4924.00        | 48.3 AV                       | 54.0              | -5.7           | 1.01 V                   | 307                        | 42.05                  | 6.25                           |
| 9   | 7386.00        | 51.2 PK                       | 74.0              | -22.8          | 1.20 V                   | 360                        | 39.59                  | 11.61                          |
| 10  | 7386.00        | 43.1 AV                       | 54.0              | -10.9          | 1.20 V                   | 360                        | 31.49                  | 11.61                          |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 802.11n (HT40)

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 3 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.8 PK                       | 74.0              | -15.2          | 1.12 H                   | 17                         | 61.69                  | -2.89                          |
| 2                                                   | 2390.00        | 45.2 AV                       | 54.0              | -8.8           | 1.12 H                   | 17                         | 48.09                  | -2.89                          |
| 3                                                   | *2422.00       | 102.4 PK                      |                   |                | 1.12 H                   | 17                         | 105.23                 | -2.83                          |
| 4                                                   | *2422.00       | 91.4 AV                       |                   |                | 1.12 H                   | 17                         | 94.23                  | -2.83                          |
| 5                                                   | 2500.00        | 59.2 PK                       | 74.0              | -14.8          | 1.21 H                   | 138                        | 61.83                  | -2.63                          |
| 6                                                   | 2500.00        | 50.2 AV                       | 54.0              | -3.8           | 1.21 H                   | 138                        | 52.83                  | -2.63                          |
| 7                                                   | 4844.00        | 52.0 PK                       | 74.0              | -22.0          | 1.05 H                   | 339                        | 45.77                  | 6.23                           |
| 8                                                   | 4844.00        | 39.8 AV                       | 54.0              | -14.2          | 1.05 H                   | 339                        | 33.57                  | 6.23                           |
| 9                                                   | 7266.00        | 57.6 PK                       | 74.0              | -16.4          | 1.33 H                   | 27                         | 46.42                  | 11.18                          |
| 10                                                  | 7266.00        | 44.7 AV                       | 54.0              | -9.3           | 1.33 H                   | 27                         | 33.52                  | 11.18                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 66.2 PK                       | 74.0              | -7.8           | 1.20 V                   | 2                          | 69.09                  | -2.89                          |
| 2                                                   | 2390.00        | 53.5 AV                       | 54.0              | -0.5           | 1.20 V                   | 2                          | 56.39                  | -2.89                          |
| 3                                                   | *2422.00       | 110.3 PK                      |                   |                | 1.45 V                   | 4                          | 113.13                 | -2.83                          |
| 4                                                   | *2422.00       | 99.1 AV                       |                   |                | 1.45 V                   | 4                          | 101.93                 | -2.83                          |
| 5                                                   | 2500.00        | 62.1 PK                       | 74.0              | -11.9          | 1.16 V                   | 360                        | 64.73                  | -2.63                          |
| 6                                                   | 2500.00        | 52.9 AV                       | 54.0              | -1.1           | 1.16 V                   | 360                        | 55.53                  | -2.63                          |
| 7                                                   | 4844.00        | 53.4 PK                       | 74.0              | -20.6          | 1.15 V                   | 342                        | 47.17                  | 6.23                           |
| 8                                                   | 4844.00        | 41.2 AV                       | 54.0              | -12.8          | 1.15 V                   | 342                        | 34.97                  | 6.23                           |
| 9                                                   | 7266.00        | 57.9 PK                       | 74.0              | -16.1          | 1.08 V                   | 360                        | 46.72                  | 11.18                          |
| 10                                                  | 7266.00        | 45.3 AV                       | 54.0              | -8.7           | 1.08 V                   | 360                        | 34.12                  | 11.18                          |

## REMARKS:

- Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
- Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
- The other emission levels were very low against the limit.
- Margin value = Emission Level – Limit value
- " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 58.4 PK                       | 74.0              | -15.6          | 1.14 H                   | 20                         | 61.29                  | -2.89                          |
| 2                                                   | 2390.00        | 43.0 AV                       | 54.0              | -11.0          | 1.14 H                   | 20                         | 45.89                  | -2.89                          |
| 3                                                   | *2437.00       | 104.3 PK                      |                   |                | 1.14 H                   | 20                         | 107.09                 | -2.79                          |
| 4                                                   | *2437.00       | 94.2 AV                       |                   |                | 1.14 H                   | 20                         | 96.99                  | -2.79                          |
| 5                                                   | 2483.50        | 53.3 PK                       | 74.0              | -20.7          | 1.14 H                   | 20                         | 55.97                  | -2.67                          |
| 6                                                   | 2483.50        | 41.3 AV                       | 54.0              | -12.7          | 1.14 H                   | 20                         | 43.97                  | -2.67                          |
| 7                                                   | 2500.00        | 58.9 PK                       | 74.0              | -15.1          | 1.25 H                   | 116                        | 61.53                  | -2.63                          |
| 8                                                   | 2500.00        | 50.0 AV                       | 54.0              | -4.0           | 1.25 H                   | 116                        | 52.63                  | -2.63                          |
| 9                                                   | 4874.00        | 52.3 PK                       | 74.0              | -21.7          | 1.05 H                   | 324                        | 46.04                  | 6.26                           |
| 10                                                  | 4874.00        | 40.2 AV                       | 54.0              | -13.8          | 1.05 H                   | 324                        | 33.94                  | 6.26                           |
| 11                                                  | 7311.00        | 59.4 PK                       | 74.0              | -14.6          | 1.36 H                   | 6                          | 48.20                  | 11.20                          |
| 12                                                  | 7311.00        | 46.3 AV                       | 54.0              | -7.7           | 1.36 H                   | 6                          | 35.10                  | 11.20                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 2390.00        | 66.3 PK                       | 74.0              | -7.7           | 1.19 V                   | 3                          | 69.19                  | -2.89                          |
| 2                                                   | 2390.00        | 51.5 AV                       | 54.0              | -2.5           | 1.19 V                   | 3                          | 54.39                  | -2.89                          |
| 3                                                   | *2437.00       | 115.1 PK                      |                   |                | 1.39 V                   | 4                          | 117.89                 | -2.79                          |
| 4                                                   | *2437.00       | 103.0 AV                      |                   |                | 1.39 V                   | 4                          | 105.79                 | -2.79                          |
| 5                                                   | 2483.50        | 61.2 PK                       | 74.0              | -12.8          | 1.33 V                   | 5                          | 63.87                  | -2.67                          |
| 6                                                   | 2483.50        | 49.3 AV                       | 54.0              | -4.7           | 1.33 V                   | 5                          | 51.97                  | -2.67                          |
| 7                                                   | 2500.00        | 62.4 PK                       | 74.0              | -11.6          | 1.20 V                   | 360                        | 65.03                  | -2.63                          |
| 8                                                   | 2500.00        | 53.4 AV                       | 54.0              | -0.6           | 1.20 V                   | 360                        | 56.03                  | -2.63                          |
| 9                                                   | 4874.00        | 54.6 PK                       | 74.0              | -19.4          | 1.19 V                   | 349                        | 48.34                  | 6.26                           |
| 10                                                  | 4874.00        | 42.3 AV                       | 54.0              | -11.7          | 1.19 V                   | 349                        | 36.04                  | 6.26                           |
| 11                                                  | 7311.00        | 59.3 PK                       | 74.0              | -14.7          | 1.05 V                   | 360                        | 48.10                  | 11.20                          |
| 12                                                  | 7311.00        | 46.4 AV                       | 54.0              | -7.6           | 1.05 V                   | 360                        | 35.20                  | 11.20                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

|                 |              |                      |              |
|-----------------|--------------|----------------------|--------------|
| CHANNEL         | TX Channel 9 | DETECTOR<br>FUNCTION | Peak (PK)    |
| FREQUENCY RANGE | 1GHz ~ 25GHz |                      | Average (AV) |

# ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | *2452.00       | 101.6 PK                      |                   |                | 1.09 H                   | 7                          | 104.35                 | -2.75                          |
| 2   | *2452.00       | 90.8 AV                       |                   |                | 1.09 H                   | 7                          | 93.55                  | -2.75                          |
| 3   | 2483.50        | 60.2 PK                       | 74.0              | -13.8          | 1.09 H                   | 7                          | 62.87                  | -2.67                          |
| 4   | 2483.50        | 45.9 AV                       | 54.0              | -8.1           | 1.09 H                   | 7                          | 48.57                  | -2.67                          |
| 5   | 2500.00        | 58.3 PK                       | 74.0              | -15.7          | 1.16 H                   | 141                        | 60.93                  | -2.63                          |
| 6   | 2500.00        | 49.8 AV                       | 54.0              | -4.2           | 1.16 H                   | 141                        | 52.43                  | -2.63                          |
| 7   | 4904.00        | 51.4 PK                       | 74.0              | -22.6          | 1.02 H                   | 334                        | 45.12                  | 6.28                           |
| 8   | 4904.00        | 39.5 AV                       | 54.0              | -14.5          | 1.02 H                   | 334                        | 33.22                  | 6.28                           |
| 9   | 7356.00        | 58.1 PK                       | 74.0              | -15.9          | 1.34 H                   | 1                          | 46.65                  | 11.45                          |
| 10  | 7356.00        | 45.1 AV                       | 54.0              | -8.9           | 1.34 H                   | 1                          | 33.65                  | 11.45                          |

# ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M

| NO. | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
|-----|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| 1   | *2452.00       | 112.4 PK                      |                   |                | 1.11 V                   | 4                          | 115.15                 | -2.75                          |
| 2   | *2452.00       | 100.9 AV                      |                   |                | 1.11 V                   | 4                          | 103.65                 | -2.75                          |
| 3   | 2483.50        | 68.3 PK                       | 74.0              | -5.7           | 1.36 V                   | 4                          | 70.97                  | -2.67                          |
| 4   | 2483.50        | 53.9 AV                       | 54.0              | -0.1           | 1.36 V                   | 4                          | 56.57                  | -2.67                          |
| 5   | 2500.00        | 62.2 PK                       | 74.0              | -11.8          | 1.14 V                   | 360                        | 64.83                  | -2.63                          |
| 6   | 2500.00        | 53.0 AV                       | 54.0              | -1.0           | 1.14 V                   | 360                        | 55.63                  | -2.63                          |
| 7   | 4904.00        | 53.1 PK                       | 74.0              | -20.9          | 1.19 V                   | 360                        | 46.82                  | 6.28                           |
| 8   | 4904.00        | 41.2 AV                       | 54.0              | -12.8          | 1.19 V                   | 360                        | 34.92                  | 6.28                           |
| 9   | 7356.00        | 58.2 PK                       | 74.0              | -15.8          | 1.02 V                   | 360                        | 46.75                  | 11.45                          |
| 10  | 7356.00        | 45.4 AV                       | 54.0              | -8.6           | 1.02 V                   | 360                        | 33.95                  | 11.45                          |

## REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " \* ": Fundamental frequency.

## 2TX Mode

### Below 1GHz Data

#### 802.11n (HT20)

|                 |              |                      |                 |
|-----------------|--------------|----------------------|-----------------|
| CHANNEL         | TX Channel 6 | DETECTOR<br>FUNCTION | Quasi-Peak (QP) |
| FREQUENCY RANGE | 30MHz ~ 1GHz |                      |                 |

| ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M |                |                               |                   |                |                          |                            |                        |                                |
|-----------------------------------------------------|----------------|-------------------------------|-------------------|----------------|--------------------------|----------------------------|------------------------|--------------------------------|
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 125.11         | 33.2 QP                       | 43.5              | -10.4          | 1.32 H                   | 220                        | 48.00                  | -14.85                         |
| 2                                                   | 175.11         | 34.3 QP                       | 43.5              | -9.3           | 1.68 H                   | 195                        | 48.11                  | -13.86                         |
| 3                                                   | 249.54         | 42.4 QP                       | 46.0              | -3.6           | 1.31 H                   | 195                        | 56.38                  | -14.02                         |
| 4                                                   | 374.71         | 37.7 QP                       | 46.0              | -8.4           | 1.26 H                   | 238                        | 47.63                  | -9.98                          |
| 5                                                   | 500.11         | 35.4 QP                       | 46.0              | -10.7          | 1.00 H                   | 116                        | 42.18                  | -6.83                          |
| 6                                                   | 749.82         | 38.5 QP                       | 46.0              | -7.5           | 1.36 H                   | 251                        | 39.70                  | -1.21                          |
| ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M   |                |                               |                   |                |                          |                            |                        |                                |
| NO.                                                 | FREQ.<br>(MHz) | EMISSION<br>LEVEL<br>(dBuV/m) | LIMIT<br>(dBuV/m) | MARGIN<br>(dB) | ANTENNA<br>HEIGHT<br>(m) | TABLE<br>ANGLE<br>(Degree) | RAW<br>VALUE<br>(dBuV) | CORRECTION<br>FACTOR<br>(dB/m) |
| 1                                                   | 34.41          | 36.1 QP                       | 40.0              | -3.9           | 1.72 V                   | 115                        | 50.20                  | -14.12                         |
| 2                                                   | 66.52          | 33.2 QP                       | 40.0              | -6.8           | 1.69 V                   | 256                        | 47.79                  | -14.55                         |
| 3                                                   | 209.76         | 36.7 QP                       | 43.5              | -6.8           | 1.61 V                   | 234                        | 52.75                  | -16.03                         |
| 4                                                   | 249.76         | 37.1 QP                       | 46.0              | -8.9           | 1.63 V                   | 268                        | 51.10                  | -14.02                         |
| 5                                                   | 400.11         | 38.4 QP                       | 46.0              | -7.6           | 1.58 V                   | 237                        | 47.83                  | -9.39                          |
| 6                                                   | 424.45         | 41.1 QP                       | 46.0              | -4.9           | 1.36 V                   | 214                        | 49.63                  | -8.51                          |

#### REMARKS:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value

## 4.2 Conducted Emission Measurement

### 4.2.1 Limits of Conducted Emission Measurement

| Frequency (MHz) | Conducted Limit (dBuV) |         |
|-----------------|------------------------|---------|
|                 | Quasi-peak             | Average |
| 0.15 - 0.5      | 66 - 56                | 56 - 46 |
| 0.50 - 5.0      | 56                     | 46      |
| 5.0 - 30.0      | 60                     | 50      |

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2.2 Test Instruments

| DESCRIPTION & MANUFACTURER                                                     | MODEL NO.                   | SERIAL NO. | CALIBRATED DATE | CALIBRATED UNTIL |
|--------------------------------------------------------------------------------|-----------------------------|------------|-----------------|------------------|
| Test Receiver<br>ROHDE & SCHWARZ                                               | ESCS 30                     | 100375     | Apr. 29, 2014   | Apr. 28, 2015    |
| Line-Impedance<br>Stabilization Network<br>(for EUT)<br>SCHWARZBECK            | NSLK-8127                   | 8127-522   | Sep. 15, 2014   | Sep. 14, 2015    |
| Line-Impedance<br>Stabilization Network<br>(for Peripheral)<br>ROHDE & SCHWARZ | ENV216                      | 100071     | Nov. 10, 2014   | Nov. 09, 2015    |
| RF Cable<br>(JYEBAO)                                                           | 5D-FB                       | COCCAB-001 | Mar. 09, 2015   | Mar. 08, 2016    |
| 50 ohms Terminator                                                             | N/A                         | EMC-03     | Sep. 22, 2014   | Sep. 21, 2015    |
| 50 ohms Terminator                                                             | N/A                         | EMC-02     | Sep. 30, 2014   | Sep. 29, 2015    |
| Software<br>ADT                                                                | BV<br>ADT_Cond_V7.3.7.<br>3 | NA         | NA              | NA               |

#### Note:

1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
2. The test was performed in Shielded Room No. C.
3. The VCCI Con C Registration No. is C-3611.
4. Tested Date: Mar. 20, 2015

#### 4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

**NOTE:** The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

#### 4.2.4 Deviation from Test Standard

No deviation.

#### 4.2.5 Test Setup



**Note:** 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

#### 4.2.6 EUT Operating Conditions

Same as 4.1.6.




#### 4.2.7 Test Results (Mode 1)

| Phase | Line (L) | Detector Function | Quasi-Peak (QP) /<br>Average (AV) |
|-------|----------|-------------------|-----------------------------------|
|-------|----------|-------------------|-----------------------------------|

| No | Freq.<br>[MHz] | Corr.  | Reading Value |       | Emission Level |       | Limit     |       | Margin |        |
|----|----------------|--------|---------------|-------|----------------|-------|-----------|-------|--------|--------|
|    |                | Factor | [dB (uV)]     |       | [dB (uV)]      |       | [dB (uV)] |       | (dB)   |        |
|    |                | (dB)   | Q.P.          | AV.   | Q.P.           | AV.   | Q.P.      | AV.   | Q.P.   | AV.    |
| 1  | 0.16953        | 0.08   | 45.48         | 32.66 | 45.56          | 32.74 | 64.98     | 54.98 | -19.42 | -22.24 |
| 2  | 0.29844        | 0.09   | 34.50         | 26.56 | 34.59          | 26.65 | 60.29     | 50.29 | -25.69 | -23.63 |
| 3  | 0.43906        | 0.10   | 24.08         | 12.52 | 24.18          | 12.62 | 57.08     | 47.08 | -32.90 | -34.46 |
| 4  | 0.89219        | 0.12   | 19.00         | 11.46 | 19.12          | 11.58 | 56.00     | 46.00 | -36.88 | -34.42 |
| 5  | 1.73047        | 0.16   | 22.24         | 16.76 | 22.40          | 16.92 | 56.00     | 46.00 | -33.60 | -29.08 |
| 6  | 13.53516       | 0.54   | 24.30         | 19.18 | 24.84          | 19.72 | 60.00     | 50.00 | -35.16 | -30.28 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




|       |             |                   |                                |
|-------|-------------|-------------------|--------------------------------|
| Phase | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|-------------|-------------------|--------------------------------|

| No | Freq.<br>[MHz] | Corr.  | Reading Value |       | Emission Level |       | Limit     |       | Margin |        |
|----|----------------|--------|---------------|-------|----------------|-------|-----------|-------|--------|--------|
|    |                | Factor | [dB (uV)]     |       | [dB (uV)]      |       | [dB (uV)] |       | (dB)   |        |
|    |                | (dB)   | Q.P.          | AV.   | Q.P.           | AV.   | Q.P.      | AV.   | Q.P.   | AV.    |
| 1  | 0.16562        | 0.08   | 46.02         | 33.10 | 46.10          | 33.18 | 65.18     | 55.18 | -19.08 | -22.00 |
| 2  | 0.18516        | 0.08   | 41.64         | 25.72 | 41.72          | 25.80 | 64.25     | 54.25 | -22.53 | -28.45 |
| 3  | 0.30234        | 0.09   | 35.24         | 26.12 | 35.33          | 26.21 | 60.18     | 50.18 | -24.85 | -23.97 |
| 4  | 0.45469        | 0.10   | 26.04         | 19.36 | 26.14          | 19.46 | 56.79     | 46.79 | -30.65 | -27.33 |
| 5  | 0.72422        | 0.12   | 25.66         | 21.18 | 25.78          | 21.30 | 56.00     | 46.00 | -30.22 | -24.70 |
| 6  | 22.19922       | 0.79   | 26.98         | 22.50 | 27.77          | 23.29 | 60.00     | 50.00 | -32.23 | -26.71 |

#### REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




#### 4.2.8 Test Results (Mode 2)

| Phase | Line (L) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|----------|-------------------|--------------------------------|
|-------|----------|-------------------|--------------------------------|

| Phase Of Power : Line (L) |                 |                        |                      |       |                       |       |              |       |             |        |
|---------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No                        | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|                           |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1                         | 0.17734         | 0.09                   | 44.28                | 28.22 | 44.37                 | 28.31 | 64.61        | 54.61 | -20.24      | -26.30 |
| 2                         | 0.19297         | 0.09                   | 40.44                | 26.78 | 40.53                 | 26.87 | 63.91        | 53.91 | -23.38      | -27.04 |
| 3                         | 0.35313         | 0.10                   | 28.42                | 17.58 | 28.52                 | 17.68 | 58.89        | 48.89 | -30.37      | -31.21 |
| 4                         | 0.45078         | 0.10                   | 22.24                | 12.70 | 22.34                 | 12.80 | 56.86        | 46.86 | -34.52      | -34.06 |
| 5                         | 2.10547         | 0.17                   | 21.28                | 15.08 | 21.45                 | 15.25 | 56.00        | 46.00 | -34.55      | -30.75 |
| 6                         | 14.09375        | 0.55                   | 23.40                | 18.28 | 23.95                 | 18.83 | 60.00        | 50.00 | -36.05      | -31.17 |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




|       |             |                   |                                |
|-------|-------------|-------------------|--------------------------------|
| Phase | Neutral (N) | Detector Function | Quasi-Peak (QP) / Average (AV) |
|-------|-------------|-------------------|--------------------------------|

| Phase Of Power : Neutral (N) |                 |                        |                      |       |                       |       |              |       |             |        |
|------------------------------|-----------------|------------------------|----------------------|-------|-----------------------|-------|--------------|-------|-------------|--------|
| No                           | Frequency (MHz) | Correction Factor (dB) | Reading Value (dBuV) |       | Emission Level (dBuV) |       | Limit (dBuV) |       | Margin (dB) |        |
|                              |                 |                        | Q.P.                 | AV.   | Q.P.                  | AV.   | Q.P.         | AV.   | Q.P.        | AV.    |
| 1                            | 0.15000         | 0.08                   | 47.06                | 30.16 | 47.14                 | 30.24 | 66.00        | 56.00 | -18.86      | -25.76 |
| 2                            | 0.17344         | 0.08                   | 43.70                | 30.08 | 43.78                 | 30.16 | 64.79        | 54.79 | -21.01      | -24.63 |
| 3                            | 0.29844         | 0.09                   | 34.90                | 25.48 | 34.99                 | 25.57 | 60.29        | 50.29 | -25.30      | -24.72 |
| 4                            | 0.67734         | 0.11                   | 25.00                | 19.26 | 25.11                 | 19.37 | 56.00        | 46.00 | -30.89      | -26.63 |
| 5                            | 0.90781         | 0.13                   | 25.02                | 20.40 | 25.15                 | 20.53 | 56.00        | 46.00 | -30.85      | -25.47 |
| 6                            | 25.04297        | 0.86                   | 26.62                | 21.46 | 27.48                 | 22.32 | 60.00        | 50.00 | -32.52      | -27.68 |

#### Remarks:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level – Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value




### 4.3 6dB Bandwidth Measurement

#### 4.3.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5 MHz.

#### 4.3.2 Test Setup



#### 4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

#### 4.3.4 Test Procedure

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW)  $\geq 3 \times$  RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

#### 4.3.5 Deviation from Test Standard

No deviation.

#### 4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

#### 4.3.7 Test Results (Mode 1)

##### 1TX Mode

##### 802.11b

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 10.10               | 0.5                 | Pass        |
| 6       | 2437            | 10.12               | 0.5                 | Pass        |
| 11      | 2462            | 10.10               | 0.5                 | Pass        |

##### 802.11g

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 16.64               | 0.5                 | Pass        |
| 6       | 2437            | 16.64               | 0.5                 | Pass        |
| 11      | 2462            | 16.65               | 0.5                 | Pass        |

##### 802.11n (HT20)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 17.86               | 0.5                 | Pass        |
| 6       | 2437            | 17.85               | 0.5                 | Pass        |
| 11      | 2462            | 17.87               | 0.5                 | Pass        |

##### 802.11n (HT40)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 3       | 2422            | 36.54               | 0.5                 | Pass        |
| 6       | 2437            | 36.52               | 0.5                 | Pass        |
| 9       | 2452            | 36.53               | 0.5                 | Pass        |

# Spectrum Plot of Worst Value


## 802.11b / CH1




## 802.11g / CH1



## 802.11n (HT20) / CH6



## 802.11n (HT40) / CH6




## 802.11n (HT20)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 |                     |             |
| 1       | 2412            | 17.88               | 17.74   | 0.5                 | Pass        |
| 6       | 2437            | 17.87               | 17.75   | 0.5                 | Pass        |
| 11      | 2462            | 17.88               | 17.79   | 0.5                 | Pass        |

## 802.11n (HT40)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 |                     |             |
| 3       | 2422            | 36.53               | 36.47   | 0.5                 | Pass        |
| 6       | 2437            | 36.50               | 36.43   | 0.5                 | Pass        |
| 9       | 2452            | 36.53               | 36.45   | 0.5                 | Pass        |

### Spectrum Plot of Worst Value





#### 4.3.8 Test Results (Mode 2)

##### 1TX Mode

##### 802.11b

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 10.13               | 0.5                 | Pass        |
| 6       | 2437            | 10.12               | 0.5                 | Pass        |
| 11      | 2462            | 10.12               | 0.5                 | Pass        |

##### 802.11g

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 16.65               | 0.5                 | Pass        |
| 6       | 2437            | 16.65               | 0.5                 | Pass        |
| 11      | 2462            | 16.64               | 0.5                 | Pass        |

##### 802.11n (HT20)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 1       | 2412            | 17.88               | 0.5                 | Pass        |
| 6       | 2437            | 17.87               | 0.5                 | Pass        |
| 11      | 2462            | 17.87               | 0.5                 | Pass        |



##### 802.11n (HT40)

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------------------|-------------|
| 3       | 2422            | 36.57               | 0.5                 | Pass        |
| 6       | 2437            | 36.56               | 0.5                 | Pass        |
| 9       | 2452            | 36.55               | 0.5                 | Pass        |

# Spectrum Plot of Worst Value



802.11b / CH6

802.11g / CH11



802.11n (HT20) / CH6

802.11n (HT40) / CH9



## 2TX Mode

### 802.11n (HT20)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 |                     |             |
| 1       | 2412            | 17.88               | 17.89   | 0.5                 | Pass        |
| 6       | 2437            | 17.85               | 17.87   | 0.5                 | Pass        |
| 11      | 2462            | 17.88               | 17.87   | 0.5                 | Pass        |

### 802.11n (HT40)


| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) |         | Minimum Limit (MHz) | Pass / Fail |
|---------|-----------------|---------------------|---------|---------------------|-------------|
|         |                 | Chain 0             | Chain 1 |                     |             |
| 3       | 2422            | 36.57               | 36.58   | 0.5                 | Pass        |
| 6       | 2437            | 36.57               | 36.58   | 0.5                 | Pass        |
| 9       | 2452            | 36.56               | 36.58   | 0.5                 | Pass        |

## Spectrum Plot of Worst Value

### 802.11n (HT20) \_Chain 0 / CH6



### 802.11n (HT40) \_Chain 0 / CH9



#### 4.4 Conducted Output Power Measurement

##### 4.4.1 Limits of Conducted Output Power Measurement

For systems using digital modulation in the 2400–2483.5 MHz bands: 1 Watt (30dBm)

Per KDB 662911 D01 Multiple Transmitter Output Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for  $NANT \leq 4$ ;

Array Gain = 0 dB (i.e., no array gain) for channel widths  $\geq 40$  MHz for any NANT;

Array Gain =  $5 \log(NANT/NSS)$  dB or 3 dB, whichever is less for 20-MHz channel widths with  $NANT \geq 5$ .

For power measurements on all other devices: Array Gain =  $10 \log(NANT/NSS)$  dB.

##### 4.4.2 Test Setup



##### 4.4.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

##### 4.4.4 Test Procedures

The average power sensor was used on the output port of the EUT. A power meter was used to read the response of the average power sensor. Record the power level.

##### 4.4.5 Deviation from Test Standard

No deviation.

##### 4.4.6 EUT Operating Conditions

Same as Item 4.3.6.

#### 4.4.7 Test Results (Mode 1)

##### 1TX Mode

##### 802.11b

| Chan. | Chan. Freq.<br>(MHz) | Average Power<br>(mW) | Average Power<br>(dBm) | Limit (dBm) | Pass / Fail |
|-------|----------------------|-----------------------|------------------------|-------------|-------------|
| 1     | 2412                 | 105.439               | 20.23                  | 30          | Pass        |
| 6     | 2437                 | 122.744               | 20.89                  | 30          | Pass        |
| 11    | 2462                 | 137.404               | 21.38                  | 30          | Pass        |

##### 802.11g

| Chan. | Chan. Freq.<br>(MHz) | Average Power<br>(mW) | Average Power<br>(dBm) | Limit (dBm) | Pass / Fail |
|-------|----------------------|-----------------------|------------------------|-------------|-------------|
| 1     | 2412                 | 119.124               | 20.76                  | 30          | Pass        |
| 6     | 2437                 | 146.893               | 21.67                  | 30          | Pass        |
| 11    | 2462                 | 89.536                | 19.52                  | 30          | Pass        |

##### 802.11n (HT20)

| Chan. | Chan. Freq.<br>(MHz) | Average Power<br>(mW) | Average Power<br>(dBm) | Limit (dBm) | Pass / Fail |
|-------|----------------------|-----------------------|------------------------|-------------|-------------|
| 1     | 2412                 | 74.302                | 18.71                  | 30          | Pass        |
| 6     | 2437                 | 148.594               | 21.72                  | 30          | Pass        |
| 11    | 2462                 | 88.716                | 19.48                  | 30          | Pass        |

##### 802.11n (HT40)

| Chan. | Chan. Freq.<br>(MHz) | Average Power<br>(mW) | Average Power<br>(dBm) | Limit (dBm) | Pass / Fail |
|-------|----------------------|-----------------------|------------------------|-------------|-------------|
| 3     | 2422                 | 38.637                | 15.87                  | 30          | Pass        |
| 6     | 2437                 | 102.802               | 20.12                  | 30          | Pass        |
| 9     | 2452                 | 35.645                | 15.52                  | 30          | Pass        |

## 2TX Mode

### 802.11n (HT20)

| Chan. | Chan. Freq.<br>(MHz) | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total Power<br>(dBm) | Limit (dBm) | Pass / Fail |
|-------|----------------------|---------------------|---------|------------------------|----------------------|-------------|-------------|
|       |                      | Chain 0             | Chain 1 |                        |                      |             |             |
| 1     | 2412                 | 18.71               | 18.34   | 142.536                | 21.54                | 30          | Pass        |
| 6     | 2437                 | 20.68               | 20.23   | 222.389                | 23.47                | 30          | Pass        |
| 11    | 2462                 | 18.97               | 18.54   | 150.336                | 21.77                | 30          | Pass        |

### 802.11n (HT40)

| Chan. | Chan. Freq.<br>(MHz) | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total Power<br>(dBm) | Limit (dBm) | Pass / Fail |
|-------|----------------------|---------------------|---------|------------------------|----------------------|-------------|-------------|
|       |                      | Chain 0             | Chain 1 |                        |                      |             |             |
| 3     | 2422                 | 16.79               | 16.74   | 94.959                 | 19.78                | 30          | Pass        |
| 6     | 2437                 | 21.12               | 21.19   | 260.942                | 24.17                | 30          | Pass        |
| 9     | 2452                 | 17.01               | 17.03   | 100.700                | 20.03                | 30          | Pass        |

#### 4.4.8 Test Results (Mode 2)

##### 1TX Mode

##### 802.11b

| Chan. | Chan. Freq. (MHz) | Average Power (mW) | Average Power (dBm) | Limit (dBm) | Pass / Fail |
|-------|-------------------|--------------------|---------------------|-------------|-------------|
| 1     | 2412              | 129.420            | 21.12               | 30          | Pass        |
| 6     | 2437              | 209.894            | 23.22               | 30          | Pass        |
| 11    | 2462              | 200.447            | 23.02               | 30          | Pass        |

##### 802.11g

| Chan. | Chan. Freq. (MHz) | Average Power (mW) | Average Power (dBm) | Limit (dBm) | Pass / Fail |
|-------|-------------------|--------------------|---------------------|-------------|-------------|
| 1     | 2412              | 53.211             | 17.26               | 30          | Pass        |
| 6     | 2437              | 142.889            | 21.55               | 30          | Pass        |
| 11    | 2462              | 85.507             | 19.32               | 30          | Pass        |

##### 802.11n (HT20)

| Chan. | Chan. Freq. (MHz) | Average Power (mW) | Average Power (dBm) | Limit (dBm) | Pass / Fail |
|-------|-------------------|--------------------|---------------------|-------------|-------------|
| 1     | 2412              | 33.266             | 15.22               | 30          | Pass        |
| 6     | 2437              | 143.880            | 21.58               | 30          | Pass        |
| 11    | 2462              | 60.256             | 17.80               | 30          | Pass        |

##### 802.11n (HT40)

| Chan. | Chan. Freq. (MHz) | Average Power (mW) | Average Power (dBm) | Limit (dBm) | Pass / Fail |
|-------|-------------------|--------------------|---------------------|-------------|-------------|
| 3     | 2422              | 21.928             | 13.41               | 30          | Pass        |
| 6     | 2437              | 53.088             | 17.25               | 30          | Pass        |
| 9     | 2452              | 47.424             | 16.76               | 30          | Pass        |

## 2TX Mode

### 802.11n (HT20)

| Chan. | Chan. Freq.<br>(MHz) | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total Power<br>(dBm) | Limit (dBm) | Pass / Fail |
|-------|----------------------|---------------------|---------|------------------------|----------------------|-------------|-------------|
|       |                      | Chain 0             | Chain 1 |                        |                      |             |             |
| 1     | 2412                 | 13.71               | 14.98   | 54.973                 | 17.40                | 30          | Pass        |
| 6     | 2437                 | 16.94               | 18.54   | 120.881                | 20.82                | 30          | Pass        |
| 11    | 2462                 | 14.14               | 15.75   | 63.526                 | 18.03                | 30          | Pass        |

### 802.11n (HT40)

| Chan. | Chan. Freq.<br>(MHz) | Average Power (dBm) |         | Total<br>Power<br>(mW) | Total Power<br>(dBm) | Limit (dBm) | Pass / Fail |
|-------|----------------------|---------------------|---------|------------------------|----------------------|-------------|-------------|
|       |                      | Chain 0             | Chain 1 |                        |                      |             |             |
| 3     | 2422                 | 12.60               | 14.09   | 43.842                 | 16.42                | 30          | Pass        |
| 6     | 2437                 | 16.76               | 17.41   | 102.505                | 20.11                | 30          | Pass        |
| 9     | 2452                 | 14.05               | 15.55   | 61.302                 | 17.87                | 30          | Pass        |




## 4.5 Power Spectral Density Measurement

### 4.5.1 Limits of Power Spectral Density Measurement

The Maximum of Power Spectral Density Measurement is 8dBm.

### 4.5.2 Test Setup



### 4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.5.4 Test Procedures

- Set instrument center frequency to DTS channel center frequency.
- Set span to at least 1.5 times the OBW.
- Set RBW to:  $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$ .
- Set VBW  $\geq 3 \times \text{RBW}$ .
- Detector = power averaging (RMS) or sample detector (when RMS not available).
- Ensure that the number of measurement points in the sweep  $\geq 2 \times \text{span}/\text{RBW}$ .
- Sweep time = auto couple.
- Employ trace averaging (RMS) mode over a minimum of 100 traces.
- Use the peak marker function to determine the maximum amplitude level.

### 4.5.5 Deviation from Test Standard

No deviation.

### 4.5.6 EUT Operating Conditions

Same as Item 4.3.6

#### 4.5.7 Test Results (Mode 1)

##### 1TX Mode

##### 802.11b

| Channel | Frequency (MHz) | PSD (dBm) | Limit (dBm) | Pass /Fail |
|---------|-----------------|-----------|-------------|------------|
| 1       | 2412            | -7.84     | 8           | Pass       |
| 6       | 2437            | -7.37     | 8           | Pass       |
| 11      | 2462            | -6.91     | 8           | Pass       |

##### 802.11g

| Channel | Frequency (MHz) | PSD (dBm) | Limit (dBm) | Pass /Fail |
|---------|-----------------|-----------|-------------|------------|
| 1       | 2412            | -9.14     | 8           | Pass       |
| 6       | 2437            | -8.97     | 8           | Pass       |
| 11      | 2462            | -10.80    | 8           | Pass       |

##### 802.11n (HT20)


| Channel | Frequency (MHz) | PSD (dBm) | Limit (dBm) | Pass /Fail |
|---------|-----------------|-----------|-------------|------------|
| 1       | 2412            | -11.70    | 8           | Pass       |
| 6       | 2437            | -8.88     | 8           | Pass       |
| 11      | 2462            | -10.89    | 8           | Pass       |

##### 802.11n (HT40)


| Channel | Frequency (MHz) | PSD (dBm) | Limit (dBm) | Pass /Fail |
|---------|-----------------|-----------|-------------|------------|
| 3       | 2422            | -16.87    | 8           | Pass       |
| 6       | 2437            | -12.22    | 8           | Pass       |
| 9       | 2452            | -16.90    | 8           | Pass       |

# Spectrum Plot of Worst Value


## 802.11b / CH11




## 802.11g / CH6



## 802.11n (HT20) / CH6



## 802.11n (HT40) / CH6



## 2TX Mode

### 802.11n (HT20)


| TX chain | Channel | Freq. (MHz) | PSD (dBm) | 10 log (N=2) dB | Total PSD (dBm) | Limit (dBm) | Pass /Fail |
|----------|---------|-------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 1       | 2412        | -12.79    | 3.01            | -9.78           | 8           | Pass       |
|          | 6       | 2437        | -10.33    | 3.01            | -7.32           | 8           | Pass       |
|          | 11      | 2462        | -12.46    | 3.01            | -9.45           | 8           | Pass       |
| 1        | 1       | 2412        | -12.49    | 3.01            | -9.48           | 8           | Pass       |
|          | 6       | 2437        | -11.87    | 3.01            | -8.86           | 8           | Pass       |
|          | 11      | 2462        | -12.62    | 3.01            | -9.61           | 8           | Pass       |

### 802.11n (HT40)


| TX chain | Channel | Freq. (MHz) | PSD (dBm) | 10 log (N=2) dB | Total PSD (dBm) | Limit (dBm) | Pass /Fail |
|----------|---------|-------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 3       | 2422        | -16.31    | 3.01            | -13.30          | 8           | Pass       |
|          | 6       | 2437        | -11.35    | 3.01            | -8.34           | 8           | Pass       |
|          | 9       | 2452        | -16.13    | 3.01            | -13.12          | 8           | Pass       |
| 1        | 3       | 2422        | -15.64    | 3.01            | -12.63          | 8           | Pass       |
|          | 6       | 2437        | -12.73    | 3.01            | -9.72           | 8           | Pass       |
|          | 9       | 2452        | -15.17    | 3.01            | -12.16          | 8           | Pass       |

## Spectrum Plot of Worst Value

### 802.11n (HT20)\_Chain 0 / CH6



### 802.11n (HT40)\_Chain 0 / CH6



#### 4.5.8 Test Results (Mode 2)

##### 1TX Mode

##### 802.11b

| Channel | Frequency (MHz) | PSD (dBm) | Limit (dBm) | Pass /Fail |
|---------|-----------------|-----------|-------------|------------|
| 1       | 2412            | -6.49     | 8           | Pass       |
| 6       | 2437            | -4.29     | 8           | Pass       |
| 11      | 2462            | -4.72     | 8           | Pass       |

##### 802.11g

| Channel | Frequency (MHz) | PSD (dBm) | Limit (dBm) | Pass /Fail |
|---------|-----------------|-----------|-------------|------------|
| 1       | 2412            | -12.23    | 8           | Pass       |
| 6       | 2437            | -7.19     | 8           | Pass       |
| 11      | 2462            | -10.27    | 8           | Pass       |

##### 802.11n (HT20)

| Channel | Frequency (MHz) | PSD (dBm) | Limit (dBm) | Pass /Fail |
|---------|-----------------|-----------|-------------|------------|
| 1       | 2412            | -14.28    | 8           | Pass       |
| 6       | 2437            | -7.72     | 8           | Pass       |
| 11      | 2462            | -11.66    | 8           | Pass       |



##### 802.11n (HT40)

| Channel | Frequency (MHz) | PSD (dBm) | Limit (dBm) | Pass /Fail |
|---------|-----------------|-----------|-------------|------------|
| 3       | 2422            | -19.38    | 8           | Pass       |
| 6       | 2437            | -15.12    | 8           | Pass       |
| 9       | 2452            | -15.31    | 8           | Pass       |

# Spectrum Plot of Worst Value



802.11b / CH6

802.11g / CH6



802.11n (HT20) / CH6

802.11n (HT40) / CH6



## 2TX Mode

### 802.11n (HT20)


| TX chain | Channel | Freq. (MHz) | PSD (dBm) | 10 log (N=2) dB | Total PSD (dBm) | Limit (dBm) | Pass /Fail |
|----------|---------|-------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 1       | 2412        | -16.10    | 3.01            | -13.09          | 8           | Pass       |
|          | 6       | 2437        | -12.71    | 3.01            | -9.70           | 8           | Pass       |
|          | 11      | 2462        | -15.49    | 3.01            | -12.48          | 8           | Pass       |
| 1        | 1       | 2412        | -14.99    | 3.01            | -11.98          | 8           | Pass       |
|          | 6       | 2437        | -11.18    | 3.01            | -8.17           | 8           | Pass       |
|          | 11      | 2462        | -14.13    | 3.01            | -11.12          | 8           | Pass       |

### 802.11n (HT40)


| TX chain | Channel | Freq. (MHz) | PSD (dBm) | 10 log (N=2) dB | Total PSD (dBm) | Limit (dBm) | Pass /Fail |
|----------|---------|-------------|-----------|-----------------|-----------------|-------------|------------|
| 0        | 3       | 2422        | -20.24    | 3.01            | -17.23          | 8           | Pass       |
|          | 6       | 2437        | -16.98    | 3.01            | -13.97          | 8           | Pass       |
|          | 9       | 2452        | -18.34    | 3.01            | -15.33          | 8           | Pass       |
| 1        | 3       | 2422        | -18.71    | 3.01            | -15.70          | 8           | Pass       |
|          | 6       | 2437        | -15.48    | 3.01            | -12.47          | 8           | Pass       |
|          | 9       | 2452        | -17.31    | 3.01            | -14.30          | 8           | Pass       |

## Spectrum Plot of Worst Value

### 802.11n (HT20)\_Chain 1 / CH6



### 802.11n (HT40)\_Chain 1 / CH6




## 4.6 Conducted Out of Band Emission Measurement

### 4.6.1 Limits of Conducted Out of Band Emission Measurement

Below 30dB of the highest emission level of operating band (in 100kHz Resolution Bandwidth).

### 4.6.2 Test Setup



### 4.6.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

### 4.6.4 Test Procedures

#### MEASUREMENT PROCEDURE REF

1. Set the RBW = 100 kHz.
2. Set the VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep time = auto couple.
5. Trace mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

#### MEASUREMENT PROCEDURE OOB

1. Set RBW = 100 kHz.
2. Set VBW  $\geq$  300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

### 4.6.5 Deviation from Test Standard

No deviation.

### 4.6.6 EUT Operating Conditions

Same as Item 4.3.6


### 4.6.7 Test Results (Mode 1)

The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.




# 1TX Mode 802.11b


## Maximum REF




## CH 1




## CH 6




## CH 11



## CH 1 Band edge




## CH 11 Band edge




802.11g


### Maximum REF





### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




## 802.11n (HT20)


### Maximum REF




### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




## 802.11n (HT40)


### Maximum REF




### CH 3




### CH 6




### CH 9



### CH 3 Band edge




### CH 9 Band edge




## 2TX Mode 802.11n (HT20)

### Maximum REF




### Chain 0


#### CH 1




#### CH 6




#### CH 11



#### CH 1 Band edge




#### CH 11 Band edge




## Chain 1


### CH 1



### CH 6




### CH 11




### CH 11 Band edge

### CH 1 Band edge




### CH 11 Band edge




## 802.11n (HT40)

### Maximum REF




### Chain 0


#### CH 3




#### CH 6




#### CH 9



#### CH 3 Band edge




#### CH 9 Band edge




# Chain 1


## CH 3




## CH 6




## CH 9



## CH 3 Band edge



## CH 9 Band edge






#### 4.6.8 Test Results (Mode 2)


The spectrum plots are attached on the following pages. D1 line indicates the highest level, and D2 line indicates the 30dB offset below D1. It shows compliance with the requirement.

# 1TX Mode 802.11b


## Maximum REF




## CH 1




## CH 6




## CH 11



## CH 1 Band edge




## CH 11 Band edge




802.11g


### Maximum REF




### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




## 802.11n (HT20)


### Maximum REF




### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




## 802.11n (HT40)


### Maximum REF




### CH 3




### CH 6




### CH 9



### CH 3 Band edge




### CH 9 Band edge




## 2TX Mode 802.11n (HT20)

### Maximum REF




### Chain 0


#### CH 1




#### CH 6




#### CH 11



#### CH 1 Band edge




#### CH 11 Band edge




## Chain 1


### CH 1




### CH 6




### CH 11



### CH 1 Band edge




### CH 11 Band edge




## 802.11n (HT40)

### Maximum REF




### Chain 0


#### CH 3




#### CH 6




#### CH 9



#### CH 3 Band edge




#### CH 9 Band edge






## Chain 1


### CH 3



### CH 6




### CH 9




### CH 9 Band edge

### CH 3 Band edge



### CH 9 Band edge



## 5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

## Appendix – Information on the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

**Linko EMC/RF Lab**

Tel: 886-2-26052180

Fax: 886-2-26051924

**Hsin Chu EMC/RF/Telecom Lab**

Tel: 886-3-5935343

Fax: 886-3-5935342

**Hwa Ya EMC/RF/Safety Lab**

Tel: 886-3-3183232

Fax: 886-3-3270892

**Email:** [service.adt@tw.bureauveritas.com](mailto:service.adt@tw.bureauveritas.com)

**Web Site:** [www.bureauveritas-adt.com](http://www.bureauveritas-adt.com)

The address and road map of all our labs can be found in our web site also.

--- END ---