

RF Exposure Report

Report No.: SA170405E08

FCC ID: I88NBG6604

Test Model: NBG6604

Series Model: NBG6602

Received Date: Apr. 08, 2017

Test Date: June 15, 2017

Issued Date: July 26, 2017

Applicant: Zyxel Communications Corporation

Address: No.2 Industry East RD. IX, Hsinchu Science Park, Hsinchu 30075, Taiwan

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Hsin Chu Laboratory

Lab Address: E-2, No.1, Li Hsin 1st Road, Hsinchu Science Park, Hsinchu City 300,
Taiwan R.O.C.

This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity.....	4
2 RF Exposure.....	5
2.1 Limits For Maximum Permissible Exposure (MPE).....	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Antenna Gain	6
2.5 Calculation Result Of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA170405E08	Original release.	July 26, 2017

1 Certificate of Conformity

Product: AC1200 Dual-Band Wireless Router

Brand: ZYXEL

Test Model: NBG6604

Series Model: NBG6602

Sample Status: ENGINEERING SAMPLE

Applicant: Zyxel Communications Corporation

Test Date: June 15, 2017

Standards: FCC Part 2 (Section 2.1091)

KDB 447498 D01 General RF Exposure Guidance v06

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

Prepared by : Wendy Wu , **Date:** July 26, 2017
Wendy Wu / Specialist

Approved by : May Chen , **Date:** July 26, 2017
May Chen / Manager

2 RF Exposure

2.1 Limits For Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user.
So, this device is classified as **Mobile Device**.

2.4 Antenna Gain

2.4GHz							
Transmitter Circuit	Brand	Model No.	Antenna Net Gain (dBi)	Frequency Range (GHz toGHz)	Antenna Type	Connector Type	Cable Length(mm)
Chain (0)	Aristotle	MiCAP-3324C	2.2	2.4~2.4835	Dipole	i-pex(MHF)	153
Chain (1)	Aristotle	MiCAP-3324C	2.55	2.4~2.4835	Dipole	i-pex(MHF)	41
5GHz							
Transmitter Circuit	Brand	Model No.	Antenna Net Gain (dBi)	Frequency Range (GHz toGHz)	Antenna Type	Connector Type	Cable Length(mm)
Chain (0)	Aristotle	MiCAP-3324C	2.78	5.15~5.85	Dipole	i-pex(MHF)	150
Chain (1)	Aristotle	MiCAP-3324C	3	5.15~5.85	Dipole	i-pex(MHF)	43

2.5 Calculation Result Of Maximum Conducted Power

Frequency Band (MHz)	Max Power (mW)	Antenna Gain (dBi)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
2412-2462	246.397	5.39	20	0.16958	1
5180-5240	177.813	5.90	20	0.13762	1
5745-5825	469.373	5.90	20	0.36328	1

NOTE:

2.4GHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 5.39\text{dBi}$

5GHz: Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20})^2 / 2] = 5.9\text{dBi}$

Conclusion:

The formula of calculated the MPE is:

CPD1 / LPD1 + CPD2 / LPD2 +etc. < 1

CPD = Calculation power density

LPD = Limit of power density

WLAN 2.4GHz + WLAN 5GHz = $0.16958 / 1 + 0.36328 / 1 = 0.53286$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---