



FCC Test Report

APPLICANT : Motorola Mobility LLC
EQUIPMENT : Mobile Cellular Phone
BRAND NAME : Motorola
MODEL NAME : XT1941-4, XT1941-1
FCC ID : IHDT56XK2
STANDARD : FCC 47 CFR FCC Part 15 Subpart B
CLASSIFICATION : Certification

The product was received on Jun. 04, 2018 and testing was completed on Jun. 13, 2018. We, Sporton International (Kunshan) Inc., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International (Kunshan) Inc., the test report shall not be reproduced except in full.

Approved by: James Huang / Manager



Sporton International (Kunshan) Inc.

***No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335
China***



TABLE OF CONTENTS

REVISION HISTORY	3
SUMMARY OF TEST RESULT	4
1. GENERAL DESCRIPTION	5
1.1. Applicant.....	5
1.2. Manufacturer	5
1.3. Product Feature of Equipment Under Test	5
1.4. Product Specification of Equipment Under Test	6
1.5. Specification of Accessory	7
1.6. Modification of EUT	8
1.7. Test Location	8
1.8. Applicable Standards	8
2. TEST CONFIGURATION OF EQUIPMENT UNDER TEST	9
2.1. Test Mode	9
2.2. Connection Diagram of Test System	11
2.3. Support Unit used in test configuration and system.....	11
2.4. EUT Operation Test Setup	12
3. TEST RESULT	13
3.1. Test of AC Conducted Emission Measurement	13
3.2. Test of Radiated Emission Measurement	19
4. LIST OF MEASURING EQUIPMENT	23
5. UNCERTAINTY OF EVALUATION	24
APPENDIX A. SETUP PHOTOGRAPHS	



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FC860402-01	Rev. 01	Initial issue of report	Jul. 30, 2018



SUMMARY OF TEST RESULT

Report Section	FCC Rule	Description	Limit	Result	Remark
3.1	15.107	AC Conducted Emission	< 15.107 limits	PASS	Under limit 7.57 dB at 13.551 MHz
3.2	15.109	Radiated Emission	< 15.109 limits	PASS	Under limit 8.19 dB at 44.550 MHz



1. General Description

1.1. Applicant

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.2. Manufacturer

Motorola Mobility LLC

222 W, Merchandise Mart Plaza, Chicago IL 60654 USA

1.3. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT1941-4, XT1941-1
FCC ID	IHDT56XK2
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE/NFC WLAN 2.4GHz 802.11b/g/n HT20 WLAN 5GHz 802.11a/n HT20/HT40 Bluetooth BR/EDR/LE
IMEI Code	Conduction: 355541090013479/355541090013487 Radiation: Sample 1: 355541090011994/355541090012000 Sample 2: 355558090001734
HW Version	DVT1B
SW Version	fastboot_deen_oem_userdebug_8.1.0_OPK28.26_f325_int cfg-test-keys_oem
EUT Stage	Identical Prototype

Remark:

1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.
2. There are two types of EUT sample 1 and sample 2, the differences between two samples are only for SIM slot, the sample 1(model name XT1941-4) is dual SIM slot, the sample 2(model name XT1941-1) is single SIM slot. According to the difference, we choose sample 1 to perform full test and the sample 2 verify worse case of the sample 1 for Radiation.

1.4. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2537.5 MHz ~ 2652.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500MHz ~ 5720 MHz ; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 38: 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2537.5 MHz ~ 2652.5 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500MHz ~ 5720 MHz ; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 MHz ~ 1610 MHz FM : 88 MHz ~ 108 MHz NFC : 13.56 MHz
Antenna Type	WWAN : Fixed Internal Antenna WLAN : IFA Antenna Bluetooth : IFA Antenna GNSS: IFA Antenna NFC : Loop Antenna FM: External headset Antenna
Type of Modulation	GSM: GMSK GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA : BPSK (Uplink) HSDPA/DC-HSDPA : QPSK (Uplink) HSUPA : QPSK (Uplink) HSPA+ : 16QAM(uplink is not supported) DC-HSDPA : 64QAM LTE: QPSK / 16QAM 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) Bluetooth LE : GFSK Bluetooth (1Mbps) : GFSK Bluetooth (2Mbps) : π /4-DQPSK Bluetooth (3Mbps) : 8-DPSK GNSS : BPSK



	NFC: ASK FM
--	----------------

Note: GNSS Rx = GPS Rx + Glonass Rx

1.5. Specification of Accessory

Specification of Accessory				
AC Adapter 1 (US)	Brand Name	Motorola(Salom)	Model Name	SC-51
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 1 (EU)	Brand Name	Motorola(Salom)	Model Name	SC-52
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 1 (UK)	Brand Name	Motorola(Salom)	Model Name	SC-53
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 1(IND)	Brand Name	Motorola(Salom)	Model Name	SC-54
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 1 (AU)	Brand Name	Motorola(Salom)	Model Name	SC-55
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 1 (AR)	Brand Name	Motorola(Salom)	Model Name	SC-56
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 1 (BR)	Brand Name	Motorola(Salom)	Model Name	SC-57
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 1 (PRC)	Brand Name	Motorola(Salom)	Model Name	SC-58
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 1 (Chile)	Brand Name	Motorola(Salom)	Model Name	SC-52
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 2 (US)	Brand Name	Motorola(chenyang)	Model Name	SC-51
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 2 (EU)	Brand Name	Motorola(chenyang)	Model Name	SC-52
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 2 (UK)	Brand Name	Motorola(chenyang)	Model Name	SC-53
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 2 (AU)	Brand Name	Motorola(chenyang)	Model Name	SC-55
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 2 (AR)	Brand Name	Motorola(chenyang)	Model Name	SC-56
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
AC Adapter 2 (PRC)	Brand Name	Motorola(chenyang)	Model Name	SC-58
	Power Rating	I/P: 100 - 240 Vac, 0.6A, O/P: 5Vdc 3000mA; 9Vdc 2000mA; 12Vdc 1500mA		
Battery	Brand Name	Motorola	Model Name	JE40
	Power Rating	3.8Vdc, 2820mAh	Type	Li-ion



Earphone	Brand Name	Motorola (New Leader)	Model Name	NLD-EM307E-09SF
	Signal Line	1.2 meter, non-shielded cable, with w/o ferrite core		
USB Cable 1	Brand Name	Motorola(Liqi)	Model Name	LQ-03500079
	Signal Line	1.0 meter, non-shielded cable, with w/o ferrite core		
USB Cable 2	Brand Name	Motorola (Saibao)	Model Name	SLQ-A1111A
	Signal Line	1.0 meter, non-shielded cable, with w/o ferrite core		

1.6. Modification of EUT

No modifications are made to the EUT during all test items.

1.7. Test Location

Sporton Lab is accredited to ISO 17025 by National Voluntary Laboratory Accreditation Program (NVLAP code: 600155-0) and the FCC designation No. is CN5013.

Test Site	Sporton International (Kunshan) Inc.		
Test Site Location	No.3-2 Ping-Xiang Rd, Kunshan Development Zone Kunshan City Jiangsu Province 215335 China TEL: +86-512-57900158 FAX: +86-512-57900958		
Test Site No.	Sporton Site No.		FCC Test Firm Registration No.
	CO01-KS	03CH02-KS	630927

Note: The test site complies with ANSI C63.4 2014 requirement.

1.8. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- FCC 47 CFR FCC Part 15 Subpart B
- ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test

2.1. Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction (150 kHz to 30 MHz), radiation (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone + Camera(Rear) for Sample 1
	Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone + Camera(Front) for Sample 1
	Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone + MPEG4 for Sample 1
	Mode 4: WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone + NFC On for Sample 1
	Mode 5: LTE Band 5 Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Data Link with Notebook) + Earphone + GNSS Rx for Sample 1
	Mode 6: LTE Band 7 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Data Link with Notebook) + Earphone + GNSS Rx for Sample 1
	Mode 7: USB Cable 1 (Charging from Adapter 1) + FM Rx (88MHz) + Earphone for Sample 1
	Mode 8: USB Cable 1 (Charging from Adapter 1) + FM Rx (98MHz) + Earphone for Sample 1
	Mode 9: USB Cable 1 (Charging from Adapter 1) + FM Rx (108MHz) + Earphone for Sample 1
	Mode 10 : WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone + NFC On for Sample 1

Radiated Emissions	Mode 1: GSM850 Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone + Camera(Rear) for Sample 1 Mode 2: GSM1900 Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone + Camera(Front) for Sample 1 Mode 3: WCDMA Band V Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone + MPEG4 for Sample 1 Mode 4: WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 1 (Charging from Adapter 1) + Earphone + NFC On for Sample 1 Mode 5: LTE Band 5 Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 1 (Data Link with Notebook) + Earphone + GNSS Rx for Sample 1 Mode 6: LTE Band 7 Idle + Bluetooth Idle + WLAN (2.4G) Idle + USB Cable 2 (Data Link with Notebook) + Earphone + GNSS Rx for Sample 1 Mode 7: USB Cable 1 (Charging from Adapter 1) + FM Rx (88MHz) + Earphone for Sample 1 Mode 8: USB Cable 1 (Charging from Adapter 1) + FM Rx (98MHz) + Earphone for Sample 1 Mode 9: USB Cable 1 (Charging from Adapter 1) + FM Rx (108MHz) + Earphone for Sample 1 Mode 10 : USB Cable 2 (Charging from Adapter 2) + FM Rx (108MHz) + Earphone for Sample 1 Mode 11 : USB Cable 1 (Charging from Adapter 1) + FM Rx (98MHz) + Earphone for Sample 2
Remark: 1. The worst case of AC is mode 10; only the test data of this mode is reported. 2. The worst case of RE is mode 8; only the test data of this mode is reported. 3. Data Link with Notebook means data application transferred mode between EUT and Notebook.	

2.2. Connection Diagram of Test System



2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	GPS Station	ADIVIC	MP9000	N/A	N/A	Unshielded, 1.8 m
3.	FM Generator	R&S	SMBV100A	N/A	N/A	Unshielded, 1.8 m
4.	WLAN AP	D-Link	DIR-855	KA2DIR855A2	N/A	Unshielded, 1.8m
5.	WLAN AP	TP-Link	TL-WDR5600	N/A	N/A	Unshielded, 1.8m
6.	Bluetooth Earphone	Lenovo	LBH308	N/A	N/A	N/A
7.	Notebook	DELL	Latitude3440	N/A	N/A	shielded cable DC O/P 1.8m Unshielded AC I/P cable 1.8m
8.	Notebook	Lenovo	G480	PRC4	N/A	shielded cable DC O/P 1.8m Unshielded AC I/P cable 1.8m
9.	SD Card	Kingston	8GB	N/A	N/A	N/A
10.	SD Card	SanDisk	Uitra	N/A	N/A	N/A
11.	Hard Disk	Lenovo	F310	FCC DoC	Shielded, 1.2m	N/A



2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or LTE idle mode during the testing. The EUT was synchronized to the BCCH, and is in continuous receiving mode by setting system simulator's paging reorganization.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test.

1. Data application is transferred between Notebook and EUT via USB cable.
2. Turn on GNSS function to make the EUT receive continuous signals from GNSS station.
3. Turn on NFC function.
4. Turn on camera to capture images.
5. Execute "Video player" to play MPEG4 files.
6. The EUT was turned to Radio frequency channels, FM88 MHz, FM98 MHz, FM108 MHz from FM Generator.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1 Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

3.1.2 Measuring Instruments

The measuring equipment is listed in the section 4 of this test report.

3.1.3 Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.


3.1.4 Test Setup





3.1.5 Test Result of AC Conducted Emission

Test Mode :	Mode 10	Temperature :	24.1~24.7℃
Test Engineer :	Amos Zhang	Relative Humidity :	51~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone + NFC On for Sample 1		




Site : CO01-KS
Condition : FCC CLASS-B LISN-L-171013-060103 LINE
Project : (FC) 860402-01
mode : Mode 10
: 355541090013479/355541090013487 #16

	Freq	Level	Over Limit	Limit	Read	LISN	Cable	
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	Remark
1	0.162	46.25	-19.09	65.34	35.51	0.17	10.57	QP
2	0.162	28.35	-26.99	55.34	17.61	0.17	10.57	Average
3	0.185	48.49	-15.75	64.24	37.80	0.19	10.50	QP
4	0.185	35.19	-19.05	54.24	24.50	0.19	10.50	Average
5	0.194	46.17	-17.67	63.84	35.50	0.20	10.47	QP
6	0.194	30.97	-22.87	53.84	20.30	0.20	10.47	Average
7	0.211	44.86	-18.32	63.18	34.21	0.20	10.45	QP
8	0.211	28.26	-24.92	53.18	17.61	0.20	10.45	Average
9	0.266	41.15	-20.10	61.25	30.49	0.22	10.44	QP
10	0.266	26.55	-24.70	51.25	15.89	0.22	10.44	Average
11	2.110	37.10	-18.90	56.00	26.60	0.29	10.21	QP
12	2.110	26.80	-19.20	46.00	16.30	0.29	10.21	Average
13	11.438	39.88	-20.12	60.00	29.20	0.32	10.36	QP
14	11.438	31.98	-18.02	50.00	21.30	0.32	10.36	Average
15	13.560	44.88	-15.12	60.00	34.21	0.28	10.39	QP
16 *	13.560	38.88	-11.12	50.00	28.21	0.28	10.39	Average
17	14.138	42.27	-17.73	60.00	31.60	0.27	10.40	QP



Test Mode :	Mode 10	Temperature :	24.1~24.7℃
Test Engineer :	Amos Zhang	Relative Humidity :	51~52%
Test Voltage :	120Vac / 60Hz	Phase :	Line
Function Type :	WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone + NFC On for Sample 1		




Site : CO01-KS
Condition : FCC CLASS-B LISN-L-171013-060103 LINE
Project : (FC) 860402-01
mode : Mode 10
: 355541090013479/355541090013487 #16

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
18	14.138	34.97	-15.03	50.00	24.30	0.27	10.40	Average
19	17.849	41.76	-18.24	60.00	31.10	0.21	10.45	QP
20	17.849	32.86	-17.14	50.00	22.20	0.21	10.45	Average



Test Mode :	Mode 10	Temperature :	24.1~24.7℃
Test Engineer :	Amos Zhang	Relative Humidity :	51~52%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone + NFC On for Sample 1		




Site : CO01-KS
 Condition : FCC CLASS-B LISN-N-171013-060103 NEUTRAL
 Project : (FC) 860402-01
 mode : Mode 10
 : 355541090013479/355541090013487 #16

	Freq	Level	Over	Limit	Read	LISN	Cable	
	MHz	dBuV	Limit	Line	Level	Factor	Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
1	0.156	48.07	-17.58	65.65	37.20	0.28	10.59	QP
2	0.156	32.37	-23.28	55.65	21.50	0.28	10.59	Average
3	0.178	45.40	-19.19	64.59	34.60	0.28	10.52	QP
4	0.178	28.40	-26.19	54.59	17.60	0.28	10.52	Average
5	0.190	49.36	-14.66	64.02	38.60	0.28	10.48	QP
6	0.190	35.96	-18.06	54.02	25.20	0.28	10.48	Average
7	0.206	48.33	-15.03	63.36	37.60	0.28	10.45	QP
8	0.206	34.23	-19.13	53.36	23.50	0.28	10.45	Average
9	0.222	41.23	-21.51	62.74	30.50	0.28	10.45	QP
10	0.222	24.33	-28.41	52.74	13.60	0.28	10.45	Average
11	0.260	41.92	-19.50	61.42	31.20	0.28	10.44	QP
12	0.260	28.92	-22.50	51.42	18.20	0.28	10.44	Average
13	2.321	39.43	-16.57	56.00	28.91	0.32	10.20	QP
14	2.321	27.73	-18.27	46.00	17.21	0.32	10.20	Average
15	4.136	38.01	-17.99	56.00	27.49	0.34	10.18	QP
16	4.136	27.71	-18.29	46.00	17.19	0.34	10.18	Average
17	12.384	43.83	-16.17	60.00	33.21	0.25	10.37	QP



Test Mode :	Mode 10	Temperature :	24.1~24.7℃
Test Engineer :	Amos Zhang	Relative Humidity :	51~52%
Test Voltage :	120Vac / 60Hz	Phase :	Neutral
Function Type :	WCDMA Band II Idle + Bluetooth Idle + WLAN (5G) Idle + USB Cable 2 (Charging from Adapter 2) + Earphone + NFC On for Sample 1		



Site : CO01-KS
Condition : FCC CLASS-B LISN-N-171013-060103 NEUTRAL
Project : (FC) 860402-01
mode : Mode 10
: 355541090013479/355541090013487 #16

	Freq	Level	Over Limit	Limit Line	Read Level	LISN Factor	Cable Loss	Remark
	MHz	dBuV	dB	dBuV	dBuV	dB	dB	
18	12.384	34.83	-15.17	50.00	24.21	0.25	10.37	Average
19	13.551	49.53	-10.47	60.00	38.91	0.23	10.39	QP
20 *	13.551	42.43	-7.57	50.00	31.81	0.23	10.39	Average
21	14.063	46.12	-13.88	60.00	35.50	0.22	10.40	QP
22	14.063	37.92	-12.08	50.00	27.30	0.22	10.40	Average
23	15.307	44.52	-15.48	60.00	33.90	0.20	10.42	QP
24	15.307	36.82	-13.18	50.00	26.20	0.20	10.42	Average
25	16.486	44.21	-15.79	60.00	33.60	0.18	10.43	QP
26	16.486	35.81	-14.19	50.00	25.20	0.18	10.43	Average
27	17.018	44.51	-15.49	60.00	33.90	0.17	10.44	QP
28	17.018	36.51	-13.49	50.00	25.90	0.17	10.44	Average

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


The measuring equipment is listed in the section 4 of this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dB μ V/m) = 20 log Emission level (μ V/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamplifier Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz




For radiated emissions above 1GHz





3.2.5. Test Result of Radiated Emission

Test Mode :	Mode 8	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Horizontal
Function Type :	USB Cable 1 (Charging from Adapter 1) + FM Rx (98MHz) + Earphone for Sample 1		
Remark :	#2 is system simulator (FM Option) signal which can be ignored.		




Site : 03CH02-KS
Condition : FCC CLASS-B 3m LF 23182-3M HORIZONTAL
Project : (FC)860402-01
Mode : 8
IMEI : 355541090011994 355541090012000 #15

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	Limit	Line	Level	Loss	Factor			
			dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	30.00	22.07	-17.93	40.00	29.03	24.50	0.57	32.03	100	0 Peak
2	97.90	29.22			43.56	16.62	1.00	31.96	---	---
3	195.87	18.92	-24.58	43.50	33.89	15.28	1.43	31.68	---	---
4	334.58	20.20	-25.80	46.00	29.35	19.91	1.91	30.97	---	---
5	496.57	22.74	-23.26	46.00	27.57	23.14	2.36	30.33	---	---
6	613.94	24.97	-21.03	46.00	27.56	24.34	2.64	29.57	---	---
7	949.56	27.75	-18.25	46.00	24.75	26.94	3.20	27.14	---	---
8	2840.00	43.96	-30.04	74.00	42.33	32.73	5.87	36.97	---	---
9	3616.00	46.17	-27.83	74.00	43.01	33.13	6.47	36.44	---	---
10	4112.00	46.34	-27.66	74.00	42.47	33.57	7.09	36.79	---	---
11	5240.00	46.50	-27.50	74.00	40.83	34.57	7.79	36.69	---	---
12	6280.00	46.62	-27.38	74.00	39.41	35.16	8.84	36.79	---	---
13	6936.00	46.47	-27.53	74.00	38.49	35.58	9.15	36.75	---	---



Test Mode :	Mode 8	Temperature :	21~22°C
Test Engineer :	Carl Ni	Relative Humidity :	41~42%
Test Distance :	3m	Polarization :	Vertical
Function Type :	USB Cable 1 (Charging from Adapter 1) + FM Rx (98MHz) + Earphone for Sample 1		
Remark :	#2 is system simulator (FM Option) signal which can be ignored.		



Site : 03CH02-KS
Condition : FCC CLASS-B 3m LF 23182-3M VERTICAL
Project : (FC)860402-01
Mode : 8
IMEI : 355541090011994 355541090012000 #15

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	44.55	31.81	-8.19	40.00	46.73	16.53	0.66	32.11	100	0 Peak
2	97.90	26.03			40.37	16.62	1.00	31.96	---	---
3	195.87	22.07	-21.43	43.50	37.04	15.28	1.43	31.68	---	---
4	419.94	21.54	-24.46	46.00	28.14	21.92	2.12	30.64	---	---
5	575.14	24.62	-21.38	46.00	27.83	24.02	2.59	29.82	---	---
6	834.13	26.61	-19.39	46.00	25.74	26.00	2.92	28.05	---	---
7	939.86	27.60	-18.40	46.00	24.79	26.84	3.18	27.21	---	---
8	1944.00	43.61	-30.39	74.00	45.06	30.76	4.56	36.77	---	---
9	2800.00	45.57	-28.43	74.00	43.97	32.70	5.84	36.94	---	---
10	3664.00	46.86	-27.14	74.00	43.57	33.23	6.51	36.45	---	---
11	4368.00	46.63	-27.37	74.00	42.59	33.72	7.17	36.85	---	---
12	5032.00	47.13	-26.87	74.00	41.48	34.51	7.84	36.70	---	---
13	6344.00	47.35	-26.65	74.00	40.13	35.20	8.77	36.75	---	---



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
EMI Receiver	R&S	ESCI7	100768	9kHz~7GHz;	Apr. 19, 2018	Jun. 13, 2018	Apr. 18, 2019	Conduction (CO01-KS)
AC LISN	MessTec	AN3016	060103	9kHz~30MHz	Oct. 13, 2017	Jun. 13, 2018	Oct. 12, 2018	Conduction (CO01-KS)
AC LISN (for auxiliary equipment)	MessTec	AN3016	060105	9kHz~30MHz	Oct. 13, 2017	Jun. 13, 2018	Oct. 12, 2018	Conduction (CO01-KS)
AC Power Source	Chroma	61602	ABP0000008 11	AC 0V~300V, 45Hz~1000Hz	Oct. 12, 2017	Jun. 13, 2018	Oct. 11, 2018	Conduction (CO01-KS)
EMI Test Receiver	R&S	ESR7	101403	9kHz~7GHz;Ma x 30dBm	Aug. 08, 2017	Jun. 13, 2018	Aug. 07, 2018	Radiation (03CH02-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44G,MAX 30dB	Apr. 17, 2018	Jun. 13, 2018	Apr. 16, 2019	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	23182	30MHz~2GHz	Jan. 29, 2018	Jun. 13, 2018	Jan. 28, 2019	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Oct. 21, 2017	Jun. 13, 2018	Oct. 20, 2018	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Feb. 07, 2018	Jun. 13, 2018	Feb. 06, 2019	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35-H G	1887435	18~40GHz	Oct. 12, 2017	Jun. 13, 2018	Oct. 11, 2018	Radiation (03CH02-KS)
Amplifier	SONOMA	310N	187289	9KHz~1GHz	Aug. 07, 2017	Jun. 13, 2018	Aug. 06, 2018	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1~26.5GHz Gain 30dB	Oct. 12, 2017	Jun. 13, 2018	Oct. 11, 2018	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	61601000247 3	N/A	NCR	Jun. 13, 2018	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	Jun. 13, 2018	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	Jun. 13, 2018	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required

5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	2.9dB
--	-------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.2dB
--	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.0dB
--	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.7dB
--	-------