



FCC EMI TEST REPORT

FCC ID : IHDT56ZB1
Equipment : Mobile Cellular Phone
Brand Name : Motorola
Model Name : XT2071-2, XT2071-3, XT2071-5
Applicant : Motorola Mobility, LLC
222 W Merchandise Mart Plaza, Suite 1800,
Chicago, IL 60654, United States
Manufacturer : Motorola Mobility, LLC
222 W Merchandise Mart Plaza, Suite 1800,
Chicago, IL 60654, United States
Standard : FCC 47 CFR FCC Part 15 Subpart B Class B

The product was received on May 22, 2020 and testing was started from May 31, 2020 and completed on Jun. 03, 2020. We, SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI C63.4-2014 and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory
No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1. General Description	5
1.1. Product Feature of Equipment Under Test	5
1.2. Product Specification of Equipment Under Test	7
1.3. Modification of EUT	9
1.4. Test Location	10
1.5. Applicable Standards	10
2. Test Configuration of Equipment Under Test	11
2.1. Test Mode	11
2.2. Connection Diagram of Test System	13
2.3. Support Unit used in test configuration and system	15
2.4. EUT Operation Test Setup	15
3. Test Result	16
3.1. Test of AC Conducted Emission Measurement	16
3.2. Test of Radiated Emission Measurement	18
4. List of Measuring Equipment.....	20
5. Uncertainty of Evaluation	21
Appendix A. AC Conducted Emission Test Result	
Appendix B. Radiated Emission Test Result	



History of this test report

Report No.	Version	Description	Issued Date
FC051232-02	01	Initial issue of report	Jul. 30, 2020



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.107	AC Conducted Emission	Pass	Under limit 5.24 dB at 0.157 MHz
3.2	15.109	Radiated Emission	Pass	Under limit 9.86 dB at 162.570 MHz for Quasi-Peak

Declaration of Conformity:

The test results with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers.

Comments and Explanations:

The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.

Reviewed by: Dara Chiu

Report Producer: Ruby Zou



1. General Description

1.1. Product Feature of Equipment Under Test

Product Feature	
Equipment	Mobile Cellular Phone
Brand Name	Motorola
Model Name	XT2071-2, XT2071-3, XT2071-5
FCC ID	IHDT56ZB1
IMEI Code	Conduction : IMEI 1:353590110017152 IMEI 2:353590110017160 Radiation : IMEI 1:353590110017152 IMEI 2:353590110017160
EUT supports Radios application	CDMA/EV-DO/GSM/EGPRS/WCDMA/HSPA/LTE/5G NR/ GNSS/NFC WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80 Bluetooth BR/EDR/LE
HW Version	DVT2
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.



Accessory List		
AC Adapter 1 (US)	Brand Name :	Motorola
	Model Name :	SC-51
	Manufacturer :	Chenyang
AC Adapter 1 (EU)	Brand Name :	Motorola
	Model Name :	SC-52
	Manufacturer :	Chenyang
AC Adapter 1 (UK)	Brand Name :	Motorola
	Model Name :	SC-53UK
	Manufacturer :	Chenyang
AC Adapter 1 (AR)	Brand Name :	Motorola
	Model Name :	SC-56
	Manufacturer :	Chenyang
AC Adapter 1 (AU)	Brand Name :	Motorola
	Model Name :	SC-55AU
	Manufacturer :	Chenyang
AC Adapter 2 (US)	Brand Name :	Motorola
	Model Name :	SC-51
	Manufacturer :	Acbel
AC Adapter 2 (EU)	Brand Name :	Motorola
	Model Name :	SC-52
	Manufacturer :	Acbel
AC Adapter 2 (AR)	Brand Name :	Motorola
	Model Name :	SC-56
	Manufacturer :	Acbel
AC Adapter 3 (IN)	Brand Name :	Motorola
	Model Name :	SC-54
	Manufacturer :	Salom
Battery 1	Brand Name :	Motorola
	Model Name :	LS30
	Manufacturer :	ATL
Battery 2	Brand Name :	Motorola
	Model Name :	LS40
	Manufacturer :	ATL
Standard 3.5mm Headset 1	Brand Name :	Motorola
	Model Name :	SH38C37773
	Manufacturer :	Lianyun
Standard 3.5mm Headset 2	Brand Name :	Motorola
	Model Name :	SH38C44959
	Manufacturer :	Lianyun
USB-C to 3.5mm headset adaptor 1	Brand Name :	Motorola
	Model Name :	SC18C27844
USB-C to 3.5mm headset adaptor 2	Brand Name :	Motorola
	Model Name :	SC18C27845
USB Cable 1	Brand Name :	Motorola
	Model Name :	SC18C24367
	Manufacturer :	Saibao
USB Cable 2	Brand Name :	Motorola
	Model Name :	SC18C24368
	Manufacturer :	Luxshare

1.2. Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band V: 826.4 MHz ~ 846.6 MHz WCDMA Band IV : 1712.4 MHz ~ 1752.6 MHz WCDMA Band II: 1852.4 MHz ~ 1907.6 MHz CDMA2000 BC0: 824.70 MHz ~ 848.31 MHz CDMA2000 BC1: 1851.25 MHz ~ 1908.75 MHz CDMA2000 BC10: 817.90 MHz ~ 823.10 MHz LTE Band 2: 1850.7 MHz ~ 1909.3 MHz LTE Band 4: 1710.7 MHz ~ 1754.3 MHz LTE Band 5: 824.7 MHz ~ 848.3 MHz LTE Band 7: 2502.5 MHz ~ 2567.5 MHz LTE Band 12: 699.7 MHz ~ 715.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz LTE Band 14 : 790.5 MHz ~ 795.5 MHz LTE Band 17: 706.5 MHz ~ 713.5 MHz LTE Band 25 : 1850.7 MHz ~ 1914.3 MHz LTE Band 26 : 824.7 MHz ~ 848.3 MHz LTE Band 30 : 2307.5 MHz ~ 2312.5 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41: 2498.5 MHz ~ 2687.5 MHz LTE Band 48 : 3552.5 MHz ~ 3697.5 MHz LTE Band 66: 1710.7 MHz ~ 1779.3 MHz LTE Band 71: 665.5 MHz ~ 695.5 MHz 5G NR Band n2: 1852.5 MHz ~ 1907.5 MHz 5G NR n5: 826.5 ~ 846.5MHz 5G NR n41: 2506.02MHz ~ 2679.99MHz 5G NR n66: 1712.5 MHz ~ 1777.5 MHz 5G NR n71: 668.0 MHz ~ 693.0 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5720 MHz; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz NFC : 13.56 MHz



Standards-related Product Specification	
Rx Frequency	GSM850: 869.2 MHz ~ 893.8 MHz GSM1900: 1930.2 MHz ~ 1989.8 MHz WCDMA Band V: 871.4 MHz ~ 891.6 MHz WCDMA Band IV : 2112.4 MHz ~ 2152.6 MHz WCDMA Band II: 1932.4 MHz ~ 1987.6 MHz CDMA2000 BC0: 869.70 MHz ~ 893.31 MHz CDMA2000 BC1: 1931.25 MHz ~ 1988.75 MHz CDMA2000 BC10: 862.90 MHz ~ 868.10 MHz LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 4 : 2110.7 MHz ~ 2154.3 MHz LTE Band 5 : 869.7 MHz ~ 893.3 MHz LTE Band 7 : 2622.5 MHz ~ 2687.5 MHz LTE Band 12 : 729.7 MHz ~ 745.3 MHz LTE Band 13: 748.5 MHz ~ 753.5 MHz LTE Band 14: 760.5 MHz ~ 765.5 MHz LTE Band 17 : 736.5 MHz ~ 743.5 MHz LTE Band 25 : 1930.7MHz ~ 1994.3 MHz LTE Band 26 : 869.7 MHz ~ 893.3 MHz LTE Band 30 : 2352.5 MHz ~ 2357.5 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2498.5 MHz ~ 2687.5 MHz LTE Band 48 : 3552.5 MHz ~ 3697.5 MHz LTE Band 66: 2110.7 MHz ~ 2199.3 MHz LTE Band 71: 619.5 MHz ~ 649.5 MHz 5G NR Band n2: 1932.5 MHz ~ 1987.5 MHz 5G NR Band n5: 826.5 ~ 846.5MHz 5G NR Band n41: 2506.02MHz ~ 2679.99MHz 5G NR Band n66: 2112.5 MHz ~ 2197.5 MHz 5G NR Band n71: 668.0 MHz ~ 693.0 MHz 802.11b/g/n: 2412 MHz ~ 2462 MHz 802.11a/n/ac: 5180 MHz ~ 5240 MHz; 5260 MHz ~ 5320 MHz; 5500 MHz ~ 5720 MHz; 5745 MHz ~ 5825 MHz Bluetooth: 2402 MHz ~ 2480 MHz GNSS : 1559 ~ 1610 MHz (GPS/Glonass/Galileo/BDS) NFC : 13.56 MHz

Standards-related Product Specification	
Antenna Type	WWAN: <Ant. 1> : Fixed Internal Antenna <Ant. 2> : Fixed Internal Antenna WLAN: <Ant. 4> : Slot Antenna <Ant. 3> : ILA Antenna Bluetooth: Slot Antenna GPS/Glonass/Galileo/BDS: PIFA Antenna NFC: Flex antenna with winding coil pattern
Type of Modulation	GSM / GPRS: GMSK EDGE(MCS 0-4): GMSK / (MCS 5-9): 8PSK WCDMA: QPSK (Uplink) HSDPA: 64QAM (Downlink) HSUPA : QPSK (Uplink) CDMA2000: QPSK LTE: QPSK / 16QAM / 64QAM 5G NR: PI/2 BPSK / QPSK / 16QAM / 64QAM / 256QAM 802.11b: DSSS (DBPSK / DQPSK / CCK) 802.11a/g/n: OFDM (BPSK / QPSK / 16QAM / 64QAM) 802.11ac: OFDM (BPSK / QPSK / 16QAM / 64QAM / 256QAM) Bluetooth LE: GFSK Bluetooth (1Mbps): GFSK Bluetooth (2Mbps): $\pi/4$ -DQPSK Bluetooth (3Mbps): 8-DPSK GPS/Glonass/Galileo/BDS: BPSK NFC: ASK

1.3. Modification of EUT

No modifications are made to the EUT during all test items.

1.4. Test Location

Test Site	SPORTON INTERNATIONAL INC. EMC & Wireless Communications Laboratory	
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978	
Test Site No.	Sporton Site No.	
	CO05-HY	03CH06-HY

FCC designation No.: TW1093

1.5. Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC 47 CFR FCC Part 15 Subpart B Class B
- ♦ ANSI C63.4-2014

Remark: All test items were verified and recorded according to the standards and without any deviation during the test.

2. Test Configuration of Equipment Under Test

2.1. Test Mode


The EUT has been associated with peripherals pursuant to ANSI C63.4-2014 and configuration operated in a manner tended to maximize its emission characteristics in a typical application.

Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (30MHz to the 5th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower).

Test Items	Function Type
AC Conducted Emission	Mode 1: CDMA2000 BC10 (Middle Channel) Idle + Bluetooth Idle + WLAN Idle + MPEG 4 + USB Cable 1 (Charging from Adapter 1) + SIM 2 for Open Mode
	Mode 2: LTE Band 12 (Middle Channel) Idle + Bluetooth Idle + WLAN Idle + Camera (Front) + USB Cable 2 (Charging from Adapter 2) + SIM 2 for Open Mode
	Mode 3: LTE Band 13 (Middle Channel) Idle + Bluetooth Idle + WLAN Idle + Camera (Back) + USB Cable 1 (Charging from Adapter 3) + SIM 2 for Open Mode
	Mode 4: LTE Band 14 (Middle Channel) Idle + Bluetooth Idle + WLAN Idle + GPS Rx + USB Cable 1 (Data Link with Notebook) + SIM 2 for Open Mode
	Mode 5: LTE Band 26 (Middle Channel) Idle + Bluetooth Idle + WLAN Idle + NFC On + USB Cable 2 (Data Link with Notebook) + SIM 2 for Open Mode
	Mode 6: LTE Band 71 (Middle Channel) Idle+ Bluetooth Idle + WLAN Idle + Camera (Back) + USB Cable 1 (Charging from Adapter 3) + SIM 1 for Close Mode
	Mode 7: 5G NR n5 Idle (Middle Channel) + Bluetooth Idle + WLAN Idle + NFC On + USB Cable 2 (Data Link with Notebook) + SIM 1 for Close Mode

Test Items	Function Type
Radiated Emissions	Mode 1: GSM850 (Middle Channel) Idle + Bluetooth Link + WLAN Link + MPEG 4 + Earphone 1 + USB-C to 3.5mm headset adaptor 1 + SIM1 for Open Mode
	Mode 2: CDMA2000 BC10 (Middle Channel) Idle + Bluetooth Link + WLAN Link + GPS Rx + Earphone 2 + USB-C to 3.5mm headset adaptor 2 + SIM1 for Open Mode
	Mode 3: WCDMA Band V (Middle Channel) Idle + Bluetooth Idle + WLAN Idle + Camera (front) + USB Cable 1 (Charging from Adapter 1) + SIM1 for Open Mode
	Mode 4: LTE Band 12 (Middle Channel) Idle + Bluetooth Idle + WLAN Idle + Camera (Back) + USB Cable 2 (Charging from Adapter 2) + SIM 1 for Open Mode
	Mode 5: LTE Band 13 (Middle Channel) Idle + Bluetooth Idle + WLAN Idle + NFC On + USB Cable 1 (Charging from Adapter 3) + SIM 1 for Open Mode
	Mode 6: LTE Band 14 (Middle Channel) Idle + Bluetooth Idle + WLAN Idle + GPS Rx + USB Cable 1 (Data Link with Notebook) + SIM 1 for Open Mode
	Mode 7: LTE Band 26 (Middle Channel) Idle + Bluetooth Idle + WLAN Idle + NFC On + USB Cable 2 (Data Link with Notebook) +SIM 1 for Open Mode
	Mode 8: LTE Band 71 (Middle Channel) Idle + Bluetooth Link + WLAN Link + GPS Rx + Earphone 2 + USB-C to 3.5mm headset adaptor 2 +SIM 2 for Close Mode
	Mode 9: 5G NR n5 Idle + Bluetooth Idle + WLAN Idle + Camera (Back) + USB Cable 2 (Charging from Adapter 2) + SIM 2 for Close Mode
	Mode 10 : 5G NR n71 Idle + Bluetooth Idle + WLAN Idle + NFC On + USB Cable 2 (Data Link with Notebook) + SIM 2 for Close Mode
Remark: - The worst case of AC is mode 7; only the test data of this mode was reported. - The worst case of RE is mode 7; only the test data of this mode was reported. - For radiation emission after pre-scanned the cellular band between 30MHz ~ 960MHz (GSM850/WCDMA Band V/CDMA BC10/LTE Band 12/13/14/71/26/5G NR n5); only the worst case for cellular band test data of this mode was reported. - Data Link with Notebook means data application transferred mode between EUT and Notebook. - All test items were performed with Adapter 1 (US), Adapter 2 (US), and Adapter 3 (IN). - For 5G NR test combination is EN-DC 7-n5 / ENDC 2-n71.	

2.2. Connection Diagram of Test System



Conduction Test Setup									
No.	Wireless Station	Connection Type	Test Mode						
			1	2	3	4	5	6	7
A1	BT Earphone	Bluetooth	X	X	X	X	X	X	X
A2	System Simulator	CDMA/LTE/5G NR	X	X	X	X	X	X	X
A3	GPS Station	GPS	-	-	-	X	-	-	-
A4	AP router	WiFi	X	X	X	X	X	X	X
No.	Power Source	Connection Type	1	2	3	4	5	6	7
B1	AC : 120V/60Hz	AC Power Cable	X	X	X	-	-	X	-
B2	Power From System	AC Power Cable	-	-	-	X	X	-	X
No.	Setup Peripherals	Connection Type	1	2	3	4	5	6	7
C1	Notebook	USB Cable	-	-	-	X	X	-	X
C1-1	iPod	USB Cable to C1	-	-	-	X	X	-	X
C1-2	AP router	RJ-45 Cable to C1	-	-	-	X	X	-	X

Radiation Test Setup									
No.	Wireless Station	Connection Type	Test Mode						
			1	2	3	4	5	6	7
A1	BT Earphone	Bluetooth	X	X	X	X	X	X	X
A2	System Simulator	GSM/WCDMA/LTE/5G NR	X	X	X	X	X	X	X
A3	GPS Station	GPS		X				X	
A4	AP router	WiFi	X	X	X	X	X	X	X
A5	Notebook	WiFi	X	X					
No.	Power Source	Connection Type	1	2	3	4	5	6	7
B1	AC : 120V/60Hz	AC Power Cable			X	X	X		
B2	From System	USB Cable						X	X
No.	Setup Peripherals	Connection Type	1	2	3	4	5	6	7
C1	Notebook	USB Cable						X	X
C1-1	iPod	USB Cable to C1						X	X
C1-2	AP router	RJ-45 Cable to C1						X	X
C3	Earphone	Earphone jack	X	X					

Radiation Test Setup									
No.	Wireless Station	Connection Type	Test Mode						
			8	9	10				
A1	BT Earphone	Bluetooth	X	X	X				
A2	System Simulator	GSM/WCDMA/LTE/5G NR	X	X	X				
A3	GPS Station	GPS	X						
A4	AP router	WiFi	X	X	X				
A5	Notebook	WiFi	X						
No.	Power Source	Connection Type	8	9	10				
B1	AC : 120V/60Hz	AC Power Cable		X					
B2	From System	USB Cable			X				
No.	Setup Peripherals	Connection Type	8	9	10				
C1	Notebook	USB Cable			X				
C1-1	iPod	USB Cable to C1			X				
C1-2	AP router	RJ-45 Cable to C1			X				
C3	Earphone	Earphone jack	X						

2.3. Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	R&S	CMU 200	N/A	N/A	Unshielded, 1.8 m
2.	System Simulator	R&S	CMW 500	N/A	N/A	Unshielded, 1.8 m
3.	System Simulator	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
4.	5G Wireless Test Platform	Keysight	E7515B	N/A	N/A	Unshielded, 1.8m
5.	GPS Station	Pendulum	GSG-54	N/A	N/A	Unshielded, 1.8 m
6.	Bluetooth Earphone	Sony Ericsson	MW600	PY7DDA-2029	N/A	N/A
7.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8 m
8.	iPod	Apple	A1285	FCC DoC	Shielded, 1.0 m	N/A
9.	Notebook	DELL	Latitude 3400	FCC DoC	N/A	AC I/P : Unshielded, 1.2m DC O/P : Shielded, 1.8m
10.	Notebook	ASUS	P2430U	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m

2.4. EUT Operation Test Setup

The EUT was in GSM or WCDMA or CDMA2000 or LTE or 5G NR idle mode during the testing. The EUT was synchronized with the BCCH, and had been continuous receiving mode by setting paging reorganization of the system simulator.

At the same time, the EUT was attached to the Bluetooth earphone or WLAN AP, and the following programs installed in the EUT were programmed during the test:

1. Data application is transferred between Laptop and EUT via USB cable.
2. Execute "GPS Test" to make the EUT receive continuous signals from GPS station.
3. Execute "Video player" to play MPEG4 files.
4. Turn on camera to capture images.
5. Turn on NFC function.

3. Test Result

3.1. Test of AC Conducted Emission Measurement

3.1.1. Limits of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

<Class B>

Frequency of emission (MHz)	Conducted limit (dBuV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.1.2. Measuring Instruments

Refer a test equipment and calibration data table in this test report.

3.1.3. Test Procedure

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN should be used.
6. Both sides of AC line were checked for maximum conducted interference.
7. The frequency range from 150 kHz to 30 MHz was searched.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

3.1.4. Test Setup



3.1.5. Test Result of AC Conducted Emission

Please refer to Appendix A.

3.2. Test of Radiated Emission Measurement

3.2.1. Limit of Radiated Emission

The emissions from an unintentional radiator shall not exceed the field strength levels specified in the following table:

<Class B>

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

3.2.2. Measuring Instruments


Refer a test equipment and calibration data table in this test report.

3.2.3. Test Procedures


1. The EUT was placed on a turntable with 0.8 meter above ground.
2. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest radiation.
4. The antenna is a Bi-Log antenna and its height is adjusted between one to four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.
6. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode (RBW=120kHz/VBW=300kHz for frequency below 1GHz; RBW=1MHz VBW=3MHz (Peak), RBW=1MHz/VBW=10Hz (Average) for frequency above 1GHz).
7. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, peak values of EUT will be reported. Otherwise, the emission will be repeated by using the quasi-peak method and reported.
8. Emission level (dBμV/m) = 20 log Emission level (μV/m)
9. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level

3.2.4. Test Setup of Radiated Emission

For radiated emissions from 30MHz to 1GHz



For radiated emissions above 1GHz



3.2.5. Test Result of Radiated Emission

Please refer to Appendix B.



4. List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Jun. 01, 2020~ Jun. 03, 2020	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Nov. 15, 2019	Jun. 01, 2020~ Jun. 03, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 07, 2019	Jun. 01, 2020~ Jun. 03, 2020	Nov. 06, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Nov. 20, 2019	Jun. 01, 2020~ Jun. 03, 2020	Nov. 19, 2020	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100081	9kHz~30MHz	Nov. 15, 2019	Jun. 01, 2020~ Jun. 03, 2020	Nov. 14, 2020	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32 V10.30	N/A	N/A	N/A	Jun. 01, 2020~ Jun. 03, 2020	N/A	Conduction (CO05-HY)
LF Cable	HUBER + SUHNER	RG-214/U	LF01	N/A	Jan. 02, 2020	Jun. 01, 2020~ Jun. 03, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100851	N/A	Jan. 02, 2020	Jun. 01, 2020~ Jun. 03, 2020	Jan. 01, 2021	Conduction (CO05-HY)
Amplifier	SONOMA	310N	186713	9kHz~1GHz	Apr. 30, 2020	May 31, 2020~ Jun. 02, 2020	Apr. 29, 2021	Radiation (03CH06-HY)
Bilog Antenna	Schaffner	CBL 6111C & N-6-06	2725 & AT-N0601	30MHz~1GHz	Jan. 09, 2020	May 31, 2020~ Jun. 02, 2020	Jan. 08, 2021	Radiation (03CH06-HY)
EMI Test Receiver	Rohde & Schwarz	ESU26	100472	20Hz~26.5GHz	Jan. 10, 2020	May 31, 2020~ Jun. 02, 2020	Jan. 09, 2021	Radiation (03CH06-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	9120D-1156	1GHz~18GHz	Aug. 30, 2019	May 31, 2020~ Jun. 02, 2020	Aug. 29, 2020	Radiation (03CH06-HY)
Preamplifier	MITEQ	00101800-30- 10P	1850117	1GHz~18GHz	Sep. 03, 2019	May 31, 2020~ Jun. 02, 2020	Sep. 02, 2020	Radiation (03CH06-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104 / STORM/LL142	MY24966/4 / 00100A1O2A1 78T	30MHz~26GHz	Nov. 21, 2019	May 31, 2020~ Jun. 02, 2020	Nov. 20, 2020	Radiation (03CH06-HY)
Controller	INN-CO	EM1000	060782	Control Turn table & Ant Mast	N/A	May 31, 2020~ Jun. 02, 2020	N/A	Radiation (03CH06-HY)
Antenna Mast	MF	MF-7802	MF780208212	1m~4m	N/A	May 31, 2020~ Jun. 02, 2020	N/A	Radiation (03CH06-HY)
Turn Table	INN-CO	DS2000	420/650/00	0-360 degree	N/A	May 31, 2020~ Jun. 02, 2020	N/A	Radiation (03CH06-HY)
Software	Audix	E3 6.2009-8-24(k 5)	N/A	N/A	N/A	May 31, 2020~ Jun. 02, 2020	N/A	Radiation (03CH06-HY)



5. Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150 kHz ~ 30 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	2.3
--	-----

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.3
--	-----

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.8
--	-----




Appendix A. AC Conducted Emission Test Results

Test Engineer :	Tom Lee, Howard Huang	Temperature :	21~24℃
		Relative Humidity :	42~50%

EUT Information

Report NO : 051232-02
Test Mode : Mode 7
Test Voltage : Power From System
Phase : Line

Full Spectrum



Final_Result


Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.157110	---	47.16	55.62	8.46	L1	OFF	19.5
0.157110	60.38	---	65.62	5.24	L1	OFF	19.5
0.168000	---	33.09	55.06	21.97	L1	OFF	19.5
0.168000	53.73	---	65.06	11.33	L1	OFF	19.5
0.191400	---	21.81	53.98	32.17	L1	OFF	19.5
0.191400	43.28	---	63.98	20.70	L1	OFF	19.5
0.215610	---	35.19	52.99	17.80	L1	OFF	19.5
0.215610	49.16	---	62.99	13.83	L1	OFF	19.5
0.234060	---	24.69	52.30	27.61	L1	OFF	19.5
0.234060	39.41	---	62.30	22.89	L1	OFF	19.5
0.255750	---	32.16	51.57	19.41	L1	OFF	19.5
0.255750	44.11	---	61.57	17.46	L1	OFF	19.5
1.257540	---	31.75	46.00	14.25	L1	OFF	19.6
1.257540	42.41	---	56.00	13.59	L1	OFF	19.6
1.365000	---	33.67	46.00	12.33	L1	OFF	19.6
1.365000	42.56	---	56.00	13.44	L1	OFF	19.6
1.497750	---	33.11	46.00	12.89	L1	OFF	19.6
1.497750	42.05	---	56.00	13.95	L1	OFF	19.6
1.635000	---	31.50	46.00	14.50	L1	OFF	19.6
1.635000	39.79	---	56.00	16.21	L1	OFF	19.6
1.765500	---	29.52	46.00	16.48	L1	OFF	19.6

1.765500	37.45	---	56.00	18.55	L1	OFF	19.6
1.894560	---	28.16	46.00	17.84	L1	OFF	19.6
1.894560	35.72	---	56.00	20.28	L1	OFF	19.6
13.560000	---	27.85	50.00	22.15	L1	OFF	19.8
13.560000	32.60	---	60.00	27.40	L1	OFF	19.8
26.533230	---	24.72	50.00	25.28	L1	OFF	19.8
26.533230	28.82	---	60.00	31.18	L1	OFF	19.8

EUT Information

Report NO : 051232-02
 Test Mode : Mode 7
 Test Voltage : Power From System
 Phase : Neutral

Full Spectrum




Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.150000	---	26.55	56.00	29.45	N	OFF	19.5
0.150000	51.50	---	66.00	14.50	N	OFF	19.5
0.163320	---	23.79	55.29	31.50	N	OFF	19.5
0.163320	46.32	---	65.29	18.97	N	OFF	19.5
0.170250	---	27.39	54.95	27.56	N	OFF	19.5
0.170250	48.77	---	64.95	16.18	N	OFF	19.5
0.183750	---	36.62	54.31	17.69	N	OFF	19.5
0.183750	51.37	---	64.31	12.94	N	OFF	19.5
0.251250	---	19.37	51.72	32.35	N	OFF	19.5
0.251250	35.50	---	61.72	26.22	N	OFF	19.5
1.250250	---	31.93	46.00	14.07	N	OFF	19.6
1.250250	40.42	---	56.00	15.58	N	OFF	19.6
1.344750	---	33.51	46.00	12.49	N	OFF	19.6
1.344750	41.50	---	56.00	14.50	N	OFF	19.6
1.448430	---	33.50	46.00	12.50	N	OFF	19.6
1.448430	41.56	---	56.00	14.44	N	OFF	19.6
1.534020	---	32.63	46.00	13.37	N	OFF	19.6
1.534020	40.55	---	56.00	15.45	N	OFF	19.6
1.626000	---	31.27	46.00	14.73	N	OFF	19.6
1.626000	38.85	---	56.00	17.15	N	OFF	19.6
1.722750	---	30.61	46.00	15.39	N	OFF	19.6

1.722750	37.44	---	56.00	18.56	N	OFF	19.6
13.562970	---	26.54	50.00	23.46	N	OFF	19.9
13.562970	31.29	---	60.00	28.71	N	OFF	19.9
23.230410	---	22.53	50.00	27.47	N	OFF	20.0
23.230410	26.95	---	60.00	33.05	N	OFF	20.0

Appendix B. Radiated Emission Test Result

Test Engineer :	Yuan Lee, You Xian Chen	Temperature :	24~26°C
		Relative Humidity :	37~41%
Test Distance :	3m	Polarization :	Horizontal
Remark :	#6 is system simulator signal which can be ignored.		




Site : 03CH06-HY
 Condition : FCC CLASS-B 3m 9120D_1156 HORIZONTAL
 Project : 051232-02
 Power : From System
 Memo : Mode 7
 : NB to eMMC

	Freq	Level	Over Limit	Limit Line	ReadAntenna Level	Cable Factor	Preamp Loss	A/Pos	T/Pos	Remark
	MHz	dBuV/m	dB	dBuV/m	dBuV	dB/m	dB	dB	cm	deg
1	65.91	27.50	-12.50	40.00	46.13	11.95	1.05	31.65	---	---
2	216.00	34.99	-8.51	43.50	49.71	14.91	1.93	31.64	---	---
3	226.02	39.01	-6.99	46.00	52.93	15.66	1.97	31.63	100	0
4	311.20	32.90	-13.10	46.00	42.89	19.19	2.33	31.61	---	---
5	792.10	31.98	-14.02	46.00	32.16	27.64	3.72	31.81	---	---
6	876.50	40.09			38.47	28.75	3.94	31.41	---	---
7	955.90	31.78	-14.22	46.00	27.54	30.57	4.07	30.85	---	---
8	1062.00	41.65	-32.35	74.00	74.26	24.80	4.22	61.63	---	---
9	4932.00	41.35	-32.65	74.00	58.59	31.30	9.74	58.28	---	---
10	6986.00	43.55	-30.45	74.00	54.02	35.30	12.64	58.41	---	---
11	8866.00	46.69	-27.31	74.00	51.92	37.73	14.69	57.65	---	---
12	10950.00	49.79	-24.21	74.00	49.27	40.40	16.61	56.49	---	---
13	12622.00	49.82	-24.18	74.00	51.55	38.73	18.09	58.55	100	0



Test Engineer :	Yuan Lee, You Xian Chen	Temperature :	24~26°C
		Relative Humidity :	37~41%
Test Distance :	3m	Polarization :	Vertical
Remark :	#6 is system simulator signal which can be ignored.		



Site : 03CH06-HY
 Condition : FCC CLASS-B 3m 9120B_1156 VERTICAL
 Project : 051232-02
 Power : From System
 Memo : Mode 7
 : NB to eMMC

	Freq	Level	Over	Limit	ReadAntenna	Cable	Preamp	A/Pos	T/Pos	Remark
	MHz	dBuV/m	Limit	Line	Level	Factor	Loss	Factor	cm	deg
1	162.57	33.64	-9.86	43.50	47.50	16.07	1.65	31.64	100	0 QP
2	230.88	41.97	-4.03	46.00	55.42	16.10	2.00	31.63	---	Peak
3	240.33	40.48	-5.52	46.00	52.76	17.22	2.04	31.63	---	Peak
4	306.30	35.78	-10.22	46.00	45.82	19.16	2.31	31.61	---	Peak
5	743.80	29.92	-16.08	46.00	30.03	27.81	3.65	31.83	---	Peak
6	876.50	44.66			43.04	28.75	3.94	31.41	---	Peak
7	944.70	33.15	-12.85	46.00	29.14	30.51	4.05	30.94	---	Peak
8	2130.00	46.11	-27.89	74.00	73.62	27.30	6.26	61.07	---	Peak
9	3198.00	42.43	-31.57	74.00	67.39	28.90	7.62	61.48	---	Peak
10	6982.00	44.41	-29.59	74.00	54.88	35.30	12.64	58.41	---	Peak
11	8938.00	47.40	-26.60	74.00	52.83	37.60	14.70	57.73	---	Peak
12	10964.00	49.99	-24.01	74.00	49.42	40.40	16.63	56.46	100	0 Peak
13	11060.00	49.66	-24.34	74.00	49.13	40.20	16.69	56.36	---	Peak

————THE END————