

## EMC TEST REPORT For FCC




Test Report No. : 2005050017  
Date of Issue : May 16, 2005  
Model/Type No. : 190M  
Kind of Product : LCD MONITOR  
Applicant : BTC KOREA CO., LTD.  
Applicant Address : 439-1, Sanggi-ri, Pongdam-eup, Hwaseong-si, Kyonggi-do, Korea  
Manufacturer : BTC KOREA CO., LTD.  
Manufacturer Address : 439-1, Sanggi-ri, Pongdam-eup, Hwaseong-si, Kyonggi-do, Korea  
Contact Person : Kim Jae Chul / Engineer  
Telephone : +82-31-299-1575  
Received Date : May 11, 2005  
Test period : Start : May 12, 2005 End : May 16, 2005  
Test Results : ☒ In Compliance ☐ Not in Compliance

The test results presented in this report relate only to the object tested.


CERTiTEK Standards Laboratory Co., Ltd. is accredited by Korea Laboratory Accreditation Scheme (KOLAS) which signed the International Laboratory Accreditation Cooperation (ILAC) Mutual Recognition Arrangement (MRA) for the above test item(s) and test method(s).

Tested by

Reviewed by



Young-Kug, Song  
EMC Test Engineer  
Date: May 16, 2005



James Hong  
EMC Technical Manager  
Date: May 16, 2005

## REPORT REVISION HISTORY

Date	Revision	Page No
May 16, 2005	Issued (2005050017)	All

*This report shall not be reproduced except in full, without the written approval of CERTiTEK Standards Laboratory Co., Ltd. This document may be altered or revised by CERTiTEK Standards Laboratory Co., Ltd. personnel only, and shall be noted in the revision section of the document. Any alteration of this document not carried out by CERTiTEK Standards Laboratory Co., Ltd. will constitute fraud and shall nullify the document.*

## TABLE OF CONTENTS

REPORT REVISION HISTORY .....	2
1.0 General Product Description .....	4
1.1 Model Differences .....	4
1.2 Device Modifications .....	4
1.3 EUT Configuration(s) .....	5
1.4 Test Software .....	5
1.5 EUT Operating Mode(s) .....	5
1.6 Configuration .....	6
1.7 Calibration Details of Equipment Used for Measurement .....	7
1.8 Test Facility .....	7
1.9 Measurement Procedure .....	7
1.10 Laboratory Accreditations and Listings .....	8
2.0 Emissions Test Regulations .....	9
2.1 Conducted Voltage Emissions .....	10
2.2 Radiated Electric Field Emissions .....	11
APPENDIX A - Test Setup Photos and Configuration .....	12
Conducted Voltage Emissions .....	12
Radiated Electric Field Emissions .....	13
APPENDIX B – TEST DATA .....	14
Conducted Voltage Emissions .....	14
Radiated Electric Field Emissions .....	16
APPENDIX C – EUT Photographs .....	17
EUT External Photographs .....	18
EUT Internal Photographs .....	20
PCB .....	22
Photographs related to Label .....	25

## 1.0 General Product Description

### 1.0.1 Tested Equipment

- ☒ Unless otherwise indicated, all tests were conducted on Model 190M.
- ☐ Tests performed on Model \_\_\_\_\_ were considered to be representative of Model(s) \_\_\_\_\_.

### 1.0.2 Equipment Size, Mobility and Identification

Dimensions: 443(W) by 453(H) by 216(D) ☒ mm ☐ inch  
Mobility: ☐ Hand-held ☒ Table-top ☐ Built-in  
☐ Traveling ☐ Floor-standing  
Serial No.: N1911US5119703

### 1.0.3 Electrical Ratings

AC Adapter Input: 100-240 Vac, 50/60 Hz, 1.5 A  
AC Adapter Output: 12 Vdc, 5.0 A

### 1.0.4 Test Voltage & Frequency

Unless indicated otherwise on the individual data sheet or test results, the test voltage and frequency was as indicated below.

Voltage: 120 Vac  
Frequency: 60 Hz

### 1.0.5 Clock & Other Frequencies Utilized

Main Board: 14.3181 MHz

## 1.1 Model Differences

Not applicable

## 1.2 Device Modifications

The following modifications were necessary for compliance:

Not applicable

### 1.3 EUT Configuration(s)

See Appendix A for individual test set-up configuration(s). The following peripheral devices and/or interface cables were connected during the measurement:

☒ Peripheral Devices

Device	Manufacturer	Model No.	Serial No.	FCC ID or DoC
AC Adapter	Suzhou LiShin Electronic Co., Ltd.	LSE9901B1260	A30452130659	DoC
Personal Computer	HEWLETT-PACKARD COMPANY	HP Pavilion t812k	KRJ50403HK	DoC
Keyboard (PS/2 type)	HEWLETT-PACKARD COMPANY	5219	BN50107686	E5XKB5209
Mouse (PS/2 type)	HEWLETT-PACKARD COMPANY	N3+ Optical	K045205991	DoC
Mouse (USB type)	SAMSUNG	OMS3CB	0303009883	DoC
Printer	SEIKO EPSON CORP.	EPSON STYLUS COLO R	BWCE143331	DoC
Headset	PLANTRONICS	LS1	-	DoC

☒ Cable Description

#	Description	Ferrite Core	Length (m)	Other Details
1	AC Power Cable, Unshielded	No	1.8	Connect to AC Power
2	AC Power Cable, Unshielded	No	1.8	Connect to AC Power
3	AC Power Cable, Unshielded	No	1.8	Connect to AC Power
4	DC output cable, Unshielded	Yes	1.5	Between the EUT and AC Adapter
5	D-SUB Cable, Unshielded	Yes	1.5	Between the EUT and Personal Computer
6	Keyboard cable, Shielded	No	1.8	Connect to Personal Computer
7	Mouse cable, Shielded	No	1.8	Connect to Personal Computer
8	Mouse cable, Shielded	No	1.8	Connect to Personal Computer
9	Headset cable, Unshielded	No	2.0	Connect to EUT
10	Audio input cable, Unshielded	Yes	1.5	Between the EUT and Personal Computer
11	PARALLEL cable, Shielded	No	1.8	Between the EUT and Printer

### 1.4 Test Software


- ☐ EMC Test V 1.0  
☐ Display Test Patterns - V1.5  
☐ Ping.exe  
☒ Not applicable

### 1.5 EUT Operating Mode(s)

Equipment under test was operated during the measurement under the following conditions:

- ☐ Standby  
☐ Display circles pattern  
☐ Practice operation  
☒ Scrolling 'H'  
☐ Read / Write

## 1.6 Configuration



## 1.7 Calibration Details of Equipment Used for Measurement

Test equipment and test accessories are calibrated on regular basis. The maximum time between calibrations is one year or what is recommended by the manufacturer, whichever is less. All test equipment calibrations are traceable to the Korea Research Institute of Standards and Science (KRISS), therefore, all test data recorded in this report is traceable to KRISS.

## 1.8 Test Facility

The measurement facility is located at 386-1, Ho-Dong, Yongin-City, Kyungki-Do, Korea 449-100. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

## 1.9 Measurement Procedure

Preliminary AC power line conducted emissions tests were performed shielded room. To find worst mode, several typical mode and typical cable position were tested.

Final AC power line conducted emissions test was performed shielded room. (location is same as Preliminary test)






Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

Preliminary radiated emissions test were performed anechoic chamber (Distance of antenna and EUT was 3 m). To find worst mode, several typical mode and typical cable position were tested and peak level and frequency were recorded.

Final radiated emissions test was performed Open Area Test Site. Based on the preliminary tests of the EUT, final test was proceeded worst case test mode and cable configuration.

\* Measurement procedures was In accordance with ANSI C63.4-2001 7.2.3, 7.2.4, 8.3.1.1, 8.3.1.2

## 1.10 Laboratory Accreditations and Listings

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3 & 10 meter Open Area Test Sites and one conducted site to perform FCC Part 15/18 measurements.	 93250
JAPAN	VCCI	10 meter Open Area Test Site and one conducted site.	 R-948, C-986
KOREA	MIC	EMI (10 meter Open Area Test Site and two conducted sites) EMS (ESD, RS, EFT/Burst, Surge, CS, Magnetic, Dips and interruptions)	 No. 51, KR0025
International	KOLAS	EMC	 NO.119
Europe	GLAS	EMC EN 55011, EN 55022, EN 61000-6-3, EN 61000-6-4, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, EN 50130-4, EN 55024, EN 61204-3, EN 60601-1-2, EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-4-11	 No.13000796-02



## 2.0 Emissions Test Regulations

The emissions tests were performed according to following regulations:

- |  |                                  |   |
|--|----------------------------------|---|
| <input type="checkbox"/> EN 61000-6-3:2001   | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 61000-6-4:2001   | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 50083-2:2001   |                                  |   |
| <input type="checkbox"/> EN 55011:1998 +A1:1999  | <input type="checkbox"/> Group 1 | <input type="checkbox"/> Group 2            |
|  | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 55011:1998 +A1:1999 +A2:2002   | <input type="checkbox"/> Group 1 | <input type="checkbox"/> Group 2            |
|  | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 55013:1990 +A12:1994 +A13:1996 +A14:1999   |                                  |   |
| <input type="checkbox"/> EN 55013:2001   |                                  |   |
| <input type="checkbox"/> EN 55014-1:2000   |                                  |   |
| <input type="checkbox"/> EN 55014-1:2000 +A1:2001  |                                  |   |
| <input type="checkbox"/> EN 55015:2000   |                                  |   |
| <input type="checkbox"/> EN 55015:2000 +A1:2001  |                                  |   |
| <input type="checkbox"/> EN 55022:1994 +A1:1995 +A2:1997   | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 55022:1998   | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 55022:1998 +A1:2000  | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 55022:1998 +A1:2000 +A2:2003   | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> EN 61000-3-2:2000   |                                  |   |
| <input type="checkbox"/> EN 61000-3-3:1995 +A1:2001  |                                  |   |
| <input type="checkbox"/> VCCI V-3/2004.04  | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |
| <input type="checkbox"/> AS/NZS 3548:1995 +A1:1997 +A2:1997  | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |
| <input checked="" type="checkbox"/> FCC Part 15 Subpart B  | <input type="checkbox"/> Class A | <input checked="" type="checkbox"/> Class B |
| <input checked="" type="checkbox"/> CISPR 22:1997  | <input type="checkbox"/> Class A | <input checked="" type="checkbox"/> Class B |
| The unit was tested to CISPR 22 and complied with the alternate methods allowed by FCC under paragraphs 15.107 and 15.109. |                                  |   |
| <input type="checkbox"/> CISPR 22:1997 +A1:2000  | <input type="checkbox"/> Class A | <input type="checkbox"/> Class B            |

## 2.1 Conducted Voltage Emissions

### Test Date

May 12, 2005

### Test Location

Shielded Room

### Test Equipment

	Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date
<input checked="" type="checkbox"/>	Field Strength Meter	Rohde & Schwarz	ESHS30	828144/002	2006-02-01
<input checked="" type="checkbox"/>	LISN	EMCO	3825/2	9607-2574	2005-09-03
<input checked="" type="checkbox"/>	LISN	EMCO	3825/2	9409-2246	2005-09-03
<input type="checkbox"/>	Field Strength Meter	Rohde & Schwarz	ESHS30	862024/001	2006-03-08
<input type="checkbox"/>	LISN	Rohde & Schwarz	ESH3-Z5	100207	2005-12-15
<input type="checkbox"/>	LISN	EMCO	3825/2	9206-1971	2005-12-15

### Frequency Range of Measurement

150 kHz to 30 MHz

### Test Results

The requirements are:

☒ MET

Frequency (MHz)	Measured Data (dBuV)	Margin (dB)	Remark
4.07	41.2	14.8	Quasi-peak

☐ NOT MET

Frequency (MHz)	Measured Data (dBuV)	Margin (dB)	Remark

☐ NOT APPLICABLE

### Remarks

See Appendix B for test data.

## 2.2 Radiated Electric Field Emissions

### Test Date

May 16, 2005

### Test Location

☒ Testing was performed at a test distance of 10 meter Open Area Test Site

### Test Equipment

	Name of Equipment	Manufacturer	Model No.	Serial No.	Due Date
<input checked="" type="checkbox"/>	Field Strength Meter	Rohde & Schwarz	ESVS30	829673/015	2005-11-15
<input checked="" type="checkbox"/>	ULTRA Broadband Antenna	Rohde & Schwarz	HL562	361324/014	2005-05-21
<input type="checkbox"/>	Biconical Antenna	EMCO	3110	9202-1510	2006-04-13
<input type="checkbox"/>	Log-periodic Antenna	EMCO	3146	9607-4567	2006-04-08

### Frequency Range of Measurement

30 MHz to 1 GHz

### Test Results

The requirements are:

☒ MET

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark
692.12	32.6	4.4	Quasi-peak

☐ NOT MET

Frequency (MHz)	Measured Data (dBuV/m)	Margin (dB)	Remark

☐ NOT APPLICABLE



### Remarks

See Appendix B for test data

## APPENDIX B – TEST DATA

### Conducted Voltage Emissions

Frequency  [MHz]	Correction Factor		Line	Quasi-peak				Average			
				Limit	Reading	Result	Margin	Limit	Reading	Result	Margin
	LISN	Cable		[dBuV]	[dBuV]	[dBuV]	[dB]	[dBuV]	[dBuV]	[dBuV]	[dB]
0.15	0.1	0.1	N	66.0	50.4	50.6	15.4	56.0	13.8	14.0	42.0
0.19	0.1	0.1	N	64.0	46.6	46.8	17.2	54.0	36.2	36.4	17.6
0.26	0.1	0.1	N	61.4	41.1	41.3	20.1	51.4	31.8	32.0	19.4
4.01	0.2	0.2	N	56.0	39.1	39.5	16.5	46.0	25.2	25.6	20.4
4.07	0.2	0.2	H	56.0	40.8	41.2	14.8	46.0	25.9	26.3	19.7
4.13	0.2	0.2	H	56.0	40.6	41.0	15.0	46.0	25.8	26.2	19.8
26.89	1.0	0.3	N	60.0	40.0	41.3	18.7	50.0	27.6	28.9	21.1
26.95	1.0	0.3	H	60.0	39.5	40.8	19.2	50.0	28.1	29.4	20.6
		</									



## Radiated Electric Field Emissions

Frequency [MHz]	Reading [dBuV/m]	Pol.	Height [m]	Correction Factor		Limits [dBuV/m]	Result [dBuV/m]	Margin [dB]
				Antenna	Cable			
85.35	11.2	V	2.6	8.7	1.7	30.0	21.6	8.4
125.17	13.8	V	2.3	9.4	2.0	30.0	25.2	4.8
314.21	16.5	H	3.5	11.3	3.4	37.0	31.2	5.8
601.99	7.6	H	3.2	17.0	4.7	37.0	29.3	7.7
692.12	9.4	H	4.0	18.2	5.0	37.0	32.6	4.4
752.82	4.0	V	1.5	19.0	5.2	37.0	28.2	8.8
753.95	7.4	H	2.1	19.0	5.2	37.0	31.6	5.4