



Engineering Solutions & Electromagnetic Compatibility Services

FCC/IC Certification Report

**Harris Corporation
221 Jefferson Ridge Parkway
Lynchburg, VA 24501
Paresh Chauhan
Phone: (434) 455-9290**

**MODEL: XL-200P
Multi-Band Portable Land Mobile Radio**

**FCC ID: OWDTR-0133-E
IC: 3636B-0133**

February 19, 2015

Standards Referenced for this Report	
Part 2: 2014	Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
Part 15: 2014	Radio Frequency Devices
Part 22: 2014	Public Mobile Services
Part 74: 2014	Experimental Radio, Auxiliary, Special Broadcast and Other Program Distributional Services
Part 80: 2014	Stations in the Maritime Services
Part 90: 2014	Private Land Mobile Radio Services
TIA-EIA-603-C August 2004	Land Mobile FM or PM Communications Equipment – Measurement and Performance Standards
Industry Canada RSS-119 Issue 11	Land Mobile and Fixed Radio Transmitters and Receivers Operating in the Frequency Range 27.41- 960 MHz

Report Prepared By: Daniel Baltzell

Document Number: 2014103

This report may not be reproduced, except in full, without the full written approval of Rhein Tech Laboratories, Inc. and Harris Corporation. Test results relate only to the item tested.

*These tests are accredited and meet the requirements of ISO/IEC 17025 as verified by ANAB.
Refer to certificate and scope of accreditation AT-1445.*

Frequency Range (MHz)	Rated Transmit Power (W) (Conducted)	Frequency Tolerance (ppm)	Transmit Model/ Emission Designator
136-174	1-6	0.4	16K0F3E (Analog Voice; WB)
136-174	1-6	0.4	16K0F1D/E (EDACS 2-Level FSK 9600 Data/Digital Voice; WB)
136-174	1-6	0.4	11K0F3E (Analog Voice; NB)
136-174	1-6	0.4	11K7F1D/E (EDACS 2-Level FSK 9600 Data/Digital Voice; NB)
136-174	1-6	0.4	7K10F1D/E (EDACS 2-level FSK 4800; Data/Digital Voice)
136-174	1-6	0.4	8K40F1D/E (4-level C4FM Data/Voice; P25 Phase 1)
136-174	1-6	0.4	8K10DXW (4-level H-CPM (TDMA) Data/Voice; P25 Phase 2)
378-522	1-5	0.7	16K0F3E (Analog Voice; WB)
378-522	1-5	0.7	16K0F1D/E (EDACS 2-Level FSK 9600 Data/Digital Voice; WB)
378-522	1-5	0.7	11K0F3E (Analog Voice; NB)
378-522	1-5	0.7	11K7F1D/E (EDACS 2-Level FSK 9600 Data/Digital Voice; NB)
378-522	1-5	0.7	7K10F1D/E (EDACS 2-level FSK 4800; Data/Digital Voice)
378-522	1-5	0.7	8K40F1D/E (4-level C4FM Data/Voice; P25 Phase 1)
378-522	1-5	0.7	8K10DXW (4-level H-CPM (TDMA) Data/Voice; P25 Phase 2)
768-776; 798-806 ¹	0.5-3	0.8	11K0F3E (Analog Voice; NB)
768-776; 798-806 ¹	0.5-3	0.8	11K7F1D/E (EDACS 2-Level FSK 9600 Data/Digital Voice; NB)
768-776; 798-806 ¹	0.5-3	0.8	15K4F9W (OpenSky; 4-level FSK Data/Voice [SMR]; WB)
768-776; 798-806 ¹	0.5-3	0.8	8K40F9W (OpenSky; 4-level FSK Data/Voice [Narrowband]; WB)
768-776; 798-806 ¹	0.5-3	0.8	8K40F1D/E (4-level C4FM Data/Voice; P25 Phase 1)
768-776; 798-806 ¹	0.5-3	0.8	8K10DXW (4-level H-CPM (TDMA) Data/Voice; P25 Phase 2)

¹Compliance with the 2 Watt ERP maximum requirement in the itinerant frequencies of the 700 MHz band is being met without reducing conducted power due to antenna losses that reduce the ERP. See the Subpart R attestation statement. Grant power for these should be 2.6W. ERP, given the antenna losses, is less than 2W.

Frequency Range (MHz)	Rated Transmit Power (W) (Conducted)	Frequency Tolerance (ppm)	Transmit Mode/ Emission Designator
806-816; 851-861	0.5-3	0.6	16K0F3E (Analog Voice; WB)
806-816; 851-861	0.5-3	0.6	16K0F1D/E (EDACS 2-Level FSK 9600 Data/Digital Voice; WB)
806-816; 851-861	0.5-3	0.6	14K0F3E (EDACS Analog Voice) (NPSPAC)
806-816; 851-861	0.5-3	0.6	14K0F1D/E (EDACS 2-Level FSK 9600 Data/Digital Voice) (NPSPAC)
806-816; 851-861	0.5-3	0.6	11K0F3E (Analog Voice; NB)
806-816; 851-861	0.5-3	0.6	11K7F1D/E (EDACS 2-Level FSK 9600 Data/Digital Voice; NB)
806-816; 851-861	0.5-3	0.5	15K4F9W (OpenSky; 4-level FSK Data/Voice [SMR]; WB)
806-816; 851-861	0.5-3	0.5	12K1F9W (OpenSky; 4-level FSK Data/Voice [NPSPAC]; WB)
806-816; 851-861	0.5-3	0.5	8K40F9W (OpenSky; 4-level FSK Data/Voice [Narrowband]; WB)
806-816; 851-861	0.5-3	0.5	8K40F1D/E (4-level C4FM Data/Voice; P25 Phase 1)
806-816; 851-861	0.5-3	0.5	8K10DXW (4-level H-CPM (TDMA) Data/Voice; P25 Phase 2)

700 MHz Band Low Power Channels

Channel No. (6.25 kHz)	Channel No. (12.5 kHz)	12.5 kHz Channel Spaced Tx Center Frequencies	
		Original 700 MHz Band Plan (MHz)	Revised 700 MHz Band Plan (MHz)
1	1-2	764.006250	769.006250
2			
3	3-4	764.018750	769.018750
4			
5	5-6	764.031250	769.031250
6			
7	7-8	764.043750	769.043750
8			
9	9-10	764.056250	769.056250
10			
11	11-12	764.068750	769.068750
12			
949	949-950	775.931250	774.931250
950			
951	951-952	775.943750	774.943750
952			
953	953-954	775.956250	774.956250
954			
955	955-956	775.968750	774.968750
956			
957	957-958	775.981250	774.981250
958			
959	959-960	775.993750	774.993750
960			
961	961-962	794.006250	799.006250
962			
963	963-964	794.018750	799.018750
964			
965	965-966	794.031250	799.031250
966			
967	967-968	794.043750	799.043750
968			
969	969-9700	794.056250	799.056250
970			
971	971-972	794.068750	799.068750
972			
1909	1909-1910	805.931250	804.931250
1910			
1911	1911-1912	805.943750	804.943750
1912			

Rhein Tech Laboratories, Inc.
 360 Herndon Parkway
 Suite 1400
 Herndon, VA 20170
<http://www.rheintech.com>

Client: Harris Corporation
 Model: XL-200P Portable Radio
 IDs: - OWDTR-0133-E/3636B-0133
 Standards: FCC 22/74/80/90/IC RSS-119
 Report #: 2014103

Channel No. (6.25 kHz)	Channel No. (12.5 kHz)	12.5 kHz Channel Spaced Tx Center Frequencies	
		Original 700 MHz Band Plan (MHz)	Revised 700 MHz Band Plan (MHz)
1913	1913-1914	805.956250	804.956250
1914			
1915	1915-19166	805.968750	804.968750
1916			
1917	1917-1918	805.981250	804.981250
1918			
1919	1919-19200	805.993750	804.993750
1920			

Table of Contents

1	Test Result Summary	20
2	General Information	20
2.1	Test Facility	20
2.2	Related Submittal(s)/Grant(s)	20
2.3	Grant Notes	21
2.4	Tested System Details	21
3	FCC Rules and Regulations Part 2.1033(C)(8): Voltages and Currents Through The Final Amplifying Stage	22
4	FCC Rules and Regulations Part 2.1046(a): RF Power Output: Conducted, Part 90.541(b)/90.542(a)(6): Transmitting Power Limits; Part 80.215: Transmitter Power; Part 74.461: Transmitter Power	23
4.1	Test Procedure	23
4.2	Test Data	24
5	FCC Rules and Regulations Part 2.1051: Spurious Emissions at Antenna Terminals; Part 90.210: Emission Limitations; Part 80.217: Suppression of Interference aboard Ships	26
5.1	Test Procedure	26
5.2	Test Data	27
6	FCC Rules and Regulations Part 90.543(a): Emission Limitations: ACP Requirements	30
6.1	Test Procedure	30
6.2	Test Data	32
7	FCC Rules and Regulations Part 90.210(g) and Part 2.1053(a): Field Strength of Spurious Radiation; Part 90.543(f): Out of Band Emissions Limit	93
7.1	Test Procedure	93
7.2	Test Data	93
7.2.1	CFR 47 Part 90.210 Requirements	93
7.2.2	CFR 47 Part 90.543(f) Requirements	96
8	FCC Rules and Regulations Part 2.1049(c)(1): Occupied Bandwidth; Part 90.210: Authorized Bandwidth; Part 74.462: Authorized Bandwidth and Emissions	98
8.1	Test Procedure	98
8.2	Test Data	99
9	FCC Rules and Regulation Part 2.1055: Frequency Stability; Part 90.213, 90.539: Frequency Stability; Part 80.209: Frequency Stability; Part 74.464: Frequency Tolerance	354
9.1	Test Procedure	354
9.2	Test Data	356
9.2.1	Frequency Stability/Voltage Variation	368
10	FCC Part 2.1047: Modulation Characteristics; Part 80.213: Modulation Requirements; Part 74.463: Modulation Requirements.	376
10.1	Test Procedures	376
10.1.1	Audio Frequency Response	376
10.1.2	Audio Low Pass Filter Response	376
10.1.3	Modulation Limiting	377
10.2	Test Data	377
10.2.1	Audio Frequency Response	377
10.2.2	Audio Low Pass Filter Response	392
10.2.3	Modulation Limiting	407
11	FCC Rules and Regulations Part 90.214: Transient Frequency Response; Part 74.462(c): Authorized Bandwidth and Emissions	462
11.1	Test Procedure	462
11.2	Test Data	463
12	FCC Rules and Regulations Part 2.202: Necessary Bandwidth and Emission Bandwidth	491

13 Conclusion	493
---------------------	-----

Table of Figures

Figure 2-1: Configuration of Tested System.....	22
---	----

Table of Tables

Table 2-1: Equipment Under Test (EUT).....	21
Table 2-2: Auxiliary Equipment	21
Table 4-1: RF Conducted Output Power - Measured.....	24
Table 4-2: Test Equipment Used For Testing RF Power Output - Conducted.....	25
Table 5-1: Test Equipment Used For Testing Spurious Emissions	29
Table 6-1: Adjacent Channel Power – 768.0125 MHz; Narrowband Analog; 400 kHz – RX band.....	32
Table 6-2: Adjacent Channel Power – 769.0125 MHz; Narrowband Analog; 400 kHz – RX band.....	33
Table 6-3: Adjacent Channel Power – 771.0125 MHz; Narrowband Analog; 400 kHz – RX band.....	34
Table 6-4: Adjacent Channel Power – 775.0125 MHz; Narrowband Analog; 400 kHz – RX band.....	35
Table 6-5: Adjacent Channel Power – 775.9875 MHz; Narrowband Analog; 400 kHz – RX band.....	36
Table 6-6: Adjacent Channel Power – 798.0125 MHz; Narrowband Analog; 400 kHz – RX band.....	37
Table 6-7: Adjacent Channel Power – 799.0125 MHz; Narrowband Analog; 400 kHz – RX band.....	38
Table 6-8: Adjacent Channel Power – 801.0125 MHz; Narrowband Analog; 400 kHz – RX band.....	39
Table 6-9: Adjacent Channel Power – 805.0125 MHz; Narrowband Analog; 400 kHz – RX band.....	40
Table 6-10: Adjacent Channel Power – 805.9875 MHz; Narrowband Analog; 400 kHz – RX band.....	41
Table 6-11: Adjacent Channel Power – 768.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band	42
Table 6-12: Adjacent Channel Power – 769.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band	43
Table 6-13: Adjacent Channel Power – 771.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band	44
Table 6-14: Adjacent Channel Power – 775.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band	45
Table 6-15: Adjacent Channel Power – 775.9875 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band	46
Table 6-16: Adjacent Channel Power – 798.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band	47
Table 6-17: Adjacent Channel Power – 799.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band	48
Table 6-18: Adjacent Channel Power – 801.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band	49
Table 6-19: Adjacent Channel Power – 805.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band	50
Table 6-20: Adjacent Channel Power – 805.9875 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band	51
Table 6-21: Adjacent Channel Power – 768.0125 MHz; OTP SMR; 400 kHz – RX band	52
Table 6-22: Adjacent Channel Power – 769.0125 MHz; OTP SMR; 400 kHz – RX band	53
Table 6-23: Adjacent Channel Power – 771.0125 MHz; OTP SMR; 400 kHz – RX band	54
Table 6-24: Adjacent Channel Power – 775.0125 MHz; OTP SMR; 400 kHz – RX band	55
Table 6-25: Adjacent Channel Power – 775.9875 MHz; OTP SMR; 400 kHz – RX band	56
Table 6-26: Adjacent Channel Power – 798.0125 MHz; OTP SMR; 400 kHz – RX band	57
Table 6-27: Adjacent Channel Power – 799.0125 MHz; OTP SMR; 400 kHz – RX band	58
Table 6-28: Adjacent Channel Power – 801.0125 MHz; OTP SMR; 400 kHz – RX band	59
Table 6-29: Adjacent Channel Power – 805.0125 MHz; OTP SMR; 400 kHz – RX band	60
Table 6-30: Adjacent Channel Power – 805.9875 MHz; OTP SMR; 400 kHz – RX band	61
Table 6-31: Adjacent Channel Power – 768.0125 MHz; OTP Narrowband; 400 kHz – RX band	62
Table 6-32: Adjacent Channel Power – 769.0125 MHz; OTP Narrowband; 400 kHz – RX band	63
Table 6-33: Adjacent Channel Power – 771.0125 MHz; OTP Narrowband; 400 kHz – RX band	64
Table 6-34: Adjacent Channel Power – 775.0125 MHz; OTP Narrowband; 400 kHz – RX band	65
Table 6-35: Adjacent Channel Power – 775.9875 MHz; OTP Narrowband; 400 kHz – RX band	66
Table 6-36: Adjacent Channel Power – 798.0125 MHz; OTP Narrowband; 400 kHz – RX band	67
Table 6-37: Adjacent Channel Power – 799.0125 MHz; OTP Narrowband; 400 kHz – RX band	68

Table 6-38:	Adjacent Channel Power – 801.0125 MHz; OTP Narrowband; 400 kHz – RX band	69
Table 6-39:	Adjacent Channel Power – 805.0125 MHz; OTP Narrowband; 400 kHz – RX band	70
Table 6-40:	Adjacent Channel Power – 805.9875 MHz; OTP Narrowband; 400 kHz – RX band	71
Table 6-41:	Adjacent Channel Power – 768.0125 MHz; P25; 400 kHz – RX band	72
Table 6-42:	Adjacent Channel Power – 769.0125 MHz; P25; 400 kHz – RX band	73
Table 6-43:	Adjacent Channel Power – 771.0125 MHz; P25; 400 kHz – RX band	74
Table 6-44:	Adjacent Channel Power – 775.0125 MHz; P25; 400 kHz – RX band	75
Table 6-45:	Adjacent Channel Power – 775.9875 MHz; P25; 400 kHz – RX band	76
Table 6-46:	Adjacent Channel Power – 798.0125 MHz; P25; 400 kHz – RX band	77
Table 6-47:	Adjacent Channel Power – 799.0125 MHz; P25; 400 kHz – RX band	78
Table 6-48:	Adjacent Channel Power – 801.0125 MHz; P25; 400 kHz – RX band	79
Table 6-49:	Adjacent Channel Power – 805.0125 MHz; P25; 400 kHz – RX band	80
Table 6-50:	Adjacent Channel Power – 805.9875 MHz; P25; 400 kHz – RX band	81
Table 6-51:	Adjacent Channel Power – 768.0125 MHz; P25 Phase 2; 400 kHz – RX band	82
Table 6-52:	Adjacent Channel Power – 769.0125 MHz; P25 Phase 2; 400 kHz – RX band	83
Table 6-53:	Adjacent Channel Power – 771.0125 MHz; P25 Phase 2; 400 kHz – RX band	84
Table 6-54:	Adjacent Channel Power – 775.0125 MHz; P25 Phase 2; 400 kHz – RX band	85
Table 6-55:	Adjacent Channel Power – 775.9875 MHz; P25 Phase 2; 400 kHz – RX band	86
Table 6-56:	Adjacent Channel Power – 798.0125 MHz; P25 Phase 2; 400 kHz – RX band	87
Table 6-57:	Adjacent Channel Power – 799.0125 MHz; P25 Phase 2; 400 kHz – RX band	88
Table 6-58:	Adjacent Channel Power – 801.0125 MHz; P25 Phase 2; 400 kHz – RX band	89
Table 6-59:	Adjacent Channel Power – 805.0125 MHz; P25 Phase 2; 400 kHz – RX band	90
Table 6-60:	Adjacent Channel Power – 805.9875 MHz; P25 Phase 2; 400 kHz – RX band	91
Table 6-61:	Test Equipment Used For Testing ACP Requirements	92
Table 7-1:	Field Strength of Spurious Radiation - 378.0125 MHz.....	93
Table 7-2:	Field Strength of Spurious Radiation - 406.1000 MHz.....	94
Table 7-3:	Field Strength of Spurious Radiation - 418.0125 MHz.....	94
Table 7-4:	Field Strength of Spurious Radiation - 430.0125 MHz.....	94
Table 7-5:	Field Strength of Spurious Radiation - 450.0125 MHz.....	94
Table 7-6:	Field Strength of Spurious Radiation - 454.0125 MHz.....	94
Table 7-7:	Field Strength of Spurious Radiation - 456.0125 MHz.....	95
Table 7-8:	Field Strength of Spurious Radiation - 459.0250 MHz.....	95
Table 7-9:	Field Strength of Spurious Radiation - 459.9750 MHz.....	95
Table 7-10:	Field Strength of Spurious Radiation - 470.0125 MHz.....	95
Table 7-11:	Field Strength of Spurious Radiation	96
Table 7-12:	Test Equipment Used For Testing Field Strength of Spurious Radiation	97
Table 8-1:	Test Equipment Used For Testing Occupied Bandwidth	353
Table 9-1:	Temperature Frequency Stability – 136.0125 MHz	356
Table 9-2:	Temperature Frequency Stability – 138.0125 MHz	356
Table 9-3:	Temperature Frequency Stability – 141.0125 MHz	356
Table 9-4:	Temperature Frequency Stability – 144.0125 MHz	357
Table 9-5:	Temperature Frequency Stability – 148.0125 MHz	357
Table 9-6:	Temperature Frequency Stability – 150.0125 MHz	357
Table 9-7:	Temperature Frequency Stability – 156.8000 MHz	358
Table 9-8:	Temperature Frequency Stability – 162.0125 MHz	358
Table 9-9:	Temperature Frequency Stability – 173.9875 MHz	358
Table 9-10:	Temperature Frequency Stability – 378.0125 MHz	359
Table 9-11:	Temperature Frequency Stability – 406.1000 MHz	359
Table 9-12:	Temperature Frequency Stability – 418.0125 MHz	359
Table 9-13:	Temperature Frequency Stability – 430.0125 MHz	360
Table 9-14:	Temperature Frequency Stability – 450.0125 MHz	360
Table 9-15:	Temperature Frequency Stability – 454.0125 MHz	360
Table 9-16:	Temperature Frequency Stability – 456.0125 MHz	361

Table 9-17:	Temperature Frequency Stability – 459.0250 MHz	361
Table 9-18:	Temperature Frequency Stability – 459.9750 MHz	361
Table 9-19:	Temperature Frequency Stability – 470.0125 MHz	362
Table 9-20:	Temperature Frequency Stability – 511.9875 MHz	362
Table 9-21:	Temperature Frequency Stability – 521.9875 MHz	362
Table 9-22:	Temperature Frequency Stability – 768.0125 MHz	363
Table 9-23:	Temperature Frequency Stability – 769.0125 MHz	363
Table 9-24:	Temperature Frequency Stability – 771.0125 MHz	363
Table 9-25:	Temperature Frequency Stability – 775.0125 MHz	364
Table 9-26:	Temperature Frequency Stability – 775.9875 MHz	364
Table 9-27:	Temperature Frequency Stability – 798.0125 MHz	364
Table 9-28:	Temperature Frequency Stability – 799.0125 MHz	365
Table 9-29:	Temperature Frequency Stability – 801.0125 MHz	365
Table 9-30:	Temperature Frequency Stability – 805.0125 MHz	365
Table 9-31:	Temperature Frequency Stability – 805.9875 MHz	366
Table 9-32:	Temperature Frequency Stability – 806.0250 MHz	366
Table 9-33:	Temperature Frequency Stability – 809.0000 MHz	366
Table 9-34:	Temperature Frequency Stability – 815.9875 MHz	367
Table 9-35:	Temperature Frequency Stability – 851.0250 MHz	367
Table 9-36:	Temperature Frequency Stability – 856.0250 MHz	367
Table 9-37:	Temperature Frequency Stability – 860.9875 MHz	368
Table 9-38:	Frequency Stability/Voltage Variation – 136.0125 MHz	368
Table 9-39:	Frequency Stability/Voltage Variation – 138.0125 MHz	368
Table 9-40:	Frequency Stability/Voltage Variation – 141.0125 MHz	368
Table 9-41:	Frequency Stability/Voltage Variation – 144.0125 MHz	369
Table 9-42:	Frequency Stability/Voltage Variation – 148.0125 MHz	369
Table 9-43:	Frequency Stability/Voltage Variation – 150.0125 MHz	369
Table 9-44:	Frequency Stability/Voltage Variation – 156.8000 MHz	369
Table 9-45:	Frequency Stability/Voltage Variation – 162.0125 MHz	369
Table 9-46:	Frequency Stability/Voltage Variation – 173.9875 MHz	369
Table 9-47:	Frequency Stability/Voltage Variation – 378.0125 MHz	370
Table 9-48:	Frequency Stability/Voltage Variation – 406.1000 MHz	370
Table 9-49:	Frequency Stability/Voltage Variation – 418.0125 MHz	370
Table 9-50:	Frequency Stability/Voltage Variation – 430.0125 MHz	370
Table 9-51:	Frequency Stability/Voltage Variation – 450.0125 MHz	370
Table 9-52:	Frequency Stability/Voltage Variation – 454.0125 MHz	370
Table 9-53:	Frequency Stability/Voltage Variation – 456.0125 MHz	371
Table 9-54:	Frequency Stability/Voltage Variation – 459.0250 MHz	371
Table 9-55:	Frequency Stability/Voltage Variation – 459.9750 MHz	371
Table 9-56:	Frequency Stability/Voltage Variation – 470.0125 MHz	371
Table 9-57:	Frequency Stability/Voltage Variation – 511.9875 MHz	371
Table 9-58:	Frequency Stability/Voltage Variation – 521.9875 MHz	371
Table 9-59:	Frequency Stability/Voltage Variation – 768.0125 MHz	372
Table 9-60:	Frequency Stability/Voltage Variation – 769.0125 MHz	372
Table 9-61:	Frequency Stability/Voltage Variation – 771.0125 MHz	372
Table 9-62:	Frequency Stability/Voltage Variation – 775.0125 MHz	372
Table 9-63:	Frequency Stability/Voltage Variation – 775.9875 MHz	372
Table 9-64:	Frequency Stability/Voltage Variation – 798.0125 MHz	372
Table 9-65:	Frequency Stability/Voltage Variation – 799.0125 MHz	373
Table 9-66:	Frequency Stability/Voltage Variation – 801.0125 MHz	373
Table 9-67:	Frequency Stability/Voltage Variation – 805.0125 MHz	373
Table 9-68:	Frequency Stability/Voltage Variation – 805.9875 MHz	373
Table 9-69:	Frequency Stability/Voltage Variation – 806.0250 MHz	373

Table 9-70:	Frequency Stability/Voltage Variation – 809.0000 MHz	373
Table 9-71:	Frequency Stability/Voltage Variation – 815.9875 MHz	374
Table 9-72:	Frequency Stability/Voltage Variation – 851.0250 MHz	374
Table 9-73:	Frequency Stability/Voltage Variation – 856.0250 MHz	374
Table 9-74:	Frequency Stability/Voltage Variation – 860.9875 MHz	374
Table 9-75:	Test Equipment Used For Testing Frequency Stability.....	375
Table 10-1:	Test Equipment Used For Modulation Requirements	461
Table 11-1:	Test Equipment Used For Testing Transient Frequency Behavior	490

Table of Plots

Plot 5-1:	Spurious Emissions at Antenna Terminals – 430.0125 MHz; Narrowband; 1-4 GHz	28
Plot 6-1:	Adjacent Channel Power – 768.0125 MHz; Narrowband Analog; <400 kHz.....	32
Plot 6-2:	Adjacent Channel Power – 769.0125 MHz; Narrowband Analog; <400 kHz.....	33
Plot 6-3:	Adjacent Channel Power – 771.0125 MHz; Narrowband Analog; <400 kHz.....	34
Plot 6-4:	Adjacent Channel Power – 775.0125 MHz; Narrowband Analog; <400 kHz.....	35
Plot 6-5:	Adjacent Channel Power – 775.9875 MHz; Narrowband Analog; <400 kHz.....	36
Plot 6-6:	Adjacent Channel Power – 798.0125 MHz; Narrowband Analog; <400 kHz.....	37
Plot 6-7:	Adjacent Channel Power – 799.0125 MHz; Narrowband Analog; <400 kHz.....	38
Plot 6-8:	Adjacent Channel Power – 801.0125 MHz; Narrowband Analog; <400 kHz.....	39
Plot 6-9:	Adjacent Channel Power – 805.0125 MHz; Narrowband Analog; <400 kHz.....	40
Plot 6-10:	Adjacent Channel Power – 805.9875 MHz; Narrowband Analog; <400 kHz.....	41
Plot 6-11:	Adjacent Channel Power – 768.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz	42
Plot 6-12:	Adjacent Channel Power – 769.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz	43
Plot 6-13:	Adjacent Channel Power – 771.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz	44
Plot 6-14:	Adjacent Channel Power – 775.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz	45
Plot 6-15:	Adjacent Channel Power – 775.9875 MHz; EDACS 2-Level FSK 9600; <400 kHz	46
Plot 6-16:	Adjacent Channel Power – 798.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz	47
Plot 6-17:	Adjacent Channel Power – 799.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz	48
Plot 6-18:	Adjacent Channel Power – 801.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz	49
Plot 6-19:	Adjacent Channel Power – 805.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz	50
Plot 6-20:	Adjacent Channel Power – 805.9875 MHz; EDACS 2-Level FSK 9600; <400 kHz	51
Plot 6-21:	Adjacent Channel Power – 768.0125 MHz; OTP SMR; <400 kHz	52
Plot 6-22:	Adjacent Channel Power – 769.0125 MHz; OTP SMR; <400 kHz	53
Plot 6-23:	Adjacent Channel Power – 771.0125 MHz; OTP SMR; <400 kHz	54
Plot 6-24:	Adjacent Channel Power – 775.0125 MHz; OTP SMR; <400 kHz	55
Plot 6-25:	Adjacent Channel Power – 775.9875 MHz; OTP SMR; <400 kHz	56
Plot 6-26:	Adjacent Channel Power – 798.0125 MHz; OTP SMR; <400 kHz	57
Plot 6-27:	Adjacent Channel Power – 799.0125 MHz; OTP SMR; <400 kHz	58
Plot 6-28:	Adjacent Channel Power – 801.0125 MHz; OTP SMR; <400 kHz	59
Plot 6-29:	Adjacent Channel Power – 805.0125 MHz; OTP SMR; <400 kHz	60
Plot 6-30:	Adjacent Channel Power – 805.9875 MHz; OTP SMR; <400 kHz	61
Plot 6-31:	Adjacent Channel Power – 768.0125 MHz; OTP Narrowband; <400 kHz	62
Plot 6-32:	Adjacent Channel Power – 769.0125 MHz; OTP Narrowband; <400 kHz	63
Plot 6-33:	Adjacent Channel Power – 771.0125 MHz; OTP Narrowband; <400 kHz	64
Plot 6-34:	Adjacent Channel Power – 775.0125 MHz; OTP Narrowband; <400 kHz	65
Plot 6-35:	Adjacent Channel Power – 775.9875 MHz; OTP Narrowband; <400 kHz	66
Plot 6-36:	Adjacent Channel Power – 798.0125 MHz; OTP Narrowband; <400 kHz	67
Plot 6-37:	Adjacent Channel Power – 799.0125 MHz; OTP Narrowband; <400 kHz	68
Plot 6-38:	Adjacent Channel Power – 801.0125 MHz; OTP Narrowband; <400 kHz	69
Plot 6-39:	Adjacent Channel Power – 805.0125 MHz; OTP Narrowband; <400 kHz	70
Plot 6-40:	Adjacent Channel Power – 805.9875 MHz; OTP Narrowband; <400 kHz	71

Plot 6-41:	Adjacent Channel Power – 768.0125 MHz; P25; <400 kHz	72
Plot 6-42:	Adjacent Channel Power – 769.0125 MHz; P25; <400 kHz	73
Plot 6-43:	Adjacent Channel Power – 771.0125 MHz; P25; <400 kHz	74
Plot 6-44:	Adjacent Channel Power – 775.0125 MHz; P25; <400 kHz	75
Plot 6-45:	Adjacent Channel Power – 775.9875 MHz; P25; <400 kHz	76
Plot 6-46:	Adjacent Channel Power – 798.0125 MHz; P25; <400 kHz	77
Plot 6-47:	Adjacent Channel Power – 799.0125 MHz; P25; <400 kHz	78
Plot 6-48:	Adjacent Channel Power – 801.0125 MHz; P25; <400 kHz	79
Plot 6-49:	Adjacent Channel Power – 805.0125 MHz; P25; <400 kHz	80
Plot 6-50:	Adjacent Channel Power – 805.9875 MHz; P25; <400 kHz	81
Plot 6-51:	Adjacent Channel Power – 768.0125 MHz; P25 Phase 2; <400 kHz	82
Plot 6-52:	Adjacent Channel Power – 769.0125 MHz; P25 Phase 2; <400 kHz	83
Plot 6-53:	Adjacent Channel Power – 771.0125 MHz; P25 Phase 2; <400 kHz	84
Plot 6-54:	Adjacent Channel Power – 775.0125 MHz; P25 Phase 2; <400 kHz	85
Plot 6-55:	Adjacent Channel Power – 775.9875 MHz; P25 Phase 2; <400 kHz	86
Plot 6-56:	Adjacent Channel Power – 798.0125 MHz; P25 Phase 2; <400 kHz	87
Plot 6-57:	Adjacent Channel Power – 799.0125 MHz; P25 Phase 2; <400 kHz	88
Plot 6-58:	Adjacent Channel Power – 801.0125 MHz; P25 Phase 2; <400 kHz	89
Plot 6-59:	Adjacent Channel Power – 805.0125 MHz; P25 Phase 2; <400 kHz	90
Plot 6-60:	Adjacent Channel Power – 805.9875 MHz; P25 Phase 2; <400 kHz	91
Plot 8-1:	Occupied Bandwidth – 136.0125 MHz; Narrowband Analog (Mask D)	99
Plot 8-2:	Occupied Bandwidth – 138.0125 MHz; Narrowband Analog (Mask D)	100
Plot 8-3:	Occupied Bandwidth – 141.0125 MHz; Narrowband Analog (Mask D)	101
Plot 8-4:	Occupied Bandwidth – 144.0125 MHz; Narrowband Analog (Mask D)	102
Plot 8-5:	Occupied Bandwidth – 148.0125 MHz; Narrowband Analog (Mask D)	103
Plot 8-6:	Occupied Bandwidth – 150.0125 MHz; Narrowband Analog (Mask D)	104
Plot 8-7:	Occupied Bandwidth – 156.8000 MHz; Narrowband Analog (Mask D)	105
Plot 8-8:	Occupied Bandwidth – 162.0125 MHz; Narrowband Analog (Mask D)	106
Plot 8-9:	Occupied Bandwidth – 173.9875 MHz; Narrowband Analog (Mask D)	107
Plot 8-10:	Occupied Bandwidth – 378.0125 MHz; Narrowband Analog (Mask D)	108
Plot 8-11:	Occupied Bandwidth – 406.1000 MHz; Narrowband Analog (Mask D)	109
Plot 8-12:	Occupied Bandwidth – 418.0125 MHz; Narrowband Analog (Mask D)	110
Plot 8-13:	Occupied Bandwidth – 430.0125 MHz; Narrowband Analog (Mask D)	111
Plot 8-14:	Occupied Bandwidth – 450.0125 MHz; Narrowband Analog (Mask D)	112
Plot 8-15:	Occupied Bandwidth – 454.0125 MHz; Narrowband Analog (Mask D)	113
Plot 8-16:	Occupied Bandwidth – 456.0125 MHz; Narrowband Analog (Mask D)	114
Plot 8-17:	Occupied Bandwidth – 459.0250 MHz; Narrowband Analog (Mask D)	115
Plot 8-18:	Occupied Bandwidth – 459.9750 MHz; Narrowband Analog (Mask D)	116
Plot 8-19:	Occupied Bandwidth – 470.0125 MHz; Narrowband Analog (Mask D)	117
Plot 8-20:	Occupied Bandwidth – 511.9875 MHz; Narrowband Analog (Mask D)	118
Plot 8-21:	Occupied Bandwidth – 521.9875 MHz; Narrowband Analog (Mask D)	119
Plot 8-22:	Occupied Bandwidth – 806.0250 MHz; Narrowband Analog (Mask D)	120
Plot 8-23:	Occupied Bandwidth – 809.0000 MHz; Narrowband Analog (Mask D)	121
Plot 8-24:	Occupied Bandwidth – 815.9875 MHz; Narrowband Analog (Mask D)	122
Plot 8-25:	Occupied Bandwidth – 851.0250 MHz; Narrowband Analog (Mask D)	123
Plot 8-26:	Occupied Bandwidth – 856.0250 MHz; Narrowband Analog (Mask D)	124
Plot 8-27:	Occupied Bandwidth – 860.9875 MHz; Narrowband Analog (Mask D)	125
Plot 8-28:	Occupied Bandwidth – 806.0250 MHz; Narrowband Analog (Mask B)	126
Plot 8-29:	Occupied Bandwidth – 809.0000 MHz; Narrowband Analog (Mask B)	127
Plot 8-30:	Occupied Bandwidth – 815.9875 MHz; Narrowband Analog (Mask B)	128
Plot 8-31:	Occupied Bandwidth – 851.0250 MHz; Narrowband Analog (Mask B)	129
Plot 8-32:	Occupied Bandwidth – 856.0250 MHz; Narrowband Analog (Mask B)	130
Plot 8-33:	Occupied Bandwidth – 860.9875 MHz; Narrowband Analog (Mask B)	131

Plot 8-34:	Occupied Bandwidth – 806.0250 MHz; NPSPAC Analog (Mask B)	132
Plot 8-35:	Occupied Bandwidth – 809.0000 MHz; NPSPAC Analog (Mask B)	133
Plot 8-36:	Occupied Bandwidth – 815.9875 MHz; NPSPAC Analog (Mask B)	134
Plot 8-37:	Occupied Bandwidth – 851.0250 MHz; NPSPAC Analog (Mask B)	135
Plot 8-38:	Occupied Bandwidth – 856.0250 MHz; NPSPAC Analog (Mask B)	136
Plot 8-39:	Occupied Bandwidth – 860.9875 MHz; NPSPAC Analog (Mask B)	137
Plot 8-40:	Occupied Bandwidth – 136.0125 MHz; Wideband Analog (Mask B)	138
Plot 8-41:	Occupied Bandwidth – 138.0125 MHz; Wideband Analog (Mask B)	139
Plot 8-42:	Occupied Bandwidth – 141.0125 MHz; Wideband Analog (Mask B)	140
Plot 8-43:	Occupied Bandwidth – 144.0125 MHz; Wideband Analog (Mask B)	141
Plot 8-44:	Occupied Bandwidth – 148.0125 MHz; Wideband Analog (Mask B)	142
Plot 8-45:	Occupied Bandwidth – 150.0125 MHz; Wideband Analog (Mask B)	143
Plot 8-46:	Occupied Bandwidth – 156.8000 MHz; Wideband Analog (Mask B)	144
Plot 8-47:	Occupied Bandwidth – 162.0125 MHz; Wideband Analog (Mask B)	145
Plot 8-48:	Occupied Bandwidth – 173.9875 MHz; Wideband Analog (Mask B)	146
Plot 8-49:	Occupied Bandwidth – 378.0125 MHz; Wideband Analog (Mask B)	147
Plot 8-50:	Occupied Bandwidth – 406.1000 MHz; Wideband Analog (Mask B)	148
Plot 8-51:	Occupied Bandwidth – 418.0125 MHz; Wideband Analog (Mask B)	149
Plot 8-52:	Occupied Bandwidth – 430.0125 MHz; Wideband Analog (Mask B)	150
Plot 8-53:	Occupied Bandwidth – 450.0125 MHz; Wideband Analog (Mask B)	151
Plot 8-54:	Occupied Bandwidth – 454.0125 MHz; Wideband Analog (Mask B)	152
Plot 8-55:	Occupied Bandwidth – 456.0125 MHz; Wideband Analog (Mask B)	153
Plot 8-56:	Occupied Bandwidth – 459.0250 MHz; Wideband Analog (Mask B)	154
Plot 8-57:	Occupied Bandwidth – 459.9750 MHz; Wideband Analog (Mask B)	155
Plot 8-58:	Occupied Bandwidth – 470.0125 MHz; Wideband Analog (Mask B)	156
Plot 8-59:	Occupied Bandwidth – 511.9875 MHz; Wideband Analog (Mask B)	157
Plot 8-60:	Occupied Bandwidth – 521.9875 MHz; Wideband Analog (Mask B)	158
Plot 8-61:	Occupied Bandwidth – 806.0250 MHz; Wideband Analog (Mask B)	159
Plot 8-62:	Occupied Bandwidth – 809.0000 MHz; Wideband Analog (Mask B)	160
Plot 8-63:	Occupied Bandwidth – 815.9875 MHz; Wideband Analog (Mask B)	161
Plot 8-64:	Occupied Bandwidth – 851.0250 MHz; Wideband Analog (Mask B)	162
Plot 8-65:	Occupied Bandwidth – 856.0250 MHz; Wideband Analog (Mask B)	163
Plot 8-66:	Occupied Bandwidth – 860.9875 MHz; Wideband Analog (Mask B)	164
Plot 8-67:	Occupied Bandwidth – 136.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	165
Plot 8-68:	Occupied Bandwidth – 138.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	166
Plot 8-69:	Occupied Bandwidth – 141.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	167
Plot 8-70:	Occupied Bandwidth – 144.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	168
Plot 8-71:	Occupied Bandwidth – 148.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	169
Plot 8-72:	Occupied Bandwidth – 150.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	170
Plot 8-73:	Occupied Bandwidth – 156.8000 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	171
Plot 8-74:	Occupied Bandwidth – 162.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	172
Plot 8-75:	Occupied Bandwidth – 173.9875 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	173
Plot 8-76:	Occupied Bandwidth – 378.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	174
Plot 8-77:	Occupied Bandwidth – 406.1000 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	175
Plot 8-78:	Occupied Bandwidth – 418.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	176
Plot 8-79:	Occupied Bandwidth – 430.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	177
Plot 8-80:	Occupied Bandwidth – 450.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	178
Plot 8-81:	Occupied Bandwidth – 454.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	179
Plot 8-82:	Occupied Bandwidth – 456.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	180
Plot 8-83:	Occupied Bandwidth – 459.0250 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	181
Plot 8-84:	Occupied Bandwidth – 459.9750 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	182
Plot 8-85:	Occupied Bandwidth – 470.0125 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	183
Plot 8-86:	Occupied Bandwidth – 511.9875 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D)	184

Plot 8-87:	Occupied Bandwidth – 521.9875 MHz; EDACS Narrowband 2-level FSK 4800 (Mask D).....185
Plot 8-88:	Occupied Bandwidth – 136.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....186
Plot 8-89:	Occupied Bandwidth – 138.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....187
Plot 8-90:	Occupied Bandwidth – 141.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....188
Plot 8-91:	Occupied Bandwidth – 144.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....189
Plot 8-92:	Occupied Bandwidth – 148.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....190
Plot 8-93:	Occupied Bandwidth – 150.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....191
Plot 8-94:	Occupied Bandwidth – 156.8000 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....192
Plot 8-95:	Occupied Bandwidth – 162.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....193
Plot 8-96:	Occupied Bandwidth – 173.9875 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....194
Plot 8-97:	Occupied Bandwidth – 378.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....195
Plot 8-98:	Occupied Bandwidth – 406.1000 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....196
Plot 8-99:	Occupied Bandwidth – 418.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....197
Plot 8-100:	Occupied Bandwidth – 430.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....198
Plot 8-101:	Occupied Bandwidth – 450.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....199
Plot 8-102:	Occupied Bandwidth – 454.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....200
Plot 8-103:	Occupied Bandwidth – 456.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....201
Plot 8-104:	Occupied Bandwidth – 459.0250 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....202
Plot 8-105:	Occupied Bandwidth – 459.9750 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....203
Plot 8-106:	Occupied Bandwidth – 470.0125 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....204
Plot 8-107:	Occupied Bandwidth – 511.9875 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....205
Plot 8-108:	Occupied Bandwidth – 521.9875 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....206
Plot 8-109:	Occupied Bandwidth – 806.0250 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....207
Plot 8-110:	Occupied Bandwidth – 809.0000 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....208
Plot 8-111:	Occupied Bandwidth – 815.9875 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....209
Plot 8-112:	Occupied Bandwidth – 851.0250 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....210
Plot 8-113:	Occupied Bandwidth – 856.0250 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....211
Plot 8-114:	Occupied Bandwidth – 860.9875 MHz; EDACS Narrowband 2-level FSK 9600 (Mask D).....212
Plot 8-115:	Occupied Bandwidth – 806.0250 MHz; EDACS Narrowband 2-level FSK 9600 (Mask H).....213
Plot 8-116:	Occupied Bandwidth – 809.0000 MHz; EDACS Narrowband 2-level FSK 9600 (Mask G).....214
Plot 8-117:	Occupied Bandwidth – 815.9875 MHz; EDACS Narrowband 2-level FSK 9600 (Mask G).....215
Plot 8-118:	Occupied Bandwidth – 851.0250 MHz; EDACS Narrowband 2-level FSK 9600 (Mask H).....216
Plot 8-119:	Occupied Bandwidth – 856.0250 MHz; EDACS Narrowband 2-level FSK 9600 (Mask G).....217
Plot 8-120:	Occupied Bandwidth – 860.9875 MHz; EDACS Narrowband 2-level FSK 9600 (Mask G).....218
Plot 8-121:	Occupied Bandwidth – 806.0250 MHz; EDACS NPSPAC 2-level FSK 9600 (Mask G).....219
Plot 8-122:	Occupied Bandwidth – 806.0250 MHz; EDACS NPSPAC 2-level FSK 9600 (Mask H).....220
Plot 8-123:	Occupied Bandwidth – 809.0000 MHz; EDACS NPSPAC 2-level FSK 9600 (Mask H).....221
Plot 8-124:	Occupied Bandwidth – 809.0000 MHz; EDACS NPSPAC 2-level FSK 9600 (Mask G).....222
Plot 8-125:	Occupied Bandwidth – 815.9875 MHz; EDACS NPSPAC 2-level FSK 9600 (Mask G).....223
Plot 8-126:	Occupied Bandwidth – 851.0250 MHz; EDACS NPSPAC 2-level FSK 9600 (Mask G).....224
Plot 8-127:	Occupied Bandwidth – 851.0250 MHz; EDACS NPSPAC 2-level FSK 9600 (Mask H).....225
Plot 8-128:	Occupied Bandwidth – 856.0250 MHz; EDACS NPSPAC 2-level FSK 9600 (Mask G).....226
Plot 8-129:	Occupied Bandwidth – 860.9875 MHz; EDACS NPSPAC 2-level FSK 9600 (Mask G).....227
Plot 8-130:	Occupied Bandwidth – 136.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C).....228
Plot 8-131:	Occupied Bandwidth – 138.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C).....229
Plot 8-132:	Occupied Bandwidth – 141.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C).....230
Plot 8-133:	Occupied Bandwidth – 144.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C).....231
Plot 8-134:	Occupied Bandwidth – 148.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C).....232
Plot 8-135:	Occupied Bandwidth – 150.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C).....233
Plot 8-136:	Occupied Bandwidth – 156.8000 MHz; EDACS Wideband 2-level FSK 9600 (Mask C).....234
Plot 8-137:	Occupied Bandwidth – 162.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C).....235
Plot 8-138:	Occupied Bandwidth – 173.9875 MHz; EDACS Wideband 2-level FSK 9600 (Mask C).....236
Plot 8-139:	Occupied Bandwidth – 378.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C).....237

Plot 8-140:	Occupied Bandwidth – 406.1000 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	238
Plot 8-141:	Occupied Bandwidth – 418.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	239
Plot 8-142:	Occupied Bandwidth – 430.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	240
Plot 8-143:	Occupied Bandwidth – 450.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	241
Plot 8-144:	Occupied Bandwidth – 454.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	242
Plot 8-145:	Occupied Bandwidth – 456.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	243
Plot 8-146:	Occupied Bandwidth – 459.0250 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	244
Plot 8-147:	Occupied Bandwidth – 459.9750 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	245
Plot 8-148:	Occupied Bandwidth – 470.0125 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	246
Plot 8-149:	Occupied Bandwidth – 511.9875 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	247
Plot 8-150:	Occupied Bandwidth – 521.9875 MHz; EDACS Wideband 2-level FSK 9600 (Mask C)	248
Plot 8-151:	Occupied Bandwidth – 806.0250 MHz; EDACS Wideband 2-level FSK 9600 (Mask H)	249
Plot 8-152:	Occupied Bandwidth – 806.0250 MHz; EDACS Wideband 2-level FSK 9600 (Mask G)	250
Plot 8-153:	Occupied Bandwidth – 809.0000 MHz; EDACS Wideband 2-level FSK 9600 (Mask H)	251
Plot 8-154:	Occupied Bandwidth – 809.0000 MHz; EDACS Wideband 2-level FSK 9600 (Mask G)	252
Plot 8-155:	Occupied Bandwidth – 815.9875 MHz; EDACS Wideband 2-level FSK 9600 (Mask G)	253
Plot 8-156:	Occupied Bandwidth – 851.0250 MHz; EDACS Wideband 2-level FSK 9600 (Mask H)	254
Plot 8-157:	Occupied Bandwidth – 851.0250 MHz; EDACS Wideband 2-level FSK 9600 (Mask G)	255
Plot 8-158:	Occupied Bandwidth – 856.0250 MHz; EDACS Wideband 2-level FSK 9600 (Mask G)	256
Plot 8-159:	Occupied Bandwidth – 860.9875 MHz; EDACS Wideband 2-level FSK 9600 (Mask G)	257
Plot 8-160:	Occupied Bandwidth – 806.0250 MHz; OTP Narrowband 4-level FSK (Mask D)	258
Plot 8-161:	Occupied Bandwidth – 809.0000 MHz; OTP Narrowband 4-level FSK (Mask D)	259
Plot 8-162:	Occupied Bandwidth – 815.9875 MHz; OTP Narrowband 4-level FSK (Mask D)	260
Plot 8-163:	Occupied Bandwidth – 851.0250 MHz; OTP Narrowband 4-level FSK (Mask D)	261
Plot 8-164:	Occupied Bandwidth – 856.0250 MHz; OTP Narrowband 4-level FSK (Mask D)	262
Plot 8-165:	Occupied Bandwidth – 860.9875 MHz; OTP Narrowband 4-level FSK (Mask D)	263
Plot 8-166:	Occupied Bandwidth – 806.0250 MHz; OTP Narrowband 4-level FSK (Mask H)	264
Plot 8-167:	Occupied Bandwidth – 809.0000 MHz; OTP Narrowband 4-level FSK (Mask H)	265
Plot 8-168:	Occupied Bandwidth – 809.0000 MHz; OTP Narrowband 4-level FSK (Mask G)	266
Plot 8-169:	Occupied Bandwidth – 815.9875 MHz; OTP Narrowband 4-level FSK (Mask G)	267
Plot 8-170:	Occupied Bandwidth – 851.0250 MHz; OTP Narrowband 4-level FSK (Mask H)	268
Plot 8-171:	Occupied Bandwidth – 856.0250 MHz; OTP Narrowband 4-level FSK (Mask G)	269
Plot 8-172:	Occupied Bandwidth – 860.9875 MHz; OTP Narrowband 4-level FSK (Mask G)	270
Plot 8-173:	Occupied Bandwidth – 806.0250 MHz; OTP NPSPAC 4-level FSK (Mask G)	271
Plot 8-174:	Occupied Bandwidth – 806.0250 MHz; OTP NPSPAC 4-level FSK (Mask G)	272
Plot 8-175:	Occupied Bandwidth – 809.0000 MHz; OTP NPSPAC 4-level FSK (Mask H)	273
Plot 8-176:	Occupied Bandwidth – 809.0000 MHz; OTP NPSPAC 4-level FSK (Mask G)	274
Plot 8-177:	Occupied Bandwidth – 815.9875 MHz; OTP NPSPAC 4-level FSK (Mask G)	275
Plot 8-178:	Occupied Bandwidth – 851.0250 MHz; OTP NPSPAC 4-level FSK (Mask H)	276
Plot 8-179:	Occupied Bandwidth – 851.0250 MHz; OTP NPSPAC 4-level FSK (Mask G)	277
Plot 8-180:	Occupied Bandwidth – 856.0250 MHz; OTP NPSPAC 4-level FSK (Mask G)	278
Plot 8-181:	Occupied Bandwidth – 860.9875 MHz; OTP NPSPAC 4-level FSK (Mask G)	279
Plot 8-182:	Occupied Bandwidth – 806.0250 MHz; OTP SMR 4-level FSK (Mask G)	280
Plot 8-183:	Occupied Bandwidth – 809.0000 MHz; OTP SMR 4-level FSK (Mask G)	281
Plot 8-184:	Occupied Bandwidth – 815.9875 MHz; OTP SMR 4-level FSK (Mask G)	282
Plot 8-185:	Occupied Bandwidth – 851.0250 MHz; OTP SMR 4-level FSK (Mask G)	283
Plot 8-186:	Occupied Bandwidth – 856.0250 MHz; OTP SMR 4-level FSK (Mask G)	284
Plot 8-187:	Occupied Bandwidth – 860.9875 MHz; OTP SMR 4-level FSK (Mask G)	285
Plot 8-188:	Occupied Bandwidth – 136.0125 MHz; C4FM (Mask D)	286
Plot 8-189:	Occupied Bandwidth – 138.0125 MHz; C4FM (Mask D)	287
Plot 8-190:	Occupied Bandwidth – 141.0125 MHz; C4FM (Mask D)	288
Plot 8-191:	Occupied Bandwidth – 144.0125 MHz; C4FM (Mask D)	289
Plot 8-192:	Occupied Bandwidth – 148.0125 MHz; C4FM (Mask D)	290

Plot 8-193:	Occupied Bandwidth – 150.0125 MHz; C4FM (Mask D)	291
Plot 8-194:	Occupied Bandwidth – 156.8000 MHz; C4FM (Mask D)	292
Plot 8-195:	Occupied Bandwidth – 162.0125 MHz; C4FM (Mask D)	293
Plot 8-196:	Occupied Bandwidth – 173.9875 MHz; C4FM (Mask D)	294
Plot 8-197:	Occupied Bandwidth – 378.0125 MHz; C4FM (Mask D)	295
Plot 8-198:	Occupied Bandwidth – 406.1000 MHz; C4FM (Mask D)	296
Plot 8-199:	Occupied Bandwidth – 418.0125 MHz; C4FM (Mask D)	297
Plot 8-200:	Occupied Bandwidth – 430.0125 MHz; C4FM (Mask D)	298
Plot 8-201:	Occupied Bandwidth – 450.0125 MHz; C4FM (Mask D)	299
Plot 8-202:	Occupied Bandwidth – 454.0125 MHz; C4FM (Mask D)	300
Plot 8-203:	Occupied Bandwidth – 456.0125 MHz; C4FM (Mask D)	301
Plot 8-204:	Occupied Bandwidth – 459.0250 MHz; C4FM (Mask D)	302
Plot 8-205:	Occupied Bandwidth – 459.9750 MHz; C4FM (Mask D)	303
Plot 8-206:	Occupied Bandwidth – 470.0125 MHz; C4FM (Mask D)	304
Plot 8-207:	Occupied Bandwidth – 511.9875 MHz; C4FM (Mask D)	305
Plot 8-208:	Occupied Bandwidth – 521.9875 MHz; C4FM (Mask D)	306
Plot 8-209:	Occupied Bandwidth – 806.0250 MHz; C4FM (Mask D)	307
Plot 8-210:	Occupied Bandwidth – 809.0000 MHz; C4FM (Mask D)	308
Plot 8-211:	Occupied Bandwidth – 815.9875 MHz; C4FM (Mask D)	309
Plot 8-212:	Occupied Bandwidth – 851.0250 MHz; C4FM (Mask D)	310
Plot 8-213:	Occupied Bandwidth – 856.0250 MHz; C4FM (Mask D)	311
Plot 8-214:	Occupied Bandwidth – 860.9875 MHz; C4FM (Mask D)	312
Plot 8-215:	Occupied Bandwidth – 806.0250 MHz; C4FM (Mask H)	313
Plot 8-216:	Occupied Bandwidth – 809.0000 MHz; C4FM (Mask H)	314
Plot 8-217:	Occupied Bandwidth – 809.0000 MHz; C4FM (Mask G)	315
Plot 8-218:	Occupied Bandwidth – 815.9875 MHz; C4FM (Mask G)	316
Plot 8-219:	Occupied Bandwidth – 851.0250 MHz; C4FM (Mask H)	317
Plot 8-220:	Occupied Bandwidth – 856.0250 MHz; C4FM (Mask G)	318
Plot 8-221:	Occupied Bandwidth – 860.9875 MHz; C4FM (Mask G)	319
Plot 8-222:	Occupied Bandwidth – 136.0125 MHz; C4FM Phase 2 (Mask D)	320
Plot 8-223:	Occupied Bandwidth – 138.0125 MHz; C4FM Phase 2 (Mask D)	321
Plot 8-224:	Occupied Bandwidth – 141.0125 MHz; C4FM Phase 2 (Mask D)	322
Plot 8-225:	Occupied Bandwidth – 144.0125 MHz; C4FM Phase 2 (Mask D)	323
Plot 8-226:	Occupied Bandwidth – 148.0125 MHz; C4FM Phase 2 (Mask D)	324
Plot 8-227:	Occupied Bandwidth – 150.0125 MHz; C4FM Phase 2 (Mask D)	325
Plot 8-228:	Occupied Bandwidth – 156.8000 MHz; C4FM Phase 2 (Mask D)	326
Plot 8-229:	Occupied Bandwidth – 162.0125 MHz; C4FM Phase 2 (Mask D)	327
Plot 8-230:	Occupied Bandwidth – 173.9875 MHz; C4FM Phase 2 (Mask D)	328
Plot 8-231:	Occupied Bandwidth – 378.0125 MHz; C4FM Phase 2 (Mask D)	329
Plot 8-232:	Occupied Bandwidth – 406.1000 MHz; C4FM Phase 2 (Mask D)	330
Plot 8-233:	Occupied Bandwidth – 418.0125 MHz; C4FM Phase 2 (Mask D)	331
Plot 8-234:	Occupied Bandwidth – 430.0125 MHz; C4FM Phase 2 (Mask D)	332
Plot 8-235:	Occupied Bandwidth – 450.0125 MHz; C4FM Phase 2 (Mask D)	333
Plot 8-236:	Occupied Bandwidth – 454.0125 MHz; C4FM Phase 2 (Mask D)	334
Plot 8-237:	Occupied Bandwidth – 456.0125 MHz; C4FM Phase 2 (Mask D)	335
Plot 8-238:	Occupied Bandwidth – 459.0250 MHz; C4FM Phase 2 (Mask D)	336
Plot 8-239:	Occupied Bandwidth – 459.9750 MHz; C4FM Phase 2 (Mask D)	337
Plot 8-240:	Occupied Bandwidth – 470.0125 MHz; C4FM Phase 2 (Mask D)	338
Plot 8-241:	Occupied Bandwidth – 511.9875 MHz; C4FM Phase 2 (Mask D)	339
Plot 8-242:	Occupied Bandwidth – 521.9875 MHz; C4FM Phase 2 (Mask D)	340
Plot 8-243:	Occupied Bandwidth – 806.0250 MHz; C4FM Phase 2 (Mask D)	341
Plot 8-244:	Occupied Bandwidth – 809.0000 MHz; C4FM Phase 2 (Mask D)	342
Plot 8-245:	Occupied Bandwidth – 815.9875 MHz; C4FM Phase 2 (Mask D)	343

Plot 8-246:	Occupied Bandwidth – 851.0250 MHz; C4FM Phase 2 (Mask D).....	344
Plot 8-247:	Occupied Bandwidth – 856.0250 MHz; C4FM Phase 2 (Mask D).....	345
Plot 8-248:	Occupied Bandwidth – 860.9875 MHz; C4FM Phase 2 (Mask D).....	346
Plot 8-249:	Occupied Bandwidth – 806.0250 MHz; C4FM Phase 2 (Mask H).....	347
Plot 8-250:	Occupied Bandwidth – 809.0000 MHz; C4FM Phase 2 (Mask H).....	348
Plot 8-251:	Occupied Bandwidth – 809.0000 MHz; C4FM Phase 2 (Mask G).....	349
Plot 8-252:	Occupied Bandwidth – 815.9875 MHz; C4FM Phase 2 (Mask G).....	350
Plot 8-253:	Occupied Bandwidth – 851.0250 MHz; C4FM Phase 2 (Mask H).....	351
Plot 8-254:	Occupied Bandwidth – 856.0250 MHz; C4FM Phase 2 (Mask G).....	352
Plot 8-255:	Occupied Bandwidth – 860.9875 MHz; C4FM Phase 2 (Mask G).....	353
Plot 10-1:	Modulation Characteristics - Audio Frequency Response – 136.0125 MHz	377
Plot 10-2:	Modulation Characteristics - Audio Frequency Response – 144.0125 MHz	378
Plot 10-3:	Modulation Characteristics - Audio Frequency Response – 173.9875 MHz	379
Plot 10-4:	Modulation Characteristics - Audio Frequency Response – 378.0125 MHz	380
Plot 10-5:	Modulation Characteristics - Audio Frequency Response – 454.0125 MHz	381
Plot 10-6:	Modulation Characteristics - Audio Frequency Response – 521.9875 MHz	382
Plot 10-7:	Modulation Characteristics - Audio Frequency Response – 768.0125 MHz	383
Plot 10-8:	Modulation Characteristics - Audio Frequency Response – 775.9875 MHz	384
Plot 10-9:	Modulation Characteristics - Audio Frequency Response – 805.9875 MHz	385
Plot 10-10:	Modulation Characteristics - Audio Frequency Response – 806.0250 MHz	386
Plot 10-11:	Modulation Characteristics - Audio Frequency Response – 809.0000 MHz	387
Plot 10-12:	Modulation Characteristics - Audio Frequency Response – 815.9875 MHz	388
Plot 10-13:	Modulation Characteristics - Audio Frequency Response – 851.0250 MHz	389
Plot 10-14:	Modulation Characteristics - Audio Frequency Response – 856.0250 MHz	390
Plot 10-15:	Modulation Characteristics - Audio Frequency Response – 860.9875 MHz	391
Plot 10-16:	Modulation Characteristics – Audio Low Pass Filter – 136.0125 MHz	392
Plot 10-17:	Modulation Characteristics – Audio Low Pass Filter – 144.0125 MHz	393
Plot 10-18:	Modulation Characteristics – Audio Low Pass Filter – 173.9875 MHz	394
Plot 10-19:	Modulation Characteristics – Audio Low Pass Filter – 406.1000 MHz (WB)	395
Plot 10-20:	Modulation Characteristics – Audio Low Pass Filter – 454.0125 MHz (WB)	396
Plot 10-21:	Modulation Characteristics – Audio Low Pass Filter – 511.9875 MHz (NB)	397
Plot 10-22:	Modulation Characteristics – Audio Low Pass Filter – 768.0125 MHz	398
Plot 10-23:	Modulation Characteristics – Audio Low Pass Filter – 775.9875 MHz	399
Plot 10-24:	Modulation Characteristics – Audio Low Pass Filter – 805.9875 MHz	400
Plot 10-25:	Modulation Characteristics – Audio Low Pass Filter – 806.0250 MHz	401
Plot 10-26:	Modulation Characteristics – Audio Low Pass Filter – 809.0000 MHz	402
Plot 10-27:	Modulation Characteristics – Audio Low Pass Filter – 815.9875 MHz	403
Plot 10-28:	Modulation Characteristics – Audio Low Pass Filter – 851.0250 MHz	404
Plot 10-29:	Modulation Characteristics – Audio Low Pass Filter – 856.0250 MHz	405
Plot 10-30:	Modulation Characteristics – Audio Low Pass Filter – 860.9875 MHz	406
Plot 10-31:	Modulation Characteristics – Modulation Limiting – 136.0125 MHz; Positive Peak; NB	407
Plot 10-32:	Modulation Characteristics – Modulation Limiting – 136.0125 MHz; Negative Peak; NB	408
Plot 10-33:	Modulation Characteristics – Modulation Limiting – 144.0125 MHz; Positive Peak; NB	409
Plot 10-34:	Modulation Characteristics – Modulation Limiting – 144.0125 MHz; Negative Peak; NB	410
Plot 10-35:	Modulation Characteristics – Modulation Limiting – 173.9875 MHz; Positive Peak; NB	411
Plot 10-36:	Modulation Characteristics – Modulation Limiting – 173.9875 MHz; Negative Peak; NB	412
Plot 10-37:	Modulation Characteristics – Modulation Limiting – 378.0125 MHz; Positive Peak; NB	413
Plot 10-38:	Modulation Characteristics – Modulation Limiting – 378.0125 MHz; Negative Peak; NB	414
Plot 10-39:	Modulation Characteristics – Modulation Limiting – 454.0125 MHz; Positive Peak; NB	415
Plot 10-40:	Modulation Characteristics – Modulation Limiting – 454.0125 MHz; Negative Peak; NB	416
Plot 10-41:	Modulation Characteristics – Modulation Limiting – 521.9875 MHz; Positive Peak; NB	417
Plot 10-42:	Modulation Characteristics – Modulation Limiting - 521.9875 MHz; Negative Peak; NB	418
Plot 10-43:	Modulation Characteristics – Modulation Limiting – 768.0125 MHz; Positive Peak; NB	419

Plot 10-44:	Modulation Characteristics – Modulation Limiting - 768.0125 MHz; Negative Peak; NB	420
Plot 10-45:	Modulation Characteristics – Modulation Limiting - 775.9875 MHz; Positive Peak; NB	421
Plot 10-46:	Modulation Characteristics – Modulation Limiting - 775.9875 MHz; Negative Peak; NB	422
Plot 10-47:	Modulation Characteristics – Modulation Limiting - 805.9875 MHz; Positive Peak; NB	423
Plot 10-48:	Modulation Characteristics – Modulation Limiting - 805.9875 MHz; Negative Peak; NB	424
Plot 10-49:	Modulation Characteristics – Modulation Limiting - 806.0250 MHz; Positive Peak; NB	425
Plot 10-50:	Modulation Characteristics – Modulation Limiting - 806.0250 MHz; Negative Peak; NB	426
Plot 10-51:	Modulation Characteristics – Modulation Limiting - 809.0000 MHz; Positive Peak; NB	427
Plot 10-52:	Modulation Characteristics – Modulation Limiting - 809.0000 MHz; Negative Peak; NB	428
Plot 10-53:	Modulation Characteristics – Modulation Limiting - 815.9875 MHz; Positive Peak; NB	429
Plot 10-54:	Modulation Characteristics – Modulation Limiting - 815.9875 MHz; Negative Peak; NB	430
Plot 10-55:	Modulation Characteristics – Modulation Limiting - 851.0250 MHz; Positive Peak; NB	431
Plot 10-56:	Modulation Characteristics – Modulation Limiting - 851.0250 MHz; Negative Peak; NB	432
Plot 10-57:	Modulation Characteristics – Modulation Limiting - 856.0250 MHz; Positive Peak; NB	433
Plot 10-58:	Modulation Characteristics – Modulation Limiting - 856.0250 MHz; Negative Peak; NB	434
Plot 10-59:	Modulation Characteristics – Modulation Limiting - 860.9875 MHz; Positive Peak; NB	435
Plot 10-60:	Modulation Characteristics – Modulation Limiting - 860.9875 MHz; Negative Peak; NB	436
Plot 10-61:	Modulation Characteristics – Modulation Limiting - 136.0125 MHz; Positive Peak; WB	437
Plot 10-62:	Modulation Characteristics – Modulation Limiting - 136.0125 MHz; Negative Peak; WB	438
Plot 10-63:	Modulation Characteristics – Modulation Limiting - 144.0125 MHz; Positive Peak; WB	439
Plot 10-64:	Modulation Characteristics – Modulation Limiting - 144.0125 MHz; Negative Peak; WB	440
Plot 10-65:	Modulation Characteristics – Modulation Limiting - 173.9875 MHz; Positive Peak; WB	441
Plot 10-66:	Modulation Characteristics – Modulation Limiting - 173.9875 MHz; Negative Peak; WB	442
Plot 10-67:	Modulation Characteristics – Modulation Limiting - 378.0125 MHz; Positive Peak; WB	443
Plot 10-68:	Modulation Characteristics – Modulation Limiting - 378.0125 MHz; Negative Peak; WB	444
Plot 10-69:	Modulation Characteristics – Modulation Limiting - 454.0125 MHz; Positive Peak; WB	445
Plot 10-70:	Modulation Characteristics – Modulation Limiting - 454.0125 MHz; Negative Peak; WB	446
Plot 10-71:	Modulation Characteristics – Modulation Limiting - 521.9875 MHz; Positive Peak; WB	447
Plot 10-72:	Modulation Characteristics – Modulation Limiting - 521.9875 MHz; Negative Peak; WB	448
Plot 10-73:	Modulation Characteristics – Modulation Limiting - 806.0250 MHz; Positive Peak; WB	449
Plot 10-74:	Modulation Characteristics – Modulation Limiting - 806.0250 MHz; Negative Peak; WB	450
Plot 10-75:	Modulation Characteristics – Modulation Limiting - 809.0000 MHz; Positive Peak; WB	451
Plot 10-76:	Modulation Characteristics – Modulation Limiting - 809.0000 MHz; Negative Peak; WB	452
Plot 10-77:	Modulation Characteristics – Modulation Limiting - 815.9875 MHz; Positive Peak; WB	453
Plot 10-78:	Modulation Characteristics – Modulation Limiting - 815.9875 MHz; Negative Peak; WB	454
Plot 10-79:	Modulation Characteristics – Modulation Limiting - 851.0250 MHz; Positive Peak; WB	455
Plot 10-80:	Modulation Characteristics – Modulation Limiting - 851.0250 MHz; Negative Peak; WB	456
Plot 10-81:	Modulation Characteristics – Modulation Limiting - 856.0250 MHz; Positive Peak; WB	457
Plot 10-82:	Modulation Characteristics – Modulation Limiting - 856.0250 MHz; Negative Peak; WB	458
Plot 10-83:	Modulation Characteristics – Modulation Limiting - 860.9875 MHz; Positive Peak; WB	459
Plot 10-84:	Modulation Characteristics – Modulation Limiting - 860.9875 MHz; Negative Peak; WB	460
Plot 11-1:	Transient Frequency Behavior – 150.0125 MHz; Wide Band; Carrier ON Time	463
Plot 11-2:	Transient Frequency Behavior – 150.0125 MHz; Wide Band; Carrier OFF Time	464
Plot 11-3:	Transient Frequency Behavior – 150.0125 MHz; Narrow Band; Carrier ON Time	465
Plot 11-4:	Transient Frequency Behavior – 150.0125 MHz; Narrow Band; Carrier OFF Time	466
Plot 11-5:	Transient Frequency Behavior – 156.8000 MHz; Wide Band; Carrier ON Time	467
Plot 11-6:	Transient Frequency Behavior – 156.8000 MHz; Wide Band; Carrier OFF Time	468
Plot 11-7:	Transient Frequency Behavior – 156.8000 MHz; Narrow Band; Carrier ON Time	469
Plot 11-8:	Transient Frequency Behavior – 156.8000 MHz; Narrow Band; Carrier OFF Time	470
Plot 11-9:	Transient Frequency Behavior – 162.0125 MHz; Wide Band; Carrier ON Time	471
Plot 11-10:	Transient Frequency Behavior – 162.0125 MHz; Wide Band; Carrier OFF Time	472
Plot 11-11:	Transient Frequency Behavior – 162.0125 MHz; Narrow Band; Carrier ON Time	473
Plot 11-12:	Transient Frequency Behavior – 162.0125 MHz; Narrow Band; Carrier OFF Time	474

Plot 11-13:	Transient Frequency Behavior – 173.9875 MHz; Wide Band; Carrier ON Time	475
Plot 11-14:	Transient Frequency Behavior – 173.9875 MHz; Wide Band; Carrier OFF Time	476
Plot 11-15:	Transient Frequency Behavior – 173.9875 MHz; Narrow Band; Carrier ON Time	477
Plot 11-16:	Transient Frequency Behavior – 173.9875 MHz; Narrow Band; Carrier OFF Time	478
Plot 11-17:	Transient Frequency Behavior – 430.0125 MHz; Wide Band; Carrier ON Time	479
Plot 11-18:	Transient Frequency Behavior – 430.0125 MHz; Wide Band; Carrier OFF Time	480
Plot 11-19:	Transient Frequency Behavior – 430.0125 MHz; Narrow Band; Carrier ON Time	481
Plot 11-20:	Transient Frequency Behavior – 430.0125 MHz; Narrow Band; Carrier OFF Time	482
Plot 11-21:	Transient Frequency Behavior – 470.0125 MHz; Wide Band; Carrier ON Time	483
Plot 11-22:	Transient Frequency Behavior – 470.0125 MHz; Wide Band; Carrier OFF Time	484
Plot 11-23:	Transient Frequency Behavior – 470.0125 MHz; Narrow Band; Carrier ON Time	485
Plot 11-24:	Transient Frequency Behavior – 470.0125 MHz; Narrow Band; Carrier OFF Time	486
Plot 11-25:	Transient Frequency Behavior – 511.9875 MHz; Wide Band; Carrier ON Time	487
Plot 11-26:	Transient Frequency Behavior – 511.9875 MHz; Wide Band; Carrier OFF Time	488
Plot 11-27:	Transient Frequency Behavior – 511.9875 MHz; Narrow Band; Carrier ON Time	489
Plot 11-28:	Transient Frequency Behavior – 511.9875 MHz; Narrow Band; Carrier OFF Time	490

Table of Appendixes

Appendix A:	FCC Part 1.1307, 1.1310, 2.1091, 2.1093: RF Exposure	494
Appendix B:	FCC Agency Authorization	495
Appendix C:	FCC Confidentiality Request Letter	496
Appendix D:	IC Letters	497
Appendix E:	IC Confidentiality Request Letter	498
Appendix F:	Canadian-Based Representative Attestation	499
Appendix G:	Extended Frequency Attestation	500
Appendix H:	Part 90 Subpart R Application Review	501
Appendix I:	AFC Attestation	502
Appendix J:	Label Information	503
Appendix K:	Operational Description	505
Appendix L:	Parts List	506
Appendix M:	Test / Tune Procedure	507
Appendix N:	Schematics	508
Appendix O:	Block Diagram	509
Appendix P:	Manual	510
Appendix Q:	Test Configuration Photographs	511
Appendix R:	External Photographs	513
Appendix S:	Internal Photographs	517

Table of Photographs

Photograph 1: ID Label Sample with RF Statement	503
Photograph 2: Label Location	504
Photograph 3: Radiated Emissions – Front View	511
Photograph 4: Radiated Emissions – Back View.....	512
Photograph 5: Front	513
Photograph 6: Back	514
Photograph 7: Top	515
Photograph 8: Side Views.....	516
Photograph 9: Top with Shields	517
Photograph 10: Bottom with Shields.....	518
Photograph 11: Top without Shields	519
Photograph 12: Bottom without Shields.....	520

1 Test Result Summary

Test	FCC & IC References	Result
RF Power Output	2.1046(a), 90.541(b), 90.542(a)(6), 80.215, 74.461 IC RSS-119 5.4	Compliant
Spurious Emissions at Antenna Terminals	2.1051, 90.210, 80.217, IC RSS-119 5.8:	Compliant
Field Strength of Spurious Radiation	2.1053(a), 90.543(c), (d), and (f) IC RSS-119 5.8, IC RSS-119 5.11	Compliant
Occupied Bandwidth/Emission Masks	2.1049(c)(1), 22.359(b), 80.205, 90.210, 74.462 IC RSS-119 5.8	Compliant
Adjacent Channel Power	90.543(b) IC RSS-119 5.8.9	Compliant
Frequency Stability vs. Temperature and Voltage	2.1055, 90.213, 90.539, 80.209, 74.464 IC RSS-119 5.3	Compliant
Modulation Characteristics	2.1047(a)(b), 80.213, 74.463	Compliant
Transient Frequency Response	90.214, 74.462(c) IC RSS-119 5.9	Compliant
Unintentional Digital/Receive Emissions	15B	Compliant

2 General Information

The following Certification Report is prepared on behalf of **Harris Corporation** in accordance with the Federal Communications Commission and Industry Canada Rules and Regulations. The Equipment Under Test (EUT) was the **XL-200P Multi-Band Portable Land Mobile Radio; FCC ID: OWDTR-0133-E, IC: 3636B-0133.**

The radio is subject to FCC DoC. DoC testing was performed and the data is contained in a separate DoC report.

All measurements contained in this application were conducted in accordance with the applicable sections of FCC Rules and Regulations CFR 47 §2, 15, 22, 74, 80, and 90. Calibration checks are performed regularly on the instruments, and all accessories including high pass filter, coaxial attenuator, preamplifier and cables.

2.1 Test Facility

The open area test site and conducted measurement facility used to collect the radiated data is located on the parking lot of Rhein Tech Laboratories, Inc. 360 Herndon Parkway, Suite 1400, Herndon, Virginia 20170. This site has been fully described in a report submitted to, and approved by, the Federal Communications Commission to perform AC line conducted and radiated emissions testing.

2.2 Related Submittal(s)/Grant(s)

This is an Industry Canada Family Certification application, which includes 8 model numbers under IC: 3636B-0133:

XL-PFM1M	XL-PFM1Y	XL-PFM1B	XL-PFM1G
XL-PPM1M	XL-PPM1Y	XL-PPM1B	XL-PPM1G

2.3 Grant Notes

Manufacturer's Rated Power is 6W for VHF, 5W for UHF, 3W for 700 MHz Band, and 3W for the 800 MHz Band.

2.4 Tested System Details

The test sample was received on December 12, 2014. Listed below are the identifiers and descriptions of all equipment, cables, and internal devices used with the EUT for this test, as applicable.

The EUT includes a System model and a Scan model, the difference being that the System model has a DTMF keypad. The System model is considered to be representative of the radio family and to have the worst case emissions, and was therefore used for testing.

The device was programmed for multiple modes of operation and modulation types.


Table 2-1: Equipment Under Test (EUT)

Part	Manufacturer	Model	PN/SN	FCC ID	RTL Bar Code
Radio	Harris Corporation	XL-200P (System)	14035-1000-01/E00236	OWDTR-0133-E	21612
Radio	Harris Corporation	XL-200P (Scan)	14035-1000-06/1Y1D-E00072	OWDTR-0133-E	21613
Radio	Harris Corporation	XL-200P (System)	14035-1000-01/0WXD-E00234	OWDTR-0133-E	21564

Table 2-2: Auxiliary Equipment

Part	Manufacturer	Model	PN/SN	FCC ID	RTL Bar Code
AC Adapter	FP	FWA020012A	002844	N/A	21549
Charger	Harris Corporation	Single Bay Charger	14035-1800-01/00060	N/A	21550
Speaker/Microphone	Harris Corporation	EM105	N/A	N/A	21563
Full-Spectrum Multiband Antenna	Harris Corporation	14035-4000-01	T1-11	N/A	21556
7.2V Li-Ion Battery	Harris Corporation	Li-Ion	22	N/A	21551
7.2V Li-Ion Battery	Harris Corporation	BAT	L-CASE-R-HR003	N/A	21552
Battery Eliminator	Harris Corporation	N/A	14035-4300-01	N/A	21553
Power Supply	Alinco	DM-33MVT 32A	1638	N/A	901124

Figure 2-1: Configuration of Tested System



3 FCC Rules and Regulations Part 2.1033(C)(8): Voltages and Currents Through The Final Amplifying Stage

VHF: 7.4 V / 1.88 A
UHF: 7.4 V / 1.94 A
700 MHz: 7.4 V / 1.79 A
800 MHz: 7.4 V / 1.55 A

4 FCC Rules and Regulations Part 2.1046(a): RF Power Output: Conducted, Part 90.541(b)/90.542(a)(6): Transmitting Power Limits; Part 80.215: Transmitter Power; Part 74.461: Transmitter Power

4.1 Test Procedure

ANSI/TIA/EIA-603-2004, section 2.2.1

The EUT was connected to a coaxial attenuator having a 50 Ω load impedance.

§74.461 Transmitter Power

(a) Transmitter power is the power at the transmitter output terminals and delivered to the antenna, antenna transmission line, or any other impedance-matched, radio frequency load. For the purpose of this Subpart, the transmitter power is the carrier power.

(b) The authorized transmitter power for a remote pickup broadcast station shall be limited to that necessary for satisfactory service and, in any event, shall not be greater than 100 watts, except that a station to be operated aboard an aircraft shall normally be limited to a maximum authorized power of 15 watts. Specific authorization to operate stations on board aircraft with an output power exceeding 15 watts will be issued only upon an adequate engineering showing of need, and of the procedures that will be taken to avoid harmful interference to other licensees.

§80.215 Transmitter Power

(a) Transmitter power shown on the radio station authorization is the maximum power the licensee is authorized to use. Power is expressed in the following terms:

(5) For all other emissions: the carrier power multiplied by 1.67.

(e) Ship stations frequencies above 27500 kHz:

The maximum power must not exceed the values listed below.

(1) Ship stations 156–162 MHz: 25W

(2) Marine utility stations and hand-held portable transmitters: 156–162 MHz: 10W

Maximum Power Authorized to use: 10.02W for VHF, 8.35W for UHF

Manufacturer's Rated Power:

VHF: 6W

UHF: 5W

700 MHz Bands: 3W

800 MHz Bands: 3W

4.2 Test Data

Table 4-1: RF Conducted Output Power - Measured

Frequency (MHz)	Power (dBm)	Power (W)
136.0125	37.8	6.0
138.0125	37.9	6.2
141.0125	38.2	6.6
144.0125	38.3	6.8
148.0125	38.3	6.8
150.0125	38.3	6.8
156.8000	38.2	6.7
162.0125	38.1	6.5
173.9875	38.3	6.8
378.0125	37.5	5.6
406.1000	37.4	5.5
418.0125	37.3	5.4
430.0125	37.3	5.4
450.0125	37.4	5.5
454.0125	37.4	5.5
456.0125	37.4	5.5
459.0250	37.3	5.4
459.9750	37.3	5.4
470.0125	37.4	5.5
511.9875	37.3	5.4
521.9875	37.3	5.4
768.0125	34.3	2.7
769.0125	34.4	2.8
771.0125	34.4	2.8
775.0125	34.4	2.8
775.9875	34.4	2.8
798.0125	34.4	2.8
799.0125	34.4	2.8
801.0125	34.4	2.8
805.0125	34.4	2.8
805.9875	34.4	2.8
806.0250	34.9	3.1
809.0000	35.0	3.2
815.9875	35.0	3.2
851.0250	34.9	3.1
856.0250	35.0	3.2
860.9875	35.0	3.2

Notes: Data presented is for Analog mode. All other modes were investigated and found to have equivalent power within measurement tolerances.

Table 4-2: Test Equipment Used For Testing RF Power Output - Conducted

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	11/13/15
900948	Weinschel Corporation	47-10-43	Attenuator DC-18 GHz 10 dB 50W	BH1487	6/16/15

Test Personnel:

Daniel Baltzell		December 13, 2014
EMC Test Engineer	Signature	Date of Test

5 FCC Rules and Regulations Part 2.1051: Spurious Emissions at Antenna Terminals; Part 90.210: Emission Limitations; Part 80.217: Suppression of Interference aboard Ships

5.1 Test Procedure

ANSI/TIA/EIA-603-2004, Section 2.2.13

The transmitter is terminated with a 50 Ω load and interfaced with a spectrum analyzer.

Device with digital modulation: Modulated to its maximum extent using a pseudo-random data sequence.

§80.217 Suppression of Interference aboard Ships

(a) A voluntarily equipped ship station receiver must not cause harmful interference to any receiver required by statute or treaty.

(b) The electromagnetic field from receivers required by statute or treaty must not exceed the following value at a distance over sea water of one nautical mile from the receiver:

Frequency of Interfering Emissions	Power to Artificial Antenna in Microwatts
Below 30 MHz	0.1
30 to 100 MHz	3
100 to 300 MHz	1.0
Over 300 MHz	3.0

or

Deliver not more than the following amounts of power, to an artificial antenna having electrical characteristics equivalent to those of the average receiving antenna(s) use on shipboard:

Frequency of Interfering Emissions	Power to Artificial Antenna in Microwatts
Below 30 MHz	400 (4 dBm)
30 to 100 MHz	4,000 (6 dBm)
100 to 300 MHz	40,000 (16 dBm)
Over 300 MHz	400,000 (26 dBm)

5.2 Test Data

Frequency range of measurement per Part 2.1057: 9 kHz to $10 \times F_c$

Limits: $(43 + 10 \text{ LOG } P(W))$ for wideband and $50 + 10 \text{ LOG } P(W)$ for narrowband

The following channels (in MHz) were investigated:

VHF: 136.0125, 138.0125, 141.0125, 144.0125, 148.0125, 150.0125, 156.8000, 162.0125, and 173.9875

UHF: 378.0125, 406.1000, 418.0125, 430.0125, 450.0125, 454.0125, 456.0125, 459.0250, 459.9750,
470.0125, 511.9875, and 521.9875

700 MHz: 768.0125, 769.0125, 771.0125, 775.0125, 775.9875, 798.0125, 799.0125, 801.0125, 805.0125,
805.9875

800 MHz: 806.0250, 809.0000, 815.9875, 851.0250, 856.0250, and 860.9875

Both high and low power settings were checked; high power was found to be worst case. All modes were investigated and analog mode is presented as representative data.

All frequencies were found to be greater than 20 dB below the limit except 430.0125 MHz, Narrowband, 1-4 GHz, shown in Plot 5-1.

Plot 5-1: Spurious Emissions at Antenna Terminals – 430.0125 MHz; Narrowband; 1-4 GHz




Table 5-1: Test Equipment Used For Testing Spurious Emissions

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901129	Par Electronics	188-174 (25W)	VHF Notch Filters	N/A	7/1/15
901135	Par Electronics	400-512 (25W)	UHF Notch Filter	N/A	7/1/15
901128	Par Electronics	806-902 (25W)	UHF Notch Filter	N/A	7/1/15
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	11/13/15
900948	Weinschel Corporation	47-10-43	Attenuator DC-18 GHz 10 dB 50W	BH1487	6/16/15
900819	Weinschel Corporation	2	10 dB Attenuator; 5 W	BF0830	7/1/15

Test Personnel:

Daniel Baltzell		December 18, 2014
EMC Test Engineer	Signature	Date of Test

6 FCC Rules and Regulations Part 90.543(a): Emission Limitations: ACP Requirements

Effective October 23, 2007, transmitters designed to operate in the 769–775 MHz and 799–805 MHz frequency bands must meet the emission limitations in paragraphs (a) through (d) of this section. Transmitters operating in the 763–768 MHz and 793–798 MHz bands must meet the emission limitations in (e) of this section.

6.1 Test Procedure

Device with digital modulation: Modulated to its maximum extent using a pseudo-random data sequence.

For a Portable transmitter designed to operate with a 12.5 kHz channel bandwidth, the ACP shall be in accordance with the values in the following table:

Offset from Center Frequency (kHz)	Measurement Bandwidth (kHz)	Maximum ACP Relative (dBc)
(+/-)9.375	6.25	-40
(+/-)15.625	6.25	-60
(+/-)21.875	6.25	-60
(+/-)37.5	25	-60
(+/-)62.5	25	-65
(+/-)87.5	25	-65
(+/-)150	100	-65
(+/-)250	100	-65
(+/-)350	100	-65
>400 kHz to 12 MHz	30(s)	-75
12 MHz to paired receive band	30(s)	-75
In the paired receive band	30(s)	-100

For a Portable transmitter designed to operate with a 25 kHz channel bandwidth, the ACP shall be in accordance with the values in the following table:

Offset from Center Frequency (kHz)	Measurement Bandwidth (kHz)	Maximum ACP Relative (dBc)
(+/-)15.625	6.25	-40
(+/-)21.875	6.25	-60
(+/-)37.5	25	-60
(+/-)62.5	25	-65
(+/-)87.5	25	-65
(+/-)150	100	-65
(+/-)250	100	-65
(+/-)350	100	-65
>400 kHz to 12 MHz	30(s)	-75
12 MHz to paired receive band	30(s)	-75
In the paired receive band	30(s)	-100

FCC Rules and Regulations Part 90.543(b)

Setting Reference Level - Part 90.543(b)(1): Using a spectrum analyzer capable of ACP measurements, set the measurement bandwidth to the channel size. Set the frequency offset of the measurement to zero and adjust the center frequency of the spectrum analyzer to give the power level in the measurement bandwidth. Record this power as the reference power level.

Measuring the power level at the frequency offset <400 kHz - Part 90.543(b)(2): Using a spectrum analyzer capable of adjacent channel power (ACP) measurements, set the measurement bandwidth as shown in table. Measure ACP in dBm. These measurements are made at maximum power. Calculate the coupled power by subtracting the measurements made in this step from the reference power level. The absolute ACP values must be less than the values given in the table for each condition.

Measuring the power level at the frequency offset >400 kHz - Part 90.543(b)(3): Set the spectrum analyzer to 30 kHz resolution bandwidth, 1 MHz video bandwidth and sample detection mode. Sweep +/- 6 MHz from the carrier frequency. Set the reference level to the RMS value of the transmitter power and note the power. The response at frequencies >400 kHz must be less than the values listed in the table.

6.2 Test Data

Plot 6-1: Adjacent Channel Power – 768.0125 MHz; Narrowband Analog; <400 kHz




Table 6-1: Adjacent Channel Power – 768.0125 MHz; Narrowband Analog; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-82.1
12 MHz to receive band	30(s)	-75	-102.5
In receive band	30(s)	-100	-111.8

Plot 6-2: Adjacent Channel Power – 769.0125 MHz; Narrowband Analog; <400 kHz




Table 6-2: Adjacent Channel Power – 769.0125 MHz; Narrowband Analog; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.7
12 MHz to receive band	30(s)	-75	-105.3
In receive band	30(s)	-100	-111.9

Plot 6-3: Adjacent Channel Power – 771.0125 MHz; Narrowband Analog; <400 kHz




Table 6-3: Adjacent Channel Power – 771.0125 MHz; Narrowband Analog; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.4
12 MHz to receive band	30(s)	-75	-107.3
In receive band	30(s)	-100	-111.2

Plot 6-4: Adjacent Channel Power – 775.0125 MHz; Narrowband Analog; <400 kHz




Table 6-4: Adjacent Channel Power – 775.0125 MHz; Narrowband Analog; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-82.0
12 MHz to receive band	30(s)	-75	-104.7
In receive band	30(s)	-100	-110.1

Plot 6-5: Adjacent Channel Power – 775.9875 MHz; Narrowband Analog; <400 kHz




Table 6-5: Adjacent Channel Power – 775.9875 MHz; Narrowband Analog; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.4
12 MHz to receive band	30(s)	-75	-101.4
In receive band	30(s)	-100	-107.8

Plot 6-6: Adjacent Channel Power – 798.0125 MHz; Narrowband Analog; <400 kHz




Table 6-6: Adjacent Channel Power – 798.0125 MHz; Narrowband Analog; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.4
12 MHz to receive band	30(s)	-75	-99.3
In receive band	30(s)	-100	-102.4

Plot 6-7: Adjacent Channel Power – 799.0125 MHz; Narrowband Analog; <400 kHz




Table 6-7: Adjacent Channel Power – 799.0125 MHz; Narrowband Analog; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-79.5
12 MHz to receive band	30(s)	-75	-99.5
In receive band	30(s)	-100	-101.8

Plot 6-8: Adjacent Channel Power – 801.0125 MHz; Narrowband Analog; <400 kHz




Table 6-8: Adjacent Channel Power – 801.0125 MHz; Narrowband Analog; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-82.1
12 MHz to receive band	30(s)	-75	-101.4
In receive band	30(s)	-100	-105.8

Plot 6-9: Adjacent Channel Power – 805.0125 MHz; Narrowband Analog; <400 kHz




Table 6-9: Adjacent Channel Power – 805.0125 MHz; Narrowband Analog; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.3
12 MHz to receive band	30(s)	-75	-93.6
In receive band	30(s)	-100	-107.6

Plot 6-10: Adjacent Channel Power – 805.9875 MHz; Narrowband Analog; <400 kHz




Table 6-10: Adjacent Channel Power – 805.9875 MHz; Narrowband Analog; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-77.1
12 MHz to receive band	30(s)	-75	-95.1
In receive band	30(s)	-100	-106.6

Plot 6-11: Adjacent Channel Power – 768.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz




Table 6-11: Adjacent Channel Power – 768.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-86.2
12 MHz to receive band	30(s)	-75	-105.2
In receive band	30(s)	-100	-107.0

Plot 6-12: Adjacent Channel Power – 769.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz




Table 6-12: Adjacent Channel Power – 769.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.4
12 MHz to receive band	30(s)	-75	-106.4
In receive band	30(s)	-100	-105.7

Plot 6-13: Adjacent Channel Power – 771.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz




Table 6-13: Adjacent Channel Power – 771.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-83.8
12 MHz to receive band	30(s)	-75	-107.3
In receive band	30(s)	-100	-107.2

Plot 6-14: Adjacent Channel Power – 775.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz




Table 6-14: Adjacent Channel Power – 775.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.3
12 MHz to receive band	30(s)	-75	-104.0
In receive band	30(s)	-100	-107.1

Plot 6-15: Adjacent Channel Power – 775.9875 MHz; EDACS 2-Level FSK 9600; <400 kHz




Table 6-15: Adjacent Channel Power – 775.9875 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-78.7
12 MHz to receive band	30(s)	-75	-101.4
In receive band	30(s)	-100	-106.7

Plot 6-16: Adjacent Channel Power – 798.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz




Table 6-16: Adjacent Channel Power – 798.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-85.6
12 MHz to receive band	30(s)	-75	-98.0
In receive band	30(s)	-100	-101.0

Plot 6-17: Adjacent Channel Power – 799.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz




Table 6-17: Adjacent Channel Power – 799.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.0
12 MHz to receive band	30(s)	-75	-100.1
In receive band	30(s)	-100	-103.7

Plot 6-18: Adjacent Channel Power – 801.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz




Table 6-18: Adjacent Channel Power – 801.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.3
12 MHz to receive band	30(s)	-75	-99.9
In receive band	30(s)	-100	-107.8

Plot 6-19: Adjacent Channel Power – 805.0125 MHz; EDACS 2-Level FSK 9600; <400 kHz




Table 6-19: Adjacent Channel Power – 805.0125 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.6
12 MHz to receive band	30(s)	-75	-94.5
In receive band	30(s)	-100	-108.0

Plot 6-20: Adjacent Channel Power – 805.9875 MHz; EDACS 2-Level FSK 9600; <400 kHz




Table 6-20: Adjacent Channel Power – 805.9875 MHz; EDACS 2-Level FSK 9600; 400 kHz–RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-79.2
12 MHz to receive band	30(s)	-75	-94.1
In receive band	30(s)	-100	-107.3

Plot 6-21: Adjacent Channel Power – 768.0125 MHz; OTP SMR; <400 kHz




Table 6-21: Adjacent Channel Power – 768.0125 MHz; OTP SMR; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-86.3
12 MHz to receive band	30(s)	-75	-107.1
In receive band	30(s)	-100	-107.1

Plot 6-22: Adjacent Channel Power – 769.0125 MHz; OTP SMR; <400 kHz




Table 6-22: Adjacent Channel Power – 769.0125 MHz; OTP SMR; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-78.6
12 MHz to receive band	30(s)	-75	-106.4
In receive band	30(s)	-100	-107.4

Plot 6-23: Adjacent Channel Power – 771.0125 MHz; OTP SMR; <400 kHz




Table 6-23: Adjacent Channel Power – 771.0125 MHz; OTP SMR; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.5
12 MHz to receive band	30(s)	-75	-106.7
In receive band	30(s)	-100	-107.9

Plot 6-24: Adjacent Channel Power – 775.0125 MHz; OTP SMR; <400 kHz




Table 6-24: Adjacent Channel Power – 775.0125 MHz; OTP SMR; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.1
12 MHz to receive band	30(s)	-75	-104.8
In receive band	30(s)	-100	-105.8

Plot 6-25: Adjacent Channel Power – 775.9875 MHz; OTP SMR; <400 kHz




Table 6-25: Adjacent Channel Power – 775.9875 MHz; OTP SMR; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	80.4
12 MHz to receive band	30(s)	-75	102.1
In receive band	30(s)	-100	106.9

Plot 6-26: Adjacent Channel Power – 798.0125 MHz; OTP SMR; <400 kHz




Table 6-26: Adjacent Channel Power – 798.0125 MHz; OTP SMR; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-79.0
12 MHz to receive band	30(s)	-75	-98.7
In receive band	30(s)	-100	-101.8

Plot 6-27: Adjacent Channel Power – 799.0125 MHz; OTP SMR; <400 kHz




Table 6-27: Adjacent Channel Power – 799.0125 MHz; OTP SMR; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.6
12 MHz to receive band	30(s)	-75	-97.4
In receive band	30(s)	-100	-102.1

Plot 6-28: Adjacent Channel Power – 801.0125 MHz; OTP SMR; <400 kHz




Table 6-28: Adjacent Channel Power – 801.0125 MHz; OTP SMR; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.1
12 MHz to receive band	30(s)	-75	-99.1
In receive band	30(s)	-100	-106.7

Plot 6-29: Adjacent Channel Power – 805.0125 MHz; OTP SMR; <400 kHz




Table 6-29: Adjacent Channel Power – 805.0125 MHz; OTP SMR; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-78.7
12 MHz to receive band	30(s)	-75	-96.1
In receive band	30(s)	-100	-106.1

Plot 6-30: Adjacent Channel Power – 805.9875 MHz; OTP SMR; <400 kHz




Table 6-30: Adjacent Channel Power – 805.9875 MHz; OTP SMR; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.5
12 MHz to receive band	30(s)	-75	-95.4
In receive band	30(s)	-100	-106.2

Plot 6-31: Adjacent Channel Power – 768.0125 MHz; OTP Narrowband; <400 kHz




Table 6-31: Adjacent Channel Power – 768.0125 MHz; OTP Narrowband; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-86.6
12 MHz to receive band	30(s)	-75	-106.2
In receive band	30(s)	-100	-106.3

Plot 6-32: Adjacent Channel Power – 769.0125 MHz; OTP Narrowband; <400 kHz




Table 6-32: Adjacent Channel Power – 769.0125 MHz; OTP Narrowband; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-79.9
12 MHz to receive band	30(s)	-75	-107.1
In receive band	30(s)	-100	-104.3

Plot 6-33: Adjacent Channel Power – 771.0125 MHz; OTP Narrowband; <400 kHz




Table 6-33: Adjacent Channel Power – 771.0125 MHz; OTP Narrowband; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.2
12 MHz to receive band	30(s)	-75	-106.2
In receive band	30(s)	-100	-106.5

Plot 6-34: Adjacent Channel Power – 775.0125 MHz; OTP Narrowband; <400 kHz




Table 6-34: Adjacent Channel Power – 775.0125 MHz; OTP Narrowband; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-79.7
12 MHz to receive band	30(s)	-75	-104.0
In receive band	30(s)	-100	-107.2

Plot 6-35: Adjacent Channel Power – 775.9875 MHz; OTP Narrowband; <400 kHz




Table 6-35: Adjacent Channel Power – 775.9875 MHz; OTP Narrowband; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.7
12 MHz to receive band	30(s)	-75	-100.1
In receive band	30(s)	-100	-106.3

Plot 6-36: Adjacent Channel Power – 798.0125 MHz; OTP Narrowband; <400 kHz




Table 6-36: Adjacent Channel Power – 798.0125 MHz; OTP Narrowband; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.3
12 MHz to receive band	30(s)	-75	-98.6
In receive band	30(s)	-100	-101.8

Plot 6-37: Adjacent Channel Power – 799.0125 MHz; OTP Narrowband; <400 kHz




Table 6-37: Adjacent Channel Power – 799.0125 MHz; OTP Narrowband; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.0
12 MHz to receive band	30(s)	-75	-98.7
In receive band	30(s)	-100	-102.6

Plot 6-38: Adjacent Channel Power – 801.0125 MHz; OTP Narrowband; <400 kHz




Table 6-38: Adjacent Channel Power – 801.0125 MHz; OTP Narrowband; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.7
12 MHz to receive band	30(s)	-75	-98.9
In receive band	30(s)	-100	-102.8

Plot 6-39: Adjacent Channel Power – 805.0125 MHz; OTP Narrowband; <400 kHz




Table 6-39: Adjacent Channel Power – 805.0125 MHz; OTP Narrowband; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-79.4
12 MHz to receive band	30(s)	-75	-94.7
In receive band	30(s)	-100	-106.0

Plot 6-40: Adjacent Channel Power – 805.9875 MHz; OTP Narrowband; <400 kHz




Table 6-40: Adjacent Channel Power – 805.9875 MHz; OTP Narrowband; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.0
12 MHz to receive band	30(s)	-75	-93.4
In receive band	30(s)	-100	-107.2

Plot 6-41: Adjacent Channel Power – 768.0125 MHz; P25; <400 kHz




Table 6-41: Adjacent Channel Power – 768.0125 MHz; P25; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-86.1
12 MHz to receive band	30(s)	-75	-108.3
In receive band	30(s)	-100	-107.5

Plot 6-42: Adjacent Channel Power – 769.0125 MHz; P25; <400 kHz




Table 6-42: Adjacent Channel Power – 769.0125 MHz; P25; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-79.6
12 MHz to receive band	30(s)	-75	-105.0
In receive band	30(s)	-100	-107.0

Plot 6-43: Adjacent Channel Power – 771.0125 MHz; P25; <400 kHz




Table 6-43: Adjacent Channel Power – 771.0125 MHz; P25; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-82.6
12 MHz to receive band	30(s)	-75	-106.8
In receive band	30(s)	-100	-106.5

Plot 6-44: Adjacent Channel Power – 775.0125 MHz; P25; <400 kHz




Table 6-44: Adjacent Channel Power – 775.0125 MHz; P25; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-77.2
12 MHz to receive band	30(s)	-75	-103.0
In receive band	30(s)	-100	-107.5

Plot 6-45: Adjacent Channel Power – 775.9875 MHz; P25; <400 kHz




Table 6-45: Adjacent Channel Power – 775.9875 MHz; P25; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-79.7
12 MHz to receive band	30(s)	-75	-101.2
In receive band	30(s)	-100	-106.1

Plot 6-46: Adjacent Channel Power – 798.0125 MHz; P25; <400 kHz




Table 6-46: Adjacent Channel Power – 798.0125 MHz; P25; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-78.6
12 MHz to receive band	30(s)	-75	-96.4
In receive band	30(s)	-100	-100.9

Plot 6-47: Adjacent Channel Power – 799.0125 MHz; P25; <400 kHz




Table 6-47: Adjacent Channel Power – 799.0125 MHz; P25; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.6
12 MHz to receive band	30(s)	-75	-99.1
In receive band	30(s)	-100	-101.6

Plot 6-48: Adjacent Channel Power – 801.0125 MHz; P25; <400 kHz




Table 6-48: Adjacent Channel Power – 801.0125 MHz; P25; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.9
12 MHz to receive band	30(s)	-75	-100.0
In receive band	30(s)	-100	-105.8

Plot 6-49: Adjacent Channel Power – 805.0125 MHz; P25; <400 kHz




Table 6-49: Adjacent Channel Power – 805.0125 MHz; P25; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-79.9
12 MHz to receive band	30(s)	-75	-96.5
In receive band	30(s)	-100	-107.4

Plot 6-50: Adjacent Channel Power – 805.9875 MHz; P25; <400 kHz




Table 6-50: Adjacent Channel Power – 805.9875 MHz; P25; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.2
12 MHz to receive band	30(s)	-75	-95.8
In receive band	30(s)	-100	-106.8

Plot 6-51: Adjacent Channel Power – 768.0125 MHz; P25 Phase 2; <400 kHz




Table 6-51: Adjacent Channel Power – 768.0125 MHz; P25 Phase 2; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-87.3
12 MHz to receive band	30(s)	-75	-108.6
In receive band	30(s)	-100	-107.8

Plot 6-52: Adjacent Channel Power – 769.0125 MHz; P25 Phase 2; <400 kHz




Table 6-52: Adjacent Channel Power – 769.0125 MHz; P25 Phase 2; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-79.5
12 MHz to receive band	30(s)	-75	-105.1
In receive band	30(s)	-100	-108.7

Plot 6-53: Adjacent Channel Power – 771.0125 MHz; P25 Phase 2; <400 kHz




Table 6-53: Adjacent Channel Power – 771.0125 MHz; P25 Phase 2; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.1
12 MHz to receive band	30(s)	-75	-106.1
In receive band	30(s)	-100	-107.2

Plot 6-54: Adjacent Channel Power – 775.0125 MHz; P25 Phase 2; <400 kHz




Table 6-54: Adjacent Channel Power – 775.0125 MHz; P25 Phase 2; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.5
12 MHz to receive band	30(s)	-75	-101.9
In receive band	30(s)	-100	-105.4

Plot 6-55: Adjacent Channel Power – 775.9875 MHz; P25 Phase 2; <400 kHz




Table 6-55: Adjacent Channel Power – 775.9875 MHz; P25 Phase 2; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.6
12 MHz to receive band	30(s)	-75	-100.1
In receive band	30(s)	-100	-105.2

Plot 6-56: Adjacent Channel Power – 798.0125 MHz; P25 Phase 2; <400 kHz




Table 6-56: Adjacent Channel Power – 798.0125 MHz; P25 Phase 2; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-80.6
12 MHz to receive band	30(s)	-75	-101.4
In receive band	30(s)	-100	-101.7

Plot 6-57: Adjacent Channel Power – 799.0125 MHz; P25 Phase 2; <400 kHz




Table 6-57: Adjacent Channel Power – 799.0125 MHz; P25 Phase 2; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.4
12 MHz to receive band	30(s)	-75	-99.1
In receive band	30(s)	-100	-103.0

Plot 6-58: Adjacent Channel Power – 801.0125 MHz; P25 Phase 2; <400 kHz




Table 6-58: Adjacent Channel Power – 801.0125 MHz; P25 Phase 2; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-83.1
12 MHz to receive band	30(s)	-75	-100.4
In receive band	30(s)	-100	-106.0

Plot 6-59: Adjacent Channel Power – 805.0125 MHz; P25 Phase 2; <400 kHz




Table 6-59: Adjacent Channel Power – 805.0125 MHz; P25 Phase 2; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.7
12 MHz to receive band	30(s)	-75	-96.2
In receive band	30(s)	-100	-107.7

Plot 6-60: Adjacent Channel Power – 805.9875 MHz; P25 Phase 2; <400 kHz




Table 6-60: Adjacent Channel Power – 805.9875 MHz; P25 Phase 2; 400 kHz – RX band

Offset from Center Frequency (kHz)	Measurement BW (kHz)	Max ACP (dBc)	Max ACP (dBc)
>400 to 12 MHz	30(s)	-75	-81.0
12 MHz to receive band	30(s)	-75	-94.8
In receive band	30(s)	-100	-105.2

Table 6-61: Test Equipment Used For Testing ACP Requirements

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	11/13/15
900948	Weinschel Corporation	47-10-43	Attenuator DC-18 GHz 10 dB 50W	BH1487	6/16/15
900819	Weinschel Corporation	2	10 dB Attenuator; 5 W	BF0830	7/1/15
901139	Weinschel Corporation	48-20-34 DC-18GHz	Attenuator, 100W 20dB	BK5859	3/25/16

Test Personnel:

Daniel Baltzell EMC Test Engineer	 Signature	January 9-10 & February 10, 2015 Dates of Tests
--------------------------------------	---	--

7 FCC Rules and Regulations Part 90.210(g) and Part 2.1053(a): Field Strength of Spurious Radiation; Part 90.543(f): Out of Band Emissions Limit

7.1 Test Procedure

ANSI/TIA/EIA-603-2004, section 2.2.12

Analog Modulation: The transmitter is terminated with a 50 Ω load and is modulated with a 2,500 Hz sine wave at an input level 16 dB greater than that required to produce 50% of the rated system deviation at 1,000 Hz.

Device with digital modulation: Modulated to its maximum extent using a pseudo-random data sequence – 19,200 bps for OTP and 9,600 bps for P25 and EDACS modes.

The spurious emissions levels were measured, and the device under test was replaced by a substitution antenna connected to a signal generator. This signal generator level was then corrected by subtracting the cable loss from the substitution antenna to the signal generator, and the gain of the antenna (dBi) was added to achieve the EIRP level, then converted from the corrected signal generator level (dBm) to dBW for the GNSS band and compared to the limit.

For emissions in the 1559-1610 band, Part 15.543(f) states: "For operations in the 763–775 MHz and 793–805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to - 70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation."

7.2 Test Data

7.2.1 CFR 47 Part 90.210 Requirements

The magnitude of emissions attenuated more than 20 dB below the FCC limit need not be recorded.

The following emissions were found to be within a 20 dB margin of the limit. All other emissions are not listed.

Table 7-1: Field Strength of Spurious Radiation - 378.0125 MHz

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd)	Corrected Signal Generator Level (dBc)	Margin (dB)
756.025	41.5	-31.4	0.2	0.9	68.3	-10.8

Table 7-2: Field Strength of Spurious Radiation - 406.1000 MHz

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd)	Corrected Signal Generator Level (dBc)	Margin (dB)
812.2	38.2	-35.9	0.3	0.6	73.1	-15.6
1218.3	43.2	-30.3	0.3	6.6	61.5	-4.0

Table 7-3: Field Strength of Spurious Radiation - 418.0125 MHz

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd)	Corrected Signal Generator Level (dBc)	Margin (dB)
836.025	47.3	-27.3	0.3	0.7	64.4	-6.9

Table 7-4: Field Strength of Spurious Radiation - 430.0125 MHz

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd)	Corrected Signal Generator Level (dBc)	Margin (dB)
860.025	42.1	-32.4	0.3	0.0	70.1	-12.6

Table 7-5: Field Strength of Spurious Radiation - 450.0125 MHz

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd)	Corrected Signal Generator Level (dBc)	Margin (dB)
900.025	45.4	-28.7	0.3	0.7	65.8	-8.3

Table 7-6: Field Strength of Spurious Radiation - 454.0125 MHz

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd)	Corrected Signal Generator Level (dBc)	Margin (dB)
908.025	43.9	-30.0	0.3	0.9	66.9	-9.4

Table 7-7: Field Strength of Spurious Radiation - 456.0125 MHz

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd)	Corrected Signal Generator Level (dBc)	Margin (dB)
912.025	45.4	-28.6	0.3	0.9	65.5	-8.0

Table 7-8: Field Strength of Spurious Radiation - 459.0250 MHz

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd)	Corrected Signal Generator Level (dBc)	Margin (dB)
918.05	42.8	-31.3	0.3	1.0	68.1	-10.6

Table 7-9: Field Strength of Spurious Radiation - 459.9750 MHz

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd)	Corrected Signal Generator Level (dBc)	Margin (dB)
919.95	44.5	-29.6	0.3	1.0	66.4	-8.9

Table 7-10: Field Strength of Spurious Radiation - 470.0125 MHz

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss (dB)	Antenna Gain (dBd)	Corrected Signal Generator Level (dBc)	Margin (dB)
940.025	43.0	-30.8	0.3	1.1	67.5	-10.0

7.2.2 CFR 47 Part 90.543(f) Requirements

The worst-case emissions test data are shown.

Limit: -80 dBW EIRP for discrete emissions

Table 7-11: Field Strength of Spurious Radiation

Frequency (MHz)	Spectrum Analyzer Level (dBuV)	Signal Generator Level (dBm)	Cable Loss to Transmit Antenna (dB)	Antenna Gain (dBi)	Corrected Signal Generator Level (dBW)	Margin (dB)
1536.025	25.6	-48.6	0.4	8.0	-71.0	-1.0
1538.025	22.8	-51.8	0.4	8.0	-74.2	-4.2
1542.025	23.5	-50.7	0.4	8.1	-73.0	-3.0
1596.025	23.1	-52.0	0.4	8.8	-73.6	-3.6
1598.025	26.1	-48.8	0.4	8.9	-70.3	-0.3
1602.025	22.0	-52.8	0.4	8.9	-74.3	-4.3

Table 7-12: Test Equipment Used For Testing Field Strength of Spurious Radiation

RTL Asset #	Manufacturer	Model	Part Type	Serial Number	Calibration Due Date
900932	Hewlett Packard	8449B OPT H02	Preamplifier (1 - 26.5 GHz)	3008A00505	9/5/15
900878	Rhein Tech Laboratories	AM3-1197-0005	3 meter antenna mast, polarizing	OATS1	N/A
901592	Insulated Wire Inc.	KPS-1503-3600-KPR	SMK RF Cables 20'	NA	9/3/15
901593	Insulated Wire Inc.	KPS-1503-360-KPR	SMK RF Cables 36"	NA	9/3/15
901594	Insulated Wire Inc.	KPS-1503-360-KPR	SMK RF Cables 36"	NA	9/3/15
901242	Rhein Tech Laboratories	WRT-000-0003	Wood rotating table	N/A	N/A
901581	Rohde & Schwarz	FSU	Spectrum Analyzer	1166.1660.50	11/13/15
901582	Rohde & Schwarz	1167.0000.02	Signal Generator	101903	11/14/15
900791	Chase	CBL6111B	Bilog Antenna (30 MHz – 2000 MHz)	N/A	6/11/17
900321	EMCO	3161-03	Horn Antennas (4 – 8 GHz)	9508-1020	4/20/15
900323	EMCO	3160-07	Horn Antennas (8.2 – 12 GHz)	9605-1054	4/20/15
900772	EMCO	3161-02	Horn Antenna (2 - 4 GHz)	9804-1044	4/20/15
901132	Par Electronics	806-902 (25W)	UHF Notch Filter	N/A	7/1/15
901133	Par Electronics	806-902 (25W)	UHF Notch Filter	N/A	7/1/15

Test Personnel:

Daniel Baltzell Test Engineer	 Signature	January 13-February 9, 2015 Dates of Tests
----------------------------------	---	---