



EMC Test Data

Client:	Pace Americas, Inc.	Job Number:	J97787
Model:	5268AC (FCC ID: PGR5200AC)	T-Log Number:	T97825
Contact:	Mark Rieger	Project Manager:	Irene Rademacher
Standard:	FCC 15.407 (New Rules)	Project Coordinator:	-
		Class:	N/A

Maximum Permissible Exposure

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 9/16/2015

Test Engineer: Mark Hill

General Test Configuration

Calculation uses the free space transmission formula:

$$S = (PG)/(4 \pi d^2)$$

Where: S is power density (W/m^2), P is output power (W), G is antenna gain relative to isotropic, d is separation distance from the transmitting antenna (m).

Summary of Results

Device complies with Power Density requirements at 20cm separation:	Yes
---	-----

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client:	Pace Americas, Inc.	Job Number:	J97787
Model:	5268AC (FCC ID: PGR5200AC)	T-Log Number:	T97825
Contact:	Mark Rieger	Project Manager:	Irene Rademacher
Standard:	FCC 15.407 (New Rules)	Project Coordinator:	-
		Class:	N/A

FCC MPE Calculation

Use: General

Antenna: 3.70dBi @ 2.4GHz, 8.08dBi directional @ 5GHz (taken from original filing)

Worse case calculation of simultaneous transmission

Band	Mode	Output Power		Antenna gain (Max)	EIRP		Channels Available	Channels Used	Total EIRP	
		Peak	Average		dBm	W			W	dBm
2400 - 2483.5	OFDM	-	25.9	3.7	29.6	0.910	11	1	0.910	29.59
5150 - 5250	OFDM	-	27.8	8.1	35.9	3.873	4	1	3.873	35.88
5250 - 5350	OFDM	-	22.8	8.1	30.8	1.213	4	0	-	-
5470 - 5725	OFDM	-	22.2	8.1	30.3	1.074	5	0	-	-
5725 - 5850	OFDM	-	27.4	8.1	35.5	3.532	5	0	-	-
Totals:							2		4.783	36.80

EIRP mW	Power Density (S) at 20 cm mW/cm^2	MPE Limit at 20 cm mW/cm^2
4783	0.952	1.000