

# Electromagnetic Emission

## FCC MEASUREMENT REPORT

### CERTIFICATION OF COMPLIANCE

#### FCC Part 15 Certification Measurement

**PRODUCT** : PLC(PowerLine Communication)Modem  
**MODEL/TYPE NO** : SU-200BX  
**FCC ID** : PQVSU-200BX  
**APPLICANT / ADDRESS** : Xeline Co., Ltd.  
7F Chungjin Bldg., 475-22, Bangbae2-dong, Seocho-gu, Seoul,  
137-819, Korea  
Attn.: IL-Soo, Kim / Senior Manager  
**FCC CLASSIFICATION** : Class B personal computers and peripherals  
(Carrier current systems)  
**FCC RULE PART(S)** : FCC Part 15 Subpart B  
**FCC PROCEDURE** : Certification  
**TRADE NAME** : N/A  
**TEST REPORT No.** : E05.0615.FCC.348N  
**DATES OF TEST** : May 31 ~ June 15, 2005  
**DATES OF ISSUE** : June 15, 2005  
**TEST LABORATORY** : ETL Inc. (FCC Registration Number: 95422)  
#584 Sangwhal-ri, Kanam-myon, Yaju-kun, Kyunggi-do,  
469-885, Korea  
Tel: (031) 885-0072 Fax: (031) 885-0074

This is PLC(PowerLine Communication) Modem, Model: SU-200BX has been tested in accordance with the measurement procedures specified in ANSI C63.4-2001 at the ETL/EMC Test Laboratory and has been shown to be complied with the electromagnetic radiated emission limits specified in FCC Rule Part15 Subpart B:

I attest to the accuracy of data. All measurement here in was performed by me or was made under my supervision and is correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

The results of testing in this report apply to the product/system, which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

*Yo Han, Park*

Yo Han, Park / Chief Engineer

**ETL Inc.**

**#584 Sangwhal-ri, Kanam-myon, Yaju-kun,  
Kyunggi-do, 469-885, Korea**



---

## Table of Contents

### FCC Measurement Report

1. Introduction
2. Product Information
3. Description of Tests
4. Test Condition
5. Test Results
  - 5.1 Summary of Test Results
  - 5.2 Conducted Emissions Measurement
  - 5.3 Radiated Emissions Measurement
6. Sample Calculation
7. List of test Equipment used for Measurement

- Appendix A. FCC ID Label and Location
- Appendix B. Test Setup Photographs
- Appendix C. External Photographs
- Appendix D. Internal Photographs
- Appendix E. Block Diagram
- Appendix F. User's Manual

**Scope** – Measurement and determination of electromagnetic emission(EME) of radio frequency devices including intentional radiators and/or unintentional radiators for compliance with the technical rules and regulations of the U.S Federal Communications Commission(FCC)

## General Information

**Applicant Name** : Xeline Co., Ltd.

**Address** : 7F Chungin Bldg., 475-22 Bangbae2-dong, Seocho-gu, Seoul  
137-819, Korea

**Attention** : IL-Soo, Kim / Senior Manager

- **EUT Type:** PLC(PowerLine Communication) Modem
- **Model Number:** SU-200BX
- **FCC ID:** PQVSU-200BX
- **S/N:** SU0504B000059
- **FCC Rule Part(s):** FCC Part 15 Subpart B
- **Test Procedure:** ANSI C63.4-2001
- **FCC Classification:** Class B personal computers and peripherals(Carrier current systems)
- **Dates of Tests:** May 31 ~ June 15, 2005
- **Place of Tests:** ETL Inc.  
EMC Testing Lab. (FCC Registration Number: 95422)  
584, Sangwhal-Ri, Kanam-Myun, Yaju-Kun,  
Kyeonggi-Do, Korea  
Tel: (031) 885-0072 Fax: (031) 885-0074
- **Test Report No.:** E05.0615.FCC.348N

## 1. INTRODUCTION

---

The measurement test for radiated and conducted emission test were conducted at the open area test site of E-RAE Testing Laboratory Inc. facility located at 584, Sangwhal-ri, Kanam-myun, Youju-kun, Kyonggi-do, Korea. The site is constructed in conformance with the requirements of the ANSI C63.4-2001 and CISPR Publication 16. The ETL has site descriptions on file with the FCC for 3 and 10meter site configurations. Detailed description of test facility was found to be in compliance with the requirements of Section 2.948 FCC Rules according to the ANSI C63.4-2001 and registered to the Federal Communications Commission (Registration Number: 95422).

The measurement procedure described in American National Standard for Method of Measurement of Radio-Noise Emission from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz (ANSI C.63.4-2001) was used in determining radiated and conducted emissions from the Xeline Co., Ltd., Model: SU-200BX.

## 2. PRODUCT INFORMATION

---

### 2.1 General Remarks

### 2.2 Equipment Description

The Equipment Under Test (EUT) is the Xeline Co., Ltd. PLC(PowerLine Communication) Modem, SU-200BX

### 2.3 General Specification



#### SU-200B Installation Manual

##### 3.3 Product Specifications

	Specifications	Remarks
Data rates	Up to 24Mbps	
Interface	RJ-45	For connection with NIC
Dimensions	186 X 143 X 40mm	(W x D x H)
Power	AC110~240V, 50/60Hz	

##### 3.4 Minimal Requirements for the Subscriber's PC

CPU	Intel Pentium 166MHz or higher
Memory	32MB or more
OS	Windows 95, 98, ME, 2000, NT, XP
Network Interface Card	10/100 base-T Ethernet Network Interface Card

## 3. DESCRIPTION OF TESTS

---

### 3.1 Conducted Emission Measurement

Conducted emissions measurements were made in accordance with § 12.2 in ANSI C63.4-2001 "Measurement of Information Technology Equipment ". The measurement were performed over the frequency range of 0.15 MHz to 30MHz using a 50 /50uH LISN as the input transducer to a Spectrum Analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Peak" amplitude within a bandwidth of 10 kHz or for "quasi-peak" within a bandwidth of 9 kHz.

- Procedure of Test

The line-conducted facility is located inside a shielded room 1 m X 1.5 m wooden table 80 cm high is placed 40 cm away from the vertical wall and 1.5 m away from the side wall of the shielded room. Two EMCO 3825/2 LISN are bonded to the shielded room. The EUT is powered from the EMCO LISN and the support equipment is powered from another EMCO LISN. Power to the LISNs are filtered by a noise cut power line filters. All electrical cables are shielded by braided tinned steel tubing with inner  $\phi$  1.2cm. If the EUT is a DC-powered device, power will be derived from the source power supply it normally will be powered from and these supply lines will be connected to the EMCO LISN. Non-inductive bundling to a 1m length shortened all interconnecting cables more than 1m. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. The RF output of the LISN was connected to the ESPI EMI Test Receiver to determine the frequency producing the max. emission from the EUT. The frequency producing max. level was reexamined using to set Quasi-Peak mode by manual, after scanned by automatic Peak mode from 0.15 MHz to 30 MHz and 0.535 MHz to 1.705 MHz. The bandwidth of the Spectrum Analyzer was set to 9 kHz. The EUT support equipment and interconnecting cables were arranged and manipulated to maximize each emission.

## 3. DESCRIPTION OF TESTS

---

### 3.2 Radiated Emission Measurement

Radiated emission measurements were in accordance with § 12.2 in ANSI C63.4-2001 "Measurement of Information Technology Equipment ". The measurements were performed over the frequency range of 30 MHz to 1 GHz and 9 kHz to 30 MHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurements were made with the detector set for "Quasi-peak" within a bandwidth of 120 kHz.

- Procedure of Test

Preliminary measurements were made at 3 meter using broadband antennas, and spectrum analyzer to determined the frequency producing the max. emission in shielded room. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turntable azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 9 to 1000 MHz using EMCO Magnetic loop antenna and SchwarzBeck Log-Bicon antenna. Above 1 GHz, linearly polarized double ridge horn antennas were used. Final measurements were made open site at 3-meters. The test equipment was placed on a wooden turntable. Sufficient time for the EUT, support equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR Quasi-peak mode and the bandwidth of the receiver was set to 200 Hz, 9 kHz, 120 kHz or 1MHz depending on the frequency of type of signal. The EUT, support equipment and interconnecting cables were re-configured to the set-up producing the max. emission for the frequency and were placed on top of a 0.8-meter high nonmetallic 1 x 1.5 meter table. The EUT, support equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the max. emission. Each emission was maximized by: varying the mode of operation to the EUT and/or support equipment and changing the polarity of the antenna, whichever determined the worst-case emission. Photographs of the worst-case emission can be seen in Photographs of the worst-case emission test setup can be seen in Appendix B.

## 4. TEST CONDITION

### 4.1 Test Configuration

The device was configured for testing in a typical fashion (as a customer would normally use it). During the tests, the following conditions and configurations were used.

### 4.2 EUT operation

The EUT was connected as user's guide.

And the test executed that data was continuously between hard drive and EUT through test program.

Operating Mode	The worst operating condition
Stand-by mode	X
Communication network monitoring mode	O

O: Worst case investigated during the Test

### 4.3 Support Equipment Used

Following peripheral devices and interface cables were connected during the measurement:

#### EUT – PLC(PowerLine Communication) Modem

FCC ID : PQVSU-200BX  
Model Name : SU-200BX  
Serial No. : N/A  
Manufacturer : Xeline Co., Ltd.  
Power Supply Type : Switching  
Power Cord : Non-shielded, Detachable: 1.2m  
Data Cable : Non-shielded Cable: 1.5m

#### Support Unit 1-Persnal computer (DELL)

FCC ID : DOC  
Model Name : DHM  
Serial No. : FNTGB1S  
Manufacturer : Dell Asia Pacific Sdn.  
Power Supply Type : Switching  
Power Cord : Non-shielded, Detachable: 1.2m  
Data Cable : Shielded Detachable: 1.2m

#### Support Unit 2-Keybord (COMPAQ)

FCC ID : DOC  
Model Name : KB-9963  
Serial No. : B26960GBUKO13F  
Manufacturer : COMPAQ  
Power Supply Type : N/A  
Power Cord : N/A  
Data Cable : Shielded, 1.5m



**Support Unit 3-Mouse (LOGITECH)**

FCC ID : DZL211029  
Model Name : M-S34  
Serial No. : LZC01002314  
Manufacturer : LOGITECH  
Power Supply Type : N/A  
Power Cord : N/A  
Data Cable : Shielded, 1.2m

**Support Unit 4- Serial Mouse (PETRA)**

FCC ID : JKGMUS5S01  
Model Name : MUS5S  
Serial No. : E183027  
Manufacturer : PETRA  
Power Supply Type : N/A  
Power Cord : N/A  
Data Cable : Shielded, 1.2m

**Support Unit 5- Monitor (E-RAE)**

FCC ID : OIOELM-150A  
Model Name : ELM-150A  
Serial No. : N/A  
Manufacturer : E-RAE Electronics Industrial Co., Ltd.  
Power Supply Type : Power Supply from DC12V of AC/DC Adapter  
Power Cord : Shielded, Detachable: 1.2m  
Data Cable : Shielded, 1.2m

**Support Unit 7- Ear Phone (JE-TECH)**

FCC ID : N/A  
Model Name : N/A  
Serial No. : N/A  
Manufacturer : JE-TECH  
Power Supply Type : N/A  
Power Cord : N/A  
Data Cable : Shielded, 1.2m

## 5. TEST RESULTS

---

### 5.1 Summary of Test Results

The measurement results were obtained with the EUT tested in the conditions described in this report. Detailed measurement data and plots showing the maximum emission of the EUT are reported.

Test Rule Parts	Measurement Required	Result
15.107(c)	Conducted Emissions Measurement	Passed by 3.21 dB
15.109(a)	Radiated Emissions Measurement	Passed by 3.60 dB
15.109(e)	Radiated Emissions Measurement	Passed by 3.86 dB

The data collected shows that the **Xeline Co., Ltd. PLC(PowerLine Communication) Modem, SU-200BX** complies with technical requirements of above rules part 15.107(c) and 15.109(a)(e) Class B Limits

The equipment is not modified anything, mechanical or circuits to improve EMI status during a measurement. No EMI suppression device(s) was added and/or modified during testing.

## 5. TEST RESULTS

### 5.21 Conducted Emissions Measurement

EUT	PLC(PowerLine Communication) Modem / SU-200BX (SN: SU0504B000059)
Limit apply to	FCC Part 15. 107(c)
Test Date	June 07, 2005
Operating Condition	Communication network monitoring mode
Environment Condition	Humidity Level : 48 %RH, Temperature : 26
Result	Passed by 3.21 dB

### Conducted Emission Test Data


The following table shows the highest levels of conducted emissions on both polarizations of hot and neutral line.

Detector mode: CISPR Quasi-Peak mode (6dB Bandwidth: 9 kHz)

Frequency [MHz]	Reading [dB $\mu$ V]		Phase (*H/**N)	Limit [dB $\mu$ V]		Margin [dB]	
	Quasi-peak	Average		Quasi-peak	Average	Q.Peak	Average
0.785	48.80		N	60.00		11.20	-
0.803	50.00		H			10.00	-
0.855	46.80		N			13.20	
1.080	50.30		N			9.70	-
1.142	48.40		H			11.60	-
1.172	51.50		N			8.50	-
1.224	50.90		H			9.10	
1.504	52.10		N			7.90	-
1.564	54.10		H			5.90	-
1.594	56.30		N			3.70	-
1.598	56.79		H			3.21	-
1.695	41.50		H			18.50	-


#### NOTES:

- \* H: HOT Line, \*\*N: Neutral Line
- Margin value = Limit – Reading
- Measurement were performed at the EUT AC power line in the frequency band of 535kHz ~ 1705kHz According to the section 15.107(c)(2)
- If the reading Quasi-Peak value is bellowed the average limit, don't test average mode.


  
 Test Engineer: K. K. Yoon

## 5. TEST RESULTS

### Line: Hot



### Line: Neutral



## 5. TEST RESULTS

### 5.3.1 Radiated Emissions Measurement

EUT	PLC(PowerLine Communication) Modem / SU-200BX (SN: SU0504B000059)
Limit apply to	FCC Part 15. 109 (a)
Test Date	June 8, 2005
Operating Condition	Communication network monitoring mode
Environment Condition	Humidity Level : 49 %RH, Temperature : 26
Result	Passed by 3.60 dB

### Radiated Emission Test Data

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.  
Detector mode: CISPR Quasi-Peak mode (6dB Bandwidth: 120 kHz)

Frequency [MHz]	Reading [dBμV]	Polarization (*H/**V)	Ant. Factor [dB/m]	Cable Loss [dB]	Result [dBμV/m]	Limit [dBμV/m]	Margin [dB]
58.63	17.87	V	11.73	2.10	31.70	40.00	8.30
61.36	22.90	V	11.39	2.11	36.40		3.60
124.76	16.42	V	12.40	3.17	32.00	43.50	11.50
149.99	11.88	H	13.27	3.55	28.70		14.80
192.26	19.13	H	10.61	3.96	33.70		9.80
299.97	15.54	H	13.16	5.50	34.20	46.00	11.80
367.17	16.01	H	14.52	6.27	36.80		9.20
376.00	21.12	H	14.72	6.36	42.20		3.80
400.75	14.99	H	15.30	6.61	36.90		9.10
499.73	13.95	H	17.25	7.60	38.80		7.20

#### NOTES:

- \* H: Horizontal polarization, \*\* V: Vertical polarization
- Result = Reading + Antenna factor + Cable loss
- Margin value = Limit - Result



Test Engineer: K. K. Yoon

## 5. TEST RESULTS

### 5.3.2 Radiated Emissions Measurement

EUT	PLC(PowerLine Communication) Modem / SU-200BX (SN: SU0504B000059)
Limit apply to	FCC Part 15. 109 (e)
Test Date	January 17, 2005
Operating Condition	Communication network monitoring mode
Environment Condition	Humidity Level : 45 %RH, Temperature : 17
Result	Passed by 3.86 dB

#### Radiated Emission Test Data

The following table shows the highest levels of radiated emissions on both polarizations of horizontal and vertical.  
Detector mode: CISPR Quasi-Peak mode.

Frequency [MHz]	Reading [dB $\mu$ V]	Polarization (*H/**V)	Ant. Factor [dB/m]	Cable Loss [dB]	Result [dB $\mu$ V/m]	Limit [dB $\mu$ V/m]	Margin [dB]
2.30	10.33	H	20.65	0.56	31.54	49.50	17.96
5.60	24.34	H	20.71	0.59	45.64		3.86
7.30	10.95	H	20.79	0.62	32.36		17.14
9.80	13.55	H	20.82	0.65	35.02		14.48
11.40	7.55	H	20.85	0.68	29.08		20.42
25.00	12.79	H	20.87	0.69	34.35		15.15

#### NOTES:

4. \* H: Horizontal polarization, \*\* V: Vertical polarization
5. Result = Reading + Antenna factor + Cable loss
6. Margin value = Limit - Result
7. The measurement was performed for the frequency range 9 kHz ~ 30 MHz according to the Section 15.109(e) requirement
9. The loop antenna was positioned with its plane vertical at 3m from the EUT and rotated about its vertical axis for maximum emission at each azimuth about the EUT



Test Engineer: K. K. Yoon

## 6. SAMPLE CALCULATION

---

### Sample of Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor.  
The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF$$

where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

$$dB(\mu V/m) = 20 \log_{10} (\mu V / m) : \text{Equation 1}$$

$$dB\mu V = dBm + 107 : \text{Equation 2}$$

Example : @ 61.36 MHz

$$\text{Class B Limit} = 40.00 \text{ dB } \mu V/m$$

$$\text{Reading} = 22.90 \text{ dB } \mu V$$

$$\text{Antenna Factor + Cable Loss} = 13.50 \text{ dB } \mu V/m$$

$$\text{Total} = 36.40 \text{ dB } \mu V/m$$

$$\text{Margin} = 40.00 - 36.40 = 3.60 \text{ dB}$$

$$= 3.60 \text{ dB below Limit}$$

## 7. TEST EQUIPMENT LIST

### List of Test Equipments Used for Measurements

	Test Equipment	Model	Mfg.	Serial No.	Cal. Due Date
<input checked="" type="checkbox"/>	Spectrum Analyzer	E7402A	H.P	US39110107	05-10-18
<input checked="" type="checkbox"/>	Receiver	ESVS 10	R & S	835165/001	06-04-07
<input checked="" type="checkbox"/>	EMI TEST Receiver	ESPI	R & S	100478	05-07-01
<input type="checkbox"/>	Preamplifier	HP 8347A	HP	2834A00544	06-04-07
<input checked="" type="checkbox"/>	LISN	3825/2	EMCO	9208-1995	06-04-07
<input checked="" type="checkbox"/>	LISN	3825/2	EMCO	9006-1669	06-04-07
<input checked="" type="checkbox"/>	Log-Bicon Antenna	VULB9160	Schwarz Beck	3082	05-07-27
<input type="checkbox"/>	Log-Bicon Antenna	VULB9165	Schwarz Beck	2023	05-07-06
<input type="checkbox"/>	Dipole Antenna	VHAP	Schwarz Beck	964	06-06-10
<input type="checkbox"/>	Dipole Antenna	VHAP	Schwarz Beck	965	05-07-09
<input type="checkbox"/>	Dipole Antenna	UHAP	Schwarz Beck	949	05-07-09
<input type="checkbox"/>	Dipole Antenna	UHAP	Schwarz Beck	950	06-06-10
<input checked="" type="checkbox"/>	Magnetic Loop Antenna	6502	EMCO	9810-2111	05-12-11
<input type="checkbox"/>	Broad band Horn Antenna	BBHA 9120D	Schwarz Beck	227	06-05-02
<input checked="" type="checkbox"/>	Turn-Table	DETT-03	Daeil EMC	-	N/A
<input checked="" type="checkbox"/>	Antenna Master	DEAM-03	Daeil EMC	-	N/A
<input type="checkbox"/>	Plotter	7440A	H.P	2725A 75722	N/A
<input checked="" type="checkbox"/>	Chamber	DTEC01	DAETONG	-	N/A
<input checked="" type="checkbox"/>	Thermo Hygrograph	3-3122	ISUZU	3312201	06-04-07
<input checked="" type="checkbox"/>	BaroMeter	-	Regulus	-	-