

FCC Test Report

Report No.: RF200723C06-1

FCC ID: PY320100480

Test Model: RAX10

Series Model: R6700AX, WAX204 (refer to item 3.1 for more details)

Received Date: Jul. 23, 2020

Test Date: Aug. 04 ~ Aug. 05, 2020

Issued Date: Aug. 07, 2020

Applicant: NETGEAR, INC.

Address: 350 East Plumeria Drive San Jose, CA 95134, USA

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, Taiwan

FCC Registration / 788550 / TW0003
Designation Number:



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification.

Table of Contents

Release Control Record	4
1 Certificate of Conformity	5
2 Summary of Test Results	6
2.1 Measurement Uncertainty	6
2.2 Modification Record	6
3 General Information	7
3.1 General Description of EUT	7
3.2 Description of Test Modes	9
3.2.1 Test Mode Applicability and Tested Channel Detail	10
3.3 Duty Cycle of Test Signal	12
3.4 Description of Support Units	13
3.4.1 Configuration of System under Test	13
3.5 General Description of Applied Standards and References	14
4 Test Types and Results	15
4.1 Radiated Emission and Bandedge Measurement	15
4.1.1 Limits of Radiated Emission and Bandedge Measurement	15
4.1.2 Test Instruments	16
4.1.3 Test Procedures	17
4.1.4 Deviation from Test Standard	17
4.1.5 Test Setup	18
4.1.6 EUT Operating Conditions	19
4.1.7 Test Results	20
4.2 Conducted Emission Measurement	40
4.2.1 Limits of Conducted Emission Measurement	40
4.2.2 Test Instruments	40
4.2.3 Test Procedures	41
4.2.4 Deviation from Test Standard	41
4.2.5 Test Setup	41
4.2.6 EUT Operating Conditions	41
4.2.7 Test Results	42
4.3 Transmit Power Measurement	44
4.3.1 Limits of Transmit Power Measurement	44
4.3.2 Test Setup	44
4.3.3 Test Instruments	44
4.3.4 Test Procedure	44
4.3.5 Deviation from Test Standard	44
4.3.6 EUT Operating Conditions	44
4.3.7 Test Result	45
4.4 Occupied Bandwidth Measurement	49
4.4.1 Test Setup	49
4.4.2 Test Instruments	49
4.4.3 Test Procedure	49
4.4.4 Test Result	50
4.5 Peak Power Spectral Density Measurement	54
4.5.1 Limits of Peak Power Spectral Density Measurement	54
4.5.2 Test Setup	54
4.5.3 Test Instruments	54
4.5.4 Test Procedures	54
4.5.5 Deviation from Test Standard	55
4.5.6 EUT Operating Conditions	55
4.5.7 Test Results	56
4.6 Frequency Stability	61
4.6.1 Limits of Frequency Stability Measurement	61

4.6.2	Test Setup	61
4.6.3	Test Instruments	61
4.6.4	Test Procedure	61
4.6.5	Deviation from Test Standard	62
4.6.6	EUT Operating Condition	62
4.6.7	Test Results	62
4.7	6dB Bandwidth Measurement	63
4.7.1	Limits of 6dB Bandwidth Measurement	63
4.7.2	Test Setup	63
4.7.3	Test Instruments	63
4.7.4	Test Procedure	63
4.7.5	Deviation from Test Standard	63
4.7.6	EUT Operating Condition	63
4.7.7	Test Results	64
5	Pictures of Test Arrangements	66
	Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)	67
	Annex B- Band Edge Measurement	70
	Appendix – Information of the Testing Laboratories	76

Release Control Record

Issue No.	Description	Date Issued
RF200723C06-1	Original release.	Aug. 07, 2020

1 Certificate of Conformity

Product: AX1800 WiFi Router, WiFi 6 AX1800 Dual Band Wireless Access Point

Brand: NETGEAR

Test Model: RAX10

Series Model: R6700AX, WAX204 (refer to item 3.1 for more details)

Sample Status: Engineering sample

Applicant: NETGEAR, INC.

Test Date: Aug. 04 ~ Aug. 05, 2020

Standards: 47 CFR FCC Part 15, Subpart E (Section 15.407)
ANSI C63.10:2013

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.

Prepared by : Pettie Chen , **Date:** Aug. 07, 2020
Pettie Chen / Senior Specialist

Approved by : Bruce Chen , **Date:** Aug. 07, 2020
Bruce Chen / Senior Project Engineer

2 Summary of Test Results

47 CFR FCC Part 15, Subpart E (Section 15.407)			
FCC Clause	Test Item	Result	Remarks
15.407(b)(6)	AC Power Conducted Emissions	Pass	Meet the requirement of limit. Minimum passing margin is -12.16dB at 0.31000MHz.
15.407(b) (1/2/3/4(i/ii)/6)	Radiated Emissions & Band Edge Measurement	Pass	Meet the requirement of limit. Minimum passing margin is -0.1dB at 5150.00MHz, 17235.00MHz.
15.407(a)(1/2/3)	Max Average Transmit Power	Pass	Meet the requirement of limit.
---	Occupied Bandwidth Measurement	Pass	Meet the requirement of limit.
15.407(a)(1/2/3)	Peak Power Spectral Density	Pass	Meet the requirement of limit.
15.407(e)	6dB bandwidth	Pass	Meet the requirement of limit. (U-NII-3 Band only)
15.407(g)	Frequency Stability	Pass	Meet the requirement of limit.
15.203	Antenna Requirement	Pass	Antenna connector is I-PEX not a standard connector.

Note:

- For U-NII-3 band compliance with rule part 15.407(b)(4)(i), the OOB test plots were recorded in Annex A.
- For U-NII-1 band compliance with rule 15.407(b) of the band-edge items, the test plots were recorded in Annex B. Test Procedures refer to report 4.1.3.
- Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

2.1 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

Measurement	Frequency	Expanded Uncertainty (k=2) ($\pm$)
Conducted Emissions at mains ports	150kHz ~ 30MHz	2.79 dB
Radiated Emissions up to 1 GHz	9kHz ~ 30MHz	3.04 dB
	30MHz ~ 200MHz	3.63 dB
	200MHz ~ 1000MHz	3.64 dB
Radiated Emissions above 1 GHz	1GHz ~ 18GHz	2.29 dB
	18GHz ~ 40GHz	2.29 dB

2.2 Modification Record

There were no modifications required for compliance.

3 General Information

3.1 General Description of EUT

Product	AX1800 WiFi Router, WiFi 6 AX1800 Dual Band Wireless Access Point
Brand	NETGEAR
Test Model	RAX10
Series Model	R6700AX, WAX204
Model Difference	Refer to note
Sample Status	Engineering sample
Power Supply Rating	12Vdc (adapter)
Modulation Type	256QAM, 64QAM, 16QAM, QPSK, BPSK for OFDM 1024QAM for OFDMA
Modulation Technology	OFDM, OFDMA
Transfer Rate	802.11a: 54/48/36/24/18/12/9/6Mbps 802.11n: up to 300Mbps 802.11ac: up to 867Mbps 802.11ax: up to 1200Mbps
Operating Frequency	5180~5240MHz, 5745~5825MHz
Number of Channel	5180 ~ 5240MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 4 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1 5745 ~ 5825MHz: 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20): 5 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40): 2 802.11ac (VHT80), 802.11ax (HE80): 1
Output Power	CDD Mode: 5180~5240MHz: 584.234mW 5745~5825MHz: 537.376mW Beamforming Mode: 5180~5240MHz: 584.234mW 5745~5825MHz: 537.376mW
Antenna Type	Refer to Note
Antenna Connector	Refer to Note
Accessory Device	Adapter
Cable Supplied	1.93m non-shielded LAN cable without core

Note:

1. All models are listed as below. Model RAX10 is the representative for final test.

Brand	Model	Product Name	RF module	Difference
NETGEAR	RAX10	AX1800 WiFi Router	RF module 1	Software firmware: V1.0.0.60
			RF module 2	
	R6700AX	AX1800 WiFi Router	RF module 1	Software firmware: V1.0.0.60
			RF module 2	
	WAX204	WiFi 6 AX1800 Dual Band Wireless Access Point	RF module 1	Software firmware: V1.0.0.62 or same as RAX10
			RF module 2	

2. The EUT incorporates a MIMO function. Physically, the EUT provides 2 completed transmitters and 2 receivers.

Modulation Mode	Beamforming Mode	TX Function
802.11a	Not Support	2TX
802.11n (HT20)	Support	2TX
802.11n (HT40)	Support	2TX
802.11ac (VHT20)	Support	2TX
802.11ac (VHT40)	Support	2TX
802.11ac (VHT80)	Support	2TX
802.11ax (HE20)	Support	2TX
802.11ax (HE40)	Support	2TX
802.11ax (HE80)	Support	2TX

* The bandwidth and modulation are similar for HT20/HT40 on 802.11n mode and VHT20/VHT40/VHT80 on 802.11ac mode and HE20/HE40/HE80 on 802.11ax mode. Therefore the investigated worst case is the representative mode in test report. (Final test mode refer section 3.2.1)

* For 802.11n and 802.11ac, CDD mode and Beamforming mode are presented in power output test item. For other test items, CDD mode is the worst case for final tests after pretesting.

3. The EUT uses following adapters.

Adapter 1	
Brand	NETGEAR
Model	AD2076F10
P/N	332-10993-01
Input Power	100-120Vac, 50/60Hz, 0.56A
Output Power	12Vdc, 1.5A
Power line	1.85m cable without core

Adapter 2	
Brand	NETGEAR
Model	2ABB018F 1
P/N	332-10927-01
Input Power	100-120Vac, 50/60Hz, 0.6A
Output Power	12Vdc, 1.5A
Power line	1.8m cable without core

*After pre-testing, adapter 1 was the worst for final tests.

4. The following antennas were provided to the EUT.

Ant. Type	Omni antenna	
Connector	I-PEX	
Gain (dBi)	Chain 0	Chain 1
2.4GHz	2.37	2.34
5GHz Band 1	2.85	2.52
5GHz Band 4	3.38	2.67

*The above Antenna information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications, the laboratory shall not be held responsible.

5. WLAN 2.4GHz & WLAN 5GHz technology can transmit at same time.

3.2 Description of Test Modes

For 5180 ~ 5240MHz:

4 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
36	5180 MHz	44	5220 MHz
40	5200 MHz	48	5240 MHz

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
38	5190 MHz	46	5230 MHz

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency
42	5210MHz

For 5745 ~ 5825MHz:

5 channels are provided for 802.11a, 802.11n (HT20), 802.11ac (VHT20), 802.11ax (HE20):

Channel	Frequency	Channel	Frequency
149	5745MHz	161	5805MHz
153	5765MHz	165	5825MHz
157	5785MHz		

2 channels are provided for 802.11n (HT40), 802.11ac (VHT40), 802.11ax (HE40):

Channel	Frequency	Channel	Frequency
151	5755MHz	159	5795MHz

1 channel is provided for 802.11ac (VHT80), 802.11ax (HE80):

Channel	Frequency
155	5775MHz

3.2.1 Test Mode Applicability and Tested Channel Detail

EUT Configure Mode	Applicable to				Description
	RE $\geq$ 1G	RE<1G	PLC	APCM	

Where RE $\geq$ 1G: Radiated Emission above 1GHz & Bandedge Measurement
 RE<1G: Radiated Emission below 1GHz
 PLC: Power Line Conducted Emission
 APCM: Antenna Port Conducted Measurement

Note:

1. The EUT had been pre-tested on the positioned of each 3 axis. The worst case was found when positioned on X-plane.
2. Radiated emission test (below 1GHz) and power line conducted emission test items chosen the worst radiated emission (above 1GHz) channel for final testing.

Radiated Emission Test (Above 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Data Rate (Mbps)
-	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	6.0
	802.11ax (HE20)		36 to 48	36, 40, 48	OFDMA	MCS0
	802.11ax (HE40)		38 to 46	38, 46	OFDMA	MCS0
	802.11ax (HE80)		42	42	OFDMA	MCS0
-	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	6.0
	802.11ax (HE20)		149 to 165	149, 157, 165	OFDMA	MCS0
	802.11ax (HE40)		151 to 159	151, 159	OFDMA	MCS0
	802.11ax (HE80)		155	155	OFDMA	MCS0

Radiated Emission Test (Below 1GHz):

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Data Rate (Mbps)
-	802.11ax (HE20)	5180-5240	36 to 48	157	OFDMA	MCS0
		5745-5825	149 to 165		OFDMA	MCS0

Power Line Conducted Emission Test:

- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Data Rate (Mbps)
-	802.11ax (HE20)	5180-5240	36 to 48	157	OFDMA	MCS0
		5745-5825	149 to 165		OFDMA	MCS0

Transmit Power Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Data Rate (Mbps)
-	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	6.0
	802.11ac (VHT20)		36 to 48	36, 40, 48	OFDM	7.2
	802.11ac (VHT40)		38 to 46	38, 46	OFDM	15.0
	802.11ac (VHT80)		42	42	OFDM	29.3
	802.11ax (HE20)		36 to 48	36, 40, 48	OFDMA	MCS0
	802.11ax (HE40)		38 to 46	38, 46	OFDMA	MCS0
	802.11ax (HE80)		42	42	OFDMA	MCS0
-	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	6.0
	802.11ac (VHT20)		149 to 165	149, 157, 165	OFDM	7.2
	802.11ac (VHT40)		151 to 159	151, 159	OFDM	15.0
	802.11ac (VHT80)		155	155	OFDM	29.3
	802.11ax (HE20)		149 to 165	149, 157, 165	OFDMA	MCS0
	802.11ax (HE40)		151 to 159	151, 159	OFDMA	MCS0
	802.11ax (HE80)		155	155	OFDMA	MCS0

Bandwidth, Peak Power Spectral Density and Frequency Stability Measurement:

- ☒ This item includes all test value of each mode, but only includes spectrum plot of worst value of each mode.
- ☒ Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations, data rates and antenna ports (if EUT with antenna diversity architecture).
- ☒ Following channel(s) was (were) selected for the final test as listed below.

EUT Configure Mode	Mode	Frequency Band (MHz)	Available Channel	Tested Channel	Modulation Technology	Data Rate (Mbps)
-	802.11a	5180-5240	36 to 48	36, 40, 48	OFDM	6.0
	802.11ax (HE20)		36 to 48	36, 40, 48	OFDMA	MCS0
	802.11ax (HE40)		38 to 46	38, 46	OFDMA	MCS0
	802.11ax (HE80)		42	42	OFDMA	MCS0
-	802.11a	5745-5825	149 to 165	149, 157, 165	OFDM	6.0
	802.11ax (HE20)		149 to 165	149, 157, 165	OFDMA	MCS0
	802.11ax (HE40)		151 to 159	151, 159	OFDMA	MCS0
	802.11ax (HE80)		155	155	OFDMA	MCS0

Test Condition:

Applicable to	Environmental Conditions	Input Power	Tested by
RE $\geq$ 1G	25 deg. C, 70% RH	120Vac, 60Hz	Noah Chang
RE<1G	25 deg. C, 70% RH	120Vac, 60Hz	Noah Chang
PLC	25 deg. C, 63% RH	120Vac, 60Hz	Jones Chang
APCM	25 deg. C, 60% RH	120Vac, 60Hz	Frank Liu

3.3 Duty Cycle of Test Signal


Duty cycle of test signal is < 98%, duty factor shall be considered.

802.11a: Duty cycle = $2.039/2.214 = 0.921$, Duty factor = $10 * \log(1/0.921) = 0.36$

802.11ax (HE20): Duty cycle = $1.48/1.532 = 0.966$, Duty factor = $10 * \log(1/0.966) = 0.15$

802.11ax (HE40): Duty cycle = $0.776/0.815 = 0.952$, Duty factor = $10 * \log(1/0.952) = 0.21$

802.11ax (HE80): Duty cycle = $0.410/0.448 = 0.915$, Duty factor = $10 * \log(1/0.915) = 0.38$



3.4 Description of Support Units

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

ID	Product	Brand	Model No.	Serial No.	FCC ID	Remarks
A.	Notebook	DELL	E5410	1HC2XM1	FCC DoC Approved	-
B.	Load	NA	NA	NA	NA	-


Note:

1. All power cords of the above support units are non-shielded (1.8m).
2. Item A acted as a communication partner to transfer data.


ID	Cable Descriptions	Qty.	Length (m)	Shielding (Yes/No)	Cores (Qty.)	Remarks
1.	LAN cable	3	1.5	N	0	RJ45, Cat5e
2.	LAN cable	1	7	N	0	RJ45, Cat5e
3.	LAN cable	1	1.93	N	0	RJ45, Cat5e, Accessory
4.	LAN cable	1	1.5	N	0	RJ45, Cat5e

3.4.1 Configuration of System under Test

AC Power Conducted Emission Test



Radiated Emissions Test



3.5 General Description of Applied Standards and References

The EUT is a RF Product. According to the specifications of the manufacturer, it must comply with the requirements of the following standards and references:

Test standard:

FCC Part 15, Subpart E (15.407)

ANSI C63.10:2013

All test items have been performed and recorded as per the above standards.

References Test Guidance:

KDB 789033 D02 General UNII Test Procedure New Rules v02r01

KDB 662911 D01 Multiple Transmitter Output v02r01

All test items have been performed as a reference to the above KDB test guidance.

4 Test Types and Results

4.1 Radiated Emission and Bandedge Measurement

4.1.1 Limits of Radiated Emission and Bandedge Measurement

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table.

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

NOTE:

- The lower limit shall apply at the transition frequencies.
- Emission level (dBuV/m) = 20 log Emission level (uV/m).
- For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Limits of unwanted emission out of the restricted bands

Applicable To			Limit	
789033 D02 General UNII Test Procedure New Rules v02r01			Field Strength at 3m	
			PK: 74 (dBµV/m)	AV: 54 (dBµV/m)
Frequency Band	Applicable To		EIRP Limit	Equivalent Field Strength at 3m
5150~5250 MHz	15.407(b)(1)		PK: -27 (dBm/MHz)	PK: 68.2(dBµV/m)
5250~5350 MHz	15.407(b)(2)			
5470~5725 MHz	15.407(b)(3)			
5725~5850 MHz	☒	15.407(b)(4)(i)	PK: -27 (dBm/MHz) ^{*1} PK: 10 (dBm/MHz) ^{*2} PK: 15.6 (dBm/MHz) ^{*3} PK: 27 (dBm/MHz) ^{*4}	PK: 68.2 (dBµV/m) ^{*1} PK: 105.2 (dBµV/m) ^{*2} PK: 110.8 (dBµV/m) ^{*3} PK: 122.2 (dBµV/m) ^{*4}
	☐	15.407(b)(4)(ii)	Emission limits in section 15.247(d)	
^{*1} beyond 75 MHz or more above of the band edge.			^{*2} below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above.	
^{*3} below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above.			^{*4} from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.	

Note: The following formula is used to convert the equipment isotropic radiated power (eirp) to field strength:

$$E = \frac{1000000 \sqrt{30 P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts).}$$

4.1.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100424	Dec. 31, 2019	Dec. 30, 2020
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Sep. 23, 2019	Sep. 22, 2020
Spectrum Analyzer ROHDE & SCHWARZ	FSV40	100980	Apr. 20, 2020	Apr. 19, 2021
BILOG Antenna SCHWARZBECK	VULB9168	9168-155	Nov. 11, 2019	Nov. 10, 2020
HORN Antenna SCHWARZBECK	BBHA 9120D	9120D-1170	Nov. 24, 2019	Nov. 23, 2020
HORN Antenna SCHWARZBECK	BBHA 9170	BBHA9170241	Nov. 24, 2019	Nov. 23, 2020
Loop Antenna TESEQ	HLA 6121	45745	Jul. 06, 2020	Jul. 05, 2021
Preamplifier Agilent (Below 1GHz)	8447D	2944A10631	Jun. 08, 2020	Jun. 07, 2021
Preamplifier KEYSIGHT (Above 1GHz)	83017A	MY53270295	Jun. 08, 2020	Jun. 07, 2021
RF Coaxial Cable WOKEN With 5dB PAD	8D-FB	Cable-CH4-01	Aug. 20, 2019	Aug. 19, 2020
RF Coaxial Cable EMCI	EMC102-KM-KM-3000	150929	Aug. 20, 2019	Aug. 19, 2020
RF Coaxial Cable EMCI	EMC102-KM-KM-600	150928	Aug. 20, 2019	Aug. 19, 2020
RF signal cable HUBER+SUHNER	SUCOFLEX 104	MY 13380+295012/04	Jun. 08, 2020	Jun. 07, 2021
RF signal cable HUBER+SUHNER	SUCOFLEX 104	Cable-CH4-03 (250724)	Jun. 08, 2020	Jun. 07, 2021
Software BV ADT	ADT_Radiated_V7.6.15.9.5	NA	NA	NA
Antenna Tower inn-co GmbH	MA 4000	010303	NA	NA
Antenna Tower Controller BV ADT	AT100	AT93021703	NA	NA
Turn Table BV ADT	TT100	TT93021703	NA	NA
Turn Table Controller BV ADT	SC100	SC93021703	NA	NA
Boresight Antenna Fixture	FBA-01	FBA-SIP01	NA	NA
Pre-amplifier (18GHz-40GHz) EMC	EMC184045B	980175	Sep. 05, 2019	Sep. 04, 2020
USB Wideband Power Sensor KEYSIGHT	U2021XA	MY55050005/MY55190004/MY55190007/MY55210005	Jul. 13, 2020	Jul. 12, 2021

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.
 2. The test was performed in HwaYa Chamber 4.

4.1.3 Test Procedures

For Radiated emission below 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f. The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz. (802.11a, 802.11ax (HE20): RBW = 1MHz, VBW = 1kHz; 802.11ax (HE40), 802.11ax (HE80): RBW = 1MHz, VBW = 3kHz)
4. All modes of operation were investigated and the worst-case emissions are reported.

4.1.4 Deviation from Test Standard


No deviation.

4.1.5 Test Setup


For Radiated emission below 30MHz



For Radiated emission 30MHz to 1GHz



For Radiated emission above 1GHz



For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.1.6 EUT Operating Conditions

- Placed the EUT on the testing table.
- Prepared a notebook to act as a communication partner and placed it outside of testing area.
- The communication partner connected with EUT via a RJ45 cable and ran a test program (provided by manufacturer) to enable EUT under transmission condition continuously at specific channel frequency.
- The communication partner sent data to EUT by command "PING".

4.1.7 Test Results

Above 1GHz data:

802.11a

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5148.30	59.8 PK	74.0	-14.2	2.63 H	360	50.8	9.0
2	5148.30	48.1 AV	54.0	-5.9	2.63 H	360	39.1	9.0
3	*5180.00	106.8 PK			2.63 H	360	66.5	40.3
4	*5180.00	97.6 AV			2.63 H	360	57.3	40.3
5	#10360.00	56.9 PK	68.2	-11.3	1.65 H	200	37.0	19.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5148.30	69.3 PK	74.0	-4.7	1.00 V	86	60.3	9.0
2	5148.30	53.6 AV	54.0	-0.4	1.00 V	86	44.6	9.0
3	*5180.00	118.2 PK			1.00 V	86	77.9	40.3
4	*5180.00	110.1 AV			1.00 V	86	69.8	40.3
5	#10360.00	57.2 PK	68.2	-11.0	2.44 V	186	37.3	19.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 40	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	61.0 PK	74.0	-13.0	2.66 H	10	52.0	9.0
2	5150.00	48.7 AV	54.0	-5.3	2.66 H	10	39.7	9.0
3	*5200.00	109.8 PK			2.66 H	10	69.6	40.2
4	*5200.00	100.2 AV			2.66 H	10	60.0	40.2
5	#10400.00	57.3 PK	68.2	-10.9	1.69 H	136	37.2	20.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	70.3 PK	74.0	-3.7	1.00 V	73	61.3	9.0
2	5150.00	53.9 AV	54.0	-0.1	1.00 V	73	44.9	9.0
3	*5200.00	120.3 PK			1.00 V	73	80.1	40.2
4	*5200.00	111.2 AV			1.00 V	73	71.0	40.2
5	#10400.00	57.6 PK	68.2	-10.6	2.64 V	193	37.5	20.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 48	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	110.3 PK			2.56 H	2	70.5	39.8
2	*5240.00	100.9 AV			2.56 H	2	61.1	39.8
3	5350.00	58.2 PK	74.0	-15.8	2.56 H	2	49.4	8.8
4	5350.00	47.3 AV	54.0	-6.7	2.56 H	2	38.5	8.8
5	#10480.00	58.1 PK	68.2	-10.1	1.65 H	105	37.9	20.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	120.0 PK			1.00 V	70	80.2	39.8
2	*5240.00	110.9 AV			1.00 V	70	71.1	39.8
3	5350.00	56.1 PK	74.0	-17.9	1.00 V	70	47.3	8.8
4	5350.00	44.9 AV	54.0	-9.1	1.00 V	70	36.1	8.8
5	#10480.00	57.8 PK	68.2	-10.4	1.96 V	254	37.6	20.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5620.40	59.1 PK	68.2	-9.1	1.32 H	340	49.7	9.4
2	*5745.00	106.0 PK			1.32 H	340	65.0	41.0
3	*5745.00	97.1 AV			1.32 H	340	56.1	41.0
4	#5929.60	60.5 PK	68.2	-7.7	1.32 H	340	50.3	10.2
5	11490.00	59.1 PK	74.0	-14.9	1.52 H	105	37.0	22.1
6	11490.00	48.9 AV	54.0	-5.1	1.52 H	105	26.8	22.1
7	#17235.00	66.8 PK	68.2	-1.4	1.00 H	349	37.5	29.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5636.00	59.3 PK	68.2	-8.9	1.00 V	64	49.9	9.4
2	*5745.00	117.8 PK			1.00 V	64	76.8	41.0
3	*5745.00	109.0 AV			1.00 V	64	68.0	41.0
4	#5954.80	59.8 PK	68.2	-8.4	1.00 V	64	49.5	10.3
5	11490.00	59.5 PK	74.0	-14.5	1.25 V	166	37.4	22.1
6	11490.00	49.9 AV	54.0	-4.1	1.25 V	166	27.8	22.1
7	#17235.00	68.1 PK	68.2	-0.1	1.00 V	349	38.8	29.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 157	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5640.80	59.1 PK	68.2	-9.1	1.28 H	337	49.6	9.5
2	*5785.00	104.4 PK			1.28 H	337	63.2	41.2
3	*5785.00	95.5 AV			1.28 H	337	54.3	41.2
4	#5969.20	60.3 PK	68.2	-7.9	1.28 H	337	50.0	10.3
5	11570.00	59.7 PK	74.0	-14.3	1.05 H	222	37.5	22.2
6	11570.00	49.1 AV	54.0	-4.9	1.05 H	222	26.9	22.2
7	#17355.00	67.0 PK	68.2	-1.2	1.28 H	332	37.2	29.8
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5628.00	58.7 PK	68.2	-9.5	1.88 V	59	49.3	9.4
2	*5785.00	117.0 PK			1.88 V	59	75.8	41.2
3	*5785.00	108.8 AV			1.88 V	59	67.6	41.2
4	#5974.80	60.0 PK	68.2	-8.2	1.88 V	59	49.7	10.3
5	11570.00	60.3 PK	74.0	-13.7	2.15 V	32	38.1	22.2
6	11570.00	49.3 AV	54.0	-4.7	2.15 V	32	27.1	22.2
7	#17355.00	67.9 PK	68.2	-0.3	1.00 V	339	38.1	29.8

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 165	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5647.60	58.0 PK	68.2	-10.2	1.28 H	335	48.5	9.5
2	*5825.00	105.9 PK			1.28 H	335	64.5	41.4
3	*5825.00	97.0 AV			1.28 H	335	55.6	41.4
4	#5984.00	60.5 PK	68.2	-7.7	1.28 H	335	50.2	10.3
5	11650.00	60.1 PK	74.0	-13.9	1.55 H	105	38.2	21.9
6	11650.00	49.1 AV	54.0	-4.9	1.55 H	105	27.2	21.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5611.20	59.4 PK	68.2	-8.8	1.18 V	144	50.0	9.4
2	*5825.00	119.0 PK			1.18 V	144	77.6	41.4
3	*5825.00	110.0 AV			1.18 V	144	68.6	41.4
4	#5929.60	59.2 PK	68.2	-9.0	1.18 V	144	49.0	10.2
5	11650.00	60.3 PK	74.0	-13.7	1.25 V	316	38.4	21.9
6	11650.00	49.0 AV	54.0	-5.0	1.25 V	316	27.1	21.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ax (HE20)

CHANNEL	TX Channel 36	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5149.00	59.9 PK	74.0	-14.1	2.62 H	358	50.9	9.0
2	5149.00	48.8 AV	54.0	-5.2	2.62 H	358	39.8	9.0
3	*5180.00	107.0 PK			2.62 H	358	66.7	40.3
4	*5180.00	96.9 AV			2.62 H	358	56.6	40.3
5	#10360.00	57.4 PK	68.2	-10.8	1.59 H	139	37.5	19.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5149.00	66.1 PK	74.0	-7.9	1.00 V	87	57.1	9.0
2	5149.00	53.6 AV	54.0	-0.4	1.00 V	87	44.6	9.0
3	*5180.00	118.5 PK			1.00 V	87	78.2	40.3
4	*5180.00	106.6 AV			1.00 V	87	66.3	40.3
5	#10360.00	57.8 PK	68.2	-10.4	1.78 V	254	37.9	19.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 40	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5149.00	62.8 PK	74.0	-11.2	3.03 H	1	53.8	9.0
2	5149.00	49.3 AV	54.0	-4.7	3.03 H	1	40.3	9.0
3	*5200.00	110.7 PK			3.03 H	1	70.5	40.2
4	*5200.00	99.8 AV			3.03 H	1	59.6	40.2
5	#10400.00	57.1 PK	68.2	-11.1	1.55 H	105	37.0	20.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5149.00	67.5 PK	74.0	-6.5	1.00 V	70	58.5	9.0
2	5149.00	53.5 AV	54.0	-0.5	1.00 V	70	44.5	9.0
3	*5200.00	119.7 PK			1.00 V	70	79.5	40.2
4	*5200.00	109.3 AV			1.00 V	70	69.1	40.2
5	#10400.00	57.3 PK	68.2	-10.9	1.96 V	241	37.2	20.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 48	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	110.2 PK			2.72 H	360	70.4	39.8
2	*5240.00	100.1 AV			2.72 H	360	60.3	39.8
3	5350.00	57.8 PK	74.0	-16.2	2.72 H	360	49.0	8.8
4	5350.00	47.4 AV	54.0	-6.6	2.72 H	360	38.6	8.8
5	#10480.00	57.5 PK	68.2	-10.7	1.69 H	200	37.3	20.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	*5240.00	122.3 PK			1.00 V	73	82.5	39.8
2	*5240.00	109.7 AV			1.00 V	73	69.9	39.8
3	5350.00	45.9 PK	74.0	-28.1	1.00 V	73	37.1	8.8
4	5350.00	45.3 AV	54.0	-8.7	1.00 V	73	36.5	8.8
5	#10480.00	57.7 PK	68.2	-10.5	2.51 V	174	37.5	20.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 149	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5640.80	59.2 PK	68.2	-9.0	1.27 H	82	49.7	9.5
2	*5745.00	105.8 PK			1.27 H	82	64.8	41.0
3	*5745.00	95.9 AV			1.27 H	82	54.9	41.0
4	#5977.20	60.6 PK	68.2	-7.6	1.27 H	82	50.3	10.3
5	11490.00	60.9 PK	74.0	-13.1	1.05 H	133	38.8	22.1
6	11490.00	49.3 AV	54.0	-4.7	1.05 H	133	27.2	22.1
7	#17235.00	66.8 PK	68.2	-1.4	1.59 H	105	37.5	29.3
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5638.00	58.6 PK	68.2	-9.6	2.04 V	65	49.1	9.5
2	*5745.00	119.0 PK			2.04 V	65	78.0	41.0
3	*5745.00	108.3 AV			2.04 V	65	67.3	41.0
4	#5988.80	59.9 PK	68.2	-8.3	2.04 V	65	49.6	10.3
5	11490.00	61.1 PK	74.0	-12.9	2.10 V	159	39.0	22.1
6	11490.00	49.7 AV	54.0	-4.3	2.10 V	159	27.6	22.1
7	#17235.00	68.0 PK	68.2	-0.2	1.00 V	352	38.7	29.3

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 157	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5628.00	60.2 PK	68.2	-8.0	1.27 H	75	50.8	9.4
2	*5785.00	106.0 PK			1.27 H	75	64.8	41.2
3	*5785.00	95.5 AV			1.27 H	75	54.3	41.2
4	#5969.60	61.5 PK	68.2	-6.7	1.27 H	75	51.2	10.3
5	11570.00	61.0 PK	74.0	-13.0	1.56 H	108	38.8	22.2
6	11570.00	49.0 AV	54.0	-5.0	1.56 H	108	26.8	22.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5604.00	59.1 PK	68.2	-9.1	1.21 V	144	49.7	9.4
2	*5785.00	121.6 PK			1.21 V	144	80.4	41.2
3	*5785.00	108.9 AV			1.21 V	144	67.7	41.2
4	#5994.80	60.2 PK	68.2	-8.0	1.21 V	144	49.8	10.4
5	11570.00	61.6 PK	74.0	-12.4	1.05 V	251	39.4	22.2
6	11570.00	49.3 AV	54.0	-4.7	1.05 V	251	27.1	22.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 165	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5611.20	58.0 PK	68.2	-10.2	2.00 H	69	48.6	9.4
2	*5825.00	109.1 PK			2.00 H	69	67.7	41.4
3	*5825.00	98.3 AV			2.00 H	69	56.9	41.4
4	#5999.60	59.9 PK	68.2	-8.3	2.00 H	69	49.5	10.4
5	11650.00	59.9 PK	74.0	-14.1	1.03 H	169	38.0	21.9
6	11650.00	48.4 AV	54.0	-5.6	1.03 H	169	26.5	21.9
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5642.40	58.9 PK	68.2	-9.3	1.93 V	64	49.4	9.5
2	*5825.00	119.4 PK			1.93 V	64	78.0	41.4
3	*5825.00	109.4 AV			1.93 V	64	68.0	41.4
4	#5989.20	61.7 PK	68.2	-6.5	1.93 V	64	51.4	10.3
5	11650.00	60.5 PK	74.0	-13.5	2.15 V	299	38.6	21.9
6	11650.00	48.8 AV	54.0	-5.2	2.15 V	299	26.9	21.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ax (HE40)

CHANNEL	TX Channel 38	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5149.00	63.5 PK	74.0	-10.5	3.14 H	44	54.5	9.0
2	5149.00	50.5 AV	54.0	-3.5	3.14 H	44	41.5	9.0
3	*5190.00	105.0 PK			3.14 H	44	64.7	40.3
4	*5190.00	94.6 AV			3.14 H	44	54.3	40.3
5	#10380.00	57.2 PK	68.2	-11.0	1.88 H	1	37.2	20.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5149.00	68.8 PK	74.0	-5.2	1.00 V	71	59.8	9.0
2	5149.00	53.8 AV	54.0	-0.2	1.00 V	71	44.8	9.0
3	*5190.00	112.2 PK			1.00 V	71	71.9	40.3
4	*5190.00	101.8 AV			1.00 V	71	61.5	40.3
5	#10380.00	57.2 PK	68.2	-11.0	1.96 V	231	37.2	20.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 46	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5149.60	65.1 PK	74.0	-8.9	3.14 H	41	54.6	10.5
2	5149.60	52.9 AV	54.0	-1.1	3.14 H	41	42.4	10.5
3	*5230.00	108.7 PK			3.14 H	41	69.4	39.3
4	*5230.00	97.3 AV			3.14 H	41	58.0	39.3
5	5350.00	59.8 PK	74.0	-14.2	3.14 H	41	49.9	9.9
6	5350.00	48.5 AV	54.0	-5.5	3.14 H	41	38.6	9.9
7	#10460.00	58.4 PK	68.2	-9.8	1.36 H	100	37.3	21.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5149.60	69.1 PK	74.0	-4.9	1.00 V	87	60.1	9.0
2	5149.60	53.8 AV	54.0	-0.2	1.00 V	87	44.8	9.0
3	*5230.00	115.1 PK			1.00 V	87	75.2	39.9
4	*5230.00	105.0 AV			1.00 V	87	65.1	39.9
5	5350.00	57.4 PK	74.0	-16.6	1.00 V	87	48.6	8.8
6	5350.00	46.2 AV	54.0	-7.8	1.00 V	87	37.4	8.8
7	#10460.00	57.7 PK	68.2	-10.5	1.89 V	245	37.5	20.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 151	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5627.20	58.4 PK	68.2	-9.8	2.42 H	52	49.0	9.4
2	*5755.00	105.4 PK			2.42 H	52	64.4	41.0
3	*5755.00	95.7 AV			2.42 H	52	54.7	41.0
4	#5992.00	59.8 PK	68.2	-8.4	2.42 H	52	49.4	10.4
5	11510.00	60.0 PK	74.0	-14.0	1.09 H	133	38.0	22.0
6	11510.00	49.0 AV	54.0	-5.0	1.09 H	133	27.0	22.0
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5646.40	63.4 PK	68.2	-4.8	2.10 V	63	53.9	9.5
2	*5755.00	115.8 PK			2.10 V	63	74.8	41.0
3	*5755.00	106.0 AV			2.10 V	63	65.0	41.0
4	#5964.80	60.0 PK	68.2	-8.2	2.10 V	63	49.7	10.3
5	11510.00	60.6 PK	74.0	-13.4	2.19 V	200	38.6	22.0
6	11510.00	49.4 AV	54.0	-4.6	2.19 V	200	27.4	22.0

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 159	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5610.00	58.9 PK	68.2	-9.3	2.60 H	51	49.5	9.4
2	*5795.00	105.8 PK			2.60 H	51	64.5	41.3
3	*5795.00	96.2 AV			2.60 H	51	54.9	41.3
4	#5937.60	59.8 PK	68.2	-8.4	2.60 H	51	49.6	10.2
5	11590.00	61.3 PK	74.0	-12.7	1.88 H	105	39.2	22.1
6	11590.00	49.0 AV	54.0	-5.0	1.88 H	105	26.9	22.1
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5636.80	59.5 PK	68.2	-8.7	1.93 V	107	50.1	9.4
2	*5795.00	118.4 PK			1.93 V	107	77.1	41.3
3	*5795.00	107.3 AV			1.93 V	107	66.0	41.3
4	#5943.60	60.5 PK	68.2	-7.7	1.93 V	107	50.3	10.2
5	11590.00	61.9 PK	74.0	-12.1	1.59 V	222	39.8	22.1
6	11590.00	49.4 AV	54.0	-4.6	1.59 V	222	27.3	22.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

802.11ax (HE80)

CHANNEL	TX Channel 42	DETECTOR FUNCTION	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz		Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	66.2 PK	74.0	-7.8	3.12 H	43	55.7	10.5
2	5150.00	51.3 AV	54.0	-2.7	3.12 H	43	40.8	10.5
3	*5210.00	100.0 PK			3.12 H	43	60.5	39.5
4	*5210.00	89.9 AV			3.12 H	43	50.4	39.5
5	5350.00	61.2 PK	74.0	-12.8	3.12 H	43	51.3	9.9
6	5350.00	48.3 AV	54.0	-5.7	3.12 H	43	38.4	9.9
7	#10420.00	59.1 PK	68.2	-9.1	1.96 H	306	37.6	21.5
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	5150.00	69.2 PK	74.0	-4.8	1.00 V	87	60.2	9.0
2	5150.00	53.5 AV	54.0	-0.5	1.00 V	87	44.5	9.0
3	*5210.00	106.8 PK			1.00 V	87	66.7	40.1
4	*5210.00	96.5 AV			1.00 V	87	56.4	40.1
5	5350.00	56.5 PK	74.0	-17.5	1.00 V	87	47.7	8.8
6	5350.00	46.4 AV	54.0	-7.6	1.00 V	87	37.6	8.8
7	#10420.00	58.0 PK	68.2	-10.2	2.31 V	174	37.9	20.1

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.

CHANNEL	TX Channel 155	DETECTOR	Peak (PK)
FREQUENCY RANGE	1GHz ~ 40GHz	FUNCTION	Average (AV)

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5630.40	65.3 PK	68.2	-2.9	2.60 H	50	55.9	9.4
2	*5775.00	102.0 PK			2.60 H	50	60.9	41.1
3	*5775.00	91.7 AV			2.60 H	50	50.6	41.1
4	#5940.40	60.4 PK	68.2	-7.8	2.60 H	50	50.2	10.2
5	11550.00	60.4 PK	74.0	-13.6	1.08 H	111	38.2	22.2
6	11550.00	49.3 AV	54.0	-4.7	1.08 H	111	27.1	22.2
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	#5605.60	67.5 PK	68.2	-0.7	1.90 V	109	58.1	9.4
2	*5775.00	113.8 PK			1.90 V	109	72.7	41.1
3	*5775.00	102.8 AV			1.90 V	109	61.7	41.1
4	#5928.40	65.4 PK	68.2	-2.8	1.90 V	109	55.2	10.2
5	11550.00	60.7 PK	74.0	-13.3	1.69 V	213	38.5	22.2
6	11550.00	49.5 AV	54.0	-4.5	1.69 V	213	27.3	22.2

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m)
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB)
3. The other emission levels were very low against the limit.
4. Margin value = Emission Level – Limit value
5. " * ": Fundamental frequency.
6. " # ": The radiated frequency is out of the restricted band.


Below 1GHz Worst-Case: 802.11ax (HE20)

CHANNEL	TX Channel 157	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	81.32	24.2 QP	40.0	-15.8	1.50 H	240	37.4	-13.2
2	166.70	26.8 QP	43.5	-16.7	1.00 H	85	35.5	-8.7
3	288.94	27.8 QP	46.0	-18.2	1.00 H	190	35.3	-7.5
4	375.29	27.3 QP	46.0	-18.7	1.00 H	19	32.9	-5.6
5	783.75	34.8 QP	46.0	-11.2	2.00 H	246	29.8	5.0
6	874.94	36.0 QP	46.0	-10.0	1.00 H	218	29.1	6.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.




CHANNEL	TX Channel 157	DETECTOR FUNCTION	Quasi-Peak (QP)
FREQUENCY RANGE	9kHz ~ 1GHz		

ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M								
NO.	FREQ. (MHz)	EMISSION LEVEL (dBuV/m)	LIMIT (dBuV/m)	MARGIN (dB)	ANTENNA HEIGHT (m)	TABLE ANGLE (Degree)	RAW VALUE (dBuV)	CORRECTION FACTOR (dB/m)
1	101.69	30.1 QP	43.5	-13.4	1.50 V	216	43.0	-12.9
2	165.73	30.2 QP	43.5	-13.3	1.00 V	230	38.8	-8.6
3	278.27	25.8 QP	46.0	-20.2	1.00 V	190	33.6	-7.8
4	480.07	26.8 QP	46.0	-19.2	1.00 V	150	30.2	-3.4
5	644.04	33.0 QP	46.0	-13.0	1.00 V	279	31.9	1.1
6	874.94	34.9 QP	46.0	-11.1	1.00 V	178	28.0	6.9

Remarks:

1. Emission Level(dBuV/m) = Raw Value(dBuV) + Correction Factor(dB/m).
2. Correction Factor(dB/m) = Antenna Factor(dB/m) + Cable Factor(dB) – Pre-Amplifier Factor(dB).
3. The other emission levels were very low against the limit of frequency range 30MHz ~ 1000MHz.
4. Margin value = Emission Level – Limit value.
5. The emission levels were very low against the limit of frequency range 9kHz ~ 30MHz: the amplitude of spurious emissions attenuated more than 20 dB below the permissible value to be report.



4.2 Conducted Emission Measurement

4.2.1 Limits of Conducted Emission Measurement

Frequency (MHz)	Conducted Limit (dBuV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30.0	60	50

Note: 1. The lower limit shall apply at the transition frequencies.

2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

4.2.2 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Test Receiver ROHDE & SCHWARZ	ESCI	100613	Dec. 11, 2019	Dec. 10, 2020
RF signal cable Woken	5D-FB	Cable-cond1-01	Sep. 05, 2019	Sep. 04, 2020
LISN ROHDE & SCHWARZ (EUT)	ENV216	101826	Feb. 20, 2020	Feb. 19, 2021
LISN ROHDE & SCHWARZ (Peripheral)	ESH3-Z5	100311	Aug. 22, 2019	Aug. 21, 2020
Software ADT	BV ADT_Cond_ V7.3.7.4	NA	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

2. The test was performed in HwaYa Shielded Room 1.

3. The VCCI Site Registration No. is C-12040.

4.2.3 Test Procedures


- The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE: The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.

4.2.4 Deviation from Test Standard

No deviation.

4.2.5 Test Setup



Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the attached file (Test Setup Photo).

4.2.6 EUT Operating Conditions

Same as 4.1.6.

4.2.7 Test Results


Worst-case data: 802.11ax (HE20)

Phase	Line (L)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	TX Channel 157		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.15000	9.80	39.88	21.97	49.68	31.77	66.00	56.00	-16.32	-24.23
2	0.17000	9.80	36.59	19.48	46.39	29.28	64.96	54.96	-18.57	-25.68
3	0.31000	9.84	33.37	27.97	43.21	37.81	59.97	49.97	-16.76	-12.16
4	0.69000	9.89	22.07	15.63	31.96	25.52	56.00	46.00	-24.04	-20.48
5	2.61800	9.99	14.66	5.20	24.65	15.19	56.00	46.00	-31.35	-30.81
6	5.10200	10.07	21.47	5.69	31.54	15.76	60.00	50.00	-28.46	-34.24

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.




Phase	Neutral (N)	Detector Function	Quasi-Peak (QP) / Average (AV)
Channel	TX Channel 157		

No	Freq. [MHz]	Corr. Factor (dB)	Reading Value [dB (uV)]		Emission Level [dB (uV)]		Limit [dB (uV)]		Margin (dB)	
			Q.P.	AV.	Q.P.	AV.	Q.P.	AV.	Q.P.	AV.
1	0.17338	9.82	35.34	18.25	45.16	28.07	64.80	54.80	-19.64	-26.73
2	0.30600	9.85	32.44	25.51	42.29	35.36	60.08	50.08	-17.79	-14.72
3	0.69800	9.92	22.78	16.75	32.70	26.67	56.00	46.00	-23.30	-19.33
4	1.55800	9.99	12.60	3.74	22.59	13.73	56.00	46.00	-33.41	-32.27
5	2.58200	10.05	14.49	4.07	24.54	14.12	56.00	46.00	-31.46	-31.88
6	5.00600	10.11	17.78	3.26	27.89	13.37	60.00	50.00	-32.11	-36.63

REMARKS:

1. Q.P. and AV. are abbreviations of quasi-peak and average individually.
2. The emission levels of other frequencies were very low against the limit.
3. Margin value = Emission level - Limit value
4. Correction factor = Insertion loss + Cable loss
5. Emission Level = Correction Factor + Reading Value.



4.3 Transmit Power Measurement

4.3.1 Limits of Transmit Power Measurement

Operation Band	EUT Category		LIMIT
U-NII-1	-	Outdoor Access Point	1 Watt (30 dBm) (Max. e.i.r.p $\leq$ 125mW(21 dBm) at any elevation angle above 30 degrees as measured from the horizon)
	-	Fixed point-to-point Access Point	1 Watt (30 dBm)
	√	Indoor Access Point	1 Watt (30 dBm)
	-	Mobile and Portable client device	250mW (24 dBm)
U-NII-2A	-		250mW (24 dBm) or 11 dBm+10 log B*
U-NII-2C	-		250mW (24 dBm) or 11 dBm+10 log B*
U-NII-3	√		1 Watt (30 dBm)

*B is the 26 dB emission bandwidth in megahertz

Per KDB 662911 Method of conducted output power measurement on IEEE 802.11 devices,


Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$;

Array Gain = 0 dB (i.e., no array gain) for channel widths ≥ 40 MHz for any N_{ANT} ;

Array Gain = $5 \log(N_{ANT}/N_{SS})$ dB or 3 dB, whichever is less for 20-MHz channel widths with $N_{ANT} \geq 5$.

For power measurements on all other devices: Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

4.3.2 Test Setup



4.3.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.3.4 Test Procedure

Method PM is used to perform output power measurement, trigger and gating function of wide band power meter is enabled to measure max output power of TX on burst and set the detector to average. Duty factor is not added to measured value.

4.3.5 Deviation from Test Standard

No deviation.

4.3.6 EUT Operating Conditions

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.3.7 Test Result

Power Output:

CDD Mode

802.11a

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
36	5180	21.17	21.50	272.172	24.35	30.00	Pass
40	5200	23.48	23.67	455.653	26.59	30.00	Pass
48	5240	24.28	24.54	552.363	27.42	30.00	Pass
149	5745	23.22	23.31	424.183	26.28	30.00	Pass
157	5785	23.20	23.33	424.208	26.28	30.00	Pass
165	5825	24.07	24.50	537.108	27.30	30.00	Pass

802.11ac (VHT20)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
36	5180	20.93	21.20	255.705	24.08	30.00	Pass
40	5200	23.47	23.73	458.379	26.61	30.00	Pass
48	5240	24.29	24.78	569.142	27.55	30.00	Pass
149	5745	23.14	23.24	416.926	26.20	30.00	Pass
157	5785	23.97	24.48	530.003	27.24	30.00	Pass
165	5825	23.95	24.37	521.840	27.18	30.00	Pass

802.11ac (VHT40)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
38	5190	19.68	19.79	188.176	22.75	30.00	Pass
46	5230	23.44	23.63	451.475	26.55	30.00	Pass
151	5755	23.85	24.38	516.818	27.13	30.00	Pass
159	5795	24.00	24.34	522.833	27.18	30.00	Pass

802.11ac (VHT80)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
42	5210	19.63	19.75	186.239	22.70	30.00	Pass
155	5775	23.07	23.26	414.604	26.18	30.00	Pass

802.11ax (HE20)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
36	5180	21.05	21.29	261.936	24.18	30.00	Pass
40	5200	23.51	23.86	467.609	26.70	30.00	Pass
48	5240	24.43	24.87	584.234	27.67	30.00	Pass
149	5745	23.19	23.30	422.245	26.26	30.00	Pass
157	5785	24.09	24.57	542.866	27.35	30.00	Pass
165	5825	24.05	24.52	537.236	27.30	30.00	Pass

802.11ax (HE40)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
38	5190	19.78	19.91	193.009	22.86	30.00	Pass
46	5230	23.54	23.72	461.449	26.64	30.00	Pass
151	5755	24.03	24.54	537.376	27.30	30.00	Pass
159	5795	24.04	24.51	536.001	27.29	30.00	Pass

802.11ax (HE80)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
42	5210	19.72	19.76	188.380	22.75	30.00	Pass
155	5775	23.23	23.39	428.651	26.32	30.00	Pass

Beamforming Mode

802.11ac (VHT20)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
36	5180	20.93	21.20	255.705	24.08	30.00	Pass
40	5200	23.47	23.73	458.379	26.61	30.00	Pass
48	5240	24.29	24.78	569.142	27.55	30.00	Pass
149	5745	23.14	23.24	416.926	26.20	29.96	Pass
157	5785	23.97	24.48	530.003	27.24	29.96	Pass
165	5825	23.95	24.37	521.840	27.18	29.96	Pass

Note:

1. 5180-5240MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 5.70\text{dBi} < 6\text{dBi}$, so the power limit is not reduced.
2. 5745-5825MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 6.04\text{dBi} > 6\text{dBi}$, so the power limit shall be reduced to $30-(6.04-6) = 29.96\text{dBm}$.

802.11ac (VHT40)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
38	5190	19.68	19.79	188.176	22.75	30.00	Pass
46	5230	23.44	23.63	451.475	26.55	30.00	Pass
151	5755	23.85	24.38	516.818	27.13	29.96	Pass
159	5795	24.00	24.34	522.833	27.18	29.96	Pass

Note:

1. 5180-5240MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 5.70\text{dBi} < 6\text{dBi}$, so the power limit is not reduced.
2. 5745-5825MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 6.04\text{dBi} > 6\text{dBi}$, so the power limit shall be reduced to $30-(6.04-6) = 29.96\text{dBm}$.

802.11ac (VHT80)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
42	5210	19.63	19.75	186.239	22.70	30.00	Pass
155	5775	23.07	23.26	414.604	26.18	29.96	Pass

Note:

1. 5180-5240MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 5.70\text{dBi} < 6\text{dBi}$, so the power limit is not reduced.
2. 5745-5825MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 6.04\text{dBi} > 6\text{dBi}$, so the power limit shall be reduced to $30-(6.04-6) = 29.96\text{dBm}$.

802.11ax (HE20)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
36	5180	21.05	21.29	261.936	24.18	30.00	Pass
40	5200	23.51	23.86	467.609	26.70	30.00	Pass
48	5240	24.43	24.87	584.234	27.67	30.00	Pass
149	5745	23.19	23.30	422.245	26.26	29.96	Pass
157	5785	24.09	24.57	542.866	27.35	29.96	Pass
165	5825	24.05	24.52	537.236	27.30	29.96	Pass

Note:

1. 5180-5240MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 5.70\text{dBi} < 6\text{dBi}$, so the power limit is not reduced.
2. 5745-5825MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 6.04\text{dBi} > 6\text{dBi}$, so the power limit shall be reduced to $30-(6.04-6) = 29.96\text{dBm}$.

802.11ax (HE40)

Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
38	5190	19.78	19.91	193.009	22.86	30.00	Pass
46	5230	23.54	23.72	461.449	26.64	30.00	Pass
151	5755	24.03	24.54	537.376	27.30	29.96	Pass
159	5795	24.04	24.51	536.001	27.29	29.96	Pass

Note:

1. 5180-5240MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 5.70\text{dBi} < 6\text{dBi}$, so the power limit is not reduced.
2. 5745-5825MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 6.04\text{dBi} > 6\text{dBi}$, so the power limit shall be reduced to $30-(6.04-6) = 29.96\text{dBm}$.

802.11ax (HE80)


Chan.	Freq. (MHz)	Maximum Conducted Power (dBm)		Total Power (mW)	Total Power (dBm)	Power Limit (dBm)	Pass / Fail
		Chain 0	Chain 1				
42	5210	19.72	19.76	188.380	22.75	30.00	Pass
155	5775	23.23	23.39	428.651	26.32	29.96	Pass

Note:

1. 5180-5240MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 5.70\text{dBi} < 6\text{dBi}$, so the power limit is not reduced.
2. 5745-5825MHz: Beamforming Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 6.04\text{dBi} > 6\text{dBi}$, so the power limit shall be reduced to $30-(6.04-6) = 29.96\text{dBm}$.

4.4 Occupied Bandwidth Measurement

4.4.1 Test Setup



4.4.2 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.4.3 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with resolution bandwidth in the range of 1% to 5% of the anticipated emission bandwidth, and a video bandwidth at least 3x the resolution bandwidth and set the detector to sampling. The width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5 %of the total mean power of a given emission.

4.4.4 Test Result

802.11a

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
36	5180	17.16	17.04
40	5200	18.24	18.12
48	5240	19.20	19.20
149	5745	17.22	17.13
157	5785	17.28	17.16
165	5825	17.52	17.52

802.11ax (HE20)

Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
36	5180	19.20	19.20
40	5200	19.56	19.56
48	5240	19.92	19.92
149	5745	19.20	19.20
157	5785	19.20	19.32
165	5825	19.32	19.32

802.11ax (HE40)


Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
38	5190	37.80	37.92
46	5230	38.16	38.16
151	5755	37.92	37.92
159	5795	38.04	37.92

802.11ax (HE80)


Channel	Frequency (MHz)	Occupied Bandwidth (MHz)	
		Chain 0	Chain 1
42	5210	77.04	77.04
155	5775	77.04	76.80

Spectrum Plot of Worst Value


802.11a




802.11ax (HE20)



802.11ax (HE40)




802.11ax (HE80)




Spectrum Plot for near By DFS Band


802.11a / Chain 0 / CH 48




802.11a / Chain 1 / CH 48




802.11ax (HE20) / Chain 0 / CH 48




802.11ax (HE20) / Chain 1 / CH 48




802.11ax (HE40) / Chain 0 / CH 46




802.11ax (HE40) / Chain 1 / CH 46



802.11ax (HE80) / Chain 0 / CH 42




802.11ax (HE80) / Chain 1 / CH 42




Spectrum Plot for near By DFS Band


802.11a / Chain 0 / CH 149




802.11a / Chain 1 / CH 149




802.11ax (HE20) / Chain 0 / CH 149




802.11ax (HE20) / Chain 1 / CH 149




802.11ax (HE40) / Chain 0 / CH 151




802.11ax (HE40) / Chain 1 / CH 151



802.11ax (HE80) / Chain 0 / CH 155



802.11ax (HE80) / Chain 1 / CH 155




4.5 Peak Power Spectral Density Measurement

4.5.1 Limits of Peak Power Spectral Density Measurement

Operation Band	EUT Category		LIMIT
U-NII-1		Outdoor Access Point	17dBm/ MHz
		Fixed point-to-point Access Point	
	√	Indoor Access Point	11dBm/ MHz
		Mobile and Portable client device	
U-NII-2A	-		11dBm/ MHz
U-NII-2C	-		11dBm/ MHz
U-NII-3	√		30dBm/ 500kHz

4.5.2 Test Setup



4.5.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.5.4 Test Procedures

For U-NII-1 band:

Duty cycle of test signal is < 98%

Using method SA-2

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 1MHz, Set VBW ≥ 3 MHz, Detector = RMS.
- 3) Set Channel power measure = 1MHz.
- 4) Sweep time = auto, trigger set to “free run”.
- 5) Trace average at least 100 traces in power averaging mode.
- 6) Record the max value and add 10 log (1/duty cycle).

For U-NII-3 band:

Duty cycle of test signal is < 98%

- 1) Set span to encompass the entire emission bandwidth (EBW) of the signal.
- 2) Set RBW = 300 kHz, Set VBW ≥ 1 MHz, Detector = RMS.
- 3) Use the peak marker function to determine the maximum power level in any 300 kHz band segment within the fundamental EBW.
- 4) Scale the observed power level to an equivalent value in 500 kHz by adjusting (reducing) the measured power by a bandwidth correction factor (BWCF) where $BWCF = 10\log(500 \text{ kHz} / 300 \text{ kHz})$.
- 5) Sweep time = auto, trigger set to “free run”.
- 6) Trace average at least 100 traces in power averaging mode.
- 7) Record the max value and add 10 log (1/duty cycle).

4.5.5 Deviation from Test Standard

No deviation.

4.5.6 EUT Operating Conditions

Same as 4.3.6.

4.5.7 Test Results

For U-NII-1 band:

802.11a

Chan.	Freq. (MHz)	PSD W/O Duty Factor (dBm/MHz)		Duty Factor (dB)	Total PSD With Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
36	5180	5.33	6.07	0.36	9.09	17.00	Pass
40	5200	7.04	6.52	0.36	10.16	17.00	Pass
48	5240	7.29	6.71	0.36	10.38	17.00	Pass

Note:

1. Method E) 2) a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 5.70\text{dBi} < 6\text{dBi}$, so the power density limit is not reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE20)

Chan.	Freq. (MHz)	PSD W/O Duty Factor (dBm/MHz)		Duty Factor (dB)	Total PSD With Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
36	5180	5.36	5.13	0.15	8.41	17.00	Pass
40	5200	7.29	7.33	0.15	10.47	17.00	Pass
48	5240	7.30	7.58	0.15	10.60	17.00	Pass

Note:

1. Method E) 2) a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 5.70\text{dBi} < 6\text{dBi}$, so the power density limit is not reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE40)

Chan.	Freq. (MHz)	PSD W/O Duty Factor (dBm/MHz)		Duty Factor (dB)	Total PSD With Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
38	5190	0.36	0.55	0.21	3.68	17.00	Pass
46	5230	3.97	4.28	0.21	7.35	17.00	Pass

Note:


1. Method E) 2) a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
2. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 5.70\text{dBi} < 6\text{dBi}$, so the power density limit is not reduced.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE80)

Chan.	Freq. (MHz)	PSD W/O Duty Factor (dBm/MHz)		Duty Factor (dB)	Total PSD With Duty Factor (dBm/MHz)	Max. Limit (dBm/MHz)	Pass / Fail
		Chain 0	Chain 1				
42	5210	-2.95	-2.80	0.38	0.52	17.00	Pass

Note:

- Method E) 2) a) of power density measurement of KDB 662911 is using for calculating total power density. Total power density is summing entire spectra across corresponding frequency bins on the various outputs by computer.
- Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 5.70\text{dBi} < 6\text{dBi}$, so the power density limit is not reduced.
- Refer to section 3.3 for duty cycle spectrum plot.



For U-NII-3 band:

802.11a

TX chain	Chan.	Freq. (MHz)	PSD W/O Duty Factor		10 log (N=3) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass / Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	149	5745	-1.13	1.09	3.01	0.36	4.46	29.96	Pass
	157	5785	-1.04	1.18	3.01	0.36	4.55	29.96	Pass
	165	5825	-0.09	2.13	3.01	0.36	5.50	29.96	Pass
1	149	5745	-1.02	1.20	3.01	0.36	4.57	29.96	Pass
	157	5785	-0.89	1.33	3.01	0.36	4.70	29.96	Pass
	165	5825	0.06	2.28	3.01	0.36	5.65	29.96	Pass

Note:

1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density.
2. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 6.04\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $30 - (6.04 - 6) = 29.96\text{dBm}$.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE20)

TX chain	Chan.	Freq. (MHz)	PSD W/O Duty Factor		10 log (N=3) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass / Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	149	5745	-1.89	0.33	3.01	0.15	3.49	29.96	Pass
	157	5785	-0.76	1.46	3.01	0.15	4.62	29.96	Pass
	165	5825	-0.81	1.41	3.01	0.15	4.57	29.96	Pass
1	149	5745	-2.05	0.17	3.01	0.15	3.33	29.96	Pass
	157	5785	-0.87	1.35	3.01	0.15	4.51	29.96	Pass
	165	5825	-0.89	1.33	3.01	0.15	4.49	29.96	Pass

Note:

1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density.
2. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 6.04\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $30 - (6.04 - 6) = 29.96\text{dBm}$.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE40)

TX chain	Chan.	Freq. (MHz)	PSD W/O Duty Factor		10 log (N=3) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass / Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	151	5755	-4.02	-1.80	3.01	0.21	1.42	29.96	Pass
	159	5795	-3.90	-1.68	3.01	0.21	1.54	29.96	Pass
1	151	5755	-3.92	-1.70	3.01	0.21	1.52	29.96	Pass
	159	5795	-3.81	-1.59	3.01	0.21	1.63	29.96	Pass

Note:

1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density.
2. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 6.04\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $30 - (6.04 - 6) = 29.96\text{dBm}$.
3. Refer to section 3.3 for duty cycle spectrum plot.

802.11ax (HE80)


TX chain	Chan.	Freq. (MHz)	PSD W/O Duty Factor		10 log (N=3) dB	Duty Factor (dB)	Total PSD With Duty Factor (dBm/500kHz)	Limit (dBm/500kHz)	Pass / Fail
			(dBm/300kHz)	(dBm/500kHz)					
0	155	5775	-7.63	-5.41	3.01	0.38	-2.02	29.96	Pass
1	155	5775	-7.52	-5.3	3.01	0.38	-1.91	29.96	Pass

Note:


1. Method E) 2) c) of power density measurement of KDB 662911 is using for calculating total power density.
2. Directional gain = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2/2] = 6.04\text{dBi} > 6\text{dBi}$, so the power density limit shall be reduced to $30 - (6.04 - 6) = 29.96\text{dBm}$.
3. Refer to section 3.3 for duty cycle spectrum plot.

Spectrum Plot of Worst Value


802.11a




802.11ax (HE20)



802.11ax (HE40)



802.11ax (HE80)




4.6 Frequency Stability

4.6.1 Limits of Frequency Stability Measurement

The frequency of the carrier signal shall be maintained within band of operation

4.6.2 Test Setup



4.6.3 Test Instruments

Description & Manufacturer	Model No.	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer ROHDE & SCHWARZ	FSP40	100040	Sep. 23, 2019	Sep. 22, 2020
Standard Temperature And Humidity Chamber	MHU-225AU	920842	May 28, 2020	May 27, 2021
Digital Multimeter Fluke	87-III	70360742	Jun. 23, 2020	Jun. 22, 2021
AC Power Supply Extech	CFW-105	E000603	NA	NA

Note: 1. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.6.4 Test Procedure

- The EUT was placed inside the environmental test chamber and powered by nominal AC voltage.
- Turn the EUT on and couple its output to a spectrum analyzer.
- Turn the EUT off and set the chamber to the highest temperature specified.
- Allow sufficient time (approximately 30 min) for the temperature of the chamber to stabilize, turn the EUT on and measure the operating frequency after 2, 5, and 10 minutes.
- Repeat step (d) with the temperature chamber set to the next desired temperature until measurements down to the lowest specified temperature have been completed.
- The test chamber was allowed to stabilize at +20 degree C for a minimum of 30 minutes. The supply voltage was then adjusted on the EUT from 85% to 115% and the frequency record.

4.6.5 Deviation from Test Standard

No deviation.

4.6.6 EUT Operating Condition

Set the EUT transmit at un-modulation mode to test frequency stability.

4.6.7 Test Results

Frequency Stability Versus Temp.									
Operating Frequency: 5180MHz									
Temp. (°C)	Power Supply (Vac)	0 Minute		2 Minute		5 Minute		10 Minute	
		Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail
50	120	5180.0044	Pass	5180.0022	Pass	5180.0030	Pass	5180.0006	Pass
40	120	5180.0079	Pass	5180.0111	Pass	5180.0071	Pass	5180.0069	Pass
30	120	5180.0047	Pass	5180.0061	Pass	5180.0062	Pass	5180.0041	Pass
20	120	5179.9816	Pass	5179.9791	Pass	5179.9800	Pass	5179.9781	Pass
10	120	5179.9976	Pass	5179.9949	Pass	5179.9950	Pass	5179.9963	Pass
0	120	5180.0098	Pass	5180.0103	Pass	5180.0114	Pass	5180.0104	Pass
-10	120	5180.0101	Pass	5180.0092	Pass	5180.0079	Pass	5180.0089	Pass
-20	120	5179.9878	Pass	5179.9860	Pass	5179.9886	Pass	5179.9866	Pass
-30	120	5180.0251	Pass	5180.0240	Pass	5180.0244	Pass	5180.0253	Pass


Frequency Stability Versus Voltage									
Operating Frequency: 5180MHz									
Temp. (°C)	Power Supply (Vac)	0 Minute		2 Minute		5 Minute		10 Minute	
		Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail	Measured Frequency (MHz)	Pass/Fail
20	138	5179.9810	Pass	5179.9796	Pass	5179.9794	Pass	5179.9783	Pass
	120	5179.9816	Pass	5179.9791	Pass	5179.9800	Pass	5179.9781	Pass
	102	5179.9812	Pass	5179.9799	Pass	5179.9810	Pass	5179.9786	Pass

4.7 6dB Bandwidth Measurement

4.7.1 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is 0.5MHz.

4.7.2 Test Setup



4.7.3 Test Instruments

Refer to section 4.1.2 to get information of above instrument.

4.7.4 Test Procedure

Measurement Procedure REF

- Set resolution bandwidth (RBW) = 100kHz
- Set the video bandwidth (VBW) $\geq 3 \times$ RBW, Detector = Peak.
- Trace mode = max hold.
- Sweep = auto couple.
- Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission

4.7.5 Deviation from Test Standard

No deviation.

4.7.6 EUT Operating Condition

The software provided by client to enable the EUT under transmission condition continuously at lowest, middle and highest channel frequencies individually.

4.7.7 Test Results

802.11a

Chan.	Freq. (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
149	5745	16.41	16.40	0.5	Pass
157	5785	16.44	16.45	0.5	Pass
165	5825	16.42	16.41	0.5	Pass

802.11ax (HE20)

Chan.	Freq. (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
149	5745	19.10	19.06	0.5	Pass
157	5785	19.03	19.06	0.5	Pass
165	5825	19.05	19.04	0.5	Pass

802.11ax (HE40)


Chan.	Freq. (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
151	5755	37.60	37.57	0.5	Pass
159	5795	37.58	37.51	0.5	Pass

802.11ax (HE80)


Chan.	Freq. (MHz)	6dB Bandwidth (MHz)		Minimum Limit (MHz)	Pass / Fail
		Chain 0	Chain 1		
155	5775	76.56	76.64	0.5	Pass

Spectrum Plot of Worst Value


802.11a




802.11ax (HE20)



802.11ax (HE40)



802.11ax (HE80)




5 Pictures of Test Arrangements

Please refer to the attached file (Test Setup Photo).

Annex A- Radiated Out of Band Emission (OOBE) Measurement (For U-NII-3 band)


802.11a




802.11ax (HE20)

CH149

Horizontal




Vertical




CH157

Horizontal




Vertical




CH165


Horizontal




Vertical



802.11ax (HE40)





802.11ax (HE80)




Annex B- Band Edge Measurement


802.11a






802.11ax (HE20)






802.11ax (HE40)



802.11ax (HE80)



Appendix – Information of the Testing Laboratories

We, Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch, were founded in 1988 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are FCC recognized accredited test firms and accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Lin Kou EMC/RF Lab

Tel: 886-2-26052180

Fax: 886-2-26051924

Hsin Chu EMC/RF/Telecom Lab

Tel: 886-3-6668565

Fax: 886-3-6668323

Hwa Ya EMC/RF/Safety Lab

Tel: 886-3-3183232

Fax: 886-3-3270892

Email: service.adt@tw.bureauveritas.com

Web Site: www.bureauveritas-adt.com

The address and road map of all our labs can be found in our web site also.

--- END ---