




Test Report 3768-166-5G-UNII1-UNII2A

Equipment Under Test:	Module, SONA NX 611 M.2 2230, 1 MHF
Requirement(s):	eCFR 47 Part 15.407 RSS-247
Test Date(s):	02/12/2024-07/10/2024
Prepared for:	Ezurio Attn: Brian Petted W66 N220 Commerce Ct. Cedarburg, WI 53012

Report Issued by: Adam Hauke, EMC Engineer
 Signature:  Date: 08/08/2024

Report Reviewed by: Adam Alger, Manager EMC Laboratory
 Signature:  Date: 8/08/2024

Report Constructed by: Adam Hauke, EMC Engineer
 Signature:  Date: 08/07/2024

This test report may not be reproduced, except in full, without approval of Ezurio

Company: Ezurio	Page 1 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: SONA NX611M
Quote: C-3768		Serial: 00047



CONTENTS

- Contents 2
- Ezurio Test Services in Review 3
- 1 Test Report Summary 4
- 2 Client Information 5
 - 2.1 Equipment Under Test (EUT) Information..... 5
 - 2.2 Product Description 5
 - 2.3 Modifications Incorporated for Compliance 5
 - 2.4 Deviations and Exclusions from Test Specifications 5
 - 2.5 EUT Information 5
 - 2.6 Ancillary Equipment 6
 - 2.7 Antenna Information 6
 - 2.8 Test Channels..... 7
 - 2.9 Power Table and Reduced Video Bandwidth for Average Measurements 7
- 3 Worst Case Test Results Summary..... 8
- 4 References 9
- 5 Uncertainty Summary 10
- 6 Test Data 11
 - 6.1 Antenna Port Conducted Emissions 11
 - 6.2 Radiated Emissions 49
 - 6.3 AC Mains Conducted Emissions..... 59
- 7 Revision History 62

Company: Ezurio	Page 2 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047

Ezurio Test Services in Review

The Ezurio laboratory located at W66 N220 Commerce Court Cedarburg, Wisconsin, 53012 USA is recognized through the following organizations:



A2LA – American Association for Laboratory Accreditation

Accreditation based on ISO/IEC 17025:2017 with Electrical (EMC) Scope

A2LA Certificate Number: 1255.01


Scope of accreditation includes all test methods listed herein unless otherwise noted



Federal Communications Commission (FCC) – USA

Accredited Test Firm Registration Number: 953492

Recognition of two 3 meter Semi-Anechoic Chambers



Innovation, Science and Economic Development Canada

Accredited U.S. Identification Number: US0218

Recognition of two 3 meter Semi-Anechoic Chambers

Company: Ezurio	Page 3 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047

1 TEST REPORT SUMMARY

During **02/15/2024-07/10/2024** the Equipment Under Test (EUT), **Module, SONA NX611 M.2 2230, 1 MHF** as provided by **Ezurio** was tested to the following requirements:

Operation in the 5.15-5.25 and 5.25-5.35 GHz bands

Requirements	Description	Method	Compliant
15.407(b)(1), (2), & (10) 15.209 RSS-247 Clause 6.2.1 & 6.2.2 RSS-GEN	Spurious Radiated Emissions in Restricted Bands 30-40000 MHz	ANSI C63.10 12.7	Yes
15.407(a)(5) RSS-247 Clause 6.2.1 & 6.2.2	26dB and 99% Occupied Bandwidth	ANSI C63.10 12.5	Yes
15.407(a)(1) & (2) RSS-247 Clause 6.2.1 & 6.2.2	RF Output Power	ANSI C63.10 12.4	Yes
15.407(b)(1) & (2) RSS-247 Clause 6.2.1 & 6.2.2	Conducted Out-of-band Emissions	ANSI C63.10 12.7	Yes
15.407(a)(1)(2) RSS-247 Clause 6.2.1 & 6.2.2	Power Spectral Density	ANSI C63.10 12.6	Yes
15.407(b)(9) 15.207 RSS-GEN	AC Conducted Emissions	ANSI C63.10 6.2	Yes
15.407(g)	Frequency Stability	ANSI C63.10 6.8	Reported

Notice:

The results relate only to the item tested as configured and described in this report. Any additional configurations, modes of operation, or modifications made to the equipment under test after the specified test date(s) are at the decision of the client and may not apply to the data seen in this test report.

The decision rule for Pass / Fail assessment to the specification or standard listed in this test report has been agreed upon by the client and laboratory to be as follows:

Measurement Type	Rule
Emissions – Amplitude	0.5 dB below specified limit
Emissions – Frequency	1% less than the specification
Immunity	Tested at specified level

Company: Ezurio	Page 4 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047



2 CLIENT INFORMATION

Company Name	Ezurio
Contact Person	Brian Petted
Address	W66 N220 Commerce Ct. Cedarburg, WI 53012

2.1 Equipment Under Test (EUT) Information

The following information has been supplied by the client

Product Name	Module, SONA NX611 M.2 2230, 1 MHF
Part Number	453-00166
Serial Number	00047
FCC ID	SQG-SONANX611M
IC ID	3147A-SONANX611M

2.2 Product Description

The NX611 is based upon NXP IW611 Wi-Fi 6 chipset. Feature-set includes 802.11 a/b/g/n/ac/ax Wi-Fi 6 and Dual-Mode Bluetooth v5.3 (BDR + EDR + BLE).

2.3 Modifications Incorporated for Compliance

None noted at time of test

2.4 Deviations and Exclusions from Test Specifications

None noted at time of test

2.5 EUT Information

Power Supply – INPUT:100-240VAC 50/60 Hz 0.3A

OUTPUT: 5VDC 2A

Firmware - sduart_nw61x_v1.bin.se

Sduart_nw61x_v1_mfg.bin.se

Company: Ezurio	Page 5 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047

2.6 Ancillary Equipment

Equipment used for EUT programming (not part of the EUT)

Development Kit, SU60-SOMC 6.0

P/N: 463-00138-K1 Rev 1

Power Supply: INPUT: 100-240 VAC 50/60Hz 0.7A

OUTPUT: 12VDC 2A

HP Elitebook 840G1

Labtool Version: 1.0.0.45.6

2.7 Antenna Information

Manufacturer	Model	Part Number	Dimension	Type	Peak Gain (dBi)	
					2400-2500 MHz	4900-5925 MHz
Laird Connectivity	FlexMIMO 6E	EFD2471A3S-10MH4L	39.5mm X 39.5mm X 4.7mm	PIFA	2.2	3.8
Laird Connectivity	FlexPIFA 6E	EFB2471A3S-10MH4L	16mm X 36mm X 2.5mm	PIFA	2.2	3.9
Laird Connectivity	Mini NanoBlade Flex 6E	EMF2471A3S-10MH4L	36mm X 12mm X 0.3mm	PCB Dipole	2.4	4.4
Joymax Electronics	N/A	TWX-100BRS3B	137mm X 13mm	Dipole	2.0	4.0
Laird Connectivity	FlexPIFA	EFB2455A3S-16MHF1	38.5mm X 12.7 mm X 2.5mm	PIFA	2.5	3.0

2.8 Test Channels

Channel	Frequency (MHz)	Bandwidth (MHz)	Data Rates
36	5180	20	
40	5200	20	
48	5240	20	
38	5190	40	
46	5230	40	
42	5210	80	
52	5260	20	802.11a – 6 and 54 Mbps
56	5280	20	802.11n – MCS0 and MCS7
64	5320	20	802.11ac – MCS0 and MCS9
54	5270	40	802.11ax – MCS0 and MCS11
62	5310	40	
58	5290	80	

2.9 Power Table and Reduced Video Bandwidth for Average Measurements

802.11	Channel BW (MHz)	Data Rate	Minimum Average VBW (Hz)	Power Setting
a	20	6 Mbps	698	16
a	20	54 Mbps	5565	16
n	20	MCS0	746	14
n	20	MCS7	5959	14
ac	20	MCS0	742	14
ac	20	MCS8	6361	14
ax	20	MCS0	956	11
ax	20	MCS11	8628	10
n	40	MCS0	1506	13
n	40	MCS7	9980	13
ac	40	MCS0	1489	13
ac	40	MCS9	10870	12
ax	40	MCS0	1815	11
ax	40	MCS11	11737	10
ac	80	MCS0	3013	11
ac	80	MCS9	15601	11
ax	80	MCS0	3414	9
ax	80	MCS11	13280	9

3 WORST CASE TEST RESULTS SUMMARY

UNII-1

Requirement	Radio	Channel and Data Rate	Frequency (MHz)	Measurement	Limit	Margin
15.407(a)(5) RSS-247 Clause 6.2.1 26dB Bandwidth	802.11a	48 54 Mbps	-	19.0 MHz	at least 500 kHz	-
15.407(a)(1) RSS-247 Clause 6.2.1 Output Power	802.11a	40 54 Mbps	-	16.2 dBm	24.0 dBm	7.8 dB
15.407(a)(1) RSS-247 Clause 6.2.1 PSD	802.11ax20	40 MCS0 RU26	-	10.5 dBm/1 MHz	11.0 dBm/1 MHz	0.5 dB
15.407(b)(1) RSS-247 Clause 6.2.1 Restricted Band	802.11n40	38 MCS0	5148.6	-28.8 dBm	-27.0 dBm	1.8 dB
15.407(b)(9) RSS-GEN Spurious Below 1 GHz	802.11a	36 6 Mbps	66.3	39.2 dBμV/m	40.0 dBμV/m	0.8 dB
15.407(b)(9) RSS-GEN AC Conducted	802.11a	36 6 Mbps	0.159	59.5 dBμV	65.5 dBμV	6.0 dB

UNII-2A

Requirement	Radio	Channel and Data Rate	Frequency (MHz)	Measurement	Limit	Margin
15.407(a)(5) RSS-247 Clause 6.2.1 26dB Bandwidth	802.11a	56 54 Mbps	-	19.1 MHz	at least 500 kHz	-
15.407(a)(1) RSS-247 Clause 6.2.1 Output Power	802.11a	52 54 Mbps	-	15.8 dBm	24.0 dBm	8.2 dB
15.407(a)(1) RSS-247 Clause 6.2.1 PSD	802.11ax40	62 MCS0 RU26	-	9.7 dBm/1 MHz	11.0 dBm/1 MHz	1.3 dB
15.407(b)(1) RSS-247 Clause 6.2.1 Restricted Band	802.11ac80	58 MCS9	5351.7	-44.1 dBm	-41.2 dBm	2.9 dB

4 REFERENCES

Publication	Edition	Date	AMD 1	AMD 2
FCC eCFR 47 Part 15	-	2023	-	-
ANSI C63.10	-	2020	-	-
RSS-247	3	2023	-	-
RSS-GEN	5	2018	2019	2021
KDB 558074 D01	-	2019	-	-

Company: Ezurio	Page 9 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047

5 UNCERTAINTY SUMMARY

Using the guidance of the following publications the calculated measurement uncertainty represents an expanded uncertainty expressed at approximately the 95 % confidence level, using a coverage factor of $k = 2$.

References

CISPR 16-4-1

CISPR 16-4-2

CISPR 32

ANSI C63.23

A2LA P103

A2LA P103c

ETSI TR 100-028

Measurement Type	Configuration	Uncertainty \pm
Radiated Emissions	Biconical Antenna	5.0 dB
Radiated Emissions	Log Periodic Antenna	5.3 dB
Radiated Emissions	Horn Antenna	4.7 dB
AC Line Conducted Emissions	Artificial Mains Network	3.4 dB
Telecom Conducted Emissions	Asymmetric Artificial Network	4.9 dB
Disturbance Power Emissions	Absorbing Clamp	4.1 dB
Radiated Immunity	3 Volts/meter	2.2 dB
Conducted Immunity	CDN/EM/BCI	2.4/3.5/3.4 dB
EFT Burst/Surge	Peak pulse voltage	164 volts
ESD Immunity	15 kV level	1377 Volts

Parameter	ETSI U.C. \pm	U.C. \pm
Radio Frequency, from F0	1×10^{-7}	0.55×10^{-7}
Occupied Channel Bandwidth	5 %	2 %
RF conducted Power (Power Meter)	1.5 dB	1.2 dB
RF conducted emissions (Spectrum Analyzer)	3.0 dB	1.7 dB
All emissions, radiated	6.0 dB	5.3 dB
Temperature	1° C	0.65° C
Humidity	5 %	2.9 %
Supply voltages	3 %	1 %


Company: Ezurio	Page 10 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047

6 TEST DATA

6.1 Antenna Port Conducted Emissions

Description of Measurement	<p>The direct measurement of emissions at the antenna port of the EUT is achieved by use of a RF connection to a spectrum analyzer or power meter.</p> <p>The cable and attenuator factors are loaded into the analyzer or power meter allowing for direct measurement readings without the need for further corrections.</p>
Example Calculations	<p>Measurement (dBm) + Cable factor (dB) + External Attenuator (dB) = Corrected Reading (dBm)</p> <p>Margin (dB) = Limit (dBm) – Corrected Reading (dBm)</p>

Block Diagram



6.1.1 26dB and 99% Occupied Bandwidth

Operator	Anthony Smith	QA	Adam Hauke
Temperature	21.9°C 22.4°C	R.H. %	27.50% 25.70%
Test Date	02/15/2024 03/28/2024	Location	Conducted RF Bench
Requirement	15.407 (a)(5) RSS-247 Clause 6.2.1 & 6.2.2	Method	ANSI C63.10 12.5

Limits: The minimum 26 dB bandwidth shall be at least 500 kHz

Test Parameters

Frequency	5150-5350 MHz		
RBW	20 MHz BW – 200 kHz 40 MHz BW – 420 kHz 80 MHz BW – 1 MHz	VBW	20 MHz BW – 620 kHz 40 MHz BW – 1.5 MHz 80 MHz BW – 3 MHz
Detector(s)	Peak	Settings	Max Hold

Instrumentation

Asset #	Description	Manufacturer	Model #	Serial #	Date	Due Date	Status
AA 960173	Cable	A.H. Systems, Inc.	SAC-26G-1	388	6/13/2023	6/12/2024	Active Verification
EE 960088	Analyzer - EMI Receiver	Agilent	N9038A	MY51210138	4/10/2023	4/10/2024	Active Calibration

EUT Parameters

Input Power	120 VAC @ 60 Hz	Mode	5 GHz WLAN Tx
Frequency	5180-5320 MHz	Channel	See 2.8

Company: Ezurio	Page 12 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047



U-NII-1 Measurements

Mode	Rate	Channel	26 dB BW (MHz)	99% BW (MHz)
802.11a	6 Mbps	36	19.4	16.5
		40	19.7	16.5
		48	19.4	16.5
	54 Mbps	36	19.1	16.5
		40	19.1	16.5
		48	19.0	16.5
802.11n20	MCS0	36	19.6	17.6
		40	19.5	17.6
		48	19.8	17.6
	MCS7	36	19.5	17.6
		40	19.7	17.6
		48	19.7	17.6
802.11ac20	MCS0	36	19.7	17.6
		40	19.7	17.6
		48	19.8	17.6
	MCS8	36	19.7	17.6
		40	19.6	17.6
		48	19.5	17.6
802.11ax20	MCS0	36	20.3	18.8
		40	20.4	18.8
		48	20.3	18.8
	MCS11	36	20.3	18.8
		40	20.2	18.8
		48	20.0	18.7
802.11n40	MCS0	38	40.4	36.1
		46	40.3	36.1
	MCS7	38	40.3	37.5
		46	39.6	37.5
802.11ac40	MCS0	38	40.6	36.1
		46	40.0	36.1
	MCS9	38	40.3	36.2
		46	40.4	36.1
802.11ax40	MCS0	38	39.6	37.5
		46	40.3	37.5
	MCS11	38	40.2	37.5
		46	40.3	37.5
802.11ac80	MCS0	42	81.5	76.0
	MCS9	42	81.8	76.4
802.11ax80	MCS0	42	80.6	77.6
	MCS11	42	80.8	77.5


Company: Ezurio	Page 13 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047

U-NII-1 Plots



802.11a | Channel 48 | 54 Mbps

802.11n20 | Channel 40 | MCS0



802.11ac20 | Channel 48 | MCS8

802.11ax20 | Channel 40 | MCS11



802.11ax40 | Channel 38 | MCS0

802.11ax80 | Channel 42 | MCS0


Company: Ezurio	Page 14 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047



U-NII-2A Measurements

Mode	Rate	Channel	26 dB BW (MHz)	99% BW (MHz)
802.11a	6 Mbps	52	19.7	16.5
		56	19.2	16.5
		64	19.4	16.5
	54 Mbps	52	19.5	16.5
		56	19.1	16.5
		64	19.4	16.5
802.11n20	MCS0	52	19.7	17.6
		56	19.8	17.6
		64	19.7	17.6
	MCS7	52	19.5	17.6
		56	19.6	17.6
		64	19.7	17.6
802.11ac20	MCS0	52	19.7	17.6
		56	19.9	17.6
		64	19.7	17.6
	MCS8	52	19.5	17.6
		56	19.6	17.6
		64	19.7	17.6
802.11ax20	MCS0	52	20.2	18.8
		56	20.3	18.8
		64	20.4	18.8
	MCS11	52	20.0	18.7
		56	20.2	18.8
		64	20.1	18.7
802.11n40	MCS0	54	40.1	36.1
		62	40.4	36.1
	MCS7	54	39.4	36.1
		62	39.9	36.2
802.11ac40	MCS0	54	40.2	36.1
		62	40.0	36.1
	MCS9	54	40.2	36.2
		62	40.5	36.2
802.11ax40	MCS0	54	40.2	37.5
		62	40.3	37.5
	MCS11	54	40.3	37.5
		62	40.2	37.5
802.11ac80	MCS0	58	81.9	75.9
	MCS9	58	81.8	76.3
802.11ax80	MCS0	58	80.5	77.5
	MCS11	58	80.7	77.4


U-NII-2A Plots



802.11a | Channel 56 | 54 Mbps



802.11n20 | Channel 52 | MCS0




802.11ac20 | Channel 52 | MCS0



802.11ax20 | Channel 52 | MCS11



802.11n40 | Channel 54 | MCS0




802.11ac40 | Channel 54 | MCS0


Company: Ezurio	Page 16 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047



802.11ax40 | Channel 54 | MCS0



802.11ac80 | Channel 58 | MCS0



802.11ax80 | Channel 58 | MCS11

Company: Ezurio	Page 17 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047

6.1.2 RF Output Power

Operator	Dylan Rosenfeldt	QA	Anthony Smith
Temperature	21.6°C 22.1°C 21.8°C 21.6°C	R.H. %	25.90% 29.30% 53.50% 44.40%
Test Date	02/26/2024-02/27/2024 04/29/2024-04/30/2024	Location	Conducted RF Bench
Requirement	15.407 (a)(1) & (2) RSS-247 Clause 6.2.1 & 6.2.2	Method	ANSI C63.10 12.4 AVGSA-2

Limit: The maximum peak conducted output power of the intentional radiator shall not exceed 250 mW.

Test Parameters

Frequency	5150-5350 MHz	Setup	Antenna Port
RBW	1 MHz	VBW	3 MHz
Detector(s)	Peak	Settings	Max Hold Span: 30 MHz 60 MHz 120 MHz
Example Calculations	Average Output Power = Measured Power + 10*log(1/D) where D is the duty cycle.		

Instrumentation

Asset #	Description	Manufacturer	Model #	Serial #	Date	Due Date	Status
AA 960172	Cable	A.H. Systems, Inc.	SAC-26G-1	387	06/13/2023	06/12/2024	Active Verification
EE 960087	Analyzer – Spectrum	Agilent	N9010A	MY53400296	04/11/2023	04/11/2024	Active Calibration

EUT Parameters

Input Power	120 VAC @ 60 Hz	Mode	5 GHz WLAN Tx
Frequency	5180-5320 MHz	Channel	See 2.9


U-NII-1 Measurements

Mode	Rate	Channel	Average Output Power (dBm)	Duty Cycle Correction (dB)	Corrected Output Power (dBm)	Limit (dBm)	Margin (dB)	
802.11a	6 Mbps	36	16.0	-	16.0	24.0	8.0	
		40	16.0	-	16.0	24.0	8.0	
		48	15.9	-	15.9	24.0	8.1	
	54 Mbps	36	15.7	0.4	16.1	24.0	7.9	
		40	15.8	0.4	16.2	24.0	7.8	
		48	15.6	0.4	16.0	24.0	8.1	
802.11n20	MCS0	36	15.0	-	15.0	24.0	9.0	
		40	15.1	-	15.1	24.0	8.9	
		48	14.9	-	14.9	24.0	9.1	
	MCS7	36	14.7	0.4	15.1	24.0	8.9	
		40	14.8	0.4	15.2	24.0	8.8	
		48	14.6	0.4	15.0	24.0	9.0	
802.11ac20	MCS0	36	14.9	-	14.9	24.0	9.1	
		40	15.2	-	15.2	24.0	8.9	
		48	15.0	-	15.0	24.0	9.0	
	MCS8	36	14.6	0.4	15.0	24.0	9.1	
		40	14.9	0.4	15.3	24.0	8.7	
		48	14.6	0.4	15.0	24.0	9.0	
802.11ax20	MCS0	36	15.2	-	15.2	24.0	8.8	
		40	15.3	-	15.3	24.0	8.7	
		48	15.1	-	15.1	24.0	8.9	
	MCS11	36	10.7	0.5	11.2	24.0	12.8	
		40	10.9	0.5	11.4	24.0	12.7	
		48	10.8	0.5	11.3	24.0	12.7	
802.11n40	MCS0	38	12.9	0.1	13.0	24.0	11.0	
		46	13.0	0.1	13.1	24.0	10.9	
	MCS7	38	12.6	0.6	13.2	24.0	10.8	
		46	12.4	0.6	13.0	24.0	11.0	
	802.11ac40	MCS0	38	14.9	0.1	15.0	24.0	9.0
			46	14.9	0.1	15.0	24.0	9.0
MCS9		38	12.5	0.7	13.2	24.0	10.8	
		46	12.3	0.7	13.0	24.0	11.0	
802.11ax40	MCS0	38	15.3	0.1	15.4	24.0	8.6	
		46	15.2	0.1	15.3	24.0	8.7	
	MCS11	38	10.6	0.7	11.3	24.0	12.7	
		46	10.7	0.7	11.4	24.0	12.6	
802.11ac80	MCS0	42	12.8	0.2	13.0	24.0	11.0	
	MCS9	42	11.0	1.0	12.0	24.0	12.0	
802.11ax80	MCS0	42	12.1	0.2	12.3	24.0	11.7	
	MCS11	42	10.4	0.8	11.2	24.0	12.8	

Company: Ezurio	Page 19 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047


Mode	Rate RU	Channel	Average Output Power (dBm)	Duty Cycle Correction (dB)	Corrected Output Power (dBm)	Limit (dBm)	Margin (dB)
802.11ax20	MCS0 RU26	36	9.7	0.2	9.9	24.0	14.1
		40	10.2	0.2	10.4	24.0	13.6
		48	10.2	0.2	10.4	24.0	13.6
	MCS0 RU52	36	9.7	0.2	9.9	24.0	14.1
		40	10.2	0.2	10.4	24.0	13.7
		48	10.3	0.2	10.5	24.0	13.5
	MCS0 RU106	36	10.0	0.2	10.2	24.0	13.8
		40	10.3	0.2	10.5	24.0	13.5
		48	10.4	0.2	10.6	24.0	13.4
802.11ax40	MCS0 RU26	38	8.7	0.2	8.9	24.0	15.1
		46	8.7	0.2	8.9	24.0	15.1
	MCS0 RU52	38	9.4	0.2	9.6	24.0	14.4
		46	10.1	0.2	10.3	24.0	13.7
	MCS0 RU106	38	9.5	0.2	9.7	24.0	14.3
		46	10.1	0.2	10.3	24.0	13.7
	MCS0 RU242	38	9.7	0.2	9.9	24.0	14.1
46		10.3	0.2	10.5	24.0	13.5	
802.11ax80	MCS0 RU26	42	9.6	0.2	9.8	24.0	14.2
		42	9.5	0.2	9.7	24.0	14.3
	MCS0 RU106	42	9.5	0.2	9.7	24.0	14.3
		42	9.4	0.2	9.6	24.0	14.4
	MCS0 RU484	42	9.7	0.2	9.9	24.0	14.1

U-NII-1 Plots




802.11a | Channel 40 | 54 Mbps

802.11n20 | Channel 40 | MCS0



802.11ac20 | Channel 40 | MCS0

802.11ax20 | Channel 40 | MCS0



802.11n40 | Channel 38 | MCS7

802.11ac40 | Channel 46 | MCS9


Company: Ezurio	Page 21 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047




802.11ax40 | Channel 46 | MCS0




802.11ac80 | Channel 42 | MCS0




802.11ax80 | Channel 42 | MCS0



802.11ax20 | Channel 40 | MCS0 | RU106



802.11ax40 | Channel 46 | MCS0 | RU242



802.11ax80 | Channel 42 | MCS0 | RU26

Company: Ezurio	Page 22 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047


U-NII-2A Measurements

Mode	Rate	Channel	Average Output Power (dBm)	Duty Cycle Correction (dB)	Corrected Output Power (dBm)	Limit (dBm)	Margin (dB)
802.11a	6 Mbps	52	15.6		15.6	23.9	8.3
		56	15.6		15.6	23.9	8.3
		64	15.3		15.3	23.9	8.6
	54 Mbps	52	15.4	0.4	15.8	23.9	8.2
		56	15.2	0.4	15.6	23.9	8.3
		64	14.9	0.4	15.3	23.9	8.6
802.11n20	MCS0	52	14.7		14.7	24.0	9.3
		56	14.6		14.6	24.0	9.4
		64	14.3		14.3	24.0	9.7
	MCS7	52	14.4	0.4	14.8	24.0	9.2
		56	14.3	0.4	14.7	24.0	9.3
		64	14.0	0.4	14.4	24.0	9.6
802.11ac20	MCS0	52	14.8		14.8	24.0	9.2
		56	14.6		14.6	24.0	9.4
		64	14.3		14.3	24.0	9.7
	MCS8	52	14.4	0.4	14.8	24.0	9.2
		56	14.3	0.4	14.7	24.0	9.3
		64	14.0	0.4	14.4	24.0	9.6
802.11ax20	MCS0	52	14.9		14.9	24.0	9.1
		56	14.8		14.8	24.0	9.2
		64	14.5		14.5	24.0	9.5
	MCS11	52	10.3	0.5	10.8	24.0	13.2
		56	10.3	0.5	10.8	24.0	13.2
		64	10.1	0.5	10.6	24.0	13.4
802.11n40	MCS0	54	12.6	0.1	12.7	24.0	11.3
		62	12.3	0.1	12.4	24.0	11.6
	MCS7	54	12.2	0.6	12.8	24.0	11.2
		62	11.9	0.6	12.5	24.0	11.5
802.11ac40	MCS0	54	14.3	0.1	14.4	24.0	9.6
		62	14.2	0.1	14.3	24.0	9.7
	MCS9	54	11.8	0.7	12.5	24.0	11.6
		62	11.7	0.7	12.4	24.0	11.6
802.11ax40	MCS0	54	14.6	0.1	14.7	24.0	9.3
		62	14.6	0.1	14.7	24.0	9.3
	MCS11	54	9.9	0.7	10.6	24.0	13.4
		62	10.0	0.7	10.7	24.0	13.3
802.11ac80	MCS0	58	12.4	0.2	12.6	24.0	11.4
	MCS9	58	10.7	1.0	11.7	24.0	12.3
802.11ax80	MCS0	58	11.7	0.2	11.9	24.0	12.1
	MCS11	58	10.0	0.8	10.8	24.0	13.2

Company: Ezurio	Page 23 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047


Mode	Rate RU	Channel	Average Output Power (dBm)	Duty Cycle Correction (dB)	Corrected Output Power (dBm)	Limit (dBm)	Margin (dB)
802.11ax20	MCS0 RU26	52	10.0	0.2	10.2	23.9	13.8
		56	10.1	0.2	10.3	23.9	13.6
		64	10.1	0.2	10.3	23.9	13.6
	MCS0 RU52	52	9.9	0.2	10.1	23.9	13.8
		56	10.0	0.2	10.2	23.9	13.7
		64	10.2	0.2	10.4	23.9	13.6
	MCS0 RU106	52	10.0	0.2	10.2	24.0	13.8
		56	10.1	0.2	10.3	24.0	13.7
		64	10.2	0.2	10.4	24.0	13.6
802.11ax40	MCS0 RU26	54	8.9	0.2	9.1	24.0	14.9
		62	9.0	0.2	9.2	24.0	14.8
	MCS0 RU52	54	9.8	0.2	10.0	24.0	14.0
		62	10.1	0.2	10.3	24.0	13.7
	MCS0 RU106	54	9.8	0.2	10.0	24.0	14.0
		62	10.1	0.2	10.3	24.0	13.8
	MCS0 RU242	54	10.0	0.2	10.2	24.0	13.8
62		10.2	0.2	10.4	24.0	13.6	
802.11ax80	MCS0 RU26	58	9.6	0.2	9.8	24.0	14.3
		58	9.4	0.2	9.6	24.0	14.4
	MCS0 RU106	58	9.4	0.2	9.6	24.0	14.4
		58	9.5	0.2	9.7	24.0	14.3
	MCS0 RU484	58	9.5	0.2	9.7	24.0	14.3

U-NII-2A Plots




802.11a | Channel 52 | 54 Mbps

802.11n20 | Channel 52 | MCS7



802.11ac20 | Channel 52 | MCS0

802.11ax20 | Channel 52 | MCS0




802.11n40 | Channel 54 | MCS7

802.11ac40 | Channel 54 | MCS0


Company: Ezurio	Page 25 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047




802.11ax40 | Channel 54 | MCS11




802.11ac80 | Channel 58 | MCS9




802.11ax80 | Channel 58 | MCS0



802.11ax20 | Channel 56 | MCS0 | RU52



802.11ax40 | Channel 54 | MCS0 | RU 242



802.11ax80 | Channel 58 | MCS0 | RU52

Company: Ezurio	Page 26 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047

6.1.3 Power Spectral Density

Operator	Dylan Rosenfeldt Anthony Smith	QA	Adam Hauke
Temperature	21.8°C-22.2°C	R.H. %	44.80%-50.40%
Test Date	05/01/2024-05/17/2024	Location	Conducted RF Bench
Requirement	15.407 (a)(1) & (2) RSS-247 Clause 6.2.1 & 6.2.2	Method	ANSI C63.10 12.6 AVGPSD-2

Limits: Power spectral density shall not be greater than 11 dBm in any 1 MHz band.

Test Parameters

Frequency	5150-5350 MHz	Detector(s)	Avg (RMS)
RBW	1 MHz	VBW	3 MHz
Notes	The same method of determining the conducted output power shall be used to determine the power spectral density		
Example Calculations	Average PSD = Measured PSD + 10*log(1/D0 where D is the duty cycle.		

Instrumentation

Asset #	Description	Manufacturer	Model #	Serial #	Date	Due Date	Status
AA 960172	Cable	A.H. Systems, Inc.	SAC-26G-1	387	06/13/2023	06/12/2024	Active Verification
EE 960087	Analyzer – Spectrum	Agilent	N9010A	MY53400296	04/11/2023	04/11/2024	Active Calibration

EUT Parameters

Input Power	120 VAC @ 60 Hz	Mode	5 GHz WLAN Tx
Frequency	5180-5320 MHz	Channel	See 2.9


U-NII-1 Measurements

Mode	Rate	Channel	Maximum Average PSD (dBm/1 MHz)	Duty Cycle Correction (dB)	Corrected Output Value (dBm/1 MHz)	Limit (dBm/1 MHz)	Margin (dB)
802.11a	6 Mbps	36	4.5	-	4.5	11.0	6.5
		40	5.1	-	5.1	11.0	5.9
		48	4.9	-	4.9	11.0	6.1
	54 Mbps	36	4.8	0.4	5.2	11.0	5.8
		40	5.0	0.4	5.4	11.0	5.6
		48	5.3	0.4	5.7	11.0	5.3
802.11n20	MCS0	36	3.6	-	3.6	11.0	7.4
		40	3.7	-	3.7	11.0	7.3
		48	3.9	-	3.9	11.0	7.1
	MCS7	36	3.2	0.4	3.6	11.0	7.4
		40	3.8	0.4	4.2	11.0	6.8
		48	3.7	0.4	4.1	11.0	6.9
802.11ac20	MCS0	36	3.5	-	3.5	11.0	7.5
		40	3.7	-	3.7	11.0	7.3
		48	3.7	-	3.7	11.0	7.3
	MCS8	36	3.7	0.4	4.1	11.0	6.9
		40	3.5	0.4	3.9	11.0	7.1
		48	3.7	0.4	4.1	11.0	6.9
802.11ax20	MCS0	36	3.6	-	3.6	11.0	7.4
		40	3.7	-	3.7	11.0	7.3
		48	3.8	-	3.8	11.0	7.2
	MCS11	36	-0.7	0.5	-0.2	11.0	11.2
		40	-0.4	0.5	0.1	11.0	10.9
		48	-0.1	0.5	0.4	11.0	10.6
802.11n40	MCS0	38	-1.6	0.1	-1.5	11.0	12.5
		46	-1.6	0.1	-1.5	11.0	12.5
	MCS7	38	-1.8	0.6	-1.2	11.0	12.2
		46	-1.3	0.6	-0.7	11.0	11.7
802.11ac40	MCS0	38	0.8	0.1	0.9	11.0	10.1
		46	0.8	0.1	0.9	11.0	10.1
	MCS9	38	-1.4	0.7	-0.7	11.0	11.7
		46	-1.5	0.7	-0.8	11.0	11.8
802.11ax40	MCS0	38	-1.6	0.1	-1.5	11.0	12.5
		46	-1.3	0.1	-1.2	11.0	12.2
	MCS11	38	-3.9	0.7	-3.2	11.0	14.2
		46	-3.5	0.7	-2.8	11.0	13.8
802.11ac80	MCS0	42	-4.8	0.2	-4.6	11.0	15.6
	MCS9	42	-6.0	1.0	-5.0	11.0	16.0
802.11ax80	MCS0	42	-7.2	0.2	-7.0	11.0	18.0
	MCS11	42	-7.4	0.8	-6.6	11.0	17.6


Company: Ezurio	Page 28 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047

Mode	Rate RU	Channel	Maximum Average PSD (dBm/1 MHz)	Duty Cycle Correction (dB)	Corrected Output Value (dBm/1 MHz)	Limit (dBm/1 MHz)	Margin (dB)
802.11ax20	MCS0 RU26	36	9.9	0.2	10.1	11.0	0.9
		40	10.3	0.2	10.5	11.0	0.5
		48	9.8	0.2	10.0	11.0	1.0
	MCS0 RU52	36	5.5	0.2	5.7	11.0	5.3
		40	6.2	0.2	6.4	11.0	4.6
		48	6.1	0.2	6.3	11.0	4.7
	MCS0 RU106	36	2.8	0.2	3.0	11.0	8.0
		40	3.2	0.2	3.4	11.0	7.6
		48	3.2	0.2	3.4	11.0	7.6
802.11ax40	MCS0 RU26	38	10.0	0.2	10.2	11.0	0.8
		46	9.4	0.2	9.6	11.0	1.4
	MCS0 RU52	38	5.6	0.2	5.8	11.0	5.2
		46	6.0	0.2	6.2	11.0	4.8
	MCS0 RU106	38	2.7	0.2	2.9	11.0	8.1
		46	3.6	0.2	3.8	11.0	7.2
	MCS0 RU242	38	-0.3	0.2	-0.1	11.0	11.1
46		0.2	0.2	0.4	11.0	10.6	
802.11ax80	MCS0 RU26	42	7.8	0.2	8.0	11.0	3.0
		42	5.0	0.2	5.2	11.0	5.8
	MCS0 RU106	42	2.2	0.2	2.4	11.0	8.6
		42	-1.0	0.2	-0.8	11.0	11.8
	MCS0 RU484	42	-3.8	0.2	-3.6	11.0	14.6

U-NII-1 Plots




802.11a | Channel 36 | 54 Mbps




802.11n20 | Channel 40 | MCS7




802.11ac20 | Channel 40 | MCS8



802.11ax20 | Channel 48 | MCS11




802.11n40 | Channel 38 | MCS7




802.11ac40 | Channel 38 | MCS0

Company: Ezurio	Page 30 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047




802.11ax40 | Channel 46 | MCS11




802.11ac80 | Channel 42 | MCS9




802.11ax80 | Channel 42 | MCS11



802.11ax20 | Channel 40 | MCS0 | RU26



802.11ax40 | Channel 46 | MCS0 | RU26



802.11ax80 | Channel 42 | MCS0 | RU26

Company: Ezurio	Page 31 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047


U-NII-2A Measurements

Mode	Rate	Channel	Maximum Average PSD (dBm/1 MHz)	Duty Cycle Correction (dB)	Corrected Output Value (dBm/1 MHz)	Limit (dBm/1 MHz)	Margin (dB)
802.11a	6 Mbps	52	4.8	-	4.8	11.0	6.2
		56	5.0	-	5.0	11.0	6.0
		64	4.7	-	4.7	11.0	6.3
	54 Mbps	52	4.8	0.4	5.2	11.0	5.8
		56	4.9	0.4	5.3	11.0	5.7
		64	4.6	0.4	5.0	11.0	6.0
802.11n20	MCS0	52	3.6	-	3.6	11.0	7.4
		56	3.8	-	3.8	11.0	7.2
		64	3.7	-	3.7	11.0	7.3
	MCS7	52	3.3	0.4	3.7	11.0	7.3
		56	3.7	0.4	4.1	11.0	6.9
		64	3.5	0.4	3.9	11.0	7.1
802.11ac20	MCS0	52	3.6	-	3.6	11.0	7.4
		56	3.8	-	3.8	11.0	7.2
		64	3.6	-	3.6	11.0	7.4
	MCS8	52	3.4	0.4	3.8	11.0	7.2
		56	3.7	0.4	4.1	11.0	6.9
		64	3.4	0.4	3.8	11.0	7.2
802.11ax20	MCS0	52	3.9	-	3.9	11.0	7.2
		56	3.7	-	3.7	11.0	7.3
		64	3.8	-	3.8	11.0	7.2
	MCS11	52	-0.9	0.5	-0.4	11.0	11.4
		56	-0.7	0.5	-0.2	11.0	11.2
		64	-0.6	0.5	-0.1	11.0	11.1
802.11n40	MCS0	54	-1.6	0.1	-1.5	11.0	12.5
		62	-1.5	0.1	-1.4	11.0	12.4
	MCS7	54	-1.9	0.6	-1.3	11.0	12.3
		62	-1.7	0.6	-1.1	11.0	12.1
802.11ac40	MCS0	54	0.6	0.1	0.7	11.0	10.3
		62	0.7	0.1	0.8	11.0	10.2
	MCS9	54	-1.4	0.7	-0.7	11.0	11.7
		62	-1.6	0.7	-0.9	11.0	11.9
802.11ax40	MCS0	54	-1.7	0.1	-1.6	11.0	12.6
		62	-1.2	0.1	-1.1	11.0	12.1
	MCS11	54	-3.7	0.7	-3.0	11.0	14.0
		62	-3.9	0.7	-3.2	11.0	14.2
802.11ac80	MCS0	58	-4.9	0.2	-4.7	11.0	15.7
	MCS9	58	-6.4	1.0	-5.4	11.0	16.4
802.11ax80	MCS0	58	-7.2	0.2	-7.0	11.0	18.0
	MCS11	58	-7.6	0.8	-6.8	11.0	17.8

Company: Ezurio	Page 32 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047


Mode	Rate RU	Channel	Maximum Average PSD (dBm/1 MHz)	Duty Cycle Correction (dB)	Corrected Output Value (dBm/1 MHz)	Limit (dBm/1 MHz)	Margin (dB)
802.11ax20	MCS0 RU26	52	9.1	0.2	9.3	11.0	1.7
		56	9.4	0.2	9.6	11.0	1.4
		64	9.4	0.2	9.6	11.0	1.4
	MCS0 RU52	52	5.8	0.2	6.0	11.0	5.0
		56	5.6	0.2	5.8	11.0	5.2
		64	5.8	0.2	6.0	11.0	5.0
	MCS0 RU106	52	3.0	0.2	3.2	11.0	7.8
		56	3.2	0.2	3.4	11.0	7.6
		64	3.3	0.2	3.5	11.0	7.5
802.11ax40	MCS0 RU26	54	9.4	0.2	9.6	11.0	1.5
		62	9.5	0.2	9.7	11.0	1.3
	MCS0 RU52	54	5.8	0.2	6.0	11.0	5.0
		62	5.9	0.2	6.1	11.0	5.0
	MCS0 RU106	54	2.7	0.2	2.9	11.0	8.1
		62	3.1	0.2	3.3	11.0	7.7
	MCS0 RU242	54	-0.2	0.2	0.1	11.0	11.0
62		-0.2	0.2	0.0	11.0	11.0	
802.11ax80	MCS0 RU26	58	7.9	0.2	8.1	11.0	2.9
		58	4.8	0.2	5.0	11.0	6.0
	MCS0 RU106	58	2.1	0.2	2.3	11.0	8.8
		58	-1.1	0.2	-0.9	11.0	11.9
	MCS0 RU484	58	-4.0	0.2	-3.8	11.0	14.8

U-NII-2A Plots




802.11a | Channel 52 | 6 Mbps

802.11n20 | Channel 64 | MCS7



802.11ac20 | Channel 52 | MCS8


802.11ax20 | Channel 52 | MCS11




802.11n40 | Channel 54 | MCS7

802.11ac40 | Channel 62 | MCS0


Company: Ezurio	Page 34 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047




802.11ax40 | Channel 62 | MCS11




802.11ac80 | Channel 58 | MCS9




802.11ax80 | Channel 58 | MCS11



802.11ax20 | Channel 52 | MCS0 | RU26



802.11ax40 | Channel 62 | MCS0 | RU26



802.11ax80 | Channel 58 | MCS0 | RU26

Company: Ezurio	Page 35 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047

6.1.4 Out-of-band Emissions

Operator	Anthony Smith Dylan Rosenfeldt	QA	Adam Hauke
Temperature	21.6°C-21.9°C 21.8°C-22.2°C	R.H. %	19.90%-41.10% 29.70%-38.0%
Test Date	02/29/2024-03/05/2024 04/05/2024-04/08/2024	Location	Conducted RF Bench
Requirement	15.407(b)(1) & (2) RSS-247 Clause 6.2.1 & 6.2.2	Method	ANSI C63.10 12.7

Limits: For transmitters operating in the 5.15-5.25 GHz band and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

15.209 Limits:

Frequency (MHz)	Quasi-Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Peak Limit (dBμV/m)
30-88	40.0	-	-
88-216	43.5	-	-
216-960	46.0	-	-
960-1000	54.0	-	-
1000-40000	-	54.0	74.0

Test Parameters

Frequency	30-40000 MHz	Setup	Antenna Port
RBW	1 MHz	VBW	3 MHz
Detector(s)	Peak and Average (RMS)		
Notes	Declared antenna gain for band edge – 4.4 dBi		
Example Calculations	Correction Factor = 20 log (1/D), where D is the duty cycle		

Instrumentation

Asset #	Description	Manufacturer	Model #	Serial #	Date	Due Date	Status
AA 960172	Cable	A.H. Systems, Inc.	SAC-26G-1	387	06/13/2023	06/12/2024	Active Verification
EE 960087	Analyzer – Spectrum	Agilent	N9010A	MY53400296	04/11/2023	04/11/2024	Active Calibration

Company: Ezurio	Page 36 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047

Input Power	120 VAC @ 60 Hz	Mode	5 GHz WLAN Tx
Frequency	5180-5320 MHz	Channel	See 2.9

U-NII-1 Measurements – Lower Band Edge

Mode	Rate	Channel	Measurement Type	Frequency (MHz)	Measurement (dBm)	Antenna Gain (dBi)	Duty Cycle Correction (dB)	Limit (dBm)	Margin (dB)
802.11a	6 Mbps	36	Peak	5147.5	-40.5	4.4	-	-27.0	9.1
		36	Average	5149.0	-50.2	4.4	-	-41.2	4.6
	54 Mbps	36	Peak	5148.2	-39.6	4.4	-	-27.0	8.2
		36	Average	5149.9	-50.9	4.4	0.4	-41.2	4.9
802.11n20	MCS0	36	Peak	5145.8	-38.1	4.4	-	-27.0	6.7
		36	Average	5148.7	-51.6	4.4	-	-41.2	6.0
	MCS7	36	Peak	5148.4	-40.7	4.4	-	-27.0	9.3
		36	Average	5149.1	-52.9	4.4	0.4	-41.2	6.9
802.11ac20	MCS0	36	Peak	5150.0	-39.4	4.4	-	-27.0	8.0
		36	Average	5147.9	-51.7	4.4	-	-41.2	6.1
	MCS8	36	Peak	5149.6	-40.1	4.4	-	-27.0	8.7
		36	Average	5149.4	-52.9	4.4	0.4	-41.2	6.9
802.11ax20	MCS0	36	Peak	5148.4	-34.4	4.4	-	-27.0	3.0
		36	Average	5149.0	-51.1	4.4	-	-41.2	5.5
	MCS11	36	Peak	5149.8	-50.2	4.4	-	-27.0	18.8
		36	Average	5150.0	-58.9	4.4	0.5	-41.2	12.8
802.11n40	MCS0	38	Peak	5148.6	-33.2	4.4	-	-27.0	1.8
		38	Average	5148.7	-51.0	4.4	0.1	-41.2	5.3
	MCS7	38	Peak	5144.4	-44.0	4.4	-	-27.0	12.6
		38	Average	5149.7	-53.4	4.4	0.6	-41.2	7.2
802.11ac40	MCS0	38	Peak	5145.4	-37.1	4.4	-	-27.0	5.7
		38	Average	5145.5	-49.0	4.4	0.1	-41.2	3.3
	MCS9	38	Peak	5145.6	-40.9	4.4	-	-27.0	9.5
		38	Average	5146.3	-53.0	4.4	0.7	-41.2	6.7
802.11ax40	MCS0	38	Peak	5144.8	-36.7	4.4	-	-27.0	5.3
		38	Average	5149.2	-48.3	4.4	0.1	-41.2	2.6
	MCS11	38	Peak	5149.7	-42.0	4.4	-	-27.0	10.6
		38	Average	5150.0	-56.3	4.4	0.7	-41.2	10.0
802.11ac80	MCS0	42	Peak	5140.9	-37.8	4.4	-	-27.0	6.4
		42	Average	5148.4	-48.9	4.4	0.2	-41.2	3.1
	MCS9	42	Peak	5145.5	-39.2	4.4	-	-27.0	7.8
		42	Average	5145.2	-50.3	4.4	1.0	-41.2	3.7
802.11ax80	MCS0	42	Peak	5134.8	-37.5	4.4	-	-27.0	6.1
		42	Average	5134.4	-49.7	4.4	0.2	-41.2	3.9
	MCS11	42	Peak	5143.6	-43.1	4.4	-	-27.0	11.7
		42	Average	5143.6	-54.0	4.4	0.8	-41.2	7.6

Company: Ezurio	Page 37 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047

Mode	Rate	Channel	Measurement Type	Frequency (MHz)	Measurement (dBm)	Antenna Gain (dBi)	Duty Cycle Correction (dB)	Limit (dBm)	Margin (dB)
802.11ax20	MCS0	36	Peak	5144.2	-45.0	4.4		-27.0	13.6
	RU26	36	Average	5148.5	-57.1	4.4		-41.2	11.5
	MCS0	36	Peak	5144.9	-46.4	4.4		-27.0	15.0
	RU52	36	Average	5149.5	-56.1	4.4		-41.2	10.5
	MCS0	36	Peak	5143.0	-46.1	4.4		-27.0	14.7
	RU106	36	Average	5146.1	-57.4	4.4		-41.2	11.8
802.11ax40	MCS0	38	Peak	5136.8	-38.8	4.4		-27.0	7.4
	RU26	38	Average	5135.7	-51.5	4.4	0.1	-41.2	5.8
	MCS0	38	Peak	5134.7	-43.8	4.4		-27.0	12.4
	RU52	38	Average	5149.7	-54.9	4.4	0.1	-41.2	9.2
	MCS0	38	Peak	5138.2	-40.7	4.4		-27.0	9.3
	RU106	38	Average	5140.5	-51.6	4.4	0.1	-41.2	5.9
	MCS0	38	Peak	5149.3	-42.4	4.4		-27.0	11.0
	RU242	38	Average	5146.4	-53.0	4.4	0.1	-41.2	7.3
802.11ax80	MCS0	42	Peak	5093.9	-38.9	4.4		-27.0	7.5
	RU26	42	Average	5096.2	-56.4	4.4	0.2	-41.2	10.6
	MCS0	42	Peak	5147.5	-42.7	4.4		-27.0	11.3
	RU52	42	Average	5142.1	-59.4	4.4	0.2	-41.2	13.6
	MCS0	42	Peak	5100.8	-43.1	4.4		-27.0	11.7
	RU106	42	Average	5098.7	-57.8	4.4	0.2	-41.2	12.0
	MCS0	42	Peak	5105.1	-46.7	4.4		-27.0	15.3
	RU242	42	Average	5148.8	-59.3	4.4	0.2	-41.2	13.5
	MCS0	42	Peak	5093.9	-38.9	4.4		-27.0	7.5
	RU484	42	Average	5096.2	-56.4	4.4	0.2	-41.2	10.6

Company: Ezurio	Page 38 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047


U-NII-2A Measurements – Upper Band Edge

Mode	Rate	Channel	Measurement Type	Frequency (MHz)	Measurement (dBm)	Antenna Gain (dBi)	Duty Cycle Correction (dB)	Limit (dBm)	Margin (dB)
802.11a	6 Mbps	64	Peak	5351.8	-42.7	4.4	-	-27.0	11.3
		64	Average	5350.1	-54.7	4.4	-	-41.2	9.1
	54 Mbps	64	Peak	5353.3	-44.1	4.4	-	-27.0	12.7
		64	Average	5350.0	-54.8	4.4	0.4	-41.2	8.8
802.11n20	MCS0	64	Peak	5350.1	-44.3	4.4	-	-27.0	12.9
		64	Average	5350.0	-55.4	4.4	-	-41.2	9.8
	MCS7	64	Peak	5358.5	-43.5	4.4	-	-27.0	12.1
		64	Average	5352.8	-55.3	4.4	0.4	-41.2	9.3
802.11ac20	MCS0	64	Peak	5350.4	-44.8	4.4	-	-27.0	13.4
		64	Average	5351.3	-55.0	4.4	-	-41.2	9.4
	MCS8	64	Peak	5351.4	-44.3	4.4	-	-27.0	12.9
		64	Average	5350.2	-55.2	4.4	0.4	-41.2	9.2
802.11ax20	MCS0	64	Peak	5352.0	-44.6	4.4	-	-27.0	13.2
		64	Average	5350.5	-54.6	4.4	-	-41.2	9.0
	MCS11	64	Peak	5350.2	-48.7	4.4	-	-27.0	17.3
		64	Average	5351.3	-59.6	4.4	0.5	-41.2	13.5
802.11n40	MCS0	62	Peak	5350.1	-35.2	4.4	-	-27.0	3.8
		62	Average	5350.7	-52.0	4.4	0.1	-41.2	6.3
	MCS7	62	Peak	5352.8	-43.0	4.4	-	-27.0	11.6
		62	Average	5351.1	-53.2	4.4	0.6	-41.2	7.0
802.11ac40	MCS0	62	Peak	5353.3	-38.5	4.4	-	-27.0	7.1
		62	Average	5350.1	-49.5	4.4	0.1	-41.2	3.8
	MCS9	62	Peak	5350.3	-43.4	4.4	-	-27.0	12.0
		62	Average	5351.1	-53.1	4.4	0.7	-41.2	6.7
802.11ax40	MCS0	62	Peak	5350.7	-36.4	4.4	-	-27.0	5.0
		62	Average	5350.1	-49.2	4.4	0.1	-41.2	3.5
	MCS11	62	Peak	5352.0	-40.0	4.4	-	-27.0	8.6
		62	Average	5352	-54.27	4.4	0.7	-41.2	8.0
802.11ac80	MCS0	58	Peak	5359.1	-38.6	4.4	-	-27.0	7.2
		58	Average	5351.7	-48.7	4.4	0.2	-41.2	2.9
	MCS9	58	Peak	5350.7	-40.6	4.4	-	-27.0	9.2
		58	Average	5353.9	-50.6	4.4	1.0	-41.2	4.0
802.11ax80	MCS0	58	Peak	5354.8	-35.6	4.4	-	-27.0	4.2
		58	Average	5354.8	-48.9	4.4	0.2	-41.2	3.1
	MCS11	58	Peak	5361.3	-42.3	4.4	-	-27.0	10.9
		58	Average	5354.7	-52.7	4.4	0.8	-41.2	6.3

Company: Ezurio	Page 39 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047


Mode	Rate	Channel	Measurement Type	Frequency (MHz)	Measurement (dBm)	Antenna Gain (dBi)	Duty Cycle Correction (dB)	Limit (dBm)	Margin (dB)
802.11ax20	MCS0	64	Peak	5360.5	-37.1	4.4		-27.0	5.7
	RU26	64	Average	5361.6	-53.6	4.4		-41.2	8.0
	MCS0	64	Peak	5356.3	-39.1	4.4		-27.0	7.7
	RU52	64	Average	5358.3	-55.9	4.4		-41.2	10.3
	MCS0	64	Peak	5352.4	-43.8	4.4		-27.0	12.4
	RU106	64	Average	5351.2	-56.1	4.4		-41.2	10.5
802.11ax40	MCS0	62	Peak	5351.2	-36.8	4.4		-27.0	5.4
	RU26	62	Average	5350.8	-53.0	4.4	0.1	-41.2	7.3
	MCS0	62	Peak	5356.4	-37.8	4.4		-27.0	6.4
	RU52	62	Average	5353.8	-50.7	4.4	0.1	-41.2	5.0
	MCS0	62	Peak	5354.9	-40.6	4.4		-27.0	9.2
	RU106	62	Average	5354.4	-54.1	4.4	0.1	-41.2	8.4
	MCS0	62	Peak	5352.1	-40.3	4.4		-27.0	8.9
	RU242	62	Average	5352.9	-53.7	4.4	0.1	-41.2	8.0
802.11ax80	MCS0	58	Peak	5389.7	-40.7	4.4		-27.0	9.3
	RU26	58	Average	5366.9	-55.0	4.4	0.2	-41.2	9.2
	MCS0	58	Peak	5350.6	-37.7	4.4		-27.0	6.3
	RU52	58	Average	5362.4	-53.5	4.4	0.2	-41.2	7.7
	MCS0	58	Peak	5373.9	-43.1	4.4		-27.0	11.7
	RU106	58	Average	5363.1	-56.3	4.4	0.2	-41.2	10.5
	MCS0	58	Peak	5354.9	-47.6	4.4		-27.0	16.2
	RU242	58	Average	5351.8	-57.5	4.4	0.2	-41.2	11.7
	MCS0	58	Peak	5351.1	-44.9	4.4		-27.0	13.5
	RU484	58	Average	5351.0	-55.6	4.4	0.2	-41.2	9.8

Worst Case Plots




802.11a | Channel 36 | 6 Mbps | Peak

802.11a | Channel 36 | 6 Mbps | Average



802.11n20 | Channel 36 | MCS7 | Peak


802.11n20 | Channel 36 | MCS7 | Average



802.11ac20 | Channel 36 | MCS0 | Peak

802.11ac20 | Channel 36 | MCS0 | Average


Company: Ezurio	Page 41 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047



802.11ax20 | Channel 36 | MCS0 | Peak




802.11ax20 | Channel 36 | MCS0 | Average




802.11n40 | Channel 38 | MCS0 | Peak



802.11ax20 | Channel 38 | MCS0 | Average




802.11ac40 | Channel 38 | MCS0 | Peak



802.11ac40 | Channel 38 | MCS0 | Average


Company: Ezurio	Page 42 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047



802.11ax40 | Channel 38 | MCS0 | Peak




802.11ax40 | Channel 38 | MCS0 | Average



802.11ac80 | Channel 58 | MCS0 | Peak



802.11ac80 | Channel 58 | MCS0 | Average




802.11ax80 | Channel 42 | MCS7 | Peak




802.11ax80 | Channel 42 | MCS7 | Average

Company: Ezurio		Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A	Page 43 of 62	Model: Sona NX611M
Quote: C-3768		Serial: 00047



802.11ax80 | Channel 58 | MCS0 | RU52 | Peak



802.11ax20 | Channel 64 | MCS0 | RU52 | Average

Company: Ezurio	Page 44 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047



6.1.5 Spurious Emissions In Restricted Bands

Operator	Anthony Smith	QA	Anthony Smith
Temperature	21.8°C	R.H. %	35.90%
Test Date	03/04/2024	Location	Conducted RF Bench
Requirement	15.407(b)(1),(2),(9), & 10 RSS-247 Clause 6.2.1 & 6.2.2 RSS-GEN	Method	ANSI C63.10 12.7

Limits: For transmitters operating in the 5.15-5.25 GHz band and 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

15.209 Limits:

Frequency (MHz)	Quasi-Peak Limit (dBμV/m)	Average Limit (dBμV/m)	Peak Limit (dBμV/m)
30-88	40.0	-	-
88-216	43.5	-	-
216-960	46.0	-	-
960-1000	54.0	-	-
1000-40000	-	54.0	74.0

Test Parameters

Frequency	30-40000 MHz	Setup	Terminated Method
RBW	1 MHz	VBW	3 MHz
Detector(s)	Peak	Settings	
Notes	Declared antenna gain– 4.4 dBi		
Example Calculations	Correction Factor = 20 log (1/D), where D is the duty cycle		

Instrumentation

Asset #	Description	Manufacturer	Model #	Serial #	Date	Due Date	Status
AA 960173	Cable	A.H. Systems, Inc.	SAC-26G-1	387	06/13/2023	06/12/2024	Active Verification
EE 960085	Analyzer – Spectrum	Agilent	N9010A	MY53400296	04/11/2023	04/11/2024	Active Calibration
AA 960161	Filter - Highpass 5 GHz	K&L Microwave	11SH10-8000	2	4/11/2023	4/11/2024	Active Calibration

Company: Ezurio	Page 45 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047


EUT Parameters

Input Power	120 VAC @ 60 Hz	Mode	5 GHz WLAN Tx
Frequency	5180-5320 MHz	Channel	36, 38, 40, 48, 52, 62

Table


Mode	Rate	Channel	Measurement Type	Frequency (MHz)	Measurement (dBm)	Antenna Gain (dBi)	Limit (dBm)	Margin (dB)
802.11a	6 Mbps	36	Peak	10360.5	-51.9	4.4	-27.0	20.5
		36	Average	-	-	-	-	-
802.11a	6 Mbps	40	Peak	10399.2	-47.7	4.4	-27.0	16.3
		40	Average	-	-	-	-	-
802.11a	6 Mbps	40	Peak	10399.9	-51.5	4.4	-27.0	20.1
		40	Average	-	-	-	-	-
802.11n	MCS0	40	Peak	10400.3	-50.3	4.4	-27.0	18.9
		40	Average	-	-	-	-	-
802.11ac20	MCS0	40	Peak	10398.5	-49.5	4.4	-27.0	18.1
		40	Average	-	-	-	-	-
802.11a	6 Mbps	64	Peak	10635.4	-55.0	4.4	-27.0	23.6
		64	Average	10640.0	-65.0	4.4	-41.2	19.4
802.11n	MCS0	64	Peak	10642.0	-57.1	4.4	-27.0	25.7
		64	Average	10639.6	-67.9	4.4	-41.2	22.3
802.11ac20	MCS0	64	Peak	10639.1	-56.8	4.4	-27.0	25.4
		64	Average	10641.4	-67.7	4.4	-41.2	22.1
802.11ax20	MCS0	64	Peak	10641.2	-57.1	4.4	-27.0	25.7
		64	Average	10640.5	-67.3	4.4	-41.2	21.7

Worst Case Plots




802.11a | Channel 36 | 6 Mbps | 30-1000 MHz

802.11a | Channel 36 | 6 Mbps | 1000-4000 MHz



802.11a | Channel 36 | 6 Mbps | 4000-8000 MHz

802.11a | Channel 36 | 6 Mbps | 8000-18000 MHz



802.11a | Channel 36 | 6 Mbps | 8000-40000 MHz

Company: Ezurio	Page 47 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047

6.1.6 Frequency Stability

Operator	Dylan Rosenfeldt	QA	Anthony Smith
Temperature	21.8°C	R.H. %	31.90%
Test Date	04/25/2024	Location	Conducted RF Bench
Requirement	15.407(g) RSS-GEN Clause 6.11	Method	ANSI C63.10 6.8

Test Parameters

Frequency	5170-5330 MHz	Voltage	4.3 VDC, 5 VDC, and 5.8 VDC
Detector(s)	Peak	Settings	Max Hold

Instrumentation

Asset #	Description	Manufacturer	Model #	Serial #	Date	Due Date	Status
AA 960173	Cable	A.H. Systems, Inc.	SAC-26G-1	387	06/13/2023	06/12/2024	Active Verification
EE 960088	Analyzer - EMI Receiver	Agilent	N9038A	MY51210138	4/10/2023	4/10/2024	Active Calibration

Table

Channel	Voltage (VDC)	Center Frequency (Hz)
36	5	5179997756
	4.3	5179997651
	5.8	5179997259
40	5	5199998064
	4.3	5199998120
	5.8	5199998148
48	5	5239998445
	4.3	5239998401
	5.8	5239998364
52	5	5259998398
	4.3	5259998377
	5.8	5259998438
56	5	5279998573
	4.3	5279998493
	5.8	5279998516
64	5	5319998861
	4.3	5319998707
	5.8	5319998626

6.2 Radiated Emissions

<p>Description of Measurement</p>	<p>The frequency spectrum is investigated for intentional and / or unintentional signals emanating from the EUT by use of a standardized test site and measurement antenna.</p> <p>The antenna, cable, pre-amp, and other necessary measurement system correction factors are loaded onto the EMI receiver / spectrum analyzer when the measurements are performed allowing the data to be gathered and reported as corrected values.</p> <p>The maximum emissions from the EUT are determined by turn-table azimuth rotation (360°) and scanning of the measurement antenna. Maximized levels are noted at degree values of azimuth, measurement antenna height, and measurement antenna polarity.</p>
<p>Example Calculations</p>	<p>Measurement (dBμV) + Cable factor (dB) + Other (dB) + Antenna Factor (dB/m) = Corrected Reading (dBμV/m)</p> <p>Margin (dB) = Limit (dBμV/m) - Corrected Reading (dBμV/m)</p> <p>Example at 4000 MHz: Reading = 40 dBμV + 3.4 dB + 0.9 dB + 6.5 dB/m = 50.8 dBμV/m Average Limit = 20 log (500) = 54 dBμV/m Margin = 54 dBμV/m - 50.8 dBμV/m = 3.2 dB</p>

Block Diagram



6.2.1 Spurious Radiated Emissions in the Restricted Bands

Operator	Mitchell Freund Nicole Sedmak Jon Dilley Zachary Brown	QA	Anthony Smith Adam Alger Adam Hauke Dylan Rosenfeldt
Temperature	23.2°C-25.1°C	R.H. %	21.30%-25.90%
Test Date	02/12/2024-04/03/2024	Location	Chamber 3 Chamber 5
Requirement	15.247 (b)(1),(2),(9) & (10) RSS-247 Clause 6.2.1 & 6.2.2 RSS-GEN Clause 8.9	Method	ANSI C63.10 12.7

Limits: For transmitters operating in the 5.15-5.25 GHzband and 5.25-5.35 GHzband: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.

15.209 Limits:

Frequency (MHz)	Quasi-Peak Limit (dBµV/m)	Average Limit (dBµV/m)	Peak Limit (dBµV/m)
30-88	40.0	-	-
88-216	43.5	-	-
216-960	46.0	-	-
960-1000	54.0	-	-
1000-40000	-	54.0	74.0

Test Parameters

Frequency	30-40000 MHz	Distance	3 m
Detector(s)	Peak Trac Peak and Average Final	Table height	150 cm
RBW	<1000 MHz – 120 kHz >1000 – 1 MHz	VBW	<1000 – 1.2 MHz >1000 – See 2.9

Instrumentation

Asset #	Description	Manufacturer	Model #	Serial #	Date	Due Date	Status
AA 960007	Antenna - Double Ridge Horn	EMCO	3115	9311-4138	8/10/2023	8/10/2024	Active Calibration
AA 960081	Antenna - Double Ridge Horn	EMCO	3115	6907	1/11/2024	1/11/2025	Active Calibration
AA 960158	Antenna - Double Ridge Horn	ETS Lindgren	3117	109300	2/7/2024	2/7/2025	Active Calibration
AA 960161	Filter - Highpass 5 GHz	K&L Microwave	11SH10-8000	2	4/11/2023	4/11/2024	Active Calibration

Company: Ezurio	Page 50 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047

AA 960163	Antenna - Log Periodic	A.H. Systems, Inc.	SAS-512-2	500	8/10/2023	8/10/2024	Active Calibration
AA 960217	Antenna - Biconical	A.H. Systems, Inc.	SAS-540	852	7/17/2023	7/17/2024	Active Calibration
AA 960220	Cable	A.H. Systems, Inc.	SAC-26G-6	552	2/16/2023	2/16/2025	Active Verification
AA 960221	Cable	A.H. Systems, Inc.	SAC-26G-6	524	6/13/2023	6/13/2024	Active Verification
EE 960085	Analyzer - EMI Receiver	Agilent	N9038A	MY51210148	4/27/2023	4/27/2024	Active Calibration
EE 960203	Analyzer - EMI Receiver	Keysight	N9038A	MY56400072	4/11/2023	4/11/2024	Active Calibration
LSC-300	Cable	Chamber 3 Emissions	-	-	1/5/2024	1/5/2025	Active Verification
LSC-500	Cable	Chamber 5 Emissions	-	-	1/8/2024	1/8/2025	Active Verification

EUT Parameters

Input Power	120 VAC @ 60 Hz	Mode	5 GHz WLAN Tx
EUT	X, Y, Z Plane Orientations Antenna ports terminated with 50 Ω SMA terminators	AE	HP Elitebook 840G1 Ezurio – SOM60 Development Kit
Notes	6000 MHz Emission from auxiliary equipment. Not a function of the EUT. No Spurious emissions observed 1000-40000 MHz. Only worst case EUT orientation reported.		

Radiated Spurious – 30-1000 MHz – All Modes

Frequency (MHz)	Antenna Polarity	Height (cm)	Azimuth (degree)	Quasi-Peak Reading (dBμV/m)	Quasi-Peak Limit (dBμV/m)	Margin (dB)
66.3	H	122	200	34.4	40.0	5.6
111.1	V	224	171	39.9	43.5	13.6
113.2	H	145	120	28.7	43.5	14.8
395.6	H	100	212	38.8	46.0	7.2
479.2	H	176	203	35.7	46.0	10.3

*The spurious signals detected do not depend on either the operating channel or the modulation mode

1000-40000 MHz – 802.11a

Band Edge

Rate	Channel	EUT Orientation	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBμV/m)	Limit (dBμV/m)	Margin (dB)
6 Mbps	36	X Plane	Peak	4766.9	Vertical	50.1	68.2	18.1
			Average	4651.3	Vertical	39.3	54.0	14.7
	64	X Plane	Peak	5442.8	Vertical	51.8	68.2	16.4
			Average	5394.8	Vertical	39.4	54.0	14.6
54 Mbps	36	X Plane	Peak	4931.9	Vertical	50.0	68.2	18.2
			Average	4506.0	Vertical	39.5	54.0	14.5
	64	X Plane	Peak	5458.3	Vertical	50.5	68.2	17.7
			Average	5403.9	Vertical	41.4	54.0	12.6

1000-40000 MHz – 802.11n20

Band Edge

Rate	Channel	EUT Orientation	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBμV/m)	Limit (dBμV/m)	Margin (dB)
MCS0	36	X Plane	Peak	5032.0	Vertical	51.0	68.2	17.2
			Average	4620.6	Vertical	39.2	54.0	14.8
	64	X Plane	Peak	5360.8	Vertical	50.6	68.2	17.6
			Average	5395.7	Vertical	39.3	54.0	14.7
MCS7	36	X Plane	Peak	5139.1	Vertical	50.6	68.2	17.6
			Average	4738.4	Vertical	41.3	54.0	12.7
	64	X Plane	Peak	5381.8	Vertical	50.8	68.2	17.4
			Average	5388.9	Vertical	41.4	54.0	12.6

1000-40000 MHz – 802.11ac20

Band Edge

Rate	Channel	EUT Orientation	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBμV/m)	Limit (dBμV/m)	Margin (dB)
MCS0	36	X Plane	Peak	5054.4	Vertical	50.3	68.2	17.9
			Average	4614.1	Vertical	39.3	54.0	14.7
	64	Z Plane	Peak	5368.4	Vertical	50.2	68.2	18.0
			Average	5416.9	Vertical	39.4	54.0	14.6
MCS8	36	X Plane	Peak	4813.4	Vertical	49.9	68.2	18.3
			Average	5130.9	Vertical	41.1	54.0	12.9
	64	Z Plane	Peak	5360.7	Vertical	51.2	68.2	17.0
			Average	5414.0	Vertical	41.5	54.0	12.5

1000-40000 MHz – 802.11ax20

Band Edge

Rate	Channel	EUT Orientation	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBμV/m)	Limit (dBμV/m)	Margin (dB)
MCS0	36	X Plane	Peak	4580.5	Vertical	49.6	68.2	18.6
			Average	4714.4	Vertical	39.5	54.0	14.5
	64	X Plane	Peak	5386.6	Vertical	50.4	68.2	17.8
			Average	5388.2	Vertical	39.7	54.0	14.3
MCS11	36	X Plane	Peak	4764.9	Vertical	50.8	68.2	17.4
			Average	4603.5	Vertical	41.5	54.0	12.5
	64	X Plane	Peak	5434.8	Vertical	50.4	68.2	17.8
			Average	5452.6	Vertical	42.0	54.0	12.0

1000-40000 MHz – 802.11n40

Band Edge

Rate	Channel	EUT Orientation	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBμV/m)	Limit (dBμV/m)	Margin (dB)
MCS0	38	X Plane	Peak	4569.5	Vertical	51.5	68.2	16.7
			Average	4607.9	Vertical	39.2	54.0	14.8
	62	Y Plane	Peak	5452.6	Vertical	42.0	54.0	12.0
			Average	5458.9	Horizontal	46.0	54.0	8.0
MCS7	38	X Plane	Peak	4747.0	Vertical	50.5	68.2	17.7
			Average	4629.9	Vertical	42.2	54.0	11.8
	62	Y Plane	Peak	5355.4	Horizontal	51.1	68.2	17.1
			Average	5419.2	Horizontal	41.8	54.0	12.2

1000-40000 MHz – 802.11ac40

Band Edge

Rate	Channel	EUT Orientation	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBμV/m)	Limit (dBμV/m)	Margin (dB)
MCS0	38	X Plane	Peak	4782.6	Vertical	50.7	68.2	17.5
			Average	4831.2	Vertical	39.8	54.0	14.2
	62	Y Plane	Peak	5396.2	Horizontal	50.5	68.2	17.7
			Average	5387.2	Horizontal	39.8	54.0	14.2
MCS9	38	X Plane	Peak	4664.2	Vertical	50.9	68.2	17.3
			Average	4667.0	Vertical	42.1	54.0	11.9
	62	Y Plane	Peak	5396.8	Horizontal	50.3	68.2	17.9
			Average	5369.5	Horizontal	41.9	54.0	12.1

1000-40000 MHz – 802.11ax40

Band Edge

Rate	Channel	EUT Orientation	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBμV/m)	Limit (dBμV/m)	Margin (dB)
MCS0	38	X Plane	Peak	4923.0	Vertical	50.1	68.2	18.1
			Average	4515.9	Vertical	40.0	54.0	14.0
	62	Y Plane	Peak	5384.2	Horizontal	50.3	68.2	17.9
			Average	5355.0	Horizontal	39.8	54.0	14.2
MCS11	38	X Plane	Peak	4739.5	Vertical	50.6	68.2	17.6
			Average	4730.6	Vertical	42.1	54.0	11.9
	62	Y Plane	Peak	5437.4	Horizontal	51.0	68.2	17.2
			Average	5453.0	Horizontal	42.3	54.0	11.7

1000-40000 MHz – 802.11ac80

Band Edge

Rate	Channel	EUT Orientation	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBμV/m)	Limit (dBμV/m)	Margin (dB)
MCS0	42	Z Plane	Peak	4656.8	Horizontal	51.2	68.2	17.0
			Average	4604.6	Horizontal	40.5	54.0	13.5
	58	Y Plane	Peak	5381.2	Vertical	51.8	68.2	16.4
			Average	5388.6	Vertical	39.8	54.0	14.2
MCS11	42	Z Plane	Peak	4905.2	Horizontal	51.6	68.2	16.6
			Average	4861.7	Horizontal	43.1	54.0	10.9
	58	Y Plane	Peak	5391.2	Vertical	51.2	68.2	17.0
			Average	5380.4	Vertical	42.3	54.0	11.7

1000-40000 MHz – 802.11ax80

Band Edge

Rate	Channel	EUT Orientation	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBμV/m)	Limit (dBμV/m)	Margin (dB)
MCS0	42	Z Plane	Peak	4893.8	Horizontal	51.1	68.2	17.1
			Average	4503.7	Horizontal	40.5	54.0	13.5
	58	X Plane	Peak	5383.5	Vertical	51.4	68.2	16.8
			Average	5365.8	Vertical	40.1	54.0	13.9
MCS11	42	Z Plane	Peak	4638.6	Horizontal	50.8	68.2	17.4
			Average	4560.1	Horizontal	42.4	54.0	11.6
	58	X Plane	Peak	5355.8	Vertical	51.7	68.2	16.5
			Average	5416.6	Vertical	42.4	54.0	11.6

1000-40000 MHz – 802.11ax20 – MU-RU – MCS0

Band Edge

EUT Orientation	Channel	RU	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBμV/m)	Limit (dBμV/m)	Margin (dB)
X Plane	36	0	Peak	4766.0	Vertical	48.1	68.2	20.1
			Average	5102.7	Vertical	38.1	54.0	15.9
		3	Peak	4310.8	Vertical	48.4	68.2	19.8
			Average	5079.1	Vertical	38.1	54.0	15.9
		8	Peak	4788.7	Vertical	48.4	68.2	19.8
			Average	5097.4	Vertical	38.1	54.0	15.9
Z Plane	64	0	Peak	5421.5	Vertical	51.3	68.2	17.1
			Average	5453.1	Vertical	39.6	54.0	14.4
		3	Peak	5467.3	Vertical	51.8	68.2	16.4
			Average	5354.2	Vertical	39.6	54.0	14.4
		8	Peak	5463.1	Vertical	51.5	68.2	16.7
			Average	5354.3	Vertical	39.6	54.0	14.4

1000-40000 MHz – 802.11ax40 – MU-RU – MCS0

Band Edge


EUT Orientation	Channel	RU	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBµV/m)	Limit (dBµV/m)	Margin (dB)
X Plane	38	0	Peak	4602.0	Vertical	51.1	68.2	17.1
			Average	4600.6	Vertical	39.9	54.0	14.1
		8	Peak	4641.6	Vertical	51.5	68.2	16.7
			Average	4599.6	Vertical	40.1	54.0	13.9
		17	Peak	4778.8	Vertical	51.0	68.2	17.2
			Average	4762.4	Vertical	39.9	54.0	14.1
Y Plane	62	0	Peak	5439.0	Horizontal	51.9	68.2	16.3
			Average	5352.1	Horizontal	40.1	54.0	13.9
		8	Peak	5375.8	Horizontal	51.4	68.2	16.9
			Average	5354.3	Horizontal	40.1	54.0	13.9
		17	Peak	5380.2	Horizontal	51.4	68.2	16.8
			Average	5357.1	Horizontal	40.1	54.0	13.9

1000-40000 MHz – 802.11ax80 – MU-RU – MCS0

Band Edge


EUT Orientation	Channel	RU	Measurement Type	Frequency (MHz)	Antenna Polarity	Measurement (dBµV/m)	Limit (dBµV/m)	Margin (dB)
Z Plane	42	0	Peak	4863.5	Horizontal	50.6	68.2	17.6
			Average	4594.7	Horizontal	40.6	54.0	13.4
		17	Peak	4584.2	Horizontal	51.7	68.2	16.5
			Average	4602.6	Horizontal	40.7	54.0	13.3
		36	Peak	4798.8	Horizontal	51.3	68.2	16.9
			Average	4611.6	Horizontal	40.6	54.0	13.4
Z Plane	58	0	Peak	5463.3	Vertical	52.8	68.2	15.4
			Average	5371.8	Vertical	40.3	54.0	13.7
		17	Peak	5377.1	Vertical	52.0	68.2	16.2
			Average	5386.7	Vertical	40.4	54.0	13.6
		36	Peak	5361.5	Vertical	53.1	68.2	15.1
			Average	5431.3	Vertical	40.4	54.0	13.6

Worst Case Plots




802.11a | Channel 36 | 6 Mbps | Y Plane
30-200 MHz | Vertical

802.11a | Channel 36 | 6 Mbps | Y Plane
200-1000 MHz | Vertical



802.11a | Channel 36 | 6 Mbps
1000-4000 MHz | Horizontal

802.11a | Channel 36 | 6 Mbps | Y Plane
4000-4500 MHz | Horizontal



802.11a | Channel 36 | 6 Mbps | Y Plane
5470-8000 MHz | Vertical

802.11a | Channel 36 | 6 Mbps | X Plane
8000-18000 MHz | Vertical

Company: Ezurio	Page 57 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047



802.11a | Channel 36 | 6 Mbps | Z Plane
18000-40000 MHz | Horizontal

Company: Ezurio	Page 58 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047

6.3 AC Mains Conducted Emissions

Description of Measurement

A line impedance stabilization network (LISN) or artificial mains network (AMN) allows the emissions of the power supply conductors to be measured while isolating the EUT from the supply mains.

The AMN, cable, and other necessary measurement system correction factors are loaded onto the EMI receiver when the measurements are performed. The data is gathered and reported as the corrected values.


Maximum emissions are determined with a peak max hold trace then measurements at a selection of the highest points are made with quasi-peak and average detectors. Results are recorded and compared to limit for each line. (e.g. line and neutral)

Example Calculations

Measurement (dBμV) + Cable factor (dB) + Other (dB) = Corrected Reading (dBμV)

Margin (dB) = Limit (dBμV) - Corrected Reading (dBμV)

Block Diagram



6.3.1 AC Mains Conducted Emissions

Operator	Jon Dillely	QA	Adam Hauke
Temperature	21.2°C	R.H. %	28.40%
Test Date	04/05/2024	Location	AC Conducted Bench
Requirement	15.407(b)(9) RSS-GEN	Method	ANSI C63.10 6.2

Limits:

Frequency (MHz)	Quasi-Peak Limit (dBµV)	Average Limit (dBµV)
0.15-0.5	66.0-56.0*	56.0-46.0*
0.5-5	56.0	46.0
5-30	60.0	50.0

*Decreases with the logarithm of the frequency.

Test Parameters

Frequency	0.15-30 MHz	Distance	40 cm from wall 80 cm from LISN
Detector(s)	Peak Trace Quasi-Peak, Average Final	Table height	80 cm
RBW	9 kHz	VBW	62 kHz
Notes	Channel has no effect on emission		

Instrumentation

Asset #	Description	Manufacturer	Model #	Serial #	Date	Due Date	Status
EE 960088	Analyzer - EMI Receiver	Agilent	N9038A	MY51210148	4/27/2023	4/27/2024	Active Calibration
EE 960089	LISN	COM-POWER	LI-215A	191943	4/10/2023	4/10/2024	Active Calibration
EE 960162	LISN	COM-POWER	LI-215A	191969	4/10/2023	4/10/2024	Active Calibration
LSC-212	Cable	Micro-Coax	UFB311A-0-1440-70U70U	64639 224071-001	1/8/2024	1/8/2025	Active Verification

EUT Parameters


Input Power	120 VAC @ 60 Hz	Mode	5 GHz WLAN Tx Channel 64
--------------------	-----------------	-------------	--------------------------

Company: Ezurio	Page 60 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047

Measurements

Line	Frequency (MHz)	Quasi Peak Reading (dB μ V)	Quasi-Peak Limit (dB μ V)	Quasi Peak Margin (dB)	Average Reading (dB μ V)	Average Limit (dB μ V)	Average Margin (dB)
1	0.159	64.5	65.5	1.0	36.9	55.5	18.6
1	0.532	47.1	56.0	8.9	25.0	46.0	21.0
1	12.080	34.6	60.0	25.4	23.4	50.0	26.6
2	0.163	63.7	65.3	1.6	36.3	55.3	19.0
2	0.500	44.2	56.0	11.8	24.4	46.0	21.6
2	12.098	28.9	60.0	31.1	15.4	50.0	34.6

Plots



Line 1

Line 2

Company: Ezurio	Page 61 of 62	Name: Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model: Sona NX611M
Quote: C-3768		Serial: 00047



7 REVISION HISTORY

Version	Date	Notes	Person
0.0	08/05/2024	Initial Draft	Adam Hauke
1.0	08/08/2024	Final Draft	Adam Hauke

END OF REPORT

Company: Ezurio	Page 62 of 62	Name:Module, SONA NX611 M.2 2230, 1 MHF
Report: TR3768-166-5G-UNII1-UNII2A		Model:Sona NX611M
Quote: C-3768		Serial:00047