

Certification of Compliance

CFR 47 Part 15 Subpart B

Test Report File No. : 06-IST-0004

Date of Issue : January 3, 2006

Model(s) : UNS-43LT2DN (Basic Model)
Kind of Product : LCoS PROJECTION TV
FCC ID : TU3UNS-43LT2DN
Applicant : Uneed System Inc.
Address : 4F, Songpa B/D, 122-5, Songpa-Dong, Songpa-Gu, Seoul,
Korea, (138-170)
Manufacturer : Uneed System Inc.
Address : 4F, Songpa B/D, 122-5, Songpa-Dong, Songpa-Gu, Seoul,
Korea, (138-170)

Test Result

☒ Positive

☐ Negative

Reviewed By

Approved By



S.J.CHO / EMC Group Manager



J.H.LEE / Chief

Comment(s)

- Investigations requested : Measurement to the relevant clauses of FCC rules and regulations Part 15 Subpart B - Unintentional Radiators, Class B.
- The test report with appendix consists of 19 pages.
- The test result only responds to the tested sample.
- It is not allowed to copy this report even partly without the allowance of IST EMC Laboratory.
- This equipment as for has been shown to be capable of continued compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in ANSI C63.4 2003.



TABLE OF CONTENTS

| | |
|--|---|
| Table of contents | 2 |
| Information of test laboratory, Environmental conditions, Power used, Product information | 3 |
| Descriptions of test | |
| Conducted Emission | 4 |
| Radiated Emission | 5 |
| Measurement Uncertainty Calculations | 6 |
| Equipment Under Test | 7 |
| Test Set-Up (Figure) | 8 |
| Summary | 9 |

■ Test Conditions and Data - Emissions

| | | | |
|----------------------------------|-----------------|------------|-------|
| ◆ Conducted Emissions | 0.15MHz - 30MHz | Applicable | |
| Test Conditions / Data and Plots | | | 10-12 |
| ◆ Radiated Emissions | 30MHz - 1GHz | Applicable | |
| Test Conditions / Data and Plots | | | 13-15 |

| | | |
|----------|---------------------------------------|-------|
| Appendix | A. The Photos of Test Setup | 16-17 |
| | B. The Photos of Equipment Under Test | 18-19 |

Note:

INFORMATIONS OF TEST LABORATORY

EMC LABORATORY of IST Co., Ltd. (*FCC Filing Lab.*)

San 21-8, Goan-Ri, Baekam-Myun, Yongin-City

Kyonggi-Do, 449-860, Korea

TEL : +82 31 333 4093

FAX : +82 31 333 4094

ENVIRONMENTAL CONDITIONS

Temperature 16.9 °C

Humidity 39.1 %

Atmospheric pressure 1010 mbar

POWER SUPPLY SYSTEM USED

Power supply system AC 120Vac, 60Hz (PC Power)

(Refer to the product information)

PRODUCT INFORMATION

**The Equipment Under Test(EUT) is LCoS PROJECTION TV of Uneed System Inc.
(FCC ID : TU3UNS-43LT2DN)**

Model Name : UNS-43LT2DN
Screen Size : Size - 43" Diagonal(109cm), 16:9
Brightness : >400cd/m²
Contrast : >350:1
Lamp Life Time : 10,000Hr. (Typical)
Power Consumption : 190W(3W standby)
Weight : Net(27kg), Gross(30.3kg)
Appearance(WxHxD) : Set(1,021 x 782 x 383), Carton Box(1,125 x 900 x 480)
Contrast Ratio - Typ. 600 : 1
Resolution : Prime - 1024 x 768 @60Hz
Standard - 640x480 @60Hz / 800x600 @60Hz
1024x768 @60Hz

- EMC suppression device is not used during the test.
- Please refer to user's manual.



DESCRIPTION OF TEST

Radiated Emissions:

The measurement was performed over the frequency range of 30MHz to 1GHz using antenna as the input transducer to a Spectrum analyzer or a Field Intensity Meter. The measurement was made with the detector set for "quasi-peak" within a bandwidth of 120KHz.

-Procedure of Test

Preliminary measurements were made at 3 meter using bi-conical and log-periodic antennas, and spectrum analyzer to determine the frequency producing the max. emission in anechoic chamber. Appropriate precaution was taken to ensure that all emission from the EUT were maximized and investigated. The system configuration, mode of operation, turn-table azimuth and height with respect to the antenna were noted for each frequency found. The spectrum was scanned from 30MHz to 1000MHz using S/B LogBicon antenna VL9160. Under 30MHz, magnetic loop antenna were used. Final measurements were made at open site with 3-meters test distance using the same antenna. The OATS have been verified in regular for its normalized site attenuation. The test equipment was placed on a wooden table. Sufficient time for the EUT, peripheral equipment, and test equipment was allowed in order for them to warm up to their normal operating condition. Each frequency found during pre-scan measurements was re-examined by manual. The detector function was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 120kHz or 1MHz depending on the frequency of type of signal. The EUT, peripheral equipment and interconnecting cables were re-configured to the set-up producing the max. emission for the frequency and were placed on top of a 0.8-meter high nonmetallic 1 x 1.5 meter table. The EUT, peripheral equipment, and interconnecting cables were re-arranged and manipulated to maximize each emission. The turntable containing the system was rotated; the antenna height was varied 1 to 4 meters and stopped at the azimuth or height producing the maximum emission. Each emission was maximized by: varying the mode of operation to the EUT and/or peripheral equipment and changing the polarity of the antenna, whichever determined the worst-case emission.



Measurement Uncertainty Calculations

The measurement uncertainties stated were calculated in accordance with the requirements of NIST Technical Note 1297 and NIS 81 (1994).

| Contribution (Conducted Emissions) | Probability Distribution | Uncertainty (\pm dB) |
|--|-----------------------------|-------------------------|
| | | 0.15-30MHz |
| Receiver Specification | Rectangular | 1.5 |
| LISN Coupling Specification | Rectangular | 1.5 |
| Cable and Input Attenuator Calibration | Normal (k=2) | 0.5 |
| Mismatch to Reciver | U-Shaped | -0.8 / +0.7 |
| System Repeatability | Normal (k=1) | 0.2 |
| Combined Standard Uncertainty | Normal (k=2) | -1.85 / +1.71 |
| Expanded Uncertainty U | Normal (k=2) | -3.7 / +3.42 |

$$U_{c,minus} = -1.85, U_{c,plus} = 1.71$$

$$U = -3.70 / +3.42 \text{ (k=2, 95.45\% confidence level)}$$

| Contribution (Radiated Emissions) | Probability Distribution | Uncertainties(\pm dB) |
|--------------------------------------|-----------------------------|--------------------------|
| | | 3 m |
| Antenna | | |
| Factor | Normal (k=2) | 0.9968 |
| Frequency Interpolation | Rectangular | 0.1039 |
| Height Variation | Rectangular | -2.6 / +1.5 |
| Directivity Difference | Rectangular | -1.0 / +0 |
| Phase Center Location | Rectangular | 1.0 |
| Cable Loss | Normal (k=2) | 0.5 |
| Receiver | | |
| Voltage Accuracy | Normal (k=2) | 2.0 |
| Pulse Response | Rectangular | 1.5 |
| Absolute Repetition Rate | Rectangular | 1.5 |
| Mismatch to Receiver | | |
| $ \Gamma_{\text{antenna}} = 0.33$ | U-Shaped | -1.0 / +0.9 |
| $ \Gamma_{\text{receiver}} = 0.33$ | | |
| System Repeatability | Std Deviation | 0.5 |
| Combined Standard Uncertainty | Normal | -2.6048 / 2.2775 |
| Expanded Uncertainty U | Normal (k=2) | -5.21 / +4.55 |

$$U_{c,minus} = -2.6048, U_{c,plus} = 2.2775$$

$$U = -5.21 / +4.55 \text{ (k=2, 95.45\% confidence level)}$$

Equipment Under Test

EUT Type :

- ☒ Table-Top. ☐ Floor-Standing.
☐ Table-Top and Floor-Standing (Combination).

Operation - mode of the E.U.T. :

The equipment under test was operated during the measurement under following conditions :

- ☐ Standby Mode
☒ Operational Condition : Scrolling H pattern on the Window
 ☒ 1024 x 768, 60Hz
 ☒ 800 x 600, 60Hz
 ☒ 640 x 480, 60Hz

Configuration of the equipment under test :

Following peripheral devices and interface cables were connected during the measurement :


| Equipment | Type | Brand | Serial No. | FCC Compliance Info. |
|----------------|-------------------|------------------|------------|----------------------|
| PC | HP Pavilion t328k | HP | SG23101784 | DoC |
| Keyboard(PS/2) | 5219 | HP | BN32403469 | E5XKB5209 |
| Mouse(PS/2) | N3+Optical | HP | K032925351 | DoC |
| Mouse(Serial) | M-M28 | Logitech | N/A | DZL210365 |
| Printer | A0302380 | Northern Telecom | 2516S60951 | BS46XU225C-L |

Connecting Interface Cables :


- Shielded monitor's signal cable(with two ferrite core) : 1.8 m
- Shielded Printer's signal cable(with two ferrite core) : 1.8 m
- Unshielded Mouse(Serial) cable(without ferrite core) : 1.6 m
- Unshielded Power cable(without ferrite core) : 1.8 m

Note :

Test Set-Up



Conducted Emissions



Radiated Emissions

TEST CONDITIONS AND DATA

Conducted Emissions

[Applicable]

◆ Test Equipment Used

| Model Name | Description | Manufacture | Calibration Date | Serial Number |
|------------|---------------|-----------------|------------------|---------------|
| ESH3 | Test Receiver | Rohde & Schwarz | Jul. 12, 2005 | 892108/018 |
| 3725/2 | LISN | EMCO | Jul. 12, 2005 | 9101-2068 |
| KNW-407 | LISN | Hyup-Rip | Jul. 12, 2005 | 8-883-10 |
| ESH3-Z2 | Pulse Limiter | Rohde & Schwarz | Jul. 12, 2005 | 357.8810.52 |

◆ Test Accessories Used

| Type | Manufacturer |
|-------------------|--------------|
| Aneroid Barometer | Sato |
| Hygrometer | Sato |

◆ Test Program Scrolling H pattern on the windows at 1024 x 768, 60Hz


◆ Test Date Dec 21, 2005

◆ Test Area Shielded Room (for Conducted Emission test)

Note : The equipment used is calibrated in regular for every year.

Conducted Emissions

Live Phase




MODEL NAME : UNS-43LT2DN
120Vac 60Hz PHASE : LIVE

| Freq. [MHz] | Measurement [dB μ V] | | Limit [dB μ V] | | Insertion Loss [dB] | Cable Loss [dB μ V] | Result [dB μ V] | | Margin [dB] | |
|----------------|-----------------------------|---------|-----------------------|---------|---------------------------|-------------------------------|------------------------|---------|----------------|---------|
| | Q-peak | Average | Q-peak | Average | | | Q-peak | Average | Q-peak | Average |
| 0.197 | 52.30 | 49.00 | 63.74 | 53.74 | 0.32 | 0.20 | 52.82 | 49.52 | 10.92 | 4.22 |
| 0.263 | 49.10 | 46.40 | 61.34 | 51.34 | 0.27 | 0.36 | 49.73 | 47.03 | 11.61 | 4.31 |
| 6.350 | 47.60 | 36.00 | 60.00 | 50.00 | 0.35 | 0.80 | 48.75 | 37.15 | 11.25 | 12.85 |
| 6.824 | 49.70 | 35.40 | 60.00 | 50.00 | 0.36 | 0.80 | 50.86 | 36.56 | 9.14 | 13.44 |

Note :

Conducted Emissions

Neutral Phase



MODEL NAME : UNS-43LT2DN
120Vac 60Hz PHASE : NRUTRAL

| Freq. [MHz] | Measurement [dB μ V] | | Limit [dB μ V] | | Insertion Loss [dB] | Cable Loss [dB μ V] | Result [dB μ V] | | Margin [dB] | |
|----------------|-----------------------------|---------|-----------------------|---------|---------------------------|-------------------------------|------------------------|---------|----------------|---------|
| | Q-peak | Average | Q-peak | Average | | | Q-peak | Average | Q-peak | Average |
| 0.197 | 49.10 | 48.80 | 63.74 | 53.74 | 0.30 | 0.20 | 49.60 | 49.30 | 14.14 | 4.44 |
| 0.263 | 45.70 | 46.00 | 61.34 | 51.34 | 0.26 | 0.36 | 46.32 | 46.62 | 15.02 | 4.72 |
| 0.611 | 44.00 | 37.60 | 56.00 | 46.00 | 0.22 | 0.60 | 44.82 | 38.42 | 11.18 | 7.58 |
| 0.814 | 44.20 | 37.80 | 56.00 | 46.00 | 0.23 | 0.60 | 45.03 | 38.63 | 10.97 | 7.37 |
| 1.152 | 44.70 | 37.40 | 56.00 | 46.00 | 0.24 | 0.62 | 45.56 | 38.26 | 10.44 | 7.74 |

Note :


Radiated Emissions
 (Disturbance Radiation)

[Applicable]

| | Freq. [MHz] | Reading [dBuV] | Antenna Factor [dB/m] | Cable Loss [dB] | Polar. [H/V] | Result [dBuV/m] | Limit [dBuV/m] | Margin [dB] |
|-----------------------|----------------|-------------------|-----------------------------|-----------------------|-----------------|--------------------|-------------------|----------------|
| 1024x768, 60Hz | 55.8 | 21.50 | 11.66 | 1.35 | V | 40.00 | 34.51 | 5.49 |
| | 210.0 | 26.60 | 9.40 | 3.66 | H | 43.50 | 39.66 | 3.84 |
| | 240.0 | 28.10 | 10.63 | 4.14 | H | 46.00 | 42.87 | 3.13 |
| | 300.0 | 24.80 | 12.61 | 4.80 | H | 46.00 | 42.21 | 3.79 |
| | 390.0 | 22.90 | 14.60 | 5.38 | H | 46.00 | 42.88 | 3.12 |
| | 420.0 | 21.60 | 15.45 | 5.70 | V | 46.00 | 42.75 | 3.25 |
| | 480.0 | 16.80 | 16.76 | 6.06 | V | 46.00 | 39.62 | 6.38 |
| | 741.8 | 13.40 | 21.42 | 7.95 | V | 46.00 | 42.77 | 3.23 |
| | 780.0 | 12.80 | 21.84 | 8.12 | V | 46.00 | 42.76 | 3.24 |
| | 900.0 | 10.70 | 22.96 | 9.00 | V | 46.00 | 42.66 | 3.34 |
| | 960.0 | 18.10 | 23.71 | 9.16 | V | 54.00 | 50.97 | 3.03 |
| 800x600, 60Hz | 210.0 | 23.90 | 9.40 | 3.66 | H | 43.50 | 36.96 | 6.54 |
| | 240.0 | 25.00 | 10.63 | 4.14 | H | 46.00 | 39.77 | 6.23 |
| | 300.0 | 20.30 | 12.61 | 4.80 | H | 46.00 | 37.71 | 8.29 |
| | 390.0 | 19.60 | 14.60 | 5.38 | H | 46.00 | 39.58 | 6.42 |
| | 420.0 | 20.10 | 15.45 | 5.70 | V | 46.00 | 41.25 | 4.75 |
| | 480.0 | 15.70 | 16.76 | 6.06 | V | 46.00 | 38.52 | 7.48 |
| | 741.8 | 11.00 | 21.42 | 7.95 | V | 46.00 | 40.37 | 5.63 |
| | 780.0 | 9.80 | 21.84 | 8.12 | V | 46.00 | 39.76 | 6.24 |
| | 900.0 | 8.90 | 22.96 | 9.00 | V | 46.00 | 40.86 | 5.14 |
| | 960.0 | 15.70 | 23.71 | 9.16 | V | 54.00 | 48.57 | 5.43 |
| | | | | | | | | |
| 640x480, 60Hz | 210.0 | 22.40 | 9.40 | 3.66 | H | 43.50 | 35.46 | 8.04 |
| | 240.0 | 23.90 | 10.63 | 4.14 | H | 46.00 | 38.67 | 7.33 |
| | 300.0 | 21.60 | 12.61 | 4.80 | H | 46.00 | 39.01 | 6.99 |
| | 390.0 | 18.50 | 14.60 | 5.38 | H | 46.00 | 38.48 | 7.52 |
| | 420.0 | 18.00 | 15.45 | 5.70 | V | 46.00 | 39.15 | 6.85 |
| | 480.0 | 14.50 | 16.76 | 6.06 | V | 46.00 | 37.32 | 8.68 |
| | 741.8 | 10.00 | 21.42 | 7.95 | V | 46.00 | 39.37 | 6.63 |
| | 780.0 | 8.90 | 21.84 | 8.12 | V | 46.00 | 38.86 | 7.14 |
| | 900.0 | 8.00 | 22.96 | 9.00 | V | 46.00 | 39.96 | 6.04 |
| | 960.0 | 13.80 | 23.71 | 9.16 | V | 54.00 | 46.67 | 7.33 |
| | | | | | | | | |

Note:

MEASUREMENT OF DISTURBANCE RADIATION



Appendix A. The Photos of Test Setup



Conducted Emissions - Front View



Conducted Emissions - Rear View

Appendix A. The Photos of Test Setup



Radiated Emissions - Front View



Radiated Emissions - Rear View

Appendix B. The Photos of Equipment Under Test



Front View



Rear View



19 of 19