



RF Exposure Report

(Part 0: SAR Char Evaluation)

FCC ID : UZ7TC58A1
Equipment : Touch Computer
Brand Name : Zebra
Model Name : TC58A1
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC 47 CFR Part 2 (2.1093)

We, SPORTON INTERNATIONAL INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL INC., the test report shall not be reproduced except in full.

Approved by: Cona Huang / Deputy Manager

Sporton International Inc.

No. 52, Huaya 1st Rd., Guishan Dist., Taoyuan City, Taiwan



Table of Contents

1. Introduction	4
2. Product Description	5
3. SAR Characterization.....	5
3.1 SAR design target and uncertainty.....	6
3.2 SAR Char Table	7



History of this test report

Report No.	Version	Description	Issued Date
FA222202C	01	Initial issue of report	Jun. 20, 2022

1. Introduction

The FCC RF exposure limit is defined based on time-averaged RF exposure. The product implements Qualcomm Smart Transmit feature which controls the instantaneous transmitting power for WWAN transmitter to ensure the product in compliance with FCC RF exposure limit over a defined time window, for SAR (transmit frequency $\leq 6\text{GHz}$) to control and manage transmitting power in real time and to ensure at all times the time-averaged RF exposure is compliant to the regulation requirement. Cannot operate without SAR characterization at the device level, beforehand.

This report describes the procedures for the SAR char and the parameters obtained from SAR characterization (referred to as SAR char respectively) will be used as input for Smart Transmit. Both SAR char will be entered via the Embedded File System (EFS) to enable the Smart Transmit Feature.

Terminologies in this report

P_{limit}	The time-averaged RF power which corresponds to SAR_design_target.
P_{max}	Maximum target power level
SAR_design_target:	The design target for SAR compliance. It should be less than regulatory power density limit to account for all device design related uncertainties.
SAR char	P_{limit} for all the technologies/bands for all applicable DSI

<Test Site Location>

The SAR measurement facilities used to collect data are within both Sporton Lab list below test site location are accredited to ISO 17025 by Taiwan Accreditation Foundation (TAF code: 1190 and 3786) and the FCC designation No. TW1190 and TW3786 under the FCC 2.948(e) by Mutual Recognition Agreement (MRA) in FCC test.

Test Site	EMC & Wireless Communications Laboratory		Wensan Laboratory		
Test Site Location	TW1190 No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan		TW3786 No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan		
Test Site No.	SAR01-HY	SAR03-HY	SAR08-HY	SAR09-HY	SAR15-HY
	SAR04-HY	SAR05-HY	SAR11-HY	SAR12-HY	
	SAR06-HY	SAR10-HY	SAR13-HY	SAR14-HY	



2. Product Description

Product Feature & Specification	
Equipment Name	Touch Computer
FCC ID	UZ7TC58A1
Wireless Technology and Frequency Range	GSM850: 824.2 MHz ~ 848.8 MHz GSM1900: 1850.2 MHz ~ 1909.8 MHz WCDMA Band II: 1850 MHz ~ 1910 MHz WCDMA Band IV: 1710 MHz ~ 1755 MHz WCDMA Band V: 824 MHz ~ 849 MHz LTE Band 2: 1850 MHz ~ 1910 MHz LTE Band 4: 1710 MHz ~ 1755 MHz LTE Band 5: 824 MHz ~ 849 MHz LTE Band 7: 2500 MHz ~ 2570 MHz LTE Band 12: 699 MHz ~ 716 MHz LTE Band 13: 777 MHz ~ 787 MHz LTE Band 14: 788 MHz ~ 798 MHz LTE Band 17: 704 MHz ~ 716 MHz LTE Band 25: 1850 MHz ~ 1915 MHz LTE Band 26: 814 MHz ~ 849 MHz LTE Band 38: 2570 MHz ~ 2620 MHz LTE Band 41: 2496 MHz ~ 2690 MHz LTE Band 48: 3550 MHz ~ 3700 MHz LTE Band 66: 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz 5G NR n2 : 1850 MHz ~ 1910 MHz 5G NR n5 : 824 MHz ~ 849 MHz 5G NR n7 : 2500 MHz ~ 2570 MHz 5G NR n12 : 699 MHz ~ 716 MHz 5G NR n13 : 777 MHz ~ 787 MHz 5G NR n14 : 788 MHz ~ 798 MHz 5G NR n25 : 1850 MHz ~ 1915 MHz 5G NR n26 : 814 MHz ~ 849 MHz 5G NR n38 : 2570 MHz ~ 2620 MHz 5G NR n41 : 2496 MHz ~ 2690 MHz 5G NR n48 : 3550 MHz ~ 3700 MHz 5G NR n66 : 1710 MHz ~ 1780 MHz 5G NR n71 : 663 MHz ~ 698 MHz 5G NR n77: 3700 MHz ~ 3980 MHz, 3450MHz ~ 3550MHz 5G NR n78: 3700 MHz ~ 3800 MHz, 3450MHz ~ 3650MHz WLAN 2.4 GHz Band: 2400 MHz ~ 2483.5 MHz WLAN 5.2 GHz Band: 5150 MHz ~ 5250 MHz WLAN 5.3 GHz Band: 5250 MHz ~ 5350 MHz WLAN 5.6 GHz Band: 5470 MHz ~ 5725 MHz WLAN 5.8 GHz Band: 5725 MHz ~ 5850 MHz WLAN 6E: 5925 MHz ~ 6425 MHz, 6425 MHz ~ 6525 MHz, 6525 MHz ~ 6875 MHz, 6875 MHz ~ 7125 MHz Bluetooth: 2400 MHz ~ 2483.5 MHz RFID : 13.56 MHz
Mode	GSM/GPRS/EGPRS RMC/AMR 12.2Kbps HSDPA HSUPA DC-HSDPA LTE: QPSK, 16QAM, 64QAM, 256QAM 5G NR: DFT-s-OFDM/CP-OFDM, Pi/2 BPSK/QPSK/16QAM/64QAM/256QAM WLAN: 802.11a/b/g/n/ac/ax HT20/HT40/VHT20/VHT40/VHT80/VHT160/HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE RFID: ASK

3. SAR Characterization

SAR char must be generated to cover all radio configurations and usage scenarios that the wireless device supports for operating at 6 GHz or below. It will then be used as input for Smart Transmit to control and manage RF exposure for f < 6 GHz.



3.1 SAR design target and uncertainty

<SAR design target and uncertainty>

The detail SAR design target relate to each exposure conditions pls refer to operation description

Band	Config	Antenna	Duty cycle	Device Uncertainty (dB)	Head 1g SAR design target DSI2	Hotspot 1g SAR design target DSI3	Body-worn 1g SAR design target DSI1	Extremity 10g SAR design target DSI1
GSM850 GPRS 4TX	TX1	4	50.00%	1.00	0.675	0.635	0.950	2.542
GSM1900 GPRS 4TX	TX1	4	50.00%	1.00	0.675	0.700	0.635	2.542
WCDMA B2	TX0	2	100.00%	1.00	0.675	0.635	0.635	2.542
WCDMA B4	TX0	2	100.00%	1.00	0.675	0.635	0.635	2.542
WCDMA B5	TX1	4	100.00%	1.00	0.675	0.635	0.635	2.542
LTE B7	TX1	6	100.00%	1.00	0.675	0.430	0.770	2.542
LTE B12/17	TX0	0	100.00%	1.00	0.675	0.635	0.635	2.542
LTE B13	TX0	0	100.00%	1.00	0.675	0.635	0.635	2.542
LTE B14	TX0	0	100.00%	1.00	0.675	0.635	0.635	2.542
LTE B25/2	TX0	2	100.00%	1.00	0.675	0.430	0.635	2.542
LTE B25/2	TX1	4	100.00%	1.00	0.675	0.635	0.675	2.542
LTE B26/5	TX1	4	100.00%	1.00	0.675	0.635	0.675	2.542
LTE B38 PC3	TX1	6	63.30%	1.00	0.675	0.430	0.950	2.542
LTE B41 PC3	TX1	6	63.30%	1.00	0.675	0.430	0.950	2.542
LTE B41 PC2	TX1	6	43.30%	1.00	0.675	0.950	0.950	2.542
LTE B48	TX1	11	63.30%	1.00	0.675	0.635	0.675	2.542
LTE B48	TX0	12	63.30%	1.00	0.675	0.635	0.635	2.542
LTE B66/4	TX1	4	100.00%	1.00	0.675	0.635	0.675	2.542
LTE B66/4	TX0	2	100.00%	1.00	0.675	0.635	0.635	2.542
LTE B71	TX0	0	100.00%	1.00	0.675	0.635	0.635	2.542
FR1 n7	TX1	6	100.00%	1.00	0.675	0.430	0.635	2.542
FR1 n12	TX0	0	100.00%	1.00	0.675	0.635	0.635	2.542
FR1 n13	TX0	0	100.00%	1.00	0.675	0.635	0.635	2.542
FR1 n14	TX0	0	100.00%	1.00	0.675	0.635	0.635	2.542
FR1 n25/n2	TX0	2	100.00%	1.00	0.675	0.635	0.635	2.542
FR1 n25/n2	TX1	4	100.00%	1.00	0.675	0.635	0.675	2.542
FR1 n26/n5	TX1	4	100.00%	1.00	0.675	0.635	0.635	2.542
FR1 n38 PC3	TX1	6	100.00%	1.00	0.675	0.430	0.675	2.542
FR1 n41 PC3	TX1	6	100.00%	1.00	0.675	0.430	0.675	2.542
FR1 n41/38 PC2	TX1	6	100.00%	1.00	0.675	0.430	0.675	2.542
FR1 n41 PC3	TX1	12	100.00%	1.00	0.675	0.430	0.675	2.542
FR1 n41 PC2	TX1	12	100.00%	1.00	0.675	0.430	0.675	2.542
FR1 n41 PC3	TX1	1	100.00%	1.00	0.675	0.635	0.675	2.542
FR1 n41 PC2	TX1	1	100.00%	1.00	0.675	0.635	0.675	2.542
FR1 n41 PC3	TX1	7	100.00%	1.00	0.675	0.635	0.675	2.542
FR1 n41 PC2	TX1	7	100.00%	1.00	0.675	0.635	0.675	2.542
FR1 n48	TX1	11	100.00%	1.00	0.675	0.675	0.675	2.542
FR1 n48	TX0	12	100.00%	1.00	0.675	0.635	0.635	2.542
FR1 n66	TX0	2	100.00%	1.00	0.675	0.635	0.635	2.542
FR1 n66	TX1	4	100.00%	1.00	0.675	0.675	0.675	2.542
FR1 n71	TX0	0	100.00%	1.00	0.675	0.635	0.635	2.542
FR1 n77/78 PC3	TX0	12	100.00%	1.00	0.380	0.430	0.480	2.542
FR1 n77/78 PC2	TX0	12	100.00%	1.00	0.380	0.430	0.480	2.542
FR1 n77/78 PC3	TX1	11	100.00%	1.00	0.380	0.340	0.480	2.542
FR1 n77/78 PC2	TX1	11	100.00%	1.00	0.380	0.340	0.480	2.542
FR1 n77/78 PC3	TX1	5	100.00%	1.00	0.380	0.635	0.380	2.542
FR1 n77/78 PC3	TX1	3	100.00%	1.00	0.380	0.380	0.380	2.542

To account for total uncertainty, SAR_design_target should be determined as:

$$SAR_{design_target} < SAR_{regulatory_limit} \times 10^{\frac{-total\ uncertainty}{10}}$$



3.2 SAR Char Table

<P_{limit} for supported technologies and bands (P_{limit} in EFS file)>

*P_{max} is used for RF tune up procedure. The maximum allowed output power is equal to P_{max} + 1dB uncertainty.

**All P_{limit} power levels entered in the Table correspond to average power levels after accounting for duty cycle in the case TDD modulation schemes (for e.g., GSM & LTE TDD & NR TDD).

The max allowed output power is the P_{limit} + 1dB device uncertainty, and if P_{limit} is higher than P_{max}, the device output power will be P_{max} instead.

Band	Config	Antenna	Duty cycle	Head Maximum Power DSI2	Hotspot Maximum Power DSI3)	Body-worn /Extremity Maximum Power DSI1	Pmax*
GSM850 GPRS 4TX**	TX1	4	50.00%	30.40	27.70	28.20	26.50
GSM1900 GPRS 4TX**	TX1	4	50.00%	30.50	22.00	25.70	23.50
WCDMA B2	TX0	2	100.00%	29.50	22.50	25.70	24.20
WCDMA B4	TX0	2	100.00%	34.80	24.80	25.90	24.20
WCDMA B5	TX1	4	100.00%	26.10	25.70	28.40	24.20
LTE B7	TX1	6	100.00%	29.30	21.30	24.60	23.00
LTE B12/17	TX0	0	100.00%	26.20	23.10	25.80	23.70
LTE B13	TX0	0	100.00%	27.70	25.20	24.00	23.50
LTE B14	TX0	0	100.00%	29.70	24.30	25.00	23.70
LTE B25/2	TX0	2	100.00%	30.40	23.30	25.80	24.20
LTE B25/2	TX1	4	100.00%	28.40	20.20	18.90	23.70
LTE B26/5	TX1	4	100.00%	27.00	25.60	27.10	24.20
LTE B38 PC3**	TX1	6	63.30%	29.80	25.80	27.70	21.50
LTE B41 PC3**	TX1	6	63.30%				22.00
LTE B41 PC2**	TX1	6	43.30%				22.40
LTE B48**	TX1	11	63.30%	16.70	17.30	24.60	19.00
LTE B48**	TX0	12	63.30%	18.80	18.90	22.80	19.00
LTE B66/4	TX1	4	100.00%	29.70	21.40	21.10	23.70
LTE B66/4	TX0	2	100.00%	34.10	23.20	24.80	24.20
LTE B71	TX0	0	100.00%	27.90	24.70	25.80	23.70
FR1 n7	TX1	6	100.00%	28.20	22.20	23.90	23.00
FR1 n12	TX0	0	100.00%	30.30	32.70	27.50	23.70
FR1 n13	TX0	0	100.00%	28.20	24.60	24.60	23.50
FR1 n14	TX0	0	100.00%	25.60	24.70	26.00	23.70
FR1 n25/n2	TX0	2	100.00%	31.40	23.40	28.00	24.20
FR1 n25/n2	TX1	4	100.00%	30.40	23.20	22.60	24.20
FR1 n26/n5	TX1	4	100.00%	28.20	26.60	27.00	24.20
FR1 n38 PC3	TX1	6	100.00%	29.90	20.90	25.20	23.50
FR1 n41 PC3	TX1	6	100.00%				24.00
FR1 n41/38 PC2	TX1	6	100.00%				26.00
FR1 n41 PC3	TX1	12	100.00%	23.50	23.50	24.90	24.00
FR1 n41 PC2	TX1	12	100.00%				26.00
FR1 n41 PC3	TX1	1	100.00%	20.40	23.40	29.20	24.00
FR1 n41 PC2	TX1	1	100.00%				26.00
FR1 n41 PC3	TX1	7	100.00%				22.10
FR1 n41 PC2	TX1	7	100.00%	26.00			
FR1 n48	TX1	11	100.00%	21.80	19.60	24.00	21.00
FR1 n48	TX0	12	100.00%	20.60	18.40	27.00	21.00
FR1 n66	TX0	2	100.00%	35.10	23.70	26.00	24.20
FR1 n66	TX1	4	100.00%	28.10	23.00	25.50	24.20
FR1 n71	TX0	0	100.00%	28.40	26.70	27.80	23.70
FR1 n77/78 PC3	TX0	12	100.00%	18.20	17.80	21.00	24.00
FR1 n77/78 PC2	TX0	12	100.00%	18.20	17.80	21.00	25.50
FR1 n77/78 PC3	TX1	11	100.00%	15.00	17.90	21.50	24.00
FR1 n77/78 PC2	TX1	11	100.00%	15.00	17.90	21.50	25.50
FR1 n77/78 PC3	TX1	5	100.00%	14.90	15.80	15.80	24.00
FR1 n77/78 PC3	TX1	3	100.00%	18.80	18.50	21.20	22.00