



FCC RADIO TEST REPORT

FCC ID : UZ7TC58A1
Equipment : Touch Computer
Brand Name : Zebra
Model Name : TC58A1
Applicant : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Manufacturer : Zebra Technologies Corporation
1 Zebra Plaza, Holtsville, NY 11742
Standard : FCC Part 15 Subpart E §15.407

The product was received on Feb. 21, 2022 and testing was performed from Mar. 02, 2022 to May 22, 2022. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	7
1.4 Testing Location	7
1.5 Applicable Standards.....	8
2 Test Configuration of Equipment Under Test	9
2.1 Carrier Frequency and Channel	9
2.2 Test Mode.....	10
2.3 Connection Diagram of Test System.....	14
2.4 Support Unit used in test configuration and system	15
2.5 EUT Operation Test Setup	15
2.6 Measurement Results Explanation Example.....	15
3 Test Result	16
3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement	16
3.2 Maximum Conducted Output Power Measurement	26
3.3 Power Spectral Density Measurement	30
3.4 Unwanted Emissions Measurement.....	38
3.5 AC Conducted Emission Measurement.....	44
3.6 Antenna Requirements	46
4 List of Measuring Equipment.....	49
5 Uncertainty of Evaluation	51
Appendix A. AC Conducted Emission Test Result	
Appendix B. Radiated Spurious Emission	
Appendix C. Radiated Spurious Emission Plots	
Appendix D. Duty Cycle Plots	
Appendix E. Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FR222202F	01	Initial issue of report	Jun. 17, 2022



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.1	15.403(i)	6dB & 26dB Bandwidth	Pass	-
3.1	2.1049	99% Occupied Bandwidth	Reporting only	-
3.2	15.407(a)	Maximum Conducted Output Power	Pass	-
3.3	15.407(a)	Power Spectral Density	Pass	-
3.4	15.407(b)	Unwanted Emissions	Pass	1.18 dB under the limit at 5647.000 MHz
3.5	15.207	AC Conducted Emission	Pass	17.51 dB under the limit at 0.258 MHz
3.6	15.203 15.407(a)	Antenna Requirement	Pass	-

Declaration of Conformity:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented in accordance with the regulation limits or requirements declared by manufacturers. It's means measurement values may risk exceeding the limit of regulation standards, if measurement uncertainty is include in test results.
2. The measurement uncertainty please refer to this report "Uncertainty of Evaluation".

Comments and Explanations:

The product specifications of the EUT presented in the report are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Wei Chen
Report Producer: Ruby Zou



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	Touch Computer
Brand Name	Zebra
Model Name	TC58A1
FCC ID	UZ7TC58A1
Sample 1	Lowell + Premium config
Sample 2	SE4720 + Base config
Sample 3	Lowell + Base config
EUT supports Radios application	GSM/EGPRS/WCDMA/HSPA/LTE/5G NR/NFC/GNSS WLAN 11a/b/g/n HT20/HT40 WLAN 11ac VHT20/VHT40/VHT80/VHT160 WLAN 11ax HE20/HE40/HE80/HE160 Bluetooth BR/EDR/LE
HW Version	EV3
SW Version	athena_A11_userdebug_GMS_RelKey_2022-02-22-2145_p roduct_SE
FW Version	FUSION_QA_4_1.0.0.013_R
MFD	19FEB22
EUT Stage	Identical Prototype

Remark: The above EUT's information was declared by manufacturer.

Specification of Accessories				
Adapter	Brand Name	Zebra	Part Number	PWR-WUA5V12W0US
Battery 1X	Brand Name	Zebra	Part Number	BT-000442-0020
Battery 1.5X	Brand Name	Zebra	Part Number	BT-000442-0820
USB TYPE A to TYPE C cable	Brand Name	Zebra	Part Number	CBL-TC5X-USBC2A-01
USB TYPE C to 3.5mm audio connector	Brand Name	Zebra	Part Number	ADP-USBC-35MM1-01
3.5mm Earphone	Brand Name	Zebra	Part Number	HDST-35MM-PTVP-01
USB TYPE C Earphone	Brand Name	Zebra	Part Number	HPST-USBC-PTT1-01
Headset Jumper	Brand Name	Zebra	Part Number	CBL-TC51-HDST35-01
Trigger Handle	Brand Name	Zebra	Part Number	TRG-NGTC5-ELEC-01
Soft Holster	Brand Name	Zebra	Part Number	SG-NGTC5TC7-HLSTR-01
TC53/TC58 RUGGED BOOT	Brand Name	Zebra	Part Number	SG-NGTC5EXO1-01



1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx/Rx Frequency Range	5745 MHz ~ 5825 MHz
Maximum Output Power to Antenna <CDD Mode>	MIMO <Ant. 9+8> 802.11a: 21.26 dBm / 0.1337 W 802.11n HT20: 20.71 dBm / 0.1178 W 802.11n HT40: 20.66 dBm / 0.1164 W 802.11ac VHT20: 20.71 dBm / 0.1178 W 802.11ac VHT40: 20.66 dBm / 0.1164 W 802.11ac VHT80: 19.71 dBm / 0.0935 W 802.11ax HE20: 20.81 dBm / 0.1205 W 802.11ax HE40: 20.76 dBm / 0.1191 W 802.11ax HE80: 19.81 dBm / 0.0958 W
Maximum Output Power to Antenna <TXBF Mode>	MIMO <Ant. 9+8> 802.11ax HE20: 20.56 dBm / 0.1138 W 802.11ax HE40: 20.66 dBm / 0.1164 W 802.11ax HE80: 17.66 dBm / 0.0583 W
99% Occupied Bandwidth <CDD Mode>	MIMO <Ant. 9> 802.11a: 24.72 MHz 802.11ax HE20: 19.23 MHz 802.11ax HE40: 38.26 MHz 802.11ax HE80: 77.32 MHz MIMO<Ant. 8> 802.11a: 26.32 MHz 802.11ax HE20: 19.18 MHz 802.11ax HE40: 38.46 MHz 802.11ax HE80: 77.32 MHz
99% Occupied Bandwidth <TXBF Mode>	MIMO <Ant. 9> 802.11ax HE20: 19.23 MHz 802.11ax HE40: 40.06 MHz 802.11ax HE80: 77.20 MHz MIMO <Ant. 8> 802.11ax HE20: 19.23 MHz 802.11ax HE40: 40.26 MHz 802.11ax HE80: 77.32 MHz
Antenna Type / Gain	<Ant. 9> : PIFA Antenna with gain 3.9 dBi <Ant. 8> : PIFA Antenna with gain 3.2 dBi



Product Specification is subject to this standard			
Type of Modulation	802.11a/n: OFDM (BPSK/QPSK/16QAM/64QAM) 802.11ac: OFDM (BPSK/QPSK/16QAM/64QAM/256QAM) 802.11ax: OFDMA (BPSK/QPSK/16QAM/64QAM/256QAM/ 1024QAM)		
Antenna Function Description		Ant. 9	Ant. 8
	802.11 a/n/ac/ax MIMO	V	V
	802.11 ax TXBF	V	V

Remark:

1. MIMO Ant. 9+8 is a calculated result from sum of the power MIMO Ant. 9 and MIMO Ant. 8.
2. The EUT's information above is declared by manufacturer. Please refer to Comments and Explanations in report summary.

1.3 Modification of EUT

No modifications made to the EUT during the testing.

1.4 Testing Location

Test Site	Sporton International Inc. EMC & Wireless Communications Laboratory
Test Site Location	No.52, Huaya 1st Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.) TEL: +886-3-327-3456 FAX: +886-3-328-4978
Test Site No.	Sporton Site No. CO05-HY (TAF Code: 1190)
Remark	The Conducted Emission test item subcontracted to Sporton International Inc. EMC & Wireless Communications Laboratory.

Note: The test site complies with ANSI C63.4 2014 requirement.

Test Site	Sporton International Inc. Wensan Laboratory
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855
Test Site No.	Sporton Site No. TH05-HY, 03CH16-HY

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW1190 and TW3786



1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart E
- ♦ FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ FCC KDB 662911 D01 Multiple Transmitter Output v02r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

- a. The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: conduction emission (150 kHz to 30 MHz), radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and find X plane as worst plane.
- b. AC power line Conducted Emission was tested under maximum output power.

2.1 Carrier Frequency and Channel

Frequency Band	Channel	Freq. (MHz)	Channel	Freq. (MHz)
5725-5850 MHz Band 4 (U-NII-3)	149	5745	157	5785
	151*	5755	159*	5795
	153	5765	161	5805
	155#	5775	165	5825

Note:

1. The above Frequency and Channel with "*" are 802.11n HT40 and 802.11ac VHT40 and 802.11ax HE40.
2. The above Frequency and Channel with "#" are 802.11ac VHT80 and 802.11ax HE80.



2.2 Test Mode

The 802.11ax mode is investigated among different tones, full resource units (RU), partial resource units. The partial RU has no higher power than full RU's, thus the full RU is chosen as main test configuration.

The CDD mode is chosen as worst case configuration for all test cases due to higher power than SISO mode.

The 802.11n/ac mode has no higher power and PSD than 802.11ax mode, thus the 802.11ax mode is chosen as main test configuration, and the 802.11n/ac mode is verified the power.

The final test modes consider the modulation and the worst data rates as shown in the table below.

CDD Mode

Modulation	Data Rate
802.11a	6 Mbps
802.11n HT20 (Covered by HE20)	MCS0
802.11n HT40 (Covered by HE40)	MCS0
802.11ac VHT20 (Covered by HE20)	MCS0
802.11ac VHT40 (Covered by HE40)	MCS0
802.11ac VHT80 (Covered by HE80)	MCS0
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0

TXBF Mode

Modulation	Data Rate
802.11ax HE20	MCS0
802.11ax HE40	MCS0
802.11ax HE80	MCS0



Test Cases	
AC Conducted Emission	Mode 1 : WCDMA Band V Link + WLAN (5GHz) Link + Bluetooth Link + NFC On + USB TYPE A to TYPE C cable (Charging with Adapter) + Battery 1X for Sample 2
Remark: For Radiated Test Cases, the tests were performed with Battery 1X and Sample 2.	

Ch. #		Band IV : 5725-5850 MHz			
		802.11a	802.11ax HE20	802.11ax HE40	802.11ax HE80
L	Low	149	149	151	-
M	Middle	157	157	-	155
H	High	165	165	159	-

Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

<CDD Mode>

MIMO <Ant. 9+8>

802.11a RF Output Power (dBm)										
Power vs. Channel			Power vs Data Rate							
Channel	Frequency (MHz)	Data Rate (bps)	Channel	Data Rate (bps)						
		6M		9M	12M	18M	24M	36M	48M	54M
CH 149	5745	21.16	CH 157	21.16	21.16	21.16	21.16	21.16	21.16	21.16
CH 157	5785	21.26								
CH 165	5825	21.16								



802.11ax HE20 RF Output Power (dBm)															
Power vs. Channel				Power vs Data Rate											
Channel	Frequency (MHz)	RU Config.	MCS Index	Channel	MCS Index										
			MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11
CH 149	5745	Full	20.66	CH 157	20.71	20.71	20.61	20.61	20.71	20.71	20.71	20.61	20.61	20.71	
CH 149	5745	26/0	10.86												
CH 149	5745	52/37	13.61												
CH 149	5745	106/53	16.86												
CH 157	5785	Full	20.81												
CH 157	5785	26/4	11.06												
CH 157	5785	52/38	14.06												
CH 157	5785	106/53	16.96												
CH 165	5825	Full	20.76												
CH 165	5825	26/8	11.17												
CH 165	5825	52/40	13.91												
CH 165	5825	106/54	16.96												

802.11ax HE40 RF Output Power (dBm)															
Power vs. Channel				Power vs Data Rate											
Channel	Frequency (MHz)	RU Config.	MCS Index	Channel	MCS Index										
			MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11
CH 151	5755	Full	20.76	CH 151	20.66	20.66	20.66	20.36	20.36	20.36	20.36	20.36	20.46	20.46	
CH 151	5755	242/61	17.81												
CH 159	5795	Full	20.71												
CH 159	5795	242/62	17.31												

802.11ax HE80 RF Output Power (dBm)															
Power vs. Channel				Power vs Data Rate											
Channel	Frequency (MHz)	RU Config.	MCS Index	Channel	MCS Index										
			MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11
CH 155	5775	Full	19.81	CH 155	19.71	19.71	19.71	19.71	19.71	19.71	19.71	19.71	19.71	19.71	
CH 155	5775	484/65	16.97												
CH 155	5775	484/66	16.81												



<TXBF Mode>

MIMO <Ant. 9+8>


802.11ax HE20 RF Output Power (dBm)															
Power vs. Channel				Power vs Data Rate											
Channel	Frequency (MHz)	RU Config.	MCS Index	Channel	MCS Index										
			MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11
CH 149	5745	Full	20.46	CH 157	20.46	20.46	20.46	20.36	20.36	20.36	20.26	20.26	20.16	20.26	20.36
CH 157	5785	Full	20.51												
CH 165	5825	Full	20.56												

802.11ax HE40 RF Output Power (dBm)															
Power vs. Channel				Power vs Data Rate											
Channel	Frequency (MHz)	RU Config.	MCS Index	Channel	MCS Index										
			MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11
CH 151	5755	Full	20.66	CH 151	20.56	20.56	20.46	20.46	20.46	20.36	20.36	20.46	20.56	20.56	20.56
CH 159	5795	Full	20.46												


802.11ax HE80 RF Output Power (dBm)															
Power vs. Channel				Power vs Data Rate											
Channel	Frequency (MHz)	RU Config.	MCS Index	Channel	MCS Index										
			MCS0		MCS1	MCS2	MCS3	MCS4	MCS5	MCS6	MCS7	MCS8	MCS9	MCS10	MCS11
CH 155	5775	Full	17.66	CH 155	17.56	17.56	17.46	17.46	17.46	17.36	17.46	17.36	17.26	17.36	17.46

2.3 Connection Diagram of Test System

<AC Conducted Emission Mode>



<WLAN Tx Mode>



2.4 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model Name	FCC ID	Data Cable	Power Cord
1.	System Simulator	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8m
2.	Bluetooth Earphone	Sony Ericsson	MW600	PY700A2029	N/A	N/A
3.	WLAN AP	ASUS	RT-AC66U	MSQ-RTAC66U	N/A	Unshielded, 1.8m
4.	Notebook	Dell	Latitude 3400	FCC DoC	N/A	AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m
5.	SD Card	SanDisk	MicroSD HC	FCC DoC	N/A	N/A

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT v4.0 version 4.0.00175.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.

For TXBF mode, the modulation modes and data rates manipulated by the command lines in the engineering program made the EUT link to another EUT by power under the normal operation. The “Magic iPerf Ver.1.0” software tool was used to enable the EUT to transmit signals continuously.

2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example :

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

$$\begin{aligned}
 \text{Offset(dB)} &= \text{RF cable loss(dB)} + \text{attenuator factor(dB)}. \\
 &= 4.2 + 10 = 14.2 \text{ (dB)}
 \end{aligned}$$

3 Test Result

3.1 6dB and 26dB and 99% Occupied Bandwidth Measurement

3.1.1 Description of 6dB and 26dB and 99% Occupied Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.

26dB and 99% Occupied bandwidth are reporting only.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section C) Emission bandwidth for the band 5.725-5.85 GHz
2. Set RBW = 100 kHz.
3. Set the VBW $\geq 3 \times$ RBW.
4. Detector = Peak.
5. Trace mode = max hold
6. Measure the maximum width of the emission that is 6 dB down from the peak of the emission.
7. Measure and record the results in the test report.

3.1.4 Test Setup





3.1.5 Test Result of 6dB and 26dB and 99% Occupied Bandwidth

Test Engineer :	Junyu Jhou and Hank Hsu	Temperature :	20.1~23.8°C
		Relative Humidity :	55.7~65.6%


<CDD Modes>

Band IV MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
					Ant 9	Ant 8	Ant 9	Ant 8	Ant 9	Ant 8		
11a	6Mbps	2	149	5745	19.23	24.33	43.03	44.68	16.40	16.45	0.5	Pass
11a	6Mbps	2	157	5785	24.72	26.32	46.88	47.67	16.40	16.45	0.5	Pass
11a	6Mbps	2	165	5825	17.48	24.33	36.39	49.72	16.40	16.40	0.5	Pass

Band IV MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Ant 9	Ant 8	Ant 9	Ant 8	Ant 9	Ant 8		
HE20	MCS0	2	149	5745	Full	19.18	19.13	32.23	28.90	19.05	18.95	0.5	Pass
HE20	MCS0	2	157	5785	Full	19.23	19.18	33.00	30.59	18.90	19.00	0.5	Pass
HE20	MCS0	2	165	5825	Full	19.13	19.18	23.19	29.67	18.85	18.95	0.5	Pass
HE40	MCS0	2	151	5755	Full	38.16	38.46	41.04	54.90	37.98	37.26	0.5	Pass
HE40	MCS0	2	159	5795	Full	38.26	38.26	40.86	40.68	37.98	37.80	0.5	Pass
HE80	MCS0	2	155	5775	Full	77.32	77.32	83.68	86.40	78.08	77.28	0.5	Pass




<802.11a>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11ax HE20>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11ax HE40>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<802.11ax HE80>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




Test Engineer :	Junyu Jhou	Temperature :	20.9~22.1°C
		Relative Humidity :	51.3~65.3%

<TXBF Modes>

Band IV MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	99% Bandwidth (MHz)		26dB Bandwidth (MHz)		6 dB Bandwidth (MHz)		6 dB Bandwidth Min. Limit (MHz)	Pass/Fail
						Ant 9	Ant 8	Ant 9	Ant 8	Ant 9	Ant 8		
HE20	MCS0	2	149	5745	Full	19.03	18.98	23.55	22.30	18.65	18.60	0.5	Pass
HE20	MCS0	2	157	5785	Full	19.23	19.23	35.00	31.20	19.20	19.20	0.5	Pass
HE20	MCS0	2	165	5825	Full	19.03	18.98	30.35	21.85	18.90	18.80	0.5	Pass
HE40	MCS0	2	151	5755	Full	39.46	39.16	73.90	74.68	38.34	38.34	0.5	Pass
HE40	MCS0	2	159	5795	Full	40.06	40.26	71.98	84.85	38.34	38.43	0.5	Pass
HE80	MCS0	2	155	5775	Full	77.20	77.32	84.16	83.52	77.60	76.16	0.5	Pass



<802.11ax HE20>




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11ax HE40>

6dB Bandwidth




Date: 31.MAR.2022 03:59:07

26dB Bandwidth



Date: 31.MAR.2022 04:03:22

99% Occupied Bandwidth




Date: 31.MAR.2022 04:00:47

NA

Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



<802.11ax HE80>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.



3.2 Maximum Conducted Output Power Measurement

3.2.1 Limit of Maximum Conducted Output Power

For the band 5.725–5.85 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

<CDD Modes>

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter.
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01


<TXBF Modes>

The testing follows Method PM-G of FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01 for TXBF modes.

Method PM-G (Measurement using a gated RF average power meter):

1. Measurement is performed using a wideband RF power meter.
2. The EUT is configured to transmit at its maximum power control level.
3. Measure the average power of the transmitter
4. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.
5. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

3.2.4 Test Setup



3.2.5 Test Result of Maximum Conducted Output Power

Test Engineer :	Junyu Jhou and Hank Hsu	Temperature :	20.1~23.8°C
		Relative Humidity :	55.7~65.6%

<CDD Modes>

Band IV MIMO												
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
					Ant 9	Ant 8	SUM	Ant 9	Ant 8	Ant 9	Ant 8	
11a	6Mbps	2	149	5745	18.20	18.10	21.16	30.00		3.90	Pass	
11a	6Mbps	2	157	5785	18.30	18.20	21.26	30.00		3.90	Pass	
11a	6Mbps	2	165	5825	18.10	18.20	21.16	30.00		3.90	Pass	
HT20	MCS0	2	149	5745	17.60	17.50	20.56	30.00		3.90	Pass	
HT20	MCS0	2	157	5785	17.80	17.60	20.71	30.00		3.90	Pass	
HT20	MCS0	2	165	5825	17.70	17.60	20.66	30.00		3.90	Pass	
HT40	MCS0	2	151	5755	17.70	17.60	20.66	30.00		3.90	Pass	
HT40	MCS0	2	159	5795	17.80	17.40	20.61	30.00		3.90	Pass	
VHT20	MCS0	2	149	5745	17.60	17.50	20.56	30.00		3.90	Pass	
VHT20	MCS0	2	157	5785	17.80	17.60	20.71	30.00		3.90	Pass	
VHT20	MCS0	2	165	5825	17.70	17.60	20.66	30.00		3.90	Pass	
VHT40	MCS0	2	151	5755	17.70	17.60	20.66	30.00		3.90	Pass	
VHT40	MCS0	2	159	5795	17.80	17.40	20.61	30.00		3.90	Pass	
VHT80	MCS0	2	155	5775	16.80	16.60	19.71	30.00		3.90	Pass	



<802.11 ax Mode>

Band IV MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 9	Ant 8	SUM	Ant 9	Ant 8	Ant 9	Ant 8	
HE20	MCS0	2	149	5745	Full	17.70	17.60	20.66	30.00		3.90		Pass
HE20	MCS0	2	149	5745	26/0	7.70	8.00	10.86	30.00		3.90		Pass
HE20	MCS0	2	149	5745	52/37	10.40	10.80	13.61	30.00		3.90		Pass
HE20	MCS0	2	149	5745	106/53	13.80	13.90	16.86	30.00		3.90		Pass
HE20	MCS0	2	157	5785	Full	17.90	17.70	20.81	30.00		3.90		Pass
HE20	MCS0	2	157	5785	26/4	8.00	8.10	11.06	30.00		3.90		Pass
HE20	MCS0	2	157	5785	52/38	11.20	10.90	14.06	30.00		3.90		Pass
HE20	MCS0	2	157	5785	106/53	14.00	13.90	16.96	30.00		3.90		Pass
HE20	MCS0	2	165	5825	Full	17.80	17.70	20.76	30.00		3.90		Pass
HE20	MCS0	2	165	5825	26/8	8.40	7.90	11.17	30.00		3.90		Pass
HE20	MCS0	2	165	5825	52/40	10.90	10.90	13.91	30.00		3.90		Pass
HE20	MCS0	2	165	5825	106/54	13.80	14.10	16.96	30.00		3.90		Pass
HE40	MCS0	2	151	5755	Full	17.80	17.70	20.76	30.00		3.90		Pass
HE40	MCS0	2	151	5755	242/61	14.90	14.70	17.81	30.00		3.90		Pass
HE40	MCS0	2	159	5795	Full	17.90	17.50	20.71	30.00		3.90		Pass
HE40	MCS0	2	159	5795	242/62	14.30	14.30	17.31	30.00		3.90		Pass
HE80	MCS0	2	155	5775	Full	16.90	16.70	19.81	30.00		3.90		Pass
HE80	MCS0	2	155	5775	484/65	14.20	13.70	16.97	30.00		3.90		Pass
HE80	MCS0	2	155	5775	484/66	13.90	13.70	16.81	30.00		3.90		Pass



Test Engineer :	Junyu Jhou	Temperature :	20.9~22.1°C
		Relative Humidity :	51.3~65.3%

<TXBF Modes>

Band IV MIMO													
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Average Conducted Power (dBm)			FCC Conducted Power Limit (dBm)		DG (dBi)		Pass/Fail
						Ant 9	Ant 8	SUM	Ant 9	Ant 8	Ant 9	Ant 8	
HE20	MCS0	2	149	5745	Full	17.40	17.50	20.46	29.43		6.57		Pass
HE20	MCS0	2	157	5785	Full	17.40	17.60	20.51	29.43		6.57		Pass
HE20	MCS0	2	165	5825	Full	17.50	17.60	20.56	29.43		6.57		Pass
HE40	MCS0	2	151	5755	Full	17.70	17.60	20.66	29.43		6.57		Pass
HE40	MCS0	2	159	5795	Full	17.50	17.40	20.46	29.43		6.57		Pass
HE80	MCS0	2	155	5775	Full	14.50	14.80	17.66	29.43		6.57		Pass



3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

For the band 5.725–5.85 GHz, the maximum power spectral density shall not exceed 30 dBm in any 500-kHz band.

If transmitting antennas of directional gain greater than 6 dBi are used, the peak output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section F) Maximum power spectral density.

<CDD Modes>

Method SA-2

(trace averaging across on and off times of the EUT transmissions, followed by duty cycle correction).

- Measure the duty cycle.
- Set span to encompass the entire emission bandwidth (EBW) of the signal.
- Set RBW = 300kHz.
- Set VBW \geq 1 MHz.
- Add $10 \log(500 \text{ kHz/RBW})$ to the measured result, whereas RBW (<500 kHz) is the reduced resolution bandwidth of the spectrum analyzer set during measurement
- Number of points in sweep $\geq 2 \text{ Span} / \text{RBW}$.
- Sweep time = auto.
- Detector = RMS
- Trace average at least 100 traces in power averaging mode.
- Add $10 \log(1/x)$, where x is the duty cycle, to the measured power in order to compute the average power during the actual transmission times. For example, add $10 \log(1/0.25) = 6 \text{ dB}$ if the duty cycle is 25 percent.


<TXBF Modes>**# Method SA-3 #**

(power averaging (rms) detection with max hold):

- Set span to encompass the entire emission bandwidth (EBW) of the signal.
 - Set RBW = 300 kHz.
 - Set VBW \geq 1 MHz.
 - Number of points in sweep \geq 2 Span / RBW.
 - Sweep time \leq (number of points in sweep) \times T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
 - Detector = power averaging (rms).
 - Trace mode = max hold.
 - Allow max hold to run for at least 60 seconds, or longer as needed to allow the trace to stabilize.
1. The RF output of EUT is connected to the spectrum analyzer by a low loss cable.
 2. Each plot has already offset with cable loss, and attenuator loss. Measure the PPSD and record it.
 3. For MIMO mode, calculation method follows FCC KDB 662911 D01 Multiple Transmitter Output v02r01.

Method (c): Measure and add $10 \log(N_{ANT})$ dB.

With this technique, spectrum measurements are performed at each output of the device, but rather than summing the spectra or the spectral peaks across the outputs, the quantity $10 \log(N_{ANT})$ dB is added to each spectrum value before comparing to the emission limit. The addition of $10 \log(N_{ANT})$ dB serves to apportion the emission limit among the N_{ANT} outputs so that each output is permitted to contribute no more than $1/N_{ANT}^{th}$ of the PSD limit.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density


Test Engineer :	Junyu Zhou and Hank Hsu	Temperature :	20.1~23.8°C
		Relative Humidity :	55.7~65.6%

<CDD Modes>

Band IV MIMO																
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
					Ant 9	Ant 8	Ant 9	Ant 8	Ant 9	Ant 8	SUM	Ant 9	Ant 8	Ant 9	Ant 8	
11a	6Mbps	2	149	5745	0.04	0.04	2.22	3.70	3.39	6.71	29.43	6.57	Pass			
11a	6Mbps	2	157	5785	0.04	0.04	2.22	3.71	3.24	6.72	29.43	6.57	Pass			
11a	6Mbps	2	165	5825	0.04	0.04	2.22	3.79	3.43	6.80	29.43	6.57	Pass			

Note: PSD Sum = Max PSD(Ant. 9, Ant. 8) + 10 log (n)

<802.11a>





<802.11ax Mode>

Band IV MIMO																	
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	Duty Factor (dB)		10log (500kHz /RBW) Factor (dB)		Average Power Density with Duty Factor (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
						Ant 9	Ant 8	Ant 9	Ant 8	Ant 9	Ant 8	SUM	Ant 8	Ant 9	Ant 8	Ant 9	
HE20	MCS0	2	149	5745	Full	0.32	0.28	2.22	2.58	2.25	5.59	29.43	6.57	Pass			
HE20	MCS0	2	149	5745	26/0	0.32	0.28	2.22	1.94	1.88	4.95	29.43	6.57	Pass			
HE20	MCS0	2	149	5745	52/37	0.32	0.28	2.22	1.52	1.77	4.78	29.43	6.57	Pass			
HE20	MCS0	2	149	5745	106/53	0.32	0.28	2.22	2.06	1.94	5.07	29.43	6.57	Pass			
HE20	MCS0	2	157	5785	Full	0.32	0.28	2.22	2.59	2.23	5.60	29.43	6.57	Pass			
HE20	MCS0	2	157	5785	26/4	0.32	0.28	2.22	2.15	2.03	5.16	29.43	6.57	Pass			
HE20	MCS0	2	157	5785	52/38	0.32	0.28	2.22	2.25	2.08	5.26	29.43	6.57	Pass			
HE20	MCS0	2	157	5785	106/53	0.32	0.28	2.22	2.09	2.07	5.10	29.43	6.57	Pass			
HE20	MCS0	2	165	5825	Full	0.32	0.28	2.22	2.58	2.38	5.59	29.43	6.57	Pass			
HE20	MCS0	2	165	5825	26/8	0.32	0.28	2.22	2.54	2.18	5.55	29.43	6.57	Pass			
HE20	MCS0	2	165	5825	52/40	0.32	0.28	2.22	2.12	2.00	5.13	29.43	6.57	Pass			
HE20	MCS0	2	165	5825	106/54	0.32	0.28	2.22	2.32	2.24	5.33	29.43	6.57	Pass			
HE40	MCS0	2	151	5755	Full	0.33	0.32	2.22	-0.18	-0.53	2.83	29.43	6.57	Pass			
HE40	MCS0	2	151	5755	242/61	0.33	0.32	2.22	-0.21	-0.77	2.80	29.43	6.57	Pass			
HE40	MCS0	2	159	5795	Full	0.33	0.32	2.22	-0.11	-0.75	2.90	29.43	6.57	Pass			
HE40	MCS0	2	159	5795	242/62	0.33	0.32	2.22	-0.75	-1.03	2.26	29.43	6.57	Pass			
HE80	MCS0	2	155	5775	Full	0.35	0.36	2.22	-4.11	-4.50	-1.10	29.43	6.57	Pass			
HE80	MCS0	2	155	5775	484/65	0.35	0.36	2.22	-4.12	-4.70	-1.11	29.43	6.57	Pass			
HE80	MCS0	2	155	5775	484/66	0.35	0.36	2.22	-4.19	-4.54	-1.18	29.43	6.57	Pass			

Note: PSD Sum = Max PSD(Ant. 9, Ant. 8) + 10 log (n)





<802.11ax HE20>

Maximum Power Density Plot (dBm/500kHz)

MIMO Ant. 9

MIMO Ant. 8





<802.11ax HE40>

Maximum Power Density Plot (dBm/500kHz)


MIMO Ant. 9

MIMO Ant. 8





<802.11ax HE80>



Note: Average Power Density (dB) = Measured value+ Duty Factor




Test Engineer :	Junyu Zhou	Temperature :	20.9~22.1°C
		Relative Humidity :	51.3~65.3%

<TXBF Modes>

Band IV MIMO															
Mod.	Data Rate	NTX	CH.	Freq. (MHz)	RU Config.	10log (500kHz /RBW) Factor (dB)		Average Power Density (dBm/500kHz)			Average PSD Limit (dBm/500kHz)		DG (dBi)		Pass /Fail
						Ant 9	Ant 8	Ant 9	Ant 8	SUM	Ant 9	Ant 8	Ant 9	Ant 8	
HE20	MCS0	2	149	5745	Full	2.22	5.99	6.18	9.19	29.43	6.57	Pass			
HE20	MCS0	2	157	5785	Full	2.22	5.84	6.10	9.11	29.43	6.57	Pass			
HE20	MCS0	2	165	5825	Full	2.22	5.68	6.86	9.87	29.43	6.57	Pass			
HE40	MCS0	2	151	5755	Full	2.22	3.03	2.99	6.04	29.43	6.57	Pass			
HE40	MCS0	2	159	5795	Full	2.22	3.21	3.76	6.77	29.43	6.57	Pass			
HE80	MCS0	2	155	5775	Full	2.22	-3.05	-2.29	0.72	29.43	6.57	Pass			

Note: PSD Sum = Max PSD(Ant. 9, Ant. 8) + 10 log (n)

<802.11ax HE20>







<802.11ax HE40>

Maximum Power Density Plot (dBm/500kHz)

MIMO Ant. 9

MIMO Ant. 8





<802.11ax HE80>

Maximum Power Density Plot (dBm/500kHz)

MIMO Ant. 9

MIMO Ant. 8





3.4 Unwanted Emissions Measurement

This section is to measure unwanted emissions through radiated measurement for band edge spurious emissions and out of band emissions measurement.

3.4.1 Limit of Unwanted Emissions

(1) For transmitters operating in the 5.725-5.85 GHz band:

15.407(b)(4)(i) All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

(2) Unwanted spurious emissions falls in restricted bands shall comply with the general field strength limits as below table,

Frequency (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30 – 88	100	3
88 – 216	150	3
216 - 960	200	3
Above 960	500	3

Note: The following formula is used to convert the EIRP to field strength.

$$E = \frac{1000000\sqrt{30P}}{3} \text{ } \mu\text{V/m, where P is the eirp (Watts)}$$

EIRP (dBm)	Field Strength at 3m (dBμV/m)
- 27	68.3

(3) KDB789033 D02 v02r01 G)2)c)

(i) Sections 15.407(b)(1-3) specifies the unwanted emissions limit for the U-NII-1 and U-NII-2 bands. As specified, emissions above 1000 MHz that are outside of the restricted bands are subject to a peak emission limit of -27 dBm/MHz.

(ii) Section 15.407(b)(4) specifies the unwanted emissions limit for the U-NII-3 band. A band emissions mask is specified in Section 15.407(b)(4)(i). The emission limits are based on the use of a peak detector.



3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.


3.4.3 Test Procedures

1. The testing follows FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01. Section G) Unwanted emissions measurement.
 - (1) Procedure for Unwanted Emissions Measurements Below 1000 MHz
 - RBW = 120 kHz
 - VBW = 300 kHz
 - Detector = Peak
 - Trace mode = max hold
 - (2) Procedure for Peak Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW \geq 3 MHz
 - Detector = Peak
 - Sweep time = auto
 - Trace mode = max hold
 - (3) Procedures for Average Unwanted Emissions Measurements Above 1000 MHz
 - RBW = 1 MHz
 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW \geq 1/T, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.
2. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
3. The EUT is set 3 meters away from the receiving antenna which is mounted on the top of a variable height antenna tower.
4. The antenna is a broadband antenna and its height is adjusted between one meter and four meters above ground to find the maximum value of the field strength for both horizontal polarization and vertical polarization of the antenna.
5. For each suspected emission, the EUT is arranged to its worst case and then adjust the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading.

6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-“.
7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “-“.


3.4.4 Test Setup

For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz

<CDD Mode>




<TXBF Modes>




For radiated test from 1GHz to 18GHz

<CDD Mode>




<TXBF Modes>




For radiated test above 18GHz

<CDD Mode>



<TXBF Modes>



3.4.5 Test Results of Radiated Emissions (9 kHz ~ 30 MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.

3.4.6 Test Result of Radiated Band Edges

Please refer to Appendix B and C.

3.4.7 Duty Cycle

Please refer to Appendix D.

3.4.8 Test Result of Unwanted Radiated Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B and C.



3.5 AC Conducted Emission Measurement

3.5.1 Limit of AC Conducted Emission

For equipment that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table.

Frequency of emission (MHz)	Conducted limit (dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.


3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The EUT is placed 0.4 meter away from the conducting wall of the shielding room, and is kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. The FCC states that a 50 ohm, 50 microhenry LISN shall be used.
6. Both Line and Neutral shall be tested in order to find out the maximum conducted emission.
7. The frequency range from 150 kHz to 30 MHz is scanned.
8. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.

3.5.4 Test Setup



3.5.5 Test Result of AC Conducted Emission

Please refer to Appendix A.

3.6 Antenna Requirements

3.6.1 Standard Applicable

If transmitting antenna directional gain is greater than 6 dBi, both the peak transmit power and the peak power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

3.6.2 Antenna Anti-Replacement Construction

An embedded-in antenna design is used.

3.6.3 Antenna Gain

<CDD Modes >

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For power measurements on IEEE 802.11 devices,

Directional gain = G_{ANT} + Array Gain, where Array Gain is as follows:

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$.

G_{ANT} is set equal to the gain of the antenna having the highest gain.

For PSD measurements, the directional gain calculation follows F)2)f)ii) of KDB 662911 D01 v02r01.

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k/20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

As minimum $N_{SS}=1$ is supported by EUT, the formula can be simplified as:

Directional gain = $10 \cdot \log[(10^{G_1/20} + 10^{G_2/20} + \dots + 10^{G_N/20})^2 / N_{ANT}]$ dBi

Where G_1, G_2, \dots, G_N denote single antenna gain.

For example: If a device has two antenna, $G_{ANT1}= 3.6$ dBi; $G_{ANT2}=4.2$ dBi

Directional gain of power measurement = $\max(3.6, 4.2) + 0 = 4.2$ dBi

Directional gain of PSD measurement = $10 \cdot \log[(10^{3.6/20} + 10^{4.2/20})^2 / 2] = 6.92$ dBi



The directional gain "DG" is calculated as following table.

<CDD Modes>						
			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant. 9	Ant. 8	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	3.90	3.20	3.90	6.57	0.00	0.57

$$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$$

$$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$$

Calculation example:

The DG for PSD is derived from formula is

$$10 \times \log \left\{ \left[10^{(3.90\text{ dBi} / 20)} + 10^{(3.20\text{ dBi} / 20)} \right]^2 \right\} / 2$$

$$= 6.57\text{ dBi}$$

TXBF modes

FCC KDB 662911 D01 Multiple Transmitter Output v02r01

For CDD transmissions, directional gain is calculated as

$$DirectionalGain = 10 \cdot \log \left[\frac{\sum_{j=1}^{N_{SS}} \left\{ \sum_{k=1}^{N_{ANT}} g_{j,k} \right\}^2}{N_{ANT}} \right]$$

where

Each antenna is driven by no more than one spatial stream;

N_{SS} = the number of independent spatial streams of data;

N_{ANT} = the total number of antennas

$g_{j,k} = 10^{G_k / 20}$ if the k th antenna is being fed by spatial stream j , or zero if it is not;
 G_k is the gain in dBi of the k th antenna.

The EUT supports beamforming modes.

The directional gain calculation is following F)2)e)ii) of KDB 662911 D01 v02r01.

The power and PSD limit should be modified if the directional gain of EUT is over 6 dBi,

The directional gain “DG” is calculated as following table.

			DG	DG	Power	PSD
			for	for	Limit	Limit
	Ant 9	Ant 8	Power	PSD	Reduction	Reduction
	(dBi)	(dBi)	(dBi)	(dBi)	(dB)	(dB)
Band IV	3.90	3.20	6.57	6.57	0.57	0.57

$Power\ Limit\ Reduction = DG(Power) - 6dBi, (min = 0)$

$PSD\ Limit\ Reduction = DG(PSD) - 6dBi, (min = 0)$

Calculation example:

For the Band IV, the DG for PSD is derived from formula is

$$10 \times \log \left\{ \left[10^{(3.90\text{ dBi} / 20)} + 10^{(3.20\text{ dBi} / 20)} \right]^2 / 2 \right\}$$

= 6.57 dBi



4 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Loop Antenna	Rohde & Schwarz	HFH2-Z2	100488	9 kHz~30 MHz	Sep. 07, 2021	Mar. 05, 2022~ Mar. 12, 2022	Sep. 06, 2022	Radiation (03CH16-HY)
Bilog Antenna	TESEQ	CBL 6111D & 00802N1D01N -06	47020 & 06	30MHz to 1GHz	Oct. 09, 2021	Mar. 05, 2022~ Mar. 12, 2022	Oct. 08, 2022	Radiation (03CH16-HY)
Horn Antenna	SCHWARZBE CK	BBHA 9120 D	9120D-02114	1G~18GHz	Aug. 04, 2021	Mar. 05, 2022~ Mar. 12, 2022	Aug. 03, 2022	Radiation (03CH16-HY)
SHF-EHF Horn Antenna	SCHWARZBE CK	BBHA 9170	00993	18GHz ~40GHz	Nov. 30, 2021	Mar. 05, 2022~ Mar. 12, 2022	Nov. 29, 2022	Radiation (03CH16-HY)
Amplifier	SONOMA	310N	371607	9kHz~1G	Jul. 05, 2021	Mar. 05, 2022~ Mar. 12, 2022	Jul. 04, 2022	Radiation (03CH16-HY)
Amplifier	EMCI	EMC051845S E	980729	1-18GHz	Jul. 09, 2021	Mar. 05, 2022~ Mar. 12, 2022	Jul. 08, 2022	Radiation (03CH16-HY)
Preamplifier	EMEC	EM18G40G	060801	18GHz~40GHz	Jun. 22, 2021	Mar. 05, 2022~ Mar. 12, 2022	Jun. 21, 2022	Radiation (03CH16-HY)
Preamplifier	Keysight	83017A	MY53270264	1GHz~26.5GHz	Dec. 09, 2021	Mar. 05, 2022~ Mar. 12, 2022	Dec. 08, 2022	Radiation (03CH16-HY)
EMI Test Receiver	Keysight	N9038A(MXE)	MY57290111	3Hz~26.5GHz	Dec. 15, 2021	Mar. 05, 2022~ Mar. 12, 2022	Dec. 14, 2022	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11680/4P E	NA	Aug. 28, 2021	Mar. 05, 2022~ Mar. 12, 2022	Aug. 27, 2022	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 104	MY11688/4P E	NA	Aug. 28, 2021	Mar. 05, 2022~ Mar. 12, 2022	Aug. 27, 2022	Radiation (03CH16-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	EC-A5-300-5 757	NA	Aug. 28, 2021	Mar. 05, 2022~ Mar. 12, 2022	Aug. 27, 2022	Radiation (03CH16-HY)
Software	Audix	E3 6.2009-8-24	RK-001136	N/A	N/A	Mar. 05, 2022~ Mar. 12, 2022	N/A	Radiation (03CH16-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Mar. 05, 2022~ Mar. 12, 2022	N/A	Radiation (03CH16-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Mar. 05, 2022~ Mar. 12, 2022	N/A	Radiation (03CH16-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Mar. 05, 2022~ Mar. 12, 2022	N/A	Radiation (03CH16-HY)
Hygrometer	TECPEL	DTM-303A	TP201996	N/A	Nov. 16, 2021	Mar. 02, 2022~ May 22, 2022	Nov. 15, 2022	Conducted (TH05-HY)
Power Sensor	DARE	RPR3006W	16I00054SNO 12 (NO:113)	10MHz~6GHz	Dec. 16, 2021	Mar. 02, 2022~ May 22, 2022	Dec. 15, 2022	Conducted (TH05-HY)
Signal Analyzer	Rohde & Schwarz	FSV40	101566	10Hz~40GHz	Aug. 30, 2021	Mar. 02, 2022~ May 22, 2022	Aug. 29, 2022	Conducted (TH05-HY)
Switch Control Mainframe	E-IUSTRUME NT	ETF-1405-0	EC1900067 (BOX7)	N/A	Aug. 12, 2021	Mar. 02, 2022~ May 22, 2022	Aug. 11, 2022	Conducted (TH05-HY)



Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
AC Power Source	ChainTek	APC-1000W	N/A	N/A	N/A	Apr. 12, 2022	N/A	Conduction (CO05-HY)
EMI Test Receiver	Rohde & Schwarz	ESR3	102388	9kHz~3.6GHz	Dec. 01, 2021	Apr. 12, 2022	Nov. 30, 2022	Conduction (CO05-HY)
Hygrometer	Testo	608-H1	34913912	N/A	Nov. 17, 2021	Apr. 12, 2022	Nov. 16, 2022	Conduction (CO05-HY)
LISN	Rohde & Schwarz	ENV216	100080	9kHz~30MHz	Dec. 03, 2021	Apr. 12, 2022	Dec. 02, 2022	Conduction (CO05-HY)
Software	Rohde & Schwarz	EMC32	N/A	N/A	N/A	Apr. 12, 2022	N/A	Conduction (CO05-HY)
Pulse Limiter	SCHWARZBECK	VTSD 9561-FN	00691	N/A	Jul. 28, 2021	Apr. 12, 2022	Jul. 27, 2022	Conduction (CO05-HY)
LISN Cable	MVE	RG-400	260260	N/A	Dec. 30, 2021	Apr. 12, 2022	Dec. 29, 2022	Conduction (CO05-HY)



5 Uncertainty of Evaluation

Uncertainty of Conducted Emission Measurement (150kHz ~ 30MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	3.1 dB
---	--------

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.8 dB
---	--------

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 18000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.2 dB
---	--------

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.8 dB
---	--------




Appendix A. AC Conducted Emission Test Results

Test Engineer :	Calvin Wang	Temperature :	23~26°C
		Relative Humidity :	40~50%

EUT Information

Report NO : 222202
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Line

Full Spectrum




Final Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.177000	---	32.10	54.63	22.53	L1	OFF	19.6
0.177000	44.65	---	64.63	19.98	L1	OFF	19.6
0.197250	---	32.66	53.73	21.07	L1	OFF	19.6
0.197250	43.49	---	63.73	20.24	L1	OFF	19.6
0.242250	---	34.15	52.02	17.87	L1	OFF	19.6
0.242250	44.00	---	62.02	18.02	L1	OFF	19.6
0.269250	---	31.27	51.14	19.87	L1	OFF	19.6
0.269250	43.02	---	61.14	18.12	L1	OFF	19.6
0.438000	---	27.52	47.10	19.58	L1	OFF	19.6
0.438000	36.75	---	57.10	20.35	L1	OFF	19.6
3.108750	---	25.87	46.00	20.13	L1	OFF	19.7
3.108750	29.60	---	56.00	26.40	L1	OFF	19.7
9.471750	---	26.52	50.00	23.48	L1	OFF	20.0
9.471750	28.42	---	60.00	31.58	L1	OFF	20.0
13.560000	---	26.39	50.00	23.61	L1	OFF	20.2
13.560000	29.01	---	60.00	30.99	L1	OFF	20.2

EUT Information

Report NO : 222202
 Test Mode : Mode 1
 Test Voltage : 120Vac/60Hz
 Phase : Neutral

Full Spectrum



Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	CAverage (dBuV)	Limit (dBuV)	Margin (dB)	Line	Filter	Corr. (dB)
0.179250	---	33.29	54.52	21.23	N	OFF	19.6
0.179250	45.67	---	64.52	18.85	N	OFF	19.6
0.192750	---	33.56	53.92	20.36	N	OFF	19.6
0.192750	44.74	---	63.92	19.18	N	OFF	19.6
0.237750	---	32.48	52.17	19.69	N	OFF	19.6
0.237750	44.64	---	62.17	17.53	N	OFF	19.6
0.258000	---	32.72	51.50	18.78	N	OFF	19.6
0.258000	43.99	---	61.50	17.51	N	OFF	19.6
0.363750	---	29.07	48.64	19.57	N	OFF	19.6
0.363750	38.09	---	58.64	20.55	N	OFF	19.6
3.673500	---	25.74	46.00	20.26	N	OFF	19.8
3.673500	28.86	---	56.00	27.14	N	OFF	19.8
10.592250	---	25.48	50.00	24.52	N	OFF	20.1
10.592250	26.99	---	60.00	33.01	N	OFF	20.1
13.560000	---	26.45	50.00	23.55	N	OFF	20.2
13.560000	28.60	---	60.00	31.40	N	OFF	20.2



Appendix B. Radiated Spurious Emission

Test Engineer :	Andy Yang, Karl Hou and Wilson Wu	Temperature :	20~25°C
		Relative Humidity :	50~60%

<CDD Mode>

Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.11a CH 149 5745MHz		5649.4	57.8	-10.4	68.2	41.19	33.3	12.91	29.6	105	85	P	H	
		5700	71.04	-34.16	105.2	54.42	33.3	12.93	29.61	105	85	P	H	
		5719.2	78.56	-32.02	110.58	61.8	33.42	12.95	29.61	105	85	P	H	
		5724.8	80.67	-41.07	121.74	63.88	33.45	12.95	29.61	105	85	P	H	
	*	5745	113.96	-	-	97.04	33.57	12.96	29.61	105	85	P	H	
	*	5745	105.49	-	-	88.57	33.57	12.96	29.61	105	85	A	H	
														H
														H
			5648	56.74	-11.46	68.2	40.13	33.3	12.91	29.6	398	85	P	V
			5700	66.36	-38.84	105.2	49.74	33.3	12.93	29.61	398	85	P	V
			5720	77.96	-32.84	110.8	61.2	33.42	12.95	29.61	398	85	P	V
			5724.4	81.84	-38.99	120.83	65.05	33.45	12.95	29.61	398	85	P	V
	*		5745	110.8	-	-	93.88	33.57	12.96	29.61	398	85	P	V
	*		5745	103.45	-	-	86.53	33.57	12.96	29.61	398	85	A	V
													V	
													V	



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11a CH 157 5785MHz		5606	54.98	-13.22	68.2	38.48	33.21	12.88	29.59	103	84	P	H	
		5691.6	59.23	-39.78	99.01	42.6	33.3	12.93	29.6	103	84	P	H	
		5715.4	66.06	-43.45	109.51	49.34	33.39	12.94	29.61	103	84	P	H	
		5724.2	68.66	-51.72	120.38	51.87	33.45	12.95	29.61	103	84	P	H	
	*	5785	114.08	-	-	97.05	33.67	12.98	29.62	103	84	P	H	
	*	5785	105.62	-	-	88.59	33.67	12.98	29.62	103	84	A	H	
		5853.6	64.37	-49.62	113.99	47.18	34	12.82	29.63	103	84	P	H	
		5855	64.16	-46.64	110.8	46.98	34	12.81	29.63	103	84	P	H	
		5878.8	59.06	-43.32	102.38	41.97	34	12.73	29.64	103	84	P	H	
		5937.6	54.1	-14.1	68.2	37.13	34.08	12.54	29.65	103	84	P	H	
														H
														H
			5638	54.78	-13.42	68.2	38.19	33.28	12.9	29.59	393	99	P	V
			5699	56.79	-47.67	104.46	40.17	33.3	12.93	29.61	393	99	P	V
			5720	62.36	-48.44	110.8	45.6	33.42	12.95	29.61	393	99	P	V
			5722.2	63.19	-52.63	115.82	46.42	33.43	12.95	29.61	393	99	P	V
	*		5785	111.48	-	-	94.45	33.67	12.98	29.62	393	99	P	V
	*		5785	103.31	-	-	86.28	33.67	12.98	29.62	393	99	A	V
			5853.2	62.51	-52.39	114.9	45.32	34	12.82	29.63	393	99	P	V
			5862.2	59.33	-49.45	108.78	42.18	34	12.79	29.64	393	99	P	V
		5880.4	57.6	-43.59	101.19	40.51	34	12.73	29.64	393	99	P	V	
		5942.8	55.13	-13.07	68.2	38.16	34.09	12.53	29.65	393	99	P	V	
													V	
													V	



WiFi Ant. 9+8	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11a CH 165 5825MHz	*	5825	113.97	-	-	96.84	33.85	12.91	29.63	102	90	P	H	
	*	5825	105.28	-	-	88.15	33.85	12.91	29.63	102	90	A	H	
		5851.2	78.78	-40.68	119.46	61.59	34	12.82	29.63	102	90	P	H	
		5858.8	75.88	-33.85	109.73	58.71	34	12.8	29.63	102	90	P	H	
		5878.4	69.5	-33.17	102.67	52.4	34	12.74	29.64	102	90	P	H	
		5928.6	55.13	-13.07	68.2	38.15	34.06	12.57	29.65	102	90	P	H	
														H
														H
	*	5825	109.88	-	-	92.75	33.85	12.91	29.63	386	83	P	V	
	*	5825	102.7	-	-	85.57	33.85	12.91	29.63	386	83	A	V	
		5851.4	78.05	-40.96	119.01	60.86	34	12.82	29.63	386	83	P	V	
		5858	73.22	-36.74	109.96	56.05	34	12.8	29.63	386	83	P	V	
		5875.2	66.81	-38.24	105.05	49.7	34	12.75	29.64	386	83	P	V	
		5929.8	55.08	-13.12	68.2	38.1	34.06	12.57	29.65	386	83	P	V	
														V
														V
														V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Band 4 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 149 5745MHz		11490	47.01	-26.99	74	43.95	38.84	19.23	55.01	-	-	P	H
		17235	49.42	-18.78	68.2	42.19	37.81	25.11	55.69	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			11490	47.91	-26.09	74	44.85	38.84	19.23	55.01	-	-	P
		17235	47.8	-20.4	68.2	40.57	37.81	25.11	55.69	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 157 5785MHz		11570	46.67	-27.33	74	43.58	38.8	19.27	54.98	-	-	P	H
		17355	48.2	-20	68.2	40.82	38.17	25.16	55.95	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			11570	47.24	-26.76	74	44.15	38.8	19.27	54.98	-	-	P
		17355	48.31	-19.89	68.2	40.93	38.17	25.16	55.95	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11a CH 165 5825MHz		11650	46.95	-27.05	74	43.9	38.7	19.3	54.95	-	-	P	H
		17475	47.97	-20.23	68.2	40.51	38.45	25.22	56.21	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			11650	47.54	-26.46	74	44.49	38.7	19.3	54.95	-	-	P
		17475	47.47	-20.73	68.2	40.01	38.45	25.22	56.21	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only. 												



**Band 4 5725~5850MHz
WIFI 802.11ax HE20_Full (Band Edge @ 3m)**

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Full CH 149 5745MHz		5644.4	62.27	-5.93	68.2	45.68	33.29	12.9	29.6	106	84	P	H	
		5697.6	76.51	-26.92	103.43	59.89	33.3	12.93	29.61	106	84	P	H	
		5713	83.07	-25.77	108.84	66.36	33.38	12.94	29.61	106	84	P	H	
		5724.4	89.09	-31.74	120.83	72.3	33.45	12.95	29.61	106	84	P	H	
	*	5745	114.84	-	-	97.92	33.57	12.96	29.61	106	84	P	H	
	*	5745	104.78	-	-	87.86	33.57	12.96	29.61	106	84	A	H	
														H
														H
			5640	57.43	-10.77	68.2	40.85	33.28	12.9	29.6	398	94	P	V
			5694.8	72.95	-28.42	101.37	56.33	33.3	12.93	29.61	398	94	P	V
			5713.4	82.04	-26.91	108.95	65.33	33.38	12.94	29.61	398	94	P	V
			5723.6	86.8	-32.21	119.01	70.02	33.44	12.95	29.61	398	94	P	V
		*	5745	112.25	-	-	95.33	33.57	12.96	29.61	398	94	P	V
		*	5745	103.37	-	-	86.45	33.57	12.96	29.61	398	94	A	V
													V	
													V	



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5606	55.04	-13.16	68.2	38.54	33.21	12.88	29.59	105	82	P	H
		5700	60.77	-44.43	105.2	44.15	33.3	12.93	29.61	105	82	P	H
		5719.4	68.48	-42.15	110.63	51.72	33.42	12.95	29.61	105	82	P	H
		5721.6	66.73	-47.72	114.45	49.96	33.43	12.95	29.61	105	82	P	H
	*	5785	114.87	-	-	97.84	33.67	12.98	29.62	105	82	P	H
	*	5785	105.14	-	-	88.11	33.67	12.98	29.62	105	82	A	H
		5854.4	63.75	-48.42	112.17	46.57	34	12.81	29.63	105	82	P	H
		5857.8	62.12	-47.89	110.01	44.95	34	12.8	29.63	105	82	P	H
		5875.2	57.8	-47.25	105.05	40.69	34	12.75	29.64	105	82	P	H
		5938	54.31	-13.89	68.2	37.34	34.08	12.54	29.65	105	82	P	H
802.11ax													H
HE20 Full													H
CH 157		5637.8	55.43	-12.77	68.2	38.84	33.28	12.9	29.59	372	94	P	V
5785MHz		5696.2	56.33	-46.07	102.4	39.71	33.3	12.93	29.61	372	94	P	V
		5717.8	60.71	-49.47	110.18	43.97	33.41	12.94	29.61	372	94	P	V
		5724.8	62.64	-59.1	121.74	45.85	33.45	12.95	29.61	372	94	P	V
	*	5785	113.13	-	-	96.1	33.67	12.98	29.62	372	94	P	V
	*	5785	103.39	-	-	86.36	33.67	12.98	29.62	372	94	A	V
		5850	64.01	-58.19	122.2	46.81	34	12.83	29.63	372	94	P	V
		5864.8	62.11	-45.94	108.05	44.97	34	12.78	29.64	372	94	P	V
		5906.2	56.87	-25.21	82.08	39.86	34.01	12.64	29.64	372	94	P	V
		5936	54.77	-13.43	68.2	37.8	34.07	12.55	29.65	372	94	P	V
													V
													V



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Full CH 165 5825MHz	*	5825	115.33	-	-	98.2	33.85	12.91	29.63	100	72	P	H	
	*	5825	105.11	-	-	87.98	33.85	12.91	29.63	100	72	A	H	
		5851.4	79.32	-39.69	119.01	62.13	34	12.82	29.63	100	72	P	H	
		5855.6	77.21	-33.42	110.63	60.03	34	12.81	29.63	100	72	P	H	
		5880.2	67.57	-33.77	101.34	50.48	34	12.73	29.64	100	72	P	H	
		5936.2	54.83	-13.37	68.2	37.86	34.07	12.55	29.65	100	72	P	H	
														H
														H
	*	5825	113.9	-	-	96.77	33.85	12.91	29.63	384	82	P	V	
	*	5825	103.63	-	-	86.5	33.85	12.91	29.63	384	82	A	V	
		5851.6	76.18	-42.37	118.55	58.99	34	12.82	29.63	384	82	P	V	
		5855.2	75.17	-35.57	110.74	57.99	34	12.81	29.63	384	82	P	V	
		5877	67.29	-36.42	103.71	50.19	34	12.74	29.64	384	82	P	V	
		5926.2	56.92	-11.28	68.2	39.94	34.05	12.58	29.65	384	82	P	V	
														V
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Band 4 5725~5850MHz

WIFI 802.11ax HE20 Full (Harmonic @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Full CH 149 5745MHz		11490	46.59	-27.41	74	43.53	38.84	19.23	55.01	-	-	P	H	
		17235	48.36	-19.84	68.2	41.13	37.81	25.11	55.69	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			11490	47.96	-26.04	74	44.9	38.84	19.23	55.01	-	-	P	V
			17235	47.87	-20.33	68.2	40.64	37.81	25.11	55.69	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE20 Full CH 157 5785MHz		11570	47.45	-26.55	74	44.36	38.8	19.27	54.98	-	-	P	H
		17355	48.58	-19.62	68.2	41.2	38.17	25.16	55.95	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
			11570	47.55	-26.45	74	44.46	38.8	19.27	54.98	-	-	P
		17355	48.53	-19.67	68.2	41.15	38.17	25.16	55.95	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V
													V



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Full CH 165 5825MHz		11650	48.18	-25.82	74	45.13	38.7	19.3	54.95	-	-	P	H	
		17475	47.31	-20.89	68.2	39.85	38.45	25.22	56.21	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			11650	47.91	-26.09	74	44.86	38.7	19.3	54.95	-	-	P	V
			17475	47.44	-20.76	68.2	39.98	38.45	25.22	56.21	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only. 													



Band 4 5725~5850MHz
WIFI 802.11ax HE20_Partial 106 (Band Edge @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Partial 106/53 CH 149 5745MHz		5641.4	66.17	-2.03	68.2	49.59	33.28	12.9	29.6	104	84	P	H	
		5694	80.23	-20.55	100.78	63.6	33.3	12.93	29.6	104	84	P	H	
		5719.4	88.14	-22.49	110.63	71.38	33.42	12.95	29.61	104	84	P	H	
		5721.6	88.77	-25.68	114.45	72	33.43	12.95	29.61	104	84	P	H	
	*	5745	118.86	-	-	101.94	33.57	12.96	29.61	104	84	P	H	
	*	5745	110.79	-	-	93.87	33.57	12.96	29.61	104	84	A	H	
														H
														H
			5646	62.53	-5.67	68.2	45.93	33.29	12.91	29.6	400	89	P	V
			5696.4	77.33	-25.22	102.55	60.71	33.3	12.93	29.61	400	89	P	V
			5716.6	88.39	-21.46	109.85	71.66	33.4	12.94	29.61	400	89	P	V
			5724.2	84.85	-35.53	120.38	68.06	33.45	12.95	29.61	400	89	P	V
		*	5745	113.74	-	-	96.82	33.57	12.96	29.61	400	89	P	V
		*	5745	105.49	-	-	88.57	33.57	12.96	29.61	400	89	A	V
														V
													V	



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Partial 106/54 CH 165 5825MHz	*	5825	118.7	-	-	101.57	33.85	12.91	29.63	100	84	P	H	
	*	5825	107.83	-	-	90.7	33.85	12.91	29.63	100	84	A	H	
		5854	89.58	-23.5	113.08	72.4	34	12.81	29.63	100	84	P	H	
		5855.2	87.62	-23.12	110.74	70.44	34	12.81	29.63	100	84	P	H	
		5877	82.34	-21.37	103.71	65.24	34	12.74	29.64	100	84	P	H	
		5925.6	65.08	-3.12	68.2	48.1	34.05	12.58	29.65	100	84	P	H	
														H
														H
	*	5825	115.4	-	-	98.27	33.85	12.91	29.63	385	97	P	V	
	*	5825	106.07	-	-	88.94	33.85	12.91	29.63	385	97	A	V	
		5854	85.17	-27.91	113.08	67.99	34	12.81	29.63	385	97	P	V	
		5857.2	86.82	-23.36	110.18	69.65	34	12.8	29.63	385	97	P	V	
		5879	76.55	-25.68	102.23	59.46	34	12.73	29.64	385	97	P	V	
		5926.4	61.3	-6.9	68.2	44.32	34.05	12.58	29.65	385	97	P	V	
														V
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Band 4 5725~5850MHz
WIFI 802.11ax HE40_Full (Band Edge @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5648	65.83	-2.37	68.2	49.22	33.3	12.91	29.6	105	84	P	H
		5700	76.31	-28.89	105.2	59.69	33.3	12.93	29.61	105	84	P	H
		5711.6	79.05	-29.4	108.45	62.35	33.37	12.94	29.61	105	84	P	H
		5722.6	83.05	-33.68	116.73	66.27	33.44	12.95	29.61	105	84	P	H
	*	5755	111.68	-	-	94.72	33.61	12.97	29.62	105	84	P	H
	*	5755	102.19	-	-	85.23	33.61	12.97	29.62	105	84	A	H
		5852.4	65.53	-51.2	116.73	48.34	34	12.82	29.63	105	84	P	H
		5864.4	67.78	-40.39	108.17	50.64	34	12.78	29.64	105	84	P	H
		5882.2	63.65	-36.2	99.85	46.57	34	12.72	29.64	105	84	P	H
		5932.2	60.65	-7.55	68.2	43.68	34.06	12.56	29.65	105	84	P	H
802.11ax													H
HE40 Full													H
CH 151		5616	65.31	-2.89	68.2	48.78	33.23	12.89	29.59	396	83	P	V
5755MHz		5696.6	68.35	-34.34	102.69	51.73	33.3	12.93	29.61	396	83	P	V
		5716	76.22	-33.46	109.68	59.49	33.4	12.94	29.61	396	83	P	V
		5724	78.64	-41.28	119.92	61.86	33.44	12.95	29.61	396	83	P	V
	*	5755	110.56	-	-	93.6	33.61	12.97	29.62	396	83	P	V
	*	5755	100.67	-	-	83.71	33.61	12.97	29.62	396	83	A	V
		5855	60.78	-50.02	110.8	43.6	34	12.81	29.63	396	83	P	V
		5868.2	64.92	-42.18	107.1	47.79	34	12.77	29.64	396	83	P	V
		5877.2	64.35	-39.22	103.57	47.25	34	12.74	29.64	396	83	P	V
		5927	57.23	-10.97	68.2	40.25	34.05	12.58	29.65	396	83	P	V
													V
													V



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5646.6	62.25	-5.95	68.2	45.65	33.29	12.91	29.6	100	82	P	H
		5690.2	65.12	-32.85	97.97	48.49	33.3	12.93	29.6	100	82	P	H
		5718.6	67.24	-43.17	110.41	50.49	33.41	12.95	29.61	100	82	P	H
		5722.6	67.87	-48.86	116.73	51.09	33.44	12.95	29.61	100	82	P	H
	*	5795	111.2	-	-	94.14	33.69	12.99	29.62	100	82	P	H
	*	5795	101.83	-	-	84.77	33.69	12.99	29.62	100	82	A	H
		5850.8	70.67	-49.71	120.38	53.48	34	12.82	29.63	100	82	P	H
		5855.2	68.96	-41.78	110.74	51.78	34	12.81	29.63	100	82	P	H
		5883.8	67.97	-30.7	98.67	50.89	34	12.72	29.64	100	82	P	H
		5926.8	61.5	-6.7	68.2	44.52	34.05	12.58	29.65	100	82	P	H
802.11ax													H
HE40 Full													H
CH 159		5628.6	58.58	-9.62	68.2	42.01	33.26	12.9	29.59	286	110	P	V
5795MHz		5699.6	63.46	-41.45	104.91	46.84	33.3	12.93	29.61	286	110	P	V
		5712.4	63.14	-45.53	108.67	46.44	33.37	12.94	29.61	286	110	P	V
		5720.8	65.78	-46.84	112.62	49.02	33.42	12.95	29.61	286	110	P	V
	*	5795	108.46	-	-	91.4	33.69	12.99	29.62	286	110	P	V
	*	5795	99.45	-	-	82.39	33.69	12.99	29.62	286	110	A	V
		5854.2	68.77	-43.85	112.62	51.59	34	12.81	29.63	286	110	P	V
		5855.2	66.34	-44.4	110.74	49.16	34	12.81	29.63	286	110	P	V
		5893.2	63.37	-28.33	91.7	46.32	34	12.69	29.64	286	110	P	V
		5935.2	59.94	-8.26	68.2	42.97	34.07	12.55	29.65	286	110	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ax HE40_Full (Harmonic @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE40 Full CH 151 5755MHz		11510	47.82	-26.18	74	44.78	38.8	19.24	55	-	-	P	H	
		17265	46.88	-21.32	68.2	39.62	37.9	25.11	55.75	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			11510	47.5	-26.5	74	44.46	38.8	19.24	55	-	-	P	V
			17265	47.27	-20.93	68.2	40.01	37.9	25.11	55.75	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE40 Full CH 159 5795MHz		11590	47.03	-26.97	74	43.92	38.8	19.28	54.97	-	-	P	H	
		17385	47.25	-20.95	68.2	39.83	38.26	25.17	56.01	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			11590	47.85	-26.15	74	44.74	38.8	19.28	54.97	-	-	P	V
			17385	46.87	-21.33	68.2	39.45	38.26	25.17	56.01	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only. 													



Band 4 5725~5850MHz
WIFI 802.11ax HE40_Partial 242 (Band Edge @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5641.8	65.3	-2.9	68.2	48.72	33.28	12.9	29.6	100	81	P	H
		5692.6	79.86	-19.88	99.74	63.23	33.3	12.93	29.6	100	81	P	H
		5719.6	77.66	-33.03	110.69	60.9	33.42	12.95	29.61	100	81	P	H
		5722.6	78.47	-38.26	116.73	61.69	33.44	12.95	29.61	100	81	P	H
	*	5755	111.3	-	-	94.34	33.61	12.97	29.62	100	81	P	H
	*	5755	102.03	-	-	85.07	33.61	12.97	29.62	100	81	A	H
		5853.2	63.3	-51.6	114.9	46.11	34	12.82	29.63	100	81	P	H
		5874.6	62.28	-43.03	105.31	45.17	34	12.75	29.64	100	81	P	H
		5879.4	63.91	-38.02	101.93	46.82	34	12.73	29.64	100	81	P	H
		5933	60.35	-7.85	68.2	43.37	34.07	12.56	29.65	100	81	P	H
802.11ax													H
HE40													H
Partial													H
242/61		5644.4	60.12	-8.08	68.2	43.53	33.29	12.9	29.6	400	97	P	V
CH 151		5693.4	71.96	-28.37	100.33	55.33	33.3	12.93	29.6	400	97	P	V
5755MHz		5719.6	74.21	-36.48	110.69	57.45	33.42	12.95	29.61	400	97	P	V
		5724.8	76.83	-44.91	121.74	60.04	33.45	12.95	29.61	400	97	P	V
	*	5755	108.87	-	-	91.91	33.61	12.97	29.62	400	97	P	V
	*	5755	100.43	-	-	83.47	33.61	12.97	29.62	400	97	A	V
		5850	60.43	-61.77	122.2	43.23	34	12.83	29.63	400	97	P	V
		5869.2	59.2	-47.62	106.82	42.07	34	12.77	29.64	400	97	P	V
		5879.4	59.34	-42.59	101.93	42.25	34	12.73	29.64	400	97	P	V
		5928.4	55.77	-12.43	68.2	38.79	34.06	12.57	29.65	400	97	P	V
													V
													V



WiFi Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE40 Partial 242/62 CH 159 5795MHz		5638.6	66.11	-2.09	68.2	49.52	33.28	12.9	29.59	102	88	P	H	
		5697.2	67.36	-35.78	103.14	50.74	33.3	12.93	29.61	102	88	P	H	
		5719.4	72.16	-38.47	110.63	55.4	33.42	12.95	29.61	102	88	P	H	
		5720.2	72.22	-39.04	111.26	55.46	33.42	12.95	29.61	102	88	P	H	
	*	5795	112.5	-	-	95.44	33.69	12.99	29.62	102	88	P	H	
	*	5795	103.15	-	-	86.09	33.69	12.99	29.62	102	88	A	H	
		5851.4	79.44	-39.57	119.01	62.25	34	12.82	29.63	102	88	P	H	
		5862.4	76.44	-32.29	108.73	59.29	34	12.79	29.64	102	88	P	H	
		5883	74.67	-24.59	99.26	57.59	34	12.72	29.64	102	88	P	H	
		5927.2	66.42	-1.78	68.2	49.44	34.05	12.58	29.65	102	88	P	H	
														H
														H
			5635	63.09	-5.11	68.2	46.51	33.27	12.9	29.59	389	97	P	V
			5693.4	67.58	-32.75	100.33	50.95	33.3	12.93	29.6	389	97	P	V
			5718.6	66.93	-43.48	110.41	50.18	33.41	12.95	29.61	389	97	P	V
			5722.2	67.45	-48.37	115.82	50.68	33.43	12.95	29.61	389	97	P	V
	*		5795	111.44	-	-	94.38	33.69	12.99	29.62	389	97	P	V
	*		5795	101.24	-	-	84.18	33.69	12.99	29.62	389	97	A	V
			5854.8	71.73	-39.53	111.26	54.55	34	12.81	29.63	389	97	P	V
			5856.4	72.2	-38.21	110.41	55.02	34	12.81	29.63	389	97	P	V
		5887.2	70.24	-25.9	96.14	53.17	34	12.71	29.64	389	97	P	V	
		5930	62.84	-5.36	68.2	45.86	34.06	12.57	29.65	389	97	P	V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Band 4 5725~5850MHz
WIFI 802.11ax HE80_Full (Band Edge @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5643.2	66.06	-2.14	68.2	49.47	33.29	12.9	29.6	103	83	P	H
		5691.2	73.73	-24.98	98.71	57.1	33.3	12.93	29.6	103	83	P	H
		5711	75.21	-33.07	108.28	58.51	33.37	12.94	29.61	103	83	P	H
		5723	75.96	-41.68	117.64	59.18	33.44	12.95	29.61	103	83	P	H
	*	5775	107.88	-	-	90.87	33.65	12.98	29.62	103	83	P	H
	*	5775	98.76	-	-	81.75	33.65	12.98	29.62	103	83	A	H
		5853.6	68.95	-45.04	113.99	51.76	34	12.82	29.63	103	83	P	H
		5862.8	69.54	-39.07	108.61	52.39	34	12.79	29.64	103	83	P	H
		5880.4	67.16	-34.03	101.19	50.07	34	12.73	29.64	103	83	P	H
		5934	59.67	-8.53	68.2	42.7	34.07	12.55	29.65	103	83	P	H
802.11ax													H
HE80 Full													H
CH 155		5613.2	64.24	-3.96	68.2	47.71	33.23	12.89	29.59	396	94	P	V
5775MHz		5696	65.67	-36.58	102.25	49.05	33.3	12.93	29.61	396	94	P	V
		5715	70.92	-38.48	109.4	54.2	33.39	12.94	29.61	396	94	P	V
		5725	72.67	-49.53	122.2	55.88	33.45	12.95	29.61	396	94	P	V
	*	5775	107.59	-	-	90.58	33.65	12.98	29.62	396	94	P	V
	*	5775	96.93	-	-	79.92	33.65	12.98	29.62	396	94	A	V
		5853.4	66.03	-48.42	114.45	48.84	34	12.82	29.63	396	94	P	V
		5864.8	67.65	-40.4	108.05	50.51	34	12.78	29.64	396	94	P	V
		5876.2	65.44	-38.87	104.31	48.34	34	12.74	29.64	396	94	P	V
		5927.2	58.87	-9.33	68.2	41.89	34.05	12.58	29.65	396	94	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz
WIFI 802.11ax HE80_Full (Harmonic @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE80 Full CH 155 5775MHz		11550	47.35	-26.65	74	44.28	38.8	19.25	54.98	-	-	P	H	
		17325	46.96	-21.24	68.2	39.62	38.08	25.14	55.88	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			11550	47.12	-26.88	74	44.05	38.8	19.25	54.98	-	-	P	V
			17325	48.04	-20.16	68.2	40.7	38.08	25.14	55.88	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line. 3. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only.													



Band 4 5725~5850MHz
WIFI 802.11ax HE80_Partial 484 (Band Edge @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5647.4	63.45	-4.75	68.2	46.85	33.29	12.91	29.6	106	84	P	H
		5697.6	68.24	-35.19	103.43	51.62	33.3	12.93	29.61	106	84	P	H
		5717.4	76.54	-33.53	110.07	59.81	33.4	12.94	29.61	106	84	P	H
		5722.6	76.3	-40.43	116.73	59.52	33.44	12.95	29.61	106	84	P	H
	*	5775	107.49	-	-	90.48	33.65	12.98	29.62	106	84	P	H
	*	5775	98.53	-	-	81.52	33.65	12.98	29.62	106	84	A	H
		5853.4	70.89	-43.56	114.45	53.7	34	12.82	29.63	106	84	P	H
		5858.4	71.12	-38.73	109.85	53.95	34	12.8	29.63	106	84	P	H
		5878	67.61	-35.36	102.97	50.51	34	12.74	29.64	106	84	P	H
802.11ax		5939.2	58.86	-9.34	68.2	41.89	34.08	12.54	29.65	106	84	P	H
HE80													H
Partial													H
484/65		5649.2	60.56	-7.64	68.2	43.95	33.3	12.91	29.6	396	96	P	V
CH 155		5654.4	63.44	-8.03	71.47	46.83	33.3	12.91	29.6	396	96	P	V
5775MHz		5719.8	70.91	-39.83	110.74	54.15	33.42	12.95	29.61	396	96	P	V
		5723.4	71.91	-46.64	118.55	55.13	33.44	12.95	29.61	396	96	P	V
	*	5775	105.98	-	-	88.97	33.65	12.98	29.62	396	96	P	V
	*	5775	96.84	-	-	79.83	33.65	12.98	29.62	396	96	A	V
		5854.2	68.07	-44.55	112.62	50.89	34	12.81	29.63	396	96	P	V
		5856.2	69.01	-41.45	110.46	51.83	34	12.81	29.63	396	96	P	V
		5876.2	67.59	-36.72	104.31	50.49	34	12.74	29.64	396	96	P	V
		5945	57.64	-10.56	68.2	40.68	34.09	12.52	29.65	396	96	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



WiFi Ant. 9+8	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE80 Partial 484/66 CH 155 5775MHz		5602.4	66.41	-1.79	68.2	49.92	33.2	12.88	29.59	104	82	P	H	
		5692.8	73.79	-26.1	99.89	57.16	33.3	12.93	29.6	104	82	P	H	
		5718	77.81	-32.43	110.24	61.07	33.41	12.94	29.61	104	82	P	H	
		5722.4	80.04	-36.23	116.27	63.27	33.43	12.95	29.61	104	82	P	H	
	*	5775	107.59	-	-	90.58	33.65	12.98	29.62	104	82	P	H	
	*	5775	98.42	-	-	81.41	33.65	12.98	29.62	104	82	A	H	
		5853.2	73.48	-41.42	114.9	56.29	34	12.82	29.63	104	82	P	H	
		5861	73.97	-35.15	109.12	56.81	34	12.79	29.63	104	82	P	H	
		5875	72.64	-32.56	105.2	55.53	34	12.75	29.64	104	82	P	H	
		5947.2	63.25	-4.95	68.2	46.3	34.09	12.51	29.65	104	82	P	H	
														H
														H
			5648.8	64.25	-3.95	68.2	47.64	33.3	12.91	29.6	371	88	P	V
			5694.6	70.05	-31.17	101.22	53.43	33.3	12.93	29.61	371	88	P	V
			5720	74.86	-35.94	110.8	58.1	33.42	12.95	29.61	371	88	P	V
			5720	74.86	-35.94	110.8	58.1	33.42	12.95	29.61	371	88	P	V
	*		5775	105.35	-	-	88.34	33.65	12.98	29.62	371	88	P	V
	*		5775	96.88	-	-	79.87	33.65	12.98	29.62	371	88	A	V
			5851.2	73.11	-46.35	119.46	55.92	34	12.82	29.63	371	88	P	V
			5861.4	72.06	-36.95	109.01	54.91	34	12.79	29.64	371	88	P	V
		5886	68.81	-28.22	97.03	51.74	34	12.71	29.64	371	88	P	V	
		5929.2	63.26	-4.94	68.2	46.28	34.06	12.57	29.65	371	88	P	V	
													V	
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Emission below 1GHz

5GHz WIFI 802.11ax HE40 Full (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
9+8		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.11ax HE40 Full LF		92.08	33.81	-9.69	43.5	49.55	14.82	1.74	32.3	-	-	P	H	
		158.04	32.83	-10.67	43.5	46.02	16.76	2.3	32.25	-	-	P	H	
		471.35	29.3	-16.7	46	34.26	23.6	3.84	32.4	-	-	P	H	
		896.21	38.88	-7.12	46	36.24	28.94	5.27	31.57	-	-	P	H	
		903	39.65	-6.35	46	36.82	29.06	5.29	31.52	-	-	P	H	
		940.83	34.91	-11.09	46	30.48	30.27	5.42	31.26	-	-	P	H	
														H
														H
														H
														H
														H
														H
			43.58	33.66	-6.34	40	47.44	17.37	1.14	32.29	-	-	P	V
			89.17	33.73	-9.77	43.5	49.86	14.45	1.72	32.3	-	-	P	V
			120.21	29.65	-13.85	43.5	42.44	17.53	1.95	32.27	-	-	P	V
			471.35	31.54	-14.46	46	36.5	23.6	3.84	32.4	-	-	P	V
			896.21	39.03	-6.97	46	36.39	28.94	5.27	31.57	-	-	P	V
			902.03	39.29	-6.71	46	36.49	29.04	5.29	31.53	-	-	P	V
														V
														V
													V	
													V	
													V	
													V	
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against limit line. The emission position marked as "-" means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only. 													



<TXBF Mode>

Band 4 - 5725~5850MHz

WIFI 802.11ax HE20_Full (Band Edge @ 3m)

WIFI Ant.	Note	Frequency	Level	Over Limit	Limit Line	Read Level	Antenna Factor	Path Loss	Preamp Factor	Ant Pos	Table Pos	Peak Avg.	Pol.	
9+8		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.11ax HE20 Full CH 149 5745MHz		5622	55.63	-12.57	68.2	39.09	33.24	12.89	29.59	100	61	P	H	
		5660	55.64	-19.99	75.63	39.03	33.3	12.91	29.6	100	61	P	H	
		5719.6	65.79	-44.9	110.69	49.03	33.42	12.95	29.61	100	61	P	H	
		5725	71.2	-51	122.2	54.41	33.45	12.95	29.61	100	61	P	H	
	*	5745	112.53	-	-	95.61	33.57	12.96	29.61	100	61	P	H	
	*	5745	102.72	-	-	85.8	33.57	12.96	29.61	100	61	A	H	
														H
														H
			5639.6	54.24	-13.96	68.2	37.66	33.28	12.9	29.6	111	175	P	V
			5679.4	54.94	-35.06	90	38.32	33.3	12.92	29.6	111	175	P	V
			5717.6	60.16	-49.97	110.13	43.42	33.41	12.94	29.61	111	175	P	V
			5724.8	68.58	-53.16	121.74	51.79	33.45	12.95	29.61	111	175	P	V
	*		5745	108.63	-	-	91.71	33.57	12.96	29.61	111	175	P	V
	*		5745	98.87	-	-	81.95	33.57	12.96	29.61	111	175	A	V
													V	
													V	



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5649.8	54.48	-13.72	68.2	37.87	33.3	12.91	29.6	101	62	P	H
		5694.4	54.01	-47.06	101.07	37.38	33.3	12.93	29.6	101	62	P	H
		5711	54.32	-53.96	108.28	37.62	33.37	12.94	29.61	101	62	P	H
		5720.6	54.09	-58.08	112.17	37.33	33.42	12.95	29.61	101	62	P	H
	*	5785	112.6	-	-	95.57	33.67	12.98	29.62	101	62	P	H
	*	5785	102.21	-	-	85.18	33.67	12.98	29.62	101	62	A	H
		5853.4	54.69	-59.76	114.45	37.5	34	12.82	29.63	101	62	P	H
		5863.2	54.68	-53.82	108.5	37.54	34	12.78	29.64	101	62	P	H
		5893.6	55.27	-36.13	91.4	38.22	34	12.69	29.64	101	62	P	H
		5926.8	55.57	-12.63	68.2	38.59	34.05	12.58	29.65	101	62	P	H
802.11ax													H
HE20 Full													H
CH 157		5629.4	54.56	-13.64	68.2	37.99	33.26	12.9	29.59	114	174	P	V
5785MHz		5690.2	54.43	-43.54	97.97	37.8	33.3	12.93	29.6	114	174	P	V
		5704.2	54.86	-51.52	106.38	38.2	33.33	12.94	29.61	114	174	P	V
		5723.6	53.57	-65.44	119.01	36.79	33.44	12.95	29.61	114	174	P	V
	*	5785	109.34	-	-	92.31	33.67	12.98	29.62	114	174	P	V
	*	5785	98.69	-	-	81.66	33.67	12.98	29.62	114	174	A	V
		5854.6	54.61	-57.1	111.71	37.43	34	12.81	29.63	114	174	P	V
		5867.6	54.26	-53.01	107.27	37.13	34	12.77	29.64	114	174	P	V
		5886	54.5	-42.53	97.03	37.43	34	12.71	29.64	114	174	P	V
		5947.4	54.83	-13.37	68.2	37.88	34.09	12.51	29.65	114	174	P	V
													V
													V



WiFi Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Full CH 165 5825MHz	*	5825	111.85	-	-	94.72	33.85	12.91	29.63	102	71	P	H	
	*	5825	103.55	-	-	86.42	33.85	12.91	29.63	102	71	A	H	
		5850.2	62.62	-59.12	121.74	45.42	34	12.83	29.63	102	71	P	H	
		5855.4	61.92	-48.77	110.69	44.74	34	12.81	29.63	102	71	P	H	
		5915.4	56.29	-18.99	75.28	39.29	34.03	12.61	29.64	102	71	P	H	
		5926.6	54.71	-13.49	68.2	37.73	34.05	12.58	29.65	102	71	P	H	
														H
														H
	*	5825	109.4	-	-	92.27	33.85	12.91	29.63	100	174	P	V	
	*	5825	98.48	-	-	81.35	33.85	12.91	29.63	100	174	A	V	
		5850	68	-54.2	122.2	50.8	34	12.83	29.63	100	174	P	V	
		5855.4	66.16	-44.53	110.69	48.98	34	12.81	29.63	100	174	P	V	
		5876.8	56.08	-47.78	103.86	38.98	34	12.74	29.64	100	174	P	V	
		5937.6	54.91	-13.29	68.2	37.94	34.08	12.54	29.65	100	174	P	V	
														V
													V	
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.													



Band 4 5725~5850MHz

WIFI 802.11ax HE20 Full (Harmonic @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Full CH 149 5745MHz		11490	48.05	-25.95	74	44.99	38.84	19.23	55.01	-	-	P	H	
		17235	47.82	-20.38	68.2	40.59	37.81	25.11	55.69	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			11490	46.75	-27.25	74	43.69	38.84	19.23	55.01	-	-	P	V
			17235	48.83	-19.37	68.2	41.6	37.81	25.11	55.69	-	-	P	V
														V
														V
														V
														V
														V
													V	
													V	
													V	
													V	



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE20 Full CH 165 5825MHz		11650	47.1	-26.9	74	44.05	38.7	19.3	54.95	-	-	P	H	
		17475	47.39	-20.81	68.2	39.93	38.45	25.22	56.21	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			11650	47.56	-26.44	74	44.51	38.7	19.3	54.95	-	-	P	V
			17475	47.4	-20.8	68.2	39.94	38.45	25.22	56.21	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only. 													



Band 4 5725~5850MHz
WIFI 802.11ax HE40_Full (Band Edge @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5648.4	65.93	-2.27	68.2	49.32	33.3	12.91	29.6	100	61	P	H
		5691.8	73.56	-25.59	99.15	56.93	33.3	12.93	29.6	100	61	P	H
		5703	77.46	-28.58	106.04	60.81	33.32	12.94	29.61	100	61	P	H
		5722.4	74.8	-41.47	116.27	58.03	33.43	12.95	29.61	100	61	P	H
	*	5755	110.39	-	-	93.43	33.61	12.97	29.62	100	61	P	H
	*	5755	99.69	-	-	82.73	33.61	12.97	29.62	100	61	A	H
		5850	69.48	-52.72	122.2	52.28	34	12.83	29.63	100	61	P	H
		5858	66.79	-43.17	109.96	49.62	34	12.8	29.63	100	61	P	H
		5886.6	66.87	-29.72	96.59	49.8	34	12.71	29.64	100	61	P	H
		5940.8	62.33	-5.87	68.2	45.37	34.08	12.53	29.65	100	61	P	H
802.11ax													H
HE40 Full													H
CH 151		5621	65.45	-2.75	68.2	48.91	33.24	12.89	29.59	100	178	P	V
5755MHz		5695.2	72.82	-28.84	101.66	56.2	33.3	12.93	29.61	100	178	P	V
		5719	76.08	-34.44	110.52	59.33	33.41	12.95	29.61	100	178	P	V
		5721.4	68.9	-45.09	113.99	52.13	33.43	12.95	29.61	100	178	P	V
	*	5755	105.94	-	-	88.98	33.61	12.97	29.62	100	178	P	V
	*	5755	95.13	-	-	78.17	33.61	12.97	29.62	100	178	A	V
		5853.4	55.93	-58.52	114.45	38.74	34	12.82	29.63	100	178	P	V
		5861	55.83	-53.29	109.12	38.67	34	12.79	29.63	100	178	P	V
		5884	56.72	-41.8	98.52	39.64	34	12.72	29.64	100	178	P	V
		5933.6	55.79	-12.41	68.2	38.81	34.07	12.56	29.65	100	178	P	V
													V
													V



WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5640.6	63.1	-5.1	68.2	46.52	33.28	12.9	29.6	100	62	P	H
		5697.4	70.03	-33.25	103.28	53.41	33.3	12.93	29.61	100	62	P	H
		5715.6	70.84	-38.73	109.57	54.12	33.39	12.94	29.61	100	62	P	H
		5720.8	68.63	-43.99	112.62	51.87	33.42	12.95	29.61	100	62	P	H
	*	5795	110.26	-	-	93.2	33.69	12.99	29.62	100	62	P	H
	*	5795	99.86	-	-	82.8	33.69	12.99	29.62	100	62	A	H
		5850.4	73.31	-47.98	121.29	56.11	34	12.83	29.63	100	62	P	H
		5859.8	71.84	-37.61	109.45	54.67	34	12.8	29.63	100	62	P	H
		5880.4	73.19	-28	101.19	56.1	34	12.73	29.64	100	62	P	H
		5943	64.9	-3.3	68.2	47.93	34.09	12.53	29.65	100	62	P	H
802.11ax													H
HE40 Full													H
CH 159		5600.6	55.53	-12.67	68.2	39.04	33.2	12.88	29.59	100	173	P	V
5795MHz		5686.4	58.91	-36.26	95.17	42.28	33.3	12.93	29.6	100	173	P	V
		5718.4	64.82	-45.53	110.35	48.07	33.41	12.95	29.61	100	173	P	V
		5723.6	64.32	-54.69	119.01	47.54	33.44	12.95	29.61	100	173	P	V
	*	5795	106.4	-	-	89.34	33.69	12.99	29.62	100	173	P	V
	*	5795	96.46	-	-	79.4	33.69	12.99	29.62	100	173	A	V
		5850.8	66.64	-53.74	120.38	49.45	34	12.82	29.63	100	173	P	V
		5858	66.31	-43.65	109.96	49.14	34	12.8	29.63	100	173	P	V
		5910.2	60.11	-19.01	79.12	43.1	34.02	12.63	29.64	100	173	P	V
		5927.4	57.87	-10.33	68.2	40.89	34.05	12.58	29.65	100	173	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ax HE40_Full (Harmonic @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE40 Full CH 151 5755MHz		11510	47.66	-26.34	74	44.62	38.8	19.24	55	-	-	P	H	
		17265	48.15	-20.05	68.2	40.89	37.9	25.11	55.75	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			11510	47.36	-26.64	74	44.32	38.8	19.24	55	-	-	P	V
			17265	48.16	-20.04	68.2	40.9	37.9	25.11	55.75	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	



WiFi Ant. 9+8	Note	Frequency (MHz)	Level (dBµV/m)	Over Limit (dB)	Limit Line (dBµV/m)	Read Level (dBµV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
802.11ax HE40 Full CH 159 5795MHz		11590	47.76	-26.24	74	44.65	38.8	19.28	54.97	-	-	P	H
		17385	47.81	-20.39	68.2	40.39	38.26	25.17	56.01	-	-	P	H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
													H
	CH 159 5795MHz		11590	46.87	-27.13	74	43.76	38.8	19.28	54.97	-	-	P
		17385	47.52	-20.68	68.2	40.1	38.26	25.17	56.01	-	-	P	V
													V
													V
													V
													V
													V
													V
													V
													V
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only. 												



Band 4 5725~5850MHz
WIFI 802.11ax HE80_Full (Band Edge @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)
		5647	67.02	-1.18	68.2	50.42	33.29	12.91	29.6	100	60	P	H
		5698.6	73.01	-31.16	104.17	56.39	33.3	12.93	29.61	100	60	P	H
		5713.4	74.47	-34.48	108.95	57.76	33.38	12.94	29.61	100	60	P	H
		5723	74.46	-43.18	117.64	57.68	33.44	12.95	29.61	100	60	P	H
	*	5775	107.68	-	-	90.67	33.65	12.98	29.62	100	60	P	H
	*	5775	97.37	-	-	80.36	33.65	12.98	29.62	100	60	A	H
		5851.2	70.81	-48.65	119.46	53.62	34	12.82	29.63	100	60	P	H
		5857.2	78.78	-31.4	110.18	61.61	34	12.8	29.63	100	60	P	H
		5882.6	72.14	-27.42	99.56	55.06	34	12.72	29.64	100	60	P	H
		5925.8	63.71	-4.49	68.2	46.73	34.05	12.58	29.65	100	60	P	H
802.11ax													H
HE80 Full													H
CH 155		5620.2	65.54	-2.66	68.2	49	33.24	12.89	29.59	100	175	P	V
5775MHz		5695.8	75.53	-26.57	102.1	58.91	33.3	12.93	29.61	100	175	P	V
		5716.2	74.17	-35.57	109.74	57.44	33.4	12.94	29.61	100	175	P	V
		5724	75.16	-44.76	119.92	58.38	33.44	12.95	29.61	100	175	P	V
	*	5775	105.02	-	-	88.01	33.65	12.98	29.62	100	175	P	V
	*	5775	93.85	-	-	76.84	33.65	12.98	29.62	100	175	A	V
		5853.4	67.1	-47.35	114.45	49.91	34	12.82	29.63	100	175	P	V
		5868	77.55	-29.61	107.16	60.42	34	12.77	29.64	100	175	P	V
		5892.6	69.81	-22.33	92.14	52.76	34	12.69	29.64	100	175	P	V
		5929.8	61.5	-6.7	68.2	44.52	34.06	12.57	29.65	100	175	P	V
													V
													V
Remark	1. No other spurious found. 2. All results are PASS against Peak and Average limit line.												



Band 4 5725~5850MHz

WIFI 802.11ax HE80_Full (Harmonic @ 3m)

WIFI Ant. 9+8	Note	Frequency (MHz)	Level (dBμV/m)	Over Limit (dB)	Limit Line (dBμV/m)	Read Level (dBμV)	Antenna Factor (dB/m)	Path Loss (dB)	Preamp Factor (dB)	Ant Pos (cm)	Table Pos (deg)	Peak Avg. (P/A)	Pol. (H/V)	
802.11ax HE80 Full CH 155 5775MHz		11550	47.01	-26.99	74	43.94	38.8	19.25	54.98	-	-	P	H	
		17325	48.49	-19.71	68.2	41.15	38.08	25.14	55.88	-	-	P	H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
													H	
			11550	46.7	-27.3	74	43.63	38.8	19.25	54.98	-	-	P	V
			17325	48.53	-19.67	68.2	41.19	38.08	25.14	55.88	-	-	P	V
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
													V	
Remark	<ol style="list-style-type: none"> No other spurious found. All results are PASS against Peak and Average limit line. The emission position marked as "-" means no suspected emission found with sufficient margin against limit line or noise floor only. 													



Emission below 1GHz

5GHz WIFI 802.11ax HE80 Full (LF @ 3m)

WIFI	Note	Frequency	Level	Over	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.	
Ant.				Limit	Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.		
9+8		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)	
802.11ax HE80 Full LF		92.08	32.95	-10.55	43.5	48.69	14.82	1.74	32.3	-	-	P	H	
		158.04	32.89	-10.61	43.5	46.08	16.76	2.3	32.25	-	-	P	H	
		828.31	38.26	-7.74	46	36.79	28.5	5.05	32.08	-	-	P	H	
		896.21	38.44	-7.56	46	35.8	28.94	5.27	31.57	-	-	P	H	
		903.97	35	-11	46	32.14	29.08	5.29	31.51	-	-	P	H	
		957.32	34.84	-11.16	46	29.72	30.79	5.47	31.14	-	-	P	H	
														H
														H
														H
														H
														H
														H
			43.58	33.15	-6.85	40	46.93	17.37	1.14	32.29	-	-	P	V
			90.14	33.52	-9.98	43.5	49.49	14.6	1.73	32.3	-	-	P	V
			120.21	31.47	-12.03	43.5	44.26	17.53	1.95	32.27	-	-	P	V
			471.35	31.05	-14.95	46	36.01	23.6	3.84	32.4	-	-	P	V
			896.21	38.73	-7.27	46	36.09	28.94	5.27	31.57	-	-	P	V
			936.95	34.54	-11.46	46	30.31	30.11	5.41	31.29	-	-	P	V
														V
														V
													V	
													V	
													V	
													V	

Remark

- No other spurious found.
- All results are PASS against limit line.
- The emission position marked as "-" means no suspected emission found and emission level has at least 6dB margin against limit or emission is noise floor only.



Note symbol

*	Fundamental Frequency which can be ignored. However, the level of any unwanted emissions shall not exceed the level of the fundamental frequency.
!	Test result is over limit line.
P/A	Peak or Average
H/V	Horizontal or Vertical



A calculation example for radiated spurious emission is shown as below:

WIFI	Note	Frequency	Level	Over Limit	Limit	Read	Antenna	Path	Preamp	Ant	Table	Peak	Pol.
Ant.					Line	Level	Factor	Loss	Factor	Pos	Pos	Avg.	
9+8		(MHz)	(dBμV/m)	(dB)	(dBμV/m)	(dBμV)	(dB/m)	(dB)	(dB)	(cm)	(deg)	(P/A)	(H/V)
802.11a CH 149 5745MHz		5650	55.45	-12.75	68.2	54.51	32.22	4.58	35.86	103	308	P	H

1. Path Loss(dB) = Cable loss(dB) + Filter loss(dB) + Attenuator loss(dB)
2. Level(dBμV/m) = Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
3. Over Limit(dB) = Level(dBμV/m) – Limit Line(dBμV/m)

For Peak Limit @ 5650MHz:

1. Level(dBμV/m)
= Antenna Factor(dB/m) + Path Loss(dB) + Read Level(dBμV) - Preamp Factor(dB)
= 32.22(dB/m) + 4.58(dB) + 54.51(dBμV) – 35.86 (dB)
= 55.45 (dBμV/m)
2. Over Limit(dB)
= Level(dBμV/m) – Limit Line(dBμV/m)
= 55.45(dBμV/m) – 68.2(dBμV/m)
= -12.75 (dB)

Both peak and average measured complies with the limit line, so test result is “PASS”.



Appendix C. Radiated Spurious Emission Plots



Test Engineer :	Andy Yang, Karl Hou and Wilson Wu	Temperature :	20~25°C
		Relative Humidity :	50~60%

<CDD Mode>

Band 4 - 5725~5850MHz
WIFI 802.11a (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
9+8	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(04)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH149 5745MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
9+8	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH157 5785MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
9+8	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11a CH165 5825MHz	
9+8	Vertical	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



Band 4 5725~5850MHz
WIFI 802.11ax HE20 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Date: 2022.03.05 PEAK_BE(84)_16-24</p> <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Date: 2022.03.05 PEAK(UNII)_3m</p> <p>Site : 03CH16-HY Condition : PEAK(UNII)_3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(U)0 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
9+8	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(U8) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site :03CH16-HY Condition :PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL :RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site :03CH16-HY Condition :PEAK(U16) 3m 91200_02114_210804 VERTICAL :RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





Band 4 5725~5850MHz
WIFI 802.11ax HE20 Partial 106 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/53 CH149 5745MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Date: 2022.03.08 PEAK_BE(045_76.32)</p> <p>Site : 03CH16-HY Condition : PEAK_BE(04)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Date: 2022.03.08 PEAK(UNB)_16-24</p> <p>Site : 03CH16-HY Condition : PEAK(UNB)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/53 CH149 5745MHz	
9+8	Vertical	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/54 CH165 5825MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(U8) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Partial 106/54 CH165 5825MHz	
9+8	Vertical	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(U8) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>



Band 4 5725~5850MHz
WIFI 802.11ax HE40 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
9+8	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full HT40 CH159 5795MHz	
9+8	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(U1) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






Band 4 5725~5850MHz
WIFI 802.11ax HE40 Partial 242 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH151 5755MHz	
9+8	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(LIN) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/61 CH151 5755MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Partial 242/62 CH159 5795MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



Band 4 5725~5850MHz
WIFI 802.11ax HE80 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Date: 2022-03-05 PEAK_BE(B4)_16-24</p> <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Date: 2022-03-05 PEAK(LINB) WFO: 51</p> <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Date: 2022-03-05 PEAK_BE(B4)_16-24</p> <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






Band 4 5725~5850MHz
WIFI 802.11ax HE80 Partial 484 (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH155 5775MHz	
9+8	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/65 CH155 5775MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(U8) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/66 CH155 5775MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Partial 484/66 CH155 5775MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank





Band 4 - 5725~5850MHz
WIFI 802.11a (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH149 5745MHz	
9+8	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 9120D_02114_210804 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 9120D_02114_210804 VERTICAL Detector : Peak</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH157 5785MHz	
9+8	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 VERTICAL Detector : Peak</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11a CH165 5825MHz	
9+8	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 VERTICAL Detector : Peak</p>





**Band 4 5725~5850MHz
WIFI 802.11ax HE20 Full (Harmonic @ 3m)**

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
9+8	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-FY Condition : PEAK(UNII) 3m 9120D_02114_210804 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH16-FY Condition : PEAK(UNII) 3m 9120D_02114_210804 VERTICAL Detector : Peak</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
9+8	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 VERTICAL Detector : Peak</p>





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
9+8	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 VERTICAL Detector : Peak</p>



**Band 4 5725~5850MHz
WIFI 802.11ax HE40 Full (Harmonic @ 3m)**

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
9+8	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-FY Condition : PEAK(UNII) 3m 9120D_02114_210804 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH16-FY Condition : PEAK(UNII) 3m 9120D_02114_210804 VERTICAL Detector : Peak</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
9+8	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 VERTICAL Detector : Peak</p>



**Band 4 5725~5850MHz
WIFI 802.11ax HE80 Full (Harmonic @ 3m)**

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
9+8	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-FY Condition : PEAK(UNII) 3m 9120D_02114_210804 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH16-FY Condition : PEAK(UNII) 3m 9120D_02114_210804 VERTICAL Detector : Peak</p>



Emission below 1GHz
5GHz WIFI 802.11ax HE40 Full (LF @ 3m)

Table with 2 columns: Horizontal and Vertical. Each column contains a spectral plot showing Level (dBm/100kHz) vs Frequency (MHz) from 50 to 1000 MHz. The plots show a blue signal line and a red limit line. Metadata includes Site: 03CH16-HY, Condition: QP 3m BIL06_47020_211009, and Detector: Peak.

QP / Peak





<TXBF Mode>




Band 4 - 5725~5850MHz
WIFI 802.11ax HE20 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
9+8	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 9120D_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(U)B 3m 9120D_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNII) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>





Band 4 5725~5850MHz
WIFI 802.11ax HE40 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
9+8	Horizontal	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(LIN) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank






WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full HT40 CH159 5795MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(UNIT) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(84)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
9+8	Vertical	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(U8) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank



Band 4 5725~5850MHz
WIFI 802.11ax HE80 Full (Band Edge @ 3m)

WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
9+8	Horizontal	Fundamental
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	 <p>Site : 03CH16-HY Condition : PEAK(LUNII) 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	 <p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 HORIZONTAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank





WIFI	Band 4 5725~5850MHz Band Edge @ 3m	
ANT	802.11ax HE80 Full CH155 5775MHz	
9+8	Vertical	Fundamental
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	<p>Site : 03CH16-HY Condition : PEAK(U8) 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>
Peak	<p>Site : 03CH16-HY Condition : PEAK_BE(B4)_16-24 3m 91200_02114_210804 VERTICAL : RBW:1000.000KHz VBW:3000.000KHz SWT:Auto</p>	Left blank





Band 4 - 5725~5850MHz
WIFI 802.11ax HE20 Full (Harmonic @ 3m)

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH149 5745MHz	
9+8	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 9120D_02114_210804 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 9120D_02114_210804 VERTICAL Detector : Peak</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH157 5785MHz	
9+8	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 VERTICAL Detector : Peak</p>





WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE20 Full CH165 5825MHz	
9+8	Horizontal	Vertical
<p>Peak</p> <p>Avg.</p>	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 VERTICAL Detector : Peak</p>



**Band 4 5725~5850MHz
WIFI 802.11ax HE40 Full (Harmonic @ 3m)**

WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Full CH151 5755MHz	
9+8	Horizontal	Vertical
Peak Avg.	<p>Site : 03CH16-FY Condition : PEAK(UNII) 3m 9120D_02114_210804 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH16-FY Condition : PEAK(UNII) 3m 9120D_02114_210804 VERTICAL Detector : Peak</p>



WIFI	Band 4 5725~5850MHz Harmonic @ 3m	
ANT	802.11ax HE40 Full CH159 5795MHz	
9+8	Horizontal	Vertical
Peak Avg.	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 HORIZONTAL Detector : Peak</p>	 <p>Site : 03CH16-HY Condition : PEAK(LINII) 3m 91200_02114_210804 VERTICAL Detector : Peak</p>



Band 4 5725~5850MHz
WIFI 802.11ax HE80 Full (Harmonic @ 3m)

Table with 4 columns: WIFI, ANT, 9+8, and two measurement plots (Horizontal and Vertical). The plots show Level (dBuV/m) vs Frequency (MHz) with Peak and Avg. markers.



Emission below 1GHz
5GHz WIFI 802.11ax HE80 Full (LF @ 3m)

WIFI	5GHz WIFI	
ANT	802.11ax HE80 Full LF	
9+8	Horizontal	Vertical
QP / Peak	<p>Site : 03CH16-HY Condition : QP 3m BIL06_47020_211009 HORIZONTAL Detector : Peak</p>	<p>Site : 03CH16-HY Condition : QP 3m BIL06_47020_211009 VERTICAL Detector : Peak</p>




Appendix D. Duty Cycle Plots

<CDD Mode>

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
9+8	802.11a	98.52	-	-	10Hz
9+8	5GHz 802.11ax HE20 Full RU	99.47	-	-	10Hz
9+8	5GHz 802.11ax HE20 106 RU	99.58	-	-	10Hz
9+8	5GHz 802.11ax HE40 Full RU	99.22	-	-	10Hz
9+8	5GHz 802.11ax HE40 242 RU	99.27	-	-	10Hz
9+8	5GHz 802.11ax HE80 Full RU	98.43	-	-	10Hz
9+8	5GHz 802.11ax HE80 484 RU	98.94	-	-	10Hz

MIMO <Ant. 9+8>






802.11ax HE20 106 RU



802.11ax HE40 Full RU




802.11ax HE40 242 RU



5GHz 802.11ax HE80 Full RU







<TXBF Mode>

Antenna	Band	Duty Cycle(%)	T(us)	1/T(kHz)	VBW Setting
9+8	5GHz 802.11ax HE20	96.71	2940	0.34	1kHz
9+8	5GHz 802.11ax HE40	97.09	3670	0.27	300Hz
9+8	5GHz 802.11ax HE80	96.01	3850	0.26	300Hz

MIMO <Ant. 9+8>

