

# RF EXPOSURE INFORMATION

### 1. MPE Limits

The limit for Maximum Permissible Exposure (MPE), specified in FCC §1.1310, is listed in Table 1 According to FCC §1.1310: the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency(RF) radiation as specified in §1.1307(b).

Table1. Limits for Maximum

Frequency	Electric Field	Magnetic Field	Power Density	Average Time
Range (MHz)	Strength (V/m)	Strength (A/m)	(mW/cm <sup>2</sup> )	(Minutes)
(A) Limits For Occupational / Control Exposures (f= frequency)				
30-300	61.4	0.163	1.0	6
300-1500				6
1500-100,000				6
(B) Limits For General Population / Uncontrolled Exposure (f=frequency)				
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

### **EUT** information

Type of equipment : Quad band GSM/GPRS Vehicle Tracker

Model Name : ST340LC

FCC ID : WA2ST340LC

Tx Frequency Band : 824.2 ~ 848.8 MHz (GSM850)

1850.2 ~ 1909.8 MHz(GMS1900)

GPRS Multi-slot class: 10

### **Procedure**

The procedure used to determine the RF power density was based upon a calculation for determining compliance with the MPE requirements.

The power generated by each transmitter used in this was initially measured as a ERP (EIRP). The power density level is calculated at a distance of 20 cm. And Minimum distance is also calculated.

Tel.: +82-31-5000-133

Fax.: +82-31-5000-147

MPE calculations are calculated under Maximum Power condition in each band.

FP-204-03-01



## **Formula**

 $P_d = (ERP) / (4\pi r^2)$ 

Where,

P<sub>d</sub>= Power Density (mW/cm<sup>2</sup>)

 $\pi = 3.1416$ 

r=distance between observation point and centre of the radiator(cm)

## **Calculated MPE**

The power density limit for General Population/Uncontrolled Exposure at each frequency is determined based on the information in Table 1. MPE calculations are calculated under Maximum Power condition in each band.

Table 2. GSM850 Calculated MPE Data

Frequency	824.2 MHz	
Limit	0.549 mW/cm <sup>2</sup>	
Distance (cm), R	20 cm	
Max output Power	32.30 dBm (1,698.2 mW)	
Power Density (mW/cm²)	0.338	
Minimum Distance	15.67 cm	

Table 3, GSM1900 Calculated MPE Data

Table 5. Golvi 1900 Calculated IVII L Data		
Frequency	1909.8 MHz	
Limit	1 mW/cm <sup>2</sup>	
Distance (cm), R	20 cm	
Max output Power	28.90 dBm (776.2 mW)	
Power Density (mW/cm²)	0.153	
Minimum Distance	7.86 cm	

nttp://www.kti.re.kr FP-204-03-01 Tel.: +82-31-5000-133
Fax.: +82-31-5000-147