

Table D 4.1

IA-9 Link Budget

Ku-band Digital

Wanted System Orbital Location -97 deg
 Interfering System Orbital Location -99 deg and 95W (FCC allocation)
 Minimum Orbital Separation (Geo-centric) 1.90 deg ; Note: the calculations take topocentric advantage into account

Uplink	I, psd	-47	dBW/hz	Tx F	14.000	GHz
Dnlink	I, eirpd	-20	dBW/hz	Rx F	11.700	GHz

Carrier Type	64K, 8PSK, R2/3 RS						64K, QPSK, R1/2 RS					
Transmit ES Location	CONUS	CONUS	Mexico	Mexico	Conus	Conus	CONUS	CONUS	Mexico	Mexico	Conus	Conus
Receive ES Location	CONUS	CONUS	Conus	Conus	Mexico	Mexico	CONUS	CONUS	Conus	Conus	Mexico	Mexico
Tx ES Size at SA	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
Transmit ES Peak gain	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2	54.2
RX ES Size	1.2	12.0	1.2	12.0	3.0	12.0	0.9	12.0	0.9	12.0	1.2	12.0
Receive ES Gain	41.1	61.1	41.1	61.1	49.1	61.1	38.6	61.1	38.6	61.1	41.1	61.1
Receive ES G/T (Temp=105K)	20.9	40.9	20.9	40.9	28.9	40.9	18.4	40.9	18.4	40.9	20.9	40.9
Carrier Type	64KR2/3	64KR2/3	64KR2/3	64KR2/3	64KR2/3	64KR2/3	64KR1/2	64KR1/2	64KR1/2	64KR1/2	64KR1/2	64KR1/2
Occupied bandwidth per carrier (kHz)	34.9	34.9	34.9	34.9	34.9	34.9	69.7	69.7	69.7	69.7	69.7	69.7
Allocated bandwidth per carrier (kHz)	47.1	47.1	47.1	47.1	47.1	47.1	94.1	94.1	94.1	94.1	94.1	94.1
C/N Threshold	10.54	10.54	10.54	10.54	10.54	10.54	4.5	4.5	4.5	4.5	4.5	4.5
System Margin	2.1	5.0	1.3	5.0	4.9	5.0	2.9	5.0	2.6	5.0	2.6	5.0
C/N, Threshold + margin	12.64	15.54	11.84	15.54	15.44	15.54	7.43	9.53	7.13	9.53	7.13	9.53
Nominal e/s e.i.r.p. per carrier @ES(dBW)	49.6	43.1	49.6	47.7	49.6	43.5	52.6	39.7	52.6	44.3	52.6	39.8
TX ES PSD	-50.0	-56.5	-50.0	-51.9	-50.0	-56.1	-50.0	-62.9	-50.0	-58.3	-50.0	-62.8
ES eirp @ bp-- minimum (dBW)	46.2	39.7	41.2	39.3	46.2	40.1	49.2	36.3	44.2	35.9	49.2	36.4
Sat G/T at bp	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5	4.5
Sat G/T at e/s	1.1	1.1	-3.9	-3.9	1.1	1.1	1.1	1.1	-3.9	-3.9	1.1	1.1
Free space path loss (dB)	206.9	206.9	206.6	206.6	206.9	206.9	206.9	206.9	206.6	206.6	206.9	206.9
Input back off, dB	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Output back off dB	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
C/N uplink (dB)	27.0	20.5	22.3	20.4	27.0	20.9	27.0	14.1	22.3	14.0	27.0	14.2
X-pol interf:C/I -uplink (dB)-wanted system	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
X-pol interf:C/I -uplink (dB)-interfering ES	34.6	28.1	34.6	32.7	34.6	28.5	34.6	21.7	34.6	26.3	34.6	21.8
C/I - copol asi uplink (dB)	26.8	20.3	21.8	19.9	26.8	20.7	26.8	13.9	21.8	13.5	26.8	14.0
HPA IM at 10 deg el angle(limit: 21,c;10,Ku)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Satellite TWTA IM per carrier @ bp	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0
C/N+others, uplink	22.3	16.6	18.5	16.6	22.3	17.0	22.3	10.5	18.5	10.5	22.3	10.6
Downlink e.i.r.p. -bp (dBW)	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5	49.5
Downlink BP-BE difference	7	7	7	7	7	7	7	7	7	7	7	7
DL ES Pattern Advantage	5	5	5	5	0	0	5	5	5	5	0	0
Satellite e.i.r.p.d. per carrier (dBW)-tow es	-25.0	-28.5	-25.0	-28.5	-30.0	-33.5	-25.0	-28.5	-25.0	-28.5	-30.0	-33.5
Satellite e.i.r.p.d. per carrier (dBW)-bp	-23.0	-26.5	-23.0	-26.5	-23.0	-26.5	-23.0	-26.5	-23.0	-26.5	-23.0	-26.5
Satellite e.i.r.p. per carrier (dBW)-bp	22.4	18.9	22.4	18.9	22.4	18.9	25.4	21.9	25.4	21.9	25.4	21.9
Satellite e.i.r.p. per carrier (dBW)-ES	20.4	16.9	20.4	16.9	15.4	11.9	23.4	19.9	23.4	19.9	18.4	14.9
Free space path loss (dB)	205.3	205.3	205.0	205.0	205.3	205.3	205.3	205.3	205.0	205.0	205.3	205.3
Earth station pointing loss (dB)	0.30	0.3	0.3	0.3	0.3	0.3	0.30	0.3	0.3	0.3	0.3	0.3
C/N downlink towards BP (dB)	25.9	42.4	26.2	42.7	28.9	37.4	23.4	42.4	23.7	42.7	20.9	37.4
C/N downlink towards ES (dB)	23.9	40.4	24.2	40.7	21.9	30.4	21.4	40.4	21.7	40.7	13.9	30.4
C/N-thermal-total	22.2	20.5	20.2	20.4	20.7	20.5	20.3	14.1	19.0	14.0	13.7	14.1
Interference & Margins:												
C/I Co-polar downlink interference d/I(dB)	20.6	38.2	20.6	38.2	24.3	33.2	11.4	38.2	11.4	38.2	15.6	33.2
C/I X-polar external interference d/I (dB)	16.1	35.6	16.1	35.6	21.8	30.6	12.3	35.6	12.3	35.6	11.1	30.6
Downlink C/(Nth +others) composite with ASI dn	14.3	32.9	14.3	32.9	17.8	26.5	8.6	32.9	8.6	32.9	8.3	26.5
Total C/(Nth +) composite with ASI tot	13.6	16.5	12.9	16.5	16.5	16.5	8.4	10.5	8.2	10.5	8.2	10.5
Total C/(Nth +others) w/o ASI	21.3	19.6	19.6	19.6	20.1	19.6	19.7	13.9	18.5	13.8	13.6	13.9
Other losses(terrestrial, OBE, etc..)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Available C/N	12.6	15.5	11.9	15.5	15.5	15.5	7.4	9.5	7.2	9.5	7.2	9.5
C/N Margin	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0