

**Table 5 – Link Budget for Voice-Rate Forward Link to  
Personal Accessory User Terminal using CDMA**

<b>Representative Forward Link Budget</b>		
UT Type		Personal Accessory
Carrier Type		CDMA
<b><u>General Parameters</u></b>	<b>Unit</b>	
E/S elevation angle	deg	28.0
Minimum user elevation angle	deg	20.0
Uplink range	km	38792
Downlink range	km	39554
Uplink frequency	GHz	29.625
Downlink frequency	GHz	2.200
Bandwidth/carrier	kHz	1250.0
<b><u>Uplink</u></b>		
Uplink E/S antenna diameter	m	11.0
Uplink E/S antenna peak gain	dBi	68.1
E/S antenna pointing error	dB	0.5
Clear-sky uplink EIRP	dBW	30.0
Rain faded uplink EIRP	dBW	46.8
Free space loss	dB	213.7
Rain attenuation	dB	16.8
Satellite antenna pointing error	dB	0.3
Satellite antenna receive system noise temp.	dB-K	30.9
Effective satellite antenna G/T	dB/K	24.8
Uplink C/N <sub>0</sub>	dBHz	69.2
Uplink C/IM <sub>0</sub>	dBHz	77.4
Uplink C/I <sub>0ASI</sub>	dBHz	67.9
Uplink C/I <sub>0 Intra-system</sub>	dBHz	69.2
Aggregate uplink C/I <sub>0</sub>	dBHz	65.5
<b><u>Downlink</u></b>		
Satellite EIRP/carrier	dBW	33.2
Free space loss	dB	191.2
Atmospheric loss	dB	0.1
User terminal antenna gain	dB	3.0
User terminal system noise temperature	dB-K	25.0
User terminal G/T	dB/K	-22.0
Downlink propagation margin	dB	5.0
Downlink C/N <sub>0</sub>	dBHz	43.5
Downlink C/IM <sub>0</sub>	dBHz	55.2
Downlink C/I <sub>0 Intra-system</sub>	dBHz	50.0
Downlink C/I <sub>0 ext</sub>	dBHz	53.5
Aggregate downlink C/I <sub>0</sub>	dBHz	48.4
<b><u>End-to-End Performance</u></b>		
End-to-end C/N <sub>0</sub>	dBHz	43.5
End-to-end aggregate C/I <sub>0</sub>	dBHz	48.3
End-to-end C/IM <sub>0</sub>	dBHz	55.1
Total aggregate C/(N <sub>0</sub> +I <sub>0</sub> +IM <sub>0</sub> )	dBHz	42.0
Total aggregate C/(N+I+IM)	dB	-18.9
Required C/N	dB	-18.9
System Margin	dB	0.0