

IA-5-77W Link Budget

-77 deg

Equivalent

-79 deg

and 74W (FCC allocation)

1.90 deg ; Note: the calculations take topocentric advantage into account

Uplink	I, psd	-48.7	dBW/hz	Tx F	14.000	GHz
Dnlink	I, eirpd	-21.7	dBW/hz	Rx F	11.700	GHz

Carrier Type	64K, 8PSK, R2/3 RS						64K, QPSK, R1/2 RS					
Transmit ES Location	CONUS	CONUS	Mexico	Mexico	Conus	Conus	CONUS	CONUS	Mexico	Mexico	Conus	Conus
Receive ES Location	CONUS	CONUS	Conus	Conus	Mexico	Mexico	CONUS	CONUS	Conus	Conus	Mexico	Mexico
Tx ES Size at SA	2.4	2.4	2.4	2.4	2.4	2.4	1.8	1.8	1.8	1.8	1.8	1.8
Transmit ES Peak gain	48.7	48.7	48.7	48.7	48.7	48.7	46.2	46.2	46.2	46.2	46.2	46.2
RX ES Size	2.4	12.0	2.4	12.0	2.4	12.0	1.2	12.0	1.2	12.0	1.2	12.0
Receive ES Gain	47.2	61.1	47.2	61.1	47.2	61.1	41.1	61.1	41.1	61.1	41.1	61.1
Receive ES G/T (Temp=105K)	26.9	40.9	26.9	40.9	26.9	40.9	20.9	40.9	20.9	40.9	20.9	40.9
Carrier Type	64KR2/3	64KR2/3	64KR2/3	64KR2/3	64KR2/3	64KR2/3	64KR1/2	64KR1/2	64KR1/2	64KR1/2	64KR1/2	64KR1/2
Occupied bandwidth per carrier (kHz)	34.9	34.9	34.9	34.9	34.9	34.9	69.7	69.7	69.7	69.7	69.7	69.7
Allocated bandwidth per carrier (kHz)	47.1	47.1	47.1	47.1	47.1	47.1	94.1	94.1	94.1	94.1	94.1	94.1
C/N Threshold	10.54	10.54	10.54	10.54	10.54	10.54	4.5	4.5	4.5	4.5	4.5	4.5
System Margin	5.0	5.0	4.1	4.9	3.0	5.0	5.0	5.0	5.0	5.0	2.3	5.0
Other losses(terrestrial, OBE, etc.)	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0	1.0
Clear Sky C/N	16.5	16.5	15.6	16.4	14.5	16.5	10.5	10.5	10.5	10.5	7.8	10.5
Nominal e/s e.i.r.p. per carrier @ES(dBW)	42.9	41.8	44.1	44.1	44.1	42.0	40.3	38.5	42.8	40.9	41.1	38.5
TX ES PSD	-51.2	-52.3	-50.0	-50.0	-50.0	-52.1	-54.3	-56.1	-51.8	-53.7	-53.5	-56.1
ES eirp @ bp- minimum (dBW)	41.1	40.0	39.5	39.5	42.3	40.2	38.5	36.7	38.2	36.3	39.3	36.7
Sat G/T at bp	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7	2.7
Sat G/T at e/s	0.9	0.9	-1.9	-1.9	0.9	0.9	0.9	0.9	-1.9	-1.9	0.9	0.9
Free space path loss (dB)	207.0	207.0	206.7	206.7	207.0	207.0	207.0	207.0	206.7	206.7	207.0	207.0
Input back off, dB	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0	5.0
Output back off dB	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0	3.0
C/N uplink (dB)	20.1	19.0	18.7	18.7	21.3	19.2	14.5	12.7	14.4	12.5	15.3	12.7
X-pol inter:C/I -uplink (dB)-wanted system	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0	30.0
X-pol inter:C/I -uplink (dB)-interfering ES	29.6	28.5	30.8	30.8	30.8	28.7	24.0	22.2	26.5	24.6	24.8	22.2
C/I - oopol asi uplink (dB)	23.4	22.3	21.8	21.8	24.6	22.5	17.8	16.0	17.5	15.6	18.6	16.0
HPA IM at 10 deg e angle(limit: 21,c;10,Ku)	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0	10.0
Satellite TWTA IM per carrier @ bp	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0	-21.0
C/N++others, uplink	17.7	16.6	16.5	16.5	18.8	16.8	12.4	10.6	12.4	10.5	13.1	10.6
Downlink e.i.r.p. -bp (dBW)	50.8	50.8	50.8	50.8	50.8	50.8	50.8	50.8	50.8	50.8	50.8	50.8
Downlink BP-BE difference	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1	7.1
DL ES Pattern Advantage	4.6	4.6	4.6	4.6	0	0	4.6	4.6	4.6	4.6	0	0
Satellite e.i.r.p.d. per carrier (dBW)-tow es	-25.5	-27.7	-25.5	-27.7	-30.1	-32.3	-25.5	-27.7	-25.5	-27.7	-30.1	-32.3
Satellite e.i.r.p.d. per carrier (dBW)-bp	-23.0	-25.2	-23.0	-25.2	-23.0	-25.2	-23.0	-25.2	-23.0	-25.2	-23.0	-25.2
Satellite e.i.r.p. per carrier (dBW)-bp	22.4	20.2	22.4	20.2	22.4	20.2	25.4	23.2	25.4	23.2	25.4	23.2
Satellite e.i.r.p. per carrier (dBW)-ES	19.9	17.7	19.9	17.7	15.3	13.1	22.9	20.7	22.9	20.7	18.3	16.1
Free space path loss (dB)	205.4	205.4	205.1	205.1	205.4	205.4	205.4	205.4	205.1	205.1	205.4	205.4
Earth station pointing loss (dB)	0.30	0.3	0.3	0.3	0.3	0.3	0.30	0.3	0.3	0.3	0.3	0.3
C/N downlink towards BP (dB)	31.4	43.2	31.7	43.5	26.8	38.6	25.4	43.2	25.7	43.5	20.8	38.6
C/N downlink towards ES (dB)	28.9	40.7	29.2	41.0	19.7	31.5	22.9	40.7	23.2	41.0	13.7	31.5
C/N-thermal-total	19.5	18.9	18.3	18.7	17.4	18.9	13.9	12.6	13.9	12.5	11.4	12.6
Interference & Margins:												
C/I Co-polar downlink interference d/I(dB)	28.5	40.8	28.5	40.8	23.9	36.2	21.8	40.8	21.8	40.8	17.2	36.2
C/I X-polar external interference d/I (dB)	25.9	38.1	25.9	38.1	21.3	33.5	17.2	38.1	17.2	38.1	12.6	33.5
Downlink C/(Nth ++others) composite with ASI dn	22.8	34.9	22.9	35.0	16.6	28.6	15.1	34.9	15.2	35.0	9.4	28.6
Total C/(Nth ++others) composite with ASI tot	16.5	16.6	15.6	16.4	14.5	16.5	10.5	10.6	10.6	10.5	7.8	10.5
Total C/(Nth ++others) w/o ASI	19.0	18.4	18.0	18.2	17.1	18.4	13.7	12.5	13.7	12.4	11.3	12.5
C/N Margin	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0