

**S1. GENERAL INFORMATION** Complete for all satellite applications.

a. Space Station or Satellite Network Name: MSV-1		e. Estimated Date of Placement into Service: 5/25/2010		i. Will the space station(s) operate on a Common Carrier Basis: N	
b. Construction Commencement Date: 5/25/2008		f. Estimated Lifetime of Satellite(s): 15 Years		j. Number of transponders offered on a common carrier basis:	
c. Construction Completion Date: 1/25/2010		g. Total Number of Transponders: 1		k. Total Common Carrier Transponder Bandwidth: MHz	
d1. Est Launch Date Begin: 2/25/2010	d2. Est Launch Date End: 4/25/2010	h. Total Transponder Bandwidth (no. transponders x Bandwidth) 34 MHz		i. Orbit Type: Mark all boxes that apply: <input checked="" type="checkbox"/> GSO <input type="checkbox"/> NGSO	

**S2. OPERATING FREQUENCY BANDS** Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper  
Also indicate the nature of service(s) for each frequency band.

Frequency Band Limits				e. T/R Mode	f. Nature of Service(s): List all that apply to this band
Lower Frequency (.Hz)		Upper Frequency (.Hz)			
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)		
1525	M	1559	M	T	Mobile-Satellite Service
1626.5	M	1660.5	M	R	Mobile-Satellite Service
12.75	G	13.25	G	R	Fixed Satellite Service
10.7	G	10.95	G	T	Fixed Satellite Service
11.2	G	11.45	G	T	Fixed Satellite Service

**S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:**

a. Nominal Orbital Longitude (Degrees E/W): 101 W		b. Alternate Orbital Longitude (Degrees E/W):		c. Reason for orbital location selection:  MSV-1 will operate its feederlinks in the Appendix 30B Ku-band., and so operates at the 101 degrees W nominal longitude orbital location that is a United States ITU Appendix 30B Ku-band longitude.	
Longitudinal Tolerance or E/W Station-Keeping:		f. Inclination Excursion or N/S Station-Keeping Tolerance:  6 Degrees	Range of orbital are in which adequate service can be provided (Optional):  g. Westernmost: h. Easternmost:		
d. Toward West: 0.05 Degrees	e. Toward East: 0.05 Degrees		Degrees      E/W		
i. Reason for service are selection (Optional):					

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.):

S4b. Total Number of Orbital Planes in Network or System:

S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital Plane No.	(f) No. of Satellites in Plane	(g) Inclination Angle (degrees)	(h) Orbital Period (Seconds)	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension of the Ascending Node (Deg.)	(l) Argument of Perigee (Degrees)	Active Service Arc Range (Degrees)		
								(m) Begin Angle	(n) End Angle	(o) Other

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the initial phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle (Degrees)

**NO NGSO DATA FILED**

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(c) Service Area Diagram File Name (GXT File)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
SAL1	S	MSV-1-SA.gxt	Figure: Service Area SAL1
SAL2	S	MSV-1-Hawaii-SA.gxt	Figure: Service Area SAL2
SAKU	S	MSV-1 Ku Service Area	Figure: Service Area SAKU
OMNI	S	MSV-101 Omni SA.gxt	Figure: Service Area OMNI

**FEDERAL COMMUNICATIONS COMMISSION**  
**SATELLITE SPACE STATION AUTHORIZATIONS**  
**FCC Form 312 - Schedule S: (Technical and Operational Description)**

S7. SPACE STATION ANTENNA BEAM CHARACTERISTICS For each antenna beam provide:

(a) Beam ID	(b) T/R Mode	(c) Isotropic Antenna Gain		(e) Pointing Error (Degrees)	(f) Rotational Error (Degrees)	(g) Min. Cross- Polar Iso- lation (dB)	(h) Polar- ization Switch- able? (Y/N)	(i) Polarization Alignment Rel. Equatorial Plane (Degrees)	(j) Service Area ID	Transmit			Receive				
		(c) Peak (dBi)	(d) Edge (dBi)							(k) Input Losses (dB)	(l) Effective Output Power (W)	(m) Max. EIRP (dBW)	(n) System Noise Temp (k)	(o) G/T Max. Gain Pt. (db/K)	(p) Min. Saturation Flux Density (dBW/m2)	Input Attenuator (dB)	
																(q) Max. Value	(r) Step Size
RLE	R	33	30	0.12		20	N		SAL1				300	7	-102.7	15	1
TLE	T	33	30	0.12		20	N		SAL1	1.52	500	57.3					
RLE	R	33	30	0.12		20	N		SAL1				300	7	-102.7	15	1
TLE	T	33	30	0.12		20	N		SAL2	1.52	500	57.3					
RLE	R	33	30	0.12		20	N		SAL2				300	7	-102.7	15	1
TKU1	T	42	40	0.12		25	N		SAKU	3.2	25	52.8					
RKU	R	42	40	0.12		25	N		SAKU				800	11	-89.6	15	1
TKU2	T	42	40	0.12		25	N		SAKU	3.2	25	52.8					
RKU	R	42	40	0.12		25	N		SAKU				800	11	-89.6	15	1
TKU3	T	42	40	0.12		25	N		SAKU	3.2	25	52.8					
RKU	R	42	40	0.12		25	N		SAKU				800	11	-89.6	15	1
TKU4	T	42	40	0.12		25	N		SAKU	3.2	25	52.8					
RKU	R	42	40	0.12		25	N		SAKU				800	11	-89.6	15	1
TL1	T	46.5	33.5	0.12		17	N		SAL1	1.52	246	69.16					
RL1	R	47	33.5	0.12		17	N		SAL1				300	21	-116.7	15	1
TLHI	T	33	30	0.12		17	N		SAL2	1.52	62	47.58					
RLHI	R	33	30	0.12		17	N		SAL2				300	7	-102.7	15	1
TOM	T	2	2	0.12		9	N		OMNI	2	1	0					
ROM	R	2	2	0.12		12	N		OMNI				800	-30		15	1
TLTP	T	46.5	43.5	0.12		17	N		SAL1	1.52	246	69.16					
RLTP	R	47	44	0.12		17	N		SAL1				300	21	-116.7	15	1
TLE	T	33	30	0.12		20	N		SAL1	1.52	500	57.3					
RLE	R	33	30	0.12		20	N		SAL1				300	7	-102.7	15	1
TLE	T	33	30	0.12		20	N		SAL1	1.52	500	57.3					
RLE	R	33	30	0.12		20	N		SAL1				300	7	-102.7	15	1
TLE	T	33	30	0.12		20	N		SAL1	1.52	500	57.3					
RLE	R	33	30	0.12		20	N		SAL1				300	7	-102.7	15	1
TLE	T	33	30	0.12		20	N		SAL1	1.52	500	57.3					

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data:  
Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a) Beam ID	(b) T/R Mode	(c) Co-or Cross Polar Mode ("C" or" X")	(d) GSO Ref. Orbital Longitude (Deg. E/W)	(e) NGSO Antenna Gain Contour Description (Figure/Table/ Exhibit)	(f) GSO Antenna Gain Contour Data (GXT File)	Max. Power Flux Density (dBW/M2/Hz)				
						At Angle of Arrival above horizontal (for emission with highest PFD)				
						(g) 5 Deg	(h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg
TL1	T	C	-101		TKu1.gxt	-113	-112.5	-112	-111.8	-111.7
RL1	R	C	-101		RL1.gxt					
TLHI	T	C	-101		TLHI.gxt	-126	-125.5	-125	-124.8	-124.7
RLHI	R	C	-101		RLHI.gxt					
TLE	T	C	-101		TLEM1.gxt	-137.2	-137	-136.8	-136.7	-136.6
RLE	R	C	-101		RLEM1.gxt					
TLE	T	C	-101		TLEM2.gxt	-137.2	-137	-136.8	-136.7	-136.6
RLE	R	C	-101		RLEM2.gxt					
TLE	T	C	-101		TLEM3.gxt	-137.2	-137	-136.8	-136.7	-136.6
RLE	R	C	-101		RLEM3.gxt					
TLE	T	C	-101		TLEM4.gxt	-137.2	-137	-136.8	-136.7	-136.6
RLE	R	C	-101		RLEM4.gxt					
TLE	T	C	-101		TLEM5.gxt	-137.2	-137	-136.8	-136.7	-136.6
RLE	R	C	-101		RLEM5.gxt					
TLE	T	C	-101		TLEM6.gxt	-137.2	-137	-136.8	-136.7	-136.6
RLE	R	C	-101		RLEM6.gxt					
TKU1	T	C	-101		TKu1.gxt	-150.4	-150	-149.6	-149.4	-149.2
RKU	R	C	-101		RKu1.gxt					
TKU2	T	C	-101		TKu2.gxt	-150.4	-150	-149.6	-149.4	-149.2
RKU	R	C	-101		RKu2.gxt					
TKU3	T	C	-101		TKu3.gxt	-150.4	-150	-149.6	-149.4	-149.2
RKU	R	C	-101		RKu3.gxt					
TKU4	T	C	-101		TKU4.gxt	-150.4	-150	-149.6	-149.4	-149.2
RKU	R	C	-101		RKU4.gxt					
TLTP	T	C	-101		TLTP1.gxt	-113	-112.5	-112	-111.8	-111.7
RLTP	R	C	-101		RLTP1.gxt					
TOM	T	C	-101		ROMNI.gxt	-159.9	-159.7	-159.5	-159.4	-159.3
ROM	R	C	-101		ROMNI.gxt					

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
KUD1L	250000	T	10825	L	C
KUD1R	250000	T	10825	R	C
KUD2L	250000	T	11325	L	C
KUD2R	250000	T	11325	R	C
KUUL	500000	R	13000	L	C
KUUR	500000	R	13000	R	C
LD	34000	T	1542	R	C
LUL	34000	R	1643.5	L	C
LUR	34000	R	1643.5	R	C
LEMD	34000	T	1542	R	C
LEMU	34000	R	1643.5	R	C
BEAC	1	T	11446.25	L	C
CMD1	1000	R	13249.0	R	T
CMD2	1000	R	12751.0	R	T
TLM1	100	T	11201	R	T
TLM2	100	T	11202	R	T
CMD3	1000	R	13249.0	L	T
TLM3	100	T	11201	L	T
TLM4	100	T	11202	L	T
BEAC2	1	T	11448.75	R	C

(a) Transponder ID	(b) Transponder Gain (dB)	Receive Band		Transmit Band	
		(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID
FWD1	132	KUUL	RKU1	LD	TL1
FWD2	132	KUUR	RKU1	LD	TL1
FWD3	132	KUUL	RKU1	LD	TLHI
FWD4	132	KUUR	RKU1	LD	TLHI
FWD5	129	KUUL	RKU1	LEMD	TLEM1
FWD6	129	KUUR	RKU1	LEMD	TLEM1
RTN1	126	LUL	RL1	KUD1R	TKU1
RTN2	126	LUL	RL1	KUD1L	TKU1
RTN3	126	LUL	RL1	KUD2R	TKU1
RTN4	126	LUL	RL1	KUD2L	TKU1
RTN5	126	LUR	RL1	KUD1R	TKU1
RTN6	126	LUR	RL1	KUD1L	TKU1
RTN7	126	LUR	RL1	KUD2R	TKU1
RTN8	126	LUR	RL1	KUD2L	TKU1
RTN9	126	LUL	RLHI	KUD1R	TKU1
RTN10	126	LUL	RLHI	KUD1L	TKU1
RTN11	126	LUL	RLHI	KUD2R	TKU1
RTN12	126	LUL	RLHI	KUD2L	TKU1
RTN13	126	LUR	RLHI	KUD1R	TKU1
RTN14	126	LUR	RLHI	KUD1L	TKU1
RTN15	126	LUR	RLHI	KUD2R	TKU1
RTN16	126	LUR	RLHI	KUD2L	TKU1
RTN17	120	LUL	RLEM1	KUD1R	TKU1
RTN18	120	LUL	RLEM1	KUD1L	TKU1
RTN19	120	LUL	RLEM1	KUD2R	TKU1
RTN20	120	LUL	RLEM1	KUD2L	TKU1
RTN21	120	LUR	RLEM1	KUD1R	TKU1
RTN22	120	LUR	RLEM1	KUD1L	TKU1
RTN23	120	LUR	RLEM1	KUD2R	TKU1
RTN24	120	LUR	RLEM1	KUD2L	TKU1

CMOM1		CMD1	ROMNI		
CMHG		CMD3	RKU3		
CMOM2		CMD2	ROMNI		
TLOM1				TLM1	TOMNI
TLOM2				TLM2	TOMNI
TLHG1				TLM3	TKU3
TLHG2				TLM4	TKU3
TBEAC				BEAC	TKU3
TBEA2				BEAC2	TKU3

**FEDERAL COMMUNICATIONS COMMISSION**  
**SATELLITE SPACE STATION AUTHORIZATIONS**  
**FCC Form 312 - Schedule S: (Technical and Operational Description)**

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e) Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
CW1	1K00N	1	1			0	9.8	22
FESC	6K00G1D	6	4	3.375	1	0	9.9	22.1
MMS	5K00G1D	5	2	0.6	0.5	0	4.2	16.4
GMRF	270G7W	200	4	76.8	0.5	0	-2.6	14.8
GMRR	050KG7W	50	4	19.2	0.5	0	-2.6	14.8
CDMA	1M25G7W	1250	4	192	0.5	1	-3.4	8.8
WCDMA	5M00G7W	5000	4	576	0.5		-5.1	7.1
WIMAX	1M25G7W	1250	4	480	0.5		6.4	18.4
PNCOD	2M50G1W	2500	2				-9	3.2



**FEDERAL COMMUNICATIONS COMMISSION**  
**SATELLITE SPACE STATION AUTHORIZATIONS**  
**FCC Form 312 - Schedule S: (Technical and Operational Description)**

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a) Analog Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) Signal Type	(e) Channels per Carrier	Multi-channel Telephony				(j) Video Standard NTSC, PAL, etc.	(k) Video Noise- Weighting (dB)	(l) Video and SCPC/FM Modulation Index	(m) SCPC/FM Compander, Preemphasis, and Noise Weighting (dB)	(n) Total C/N Performance Objective (dB)	(o) Single Entry C/I Objective (dB)
					(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index						
TELE	138KGXD	100	PM	1									5	17.2
CMD	700K9D	1000	FM	1									25	37.2

**Typical Emissions**

This Space Station)	
(n) Max. Power Flux Density (dBW/m2/Hz)	(o)Assoc. Stn Rec. G/T (dB/K)
-119	-31
-124	-31
-129	-31
-125.4	-27
-136	-16
-136.8	-16
-140	-21
-153.5	36.5
-153.5	36.5

RTN1	RTN16	WCDMA		1	Noise Budget-S		-4	-1	-1	38.4	40.4	-153.6
------	-------	-------	--	---	----------------	--	----	----	----	------	------	--------

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

**Remote Control (TT C) Location(s):**

S14a: Street Address: 1601 Telesat Court			
S14b. City: Ottawa	S14c. County:	S14d. State/Country	S14e. Zip Code: K1B 1B9
S14f. Telephone Number: 888-835-3728 x3315		S14g. Call Sign of Control Station (if appropriate):	

**Remote Control (TT C) Location(s):**

S14a: Street Address:			
S14b. City: Napa	S14c. County:	S14d. State/Country CA	S14e. Zip Code:
S14f. Telephone Number:		S14g. Call Sign of Control Station (if appropriate):	

**FEDERAL COMMUNICATIONS COMMISSION  
SATELLITE SPACE STATION AUTHORIZATIONS  
FCC Form 312 - Schedule S: (Technical and Operational Description)**

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a. Mass of spacecraft without fuel (kg): 3253	Spacecraft Dimensions (meters)	Probability of Survival to End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 2180		
S15c. Mass of spacecraft and fuel at launch (kg): 5433	S15f. Length (m): 40.5	S15i. Payload: 0.8541
S15d. Mass of fuel, in orbit, at beginning of life (kg): 2175	S15g. Width (m): 29.1	S15j. Bus: 0.8357
S15e. Deployed Area of Solar Array (square meters): 64.5	S15h. Height (m): 18.4	S15k. Total: 0.71

S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem	Electrical Power (Watts) At Beginning of Life		Electrical Power (Watts) At End of Life	
	At Equinox	At Solstice	At Equinox	At Solstice
Payload (Watts):	(a): 10650	(f): 10650	(k): 10650	(p): 10650
Bus (Watts):	(b): 750	(g): 880	(l): 750	(q): 880
Total (Watts):	(c): 11400	(h): 11530	(m): 11400	(r): 11530
Solar Array (Watts):	(d): 14200	(i): 13360	(n): 12900	(s): 12145
Depth of Battery Discharge (%):	(e) 63 %	(j) 0 %	(o) 73 %	(t) 0 %

S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) met?	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO	<input type="checkbox"/> N/A

**In addition to the information required in this Form, the space station applicant is required to provide all the information specified in Section 25.114 of the Commission's rules, 47 C.F.R § 25.114.**