

EchoStar 17/24 GHz Link Budget

Link Parameters		Clear Sky (New York)	Faded D/L (New York)	Clear Sky (Los Angeles)	Faded D/L (Los Angeles)
Link Geometry:					
Tx E/S Range to Satellite (Cheyenne)	(km)	38,121	38,121	38,121	38,121
Rx E/S Range to Satellite	(km)	37,575	37,575	38,371	38,371
Uplink:					
Carrier Frequency	(MHz)	25,000	25,000	25,000	25,000
Tx E/S Antenna Diameter	(m)	12.0	12.0	12.0	12.0
Max. Tx E/S Power to Antenna	(W)	4.7	4.7	4.7	4.7
Max. Tx E/S Power Density to Antenna	(dBW/MHz)	-6.9	-6.9	-6.9	-6.9
Tx E/S Antenna Gain	(dB)	68.2	68.2	68.2	68.2
Tx E/S EIRP per Carrier	(dBW)	74.9	74.9	74.9	74.9
Atmospheric and Other Losses	(dB)	0.5	0.5	0.5	0.5
Free Space Loss	(dB)	212.0	212.0	212.0	212.0
Satellite:					
G/T towards Tx E/S	(dB/K)	10.3	10.3	10.3	10.3
EIRP per Carrier towards Rx E/S	(dBW)	56.9	56.9	53.8	53.8
Downlink:					
Carrier Frequency	(MHz)	17,500	17,500	17,500	17,500
Atmospheric and Other Losses	(dB)	0.2	4.4	0.2	2.2
Free Space Loss	(dB)	208.8	208.8	209.0	209.0
Rx E/S Antenna Diameter	(m)	0.45	0.45	0.45	0.45
Rx E/S Antenna Gain	(dB)	36.1	36.1	36.1	36.1
Pointing Error	(dB)	0.5	0.5	0.5	0.5
Rx E/S G/T	(dB/K)	13.1	10.4	13.1	11.3
System (LNA+Sky) Noise Temperature	(K)	200	373	200	304
Total Link:					
Bandwidth	(dB-Hz)	73.60	73.60	73.60	73.60
C/N - Thermal Uplink	(dB)	27.6	27.6	27.6	27.6
C/N - Thermal Downlink	(dB)	15.5	8.6	12.2	8.4
C/I - Aggregate uplink ASI	(dB)	37.4	37.4	37.4	37.4
C/I - Aggregate downlink ASI	(dB)	20.6	20.6	20.4	20.4
C/I - Other Link Degradations	(dB)	20.0	20.0	20.0	20.0
C/(N+I) - Total, Actual	(dB)	13.1	8.0	10.9	7.8
C/(N+I) - Total, Required	(dB)	7.5	7.5	7.5	7.5
Excess Margin	(dB)	5.6	0.5	3.4	0.3
Availability	(%)	N/A	99.85	N/A	99.85
Aggregate Interference Assessment:					
(C/N) - no ASI	(dB)	14.0	8.2	11.4	8.1
Degradation due to aggregate ASI	(dB)	0.9	0.2	0.5	0.3