

# EchoStar 17/24 GHz Link Budget

Link Parameters		Clear Sky (Los Angeles)	Faded D/L (Los Angeles)	Clear Sky (Mexico City)	Faded D/L (Mexico City)
<b>Link Geometry:</b>					
Tx E/S Range to Satellite (Cheyenne)	(km)	38,983	38,983	38,983	38,983
Rx E/S Range to Satellite	(km)	39,610	39,610	37,592	37,592
<b>Uplink:</b>					
Carrier Frequency	(MHz)	25,000	25,000	25,000	25,000
Tx E/S Antenna Diameter	(m)	12.0	12.0	12.0	12.0
Max. Tx E/S Power to Antenna	(W)	5.0	5.0	5.0	5.0
Max. Tx E/S Power Density to Antenna	(dBW/MHz)	-6.6	-6.6	-6.6	-6.6
Tx E/S Antenna Gain	(dB)	68.2	68.2	68.2	68.2
Tx E/S EIRP per Carrier	(dBW)	75.2	75.2	75.2	75.2
Atmospheric and Other Losses	(dB)	0.5	0.5	0.5	0.5
Free Space Loss	(dB)	212.2	212.2	212.2	212.2
<b>Satellite:</b>					
G/T towards Tx E/S	(dB/K)	17.2	17.2	17.2	17.2
EIRP per Carrier towards Rx E/S	(dBW)	53.6	53.6	53.3	53.3
<b>Downlink:</b>					
Carrier Frequency	(MHz)	17,500	17,500	17,500	17,500
Atmospheric and Other Losses	(dB)	0.4	2.3	0.2	1.8
Free Space Loss	(dB)	209.3	209.3	208.8	208.8
Rx E/S Antenna Diameter	(m)	0.45	0.45	0.45	0.45
Rx E/S Antenna Gain	(dB)	36.1	36.1	36.1	36.1
Pointing Error	(dB)	0.5	0.5	0.5	0.5
Rx E/S G/T	(dB/K)	13.1	11.4	13.1	11.6
System (LNA+Sky) Noise Temperature	(K)	200	298	200	285
<b>Total Link:</b>					
Bandwidth	(dB-Hz)	73.6	73.6	73.6	73.6
C/N - Thermal Uplink	(dB)	34.6	34.6	34.6	34.6
C/N - Thermal Downlink	(dB)	11.5	7.9	11.9	8.8
C/I - Aggregate uplink ASI	(dB)	37.5	37.5	37.5	37.5
C/I - Aggregate downlink ASI	(dB)	19.9	19.9	14.0	14.0
C/I - Other Link Degradations	(dB)	22.0	22.0	22.0	22.0
C/(N+I) - Total, Actual	(dB)	10.6	7.5	9.5	7.5
C/(N+I) - Total, Required	(dB)	7.5	7.5	7.5	7.5
Excess Margin	(dB)	3.1	0.0	2.0	0.0
Availability	(%)	N/A	99.55	N/A	99.67
<b>Aggregate Interference Assessment:</b>					
(C/N) - no ASI	(dB)	11.1	7.7	11.5	8.5
Degradation due to aggregate ASI	(dB)	0.6	0.3	1.9	1.1