

EchoStar 17/24 GHz Link Budget

Link Parameters		Clear Sky (Los Angeles)	Faded D/L (Los Angeles)	Clear Sky (Mexico City)	Faded D/L (Mexico City)
Link Geometry:					
Tx E/S Range to Satellite (Cheyenne)	(km)	38,983	38,983	38,983	38,983
Rx E/S Range to Satellite	(km)	39,610	39,610	37,592	37,592
Uplink:					
Carrier Frequency	(MHz)	25,000	25,000	25,000	25,000
Tx E/S Antenna Diameter	(m)	12.0	12.0	12.0	12.0
Max. Tx E/S Power to Antenna	(W)	5.0	5.0	5.0	5.0
Max. Tx E/S Power Density to Antenna	(dBW/MHz)	-6.8	-6.8	-6.8	-6.8
Tx E/S Antenna Gain	(dB)	68.2	68.2	68.2	68.2
Tx E/S EIRP per Carrier	(dBW)	75.2	75.2	75.2	75.2
Atmospheric and Other Losses	(dB)	0.5	0.5	0.5	0.5
Free Space Loss	(dB)	212.2	212.2	212.2	212.2
Satellite:					
G/T towards Tx E/S	(dB/K)	17.2	17.2	17.2	17.2
EIRP per Carrier towards Rx E/S	(dBW)	53.6	53.6	53.3	53.3
Downlink:					
Carrier Frequency	(MHz)	17,500	17,500	17,500	17,500
Atmospheric and Other Losses	(dB)	0.4	3.4	0.2	3.0
Free Space Loss	(dB)	209.3	209.3	208.8	208.8
Rx E/S Antenna Diameter	(m)	0.45	0.45	0.45	0.45
Rx E/S Antenna Gain	(dB)	36.1	36.1	36.1	36.1
Pointing Error	(dB)	0.5	0.5	0.5	0.5
Rx E/S G/T	(dB/K)	13.1	10.8	13.1	10.9
System (LNA+Sky) Noise Temperature	(K)	200	338	200	330
Total Link:					
Bandwidth	(dB-Hz)	73.8	73.8	73.8	73.8
C/N - Thermal Uplink	(dB)	34.4	34.4	34.4	34.4
C/N - Thermal Downlink	(dB)	11.3	6.1	11.7	6.8
C/I - Aggregate uplink ASI	(dB)	37.3	37.3	37.3	37.3
C/I - Aggregate downlink ASI	(dB)	19.7	19.7	13.8	13.8
C/I - Other Link Degradations	(dB)	22.0	22.0	22.0	22.0
C/(N+I) - Total, Actual	(dB)	10.4	5.8	9.4	5.9
C/(N+I) - Total, Required	(dB)	5.8	5.8	5.8	5.8
Excess Margin	(dB)	4.6	0.0	3.6	0.1
Availability	(%)	N/A	99.76	N/A	99.87
Aggregate Interference Assessment:					
(C/N) - no ASI	(dB)	11.0	6.0	11.3	6.6
Degradation due to aggregate ASI	(dB)	0.6	0.2	1.9	0.8