# FEDERAL COMMUNICATIONS COMMISSION SATELLITE SPACE STATION AUTHORIZATIONS (Technical and Operational Description)

#### S1. GENERAL INFORMATION Complete for all satellite applications.

a. Space Station or Satellite Network Name: ORBCOMM GENERATION 2	e. Estimated Date of Placement into Service:	i Will the space station(s) operate on a Common Carrier Basis: N
b. Construction Commencement Date:	f. Estimated Lifetime of Satellite(s): 5 Years	j. Number of transponders offered on a common carrier basis:
c. Construction Completion Date:	g. Total Number of Transponders: 4	k. Total Common Carrier Transponder Bandwidth: MHz
d1. Est Launch Date Begin: d2. Est Launch Date End:	h. Total Transponder Bandwidth (no. transponders x Bandwidth) 5.9 MHz	I. Orbit Type: Mark all boxes that apply:

#### S2. OPERATING FREQUENCY BANDS Identify the frequency range and transmit/receive mode for all frequency bands in which this station will oper Also indicate the nature of service(s) for each frequency band.

	Frequency Band Limits				f.				
Lower Frequency	/ (_Hz)	Upper Frequency	(_Hz)	e. T/R Mode	Nature of Service(s): List all that apply to this band				
a. Numeric	b. Unit (K/M/G)	c. Numeric	d. Unit (K/M/G)						
137.025	Μ	137.175	М	Т	NVNG MSS				
137.000	М	137.025	М	Т	NVNG MSS (Non-voice, non-geostationary mobile satellite service)				
137.175	М	137.825	М	Т	NVNG MSS				
137.825	М	138.000	М	Т	NVNG MSS				
148.000	М	149.900	М	R	NVNG MSS				
149.900	Μ	150.050	М	R	NVNG MSS				
161.000	М	161.575	М	R	AIS (USCG Automatic Identification System)				
161.575	М	161.625	М	R	AIS				
161.625	М	161.775	М	R	AIS				
161.775	Μ	162.0125	М	R	AIS				
162.0125	Μ	163.000	М	R	AIS				
400.15	М	401	М	Т	NVNG MSS				

S3. ORBITAL INFORMATION FOR GEOSTATIONARY SATELLITES ONLY:

S4. ORBITAL INFORMATION FOR NON-GEOSTATIONARY SATELLITES ONLY

S4a. Total Number of Satellites in Network or System:18S4b. Total Number of Orbital Planes in Network or System:

S4c. Celestial Reference Body (Earth, Sun, Moon, etc.): E

8/30/2012

5 S4d. Orbit Epoch Date:

For each Orbital Plane Provide:

(e) Orbital	(f) No. of	(g) Inclination	(h) Orbital	(i) Apogee (km)	(j) Perigee (km)	(k) Right Ascension	(I) Argument of	Active Se	rvice Arc Rang	e (Degrees)
Plane No.	Satellites in Plane	Angle (degrees)	Period (Seconds)			of the Ascending Node (Deg.)	Perigee (Degrees)	(m) Begin Angle	(n) End Angle	(o) Other
1	4	52	5989	750	750	0	0	0	360	
2	4	52	5989	750	750	90	0	0	360	
3	4	52	5989	750	750	180	0	0	360	
4	5	52	5989	750	750	270	0	0	360	
5	1	51.7	5989	750	750		0	0	360	

S5. INITIAL SATELLITE PHASE ANGLE For each satellite in each orbital plane, provide the intital phase angle.

(a) Orbital Plane No.	(b) Satellite Number	(c) Initial Phase Angle (Degrees)		
1	1	0		
1	2	90		
1	3	180		
1	4	270		
2	1	0		
2	2	90		
2	3	180		
2	4	270		
3	1	0		
3	2	90		
3	3	180		
3	4	270		
4	1	0		
4	2	72		
4	3	144		
4	4	216		
4	5	288		

5	1	0

Page 3: Service Areas

S6. SERVICE AREA CHARACTERISTICS for each service area provide:

(a) Service Area ID	(b) Type of Associated Station (Earth or Space)	(d) Service Area Description. Provide list of geographic areas (state postal codes or ITU 3-ltr codes), satellites or Figure No. of Service Area Diagram.
A	S	Global Coverage

Page 4: Antenna Beams

(a)	(b)	Isotropic	Antenna	(e)	(f)	(g) Min.	(h) Polar-	(i) Polarization	(j) Service		Transmit				Receive		
Beam	T/R		ain	_ 0	Rotational	Cross-	ization	Alignment Rel.	Area ID	(k) Input	(I) Effective	(m)	( )	(o) G/T	(p) Min.	Input Atten	uator (dB)
ID	Mode	(c) Peak (dBi)	(d) Edge (dBi)	Error (Degrees)	Error (Degrees)	Polar Iso- lation (dB)	Switch- able? (Y/N)	Equatorial Plane (Degrees)		Losses (dB)	Output Power (W)	Max. EIRP (dBW)	System Noice Temp (k)		Saturation Flux Density (dBW/m2)	(q) Max. Value	(r) Step Size
VHF-	Т	0	-5.2	0	0	18.8	N		A	1	22.4	13.5					
UHF-	Т	0	-5.2	0	0	12.9	Ν		A	1	1.26	1					
VHF-	R	1.5	-9.2	0	0	18.8	Ν		А				680	-26.8			
AIS-R	R	0.4	-0.1	0	0	18.8	Ν		А				680	-27.9			

S8. ANTENNA BEAM DIAGRAMS For each beam pattern provide the reference to the graphic image and numerical data: Also provide the power flux density levels in each beam that result from the emission with the highest power flux density.

(a)	(b)	(c) Co-or	(d) GSO	(e) NGSO Antenna Gain	(f) GSO Antenna Gain Contour Data (GXT File)	Max. Power Flux Density (dBW/M2/Hz) At Angle of Arrival above horizontal (for emission with highest PFD)						
Beam ID	T/R Mode	Cross Polar Mode ("C" or" X")	Ref. Orbital Longitude (Deg. E/W)	Contour Description (Figure/Table/ Exhibit)		(g) 5 Deg	Arrival above ho (h) 10 Deg	(i) 15 Deg	(j) 20 Deg	(k) 25 Deg		
VHF-	Т	С		Attachment A		-126.92	-126.77	-126.52	-126.29	-125.88		
UHF-	Т	С		Attachment A		-147.2	-147.05	-146.81	-146.57	-146.16		
VHF-	R	С		Attachment A								
AIS-R	R	С		Attachment A								

Page 5: Beam Diagrams

Page 6: Channels and Transponders

(a) Channel No.	(B) Assigned Bandwidth (kHz)	(c) T/R Mode	(d) Center Frequency (MHz)	(e) Polarization (H, V, L, R)	(f) TTC or Comm Channel (T or C)
VF-T	1000	Т	137.5	R	С
VF-R	2050	R	149.025	R	С
AS-R	2000	R	162	R	С
UF-T	850	Т	400.575	R	С

S9. SPACE STATION CHANNELS For each frequency channel provide: S10. SPACE STATION TRANSPONDERS For each transponder provide:

(a)	(b)	Receive	Band	Transmit Band		
Transponder ID	Transponder Gain (dB)	(c) Channel No.	(d) Beam ID	(e) Channel No.	(f) Beam ID	
V-R		VF-R	VHF-R			
A-R		AS-R	AIS-R			
U-T				UF-T	UHF-T	
V-T				VF-T	VHF-T	

S11. DIGITAL MODULATION PARAMETERS For each digital emission provide:

(a) Digital Mod. ID	(b) Emission Designator	(c) Assigned Bandwidth (kHz)	(d) No. of Phases	(e)Uncoded Data Rate (kbps)	(f) FEC Error Correction Coding Rate	(g) CDMA Processing Gain (dB)	(h) Total C/N Performance Objective (dB)	(i) Single Entry C/I Objective (dB)
1	6K72G1D	15	2	4.8			12.3	24.5
2	6K72G1D	15	4	7.2	0.75		8.1	20.3
3	40K3G1D	50	4	57.6			15.6	27.8
4	40K3G1D	50	16	172.8	0.75		16.4	28.6
5	10K0F1D	25	2	9.6			15.5	27.7
6	3K36G1D	5	2	2.4			12.3	24.5
7	40K3G1D	60	4	57.6			15.6	27.8
8	40K3G1D	60	16	172.8	0.75		16.4	28.6
9	3K60G1D	5	4	4.8	0.9		12.3	24.5
10	40K3G1D	50	15	86.4	0.75		16.4	28.6

Page 7: Digital Modulation

Page 8: Analog Modulation

S12. ANALOG MODULATION PARAMETERS For each analog emission provide:

(a)	(b) Emission	(C)	(d) Signal	(e)		Multi-channe	Telephony		(j) Video	(k) Video	(I) Video	( )	(n) Total C/N	(-) - 3 -
Analog Mod. ID		Assigned Bandwidth (kHz)	Туре	Channels per Carrier	(f) Ave. Companded Talker Level (dBm0)	(g) Bottom Baseband Freq. (MHz)	(h) Top Baseband Freq. (MHz)	(i) RMS Modulation Index	Standard NTSC, PAL, etc.	Noise- Weighting (dB)	and SCPC/FM Modulation Index	Compander, Preemphasis, and Noise Weighting (dB)	Performance Objective (dB)	Entry C/I Objective (dB)

Page 9: Typical Emissions

S13. TYPICAL EMISSIONS For each planned type of emission provide:

	Associated Transponder ID Range		lation ID	(e) Carriers	(f) Carrier	(g)Noise Budget	(h) Energy	Receive Band (Assoc. Transmit Stn)			Transmit Band (This Space Station)			
		(c) Digital (Table S11)	(d) Analog (Table S12)	per Transponder	Spacing (kHz)	Reference (Table No.)	Dispersal Bandwidth	(i)Assoc. Stn. Max.	Assoc. Stati Power	on Transmit (dBW)	EIRP	(dBW)	(n) Max. Power Flux Density	(o)Assoc. Stn Rec.
(a) Start	(b) End	·	· · · ·				(kHz)	Antenna Gain (dBi)	(j) Min.	(k) Max.	(I) Min.	(m) Max.	(dBW/m2/Hz)	G/T (dB/K)
V-T	V-T	1		6	15	Attach 1					8.3	13.5	-125.8	-32.7
V-T	V-T	2		6	15	Attach 1					8.3	13.5	-125.8	-32.7
V-T	V-T	3		1		Attach 1					-3.9	1.3	-145.8	-12.6
V-T	V-T	4		1		Attach 1					-3.9	1.3	-145.8	-12.6
U-T	U-T	7		1		Attach 1					-4.2	1	-146.1	-3.36
U-T	U-T	8		1		Attach 1					-4.2	1	-146.1	-3.36
V-R	V-R	6		80	5	Attach 1		0	7	7				
V-R	V-R	9		80	5	Attach 1		0	7	7				
V-R	V-R	3		1		Attach 1		0	32.7	32.7				
V-R	V-R	10		1		Attach 1		0	32.7	32.7				
A-R	A-R	5		2	25	Attach 1		0	10.8	10.8				

Page 10: TT and C

S14. Is the space station(s) controlled and monitored remotely? If Yes, provide the location and telephone number of the TT and C control point(s): Yes

#### Remote Control (TT C) Location(s):

S14a: Street Address: 22265 Pacific Boulevard				
S14b. City: Dulles	S14c. County: Loudoun		S14d. State/Country VA	S14e. Zip Code: 20166
S14f. Telephone Number: 703-433-6300	l	S14g. Call Sign of Cor	trol Station (if appropriate):	
Remote Control (TT C) Locati	on(s):			
S14a: Street Address: 1527 Bray Road				
S14b. City:	S14c. County:		S14d. State/Country	S14e. Zip Code:
Arcade	Wyoming		NY	14009
S14f. Telephone Number:		S14g. Call Sign of Cor E940535	ntrol Station (if appropriate):	
Remote Control (TT C) Locati	on(s):			
S14a: Street Address: RT #2 Box 401				
S14b. City:	S14c. County:		S14d. State/Country	S14e. Zip Code:
Ocilla	Irwin		GA	31774
S14f. Telephone Number:		S14g. Call Sign of Cor E940536	trol Station (if appropriate):	

#### Remote Control (TT C) Location(s):

S14a: Street Address: State Road 61				
S14b. City: St. Johns	S14c. County: Apache		S14d. State/Country AZ	S14e. Zip Code: 85936
S14f. Telephone Number:		S14g. Call Sign of Control Stat E940537	ion (if appropriate):	

S14a: Street Address: 1011 Bager Mountain Rd.				
S14b. City: East Wenatchee	S14c. County: Douglas		S14d. State/Country WA	S14e. Zip Code: 98801
S14f. Telephone Number:		14g. Call Sign of Control Stat E940537	ion (if appropriate):	

Page 11: Characteristics and Certifications

S15. SPACECRAFT PHYSICAL CHARACTERISTICS:

S15a: Mass of spacecraft without fuel (kg):	Spacecraft Dimensions	Probability of Survival to
160	(meters)	End of Life (0.0 - 1.0)
S15b. Mass of fuel and disposables at launch (kg): 10	1	
S15c. Mass of spacecraft and fuel at launch (kg): 170	S15f. Length (m): 1	S15i. Payload: 0.8367
S15d. Mass of fuel, in orbit, at beginning of life (kg):	S15g. Width (m):	S15j. Bus:
10	1	0.8367
S15e. Deployed Area of Solar Array (square meters):	S15h. Height (m):	S15k. Total:
4	9.6	0.7

#### S16. SPACECRAFT ELECTRICAL CHARACTERISTICS:

Spacecraft Subsystem	Electrical Pov Beginnir	ver (Watts) At ng of Life	Electrical Power (Watts) A End of Life				
	At Equinox	At Solstice	At Equinox	At Solstice			
Payload (Watts):	<sup>(a):</sup> 250	<sup>(f):</sup> 250	<sup>(k):</sup> 250	<sup>(p):</sup> 250			
Bus (Watts):	<sup>(b):</sup> 50	<sup>(g):</sup> 50	<sup>(I):</sup> 50	<sup>(q):</sup> 50			
Total (Watts):	<sup>(c):</sup> 300	<sup>(h):</sup> 300	<sup>(m)</sup> 300	<sup>(r):</sup> 300			
Solar Array (Watts):	<sup>(d):</sup> 600	<sup>(i):</sup> 537	<sup>(n):</sup> 552	<sup>(s):</sup> 494			
Depth of Battery Discharge (%):	<sup>(e)</sup> 20 %	<sup>(j)</sup> 20 %	<sup>(0)</sup> 20 %	<sup>(t)</sup> 20 %			

#### S17. CERTIFICATIONS:

a. Are the power flux density limits of § 25.208 met?:		YES		NO	Х	N/A		
b. Are the appropriate service area coverage requirements of § 25.143(b)(ii) and (iii), or § 25.145(c)(1) and (2) met	?	YES		NO	Х	N/A		
c. Are the frequency tolerances of § 25.202(e) and the out-of-band emission limits of § 25.202(f)(1), (2) and (3) me	? X	YES		NO		N/A		
In addition to the information required in this Form, the space station applicant is required to provide all	the in	formation s	peci	ified in S	ectio	n 25.114 of the		
Commission's rules, 47 C.F.R § 25.114.								