



312 File Number: **SATAMD2021121300189**

Filing Description

Question	Response
----------	----------

Description	Galaxy 25 redeployment and operate from 32.9 E.L to 66.125 E.L
-------------	--

Satellite
Information

Question	Response
Select Orbit Type	GSO
Space Station or Satellite Network Name	Galaxy 25
Estimated Lifetime of Satellite(s) From Date of Launch	25 Years
Will the space station(s) operate on a Common Carrier basis?	No

Operating
Frequency
Bands (4)

Nature of service	Description	Frequency Band(s)	Mode Type
Fixed-Satellite Service		14000.0 MHz -14500.0 MHz	Receive
Fixed-Satellite Service		11700.0 MHz -12200.0 MHz	Transmit
Fixed-Satellite Service		5925.0 MHz -6425.0 MHz	Receive
Fixed-Satellite Service		3700.0 MHz -4200.0 MHz	Transmit

**Orbital
Information For
Geostationary
Satellites**

Section	Question	Response
Orbital Longitude Information	Orbital Longitude	66.0 degrees
	Hemisphere of Orbital Longitude	E
Longitudinal Tolerance or East /West Station-Keeping	Toward West	0.05 degrees
	Toward East	0.05 degrees
Inclination Excursion or North /South Station-Keeping Tolerance	Inclination Excursion or North /South Station-Keeping Tolerance	3.1 degrees
Antenna Axis Attitude Accuracy	Roll	0.1 degrees
	Pitch	0.1 degrees
	Yaw	0.1 degrees

Receiving Beams 1:

Question	Response
Beam ID	CMDB
Receive Beam Frequency	6423.02 MHz -6424.98 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	-99.0 dB/K
Min. Saturation Flux Density	-90.0 dBW/m2
Max. Saturation Flux Density	-89.0 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Command : Global -Gain contours attachment not provided pursuant to section25.114(c)(4)(vi)(A) of the FCC rules

Receiving Beams 2:

Question	Response
Beam ID	CMDC
Receive Beam Frequency	5926.02 MHz -5926.98 MHz
Beam Type	Fixed
Polarization	V

Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
G/T at Max. Gain Point	-99.0 dB/K
Min. Saturation Flux Density	-90.0 dBW/m2
Max. Saturation Flux Density	-89.0 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Command: Global- Gain contour attachment not provided pursuant to section 25.114(c)(4)(vi)(A) of the FCC rules

Receiving Beams 3:

Question	Response
Beam ID	NCVU
Receive Beam Frequency	5925.0 MHz -6425.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
G/T at Max. Gain Point	3.0 dB/K
Min. Saturation Flux Density	-95.8 dBW/m2

Receiving Beams 4:

Max. Saturation Flux Density	-74.8 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Europe, Russia, North Africa, Asia,

Question	Response
Beam ID	NCHU
Receive Beam Frequency	5925.0 MHz -6425.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	3.9 dB/K
Min. Saturation Flux Density	-97.9 dBW/m2
Max. Saturation Flux Density	-76.9 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Europe, Russia, North Africa, Asia,

Receiving Beams 5:

Question	Response
Beam ID	NKHU
Receive Beam Frequency	14000.0 MHz -14500.0 MHz
Beam Type	Fixed

Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
G/T at Max. Gain Point	2.5 dB/K
Min. Saturation Flux Density	-98.4 dBW/m2
Max. Saturation Flux Density	-77.4 dBW/m2
Co- or Cross Polar Mode	C
Service Area Description	Europe, Middle East North Africa,

Receiving Beams 6:

Question	Response
Beam ID	NKVU
Receive Beam Frequency	14000.0 MHz -14500.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
G/T at Max. Gain Point	2.9 dB/K
Min. Saturation Flux Density	-97.4 dBW/m2
Max. Saturation Flux Density	-76.4 dBW/m2

Co- or Cross Polar Mode	C
Service Area Description	Europe, Middle East, North Africa,

Receiving Channels (54)

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
KU28	27.0	14483.5	Service Link
KU27	27.0	14477.0	Service Link
KU26	27.0	14452.5	Service Link
KU25	27.0	14446.0	Service Link
KU24	27.0	14421.5	Service Link
KU13	27.0	14260.0	Service Link
KU12	27.0	14235.5	Service Link
KU11	27.0	14229.0	Service Link
KU10	27.0	14204.5	Service Link
KU09	27.0	14198.3	Service Link
KU08	27.0	14173.5	Service Link
KU07	27.0	14167.5	Service Link
KU06	27.0	14142.5	Service Link
KU05	27.0	14136.0	Service Link
KU04	54.0	14096.0	Service Link
KU03	54.0	14089.5	Service Link
KU02	54.0	14035.0	Service Link
KU01	54.0	14028.5	Service Link
CU01	36.0	5945.0	Service Link
CMDC	0.96	5926.5	TT&C
CU21	36.0	6345.0	Service Link
CU22	36.0	6365.0	Service Link
CU23	36.0	6385.0	Service Link
CU24	36.0	6405.0	Service Link

CU10	36.0	6125.0	Service Link
CU06	36.0	6045.0	Service Link
CU19	36.0	6305.0	Service Link
CU02	36.0	5965.0	Service Link
CU04	36.0	6005.0	Service Link
CU18	36.0	6285.0	Service Link
CU12	36.0	6165.0	Service Link
CU13	36.0	6185.0	Service Link
CU07	36.0	6065.0	Service Link
CU08	36.0	6085.0	Service Link
CU14	36.0	6205.0	Service Link
CMDB	0.96	6423.5	TT&C
CU03	36.0	5985.0	Service Link
CU05	36.0	6025.0	Service Link
CU09	36.0	6105.0	Service Link
CU11	36.0	6145.0	Service Link
CU20	36.0	6325.0	Service Link
CU17	36.0	6265.0	Service Link
CU16	36.0	6245.0	Service Link
CU15	36.0	6225.0	Service Link
KU23	27.0	14415.5	Service Link
KU22	27.0	14390.5	Service Link
KU21	27.0	14384.0	Service Link
KU20	27.0	14359.5	Service Link
KU19	27.0	14353.0	Service Link
KU18	27.0	14328.5	Service Link

KU17	27.0	14322.0	Service Link
KU16	27.0	14297.5	Service Link
KU15	27.0	14291.0	Service Link
KU14	27.0	14266.5	Service Link

Transmitting Beams 1:

Question	Response
Beam ID	NKHD
Transmit Beam Frequency	11700.0 MHz -12200.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-24.0 dBW/Hz
Max. Transmit EIRP	50.3 dBW
Co- or Cross Polar Mode	C
Service Area Description	Europe, Middle East , North Africa,

Max. Power Flux Density

Information not provided.

Transmitting Beams 2:

Question	Response
Beam ID	NKVD
Transmit Beam Frequency	11700.0 MHz -12200.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees

Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-22.9 dBW/Hz
Max. Transmit EIRP	51.4 dBW
Co- or Cross Polar Mode	C
Service Area Description	Europe, Middle East, North Africa,

Max. Power Flux Density

Information not provided.

Transmitting Beams 3:

Question	Response
Beam ID	UPC1
Transmit Beam Frequency	11701.987 MHz -11702.012 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-32.2 dBW/Hz
Max. Transmit EIRP	24.8 dBW
Co- or Cross Polar Mode	C
Service Area Description	Global ULPC Ku

Max. Power Flux Density

Information not provided.

Transmitting Beams 4:

Question	Response
Beam ID	UPCC
Transmit Beam Frequency	12197.987 MHz -12198.012 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-21.0 dBW/Hz
Max. Transmit EIRP	23.0 dBW
Co- or Cross Polar Mode	C
Service Area Description	Global ULPC2 Ku

Max. Power Flux Density

Information not provided.

Transmitting Beams 5:

Question	Response
Beam ID	TLMB
Transmit Beam Frequency	4199.25 MHz -4199.75 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees

Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-35.6 dBW/Hz
Max. Transmit EIRP	21.4 dBW
Co- or Cross Polar Mode	C
Service Area Description	TM

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-162.8	-162.7	-162.6	-162.5	-162.4	-161.6

Transmitting Beams 6:

Question	Response
Beam ID	TLMC
Transmit Beam Frequency	4195.25 MHz -4195.75 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-34.6 dBW/Hz

Max. Transmit EIRP	22.4 dBW
Co- or Cross Polar Mode	C
Service Area Description	TM GLOBAL

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²	(dBW/m ²
* BW:	/BW):	/BW):	/BW):	/BW):	/BW):	/BW):
4.0 kHz	-161.8	-161.7	-161.6	-161.5	-161.4	-160.6

Transmitting Beams 7:

Question	Response
Beam ID	NCVD
Transmit Beam Frequency	3700.0 MHz -4200.0 MHz
Beam Type	Fixed
Polarization	V
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	90.0 degrees
Max. Transmit EIRP Density	-35.6 dBW/Hz
Max. Transmit EIRP	40.0 dBW
Co- or Cross Polar Mode	C
Service Area Description	Europe, Russia, North Africa, Asia,

Max. Power Flux Density

Transmitting
Beams 8:

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* BW:	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):
4.0 kHz	-162.9	-162.7	-162.6	-162.5	-162.4	-161.6

Question	Response
Beam ID	NCHD
Transmit Beam Frequency	3700.0 MHz -4200.0 MHz
Beam Type	Fixed
Polarization	H
Peak Gain	dBi
Antenna Pointing Error	0.19 degrees
Antenna Rotational Error	0.34 degrees
Polarization Switchable	No
Polarization Alignment Relative to the Equatorial Plane	0.0 degrees
Max. Transmit EIRP Density	-35.1 dBW/Hz
Max. Transmit EIRP	40.5 dBW
Co- or Cross Polar Mode	C
Service Area Description	Europe, Russia, North Africa, Asia,

Max. Power Flux Density

	* 0° - 5°	* 5° - 10°	* 10° - 15°	* 15° - 20°	* 20° - 25°	* 25° - 90°
* BW:	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):	(dBW/m ² /BW):
4.0 kHz	-162.4	-162.2	-162.1	-162.0	-161.9	-161.1

**Transmitting
Channels (56)**

Channel ID	Channel Bandwidth (MHz)	Center Frequency s (MHz)	Feeder Link, Service Link or TT&C
CD21	36.0	4120.0	Service Link
CD19	36.0	4080.0	Service Link
CD12	36.0	3940.0	Service Link
CD10	36.0	3900.0	Service Link
TLMB	0.5	4199.5	TT&C
CD11	36.0	3920.0	Service Link
CD14	36.0	3980.0	Service Link
TLMC	0.5	4195.5	TT&C
CD01	36.0	3720.0	Service Link
CD02	36.0	3740.0	Service Link
CD04	36.0	3780.0	Service Link
CD06	36.0	3820.0	Service Link
CD23	36.0	4160.0	Service Link
CD03	36.0	3760.0	Service Link
CD08	36.0	3860.0	Service Link
CD24	36.0	4180.0	Service Link
CD05	36.0	3800.0	Service Link
CD22	36.0	4140.0	Service Link
CD07	36.0	3840.0	Service Link
CD09	36.0	3880.0	Service Link
CD20	36.0	4100.0	Service Link
CD13	36.0	3960.0	Service Link
CD17	36.0	4040.0	Service Link
CD18	36.0	4060.0	Service Link

CD16	36.0	4020.0	Service Link
KU15	27.0	11991.0	Service Link
KU14	27.0	11966.5	Service Link
KU12	27.0	11935.5	Service Link
KU11	27.0	11929.0	Service Link
KU10	27.0	11904.0	Service Link
KU02	54.0	11735.0	Service Link
KU03	54.0	11789.0	Service Link
KU04	54.0	11796.0	Service Link
KU07	27.0	11867.0	Service Link
KU08	27.0	11873.5	Service Link
KU09	27.0	11898.0	Service Link
UCPC	0.025	12198.0	TT&C
UPC1	0.025	11702.0	TT&C
KU13	27.0	11960.0	Service Link
KU16	27.0	11997.5	Service Link
KU17	27.0	12022.0	Service Link
KU18	27.0	12028.5	Service Link
KU19	27.0	12053.0	Service Link
KU20	27.0	12059.5	Service Link
KU21	27.0	12084.0	Service Link
KU22	27.0	12090.5	Service Link
KU23	27.0	12115.0	Service Link
KU28	27.0	12183.5	Service Link
KU27	27.0	12177.0	Service Link
KU26	27.0	12152.5	Service Link

KU25	27.0	12146.0	Service Link
KU24	27.0	12121.5	Service Link
KU06	27.0	11842.5	Service Link
KU05	27.0	11836.0	Service Link
KU01	54.0	11728.5	Service Link
CD15	36.0	4000.0	Service Link

Certification Questions

Question	Response
Are the applicable service area coverage requirements of 25.143(b)(2) (ii) and (iii), or 25.144(a)(3)(i), or 25.145 (c)(1) and (2), or 25.146(i)(1) and (2), or 25.148(c), or 25.225 met?	N/A
Are the applicable frequency tolerances of 25.202(e) and out-of-band emission limits of 25.202(f)(1),(2), and (3) met?	Yes
Are the cessation of emissions requirements of 25.207 met?	Yes
Are the applicable power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?	Yes
For NGSO applications, are the applicable equivalent-power-flux-density limits of 25.208 met, and is the appropriate technical showing provided within the application?	N/A
Are the applicable full-frequency-reuse requirements of 25.210 met?	Yes
If the application is for a 17/24 GHz BSS space station, will it be operated at an offset location with full power and interference protection in accordance with 25.262(b)?	

Attachments

File Name		Beam	Field	Attachment Type	Description
<u>new mdb.</u> <u>mdb</u>			GSO Antenna Gain Contour Data	GIMS file (*.mdb)	