

Table D4.10 Representative Link Budget/ASI analysis for QPSK 24M0G7W R2/3 (NF HP XPDR @ 121.0°W)

		CLEAR-SKY		DEGRADED		
Carrier	Carrier Type		24MG7W	24MG7W	24MG7W	24MG7W
	Modulation		QPSK	QPSK	QPSK	QPSK
	Info Rate	Mbit/s	26.65	26.65	26.65	26.65
	FEC:		0.67	0.67	0.67	0.67
	Noise BW:	MHz	19.988	19.988	19.988	19.988
	Eb/No required:	dB	2.9	2.9	2.9	2.9
	C/N required	dB	4.1	4.1	4.1	4.1
ASI+Terrestrial losses	dB	1.5	1.5	1.5	1.5	
Adjusted required C/N	dB	5.6	5.6	5.649	5.6	
S/C Loc	Longitude	deg	-121.00	-121.00	-121.00	-121.00
Beam Polarization	Uplink Beam Name		NRF	NRF	NRF	NRF
	Polarisation (H, V or, C)		C	C	C	C
	Uplink Frequency	MHz	24750.0	24750.0	24750.0	24750.0
	Downlink Beam Name		NTF	NTF	NTF	NTF
Frequency	Polarisation (H, V or, C)		C	C	C	C
	Downlink Frequency	MHz	17300.0	17300.0	17300.0	17300.0
Rain Analysis	Rain Model (ITU/Crane)				ITU	ITU
	% time uplink rain attenuation exceeded				0.03	0.03
	% time downlink rain attenuation exceeded				0.27	0.37
	Total Link Availability				99.70	99.60
Tx E/S	ES Longitude	deg	Denver	Denver	Denver	Denver
	ES Latitude	deg	-105.0	-105.0	-105.0	-105.0
	Temperature ground	deg C	39.5	39.5	39.5	39.5
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		50.0	50.0	50.0	50.0
	Uplink Power Control range	dB	E	E	E	E
	E/S Elevation angle	deg	20.0	20.0	20.0	20.0
	E/S size	m	41.4	41.4	41.4	41.4
	Transmit E/S peak gain (Eff=0.6)	dB	9.00	9.00	9.00	9.00
Rx E/S	ES Longitude	deg	Reno	Miami	Reno	Miami
	ES Latitude	deg	-119.8	-80.2	-119.8	-80.2
	Temperature ground	deg C	39.5	25.5	39.5	25.5
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		30.0	70.0	30.0	70.0
	E/S Elevation angle	deg	D	N	D	N
	E/S size	m	44.3	36.1	44.3	36.1
	Receive E/S peak gain (Eff=0.6)	dB	0.45	1.20	0.45	1.20
	System (LNA + Sky) Noise Temp.	km	36.0	44.5	36.0	44.5
	Temperature due to rain fade and gases	K	200.0	200.0	200.0	200.0
Receive E/S G/T	dB/K	5.2	6.2	93.0	242.3	
Uplink Thermal	U/L eirp	dBW	12.9	21.4	11.3	18.1
	Uplink PSD	dBW/Hz	77.2	77.5	77.6	77.5
	Transponder BP SFD	dBW/m2	-80.9	-80.7	-80.5	-80.7
	Input Backoff	dB	-84.0	-84.0	-83.6	-84.0
	Uplink Path Loss, clear sky	dB	-3.4	-3.2	-3.4	-3.2
	Uplink gaseous attenuation	dB	212.2	212.2	212.2	212.2
	Uplink rain attenuation	dB	0.1	0.1	1.0	1.0
	Uplink power control correction (dB)	dB	0.0	0.0	9.4	9.4
	+ Satellite G/T	dB/K	0.0	0.0	9.4	9.4
	Antenna pattern towards E/S	dB	6.6	6.6	6.6	6.6
C/N thermal uplink	dB	-1.8	-1.8	-1.8	-1.8	
Downlink Thermal	S/C saturated EIRP (Beam Peak)	dBW	25.3	25.6	24.8	24.7
	Carrier Output backoff	dB	55.6	55.6	55.6	55.6
	Antenna pattern towards E/S	dB	-1.5	-1.3	-1.5	-1.3
	Downlink EIRP towards E/S	dBW	-4.2	-5.0	-4.2	-5.0
	Downlink Path Loss, clear sky	dB	49.8	49.3	49.8	49.3
	Downlink gaseous attenuation	dB	208.9	209.0	208.9	209.0
	Downlink rain attenuation	dB	0.1	0.1	0.2	0.5
	- Antenna Pointing error	dB	0.0	0.0	1.5	7.4
	+ Earth Station G/T, clear sky	dB/K	-0.3	-0.3	-0.3	-0.3
	C/N thermal downlink	dB	12.9	21.4	11.3	18.1
Other	C/I (Other link degradation)	dB	9.1	16.8	5.9	5.8
Total	Available C/N	dB	25.0	25.0	25.0	25.0
	PF	dBW/m2/MHz	8.8	15.7	5.8	5.6
	Margin	dB	-121.6	-121.6	-121.6	-121.6
ASI	Geocentric Separation	deg	3.2	10.1	0.1	0.0
	Topocentric Separation w/o pointing error	deg	4.0	4.0	4.0	4.0
	Orbital Separation w/pointing error	deg	4.4	4.4	4.4	4.4
	Interfering Uplink power density	dBW/Hz	4.0	4.2	4.0	4.2
	Interfering D/L eirp density	dBW/Hz	-66.5	-66.5	-66.5	-66.5
	D/Lambda	dBW/Hz	-12.3	-12.2	-12.3	-12.2
	Gain at offset angle	dB	26.0	69.2	26.0	69.2
	C/I ASI uplink	dB	14.0	13.3	14.0	13.3
	C/I ASI downlink	dB	47.8	48.0	48.2	48.0
	C/I (ASI total)	dB	10.9	19.4	10.9	19.4
	ASI uplink	%	10.9	19.3	10.9	19.3
ASI downlink	%	0%	0%	0%	0%	
ASI total	%	23%	4%	23%	4%	
ASI degradation	dB	23%	4%	23%	4%	

Table D4.11 Representative Link Budget/ASI analysis for QPSK 24M0G7W R2/3 (NF SHP XPDR @ 121.0°W)

		CLEAR-SKY		DEGRADED		
Carrier	Carrier Type		24MG7W	24MG7W	24MG7W	24MG7W
		Modulation		QPSK	QPSK	QPSK
	Info Rate	Mbit/s	26.65	26.65	26.65	26.65
	FEC:		0.67	0.67	0.67	0.67
	Noise BW:	MHz	19.988	19.988	19.988	19.988
	Eb/No required:	dB	2.9	2.9	2.9	2.9
	C/N required	dB	4.1	4.1	4.1	4.1
	ASI+Terrestrial losses	dB	1.5	1.5	1.5	1.5
	Adjusted required C/N	dB	5.6	5.6	5.649	5.6
S/C Loc	Longitude	deg	-121.00	-121.00	-121.00	-121.00
Beam Polarization	Uplink Beam Name		NRF	NRF	NRF	NRF
	Polarisation (H, V or, C)		C	C	C	C
Frequency	Uplink Frequency	MHz	25150.0	25150.0	25150.0	25150.0
	Downlink Beam Name		NTF	NTF	NTF	NTF
	Polarisation (H, V or, C)		C	C	C	C
	Downlink Frequency	MHz	17700.0	17700.0	17700.0	17700.0
Rain Analysis	Rain Model (ITU/Crane)				ITU	ITU
	% time uplink rain attenuation exceeded				0.03	0.03
	% time downlink rain attenuation exceeded				0.27	0.37
	Total Link Availability				99.70	99.60
Tx E/S	ES Longitude	deg	Denver	Denver	Denver	Denver
	ES Latitude	deg	-105.0	-105.0	-105.0	-105.0
	Temperature ground	deg C	39.5	39.5	39.5	39.5
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		50.0	50.0	50.0	50.0
	Uplink Power Control range	dB	E	E	E	E
	E/S Elevation angle	deg	20.0	20.0	20.0	20.0
	E/S size	m	41.4	41.4	41.4	41.4
	Transmit E/S peak gain (Eff=0.6)	dB	9.00	9.00	9.00	9.00
			dB	65.3	65.3	65.3
Rx E/S	ES Longitude	deg	Reno	Miami	Reno	Miami
	ES Latitude	deg	-119.8	-80.2	-119.8	-80.2
	Temperature ground	deg C	39.5	25.5	39.5	25.5
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		30.0	70.0	30.0	70.0
	E/S Elevation angle	deg	D	N	D	N
	E/S size	m	44.3	36.1	44.3	36.1
	Receive E/S peak gain (Eff=0.6)	dB	0.45	0.90	0.45	0.90
	System (LNA + Sky) Noise Temp.	km	36.2	42.2	36.2	42.2
	Temperature due to rain fade and gases	K	200.0	200.0	200.0	200.0
Receive E/S G/T	dB/K	5.3	6.3	96.8	245.8	
		dB/K	13.1	19.1	11.5	15.7
Uplink Thermal	U/L eirp	dBW	74.7	77.7	75.2	77.7
	Uplink PSD	dBW/Hz	-63.5	-60.6	-63.1	-60.6
	Transponder BP SFD	dBW/m2	-84.0	-84.0	-83.6	-84.0
	Input Backoff	dB	-5.9	-2.9	-5.9	-2.9
	Uplink Path Loss, clear sky	dB	212.4	212.4	212.4	212.4
	Uplink gaseous attenuation	dB	0.1	0.1	0.9	0.9
	Uplink rain attenuation	dB	0.0	0.0	9.6	9.6
	Up link power control correction (dB)		0.0	0.0	9.6	9.6
	+ Satellite G/T	dB/K	6.6	6.6	6.6	6.6
	Antenna pattern towards E/S	dB	-1.8	-1.8	-1.8	-1.8
C/N thermal uplink	dB	22.7	25.7	22.3	24.9	
Downlink Thermal	S/C saturated EIRP (Beam Peak)	dBW	58.2	58.2	58.2	58.2
	Carrier Output backoff	dB	-4.0	-1.0	-4.0	-1.0
	Antenna pattern towards E/S	dB	-4.2	-5.0	-4.2	-5.0
	Downlink EIRP towards E/S	dBW	50.0	52.1	50.0	52.1
	Downlink Path Loss, clear sky	dB	209.1	209.2	209.1	209.2
	Downlink gaseous attenuation	dB	0.1	0.1	0.2	0.5
	Downlink rain attenuation	dB	0.0	0.0	1.5	7.6
	- Antenna Pointing error	dB	-0.3	-0.3	-0.3	-0.3
	+ Earth Station G/T, clear sky	dB/K	13.1	19.1	11.5	15.7
	C/N thermal downlink	dB	9.2	17.2	5.9	5.8
Other	C/I (Other link degradation)	dB	25.0	25.0	25.0	25.0
Total	Available C/N	dB	8.9	16.0	5.7	5.6
Margin	PFM	dBW/m2/MHz	-121.5	-118.7	-121.5	-118.7
	Margin	dB	3.2	10.4	0.1	0.0
ASI	Geocentric Separation	deg	4.0	4.0	4.0	4.0
	Topocentric Separation	deg	4.4	4.4	4.4	4.4
	Orbital Separation w/pointing error	deg	4.0	4.2	4.0	4.2
	Interfering Uplink power density	dBW/Hz	-56.5	-56.5	-56.5	-56.5
	Interfering D/L eirp density	dBW/Hz	-12.3	-12.2	-12.3	-12.2
	D/Lambda		26.6	53.1	26.6	53.1
	Gain at offset angle	dB	14.0	13.4	14.0	13.4
	C/I ASI uplink	dB	45.3	48.3	45.7	48.3
	C/I ASI downlink	dB	11.2	19.8	11.2	19.8
	C/I (ASI total)	dB	11.2	19.8	11.2	19.8
ASI uplink	%	0%	0%	0%	0%	
ASI downlink	%	22%	4%	22%	4%	
ASI total	%	22%	4%	22%	4%	
ASI degradation	dB	1.1	0.2	1.1	0.2	

Table D4.12 Representative Link Budget/ASI analysis for QPSK 24M0G7W R2/3 (SF SHP XPDR @ 121.0°W)

		CLEAR-SKY		DEGRADED		
		24M0G7W	24M0G7W	24M0G7W	24M0G7W	
Carrier	Carrier Type		24M0G7W	24M0G7W	24M0G7W	
	Modulation		QPSK	QPSK	QPSK	
	Info Rate	Mbit/s	26.65	26.65	26.65	
	FEC:		0.67	0.67	0.67	
	Noise BW:	MHz	19.988	19.988	19.988	
	Eb/No required:	dB	2.9	2.9	2.9	
C/N required	dB	4.1	4.1	4.1		
ASI+Terrestrial losses	dB	1.5	1.5	1.5		
Adjusted required C/N	dB	5.6	5.6	5.649		
S/C Loc	Longitude	deg	-121.00	-121.00	-121.00	
Beam Polarization Frequency	Uplink Beam Name		SRF	SRF	SRF	
	Polarisation (H, V or, C)		C	C	C	
	Uplink Frequency	MHz	25150.0	25150.0	25150.0	
	Downlink Beam Name		STF	STF	STF	
Polarisation (H, V or, C)		C	C	C		
Downlink Frequency	MHz	17700.0	17700.0	17700.0		
Rain Analysis	Rain Model (ITU/Crane)			ITU	ITU	
	% time uplink rain attenuation exceeded			0.03	0.03	
	% time downlink rain attenuation exceeded			0.27	0.97	
	Total Link Availability			99.70	99.00	
Tx E/S	ES Longitude	deg	Santiago	Santiago	Santiago	
	ES Latitude	deg	-70.4	-70.4	-70.4	
	Temperature ground	deg C	-33.3	-33.3	-33.3	
	Humidity	%	25.0	25.0	25.0	
	Rain Zone (as per rain model)		50.0	50.0	50.0	
	Uplink Power Control range	dB	E	E	E	
	E/S Elevation angle	deg	20.0	20.0	20.0	
	E/S size	m	24.1	24.1	24.1	
	Transmit E/S peak gain (Eff=0.6)	dB	9.0	9.0	9.0	
Rx E/S	ES Longitude	deg	65.3	65.3	65.3	
ES Latitude	deg	Santiago	Rio	Santiago	Rio	
Temperature ground	deg C	-70.4	-43.2	-70.4	-43.2	
Humidity	%	-33.3	-22.5	-33.3	-22.5	
Rain Zone (as per rain model)		25.0	25.0	25.0	25.0	
E/S Elevation angle	deg	50.0	75.0	50.0	75.0	
E/S size	m	E	N	E	N	
Receive E/S peak gain (Eff=0.6)	dB	24.1	2.5	24.1	2.5	
System (LNA + Sky) Noise Temp.	km	0.45	1.80	0.45	1.80	
Temperature due to rain fade and gases	K	36.2	48.2	36.2	48.2	
Receive E/S G/T	dB/K	200.0	200.0	200.0	200.0	
		9.0	73.1	159.3	281.1	
		13.0	23.9	10.7	21.4	
Uplink Thermal	U/L eirp	dBW	74.6	74.4	75.0	78.4
	Uplink PSD	dBW/Hz	-83.7	-59.9	-83.3	-59.9
	Transponder BP SFD	dBW/m2	-84.0	-84.0	-83.6	-84.0
	Input Backoff	dB	-5.9	-2.1	-5.9	-2.1
	Uplink Path Loss, clear sky	dB	212.9	212.9	212.9	212.9
	Uplink gaseous attenuation	dB	0.2	0.2	1.5	1.5
	Uplink rain attenuation	dB	0.0	0.0	14.9	14.9
	Uplink power control correction (dB)		0.0	0.0	14.9	14.9
	+ Satellite G/T	dB/K	8.5	8.5	8.5	8.5
	Antenna pattern towards E/S	dB	-1.0	-1.0	-1.0	-1.0
C/N thermal uplink	dB	24.6	28.4	23.7	27.1	
Downlink Thermal	S/C saturated EIRP (Beam Peak)	dBW	58.1	58.1	58.1	58.1
	Carrier Output backoff	dB	-4.0	-0.2	-4.0	-0.2
	Antenna pattern towards E/S	dB	-1.3	-1.3	-1.3	-1.3
	Downlink EIRP towards E/S	dBW	52.9	56.7	52.9	56.7
	Downlink Path Loss, clear sky	dB	209.6	212.5	209.6	212.5
	Downlink gaseous attenuation	dB	0.1	1.3	0.5	7.3
	Downlink rain attenuation	dB	0.0	0.0	2.9	7.6
	- Antenna Pointing error	dB	-0.3	-0.3	-0.3	-0.3
	+ Earth Station G/T, clear sky	dB/K	13.0	23.9	10.7	21.4
C/N thermal downlink	dB	11.4	22.1	5.8	5.7	
Other	C/I (Other link degradation)	dB	25.0	25.0	25.0	
Total	Available C/N	dB	11.1	19.7	5.6	
Margin	PF	dBW/m2/MHz	-122.1	-121.2	-122.1	
	Margin	dB	5.4	14.0	0.0	
ASI	Geocentric Separation	deg	4.0	4.0	4.0	
	Topocentric Separation	deg	4.4	4.4	4.4	
	Orbital Separation wipointing error	deg	4.0	4.3	4.0	
	Interfering Uplink power density	dBW/Hz	-66.5	-66.5	-66.5	
	Interfering D/L eirp density	dBW/Hz	-11.8	-8.9	-11.8	
	D/L lambda		26.6	106.2	26.6	
	Gain at offset angle	dB	14.0	13.2	14.0	
	C/I ASI uplink	dB	45.2	49.0	45.6	
	C/I ASI downlink	dB	13.6	27.3	13.6	
	C/I (ASI total)	dB	13.6	27.3	13.6	
	ASI uplink	%	0%	0%	0%	
ASI downlink	%	14%	1%	14%		
ASI total	%	14%	1%	14%		
ASI degradation	dB	0.6	0.0	0.6		

Table D4.13 Representative Link Budget/ASI analysis for 8PSK 48M0G7W R5/6 & R2/3 (Local DBS XPDR)

		CLEAR-SKY		DEGRADED		
Carrier	Carrier Type		48M0G7W	48M0G7W	48M0G7W	48M0G7W
	Modulation		8PSK	8PSK	8PSK	8PSK
	Bits/Symbol		3	3	3	3
	Info Rate	Mbit/s	100	100	80	80
	FEC:		0.83	0.83	0.67	0.67
	Noise BW:	MHz	40.000	40.000	40.000	40.000
	Eb/No required:	dB	4.9	4.9	6.6	6.6
	C/N required	dB	8.9	8.9	9.6	9.6
	ASI+Terrestrial losses	dB	1.5	1.5	1.5	1.5
	Adjusted required C/N	dB	10.4	10.4	11.1	11.1
Beam Polarization	Uplink Beam Name		GR	GR	GR	GR
	Polarisation (H, V or, C)		C	C	C	C
Frequency	Uplink Frequency	MHz	24750.0	24750.0	24750.0	24750.0
	Downlink Beam Name		UT	UT	UT	UT
	Polarisation (H, V or, C)		C	C	C	C
	Downlink Frequency	MHz	17300.0	17300.0	17300.0	17300.0
Rain Analysis	Rain Model (ITU/Crane)				ITU	ITU
	% time uplink rain attenuation exceeded				0.100	0.100
	% time downlink rain attenuation exceeded				4.900	4.900
	Total Link Availability				95.0	95.0
Tx E/S	ES Longitude	deg	Hagerstwn	Hagerstwn	Hagerstwn	Hagerstwn
	ES Latitude	deg	-77.4	-77.4	-77.4	-77.4
	Temperature ground	deg C	39.3	39.3	39.3	39.3
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		50.0	50.0	50.0	50.0
	Uplink Power Control range	dB	K	K	K	K
	E/S Elevation angle	deg	20.0	20.0	20.0	20.0
	E/S size	m	39.2	39.2	39.2	39.2
	Transmit E/S peak gain (Eff=0.6)	dB	9.0	9.0	9.0	9.0
		dB	65.1	65.1	65.1	65.1
Rx E/S	ES Longitude	deg	Riverside	Miami	Riverside	Miami
	ES Latitude	deg	-117.2	-80.2	-117.2	-80.2
	Temperature ground	deg C	33.6	25.5	33.6	25.5
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		50.0	75.0	50.0	75.0
	E/S Elevation angle	deg	E	N	E	N
	E/S size	m	14.9	49.5	14.9	49.5
	Receive E/S peak gain (Eff=0.6)	dB	0.45	0.45	0.45	0.45
	System (LNA + Sky) Clearsky Temp.	K	36.0	36.0	36.0	36.0
	Temperature due to rain fade and gases	K	200.0	200.0	200.0	200.0
Receive E/S G/T	dB/K	14.0	4.8	86.8	107.3	
	dB/K	12.7	12.9	11.4	11.1	
Uplink Thermal	U/L eirp	dBW	76.9	76.7	76.9	76.7
	Uplink PSD	dBW/Hz	-84.3	-84.5	-84.3	-84.5
	Transponder BP SFD	dBW/m2	-88.0	-88.0	-88.0	-88.0
	Input Backoff	dB	-3.1	-3.3	-3.1	-3.3
	Uplink Path Loss, clear sky	dB	212.3	212.3	212.3	212.3
	Uplink gaseous attenuation	dB	0.1	0.1	1.1	1.1
	Uplink rain attenuation	dB	0.0	0.0	10.6	10.6
	Up link power control correction (dB)		0.0	0.0	10.6	10.6
	+ Satellite G/T	dB/K	16.7	16.7	16.7	16.7
	Antenna pattern towards E/S	dB	-5.0	-5.0	-5.0	-5.0
C/N thermal uplink	dB	26.8	26.5	27.8	27.6	
Downlink Thermal	S/C saturated EIRP (Beam Peak)	dBW	64.7	64.7	64.7	64.7
	Carrier Output backoff	dB	-1.2	-1.4	-1.2	-1.4
	Antenna pattern towards E/S	dB	-4.1	-4.1	-4.1	-4.1
	Downlink EIRP towards E/S	dBW	59.4	59.2	59.4	59.2
	Downlink Path Loss, clear sky	dB	209.8	208.8	209.8	208.8
	Downlink gaseous attenuation	dB	0.2	0.1	0.8	0.4
	Downlink rain attenuation	dB	0.0	0.0	0.8	1.6
	- Antenna Pointing error	dB	-0.3	-0.3	-0.3	-0.3
	+ Earth Station G/T, clear sky	dB/K	12.7	12.9	11.4	11.1
	C/N thermal downlink	dB	14.4	15.5	11.8	11.8
Other	C/I (Other link degradation)	dB	20.0	20.0	20.0	20.0
Total	Available C/N	dB	13.24	14.04	11.11	11.11
	PFDF Margin	dBW/m2/MHz	-116.1	-115.3	-116.1	-115.3
		dB	2.9	3.7	0.0	0.0
ASI	Geocentric Separation	deg	4.0	4.0	4.0	4.0
	Topocentric Separation	deg	4.4	4.4	4.4	4.4
	Orbital Separation w/pointing error	deg	4.0	4.0	4.0	4.0
	Interfering Uplink power density	dBW/Hz	-56.5	-56.5	-56.5	-56.5
	Interfering D/L eirp density	dBW/Hz	-11.4	-12.4	-11.4	-12.4
	D/Lambda		26.0	26.0	26.0	26.0
	Gain at offset angle	dB	14.0	14.0	14.0	14.0
	C/I ASI uplink	dB	44.5	44.2	44.5	44.2
	C/I ASI downlink	dB	16.8	17.6	16.8	17.6
	C/I (ASI total)	dB	16.8	17.6	16.8	17.6
ASI uplink	%	0%	0%	0%	0%	
ASI downlink	%	18%	16%	21%	18%	
ASI total	%	18%	16%	21%	18%	
	ASI degradation	dB	0.9	0.8	1.0	0.9

Table D4.14 Representative Link Budget/ASI analysis for 8PSK 24M0G7W R5/6 & R2/3 (Local DBS XPDR)

		CLEAR-SKY		DEGRADED	
		24M0G7W	24M0G7W	24M0G7W	24M0G7W
Carrier	Carrier Type		8PSK	8PSK	8PSK
	Modulation		3	3	3
	Bits/Symbol		50	50	40
	Info Rate	Mbit/s	0.83	0.83	0.67
	FEC:		20.000	20.000	20.000
	Noise BW:	MHz	4.9	4.9	6.6
	Eb/No required:	dB	8.9	8.9	9.6
	C/N required	dB	1.5	1.5	1.5
ASI+Terrestrial losses	dB	10.4	10.4	11.1	
Adjusted required C/N	dB				
Beam Polarization	Uplink Beam Name		GR	GR	GR
	Polarisation (H, V or, C)		C	C	C
	Uplink Frequency	MHz	24750.0	24750.0	24750.0
	Downlink Beam Name		UT	UT	UT
Frequency	Polarisation (H, V or, C)		C	C	C
	Downlink Frequency	MHz	17300.0	17300.0	17300.0
Rain Analysis	Rain Model (ITU/Crane)			ITU	ITU
	% time uplink rain attenuation exceeded			0.100	0.100
	% time downlink rain attenuation exceeded			4.900	4.900
	Total Link Availability			95.0	95.0
Tx E/S	ES Longitude	deg	Hagerstwn	Hagerstwn	Hagerstwn
	ES Latitude	deg	-77.4	-77.4	-77.4
	Temperature ground	deg C	39.3	39.3	39.3
	Humidity	%	25.0	25.0	25.0
	Rain Zone (as per rain model)		50.0	50.0	50.0
	Uplink Power Control range	dB	K	K	K
	E/S Elevation angle	deg	20.0	20.0	20.0
	E/S size	m	39.2	39.2	39.2
	Transmit E/S peak gain (Eff=0.6)	dB	9.0	9.0	9.0
Rx E/S	ES Longitude	deg	65.1	65.1	65.1
	ES Latitude	deg	Riverside	Miami	Riverside
	Temperature ground	deg C	-117.2	-80.2	-117.2
	Humidity	%	33.6	25.5	33.6
	Rain Zone (as per rain model)		25.0	25.0	25.0
	E/S Elevation angle	deg	50.0	75.0	50.0
	E/S size	m	E	N	E
	Receive E/S peak gain (Eff=0.6)	dB	14.9	49.5	14.9
	System (LNA + Sky) Clearsky Temp.	K	0.45	0.45	0.45
Temperature due to rain fade and gases	K	36.0	36.0	36.0	
Receive E/S G/T	dB/K	200.0	200.0	200.0	
Thermal	U/L eirp	dBW	14.0	4.8	88.8
	Uplink PSD	dBW/Hz	12.7	12.9	11.4
	Transponder BP SFD	dBW/m2			
	Input Backoff	dB			
	Uplink Path Loss, clear sky	dB			
	Uplink gaseous attenuation	dB			
	Uplink rain attenuation	dB			
	Up link power control correction (dB)	dB			
	+ Satellite G/T	dB/K			
	Antenna pattern towards E/S	dB			
C/N thermal uplink	dB				
Downlink Thermal	S/C saturated EIRP (Beam Peak)	dBW	74.1	73.8	74.1
	Carrier Output backoff	dB	-84.1	-84.3	-84.1
	Antenna pattern towards E/S	dB	-88.0	-88.0	-88.0
	Downlink EIRP towards E/S	dBW	-5.9	-6.1	-5.9
	Downlink Path Loss, clear sky	dB	212.3	212.3	212.3
	Downlink gaseous attenuation	dB	0.1	0.1	1.1
	Downlink rain attenuation	dB	0.0	0.0	10.6
	- Antenna Pointing error	dB	0.0	0.0	10.6
	+ Earth Station G/T, clear sky	dB/K	16.7	16.7	16.7
C/N thermal downlink	dB	-5.0	-5.0	-5.0	
ASI	C/I (Other link degradation)	dB	28.9	28.7	28.0
	Total Available C/N	dB	64.7	64.7	64.7
	PFD	dBW/m2/MHz	-4.0	-4.2	-4.0
	Margin	dB	-4.1	-4.1	-4.1
	Geocentric Separation	deg	56.6	56.3	56.6
	Topocentric Separation	deg	209.8	208.8	209.8
	Orbital Separation w/pointing error	deg	0.2	0.1	0.8
	Interfering Uplink power density	dBW/Hz	0.0	0.0	0.8
	Interfering D/L eirp density	dBW/Hz	0.0	0.0	1.6
	D/Lambda	dB	-0.3	-0.3	-0.3
Gain at offset angle	dB	12.7	12.9	11.4	
C/I ASI uplink	dB	14.6	15.7	12.0	
C/I ASI downlink	dB	19.0	19.0	19.0	
C/I (ASI total)	dB	13.13	13.88	11.11	
ASI uplink	%	-115.9	-115.1	-115.9	
ASI downlink	%	2.8	3.5	0.0	
ASI total	%	4.0	4.0	4.0	
ASI degradation	dB	4.0	4.0	4.0	
		4.4	4.4	4.4	
		4.0	4.0	4.0	
		-66.5	-66.5	-66.5	
		-11.4	-12.4	-11.4	
		26.0	26.0	26.0	
		14.0	14.0	14.0	
		44.6	44.4	44.4	
		17.0	17.8	17.0	
		17.0	17.8	17.0	
		0%	0%	0%	
		18%	15%	20%	
		18%	15%	20%	
		0.9	0.7	1.0	
				0.6	