

Table D4.4 Representative Link Budget/ASI analysis for QPSK 24M0G7W R2/3 (NF HP XPDR @ 89.0°W)

			CLEAR-SKY		DEGRADED	
Carrier	Carrier Type		24M0G7W	24M0G7W	24M0G7W	24M0G7W
	Modulation		QPSK	QPSK	QPSK	QPSK
	Info Rate	Mbit/s	26.65	26.65	26.65	26.65
	FEC:		0.67	0.67	0.67	0.67
	Noise BW:	MHz	19.988	19.988	19.988	19.988
	Eb/No required:	dB	2.9	2.9	2.9	2.9
	C/N required	dB	4.1	4.1	4.1	4.1
S/C Loc	ASI+Terrestrial losses	dB	1.5	1.5	1.5	1.5
	Adjusted required C/N	dB	5.6	5.6	5.649	5.6
	Longitude	deg	-89.00	-89.00	-89.00	-89.00
Beam Polarization Frequency	Uplink Beam Name		NRF	NRF	NRF	NRF
	Polarisation (H, V or, C)		C	C	C	C
	Uplink Frequency	MHz	24750.0	24750.0	24750.0	24750.0
	Downlink Beam Name		NTF	NTF	NTF	NTF
Rain Analysis	Polarisation (H, V or, C)		C	C	C	C
	Downlink Frequency	MHz	17300.0	17300.0	17300.0	17300.0
	Rain Model (ITU/Crane)				ITU	ITU
Tx E/S	% time uplink rain attenuation exceeded				0.03	0.03
	% time downlink rain attenuation exceeded				0.27	0.37
	Total Link Availability				99.70	99.60
	ES Longitude	deg	Denver	Denver	Denver	Denver
Rx E/S	ES Latitude	deg	-105.0	-105.0	-105.0	-105.0
	Temperature ground	deg C	39.5	39.5	39.5	39.5
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		50.0	50.0	50.0	50.0
	Uplink Power Control range	dB	E	E	E	E
	E/S Elevation angle	deg	20.0	20.0	20.0	20.0
	E/S size	m	41.4	41.4	41.4	41.4
Uplink Thermal	Transmit E/S peak gain (Eff=0.6)	dB	9.00	9.00	9.00	9.00
	Receive E/S peak gain (Eff=0.6)	dB	65.1	65.1	65.1	65.1
	System (LNA + Sky) Noise Temp.	km	Reno	Miami	Reno	Miami
	Temperature due to rain fade and gases	K	-119.8	-80.2	-119.8	-80.2
	Receive E/S G/T	dB/K	25.0	25.0	25.0	25.0
	U/L eirp	dBW	-81.4	-82.8	-81.0	-82.6
	Uplink PSD	dBW/Hz	-84.0	-84.0	-83.6	-84.0
Downlink Thermal	Transponder BP SFD	dBW/m ²	-84.0	-84.0	-84.0	-84.0
	Input Backoff	dB	-3.2	-4.4	-3.2	-4.4
	Uplink Path Loss, clear sky	dB	212.2	212.2	212.2	212.2
	Uplink gaseous attenuation	dB	0.1	0.1	1.0	1.0
	Uplink rain attenuation	dB	0.0	0.0	0.4	0.4
	Up link power control correction (dB)		0.0	0.0	0.4	0.4
	+ Satellite G/T	dB/K	5.7	5.7	5.7	5.7
Other	Antenna pattern towards E/S	dB	-1.0	-1.0	-1.0	-1.0
	C/N thermal uplink	dB	24.6	23.4	24.2	22.6
	S/C saturated EIRP (Beam Peak)	dBW	54.5	54.5	54.5	54.5
	Carrier Output backoff	dB	-1.3	-2.5	-1.3	-2.5
	Antenna pattern towards E/S	dB	-2.8	-1.5	-2.8	-1.5
	Downlink EIRP towards E/S	dBW	50.4	50.5	50.4	50.5
	Downlink Path Loss, clear sky	dB	209.1	208.8	209.1	208.8
ASI	Downlink gaseous attenuation	dB	0.1	0.1	0.2	0.3
	Downlink rain attenuation	dB	0.0	0.0	1.7	6.7
	- Antenna Pointing error	dB	-0.3	-0.3	-0.3	-0.3
	+ Earth Station G/T, clear sky	dB/K	12.9	12.9	11.1	15.7
	C/N thermal downlink	dB	0.4	10.0	5.8	5.8
	C/I (Other link degradation)	dB	25.0	25.0	25.0	25.0
	Total Available C/N	dB	9.2	9.7	5.7	5.6
ASI	PFD Margin	dBW/m ² /MHz	-122.7	-123.4	-122.7	-123.4
	Geocentric Separation	dB	4.0	4.0	4.0	4.0
	Topocentric Separation w/o pointing error	dB	4.4	4.4	4.4	4.4
	Orbital Separation w/pointing error	dB	4.0	4.0	4.0	4.2
	Interfering Uplink power density	dBW/Hz	-86.5	-86.5	-86.5	-86.5
	Interfering D/L eirp density	dBW/Hz	-12.1	-12.8	-12.1	-12.8
	D/Lambda		26.0	26.0	26.0	51.9
ASI	Gain at offset angle	dB	14.0	14.0	14.0	13.4
	C/I ASI uplink	dB	47.3	46.1	47.7	46.1
	C/I ASI downlink	dB	11.3	11.8	11.3	18.4
	C/I (ASI total)	dB	11.3	11.8	11.3	18.4
ASI	ASI uplink	%	0%	0%	0%	0%
	ASI downlink	%	22%	20%	22%	5%
	ASI total	%	22%	20%	22%	5%
	ASI degradation	dB	1.1	0.9	1.1	0.2

Table D4.5 Representative Link Budget/ASI analysis for QPSK 24M0G7W R2/3 (NF SHP XPDR @ 89.0°W)

			CLEAR-SKY		DEGRADED	
Carrier	Carrier Type		24MG7W	24MG7W	24MG7W	24MG7W
	Modulation		QPSK	QPSK	QPSK	QPSK
	Info Rate	Mbit/s	26.85	26.85	26.85	26.85
	FEC:		0.67	0.67	0.67	0.67
	Noise BW:	MHz	19.988	19.988	19.988	19.988
	Eb/N0 required:	dB	2.9	2.9	2.9	2.9
	C/N required	dB	4.1	4.1	4.1	4.1
	ASI+Terrestrial losses	dB	1.5	1.5	1.5	1.5
S/C Loc	Adjusted required C/N	dB	5.6	5.6	5.649	5.6
	Longitude	deg	-89.00	-89.00	-89.00	-89.00
Beam Polarization Frequency	Uplink Beam Name		NRF	NRF	NRF	NRF
	Polarisation (H, V or, C)		C	C	C	C
	Uplink Frequency	MHz	25150.0	25150.0	25150.0	25150.0
	Downlink Beam Name		NTF	NTF	NTF	NTF
Rain Analysis	Polarisation (H, V or, C)		C	C	C	C
	Downlink Frequency	MHz	17700.0	17700.0	17700.0	17700.0
	Rain Model (ITU/Crane)				ITU	ITU
Tx E/S	% time uplink rain attenuation exceeded				0.03	0.03
	% time downlink rain attenuation exceeded				0.27	0.37
	Total Link Availability				99.70	99.60
Rx E/S	ES Longitude	deg	Denver	Denver	Denver	Denver
	ES Latitude	deg	-105.0	-105.0	-105.0	-105.0
	Temperature ground	deg C	39.5	39.5	39.5	39.5
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		50.0	50.0	50.0	50.0
	Uplink Power Control range	dB	E	E	E	E
	E/S Elevation angle	deg	20.0	20.0	20.0	20.0
	E/S size	m	41.4	41.4	41.4	41.4
	Transmit E/S peak gain (Eff=0.6)	dB	9.00	9.00	9.00	9.00
			65.3	65.3	65.3	65.3
Uplink Thermal	ES Longitude	deg	Reno	Miami	Reno	Miami
	ES Latitude	deg	-119.8	-80.2	-119.8	-80.2
	Temperature ground	deg C	39.5	25.5	39.5	25.5
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		30.0	70.0	30.0	70.0
	E/S Elevation angle	deg	D	N	D	N
	E/S size	m	34.4	58.7	34.4	58.7
	Receive E/S peak gain (Eff=0.6)	dB	0.45	0.65	0.45	0.65
	System (LNA + Sky) Noise Temp.	km	36.2	39.4	36.2	39.4
	Temperature due to rain fade and gases	K	200.0	200.0	200.0	200.0
Downlink Thermal	Receive E/S G/T	dBi/K	6.5	4.3	110.4	236.5
	C/N thermal uplink	dBi/K	13.1	16.3	11.3	13.0
Other	UL eirp	dBW	74.3	76.1	74.7	76.1
	Uplink PSD	dBW/Hz	-84.0	-82.2	-83.6	-82.2
	Transponder BP SFD	dBW/m ²	-84.0	-84.0	-83.6	-84.0
	Input Backoff	dB	-5.6	-3.8	-5.6	-3.8
	Uplink Path Loss, clear sky	dB	212.4	212.4	212.4	212.4
	Uplink gaseous attenuation	dB	0.1	0.1	0.9	0.9
	Uplink rain attenuation	dB	0.0	0.0	9.6	9.6
	Up link power control correction (dB)		0.0	0.0	9.6	9.6
	+ Satellite G/T	dBi/K	5.7	5.7	5.7	5.7
	Antenna pattern towards E/S	dB	-1.0	-1.0	-1.0	-1.0
Total	C/N thermal downlink	dB	22.0	23.8	21.7	23.0
	C/I (Other link degradation)	dB	25.0	25.0	25.0	25.0
ASI	Available C/N	dB	9.2	15.2	5.6	5.6
	PFD Margin	dBW/m ² /MHz	-122.5	-120.3	-122.6	-120.3
ASI	Geocentric Separation	deg	4.0	4.0	4.0	4.0
	Topocentric Separation	deg	4.4	4.4	4.4	4.4
	Orbital Separation w/pointing error	deg	4.0	4.1	4.0	4.1
	Interfering Uplink power density	dBW/Hz	-56.5	-56.5	-56.5	-56.5
	Interfering DL eirp density	dBW/Hz	-12.1	-12.6	-12.1	-12.6
	DLambda		26.6	38.4	26.6	38.4
	Gain at offset angle	dB	14.0	13.6	14.0	13.6
	C/I ASI uplink	dB	44.8	46.6	45.3	46.6
	C/I ASI downlink	dB	11.6	18.7	11.6	18.7
	C/I (ASI total)	dB	11.6	18.7	11.6	18.7
ASI	ASI uplink	%	0%	0%	0%	0%
	ASI downlink	%	20%	5%	20%	5%
	ASI total	%	20%	5%	20%	5%
ASI	ASI degradation	dB	1.0	0.2	1.0	0.2

Table D4.6 Representative Link Budget/ASI analysis for QPSK 24M0G7W R2/3 (SF SHP XPDR @ 89.0°W)

			CLEAR-SKY		DEGRADED
Carrier	Carrier Type		24MG7W	24MG7W	24MG7W
	Modulation		QPSK	QPSK	QPSK
	Info Rate	Mbit/s	26.65	26.65	26.65
	FEC:		0.67	0.67	0.67
	Noise BW:	MHz	19.988	19.988	19.988
	Eb/No required:	dB	2.9	2.9	2.9
	C/N required	dB	4.1	4.1	4.1
S/C Loc	ASI+Terrestrial losses	dB	1.5	1.5	1.5
	Adjusted required C/N	dB	5.6	5.6	5.649
	Longitude	deg	-89.00	-89.00	-89.00
	Latitude	deg			
Beam Polarization	Uplink Beam Name	SRF	SRF	SRF	SRF
	Polarisation (H, V or, C)	C	C	C	C
	Uplink Frequency	MHz	25150.0	25150.0	25150.0
Frequency	Downlink Beam Name	STF	STF	STF	STF
	Polarisation (H, V or, C)	C	C	C	C
	Downlink Frequency	MHz	17700.0	17700.0	17700.0
Rain Analysis	Rain Model (ITU/ Crane)			ITU	ITU
	% time uplink rain attenuation exceeded			0.03	0.03
	% time downlink rain attenuation exceeded			0.27	0.47
Total Link Availability			99.70	99.50	
Tx E/S	ES Longitude	deg	Santiago	Santiago	Santiago
	ES Latitude	deg	-70.4	-70.4	-70.4
	Temperature ground	deg C	-33.3	-33.3	-33.3
	Humidity	%	25.0	25.0	25.0
	Rain Zone (as per rain model)	%	50.0	50.0	50.0
	Uplink Power Control range	dB	20.0	20.0	20.0
	E/S Elevation angle	deg	46.4	46.4	46.4
	E/S size	m	9.0	9.0	9.0
Transmit E/S peak gain (Eff=0.6)			65.3	65.3	65.3
Rx E/S	ES Longitude	deg	Santiago	Rio	Santiago
	ES Latitude	deg	-70.4	-43.2	-70.4
	Temperature ground	deg C	-33.3	-22.5	-33.3
	Humidity	%	25.0	25.0	25.0
	Rain Zone (as per rain model)	%	50.0	75.0	50.0
	E/S Elevation angle	deg	46.4	32.8	46.4
	E/S size	m	0.45	0.90	0.45
	Receive E/S peak gain (Eff=0.6)	dB	36.2	42.2	36.2
Uplink Thermal	System (LNA + Sky) Noise Temp.	km	200.0	200.0	200.0
	Temperature due to rain fade and gases	K	5.1	6.8	117.5
	Receive E/S G/T	dBi/K	13.1	19.1	11.2
	UL eirp	dBW	77.4	78.5	77.4
	Uplink PSD	dBW/Hz	-80.9	-59.8	-80.9
	Transponder BP SFD	dBW/m ²	-86.0	-86.0	-86.0
	Input Backoff	dB	-5.4	-4.3	-5.4
	Uplink Path Loss, clear sky	dB	212.2	212.2	212.2
Downlink Thermal	Uplink gaseous attenuation	dB	0.1	0.1	0.8
	Uplink rain attenuation	dB	0.0	0.0	9.9
	Up link power control correction (dB)	dB	0.0	0.0	9.9
	+ Satellite G/T	dBi/K	6.3	6.3	6.3
	Antenna pattern towards E/S	dB	-6.0	-6.0	-6.0
	C/N thermal uplink	dB	20.9	22.1	20.2
	S/C saturated EIRP (Beam Peak)	dBW	55.2	55.2	55.2
	Carrier Output backoff	dB	-3.5	-2.4	-3.5
Other	Antenna pattern towards E/S	dB	-1.0	-1.0	-1.0
	Downlink EIRP towards E/S	dBW	50.7	51.8	50.7
	Downlink Path Loss, clear sky	dB	209.0	209.3	209.0
	Downlink gaseous attenuation	dB	0.1	0.1	0.6
	Downlink rain attenuation	dB	0.0	0.0	1.9
	- Antenna Pointing error	dB	-0.3	-0.3	-0.3
	+ Earth Station G/T, clear sky	dBi/K	13.1	19.1	11.2
	C/N thermal downlink	dB	9.9	16.7	5.9
Total	C/I (Other link degradation)	dB	25.0	25.0	25.0
	Available C/N	dB	9.5	15.1	5.8
ASI	PFD	dBW/m ² /MHz	-124.0	-123.2	-124.0
	Margin	dB	3.8	9.5	0.0
	Geocentric Separation	deg	4.0	4.0	4.0
	Topocentric Separation	deg	4.4	4.4	4.4
	Orbital Separation w/pointing error	deg	4.0	4.2	4.0
	Interfering Uplink power density	dBW/Hz	-56.5	-56.5	-56.5
	Interfering D/L eirp density	dBW/Hz	-12.4	-12.1	-12.4
	D/Lamda		26.8	53.1	26.8
	Gain at offset angle	dB	14.0	13.4	14.0
	C/I ASI uplink	dB	48.0	49.1	48.0
	C/I ASI downlink	dB	12.0	19.3	12.0
	C/I (ASI total)	dB	12.0	19.3	12.0
ASI degradation	ASI uplink	%	0%	0%	0%
	ASI downlink	%	19%	4%	19%
	ASI total	%	19%	4%	19%
	ASI degradation	dB	0.9	0.2	0.2

Table D4.13 Representative Link Budget/ASI analysis for 8PSK 48M0G7W R5/6 & R2/3 (Local DBS XPDR)

			CLEAR-SKY		DEGRADED	
Carrier	Carrier Type		48M0G7W	48M0G7W	48M0G7W	48M0G7W
	Modulation		8PSK	8PSK	8PSK	8PSK
	Bits/Symbol		3	3	3	3
	Info Rate	Mbit/s	100	100	80	80
	FEC:		0.83	0.83	0.67	0.67
	Noise BW:	MHz	40.000	40.000	40.000	40.000
	Eb/No required:	dB	4.9	4.9	6.6	6.6
	C/I required	dB	8.9	8.9	9.6	9.6
Beam Polarization Frequency	ASI+Terrestrial losses	dB	1.5	1.5	1.5	1.5
	Adjusted required C/N	dB	10.4	10.4	11.1	11.1
	Uplink Beam Name		GR	GR	GR	GR
	Polarisation (H, V or, C)		C	C	C	C
Rain Analysis	Uplink Frequency	MHz	24750.0	24750.0	24750.0	24750.0
	Downlink Beam Name		UT	UT	UT	UT
	Polarisation (H, V or, C)		C	C	C	C
	Downlink Frequency	MHz	17300.0	17300.0	17300.0	17300.0
Rain Analysis	Rain Model (ITU/ Crane)				ITU	ITU
	% time uplink rain attenuation exceeded				0.100	0.100
	% time downlink rain attenuation exceeded				4.900	4.900
	Total Link Availability				95.0	95.0
Tx E/S	ES Longitude	deg	Hagerstwn	Hagerstwn	Hagerstwn	Hagerstwn
	ES Latitude	deg	-77.4	-77.4	-77.4	-77.4
	Temperature ground	deg C	39.3	39.3	39.3	39.3
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		50.0	50.0	50.0	50.0
	Uplink Power Control range	dB	K	K	K	K
	E/S Elevation angle	deg	20.0	20.0	20.0	20.0
	E/S size	m	39.2	39.2	39.2	39.2
	Transmit E/S peak gain (Eff=0.6)	dB	9.0	9.0	9.0	9.0
		dB	65.1	65.1	65.1	65.1
Rx E/S	ES Longitude	deg	Riverside	Miami	Riverside	Miami
	ES Latitude	deg	-117.2	-80.2	-117.2	-80.2
	Temperature ground	deg C	33.6	25.5	33.6	25.5
	Humidity	%	25.0	25.0	25.0	25.0
	Rain Zone (as per rain model)		50.0	75.0	50.0	75.0
	E/S Elevation angle	deg	E	N	E	N
	E/S size	m	14.9	49.5	14.9	49.5
	Receive E/S peak gain (Eff=0.6)	dB	0.45	0.45	0.45	0.45
	System (LNA + Sky) Clearskey Temp.	K	36.0	36.0	36.0	36.0
	Temperature due to rain fade and gases		200.0	200.0	200.0	200.0
Uplink Thermal	Receive E/S G/T	dBi/K	14.0	4.8	88.8	107.3
	Antenna pattern towards E/S	dBi/K	12.7	12.9	11.4	11.1
	C/N thermal uplink	dBi/K	28.8	28.5	27.8	27.6
	UL eirp	dBW	78.9	78.7	78.9	78.7
	Uplink PSD	dBW/Hz	-64.3	-64.5	-64.3	-64.5
	Transponder BP SFD	dBW/m ²	-88.0	-88.0	-88.0	-88.0
	Input Backoff	dB	-3.1	-3.3	-3.1	-3.3
	Uplink Path Loss, clear sky	dB	212.3	212.3	212.3	212.3
	Uplink gaseous attenuation	dB	0.1	0.1	1.1	1.1
	Uplink rain attenuation	dB	0.0	0.0	10.6	10.6
Downlink Thermal	Up link power control correction (dB)		0.0	0.0	10.6	10.6
	+ Satellite G/T	dBi/K	16.7	16.7	16.7	16.7
	Antenna pattern towards E/S	dBi/K	-5.0	-5.0	-5.0	-5.0
	C/N thermal uplink	dBi/K	12.7	12.9	11.4	11.1
	S/C saturated EIRP (Beam Peak)	dBW	84.7	84.7	84.7	84.7
	Carrier Output backoff	dB	-1.2	-1.4	-1.2	-1.4
	Antenna pattern towards E/S	dBi	-4.1	-4.1	-4.1	-4.1
	Downlink EIRP towards E/S	dBW	58.4	59.2	59.4	59.2
	Downlink Path Loss, clear sky	dB	209.8	208.8	209.8	208.8
	Downlink gaseous attenuation	dB	0.2	0.1	0.8	0.4
Other	Downlink rain attenuation	dB	0.0	0.0	0.8	1.6
	- Antenna Pointing error	dB	-0.3	-0.3	-0.3	-0.3
	+ Earth Station G/T, clear sky	dBi/K	12.7	12.9	11.4	11.1
	C/N thermal downlink	dBi/K	14.4	15.5	11.8	11.8
	C/I (Other link degradation)	dB	20.0	20.0	20.0	20.0
	Available C/N	dB	13.24	14.04	11.11	11.11
	PFD Margin	dBW/m ² /MHz	-116.1	-115.3	-116.1	-115.3
		dB	2.9	3.7	0.0	0.0
ASI	Geocentric Separation	deg	4.0	4.0	4.0	4.0
	Topocentric Separation	deg	4.4	4.4	4.4	4.4
	Orbital Separation w/pointing error	deg	4.0	4.0	4.0	4.0
	Interfering Uplink power density	dBW/Hz	-56.5	-56.5	-56.5	-56.5
	Interfering D/L eirp density	dBW/Hz	-11.4	-12.4	-11.4	-12.4
	D/Lambda		26.0	26.0	26.0	26.0
	Gain at offset angle	dB	14.0	14.0	14.0	14.0
	C/I ASI uplink	dBi	44.5	44.2	44.5	44.2
	C/I ASI downlink	dBi	16.8	17.6	16.8	17.6
	C/I (ASI total)	dBi	16.8	17.6	16.8	17.6
ASI	ASI uplink	%	0%	0%	0%	0%
	ASI downlink	%	18%	16%	21%	18%
	ASI total	%	18%	16%	21%	18%
	ASI degradation	dB	0.0	0.8	1.0	0.0

Table D4.14 Representative Link Budget/ASI analysis for 8PSK 24M0G7W R5/6 & R2/3 (Local DBS XPDR)

			CLEAR-SKY		DEGRADED	
Carrier	Carrier Type		24M0G7W	24M0G7W	24M0G7W	24M0G7W
	Modulation		8PSK	8PSK	8PSK	8PSK
	Bits/Symbol		3	3	3	3
	Info Rate	Mbit/s	50	50	40	40
	FEC:		0.83	0.83	0.67	0.67
	Noise BW:	MHz	20.000	20.000	20.000	20.000
	Eb/No required:	dB	4.9	4.9	6.6	6.6
	C/I required	dB	8.9	8.9	9.6	9.6
Beam Polarization Frequency	ASI+Terrestrial losses	dB	1.5	1.5	1.5	1.5
	Adjusted required C/N	dB	10.4	10.4	11.1	11.1
	Uplink Beam Name		GR	GR	GR	GR
Rain Analysis	Polarisation (H, V or, C)		C	C	C	C
	Uplink Frequency	MHz	24750.0	24750.0	24750.0	24750.0
	Downlink Beam Name		UT	UT	UT	UT
	Polarisation (H, V or, C)		C	C	C	C
Rain Analysis	Downlink Frequency	MHz	17300.0	17300.0	17300.0	17300.0
	Rain Model (ITU/Crane)				ITU	ITU
	% time uplink rain attenuation exceeded				0.100	0.100
	% time downlink rain attenuation exceeded				4.900	4.900
Total Link Availability					95.0	95.0
Tx E/S	ES Longitude	deg	Hagerstwn	Hagerstwn	Hagerstwn	Hagerstwn
	ES Latitude	deg	39.3	39.3	39.3	39.3
	Temperature ground	deg C	25.0	25.0	25.0	25.0
	Humidity	%	50.0	50.0	50.0	50.0
	Rain Zone (as per rain model)	K	K	K	K	K
	Uplink Power Control range	dB	20.0	20.0	20.0	20.0
	E/S Elevation angle	deg	39.2	39.2	39.2	39.2
	E/S size	m	9.0	9.0	9.0	9.0
	Transmit E/S peak gain (Eff=0.6)	dB	65.1	65.1	65.1	65.1
Rx E/S	ES Longitude	deg	Riverside	Miami	Riverside	Miami
	ES Latitude	deg	33.6	25.5	33.6	25.5
	Temperature ground	deg C	25.0	25.0	25.0	25.0
	Humidity	%	50.0	75.0	50.0	75.0
	Rain Zone (as per rain model)	E	N	E	N	N
	E/S Elevation angle	deg	14.9	49.5	14.9	49.5
	E/S size	m	0.45	0.45	0.45	0.45
	Receive E/S peak gain (Eff=0.6)	dB	36.0	36.0	36.0	36.0
	System (LNA + Sky) Clearsky Temp.	K	200.0	200.0	200.0	200.0
Thermal	Temperature due to rain fade and gases	K	14.0	4.8	86.8	107.3
	Receive E/S G/T	dB/K	12.7	12.9	11.4	11.1
	U/L eirp	dBW	74.1	73.8	74.1	73.8
	Uplink PSD	dBW/Hz	-64.1	-64.3	-64.1	-64.3
	Transponder BP SFD	dBW/m ²	-88.0	-88.0	-88.0	-88.0
	Input Backoff	dB	-5.9	-6.1	-5.9	-6.1
	Uplink Path Loss, clear sky	dB	212.3	212.3	212.3	212.3
	Uplink gaseous attenuation	dB	0.1	0.1	1.1	1.1
	Uplink rain attenuation	dB	0.0	0.0	10.6	10.6
Downlink Thermal	Up link power control correction (dB)		0.0	0.0	10.6	10.6
	+ Satellite G/T	dB/K	16.7	16.7	16.7	16.7
	Antenna pattern towards E/S	dB	-5.0	-5.0	-5.0	-5.0
	C/I thermal uplink	dB	28.9	28.7	28.0	27.8
	S/C saturated EIRP (Beam Peak)	dBW	64.7	64.7	64.7	64.7
	Carrier Output backoff	dB	4.0	4.2	4.0	4.2
	Antenna pattern towards E/S	dB	-4.1	-4.1	-4.1	-4.1
	Downlink EIRP towards E/S	dBW	56.8	56.3	56.8	56.3
	Downlink Path Loss, clear sky	dB	209.8	208.8	209.8	208.8
Other	Downlink gaseous attenuation	dB	0.2	0.1	0.8	0.4
	Downlink rain attenuation	dB	0.0	0.0	0.8	1.6
	- Antenna Pointing error	dB	-0.3	-0.3	-0.3	-0.3
	+ Earth Station G/T, clear sky	dB/K	12.7	12.9	11.4	11.1
	C/I thermal downlink	dB	14.6	15.7	12.0	12.0
	C/I (Other link degradation)	dB	19.0	19.0	19.0	19.0
	Total Available C/N	dB	13.13	13.88	11.11	11.11
	PFD Margin	dBW/m ² /MHz	-115.9	-115.1	-115.9	-115.1
		dB	2.8	3.5	0.0	0.0
ASI	Geocentric Separation	deg	4.0	4.0	4.0	4.0
	Topocentric Separation	deg	4.4	4.4	4.4	4.4
	Orbital Separation w/pointing error	deg	4.0	4.0	4.0	4.0
	Interfering Uplink power density	dBW/Hz	-56.5	-56.5	-56.5	-56.5
	Interfering D/L eirp density	dBW/Hz	-11.4	-12.4	-11.4	-12.4
	D/Lambda		26.0	26.0	26.0	26.0
	Gain at offset angle	dB	14.0	14.0	14.0	14.0
	C/I ASI uplink	dB	44.8	44.4	44.8	44.4
	C/I ASI downlink	dB	17.0	17.8	17.0	17.8
	C/I (ASI total)	dB	17.0	17.8	17.0	17.8
ASI uplink		%	0%	0%	0%	0%
ASI downlink		%	18%	15%	20%	18%
ASI total		%	18%	15%	20%	18%
ASI degradation		dB	0.9	0.7	1.0	0.8